

<b>Document Title</b>	Requirements on Watchdog Driver
<b>Document Owner</b>	AUTOSAR
<b>Document Responsibility</b>	AUTOSAR
<b>Document Identification No</b>	197

<b>Document Status</b>	published
<b>Part of AUTOSAR Standard</b>	Classic Platform
<b>Part of Standard Release</b>	R24-11

<b>Document Change History</b>			
<b>Date</b>	<b>Release</b>	<b>Changed by</b>	<b>Description</b>
2024-11-27	R24-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> </ul>
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>No content changes</li> <li>Changed Document Status from Final to published</li> </ul>
2018-10-31	4.4.0	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Editorial changes</li> </ul>
2017-12-08	4.3.1	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation</li> </ul>
2016-11-30	4.3.0	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>Added chapter 5: Requirements Tracing</li> </ul>



△

2014-10-31	4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>• Editorial Changes</li> </ul>
2013-10-31	4.1.2	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• ID-Renaming,</li> <li>• usage of standardization template</li> <li>• Link SRS requirements to new feature documents</li> </ul>
2011-12-22	4.0.3	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Requirement for Windowed Watchdog Concept added</li> </ul>
2010-09-30	3.1.5	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Legal disclaimer revised</li> </ul>
2008-08-13	3.1.1	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Legal disclaimer revised</li> </ul>
2007-12-21	3.0.1	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Document meta information extended</li> <li>• Small layout adaptations made</li> </ul>
2007-01-24	2.1.15	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• "Advice for users" revised</li> <li>• "Revision Information" added</li> </ul>
2006-11-28	2.1	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Legal disclaimer revised</li> </ul>
2006-05-16	2.0	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Release as a separate document. The SRS SPAL V1.0.0 has been split into 15 independent documents for Release 2.0</li> </ul>
2005-05-31	1.0	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Initial release as a part of the SRS SPAL V1.0.0</li> </ul>

## Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

## Contents

1	Scope of Document	5
1.1	Constraints	5
2	Conventions to be used	6
2.1	Document Conventions	6
2.2	Requirement structure	7
3	Acronyms and abbreviations	8
4	Requirements Specification	9
4.1	Functional Overview	9
4.2	Internal Watchdog Driver	9
4.3	External Watchdog Driver	9
4.4	Functional Requirements	9
4.4.1	Internal Watchdog Driver	9
4.4.1.1	Configuration	9
4.4.1.2	Initialization	10
4.4.1.3	Normal Operation	11
4.4.1.4	Shutdown Operation	12
4.4.2	External Watchdog Driver	12
4.4.2.1	General	12
4.4.2.2	Configuration	13
4.5	Non-Functional Requirements	13
4.5.1	External Watchdog Driver	13
5	Requirements Tracing	15
6	References	16
A	Change history of AUTOSAR traceable items	17
A.1	Traceable item history of this document according to AUTOSAR Release R24-11	17
A.1.1	Added Requirements in R24-11	17
A.1.2	Changed Requirements in R24-11	17
A.1.3	Deleted Requirements in R24-11	17
A.2	Traceable item history of this document according to AUTOSAR Release R23-11	17
A.2.1	Added Requirements in R23-11	17
A.2.2	Changed Requirements in R23-11	17
A.2.3	Deleted Requirements in R23-11	17
A.3	Traceable item history of this document according to AUTOSAR Release R22-11	18
A.3.1	Added Requirements in R22-11	18
A.3.2	Changed Requirements in R22-11	18
A.3.3	Deleted Requirements in R22-11	18

# 1 Scope of Document

This document specifies requirements on the module Watchdog Driver.

## 1.1 Constraints

First scope for specification of requirements on basic software modules are systems which are not safety relevant. For this reason safety requirements are assigned to medium priority.

## 2 Conventions to be used

### 2.1 Document Conventions

The representation of requirements in AUTOSAR documents follows the table specified in [TPS\_STDT\_00078], see Standardization Template, chapter Support for Traceability ([1]).

The verbal forms for the expression of obligation specified in [TPS\_STDT\_00053] shall be used to indicate requirements, see Standardization Template, chapter Support for Traceability ([1]).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as follows.

Note that the requirement level of the document in which they are used modifies the force of these words.

- **MUST:** This word, or the adjective "LEGALLY REQUIRED", means that the definition is an absolute requirement of the specification due to legal issues.
- **MUST NOT:** This phrase, or the phrase "MUST NOT", means that the definition is an absolute prohibition of the specification due to legal issues.
- **SHALL:** This phrase, or the adjective "REQUIRED", means that the definition is an absolute requirement of the specification.
- **SHALL NOT:** This phrase means that the definition is an absolute prohibition of the specification.
- **SHOULD:** This word, or the adjective "RECOMMENDED", means that there may exist valid reasons in particular circumstances to ignore a particular item, but the full implications must be understood and carefully weighed before choosing a different course.
- **SHOULD NOT:** This phrase, or the phrase "NOT RECOMMENDED", means that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
- **MAY:** This word, or the adjective "OPTIONAL", means that an item is truly optional. One vendor may choose to include the item because a particular market-place requires it or because the vendor feels that it enhances the product while another vendor may omit the same item.

An implementation, which does not include a particular option, SHALL be prepared to interoperate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, SHALL be prepared to interoperate with another implemen-

tation, which does not include the option (except, of course, for the feature the option provides.)

## 2.2 Requirement structure

Each module specific chapter contains a short functional description of the Basic Software Module. Requirements of the same kind within each chapter are grouped under the following headlines (where applicable):

Functional Requirements:

- Configuration (which elements of the module need to be configurable)
- Initialisation
- Normal Operation
- Shutdown Operation
- Fault Operation
- ...

Non-Functional Requirements:

- Timing Requirements
- Resource Usage
- Usability
- Output for other WPs (e.g. Description Templates, Tooling,...)
- ...

### 3 Acronyms and abbreviations

The glossary below includes acronyms and abbreviations relevant to SRS Watchdog-Driver that are not included in the AUTOSAR Glossary [2].

Acronym / Abbreviation	Description:
CS	Chip select
DIO	Digital Input Output
ECU	Electric Control Unit
EOL	End Of Line Often used in the term 'EOL Programming' or 'EOL Configuration'
HIS	Herstellerinitiative Software
ICU	Interrupt Capture Unit
MAL	Old name of Microcontroller Abstraction Layer (replaced by MCAL because 'MAL' is a french term meaning 'bad')
MCAL	Microcontroller Abstraction Layer
MCU	Microcontroller Unit
MMU	Memory Management Unit
Master	A device controlling other devices (slaves, see below)
Slave	A device being completely controlled by a master device
NMI	Non maskable interrupt
OS	Operating System
PLL	Phase Locked Loop
PWM	Pulse Width Modulation
RX	Reception (in the context of bus communication)
SPAL	The name of this working group
SFR	Special Function Register
RTE	Runtime environment
WP	Work Package
STD	Standard
REQ	Requirement
UNINIT	Uninitialized (= not initialized)



## 4 Requirements Specification

This chapter describes all requirements driving the work to define the Watchdog.

### 4.1 Functional Overview

### 4.2 Internal Watchdog Driver

The Internal Watchdog Driver controls the internal watchdog timer of the MCU. It offers the trigger functionality and a mode select service.

### 4.3 External Watchdog Driver

The External Watchdog Driver controls an external hardware watchdog. It offers the trigger functionality and a mode select service. It has the same functional scope like the internal watchdog driver.

### 4.4 Functional Requirements

#### 4.4.1 Internal Watchdog Driver

##### 4.4.1.1 Configuration

**[SRS\_Wdg\_12015] The watchdog driver shall allow the static configuration of watchdog modes**

*Upstream requirements:* [RS\\_BRF\\_01464](#)

[

<b>Description:</b>	The watchdog driver shall allow the static configuration of watchdog modes. A watchdog mode shall minimally consist of the desired watchdog period. Any MCU specific parameter can be added.  Further explanation: Each watchdog mode has the same set of parameters, values will differ.
<b>Rationale:</b>	For mode switching.
<b>Use Case:</b>	Other mode parameters could be: <ul style="list-style-type: none"> <li>• selection of window / timeout mode</li> <li>• timeout reaction (reset or NMI)</li> </ul>
<b>Dependencies:</b>	[SRS_Wdg_12018] Watchdog mode selection service

▽

△

<b>Supporting Material:</b>	BMW Specification MCAL V1.0a, REQ MAL31.1.2
-----------------------------	---

]

#### 4.4.1.2 Initialization

**[SRS\_Wdg\_12105] The watchdog driver shall provide an initialization service that allows the selection of one of the statically configured watchdog modes**

*Upstream requirements:* [RS\\_BRF\\_01136](#)

[

<b>Description:</b>	The watchdog driver shall provide an initialization service that allows the selection of one of the statically configured watchdog modes.
<b>Rationale:</b>	Basic functionality
<b>Use Case:</b>	–
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

]

**[SRS\_Wdg\_12106] The disabling of the watchdog shall not be possible**

*Upstream requirements:* [RS\\_BRF\\_01464](#)

[

<b>Description:</b>	The watchdog initialization service and the watchdog mode selection service must not allow the disabling of the watchdog.  This requirement is only applicable for safety relevant systems. For that reason, this feature shall be statically configurable (by a preprocessor switch)
<b>Rationale:</b>	Avoid the presence of code sequences in a safety relevant ECU that disable the watchdog.
<b>Use Case:</b>	Usage within safety relevant systems.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

]

#### 4.4.1.3 Normal Operation

##### [SRS\_Wdg\_12018] The watchdog driver shall provide a service for selecting the watchdog mode

Upstream requirements: [RS\\_BRF\\_01448](#)

[

<b>Description:</b>	The watchdog driver shall provide a service for selecting the watchdog mode: <ul style="list-style-type: none"> <li>• Fast mode (mandatory)</li> <li>• Slow mode (optional)</li> <li>• Off (optional)</li> </ul>
<b>Rationale:</b>	Allow adaptation of watchdog behavior to ECU state.
<b>Use Case:</b>	Allow switching of different timeout periods for start-up and run mode: <ul style="list-style-type: none"> <li>• ECU Start-up mode: Slow mode (long timeout period)</li> <li>• ECU Run mode: Fast mode (short timeout period)</li> </ul>
<b>Dependencies:</b>	[SRS_Wdg_12015] Configuration of watchdog modes
<b>Supporting Material:</b>	It is not required for each microcontroller to provide all modes. Some watchdogs do not allow mode changes once they have been set up.

]

##### [SRS\_Wdg\_12019] The watchdog driver shall provide a watchdog trigger routine.

Upstream requirements: [RS\\_BRF\\_01464](#)

[

<b>Description:</b>	The watchdog driver shall provide a watchdog trigger routine. This routine shall allow data exchange with the watchdog device (to and from)
<b>Rationale:</b>	Basic functionality
<b>Use Case:</b>	As long as the watchdog trigger condition is valid, this routine shall re-trigger the watchdog to keep it from expiring. The data exchange can be used with complex watchdogs that provide a password mechanism (e.g. for use in safety relevant systems).
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	Windowed Watchdog Concept

]

**[SRS\_Wdg\_13500] The watchdog driver shall provide a service to set the watchdog trigger condition**

Upstream requirements: [RS\\_BRF\\_01464](#)

[

<b>Description:</b>	The watchdog driver shall provide a service to set the watchdog trigger condition.
<b>Rationale:</b>	Basic functionality
<b>Use Case:</b>	This service shall be used by the watchdog interface module to (re-)set the trigger condition for the watchdog driver.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	Windowed Watchdog Concept

]

#### 4.4.1.4 Shutdown Operation

A Deinit function is not provided for the watchdog driver due to safety reasons and because most watchdogs do not allow a deactivation. Thus, [SRS\_SPAL\_12163] Driver module deinitialization is not valid for this module.

### 4.4.2 External Watchdog Driver

#### 4.4.2.1 General

**[SRS\_Wdg\_12165] For an external watchdog driver the same requirements shall apply like for an internal watchdog driver**

Upstream requirements: [RS\\_BRF\\_01936](#)

[

<b>Description:</b>	For an external watchdog driver the same requirements shall apply like for an internal watchdog driver.
<b>Rationale:</b>	Make no functional differences between internal and external watchdog. Keep the functional scope the same.
<b>Use Case:</b>	–
<b>Dependencies:</b>	Requirements on internal watchdog driver
<b>Supporting Material:</b>	–

]

#### 4.4.2.2 Configuration

**[SRS\_Wdg\_12166] A driver for an external SPI watchdog shall allow the static configuration of the required SPI parameters**

*Upstream requirements:* [RS\\_BRF\\_01912](#)

[

<b>Description:</b>	A driver for an external SPI watchdog shall allow the static configuration of the required SPI parameters. Those parameters are specified by the SPI Handler specification.
<b>Rationale:</b>	Basic configuration of SPI access
<b>Use Case:</b>	Use the SPI watchdog driver together with other SPI device drivers on the same SPI bus.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	AUTOSAR SWS SPI Handler

]

## 4.5 Non-Functional Requirements

### 4.5.1 External Watchdog Driver

**[SRS\_Wdg\_12167] The external watchdog driver shall have a semantically identical API as an internal watchdog driver**

*Upstream requirements:* [RS\\_BRF\\_01936](#)

[

<b>Description:</b>	The external watchdog driver shall have a semantically identical API as an internal watchdog driver.
<b>Rationale:</b>	Ease control of watchdogs by the Watchdog Manager. Keep handling of internal and external Watchdogs similar.
<b>Use Case:</b>	Use the same Watchdog manager with an internal or with an external watchdog driver.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

]

**[SRS\_Wdg\_12168] The source code of the external watchdog driver shall be independent from the underlying microcontroller**

*Upstream requirements:* [RS\\_BRF\\_01008](#)

[

<b>Description:</b>	The source code of the external watchdog driver shall be independent from the underlying microcontroller.
<b>Rationale:</b>	Reuse of external watchdog driver across multiple microcontrollers
<b>Use Case:</b>	Example: The same external watchdog driver for an SPI watchdog device can be used on a NEC V850 and on a Renesas M16C without any modification using the standardized SPI Handler interface.
<b>Dependencies:</b>	–
<b>Supporting Material:</b>	–

]

## 5 Requirements Tracing

The following table references the features specified in [3] and links to the fulfillments of these.

Requirement	Description	Satisfied by
[RS_BRF_01008]	AUTOSAR shall organize the hardware dependent layer in a microcontroller independent and a microcontroller dependent layer	[SRS_Wdg_12168]
[RS_BRF_01136]	AUTOSAR shall support variants of configured BSW data resolved after system start-up	[SRS_Wdg_12105]
[RS_BRF_01448]	AUTOSAR services shall support mode and state management	[SRS_Wdg_12018]
[RS_BRF_01464]	AUTOSAR services shall support standardized handling of watchdogs	[SRS_Wdg_12015] [SRS_Wdg_12019] [SRS_Wdg_12106] [SRS_Wdg_13500]
[RS_BRF_01912]	AUTOSAR microcontroller abstraction shall provide access to SPI	[SRS_Wdg_12166]
[RS_BRF_01936]	AUTOSAR microcontroller abstraction shall provide access to MCU internal and external hardware watchdogs	[SRS_Wdg_12165] [SRS_Wdg_12167]

**Table 5.1: Requirements Tracing**

## 6 References

- [1] Standardization Template  
AUTOSAR\_FO\_TPS\_StandardizationTemplate
- [2] Glossary  
AUTOSAR\_FO\_TR\_Glossary
- [3] Requirements on AUTOSAR Features  
AUTOSAR\_CP\_RS\_Features



## **A Change history of AUTOSAR traceable items**

Please note that the lists in this chapter also include traceable items that have been removed from the specification in a later version. These items do not appear as hyperlinks in the document.

### **A.1 Traceable item history of this document according to AUTOSAR Release R24-11**

#### **A.1.1 Added Requirements in R24-11**

none

#### **A.1.2 Changed Requirements in R24-11**

none

#### **A.1.3 Deleted Requirements in R24-11**

none

### **A.2 Traceable item history of this document according to AUTOSAR Release R23-11**

#### **A.2.1 Added Requirements in R23-11**

none

#### **A.2.2 Changed Requirements in R23-11**

none

#### **A.2.3 Deleted Requirements in R23-11**

none

### **A.3 Traceable item history of this document according to AUTOSAR Release R22-11**

#### **A.3.1 Added Requirements in R22-11**

none

#### **A.3.2 Changed Requirements in R22-11**

none

#### **A.3.3 Deleted Requirements in R22-11**

none