

Document Title	Collection of constraints on AUTOSAR M1 models
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	635

Document Status	published
Part of AUTOSAR Standard	Classic Platform
Part of Standard Release	R24-11

Document Change History			
Date	Release	Changed by	Description
2024-11-27	R24-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2023-11-23	R23-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2022-11-24	R22-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2021-11-25	R21-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents
2020-11-30	R20-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in TPS documents Removed all SWS constraints Split document into 3 documents, reflecting the standards CP, AP, FO
2019-11-28	R19-11	AUTOSAR Release Management	<ul style="list-style-type: none"> Updated constraints according to changes in SWS and TPS documents Changed Document Status from Final to published
2018-10-31	4.4.0	AUTOSAR Release Management	<ul style="list-style-type: none"> Completion of constraint context by adding tables and classtables referenced by model constraints to this document



△

2017-12-08	4.3.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation
2016-11-30	4.3.0	AUTOSAR Release Management	<ul style="list-style-type: none"> • minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation
2015-07-31	4.2.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • minor corrections / clarifications / editorial changes; For details please refer to the ChangeDocumentation
2014-10-31	4.2.1	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes
2013-10-31	4.1.2	AUTOSAR Release Management	<ul style="list-style-type: none"> • Updated constraints according to changes in SWS and TPS documents
2013-03-15	4.1.1	AUTOSAR Administration	<ul style="list-style-type: none"> • Initial Release

Disclaimer

This work (specification and/or software implementation) and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the work.

The material contained in this work is protected by copyright and other types of intellectual property rights. The commercial exploitation of the material contained in this work requires a license to such intellectual property rights.

This work may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only. For any other purpose, no part of the work may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The work has been developed for automotive applications only. It has neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Contents

1	Document Information and Content	6
2	Autosar Model Constraints	7
2.1	CP_TPS_BSWModuleDescriptionTemplate	7
2.2	CP_TPS_DiagnosticExtractTemplate	46
2.3	CP_TPS_ECUConfiguration	91
2.4	CP_TPS_ECUResourceTemplate	103
2.5	CP_TPS_SoftwareComponentTemplate	104
2.6	CP_TPS_SystemTemplate	291
2.7	CP_TPS_TimingExtensions	501
2.8	FO_TPS_GenericStructureTemplate	531
2.9	FO_TPS_StandardizationTemplate	543
A	Mentioned Class Tables	551
B	Change history of AUTOSAR traceable items	1071
B.1	Traceable item history of this document according to AUTOSAR Release R24-11	1071
B.1.1	Added Constraints in R24-11	1071
B.1.2	Changed Constraints in R24-11	1074
B.1.3	Deleted Constraints in R24-11	1082

References

- [1] General Specification of Basic Software Modules
AUTOSAR_CP_SWS_BSWGeneral
- [2] Software Component Template
AUTOSAR_CP_TPS_SoftwareComponentTemplate
- [3] ISO 14229-1 – Unified diagnostic services (UDS) – Part 1: Specification and requirements (Release 2006-12)
<https://www.iso.org>
- [4] ISO 26021-2 – Road vehicles – End-of-life activation of on-board pyrotechnic devices – Part 2: Communication requirements
<https://www.iso.org>
- [5] ISO 17356-4: Road vehicles – Open interface for embedded automotive applications – Part 4: OSEK/VDX Communication (COM)
- [6] Collection of blueprints for AUTOSAR M1 models
AUTOSAR_FO_MOD_GeneralBlueprints
- [7] ISO 10646:2012 – Information technology – Universal Coded Character Set (UCS)
<https://www.iso.org>
- [8] Specification of COM Based Transformer
AUTOSAR_CP_SWS_COMBasedTransformer
- [9] SAE J1939-21 Data Link Layer
- [10] Transport Layer Security (TLS) Parameters
<https://www.iana.org/assignments/tls-parameters/tls-parameters.xhtml>
- [11] Generic Structure Template
AUTOSAR_FO_TPS_GenericStructureTemplate
- [12] XML Path language (XPath)
<http://www.w3.org/TR/xpath/>
- [13] ASAM MCD-2 MC (ASAP2 / A2L)
<http://www.asam.net>
ASAM_AE_MCD-2_MC_BS_V1-7-1.pdf

1 Document Information and Content

This auxiliary document provides a collection of constraints for AUTOSAR models. All constraints are copied from template specification from the AUTOSAR Classic Platform, so this document does not introduce any new constraints.

A list of the documents that the constraints originate from can be found in the table of contents. Chapter [2](#) contains the collected constraints, grouped by source documents. All constraints from the same source document are contained within a single section.

2 Autosar Model Constraints

2.1 CP_TPS_BSWModuleDescriptionTemplate

[constr_1275] Applicability of reference `startsOnEvent` for `BswScheduleEvent`

Imposition time: IT_BswMD

[The reference `BswScheduleEvent.startsOnEvent` shall only refer to a `BswSchedulableEntity`.

]

[constr_1276] Applicability of reference `startsOnEvent` for `BswOperationInvokedEvent`

Imposition time: IT_BswMD

[The reference `BswOperationInvokedEvent.startsOnEvent` shall only refer to a `BswCalledEntity`.

]

[constr_4013] BSW service identifier

Imposition time: IT_BswMD

[For Standardized Interfaces, this identifier is defined in the AUTOSAR Software Specification (SWS) of the module. In case the C-function prototype represented by the entry is not standardized, it still can be used optionally, but its value shall differ from the standardized ones.

]

[constr_4014] Call type and execution context

Imposition time: IT_BswMD

[Within a given `BswModuleEntry`, the following constraint holds for its attributes:

- if attribute `callType` is set to value `interrupt`, it is not allowed that attribute `executionContext` is set to either of the values `task` or `hook`
- if attribute `callType` is set to value `scheduled`, it is not allowed that attribute `executionContext` is set to either of the values `interruptCat1` or `interruptCat2`

]

[constr_4015] calledEntry constraints for direct calls

Imposition time: IT_BswMD

[The following holds if `callPoint` is aggregated as an instance of `BswDirectCallPoint`:

- `BswModuleEntity.callPoint.calledEntry.executionContext` shall be identical to `BswModuleEntity.implementedEntry.executionContext`
- `BswModuleEntity.callPoint.calledEntry.callType` shall have the value 'regular' or 'callback'

]

[constr_4016] BswCalledEntity constraints

Imposition time: IT_BswMD

[

- `BswCalledEntity.implementedEntry.callType` shall be 'regular' or 'callback'
- `BswCalledEntity.implementedEntry.executionContext` is in general not restricted, but see [constr_4076] for constraints on the server side of a Client-Server communication.

]

[constr_4017] BswSchedulableEntity constraints

Imposition time: IT_BswMD

[

- `BswModuleEntity.implementedEntry.callType` shall be 'scheduled'
- `BswModuleEntity.implementedEntry.executionContext` shall be 'task'

]

[constr_4018] BswInterruptEntity constraints

Imposition time: IT_BswMD

[

- `BswInterruptEntity.implementedEntry.callType` shall be 'interrupt'
- `BswInterruptEntity.implementedEntry.executionContext` shall be 'interruptCat1' if and only if `BswInterruptEntity.interruptCategory` is 'Cat1'

- `BswInterruptEntity.implementedEntry.executionContext` shall be 'interruptCat2' if and only if `BswInterruptEntity.interruptCategory` is 'Cat2'
- A `BswInterruptEvent` shall only trigger a `BswInterruptEntity` where attribute `interruptCategory` is set to `BswInterruptCategory.cat2`.

]

[constr_4019] BSW module identifier

Imposition time: IT_BswMD

[`BswModuleDescription.moduleId` shall refer to the identifier of the standardized AUTOSAR modules according to [1], if applicable¹. Otherwise (e.g. for ICC2 clusters) the identifier shall either be empty or chosen differently from the ones given in [1].

]

[constr_4020] Allowed categories of `BswModuleDescription`

Imposition time: IT_BswMD

[

<i>category</i>	<i>Explanation</i>
BSW_MODULE	Specifies a single BSW module (ICC3 granularity).
BSW_CLUSTER	Specifies a BSW module cluster (ICC2 granularity).
LIBRARY	Specifies a Library (not restricted to be used within the BSW).

]

[constr_4021] Implementation policy of function pointer target

Imposition time: IT_BswMD

[

A `BswModuleEntry` can only be used as target of a function pointer (`SwPointerTargetProps.functionPointerSignature`), if its `swServiceImplPolicy` is 'standard'.

]

[constr_4022] `BswModuleEntity` only uses the module's interface

Imposition time: IT_BswMD

[

- `BswModuleEntity.implementedEntry` shall refer to an element declared as `implementedEntry` of the enclosing `BswModuleDescription`

¹Note that there may be more than one module in an ECU software with the same identifier, e.g. according to the standard Complex Drivers all have the same identifier.

- `BswModuleEntity.callPoint.calledEntry` - where `callPoint` is instantiated from `BswDirectCallPoint` - shall refer to an element declared as `expectedEntry` or `implementedEntry` of the enclosing `BswModuleDescription`.
- `BswModuleEntity.callPoint.calledEntry` - where `callPoint` is instantiated from `BswSynchronousServerCallPoint` or `BswAsynchronousServerCallPoint` - shall refer to an element declared as `requiredClientServerEntry` of the enclosing `BswModuleDescription`.
- `BswModuleEntity.callPoint` - where `callPoint` is instantiated from `BswAsynchronousServerCallResultPoint` - shall refer to an `BswAsynchronousServerCallPoint` declared in turn as `callPoint` of the same `BswModuleEntity`.
- `BswModuleEntity.issuedTrigger` shall refer to an element declared as `releasedTrigger` of the enclosing `BswModuleDescription`
- `BswModuleEntity.managedModeGroup` shall refer to an element declared as `providedModeGroup` of the enclosing `BswModuleDescription`
- `BswModuleEntity.accessedModeGroup` shall refer to an element declared as `requiredModeGroup` of the enclosing `BswModuleDescription`
- `BswModuleEntity.dataSendPoint.accessedVariable` shall refer to an element declared as `providedData` of the enclosing `BswModuleDescription`
- `BswModuleEntity.dataReceivePoint.accessedVariable` shall refer to an element declared as `requiredData` of the enclosing `BswModuleDescription`
- an `accessedModeGroup` should be allowed to refer to an element declared as `providedModeGroup`

]

[constr_4023] External trigger shall belong to the interface*Imposition time:* IT_BswMD

[A `BswExternalTriggerOccurredEvent` shall refer to a `Trigger` that is declared via `BswModuleDescription.requiredTrigger` for the same module.

]

[constr_4024] Semantics of BSW mode switch event*Imposition time:* IT_BswMD

[If `BswModeSwitchEvent.activation` has the value `onTransition` `BswModeSwitchEvent` shall refer to two different modes belonging to the same instance of

ModeDeclarationGroup, their order defining the direction of the transition. In all other cases, `BswModeSwitchEvent` shall refer to exactly one mode.

]

[constr_4025] Modes used by BSW mode switch event

Imposition time: IT_BswMD

[The `ModeDeclaration` used by `BswModeSwitchEvent` shall belong to the `ModeDeclarationGroupPrototype` referred as `BswInternalBehavior.entity.accessedModeGroup` of the enclosing `BswInternalBehavior`.

]

[constr_4026] Mode group used by BSW mode switch acknowledge event

Imposition time: IT_BswMD

[The `ModeDeclarationGroupPrototype` used by `BswModeSwitchedAckEvent` shall be referred as `BswModuleDescription.providedModeGroup` by the same module.

]

[constr_4028] Semantics of memory section type

Imposition time: IT_BswMD

[`sectionType` shall be semantically compatible to the usage of the enclosing `SwAddrMethod`, this means especially that if `SwAddrMethod` is associated by `ExecutableEntity`-s, the `sectionType` shall be usable as code section, if it is associated by `SwDataDefProps`, `sectionType` shall be usable as data section.

]

[constr_4029] Measured stack usage

Imposition time: IT_BswMD

[The attribute values of `MeasuredStackUsage` shall fulfill:
`minimumMemoryConsumption` <= `averageMemoryConsumption` <= `maximumMemoryConsumption`

]

[constr_4030] Measured heap usage

Imposition time: IT_BswMD

[The attribute values of `MeasuredHeapUsage` shall fulfill:

`minimumMemoryConsumption <= averageMemoryConsumption <= maximumMemoryConsumption`

]

[constr_4031] Analyzed execution time

Imposition time: IT_BswMD

[The attribute values of `AnalyzedExecutionTime` shall fulfill:

`bestCaseExecutionTime <= bestCaseExecutionTime`

]

[constr_4032] Measured execution time

Imposition time: IT_BswMD

[The attribute values of `MeasuredExecutionTime` shall fulfill:

`minimumExecutionTime <= nominalExecutionTime <= maximumExecutionTime`

]

[constr_4033] Simulated execution time

Imposition time: IT_BswMD

[The attribute values of `SimulatedExecutionTime` shall fulfill:

`minimumExecutionTime <= nominalExecutionTime <= maximumExecutionTime`

]

[constr_4034] Target and context of MC emulation reference

Imposition time: IT_BswMD

[Within one `ImplementationElementInParameterInstanceRef`, the `target` shall refer to a sub-element of the `ParameterDataPrototype` which is referred as `context`.

]

[constr_4038] `bswModuleDependency` shall refer to a different module

Imposition time: IT_BswMD

[

- `BswModuleDescription.bswModuleDependency.targetModuleId` (if given) shall differ from `BswModuleDescription.moduleId`. This does not hold if the value is 254 (used for IO Hardware Abstraction modules) or 255 (used for Complex Driver modules).
- `BswModuleDependency.targetModuleRef` (if given) shall differ from the package location of the `BswModuleDescription` that owns the `BswModuleDependency`.

]

[constr_4039] Semantics of `SwcBswMapping`*Imposition time:* IT_BswMD

[An `SwcBswMapping` is only valid, if the referred `SwcInternalBehavior` is aggregated by a `ServiceSwComponentType`, `EcuAbstractionSwComponentType` or `ComplexDeviceDriverSwComponentType`.

]

[constr_4040] Synchronized mode groups shall have same type*Imposition time:* IT_BswMD

[`SwcBswSynchronizedModeGroupPrototype` can only refer to equally typed `ModeDeclarationGroupPrototypes`, i.e. which have identical `ModeDeclarationGroups`.

]

[constr_4041] Synchronized mode groups shall have same context*Imposition time:* IT_BswMD

[The mapping defined by `SwcBswSynchronizedModeGroupPrototype` implies that the component providing the one mode group prototype is also mapped to the module which provides the other mode group prototype by means of synchronizing their respective behaviors in `SwcBswMapping`.

]

[constr_4042] Synchronized triggers shall have same context*Imposition time:* IT_BswMD

[The mapping defined by `SwcBswSynchronizedTrigger` implies that the component providing the one trigger is also mapped to the module which provides the other trigger by means of synchronizing their respective behaviors in `SwcBswMapping`.

]

[constr_4043] Period of BswTimingEvent

Imposition time: IT_BswMD

[BswTimingEvent.period shall be greater than 0.

]

[constr_4044] Content of McSwEmulationMethodSupport

Imposition time: IT_BswMD

[The following constraints hold for the attributes of McSwEmulationMethodSupport:

- If *category* is DOUBLE_POINTERED, a *baseReference* shall exist.
- If *category* is SINGLE_POINTERED, a *referenceTable* shall exist.
- If *category* is INITIALIZED_RAM, one or more *elementGroups* shall exist.

]

[constr_4045] implementationConfigVariant of preconfigured configuration

Imposition time: IT_BswMD

[An EcucModuleConfigurationValues element with the *implementationConfigVariant* set to the value PreconfiguredConfiguration shall only be referenced in the role *preconfiguredConfiguration* and no other value for *implementationConfigVariant* is allowed in this role.

]

[constr_4046] implementationConfigVariant of recommended configuration

Imposition time: IT_BswMD

[An EcucModuleConfigurationValues element with the *implementationConfigVariant* set to the value RecommendedConfiguration shall only be referenced in the role *recommendedConfiguration* and no other value for *implementationConfigVariant* is allowed in this role.

]

[constr_4047] Multiplicity of vendor specific configuration parameters

Imposition time: IT_BswMD

[The association BswImplementation.vendorSpecificModuleDef shall be implemented as reference to one or more instances of EcucModuleDef if the underlying BswModuleDescription has the *category* BSW_CLUSTER. In all other cases, it shall refer to exactly one instance of EcucModuleDef (the one belonging to this module).

]

[constr_4048] Multiplicity of preconfigured values

Imposition time: IT_BswMD

[The association `BswImplementation.preconfiguredConfiguration` shall be implemented as reference to zero or more different instances of `EcucModuleConfigurationValues` if the underlying `BswModuleDescription` has the `category` BSW_CLUSTER. In all other cases, it shall refer to at most one instance of `EcucModuleConfigurationValues` (the one belonging to this module).

]

[constr_4051] RoleBasedDataAssignment in BSW

Imposition time: IT_BswMD

[When used in the context of `BswServiceDependency`, the following restriction hold for data references described by `RoleBasedDataAssignment`:

- Within `RoleBasedDataAssignment.usedDataElement`, only the reference `AutosarVariableRef.localVariable` is applicable.
- Within `RoleBasedDataAssignment.usedParameterElement`, only the reference `AutosarParameterRef.localParameter` is applicable.
- The reference `RoleBasedDataAssignment.usedPim` shall not be set.

]

[constr_4052] BswModuleEntry returnType direction

Imposition time: IT_BswMD

[`BswModuleEntry.returnType.direction` shall not have the value **in** or **inout**.

]

[constr_4053] BswModuleEntry argument direction

Imposition time: IT_BswMD

[If `BswModuleEntry.argument.direction` has the value **out** or **inout**, the corresponding `BswModuleEntry.argument.swDataDefProps` plus eventually referred `ImplementationDataType` shall be such that they result in a pointer declaration.

]

[constr_4054] Unambiguous links to addressing method

Imposition time: IT_BswMD

[`MemorySection.executableEntity` shall not be defined, if `MemorySection.swAddrMethod` represents a data section. `MemorySection.executableEntity`

shall not refer to an `ExecutableEntity` which is linked to a different `SwAddrMethod` than `MemorySection.swAddrMethod`.

]

[constr_4056] `BswModuleEntry` with no `returnType`

Imposition time: IT_BswMD

[

In case of an empty return type ("void" in C) the reference `BswModuleEntry.returnType` shall not be set.

]

[constr_4057] `BswModuleEntry` with no argument

Imposition time: IT_BswMD

[

In case of an empty argument list ("void" in C) no reference `BswModuleEntry.argument` shall be set.

]

[constr_4058] Different mode groups in mapped BSWM and SWC shall have different names

Imposition time: IT_BswMD

[If an `SwcInternalBehavior` is mapped to a `BswInternalBehavior` the corresponding SWC and BSW module descriptions may not refer to different `ModeDeclarationGroups` having the same `shortName` but different elements. This holds especially if these mode groups are not synchronized but used independently.

]

[constr_4059] Different mode groups referred by a BSWM shall have different names

Imposition time: IT_BswMD

[A `BswModuleDescription` may not refer to different `ModeDeclarationGroups` (via `requiredModeGroup` and/or `providedModeGroup`) having the same `shortName` but different elements.

]

[constr_4060] Allowed values of `Trigger.swImplPolicy` for BSW

Imposition time: IT_BswMD

[The **only** allowed values for the attribute `Trigger.swImplPolicy` are either `STANDARD` (in which case the `Trigger` processing does not use a queue) or `QUEUED` (in which case the processing of `Triggers` positively uses a queue).

]

[constr_4061] Completeness of MC emulation reference

Imposition time: IT_BswMD

[If an `McDataInstance` in the role of a `subElement` of another `McDataInstance` specifies an `instanceInMemory`, then the containing `McDataInstance` shall also specify an `instanceInMemory`. The `target` of the latter (i.e. upper level) `instanceInMemory` shall be identical (including array index, if defined) to the `context` of the first (i.e. lower level) `instanceInMemory`.

]

[constr_4062] Mandatory symbol for `McDataInstance` root

Imposition time: IT_BswMD

[`McDataInstances` directly aggregated in `McSupportData` shall have a valid `McDataInstance.symbol`.

]

[constr_4063] Restrictions of `ModeRequestTypeMap` in BSW

Imposition time: IT_BswMD

[For every `ModeDeclarationGroup` referenced by a `ModeDeclarationGroup-Prototype` used in a `BswModuleDescription` a `ModeRequestTypeMap` shall exist that points to the `ModeDeclarationGroup` and also to an eligible `ImplementationDataType`.

The `ModeRequestTypeMap` shall be aggregated by a `DataTypeMappingSet` which is referenced from the `BswInternalBehavior` that is aggregated by the `BswModuleDescription`.

]

[constr_4064] Synchronized triggers shall implement same policy

Imposition time: IT_BswMD

[The mapping defined by `SwcBswSynchronizedTrigger` is only valid if the attribute `SwcBswSynchronizedTrigger.swcTrigger.swImplPolicy` has the same value as the attribute `SwcBswSynchronizedTrigger.bswTrigger.swImplPolicy`.

]

[constr_4065] Allowed values of `BswInternalTriggeringPoint.swImplPolicy`

Imposition time: IT_BswMD

[The **only** allowed values for the attribute `BswInternalTriggeringPoint.swImplPolicy` are either `STANDARD` (in which case the internal trigger processing does not use a queue) or `QUEUED` (in which case the internal trigger processing uses a queue).

]

[constr_4066] `BswModeSwitchEvent` and the definition of `ModeTransition`

Imposition time: IT_BswMD

[For each pair of `ModeDeclarations` referenced by a `BswModeSwitchEvent` with attribute `activation` set to `onTransition` a `ModeTransition` shall be defined in the corresponding direction (i.e. from `exitedMode` to `enteredMode`). This constraint shall only apply if the respective `ModeDeclarationGroup` defines at least one `modeTransition`.

]

[constr_4068] `McFunctionDataRefSet.flatMapEntry`'s semantic

Imposition time: IT_BswMD

[

- An `McFunctionDataRefSet` aggregated in the role of `McFunction.defCalprmSet` or `McFunction.refCalprmSet` shall only refer to `FlatInstanceDescriptors` that
 - either can be traced down to a `ParameterDataPrototype`
 - or can be traced down to a `VariableDataPrototype` of category `COM_AXIS`, `RES_AXIS`, `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5` or `VAL_BLK`

and which are declared for calibration access i.e. have an associated `SwDataDefProps.swCalibrationAccess` set to `readWrite` or `readOnly`.

- An `McFunctionDataRefSet` aggregated in the role of `McFunction.inMeasurementSet`, `McFunction.outMeasurementSet` or `McFunction.locMeasurementSet` shall only refer to `FlatInstanceDescriptors` that can be traced down to either a `VariableDataPrototype`, an `ArgumentDataPrototype` or a `ModeDeclarationGroupPrototype` and are declared as measurable i.e. have an associated `SwDataDefProps.swCalibrationAccess` set to `readOnly`.

]

[constr_4069] McFunctionDataRefSet.mcDataInstance's semantic

Imposition time: IT_BswMD

[

- An `McFunctionDataRefSet` aggregated in the role of `McFunction.defCalprmSet` or `McFunction.refCalprmSet` shall only refer to `McDataInstances` that are declared for calibration access i.e. are aggregated in the role `McSupportData.mcParameterInstance` or `McSupportData.mcVariableInstance` of category `COM_AXIS`, `RES_AXIS`, `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5` or `VAL_BLK`.
- An `McFunctionDataRefSet` aggregated in the role of `McFunction.inMeasurementSet`, `McFunction.outMeasurementSet` or `McFunction.locMeasurementSet` shall only refer to `McDataInstances` that are declared as measurable i.e. are aggregated in the role `McSupportData.mcVariableInstance`.

]

[constr_4070] Applicability of BswModuleEntity.activationReason

Imposition time: IT_BswMD

[An `activationReason` shall not be set

- for instances of `BswInterruptEntity`
- for instances of `BswCalledEntity`

]

[constr_4071] Synchronized runnables and schedulable entities shall be consistent

Imposition time: IT_BswMD

[A `SwcBswRunnableMapping` that maps a `RunnableEntity` to a `BswCalledEntity` or `BswSchedulableEntity` is only valid if several attributes of the mapped `RunnableEntity` and `BswSchedulableEntity` are consistent, especially all of the following constraints apply to the attributes of the given instance of `SwcBswRunnableMapping`:

- `swcRunnable.symbol` shall be identical to the symbol of `bswEntity` as defined in [TPS_BSWMDT_04138].
- `swcRunnable.minimumStartInterval` shall be identical to `bswEntity.minimumStartInterval`.
- `swcRunnable.canBeInvokedConcurrently` shall be identical to `bswEntity.implementedEntry.isReentrant`.

- `swcRunnable.swAddrMethod` shall either be empty or shall have identical attributes as the `SwAddrMethod` defined via `bswEntity.swAddrMethod`. This is required to ensure a unique configuration for the memory segment of the underlying code entity.
- `swcRunnable.activationReason` and `bswEntity.activationReason` shall have identical `shortName` if they define the same `bitPosition` and shall have identical `bitPosition` if they define the same `shortName`

]

[constr_4072] Constraints of `SectionNamePrefix.implementedIn`*Imposition time:* IT_BswMD

[

- The `SectionNamePrefix` and the `DependencyOnArtifact` connected via this link shall belong to the same `BswImplementation`.
- The `DependencyOnArtifact` referred by this link shall be aggregated by `BswImplementation` in the role `requiredArtifact`.
- The `DependencyOnArtifact` referred by this link shall have the `category` value set to MEMMAP.

]

[constr_4073] `McDataAccessDetails` shall refer to one ECU Extract*Imposition time:* IT_BswMD

[Within one given `McDataAccessDetails`, all instances of `System` referenced as the base of any `McDataAccessDetails.variableAccess` or as the base of any `McDataAccessDetails.rteEvent` shall be identical and of `category` ECU_EXTRACT.

]

[constr_4074] Compatibility of `BswModuleClientServerEntry-s`*Imposition time:* IT_BswMD

[Two `BswModuleClientServerEntry-s` are compatible if and only if all of the following conditions hold:

- Their synchronicity values are identical. These values are taken from the attribute `isSynchronous` or, if this is undefined, from `encapsulatedEntry.isSynchronous`.
- The two `BswModuleEntry-s` referred as `encapsulatedEntry` have `SwServiceArg`, `returnType`, `serviceId` and `swServiceImplPolicy` identical.

]

[constr_4075] Constraints for `providedData` and `requiredData`

Imposition time: IT_BswMD

[Sender-Receiver communication in BSW is restricted to the pattern of so-called *explicit communication* (in the same way as described for software components in [2]) with queued behavior. This leads to some constraints for the `VariableDataPrototype` referred in the role `BswModuleDescription.providedData` or `BswModuleDescription.requiredData`:

- It shall not have an `initValue`.
- Its `swDataDefProps.swImplPolicy` shall be set to `queued`.
- Its `swDataDefProps.swCalibrationAccess` shall be set to `notAccessible`.

There are no further formal constraints on the attributes of the `VariableDataPrototype` to be used in these roles or on the underlying `AutosarDataPrototype`.

]

[constr_4076] Constraints on `BswModuleEntry` used for Client-Server

Imposition time: IT_BswMD

[A `BswModuleEntry` used in the role `BswModuleClientServerEntry.encapsulatedEntry` shall have attribute values as follows:

- `callType` shall be `regular` or `callback`.
- `executionContext` shall be `task`.

]

[constr_4077] Constraints for `BswModuleEntity.reentrancyLevel`

Imposition time: IT_BswMD

[

- If the attribute `isReentrant` of a `BswModuleEntry` referred by an `BswModuleEntity` in the role `implementedEntry` has the value `true`, then the attribute `reentrancyLevel` of the same `BswModuleEntity` (if it exists) can only have the values `singleCoreReentrant` or `multicoreReentrant`.
- If the attribute `isReentrant` of a `BswModuleEntry` referred by an `BswModuleEntity` in the role `implementedEntry` has the values `false`, then there are no restrictions for the values of the attribute `reentrancyLevel` of the same `BswModuleEntity` (if it exists).

]

[constr_4078] Consistent usage of `BswOperationInvokedEvent`

Imposition time: IT_BswMD

[The `BswCalledEntity` referred by the attribute `BswOperationInvokedEvent.startsOnEvent` shall refer to the same `BswModuleEntry` (via its attribute `implementedEntry`) as the `BswOperationInvokedEvent` (via its attribute `entry.encapsulatedEntry`.)

]

[constr_4079] `calledEntry` constraints for client-server calls

Imposition time: IT_BswMD

[

- The `BswModuleClientServerEntry` aggregated as `calledEntry` in a `BswSynchronousServerCallPoint` shall have the attribute `isSynchronous = true`.
- The `BswModuleClientServerEntry` aggregated as `calledEntry` in a `BswAsynchronousServerCallPoint` shall have the attribute `isSynchronous = false`.

]

[constr_4080] Existence of reception policy

Imposition time: IT_BswMD

[If a `VariableDataPrototype` is referred from a `dataReceivePoint` of any `BswModuleEntity` in a given `BswInternalBehavior`, then exactly one corresponding `BswDataReceptionPolicy` shall be aggregated by this `BswInternalBehavior`.

]

[constr_4081] Mode group used by BSW mode manager error event

Imposition time: IT_BswMD

[The `ModeDeclarationGroupPrototype` used by `BswModeManagerErrorEvent` shall be referred as `BswModuleDescription.providedModeGroup` by the same module.

]

[constr_4083] `BswDistinguishedPartition` shall be used only in the context of a particular `BswInternalBehavior`

Imposition time: IT_BswMD

[All instances of `BswEvent`, `BswModuleCallPoint` and `BswVariableAccess` which refer to a `BswDistinguishedPartition` shall belong to the same `BswIn-`

ternalBehavior that also aggregates the referred BswDistinguishedPartition.

]

[constr_4084] Consistency of references of InternalBehavior

Imposition time: IT_BswMD

[The SwcInternalBehavior referenced by SwcBswMapping.swcBehavior in the SwcBswMapping determined by SwcImplementation.swcBswMapping shall be identical to the SwcInternalBehavior referenced by SwcImplementation.behavior.

]

[constr_4085] Consistency of references of InternalBehavior

Imposition time: IT_BswMD

[The BswInternalBehavior referenced by SwcBswMapping.bswBehavior in the SwcBswMapping determined by BswImplementation.swcBswMapping shall be identical to the BswInternalBehavior referenced by BswImplementation.behavior.

]

[constr_4087] Usage of category "MACRO"

Imposition time: IT_BswMD

[It is only allowed to use the category "MACRO" for SwServiceArg if the owning BswModuleEntry has its swServiceImplPolicy attribute set to macro.

]

[constr_4088] Existence of RoleBasedDataTypeAssignment.role vs. RoleBasedDataAssignment.role

Imposition time: IT_BswMD

[The usage of a RoleBasedDataTypeAssignment with attribute role set to the value temporaryRamBlock is only allowed if no RoleBasedDataAssignment defined with attribute role set to value defaultValue exists in the owning BswServiceDependency.

]

[constr_4089] Association `callbackHeader` is only applicable for BSW modules

Imposition time: IT_BswMD

[The reference `Code.callbackHeader` is only allowed to be used if the `Code` is aggregated by a `BswImplementation` in the role `codeDescriptor`.

]

[constr_4090] The `callbackHeader` reference has to be consistent with behavior reference

Imposition time: IT_BswMD

[The reference `Code.callbackHeader` is only allowed to reference `ServiceNeeds` in the context of the `BswServiceDependency` that in turn is aggregated by a `BswImplementation` via `BswInternalBehavior` that is owning the `Code` in the role `codeDescriptor`.

]

[constr_4091] `AccessCount.value` needs to be unambiguous

Imposition time: IT_BswMD

[AUTOSAR model shall define at most one `AccessCount.value` per `countProfile` for a specific `AbstractAccessPoint`.

]

[constr_4092] Number of `ErrorTracerNeeds` in `BswInternalBehavior`

Imposition time: IT_BswMD

[A `BswInternalBehavior` shall provide at most one `ErrorTracerNeeds` element.

]

[constr_4093] Entries linked to `BswModuleEntry`s shall have compatible signature

Imposition time: IT_BswMD

[Matching `BswModuleEntry`s according to [TPS_BSWMDT_04130] are compatible if the following conditions are fulfilled:

- both or neither of them define a `returnType`
- when the `returnTypes` are defined, the `SwServiceArgs` in the role `returnType` shall be compatible
- both define the same number of compatible arguments in same order

]

[constr_4094] compatibility of `SwServiceArg` in role `returnType`

Imposition time: IT_BswMD

[`SwServiceArg` in role `returnType` are compatible if they are identically typed
]

[constr_4095] Compatibility of `SwServiceArg` in role `argument`

Imposition time: IT_BswMD

[`SwServiceArg` in role `returnType` are compatible if:

- they are identically typed

and

- if both do have the same `shortName`

]

[constr_4096] Matching `BswModuleEntry`s should have compatible attributes

Imposition time: IT_BswMD

[Matching `BswModuleEntry`s according to [TPS_BSWMDT_04130] should be defined with identical values of the attributes

- `callType`
- `executionContext`
- `isReentrant`
- `isSynchronous`
- `serviceId`
- `swServiceImplPolicy`
- `bswEntryKind`

]

[constr_4097] Limitation on the number of `BswExclusiveAreaPolicys`

Imposition time: IT_BswMD

[An `ExclusiveArea` can only be referenced by at most one `BswExclusiveAreaPolicy`.

]

[constr_4098] No mode disabling for `BswOperationInvokedEvent`

Imposition time: IT_BswMD

[A `BswOperationInvokedEvent` shall not have a reference to a `ModeDeclaration` in the role `disabledInMode`.

]

[constr_4099] Support of multiple instantiation

Imposition time: IT_BswMD

[If a BSW Module supports multiple instantiation the attribute `vendorApiInfix` is mandatory.

]

[constr_4100] Uniqueness of module implementation prefixes

Imposition time: IT_BswMD

[Inside one ECU the Module implementation prefixes (Mip) of BSW Modules shall be unique.

]

[constr_4101] Semantics of `McGroupDataRefSet.flatMapEntry`

Imposition time: IT_BswMD

[

- An `McGroupDataRefSet` aggregated in the role of `McGroup.refCalprmSet` or `McGroup.refCalprmSet` shall only refer to `FlatInstanceDescriptors` that can either be traced down to a `ParameterDataPrototype` or can be traced down to a `VariableDataPrototype` of category `COM_AXIS`, `RES_AXIS`, `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5` or `VAL_BLK` and which are declared for calibration access i.e. have an associated `SwDataDefProps.swCalibrationAccess` set to `readWrite` or `readOnly`.
- An `McGroupDataRefSet` aggregated in the role of `McGroup.refMeasurementSet` shall only refer to `FlatInstanceDescriptors` that can be traced down to either a `VariableDataPrototype`, an `ArgumentDataPrototype` or a `ModeDeclarationGroupPrototype` and are declared as measurable i.e. have an associated `SwDataDefProps.swCalibrationAccess` set to `readOnly`.

]

[constr_4102] Semantics of `McGroupDataRefSet.mcDataInstance`

Imposition time: IT_BswMD

[

- An `McGroupDataRefSet` aggregated in the role of `McGroup.refCalprmSet` shall only refer to `McDataInstances` that are declared for calibration access i.e. are aggregated in the role `McSupportData.mcParameterInstance` or `McSupportData.mcParameterInstance` of category `VALUE`, `COM_AXIS`, `RES_AXIS`, `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5` or `VAL_BLK`.
- An `McGroupDataRefSet` aggregated in the role of `McGroup.refMeasurementSet` shall only refer to `McDataInstances` that are declared as measurable i.e. are aggregated in the role `McSupportData.mcVariableInstance`.

]

[constr_4103] Name convention for `SectionNamePrefix.symbol`*Imposition time:* IT_BswMD

[In case a BSW module is split into allocatable memory parts the existing (according to [SWS_MemMap_00041]) `SectionNamePrefix.symbol` shall be set in the `<MIP>_<FEATURE>` form, where:

- `<MIP>` : is the capitalized module implementation prefix
- `<FEATURE>` : is the name of the sub-feature in the BSW module denoting the allocatable memory part

]

[constr_4104] Referencing of `MemorySections` to `SectionNamePrefix`*Imposition time:* IT_BswMD

[In case a BSW module or Software Component is split into allocatable memory parts all `MemorySections` belonging to the same allocatable memory part shall reference the identical `SectionNamePrefix` representing the allocatable memory part.

]

[constr_4105] Use of attribute `task` or `cat2Isr`*Imposition time:* IT_BswMD

[Only one of the attributes is allowed to exist. Either `task` or `cat2Isr` should be configured.

]

[constr_4106] Restriction for the value of `SwServiceArg.swImplPolicy`*Imposition time:* IT_BswMD

[The attribute `SwServiceArg.swImplPolicy` shall only have one of the following values:

- `SwImplPolicyEnum.const`

- `SwImplPolicyEnum.standard`

]

[constr_4107] `swImplPolicy` for `SwServiceArg`*Imposition time:* IT_BswMD

[The overriding value of attribute `swImplPolicy` of a `SwServiceArg` shall be `standard` or `const`.

]

[constr_4108] Restriction regarding the value of `SwServiceArg.category`*Imposition time:* IT_BswMD

[The attribute `SwServiceArg.category` shall only have the following values:

- VALUE²
- DATA_REFERENCE
- FUNCTION_REFERENCE
- TYPE_REFERENCE
- MACRO

]

[constr_9316] Multi instantiated BSW Modules not mappable*Imposition time:* IT_BswMD

[In case a BSW Module is multi instantiated in an ECU its `BswImplementations` shall not reference a `SwcBswMapping` in the role `swcBswMapping`.

]

[constr_10257] Existence of attribute `BswServiceDependency.serviceNeeds`*Imposition time:* IT_BswMD

[For each `BswServiceDependency`, the attribute `serviceNeeds` shall exist.

]

²This option has **very few** valid use cases, e.g. for defining a function pointer in native C notation, for example: `int (*SwCluC_BManif_VoidFncPtrType)(void);`

[constr_10258] Existence of the reference in the role `RoleBasedBswModuleEntryAssignment.assignedEntry`*Imposition time:* IT_BswMD[For each `RoleBasedBswModuleEntryAssignment`, the reference in the role `assignedEntry` shall exist.

]

[constr_10259] Existence of attribute `RoleBasedBswModuleEntryAssignment.role`*Imposition time:* IT_BswMD[For each `RoleBasedBswModuleEntryAssignment`, the attribute `role` shall exist.

]

[constr_10260] Existence of attribute `BswModuleEntry.callType`*Imposition time:* IT_BswMD[For each `BswModuleEntry`, the attribute `callType` shall exist.

]

[constr_10261] Existence of attribute `BswModuleEntry.executionContext`*Imposition time:* IT_BswMD[For each `BswModuleEntry`, the attribute `executionContext` shall exist.

]

[constr_10262] Existence of attribute `BswModuleEntry.isReentrant`*Imposition time:* IT_BswMD[For each `BswModuleEntry`, the attribute `isReentrant` shall exist.

]

[constr_10263] Existence of attribute `BswModuleEntry.isSynchronous`*Imposition time:* IT_BswMD[For each `BswModuleEntry`, the attribute `isSynchronous` shall exist.

]

[constr_10264] Existence of attribute `BswModuleEntry.swServiceImplPolicy`*Imposition time:* IT_BswMD[For each `BswModuleEntry`, the attribute `swServiceImplPolicy` shall exist.

]

[constr_10265] Existence of attribute `BswEntryRelationshipSet.bswEntryRelationship`*Imposition time:* IT_BswMD[For each `BswEntryRelationshipSet`, the attribute `bswEntryRelationship` shall exist at least once.

]

[constr_10266] Existence of attribute `BswEntryRelationship.bswEntryRelationshipType`*Imposition time:* IT_BswMD[For each `BswEntryRelationship`, the attribute `bswEntryRelationshipType` shall exist.

]

[constr_10267] Existence of reference in the role `BswEntryRelationship.from`*Imposition time:* IT_BswMD[For each `BswEntryRelationship`, the reference in the role `from` shall exist.

]

[constr_10268] Existence of reference in the role `BswEntryRelationship.to`*Imposition time:* IT_BswMD[For each `BswEntryRelationship`, the reference in the role `to` shall exist.

]

[constr_10269] Existence of the reference in the role `BswModuleClientServerEntry.encapsulatedEntry`*Imposition time:* IT_BswMD[For each `BswModuleClientServerEntry`, the the reference in the role `encapsulatedEntry` shall exist.

]

[constr_10270] Existence of attribute `AccessCountSet.countProfile`*Imposition time:* IT_BswMD[For each `AccessCountSet`, the attribute `countProfile` shall exist.

]

[constr_10271] Existence of attribute `AccessCount.value`*Imposition time:* IT_BswMD[For each `AccessCount`, the attribute `value` shall exist.

]

[constr_10272] Existence of the reference in the role `BswModuleEntity.implementedEntry`*Imposition time:* IT_BswMD[For each `BswModuleEntity`, the reference in the role `implementedEntry` shall exist.

]

[constr_10273] Existence of attribute `BswInterruptEntity.interruptCategory`*Imposition time:* IT_BswMD[For each `BswInterruptEntity`, the attribute `interruptCategory` shall exist.

]

[constr_10274] Existence of attribute `BswInterruptEntity.interruptSource`*Imposition time:* IT_BswMD[For each `BswInterruptEntity`, the attribute `interruptSource` shall exist.

]

[constr_10275] Existence of the reference in the role `BswDirectCallPoint.calledEntry`*Imposition time:* IT_BswMD[For each `BswDirectCallPoint`, the reference in the role `calledEntry` shall exist.

]

[constr_10276] Existence of the reference in the role `BswSynchronousServerCallPoint.calledEntry`

Imposition time: IT_BswMD

[For each `BswSynchronousServerCallPoint`, the reference in the role `calledEntry` shall exist.

]

[constr_10277] Existence of the reference in the role `BswAsynchronousServerCallPoint.calledEntry`

Imposition time: IT_BswMD

[For each `BswAsynchronousServerCallPoint`, the reference in the role `calledEntry` shall exist.

]

[constr_10278] Existence of the reference in the role `BswAsynchronousServerCallResultPoint.asynchronousServerCallPoint`

Imposition time: IT_BswMD

[For each `BswAsynchronousServerCallResultPoint`, the reference in the role `asynchronousServerCallPoint` shall exist.

]

[constr_10279] Existence of the reference in the role `BswVariableAccess.accessedVariable`

Imposition time: IT_BswMD

[For each `BswVariableAccess`, the reference in the role `accessedVariable` shall exist.

]

[constr_10280] Existence of the reference in the role `BswExclusiveAreaPolicy.exclusiveArea`

Imposition time: IT_BswMD

[For each `BswExclusiveAreaPolicy`, the reference in the role `exclusiveArea` shall exist.

]

[constr_10281] Existence of attribute `BswTimingEvent.period`*Imposition time:* IT_BswMD[For each `BswTimingEvent`, the attribute `period` shall exist.

]

[constr_10282] Existence of the reference in the role `BswInternalTriggerOccurredEvent.eventSource`*Imposition time:* IT_BswMD[For each `BswInternalTriggerOccurredEvent`, the reference in the role `eventSource` shall exist.

]

[constr_10283] Existence of the reference in the role `BswExternalTriggerOccurredEvent.trigger`*Imposition time:* IT_BswMD[For each `BswExternalTriggerOccurredEvent`, the reference in the role `trigger` shall exist.

]

[constr_10284] Existence of attribute `BswModeSwitchEvent.activation`*Imposition time:* IT_BswMD[For each `BswModeSwitchEvent`, the attribute `activation` shall exist.

]

[constr_10285] Existence of the reference in the role `BswModeSwitchedAckEvent.modeGroup`*Imposition time:* IT_BswMD[For each `BswModeSwitchedAckEvent`, the reference in the role `modeGroup` shall exist.

]

[constr_10286] Existence of the reference in the role `BswModeManagerErrorEvent.modeGroup`*Imposition time:* IT_BswMD[For each `BswModeManagerErrorEvent`, the reference in the role `modeGroup` shall exist.

]

[constr_10287] Existence of the reference in the role `BswOperationInvokedEvent.entry`*Imposition time:* IT_BswMD

[For each `BswOperationInvokedEvent`, the reference in the role `entry` shall exist.]

[constr_10288] Existence of the reference in the role `BswAsynchronousServerCallReturnsEvent.eventSource`*Imposition time:* IT_BswMD

[For each `BswAsynchronousServerCallReturnsEvent`, the reference in the role `eventSource` shall exist.]

[constr_10289] Existence of the reference in the role `BswDataReceivedEvent.data`*Imposition time:* IT_BswMD

[For each `BswDataReceivedEvent`, the reference in the role `data` shall exist.]

[constr_10290] Existence of the reference in the role `BswTriggerDirectImplementation.masteredTrigger`*Imposition time:* IT_BswMD

[For each `BswTriggerDirectImplementation`, the reference in the role `masteredTrigger` shall exist.]

[constr_10291] Existence of the reference in the role `BswModeSenderPolicy.providedModeGroup`*Imposition time:* IT_BswMD

[For each `BswModeSenderPolicy`, the reference in the role `providedModeGroup` shall exist.]

[constr_10292] Existence of attribute `BswModeSenderPolicy.queueLength`*Imposition time:* IT_BswMD

[For each `BswModeSenderPolicy`, the attribute `queueLength` shall exist.]

[constr_10293] Existence of attribute `BswModeSwitchAckRequest.timeout`*Imposition time:* IT_BswMD[For each `BswModeSwitchAckRequest`, the attribute `timeout` shall exist.

]

[constr_10294] Existence of the reference in the role `BswModeReceiverPolicy.requiredModeGroup`*Imposition time:* IT_BswMD[For each `BswModeReceiverPolicy`, the reference in the role `requiredModeGroup` shall exist.

]

[constr_10295] Existence of attribute `BswModeReceiverPolicy.supportsAsynchronousModeSwitch`*Imposition time:* IT_BswMD[For each `BswModeReceiverPolicy`, the attribute `supportsAsynchronousModeSwitch` shall exist.

]

[constr_10296] Existence of reference in the role `BswDataReceptionPolicy.receivedData`*Imposition time:* IT_BswMD[For each `BswDataReceptionPolicy`, the reference in the role `receivedData` shall exist.

]

[constr_10297] Existence of attribute `BswQueuedDataReceptionPolicy.queueLength`*Imposition time:* IT_BswMD[For each `BswQueuedDataReceptionPolicy`, the attribute `queueLength` shall exist.

]

[constr_10298] Existence of the reference in the role `SwcBswRunnableMapping.bswEntity`*Imposition time:* IT_BswMD[For each `SwcBswRunnableMapping`, the reference in the role `bswEntity` shall exist.

]

[constr_10299] Existence of the reference in the role `SwcBswRunnableMapping.swcRunnable`*Imposition time:* IT_BswMD[For each `SwcBswRunnableMapping`, the reference in the role `swcRunnable` shall exist.

]

[constr_10300] Existence of the reference in the role `SwcBswSynchronizedTrigger.bswTrigger`*Imposition time:* IT_BswMD[For each `SwcBswSynchronizedTrigger`, the reference in the role `bswTrigger` shall exist.

]

[constr_10301] Existence of the instanceRef in the role `SwcBswSynchronizedTrigger.swcTrigger`*Imposition time:* IT_BswMD[For each `SwcBswSynchronizedTrigger`, the instanceRef in the role `swcTrigger` shall exist.

]

[constr_10302] Existence of attribute `BswImplementation.arReleaseVersion`*Imposition time:* IT_BswMD[For each `BswImplementation`, the attribute `arReleaseVersion` shall exist.

]

[constr_10303] Existence of the reference in the role `BswImplementation.behavior`*Imposition time:* IT_BswMD[For each `BswImplementation`, the reference in the role `behavior` shall exist.

]

[constr_10304] Existence of attribute `DependencyOnArtifact.usage`*Imposition time:* IT_BswMD[For each `DependencyOnArtifact`, the attribute `usage` shall exist at least once.

]

[constr_10305] Existence of attribute `WorstCaseStackUsage.memoryConsumption`*Imposition time:* IT_BswMD[For each `WorstCaseStackUsage`, the attribute `memoryConsumption` shall exist.

]

[constr_10306] Existence of attribute `MeasuredStackUsage.averageMemoryConsumption`*Imposition time:* IT_BswMD[For each `MeasuredStackUsage`, the attribute `averageMemoryConsumption` shall exist.

]

[constr_10307] Existence of attribute `MeasuredStackUsage.maximumMemoryConsumption`*Imposition time:* IT_BswMD[For each `MeasuredStackUsage`, the attribute `maximumMemoryConsumption` shall exist.

]

[constr_10308] Existence of attribute `RoughEstimateStackUsage.memoryConsumption`*Imposition time:* IT_BswMD[For each `RoughEstimateStackUsage`, the attribute `memoryConsumption` shall exist.

]

[constr_10309] Existence of attribute `WorstCaseHeapUsage.memoryConsumption`*Imposition time:* IT_BswMD[For each `WorstCaseHeapUsage`, the attribute `memoryConsumption` shall exist.

]

[constr_10310] Existence of attribute `MeasuredHeapUsage.averageMemoryConsumption`*Imposition time:* IT_BswMD

[For each `MeasuredHeapUsage`, the attribute `averageMemoryConsumption` shall exist.

]

[constr_10311] Existence of attribute `MeasuredHeapUsage.maximumMemoryConsumption`*Imposition time:* IT_BswMD

[For each `MeasuredHeapUsage`, the attribute `maximumMemoryConsumption` shall exist.

]

[constr_10312] Existence of attribute `RoughEstimateHeapUsage.memoryConsumption`*Imposition time:* IT_BswMD

[For each `RoughEstimateHeapUsage`, the attribute `memoryConsumption` shall exist.

]

[constr_10313] Existence of attribute `ExecutionTime.hardwareConfiguration`*Imposition time:* IT_BswMD

[For each `ExecutionTime`, the attribute `hardwareConfiguration` shall exist.

]

[constr_10314] Existence of attribute `ExecutionTime.softwareContext`*Imposition time:* IT_BswMD

[For each `ExecutionTime`, the attribute `softwareContext` shall exist.

]

[constr_10315] Existence of attribute `HardwareConfiguration.additionalInformation`*Imposition time:* IT_BswMD

[For each `HardwareConfiguration`, the attribute `additionalInformation` shall exist.

]

[constr_10316] Existence of attribute `HardwareConfiguration.processorMode`*Imposition time:* IT_BswMD

[For each `HardwareConfiguration`, the attribute `processorMode` shall exist.
]

[constr_10317] Existence of attribute `HardwareConfiguration.processorSpeed`*Imposition time:* IT_BswMD

[For each `HardwareConfiguration`, the attribute `processorSpeed` shall exist.
]

[constr_10318] Existence of reference `MemorySectionLocation.providedMemory`*Imposition time:* IT_BswMD

[For each `MemorySectionLocation`, the reference in the role `providedMemory` shall exist.
]

[constr_10319] Existence of reference `MemorySectionLocation.softwareMemorySection`*Imposition time:* IT_BswMD

[For each `MemorySectionLocation`, the reference in the role `softwareMemorySection` shall exist.
]

[constr_10320] Existence of attribute `SoftwareContext.input`*Imposition time:* IT_BswMD

[For each `SoftwareContext`, the attribute `input` shall exist.
]

[constr_10321] Existence of attribute `SoftwareContext.state`*Imposition time:* IT_BswMD

[For each `SoftwareContext`, the attribute `state` shall exist.
]

[constr_10323] Existence of attribute `AnalyzedExecutionTime.bestCaseExecutionTime`

Imposition time: IT_BswMD

[For each `AnalyzedExecutionTime`, the attribute `bestCaseExecutionTime` shall exist.

]

[constr_10324] Existence of attribute `AnalyzedExecutionTime.worstCaseExecutionTime`

Imposition time: IT_BswMD

[For each `AnalyzedExecutionTime`, the attribute `worstCaseExecutionTime` shall exist.

]

[constr_10325] Existence of attribute `MeasuredExecutionTime.maximumExecutionTime`

Imposition time: IT_BswMD

[For each `MeasuredExecutionTime`, the attribute `maximumExecutionTime` shall exist.

]

[constr_10326] Existence of attribute `MeasuredExecutionTime.minimumExecutionTime`

Imposition time: IT_BswMD

[For each `MeasuredExecutionTime`, the attribute `minimumExecutionTime` shall exist.

]

[constr_10327] Existence of attribute `MeasuredExecutionTime.nominalExecutionTime`

Imposition time: IT_BswMD

[For each `MeasuredExecutionTime`, the attribute `nominalExecutionTime` shall exist.

]

[constr_10328] Existence of the reference in the role `BswEvent.startsOnEvent`

Imposition time: IT_BswMD

[For each `BswEvent`, the reference in the role `startsOnEvent` shall exist.

]

[constr_10329] Existence of the instanceRef in the role `McDataAccessDetails.variableAccess`

Imposition time: IT_BswMD

[For each `McDataAccessDetails`, the instanceRef in the role `variableAccess` shall exist at least once.

]

[constr_10330] Existence of attribute `RptServicePoint.symbol`

Imposition time: IT_BswMD

[For each `RptServicePoint`, the attribute `symbol` shall exist.

]

[constr_10331] Existence of attribute `SimulatedExecutionTime.maximumExecutionTime`

Imposition time: IT_BswMD

[For each `SimulatedExecutionTime`, the attribute `maximumExecutionTime` shall exist.

]

[constr_10332] Existence of attribute `SimulatedExecutionTime.minimumExecutionTime`

Imposition time: IT_BswMD

[For each `SimulatedExecutionTime`, the attribute `minimumExecutionTime` shall exist.

]

[constr_10333] Existence of attribute `SimulatedExecutionTime.nominalExecutionTime`

Imposition time: IT_BswMD

[For each `SimulatedExecutionTime`, the attribute `nominalExecutionTime` shall exist.

]

[constr_10334] Existence of attribute `RoughEstimateOfExecutionTime.additionalInformation`*Imposition time:* IT_BswMD

[For each `RoughEstimateOfExecutionTime`, the attribute `additionalInformation` shall exist.

]

[constr_10335] Existence of attribute `RoughEstimateOfExecutionTime.estimatedExecutionTime`*Imposition time:* IT_BswMD

[For each `RoughEstimateOfExecutionTime`, the attribute `estimatedExecutionTime` shall exist.

]

[constr_10336] Existence of the reference in the role `SwcBswSynchronizedModeGroupPrototype.bswModeGroup`*Imposition time:* IT_BswMD

[For each `SwcBswSynchronizedModeGroupPrototype`, the reference in the role `bswModeGroup` shall exist.

]

[constr_10337] Existence of the instanceRef in the role `SwcBswSynchronizedModeGroupPrototype.swcModeGroup`*Imposition time:* IT_BswMD

[For each `SwcBswSynchronizedModeGroupPrototype`, the instanceRef in the role `swcModeGroup` shall exist.

]

[constr_10338] Existence of attribute `MultidimensionalTime.cseCode`*Imposition time:* IT_BswMD

[For each `MultidimensionalTime`, the attribute `cseCode` shall exist.

]

[constr_10339] Existence of attribute `MultidimensionalTime.cseCodeFactor`*Imposition time:* IT_BswMD

[For each `MultidimensionalTime`, the attribute `cseCodeFactor` shall exist.

]

[constr_10340] Existence of attribute `McSwEmulationMethodSupport.category`*Imposition time:* IT_BswMD

[For each `McSwEmulationMethodSupport`, the attribute `category` shall exist.
]

[constr_10341] Existence of attribute `McSwEmulationMethodSupport.shortLabel`*Imposition time:* IT_BswMD

[For each `McSwEmulationMethodSupport`, the attribute `shortLabel` shall exist.
]

[constr_10342] Existence of the reference in the role `McParameterElementGroup.ramLocation`*Imposition time:* IT_BswMD

[For each `McParameterElementGroup`, the reference in the role `ramLocation` shall exist.
]

[constr_10343] Existence of the reference in the role `McParameterElementGroup.romLocation`*Imposition time:* IT_BswMD

[For each `McParameterElementGroup`, the reference in the role `romLocation` shall exist.
]

[constr_10344] Existence of attribute `McParameterElementGroup.shortLabel`*Imposition time:* IT_BswMD

[For each `McParameterElementGroup`, the attribute `shortLabel` shall exist.
]

[constr_10345] Existence of the reference in the role `ImplementationElementInParameterInstanceRef.context`*Imposition time:* IT_BswMD

[For each `ImplementationElementInParameterInstanceRef`, the reference in the role `context` shall exist.
]

[constr_10346] Existence of the reference in the role `ImplementationElementInParameterInstanceRef.target`

Imposition time: IT_BswMD

[For each `ImplementationElementInParameterInstanceRef`, the reference in the role `target` shall exist.

]

[constr_10347] Existence of the instanceRef in the role `McDataAccessDetails.rteEvent`

Imposition time: IT_BswMD

[For each `McDataAccessDetails`, the instanceRef in the role `rteEvent` shall exist at least once.

]

[constr_10349] Existence of attribute `RptSupportData.executionContext`

Imposition time: IT_BswMD

[For each `RptSupportData`, the attribute `executionContext` shall exist at least once.

]

[constr_10350] Existence of attribute `RptSupportData.rptComponent`

Imposition time: IT_BswMD

[For each `RptSupportData`, the attribute `rptComponent` shall exist at least once.

]

[constr_10351] Existence of attribute `RptSupportData.rptServicePoint`

Imposition time: IT_BswMD

[For each `RptSupportData`, the attribute `rptServicePoint` shall exist at least once.

]

[constr_10352] Existence of attribute `RptComponent.rptExecutableEntity`

Imposition time: IT_BswMD

[For each `RptComponent`, the attribute `rptExecutableEntity` shall exist at least once.

]

[constr_10353] Existence of attribute `RptExecutableEntity.rptExecutableEntityEvent`*Imposition time:* IT_BswMD

[For each `RptExecutableEntity`, the attribute `rptExecutableEntityEvent` shall exist at least once.

]

[constr_10354] Existence of attribute `RptExecutableEntity.symbol`*Imposition time:* IT_BswMD

[For each `RptExecutableEntity`, the attribute `symbol` shall exist.

]

[constr_10355] Existence of the reference in the role `RptExecutableEntityEvent.executionContext`*Imposition time:* IT_BswMD

[For each `RptExecutableEntityEvent`, the reference in the role `executionContext` shall exist at least once.

]

[constr_10356] Existence of attribute `RptExecutableEntityEvent.rptEventId`*Imposition time:* IT_BswMD

[For each `RptExecutableEntityEvent`, the attribute `rptEventId` shall exist.

]

[constr_10357] Existence of attribute `RptExecutableEntityEvent.rptExecutableEntityProperties`*Imposition time:* IT_BswMD

[For each `RptExecutableEntityEvent`, the attribute `rptExecutableEntityProperties` shall exist.

]

[constr_10358] Existence of the reference in the role `RptExecutableEntityEvent.rptServicePointPost`*Imposition time:* IT_BswMD

[For each `RptExecutableEntityEvent`, the reference in the role `rptServicePointPost` shall exist at least once.

]

[constr_10359] Existence of the reference in the role `RptExecutableEntityEvent.rptServicePointPre`

Imposition time: IT_BswMD

[For each `RptExecutableEntityEvent`, the reference in the role `rptServicePointPre` shall exist at least once.

]

[constr_10360] Existence of attribute `RptServicePoint.serviceId`

Imposition time: IT_BswMD

[For each `RptServicePoint`, the attribute `serviceId` shall exist.

]

[constr_10362] Existence of attribute `AliasNameSet.aliasName`

Imposition time: IT_BswMD

[For each `AliasNameSet`, the attribute `aliasName` shall exist at least once.

]

[constr_10363] Existence of attribute `AliasNameAssignment.shortLabel`

Imposition time: IT_BswMD

[For each `AliasNameAssignment`, the attribute `shortLabel` shall exist.

]

2.2 CP_TPS_DiagnosticExtractTemplate

[constr_1324] Existence of attribute `DiagnosticDataIdentifier.representsVin`

Imposition time: IT_Dext

[Within the context of a given `DiagnosticContributionSet`, the attribute `DiagnosticDataIdentifier.representsVin` shall have the value `true` for only a single `DiagnosticDataIdentifier`.

]

[constr_1325] Allowed attributes of `SwDataDefProps` for `DiagnosticDataElement.swDataDefProps`

Imposition time: IT_Dext

[

Attributes of <code>SwDataDefProps</code>	<code>DiagnosticDataElement.swDataDefProps</code>
<code>additionalNativeTypeQualifier</code>	
<code>annotation</code>	
<code>baseType.baseTypeDefinition.baseTypeEncoding</code>	D
<code>baseType.baseTypeDefinition.baseTypeSize</code>	D
<code>baseType.baseTypeDefinition.byteOrder</code>	D
<code>baseType.baseTypeDefinition.memAlignment</code>	
<code>baseType.baseTypeDefinition.nativeDeclaration</code>	
<code>compuMethod</code>	D
<code>dataConstr</code>	D
<code>displayFormat</code>	D
<code>displayPresentation</code>	
<code>implementationDataType</code>	
<code>invalidValue</code>	
<code>swAddrMethod</code>	
<code>swAlignment</code>	
<code>swBitRepresentation</code>	
<code>swCalibrationAccess</code>	
<code>swCalprmAxisSet</code>	
<code>swComparisonVariable</code>	
<code>swDataDependency</code>	
<code>swImplPolicy</code>	
<code>swIntendedResolution</code>	
<code>swInterpolationMethod</code>	
<code>swIsVirtual</code>	
<code>swPointerTargetProps</code>	
<code>swRecordLayout</code>	
<code>swRefreshTiming</code>	
<code>swTextProps</code>	
<code>swValueBlockSize</code>	
<code>unit</code>	D
<code>valueAxisDataType</code>	

]

[constr_1326] Existence of a variable-sized array

Imposition time: IT_Dext

[The value of the attribute `DiagnosticDataElement.arraySizeSemantics` **shall not** be set to `ArraySizeSemanticsEnum.variableSize` if the respective `DiagnosticDataElement` is referenced from a `DiagnosticServiceDataMapping`.

]

[constr_1327] Multiplicity of `DiagnosticEcuInstanceProps.ecuInstance`

Imposition time: IT_Dext

[The multiplicity of `DiagnosticEcuInstanceProps.ecuInstance` shall be limited to 1 and the enclosing `DiagnosticContributionSet` shall only refer to at most one `DiagnosticEcuInstanceProps` if the enclosing `DiagnosticContributionSet` is of category `DIAGNOSTICS_ECU_EXTRACT`.

]

[constr_1328] Consistency of `DiagnosticEcuInstanceProps.ecuInstance` and `DiagnosticServiceTable.ecuInstance`

Imposition time: IT_Dext

[Each `DiagnosticServiceTable` referenced by any given `DiagnosticContributionSet` in the role `serviceTable` shall define a reference in the role `DiagnosticServiceTable.ecuInstance` to an `EcuInstance` that is also referenced in the role `DiagnosticEcuInstanceProps.ecuInstance` by a `DiagnosticEcuInstanceProps` referenced by the mentioned `DiagnosticContributionSet` if the respective `DiagnosticContributionSet` is of category `DIAGNOSTICS_ECU_EXTRACT`.

]

[constr_1329] Existence of concrete sub-classes of `DiagnosticServiceClass` in the context created by a `DiagnosticContributionSet`

Imposition time: IT_Dext

[One of the following mutually exclusive conditions shall apply for the existence of any concrete sub-class of `DiagnosticServiceClass` in the context created by a `DiagnosticContributionSet`:

- The subclass of `DiagnosticServiceClass` (except `DiagnosticCustomServiceClass`) shall only appear once in the context created by a `DiagnosticContributionSet`.
- A `DiagnosticCustomServiceClass` with a given value of attribute `customServiceId` shall only appear once in the context created by a `DiagnosticContributionSet`.
- If the subclass of `DiagnosticServiceClass` (except `DiagnosticCustomServiceClass`) appears multiple times in the context created by a `DiagnosticContributionSet`, then all instances of the sub-class of `DiagnosticServiceClass` shall have identical values for all of their attributes.

In case of aggregations, the number of aggregated elements shall be identical and the values of primitive attributes of aggregated elements shall again be identical.

]

[constr_1330] Custom service identifier shall not overlap with standardized service identifiers

Imposition time: IT_Dext

[The value of the attribute `DiagnosticCustomServiceClass.customServiceId` shall not be set to any of the values reserved for standardized service identifiers as defined by the, see [3].

]

[constr_1331] Existence of `DiagnosticEcuReset.customSubFunctionNumber`

Imposition time: IT_Dext

[The attribute `DiagnosticEcuReset.customSubFunctionNumber` shall only exist if the value of `DiagnosticEcuReset.category` is outside the standardized set of values as defined by [TPS_DEXT_01056].

]

[constr_1332] Value range for `DiagnosticEcuReset.customSubFunctionNumber`

Imposition time: IT_Dext

[The allowed value for `DiagnosticEcuReset.customSubFunctionNumber` shall always be within the closed interval **0x40 .. 0x7E**.

]

[constr_1333] Existence of attributes of meta-class `DiagnosticMemoryIdentifier`

Imposition time: IT_Dext

[If a `DiagnosticMemoryIdentifier` is referenced in the role `memoryRange` by a `DiagnosticRequestDownload` or a `DiagnosticRequestUpload`, then the attributes

- `memoryLowAddress`
- `memoryLowAddressLabel`
- `memoryHighAddress`
- `memoryHighAddressLabel`
- `accessPermission`

shall **not** exist for the referenced `DiagnosticMemoryIdentifier`.

]

[constr_1334] Existence of `DiagnosticComControl.customSubFunctionNumber`

Imposition time: IT_Dext

[The attribute `DiagnosticComControl.customSubFunctionNumber` shall only exist if the value of `DiagnosticComControl.category` is outside the standardized set of values as defined by [TPS_DEXT_01057].

]

[constr_1335] Possible values for `DiagnosticComControl.customSubFunctionNumber`

Imposition time: IT_Dext

[Given the fulfillment of [constr_1334], the value of a given `DiagnosticComControl.customSubFunctionNumber` shall always be within the closed interval `0x40 .. 0x5F` (for manufacturer-specific sub-functions) or the closed interval `0x60 .. 0x7E` (for supplier-specific sub-functions).

]

[constr_1336] Applicable value range for `DiagnosticComControlSpecificChannel.subnetNumber`

Imposition time: IT_Dext

[The value of attribute `DiagnosticComControlSpecificChannel.subnetNumber` shall be within the closed interval `1 .. 14`.

]

[constr_1337] Allowed value range for attribute `DiagnosticComControlSubNodeChannel.subNodeNumber`

Imposition time: IT_Dext

[The value of attribute `DiagnosticComControlSubNodeChannel.subNodeNumber` shall not exceed the closed interval `0 .. 65535`.

]

[constr_1338] Maximum number of aggregated `DiagnosticReadDataByPeriodicIDClass.periodicRate`

Imposition time: IT_Dext

[The number of aggregated `periodicRate` within the context of one `DiagnosticReadDataByPeriodicIDClass` shall be within the closed interval `1..3`.

]

[constr_1339] Existence of `DiagnosticRoutine.start`

Imposition time: IT_Dext

[In a complete `DiagnosticExtract`, the attribute `DiagnosticRoutine.start` shall always exist for any given `DiagnosticRoutine`.

]

[constr_1340] Consistency of `DiagnosticServiceSwMapping` with respect to synchronously called `DiagnosticRoutines`

Imposition time: IT_Dext

[Each `DiagnosticServiceSwMapping` that references a `DiagnosticRoutineControl` that only aggregates a `DiagnosticStartRoutine` in the role `start` shall only reference a `SwcServiceDependency` or `BswServiceDependency` that in turn aggregates a `DiagnosticRoutineNeeds` with attribute `diagRoutineType` set to `DiagnosticRoutineTypeEnum.synchronous`.

]

[constr_1341] Consistency of `DiagnosticServiceSwMapping` with respect to asynchronously called `DiagnosticRoutines`

Imposition time: IT_Dext

[Each `DiagnosticServiceSwMapping` that references a `DiagnosticRoutineControl` that aggregates a `DiagnosticStopRoutine` and/or `DiagnosticRequestRoutineResults` in the role `stop` or `requestResult` shall only reference a `SwcServiceDependency` or `BswServiceDependency` that in turn aggregates a `DiagnosticRoutineNeeds` with attribute `diagRoutineType` set to `DiagnosticRoutineTypeEnum.asynchronous`.

]

[constr_1342] Possible values for `DiagnosticSecurityAccess.requestSeedId`

Imposition time: IT_Dext

[The value of the attribute `DiagnosticSecurityAccess.requestSeedId` shall only be set to an odd number³.

The supported value range consists of the following list:

- all odd numbers in the closed interval **0x01 .. 0x41**
- **0x5F** (this corresponds to the case of *end-of-life activation of on-board pyrotechnic devices according to [4]*)
- all odd numbers in the closed interval **0x61 .. 0x7E**

³The even numbers are reserved for the identification of the corresponding `sendKey` sub-function, as explained by [TPS_DEXT_01036].

]

[constr_1343] Simultaneous existence of the attributes `DiagnosticServiceDataMapping.diagnosticDataElement` and `DiagnosticDataByIdentifier.dataIdentifier`

Imposition time: IT_Dext

[A `DiagnosticServiceDataMapping.diagnosticDataElement` shall also be aggregated by a `DiagnosticDataByIdentifier` in the role `dataIdentifier.dataElement.dataElement`.

]

[constr_1345] `DiagnosticDataElement` shall not (finally) be aggregated by a `DiagnosticRoutine`

Imposition time: IT_Dext

[A `DiagnosticDataElement` that is referenced by a `DiagnosticServiceDataMapping` shall not (finally) be aggregated by a `DiagnosticRoutine`.

]

[constr_1346] Allowed values of `DiagnosticServiceSwMapping.serviceInstance`

Imposition time: IT_Dext

[The applicability of the `DiagnosticServiceSwMapping` is limited to predefined set of diagnostic services.

By regulation of the AUTOSAR standard, `DiagnosticServiceSwMapping.serviceInstance` shall only point to the following sub-classes of `DiagnosticServiceInstance`:

- `DiagnosticRoutine`
- `DiagnosticSecurityAccess`
- `DiagnosticReadDataByIdentifier`
- `DiagnosticWriteDataByIdentifier`
- `DiagnosticIOControl`

]

[constr_1347] Existence of attributes of `DiagnosticServiceSwMapping`

Imposition time: IT_Dext

[For any given `DiagnosticServiceSwMapping`, **one and only one** of the following references shall exist:

- `DiagnosticServiceSwMapping.mappedFlatSwcServiceDependency`
- `DiagnosticServiceSwMapping.mappedSwcServiceDependencyInSystem`
- `DiagnosticServiceSwMapping.mappedBswServiceDependency`

]

[constr_1349] Value of `udsDtcValue` shall be unique*Imposition time:* IT_Dext

[The value of `DiagnosticTroubleCodeUds.udsDtcValue` shall be unique for all `DiagnosticTroubleCodeUds` that refer to the same `DiagnosticMemoryDestination` via the reference `DiagnosticTroubleCodeUds.troubleCodeProps.diagnosticMemory`.

]

[constr_1350] Value of `DiagnosticTroubleCodeGroup.groupNumber` shall be unique*Imposition time:* IT_Dext

[The value of `DiagnosticTroubleCodeGroup.groupNumber` shall be unique to any other DTC and DTC group value.

]

[constr_1351] Value of `DiagnosticTroubleCodeGroup.groupNumber`*Imposition time:* IT_Dext

[To be compliant to ISO, the value of `DiagnosticTroubleCodeGroup.groupNumber` shall be set as defined in [3].

]

[constr_1352] Existence of `maxNumberFreezeFrameRecords` vs. `freezeFrame`*Imposition time:* IT_Dext

[If the attribute `DiagnosticTroubleCodeProps.maxNumberFreezeFrameRecords` exists than the attribute `DiagnosticTroubleCodeProps.freezeFrame` shall not exist or vice versa.

]

[constr_1353] Applicability of [constr_1352]*Imposition time:* IT_Dext

[[constr_1352] shall apply in the identical way (either one or the other attribute shall exist) for all `DiagnosticTroubleCodeProps` within the context of all `Diagnos-`

ticContributionSets of category DIAGNOSTIC_ECU_EXTRACT that refer to the same EcuInstance.

]

[constr_1354] Existence of attribute DiagnosticTroubleCodeProps.snapshotRecordContent

Imposition time: IT_Dext

[If one of the attributes DiagnosticTroubleCodeProps.maxNumberFreezeFrameRecords or DiagnosticTroubleCodeProps.freezeFrame exists then the attribute DiagnosticTroubleCodeProps.snapshotRecordContent shall exist.

]

[constr_1355] Value of extendedDataRecord.recordNumber

Imposition time: IT_Dext

[To be compliant to ISO, the value of extendedDataRecord.recordNumber shall be set in the interval as defined in [3].

]

[constr_1357] Value of freezeFrame.recordNumber

Imposition time: IT_Dext

[To be compliant to ISO, the value of freezeFrame.recordNumber shall be set in the interval as defined in [3].

]

[constr_1359] Condition for the existence of attribute DiagnosticDebounceAlgorithmProps.debounceCounterStorage

Imposition time: IT_Dext

[Attribute debounceCounterStorage of meta-class DiagnosticDebounceAlgorithmProps shall only exist if the aggregation of attribute debounceAlgorithm at DiagnosticDebounceAlgorithmProps actually aggregates a DiagEventDebounceCounterBased.

]

[constr_1361] Number of DiagnosticEventToEnableConditionGroupMapping elements per DiagnosticEvent

Imposition time: IT_Dext

[The mapping element DiagnosticEventToEnableConditionGroupMapping shall be created no more than once per DiagnosticEvent.

If several `DiagnosticEventToEnableConditionGroupMapping` elements referring to the same `DiagnosticEvent` are defined, then the `Enable Condition Group` mapping shall be regarded as defective.

]

[constr_1362] Number of `DiagnosticEventToStorageConditionGroupMapping` elements per `DiagnosticEvent`

Imposition time: IT_Dext

[The mapping element `DiagnosticEventToStorageConditionGroupMapping` shall be created no more than once or once per `DiagnosticEvent`.

If several `DiagnosticEventToStorageConditionGroupMapping` elements referring to the same `DiagnosticEvent` are defined, then the `Storage Condition Group` mapping shall be regarded as defective.

]

[constr_1378] Value of `DiagnosticMemoryDestinationUserDefined.memoryId`

Imposition time: IT_Dext

[Within the scope of one `DiagnosticContributionSet`, no two (or more) `DiagnosticMemoryDestinationUserDefineds` shall exist that share the same value for attribute `DiagnosticMemoryDestinationUserDefined.memoryId`

]

[constr_1379] Existence of `DiagnosticMemoryDestinationPrimary`

Imposition time: IT_Dext

[Within the scope of one `DiagnosticContributionSet` only one `DiagnosticMemoryDestinationPrimary` shall exist.

]

[constr_1394] Value of `DiagnosticDataElement.maxNumberOfElements` depending on its existence

Imposition time: IT_Dext

[If the attribute `DiagnosticDataElement.maxNumberOfElements` exists then its value shall be greater than 0.

]

[constr_1405] Value of `DiagnosticProtocol.serviceTable` vs. `DiagnosticServiceTable.protocolKind`

Imposition time: IT_Dext

[If the reference `DiagnosticProtocol.serviceTable` exists then the value of `DiagnosticProtocol.protocolKind` shall be identical to the value of `DiagnosticServiceTable.protocolKind`.

]

[constr_1406] `DiagnosticServiceTable.diagnosticConnection` vs. `DiagnosticProtocol.diagnosticConnection`

Imposition time: IT_Dext

[If a `DiagnosticServiceTable` exists that fulfills the following conditions:

- reference `DiagnosticServiceTable.diagnosticConnection` exists
- the `DiagnosticServiceTable` is referenced by means of `DiagnosticProtocol.serviceTable`

then all of the `DiagnosticConnections` referenced by means of `DiagnosticServiceTable.diagnosticConnection` shall also be referenced in the role `diagnosticConnection` from a `DiagnosticProtocol` that in turn references the respective `DiagnosticServiceTable` in the role `DiagnosticProtocol.serviceTable`.

]

[constr_1411] Existence of attribute `DiagnosticMemoryIdentifier.memoryHighAddressLabel` vs. `DiagnosticMemoryIdentifier.memoryHighAddress`

Imposition time: IT_Dext

[At most **one** of the attributes in the following list shall exist:

- `DiagnosticMemoryIdentifier.memoryHighAddressLabel`
- `DiagnosticMemoryIdentifier.memoryHighAddress`

]

[constr_1412] Existence of `DiagnosticMemoryIdentifier.memoryLowAddressLabel` vs. `DiagnosticMemoryIdentifier.memoryLowAddress`

Imposition time: IT_Dext

[At most **one** of the attributes in the following list shall exist:

- `DiagnosticMemoryIdentifier.memoryLowAddressLabel`
- `DiagnosticMemoryIdentifier.memoryLowAddress`

]

[constr_1419] Value of `DiagnosticSecurityLevel.accessDataRecordSize`

Imposition time: IT_Dext

[If the attribute `DiagnosticSecurityLevel.accessDataRecordSize` exists then its value shall be greater than zero.

]

[constr_1421] Consistency of `DiagnosticDynamicallyDefineDataIdentifierClass.subfunction`

Imposition time: IT_Dext

[The values of `DiagnosticDynamicallyDefineDataIdentifierClass.subfunction` shall not repeat, i.e. every value of `DiagnosticDynamicallyDefineDataIdentifierSubfunctionEnum` shall at most appear once in the `subfunction` attribute.

]

[constr_1435] Debouncing in the presence of a `DiagnosticEventPortMapping`

Imposition time: IT_Dext

[If a `DiagnosticEventPortMapping` exists and the enclosed `DiagnosticEventPortMapping.diagnosticEvent` is also referenced by a `DiagnosticEventToDebounceAlgorithmMapping` then the concrete subclass of the respective `DiagnosticEventToDebounceAlgorithmMapping.debounceAlgorithm.debounceAlgorithm` shall be identical to the `DiagnosticEventPortMapping.swcServiceDependencyInSystem/swcFlatServiceDependency.serviceNeeds.diagEventDebounceAlgorithm`.

It is assumed that the target of reference `DiagnosticEventPortMapping.swcServiceDependencyInSystem` resp. `swcFlatServiceDependency` aggregates a `DiagnosticEventNeeds`.

]

[constr_1447] Restrictions for the value of `DiagnosticParameterIdentifier.id`

Imposition time: IT_Dext

[The values 0x00, 0x20, 0x40, 0x60, 0x80, 0xA0, 0xC0, and 0xE0 are not allowed to appear in the value of `DiagnosticParameterIdentifier.id`.

]

[constr_1448] Interval of `DiagnosticParameterIdentifier.id`

Imposition time: IT_Dext

[The allowed interval for values of `DiagnosticParameterIdentifier.id` shall not exceed [0..255].

]

[constr_1449] PID shall only carry a fixed-length collection of data

Imposition time: IT_Dext

[The value of `DiagnosticParameterIdentifier.dataElement.dataElement.arraySizeSemantics` shall not be set to `variableSize`.

]

[constr_1450] Service mapping for ODB mode 0x01 for `DiagnosticParameterIdentifier`

Imposition time: IT_Dext

[if a `DiagnosticServiceSwMapping` or `DiagnosticServiceDataMapping` refers to a `DiagnosticRequestCurrentPowertrainData` and a `DiagnosticDataElement` that is aggregated by a `DiagnosticParameterIdentifier` then then one of two alternative model configurations shall exist:

- `SwcServiceDependency` referenced by the same `DiagnosticServiceSwMapping` or `DiagnosticServiceDataMapping` shall aggregate an `ObdPidServiceNeeds` in the role `serviceNeeds`.
- The `BswServiceDependencyIdent` referenced by the same `DiagnosticServiceSwMapping` shall aggregate an `ObdPidServiceNeeds` in the role `serviceNeeds`.

]

[constr_1451] Service mapping for OBD mode 0x09 for `DiagnosticInfoType`

Imposition time: IT_Dext

[if a `DiagnosticServiceSwMapping` refers to `DiagnosticRequestVehicleInfo` and a `DiagnosticDataElement` that is aggregated by a `DiagnosticInfoType` then one of two alternative model configurations shall exist:

- The `SwcServiceDependency` referenced by the same `DiagnosticServiceSwMapping` shall aggregate a `ObdInfoServiceNeeds` in the role `serviceNeeds`.
- The `BswServiceDependencyIdent` referenced by the same `DiagnosticServiceSwMapping` shall aggregate an `ObdInfoServiceNeeds` in the role `serviceNeeds`.

]

[constr_1452] Service mapping for OBD mode 0x08 for [DiagnosticInfoType](#)*Imposition time:* IT_Dext

[if a [DiagnosticServiceSwMapping](#) refers to a [DiagnosticRequestControlOfOnBoardDevice](#) then the [SwcServiceDependency](#) referenced by the same [DiagnosticServiceSwMapping](#) shall aggregate an [ObdControlServiceNeeds](#) in the role [serviceNeeds](#).

]

[constr_1453] References from [DiagnosticFunctionInhibitSource](#)*Imposition time:* IT_Dext

[Each [DiagnosticFunctionInhibitSource](#) may either reference one of the following meta-classes in their respective roles:

- [DiagnosticFimAliasEventMapping](#) in the role [event](#)
- [DiagnosticFimAliasEventGroupMapping](#) in the role [eventGroup](#)

]

[constr_1454] [DiagnosticFimFunctionMapping](#) shall only reference a [SwcServiceDependency](#) that aggregates [FunctionInhibitionNeeds](#)*Imposition time:* IT_Dext

[A [DiagnosticFimFunctionMapping](#) shall only reference a [SwcServiceDependency](#) that aggregates [FunctionInhibitionNeeds](#) in the role [serviceNeeds](#).

]

[constr_1455] Relation of [DiagnosticJ1939Node](#) to [J1939NmNode](#)*Imposition time:* IT_Dext

[Each [J1939NmNode](#) shall only be referenced in the role [nmNode](#) by a single [DiagnosticJ1939Node](#).

]

[constr_1456] Valid interval for attribute [DiagnosticTroubleCodeJ1939.fmi](#)*Imposition time:* IT_Dext

[The value of the attribute [DiagnosticTroubleCodeJ1939.fmi](#) shall be in the interval 0..31.

]

[constr_1457] Service-only DTCs shall refer to a common memory section

Imposition time: IT_Dext

[All `DiagnosticTroubleCodeJ1939` with attribute `kind` set to the value `serviceOnly` that reference the same `DiagnosticJ1939Node` shall also reference the same `DiagnosticTroubleCodeProps.diagnosticMemory`.

]

[constr_1458] Reference to `DiagnosticMemoryDestination`

Imposition time: IT_Dext

[A `DiagnosticMemoryDestination` that is referenced by a `DiagnosticTroubleCodeJ1939.dtcProps.diagnosticMemory` where the value of attribute `DiagnosticTroubleCodeJ1939.kind` is set to `serviceOnly` shall **not be referenced by any other** `DiagnosticTroubleCodeJ1939` where attribute `kind` is set to any other value than `serviceOnly`.

]

[constr_1460] Restrictions for the value of `DiagnosticInfoType.id`

Imposition time: IT_Dext

[The values 0x00, 0x20, 0x40, 0x60, 0x80, 0xA0, 0xC0, and 0xE0 are not allowed to appear in the value of `DiagnosticInfoType.id`.

]

[constr_1461] Restrictions for the value of `DiagnosticTestRoutineIdentifier.id`

Imposition time: IT_Dext

[The values 0x00, 0x20, 0x40, 0x60, 0x80, 0xA0, 0xC0, and 0xE0 are not allowed to appear in the value of `DiagnosticTestRoutineIdentifier.id`.

]

[constr_1462] Restrictions for the value of `DiagnosticTestResult.testIdentifier.id`

Imposition time: IT_Dext

[The values 0x00, 0x20, 0x40, 0x60, 0x80, 0xA0, 0xC0, and 0xE0 are not allowed to appear in the value of `DiagnosticTestResult.testIdentifier.id`.

]

[constr_1464] Allowed value range of `DiagnosticEnvConditionFormula.nrcValue`

Imposition time: IT_Dext

[The value of attribute `DiagnosticEnvConditionFormula.nrcValue` shall be limited to the interval [1..255].

]

[constr_1466] Allowed values of `compareType` in the context of a `DiagnosticEnvModeCondition`

Imposition time: IT_Dext

[Within the context of a `DiagnosticEnvDataCondition` **only a subset** of the values of `DiagnosticCompareTypeEnum` is supported for the inherited attribute `compareType`, namely:

- `DiagnosticCompareTypeEnum.isEqual`
- `DiagnosticCompareTypeEnum.isNotEqual`

]

[constr_1467] References in `DiagnosticEnvModeCondition`

Imposition time: IT_Dext

[In a `DiagnosticEnvModeCondition` the reference `modeElement` shall only point to a `DiagnosticEnvModeElement` that is aggregated inside the same `DiagnosticEnvironmentalCondition` as the `DiagnosticEnvModeCondition` itself.

]

[constr_1470] Value of `DiagnosticAbstractParameter.bitOffset`

Imposition time: IT_Dext

[The value of `DiagnosticAbstractParameter.bitOffset` shall only be set to a multiple of 8.

]

[constr_1472] Existence of `DiagnosticDataIdentifier.supportInfoByte`

Imposition time: IT_Dext

[The attribute `DiagnosticDataIdentifier.supportInfoByte` shall not exist if the value of `DiagnosticDataIdentifier.id` is **outside the range 0xF400-0xF4FF**.

]

[constr_1509] Value of `extendedDataRecord.recordNumber` shall be unique within primary fault memory

Imposition time: IT_Dext

[For all `DiagnosticTroubleCodeProps` that refer to `DiagnosticMemoryDestinationPrimary` in the role `diagnosticMemory` there shall be no two `extendedDataRecord.recordNumber` with the same value.

]

[constr_1511] Value of `extendedDataRecord.recordNumber` shall be unique within user-defined fault memory

Imposition time: IT_Dext

[For all `DiagnosticTroubleCodeProps` that refer to `DiagnosticMemoryDestinationUserDefined` in the role `diagnosticMemory` there shall be no two `extendedDataRecord.recordNumber` with the same value for any `DiagnosticMemoryDestinationUserDefined` referenced as `DiagnosticTroubleCodeProps.diagnosticMemory` with a given value of `memoryId`.

]

[constr_1512] `freezeFrame.recordNumber` shall be unique within primary fault memory

Imposition time: IT_Dext

[For all `DiagnosticTroubleCodeProps` that refer to `DiagnosticMemoryDestinationPrimary` in the role `diagnosticMemory` there shall be no two `freezeFrame.recordNumber` with the same value.

]

[constr_1514] `freezeFrame.recordNumber` shall be unique within user-defined fault memory

Imposition time: IT_Dext

[For all `DiagnosticTroubleCodeProps` that refer to `DiagnosticMemoryDestinationUserDefined` in the role `diagnosticMemory` there shall be no two `freezeFrame.recordNumber` with the same value for any `DiagnosticMemoryDestinationUserDefined` referenced as `DiagnosticTroubleCodeProps.diagnosticMemory` with a given value of `memoryId`.

]

[constr_1552] Meta-class `DiagnosticDataIdentifier` referenced by `DiagnosticDataIdentifierSet`

Imposition time: IT_Dext

[If a `DiagnosticDataIdentifier` is referenced by `DiagnosticDataIdentifierSet`, then the `DiagnosticDataIdentifier` shall fulfill **all of the following conditions**:

- The `DiagnosticDataIdentifier` does **not** aggregate any `DiagnosticParameter` which in turn aggregates (via the aggregation of `DiagnosticParameterIdent`) a `DiagnosticParameterElement`.
- Gaps in between individual elements (i.e. from the begin of an individual `DiagnosticDataElement`, as indicated by `DiagnosticParameter.bitOffset`, and the length of the aggregated `DiagnosticDataElement`) or at the end of the `DiagnosticDataIdentifier` (as indicated by attribute `DiagnosticDataIdentifier.didSize`) shall **not** exist.

The individual `DiagnosticDataElement` contained (via the aggregation of `DiagnosticParameter` in the role `dataElement`) in the `DiagnosticDataIdentifier` shall satisfy **one of the following conditions**:

- The `DiagnosticDataElement` does **not** define the attribute `maxNumberOfElements` at all.
- The modeling of attribute `DiagnosticDataElement.arraySizeSemantics` shall follow the description in [TPS_DEXT_01001].

]

[constr_1584] `DiagnosticDataElement` shall not be used more than once in I/O Control instance

Imposition time: IT_Dext

[A given `DiagnosticDataElement` shall not be used by more than one `DiagnosticServiceDataMapping` that in turn refers to a `DataPrototype` defined in the context of a `DataInterface` that is used to type a `PortPrototype` that in turn is referenced by a `RoleBasedPortAssignment` where attribute `role` is set to the value `IOControlRequest`.

]

[constr_1590] `DiagnosticEvent` referenced in the role `masterEvent` or `slaveEvent`

Imposition time: IT_Dext

[Any given `DiagnosticEvent` shall at most once be referenced from a `DiagnosticMasterToSlaveEventMapping`.

]

[constr_1591] DiagnosticEvent referenced as slaveEvent shall not be reported by diagnostic monitor

Imposition time: IT_Dext

[Any `DiagnosticEvent` that is referenced in the role `DiagnosticMasterToSlaveEventMapping.slaveEvent` shall not be referenced in the role `DiagnosticEventPortMapping.diagnosticEvent` and vice versa.

]

[constr_1612] Reference from DiagnosticRoutineControl to DiagnosticAccessPermission has no meaning

Imposition time: IT_Dext

[The reference from `DiagnosticRoutineControl` (via its abstract base class `DiagnosticServiceInstance`) in the role `accessPermission` to meta-class `DiagnosticAccessPermission` shall not be used.

]

[constr_1616] Existence of attribute DiagnosticExtendedDataRecord.customTrigger

Imposition time: IT_Dext

[The attribute `DiagnosticExtendedDataRecord.customTrigger` shall only exist if the attribute `DiagnosticExtendedDataRecord.trigger` is set to the value `DiagnosticRecordTriggerEnum.custom`.

]

[constr_1617] Existence of attribute DiagnosticFreezeFrame.customTrigger

Imposition time: IT_Dext

[The attribute `DiagnosticFreezeFrame.customTrigger` shall only exist if the attribute `DiagnosticFreezeFrame.trigger` is set to the value `DiagnosticRecordTriggerEnum.custom`.

]

[constr_1623] Restriction on DiagnosticReadScalingDataByIdentifier.dataIdentifier

Imposition time: IT_Dext

[The reference `DiagnosticReadScalingDataByIdentifier.dataIdentifier` shall only refer to a `DiagnosticDataIdentifier`.

]

[constr_1624] Existence of `DiagnosticDataElement.scalingInfoSize`

Imposition time: IT_Dext

[The attribute `DiagnosticDataElement.scalingInfoSize` shall only exist if the enclosing `DiagnosticAbstractParameter` is aggregated by a `DiagnosticDataIdentifier` that is referenced by a `DiagnosticReadScalingDataByIdentifier` in the role `DiagnosticReadScalingDataByIdentifier.dataIdentifier`.

]

[constr_1721] `DiagnosticControlEnableMaskBit.bitNumber` shall be unique

Imposition time: IT_Dext

[Within the context of the enclosing `DiagnosticIOControl` the value of attribute `DiagnosticIOControl.controlEnableMaskBit.bitNumber` shall be unique.

]

[constr_1722] Relation between reference `DiagnosticIOControl.dataIdentifier` and attribute `DiagnosticIOControl.controlEnableMaskBit`

Imposition time: IT_Dext

[Any `DiagnosticDataElement` referenced in the role `DiagnosticIOControl.controlEnableMaskBit.controlledDataElement` shall be defined in the scope of the `DiagnosticDataIdentifier` that is referenced in the role `DiagnosticIOControl.dataIdentifier`.

]

[constr_1745] Indirect reference to `DiagnosticCommonElement`

Imposition time: IT_Dext

[If a `DiagnosticCommonElement` is referenced from within the context of another `DiagnosticCommonElement` and the referencing `DiagnosticCommonElement` is in turn referenced by a `DiagnosticContributionSet` in the role `element` then the referenced `DiagnosticCommonElement` shall also be referenced by the same `DiagnosticContributionSet`.

]

[constr_1749] Existence of `DiagnosticInfoType.dataElement`

Imposition time: IT_Dext

[For each `DiagnosticInfoType`, at least one aggregation of `DiagnosticParameter` in the role `dataElement` shall exist.

]

[constr_1750] Existence of attribute `DiagnosticParameterIdentifier.pidSize`

Imposition time: IT_Dext

[Attribute `DiagnosticParameterIdentifier.pidSize` is only relevant if a gap exists at the end of the `DiagnosticParameterIdentifier`. If this gap does not exist, the size of the `DiagnosticParameterIdentifier` can be computed.

]

[constr_1752] Existence of references owned by `DiagnosticEnableConditionPortMapping`

Imposition time: IT_Dext

[For each `DiagnosticEnableConditionPortMapping`, only one of the following references

- to `SwcServiceDependency` in the role `swcFlatServiceDependency`
- to `SwcServiceDependency` in the role `swcServiceDependencyInSystem`

may exist.

]

[constr_1753] Existence of references owned by `DiagnosticStorageConditionPortMapping`

Imposition time: IT_Dext

[For each `DiagnosticStorageConditionPortMapping`, only one of the following references

- to `SwcServiceDependency` in the role `swcFlatServiceDependency`
- to `SwcServiceDependency` in the role `swcServiceDependencyInSystem`

may exist.

]

[constr_1756] Existence of attributes `DiagnosticExtendedDataRecord.trigger` and `update`

Imposition time: IT_Dext

[For each `DiagnosticExtendedDataRecord`, attributes `trigger` and `update` shall only exist if at least one `DiagnosticDataElement` is aggregated by a `DiagnosticExtendedDataRecord.recordElement` in the role `dataElement` to which no reference in the role `DiagnosticDemProvidedDataMapping.dataElement` exists.

]

[constr_1757] Existence of attribute `DiagnosticTroubleCodeUds.udsDtcValue`*Imposition time:* IT_Dext

[For each `DiagnosticTroubleCodeUds`, attribute `udsDtcValue` shall exist.
]

[constr_1758] Existence of attribute `DiagnosticTroubleCodeObd.obdDTCValue`*Imposition time:* IT_Dext

[For each `DiagnosticTroubleCodeObd`, attribute `obdDTCValue` shall exist.
]

[constr_1759] Existence of references owned by `DiagnosticOperationCyclePortMapping`*Imposition time:* IT_Dext

[For each `DiagnosticOperationCyclePortMapping`, only one of the following references

- to `SwcServiceDependency` in the role `swcFlatServiceDependency`
- to `SwcServiceDependency` in the role `swcServiceDependencyInSystem`

shall exist.

]

[constr_1760] Existence of `DiagnosticExtendedDataRecord.recordElement`*Imposition time:* IT_Dext

[For each `DiagnosticExtendedDataRecord`, at least one aggregation of `DiagnosticParameter` in the role `recordElement` shall exist.

]

[constr_1761] Existence of attribute `DiagnosticConnectedIndicator.healingCycle`*Imposition time:* IT_Dext

[`DiagnosticConnectedIndicator.healingCycle` shall **only exist** if the value of `DiagnosticConnectedIndicator.healingCycleCounterThreshold` is **not equal to 0**.

]

[constr_1762] Existence of references owned by `DiagnosticEventPortMapping`

Imposition time: IT_Dext

[For each `DiagnosticEventPortMapping`, only one of the references

- to `BswServiceDependency` in the role `bswServiceDependency`
- to `SwcServiceDependency` in the role `swcFlatServiceDependency`
- to `SwcServiceDependency` in the role `swcServiceDependencyInSystem`

shall exist.

]

[constr_1763] Existence of attribute `DiagnosticPeriodicRate.periodicRateCategory`

Imposition time: IT_Dext

[For each `DiagnosticPeriodicRate`, the attribute `periodicRateCategory` shall exist.

]

[constr_1766] Existence of `DiagEventDebounceCounterBased.counterJumpDownValue`

Imposition time: IT_Dext

[For each `DiagEventDebounceCounterBased`, attribute `counterJumpDownValue` shall only exist if attribute `counterJumpDown` exists and is set to `true`.

]

[constr_1767] Existence of `DiagEventDebounceCounterBased.counterJumpUpValue`

Imposition time: IT_Dext

[For each `DiagEventDebounceCounterBased`, attribute `counterJumpUpValue` shall only exist if attribute `counterJumpUp` exists and is set to `true`.

]

[constr_1768] Existence of attribute `DiagnosticEvent.associatedEventIdentification`

Imposition time: IT_Dext

[Attribute `DiagnosticEvent.associatedEventIdentification` shall exist if the respective `DiagnosticEvent` is mapped to a `DiagnosticTroubleCodeUds` and one of the following conditions is fulfilled:

- The reference `DiagnosticTroubleCodeUds.troubleCodeProps.snapshotRecordContent` exists and the referenced `DiagnosticDataIdentifierSet` references at least one `dataIdentifier.dataElement.dataElement` that is also referenced by a `DiagnosticDemProvidedDataMapping` that has attribute `dataProvider` set to the value `DEM_EVENT_ASSOCIATED_IDENTIFICATION`.
- The reference `DiagnosticTroubleCodeUds.troubleCodeProps.extendedDataRecord` exists and the referenced `DiagnosticExtendedDataRecord` aggregates at least one `recordElement.dataElement` that is also referenced by a `DiagnosticDemProvidedDataMapping` that has attribute `dataProvider` set to the value `DEM_EVENT_ASSOCIATED_IDENTIFICATION`.

]

[constr_1772] Unique `DiagnosticSession` and `DiagnosticSecurityLevel` for diagnostic routines that have the same identifier*Imposition time:* IT_Dext

[All `DiagnosticAccessPermissions` referenced from `DiagnosticRoutines` where attribute `DiagnosticRoutine.id` has the identical value shall refer to the identical set of `DiagnosticSession` and `DiagnosticSecurityLevel`.

]

[constr_1780] Existence of attribute `DiagnosticTroubleCodeJ1939.fmi`*Imposition time:* IT_Dext

[For each `DiagnosticTroubleCodeJ1939`, attribute `fmi` shall exist.

]

[constr_1781] Existence of attribute `DiagnosticTroubleCodeJ1939.spn`*Imposition time:* IT_Dext

[For each `DiagnosticTroubleCodeJ1939`, attribute `spn` shall exist.

]

[constr_1782] Usage of internal data elements only for extended data records*Imposition time:* IT_Dext

[A `DiagnosticDemProvidedDataMapping` shall **only** refer to a `DiagnosticDataElement` that is aggregated by a `DiagnosticExtendedDataRecord` in the role `recordElement.dataElement`.

]

[constr_1790] Existence of attribute `DiagnosticAbstractParameter.bitOffset`*Imposition time:* IT_Dext

[For each `DiagnosticParameter`, attribute `bitOffset` shall exist.
]

[constr_1791] Existence of attribute `dataElement` vs. `parameterSize` of meta-class `DiagnosticParameter`*Imposition time:* IT_Dext

[For each `DiagnosticParameter`, exactly **one** of the attributes

- `dataElement` or
- `parameterSize`

shall exist.
]

[constr_1792] Existence of `DiagnosticDataIdentifier.dataElement`*Imposition time:* IT_Dext

[For each `DiagnosticDataIdentifier`, the aggregation of `DiagnosticParameter` in the role `dataElement` shall exist at least once.
]

[constr_1793] Existence of attribute `DiagnosticAbstractDataIdentifier.id`*Imposition time:* IT_Dext

[For each `DiagnosticAbstractDataIdentifier`, attribute `id` shall exist.
]

[constr_1794] Existence of attribute `DiagnosticProtocol.priority`*Imposition time:* IT_Dext

[For each `DiagnosticProtocol`, attribute `priority` shall exist.
]

[constr_1795] Existence of attribute `DiagnosticProtocol.protocolKind`*Imposition time:* IT_Dext

[For each `DiagnosticProtocol`, attribute `protocolKind` shall exist.
]

[constr_1797] Existence of attribute `DiagnosticServiceTable.protocolKind`*Imposition time:* IT_Dext[For each `DiagnosticServiceTable`, attribute `protocolKind` shall exist.

]

[constr_1798] Existence of `DiagnosticServiceInstance.serviceClass`*Imposition time:* IT_Dext[For each subclass of `DiagnosticServiceInstance`, a reference with the abstract role `serviceClass` shall exist to a matching subclass of `DiagnosticServiceClass`.This rule applies unless a rule for a specific combination of matching sub-classes of `DiagnosticServiceInstance` and `DiagnosticServiceClass` exists.

]

[constr_1799] Existence of `DiagnosticEnvironmentalCondition.formula`*Imposition time:* IT_Dext[For each `DiagnosticEnvironmentalCondition`, the aggregation of `DiagnosticEnvConditionFormula` in the role `formula` shall exist.

]

[constr_1800] Existence of `DiagnosticEnvConditionFormula.op`*Imposition time:* IT_Dext[For each `DiagnosticEnvConditionFormula`, that attribute `op` shall exist.

]

[constr_1801] Existence of `DiagnosticEnvCompareCondition.compareType`*Imposition time:* IT_Dext[For each `DiagnosticEnvCompareCondition`, that attribute `compareType` shall exist.

]

[constr_1802] Existence of `DiagnosticEnvDataCondition.compareValue`*Imposition time:* IT_Dext[For each `DiagnosticEnvDataCondition`, that attribute `compareValue` shall exist.

]

[constr_1803] Existence of `DiagnosticEnvDataCondition.dataElement`*Imposition time:* IT_Dext

[For each `DiagnosticEnvDataCondition`, that attribute `dataElement` shall exist.
]

[constr_1804] Existence of `DiagnosticEnvModeCondition.modeElement`*Imposition time:* IT_Dext

[For each `DiagnosticEnvModeCondition`, that attribute `modeElement` shall exist.
]

[constr_1805] Existence of `DiagnosticEnvSwcModeElement.mode`*Imposition time:* IT_Dext

[For each `DiagnosticEnvSwcModeElement`, that attribute `mode` shall exist.
]

[constr_1806] Existence of `DiagnosticEnvBswModeElement.mode`*Imposition time:* IT_Dext

[For each `DiagnosticEnvBswModeElement`, that attribute `mode` shall exist.
]

[constr_1807] Existence of reference `DiagnosticDataByIdentifier.dataIdentifier`*Imposition time:* IT_Dext

[For each `DiagnosticDataByIdentifier`, the reference `dataIdentifier` shall exist.
]

[constr_1808] Existence of reference `DiagnosticDynamicallyDefineDataIdentifier.dataIdentifier`*Imposition time:* IT_Dext

[For each `DiagnosticDynamicallyDefineDataIdentifier`, the reference to `DiagnosticDynamicDataIdentifier` in the role `dataIdentifier` shall exist.
]

[constr_1810] Existence of aggregation `DiagnosticReadDataByPeriodicIDClass.periodicRate`*Imposition time:* IT_Dext

[For each `DiagnosticReadDataByPeriodicIDClass`, the aggregation of `DiagnosticPeriodicRate` in the role `periodicRate` shall exist at least once.

]

[constr_1811] Existence of attribute `DiagnosticReadDataByPeriodicIDClass.maxPeriodicDidToRead`*Imposition time:* IT_Dext

[For each `DiagnosticReadDataByPeriodicIDClass`, the attribute `maxPeriodicDidToRead` shall exist at least once.

]

[constr_1812] Existence of attribute `DiagnosticReadDataByPeriodicIDClass.schedulerMaxNumber`*Imposition time:* IT_Dext

[For each `DiagnosticReadDataByPeriodicIDClass`, the attribute `schedulerMaxNumber` shall exist at least once.

]

[constr_1815] Existence of attribute `DiagnosticRoutine.id`*Imposition time:* IT_Dext

[For each `DiagnosticRoutine`, the attribute `id` shall exist at least once.

]

[constr_1816] Existence of attribute `DiagnosticSecurityAccess.requestSeedId`*Imposition time:* IT_Dext

[For each `DiagnosticSecurityAccess`, the attribute `requestSeedId` shall exist at least once.

]

[constr_1817] Existence of attribute `DiagnosticSecurityAccess.securityLevel`*Imposition time:* IT_Dext

[For each `DiagnosticSecurityAccess`, the attribute `securityLevel` shall exist at least once.

]

[constr_1818] Existence of reference `DiagnosticSessionControl.diagnosticSession`*Imposition time:* IT_Dext

[For each `DiagnosticSessionControl`, the reference to `DiagnosticSession` in the role `diagnosticSession` shall exist.

]

[constr_1819] Existence of attribute `DiagnosticParameterIdentifier.id`*Imposition time:* IT_Dext

[For each `DiagnosticParameterIdentifier`, attribute `id` shall exist.

]

[constr_1820] Existence of reference `DiagnosticRequestCurrentPowertrainData.pid`*Imposition time:* IT_Dext

[For each `DiagnosticRequestCurrentPowertrainData`, the reference to `DiagnosticParameterIdentifier` in the role `pid` shall exist.

]

[constr_1821] Existence of reference `DiagnosticRequestPowertrainFreezeFrameData.freezeFrame`*Imposition time:* IT_Dext

[For each `DiagnosticRequestPowertrainFreezeFrameData`, the reference to `DiagnosticParameterIdentifier` in the role `freezeFrame` shall exist.

]

[constr_1822] Existence of reference `DiagnosticRequestControlOfOnBoardDevice.testId`

Imposition time: IT_Dext

[For each `DiagnosticRequestControlOfOnBoardDevice`, the reference to `DiagnosticParameterIdentifier` in the role `testId` shall exist.

]

[constr_1823] Existence of attribute `DiagnosticTestRoutineIdentifier.id`

Imposition time: IT_Dext

[For each `DiagnosticTestRoutineIdentifier`, attribute `id` shall exist.

]

[constr_1824] Existence of attribute `DiagnosticTestRoutineIdentifier.requestDataSize`

Imposition time: IT_Dext

[For each `DiagnosticTestRoutineIdentifier`, attribute `requestDataSize` shall exist.

]

[constr_1825] Existence of attribute `DiagnosticTestRoutineIdentifier.responseDataSize`

Imposition time: IT_Dext

[For each `DiagnosticTestRoutineIdentifier`, attribute `responseDataSize` shall exist.

]

[constr_1826] Existence of reference `DiagnosticRequestVehicleInfo.infoType`

Imposition time: IT_Dext

[For each `DiagnosticRequestVehicleInfo`, the reference to `DiagnosticParameterIdentifier` in the role `infoType` shall exist.

]

[constr_1827] Existence of attribute `DiagnosticInfoType.id`

Imposition time: IT_Dext

[For each `DiagnosticInfoType`, attribute `id` shall exist.

]

[constr_1828] Existence of referenced from `DiagnosticServiceDataMapping`*Imposition time:* IT_Dext[For each `DiagnosticServiceDataMapping`, the following references shall exist:

- Reference to a `DiagnosticServiceMappingDiagTarget`, i.e. one of
 - Reference to `DiagnosticDataElement` in the role `diagnosticDataElement`
 - Reference to `DiagnosticParameterIdent` in the role `diagnosticParameter`
 - Reference to `DiagnosticParameterElement` in the roles
 - * `contextElement` (optional)
 - * `targetElement`from within `parameterElementAccess`
- Reference to `DataPrototype` in the role `mappedDataElement`

]

[constr_1829] Existence of reference `DiagnosticConnectedIndicator.indicator`*Imposition time:* IT_Dext[For each `DiagnosticConnectedIndicator`, the reference to `DiagnosticIndicator` in the role `indicator` shall exist.

]

[constr_1830] Existence of `DiagnosticTroubleCodeGroup.groupNumber`*Imposition time:* IT_Dext[For each `DiagnosticTroubleCodeGroup`, attribute `groupNumber` shall exist.

]

[constr_1831] Existence of `DiagnosticTroubleCodeProps.priority`*Imposition time:* IT_Dext[For each `DiagnosticTroubleCodeProps`, attribute `priority` shall exist.

]

[constr_1832] Existence of `DiagnosticExtendedDataRecord.recordNumber`*Imposition time:* IT_Dext

[For each `DiagnosticExtendedDataRecord`, attribute `recordNumber` shall exist.
]

[constr_1833] Existence of `DiagnosticFreezeFrame.trigger`*Imposition time:* IT_Dext

[For each `DiagnosticFreezeFrame`, attribute `trigger` shall exist.
]

[constr_1834] Existence of `DiagnosticCondition.initValue`*Imposition time:* IT_Dext

[For each `DiagnosticCondition`, attribute `initValue` shall exist.
]

[constr_1835] Existence of `DiagEventDebounceCounterBased.counterDecrementStepSize`*Imposition time:* IT_Dext

[For each `DiagEventDebounceCounterBased`, attribute `counterDecrementStepSize` shall Existence.
]

[constr_1836] Existence of `DiagEventDebounceCounterBased.counterIncrementStepSize`*Imposition time:* IT_Dext

[For each `DiagEventDebounceCounterBased`, attribute `counterIncrementStepSize` shall exist.
]

[constr_1837] Existence of `DiagEventDebounceCounterBased.counterFailedThreshold`*Imposition time:* IT_Dext

[For each `DiagEventDebounceCounterBased`, attribute `counterFailedThreshold` shall exist.
]

[constr_1838] Existence of `DiagEventDebounceCounterBased.counterPassedThreshold`*Imposition time:* IT_Dext

```
[For each DiagEventDebounceCounterBased, attribute counterPassedThreshold shall exist.
```

]

[constr_1839] Existence of attribute `DiagEventDebounceTimeBased.timeFailedThreshold`*Imposition time:* IT_Dext

```
[For each DiagEventDebounceTimeBased, attribute timeFailedThreshold shall exist.
```

]

[constr_1840] Existence of attribute `DiagEventDebounceTimeBased.timePassedThreshold`*Imposition time:* IT_Dext

```
[For each DiagEventDebounceTimeBased, attribute timePassedThreshold shall exist.
```

]

[constr_1841] Existence of `DiagnosticEnableConditionGroup.enableCondition`*Imposition time:* IT_Dext

```
[For each DiagnosticEnableConditionGroup, attribute enableCondition shall exist.
```

]

[constr_1842] Existence of `DiagnosticStorageConditionGroup.storageCondition`*Imposition time:* IT_Dext

```
[For each DiagnosticStorageConditionGroup, attribute storageCondition shall exist.
```

]

[constr_1843] Existence of reference `DiagnosticEventPortMapping.diagnosticEvent`*Imposition time:* IT_Dext

[For each `DiagnosticEventPortMapping`, the reference to `DiagnosticEvent` in the role `diagnosticEvent` shall exist.

]

[constr_1844] Existence of reference `DiagnosticOperationCyclePortMapping.operationCycle`*Imposition time:* IT_Dext

[For each `DiagnosticOperationCyclePortMapping`, the reference to `DiagnosticOperationCycle` in the role `operationCycle` shall exist.

]

[constr_1845] Existence of reference `DiagnosticEnableConditionPortMapping.enableCondition`*Imposition time:* IT_Dext

[For each `DiagnosticEnableConditionPortMapping`, the reference to `DiagnosticEnableCondition` in the role `enableCondition` shall exist.

]

[constr_1846] Existence of reference `DiagnosticStorageConditionPortMapping.diagnosticStorageCondition`*Imposition time:* IT_Dext

[For each `DiagnosticStorageConditionPortMapping`, the reference to `DiagnosticStorageCondition` in the role `diagnosticStorageCondition` shall exist.

]

[constr_1847] Existence of reference `DiagnosticDemProvidedDataMapping.dataElement`*Imposition time:* IT_Dext

[For each `DiagnosticDemProvidedDataMapping`, the reference to `DiagnosticDataElement` in the role `dataElement` shall exist.

]

[constr_1848] Existence of attribute `DiagnosticAging.agingCycle`*Imposition time:* IT_Dext[For each `DiagnosticAging`, attribute `agingCycle` shall exist.

]

[constr_1849] Existence of attribute `DiagnosticAging.threshold`*Imposition time:* IT_Dext[For each `DiagnosticAging`, attribute `threshold` shall exist.

]

[constr_1850] Existence of aggregation `DiagnosticTestResult.testIdentifier`*Imposition time:* IT_Dext[For each `DiagnosticTestResult`, the aggregation of meta-class `DiagnosticTestIdentifier` in the role `testIdentifier` shall exist.

]

[constr_1851] Existence of reference `DiagnosticTestResult.monitoredIdentifier`*Imposition time:* IT_Dext[For each `DiagnosticTestResult`, the reference to meta-class `DiagnosticTestIdentifier` in the role `monitoredIdentifier` shall exist.

]

[constr_1852] Existence of attribute `DiagnosticEcuInstanceProps.obdSupport`*Imposition time:* IT_Dext[For each `DiagnosticEcuInstanceProps`, attribute `obdSupport` shall exist.

]

[constr_1853] Existence of attribute `DiagnosticIumprGroup.iumprGroupIdentifier`*Imposition time:* IT_Dext[For each `DiagnosticIumprGroup`, attribute `iumprGroupIdentifier` shall exist.

]

[constr_1854] Existence of attribute `DiagnosticIumprGroupIdentifier.groupId`*Imposition time:* IT_Dext

[For each `DiagnosticIumprGroupIdentifier`, attribute `groupId` shall exist.
]

[constr_1855] Existence of attribute `DiagnosticFunctionIdentifierInhibit.inhibitionMask`*Imposition time:* IT_Dext

[For each `DiagnosticFunctionIdentifierInhibit`, attribute `inhibitionMask` shall exist.
]

[constr_1856] Existence of attribute `DiagnosticJ1939Spn.spn`*Imposition time:* IT_Dext

[For each `DiagnosticJ1939Spn`, attribute `spn` shall exist.
]

[constr_1857] Existence of the reference `DiagnosticEventToTroubleCodeJ1939Mapping.diagnosticEvent`*Imposition time:* IT_Dext

[For each `DiagnosticEventToTroubleCodeJ1939Mapping`, reference `diagnosticEvent` shall exist.
]

[constr_1858] Existence of the attribute `DiagnosticEventToTroubleCodeJ1939Mapping.troubleCodeJ1939`*Imposition time:* IT_Dext

[For each `DiagnosticEventToTroubleCodeJ1939Mapping`, attribute `troubleCodeJ1939` shall exist.
]

[constr_1859] Usage of `DiagnosticRecordTriggerEnum.testFailedThisOperationCycle`

Imposition time: IT_Dext

[The enumeration value `DiagnosticRecordTriggerEnum.testFailedThisOperationCycle` shall only be used in the context of meta-class `DiagnosticFreezeFrame`.

]

[constr_10024] Existence of reference in the role `DiagnosticSecurityEventReportingModeMapping.dataElement`

Status: DRAFT

Imposition time: IT_Dext

[For each `DiagnosticSecurityEventReportingModeMapping`, the reference to `DiagnosticDataElement` in the role `dataElement` shall exist.

]

[constr_10025] Existence of reference in the role `DiagnosticSecurityEventReportingModeMapping.securityEvent`

Status: DRAFT

Imposition time: IT_Dext

[For each `DiagnosticSecurityEventReportingModeMapping`, the reference to `SecurityEventContextProps` in the role `securityEvent` shall exist.

]

[constr_10026] Existence of reference in the role `DiagnosticEventToSecurityEventMapping.diagnosticEvent`

Status: DRAFT

Imposition time: IT_Dext

[For each `DiagnosticEventToSecurityEventMapping`, the reference to `DiagnosticEvent` in the role `diagnosticEvent` shall exist.

]

[constr_10027] Existence of reference in the role `DiagnosticEventToSecurityEventMapping.securityEventProps`

Status: DRAFT

Imposition time: IT_Dext

[For each `DiagnosticEventToSecurityEventMapping`, the reference to `SecurityEventContextProps` in the role `securityEventProps` shall exist.

]

[constr_10038] Restriction for the usage of `DiagnosticAccessPermission.authenticationEnabled`

Imposition time: IT_Dext

[Attribute `DiagnosticAccessPermission.authenticationEnabled` shall not exist if the `DiagnosticAccessPermission` is referenced from

- `DiagnosticRequestCurrentPowertrainData`
- `DiagnosticRequestPowertrainFreezeFrameData`
- `DiagnosticRequestEmissionRelatedDTC`
- `DiagnosticClearResetEmissionRelatedInfo`
- `DiagnosticRequestOnBoardMonitoringTestResults`
- `DiagnosticRequestControlOfOnBoardDevice`
- `DiagnosticRequestVehicleInfo`
- `DiagnosticRequestEmissionRelatedDTCPermanentStatus`
- sub-classes of `DiagnosticAuthentication`

]

[constr_10042] Existence of attribute `DiagnosticCommonProps.defaultEndianness`

Imposition time: IT_Dext

[One of the following conditions shall be fulfilled:

- `DiagnosticCommonProps.defaultEndianness` exists.
- The attribute `DiagnosticParameter.dataElement.swDataDefProps.baseType.baseTypeDefinition.baseTypeEncoding` exist for **all** `DiagnosticParameters` defined in the context of the `DiagnosticContributionSet`.

]

[constr_10043] Existence of attribute `DiagnosticCommonProps.resetConfirmedBitOnOverflow`

Imposition time: IT_Dext

[Attribute `DiagnosticCommonProps.resetConfirmedBitOnOverflow` shall exist.

]

[constr_10044] Existence of attribute `DiagnosticCommonProps.occurrenceCounterProcessing`

Imposition time: IT_Dext

[If, in the context of a `DiagnosticContributionSet`, a `DiagnosticDemProvidedDataMapping` exists where attribute `DiagnosticDemProvidedDataMapping.dataProvider` is set to the value `DEM_OCCCTR`, then attribute `DiagnosticCommonProps.occurrenceCounterProcessing` shall exist.

]

[constr_10045] Existence of attribute `DiagnosticSecurityAccessClass.securityDelayTimeOnBoot`

Imposition time: IT_Dext

[Attribute `DiagnosticSecurityAccessClass.securityDelayTimeOnBoot` shall exist.

]

[constr_10084] Existence of `DiagnosticIumprToFunctionIdentifierMapping.iumpr`

Imposition time: IT_Dext

[For all `DiagnosticIumprToFunctionIdentifierMapping`, the reference in the role `iumpr` shall exist.

]

[constr_10085] Existence of `DiagnosticIumprToFunctionIdentifierMapping.functionIdentifier`

Imposition time: IT_Dext

[For all `DiagnosticIumprToFunctionIdentifierMapping`, the reference in the role `functionIdentifier` shall exist.

]

[constr_10088] Relation between event and DTC without event combination

Imposition time: IT_Dext

[If attribute `DiagnosticCommonProps.typeOfEventCombinationSupported` is not configured, then all `DiagnosticTroubleCodeUds` that refer to a `DiagnosticTroubleCodeProps` in the role `troubleCodeProps` that in turn refers to a `DiagnosticMemoryDestination` in the role `diagnosticMemory` shall only be referenced by at most one `DiagnosticEventToTroubleCodeUdsMapping`.

]

[constr_10089] Existence of attribute `DiagnosticCommonProps.eventCombinationReportingBehavior`

Imposition time: IT_Dext

[Attribute `DiagnosticCommonProps.eventCombinationReportingBehavior` is always optional and shall be set to the value `DiagnosticEventCombinationReportingBehaviorEnum.reportingInChronologicalOrderOldestFirst` only if attribute `DiagnosticCommonProps.typeOfEventCombinationSupported` is set to the value `DiagnosticEventCombinationBehaviorEnum.eventCombinationOnRetrieval`.

If it is missing, then the reporting order is not specified.

]

[constr_10091] Mandatory subfunction of diagnostic service `Authentication`

Imposition time: IT_Dext

[If the diagnostic service `Authentication` is supported, then the following subfunctions shall be configured:

- De-authentication, formalized by meta-class `DiagnosticDeAuthentication`.
- Proof of ownership, formalized by meta-class `DiagnosticProofOfOwnership`.
- Authentication configuration, formalized by meta-class `DiagnosticAuthenticationConfiguration`.
- One of
 - Verify certificate unidirectional, formalized by meta-class `DiagnosticVerifyCertificateUnidirectional`.
 - Verify certificate bidirectional, formalized by meta-class `DiagnosticVerifyCertificateBidirectional`.

]

[constr_10100] Existence of `DiagnosticRoutineControl.routine`

Imposition time: IT_Dext

[For each `DiagnosticRoutineControl`, the attribute `routine` shall exist.

]

[constr_10115] Existence of attributes of `DiagnosticEnvDataElementCondition` if the reference in the role `dataPrototype` exists

Imposition time: IT_Dext

[If the reference in the role `DiagnosticEnvDataElementCondition.dataPrototype` exists, then

- the aggregation in the role `compareValue` shall exist and
- the aggregation in the role `swDataDefProps` shall not exist.

]

[constr_10116] Existence of attributes of `DiagnosticEnvDataElementCondition` if the reference in the role `dataPrototype` does not exist

Imposition time: IT_Dext

[If the reference in the role `DiagnosticEnvDataElementCondition.dataPrototype` does **not** exist, then the aggregations in the role

- `compareValue` and
- `swDataDefProps`

shall exist.

]

[constr_10117] Existence of attributes of `DiagnosticEnvDataElementCondition.swDataDefProps`

Imposition time: IT_Dext

[

Attribute of <code>SwDataDefProps</code>	Attribute Existence
<code>baseType</code>	1
<code>compuMethod</code>	0..1
<code>dataConstr</code>	0..1

]

[constr_10122] Existence of attribute `DiagnosticComControlSubNodeChannel.subNodeChannel`

Imposition time: IT_Dext

[Attribute `DiagnosticComControlSubNodeChannel.subNodeChannel` shall only exist if the value of `DiagnosticComControl.category` is set to either

- `ENABLE_RX_AND_DISABLE_TX_WITH_ENHANCED_ADDRESS_INFORMATION`
or

- ENABLE_RX_AND_TX_WITH_ENHANCED_ADDRESS_INFORMATION.

]

[constr_10364] Usage of [DiagnosticRecordTriggerEnum.testPassed](#)

Imposition time: IT_Dext

[The enumeration value [DiagnosticRecordTriggerEnum.testPassed](#) shall only be used in context of [DiagnosticExtendedDataRecord.trigger](#).

]

[constr_10368] Restriction regarding the reference [DiagnosticDataIdentifierSet.dataIdentifier](#)

Imposition time: IT_Dext

[A [DiagnosticDataIdentifier](#) that is referenced in the role [DiagnosticDataIdentifierSet.dataIdentifier](#) shall not aggregate in the role [dataElement](#) a [DiagnosticParameter](#) that aggregates in the role [ident](#) a [DiagnosticParameterIdent](#) that in turn aggregates in the role [subElement](#) a [DiagnosticParameterElement](#).

]

[constr_10369] Existence of attributes of [DiagnosticParameterElement](#) depending on the value of attribute [category](#)

Imposition time: IT_Dext

[

Value of category	Description	array-Size	subElement	dataElement
LEAF	The DiagnosticParameterElement represents a "leaf" element of a nested structure.	No	No	Yes
ARRAY	The DiagnosticParameterElement represents an array, i.e references to this DiagnosticParameterElement shall define a value for the attribute index . Arrays of "primitive" types are defined in the context of the DiagnosticDataElement	Yes	Yes, if dataElement does not exist	Yes, if subElement does not exist
STRUCTURE	The DiagnosticParameterElement represents a structure with one or more elements.	No	Yes	No

]

[constr_10370] Restriction regarding the role [DiagnosticParameterIdentifier.dataElement](#)

Imposition time: IT_Dext

[A [DiagnosticParameter](#) that is aggregated by a [DiagnosticParameterIdentifier](#) in the role [dataElement](#) shall not aggregate in the role [ident](#) a [Diagnos-](#)

`DiagnosticParameterIdent` that in turn aggregates in the role `subElement` a `DiagnosticParameterElement`.

]

[constr_10371] **DiagnosticDataElements** owned by a **DiagnosticExtendedDataRecord**

Imposition time: IT_Dext

[Within the context of `DiagnosticExtendedDataRecord`, all aggregated `DiagnosticParameter` in the role `recordElement` shall not aggregate any `DiagnosticParameter` which in turn aggregates (via the aggregation of `DiagnosticParameterIdent`) a `DiagnosticParameterElement`.

In addition, gaps between individual elements (defined by the begin of an individual `DiagnosticDataElement`, as indicated by `DiagnosticParameter.bitOffset`, and the length of the aggregated `DiagnosticDataElement`) shall **not** exist.

Any individual `DiagnosticDataElement` contained (via the aggregation of `DiagnosticParameter` in the role `recordElement`) in the `DiagnosticExtendedDataRecord` shall satisfy **one of the following conditions**:

- The `DiagnosticDataElement` does **not** define the attribute `maxNumberOfElements` at all.
- The modeling of attribute `DiagnosticDataElement.maxNumberOfElements` shall follow the description in [TPS_DEXT_01001].

]

[constr_10412] **Existence of attribute `DiagnosticTestIdentifier.id`**

Imposition time: IT_Dext

[For each `DiagnosticTestIdentifier`, attribute `id` shall exist.

]

[constr_10413] **Existence of attribute `DiagnosticTestIdentifier.uasId`**

Imposition time: IT_Dext

[For each `DiagnosticTestIdentifier`, attribute `uasId` shall exist.

]

[constr_10414] Existence of attribute `DiagnosticMeasurementIdentifier.obdMid`*Imposition time:* IT_Dext

[For each `DiagnosticMeasurementIdentifier`, attribute `obdMid` shall exist.
]

[constr_10418] Existence of attribute `DiagnosticDebounceAlgorithmProps.debounceAlgorithm`*Imposition time:* IT_Dext

[For each `DiagnosticDebounceAlgorithmProps`, attribute `debounceAlgorithm` shall exist.
]

[constr_10419] Existence of the attribute `DiagnosticCommonProps.resetPendingBitOnOverflow`*Imposition time:* IT_Dext

[Attribute `DiagnosticCommonProps.resetPendingBitOnOverflow` shall exist.
]

[constr_10421] Existence of attribute `DiagnosticMemoryDestination.dtcStatusAvailabilityMask`*Imposition time:* IT_Dext

[For each `DiagnosticMemoryDestination`, attribute `dtcStatusAvailabilityMask` shall exist.
]

[constr_10422] Existence of attribute `DiagnosticMemoryDestination.eventDisplacementStrategy`*Imposition time:* IT_Dext

[For each `DiagnosticMemoryDestination`, attribute `eventDisplacementStrategy` shall exist.
]

[constr_10423] Existence of attribute `DiagnosticMemoryDestination.maxNumberOfEventEntries`

Imposition time: IT_Dext

[For each `DiagnosticMemoryDestination`, attribute `maxNumberOfEventEntries` shall exist.

]

[constr_10440] Restriction for the minimum value of attribute `DiagnosticSessionControlClass.s3ServerTimeout`

Imposition time: IT_Dext

[The value of attribute `DiagnosticSessionControlClass.s3ServerTimeout` shall be **greater than or equal to 5.0**.

]

[constr_10522] OBD trouble code shall only be placed in primary fault memory

Imposition time: IT_Dext

[If a `DiagnosticTroubleCodeUds` that is referenced in the role `DiagnosticTroubleCodeUdsToTroubleCodeObdMapping.troubleCodeUds` in turn references a `DiagnosticTroubleCodeProps` in the role `troubleCodeProps`, and if the `DiagnosticTroubleCodeProps` refers to a `DiagnosticMemoryDestination` in the role `diagnosticMemory`, then the referenced `diagnosticMemory` shall be a `DiagnosticMemoryDestinationPrimary`.

]

[constr_10523] Existence of role `DiagnosticTroubleCodeUdsToTroubleCodeObdMapping.troubleCodeUds`

Imposition time: IT_Dext

[For each `DiagnosticTroubleCodeUdsToTroubleCodeObdMapping`, the reference in the role `troubleCodeUds` shall exist.

]

[constr_10524] Existence of role `DiagnosticTroubleCodeUdsToTroubleCodeObdMapping.troubleCodeObd`

Imposition time: IT_Dext

[For each `DiagnosticTroubleCodeUdsToTroubleCodeObdMapping`, the reference in the role `troubleCodeObd` shall exist.

]

[constr_10545] Existence of `DiagnosticParameterIdentifier.dataElement`.

Imposition time: IT_Dext

[For each `DiagnosticParameterIdentifier`, at least one aggregation of `DiagnosticParameter` in the role `DiagnosticParameterIdentifier.dataElement` shall exist.

]

[constr_10573] Existence of attribute `DiagnosticServiceTable.diagnosticServiceInstance`

Imposition time: IT_Dext

[For each `DiagnosticServiceTable`, attribute `diagnosticServiceInstance` shall exist.

]

[constr_10577] Existence of `DiagnosticResponseOnEventClass.storeEventEnabled`

Imposition time: IT_Dext

[For each `DiagnosticResponseOnEventClass`, the attribute `storeEventEnabled` shall exist.

]

2.3 CP_TPS_ECUConfiguration

[constr_3022] `EcucModuleDef` category restriction [The category definition shall be restricted to exactly the two defined ones:

- `VENDOR_SPECIFIC_MODULE_DEFINITION`
- `STANDARDIZED_MODULE_DEFINITION`

]

[constr_3023] Usage of `apiServicePrefix` [The attribute `apiServicePrefix` is mandatory for VSMDs derived from the CDD and Xfrm StMD. The attribute shall not be provided for VSMDs derived from any other StMDs.

]

[constr_3091] Multiplicity of `valueConfigClass` [The multiplicity of the attribute `EcucCommonAttributes.valueConfigClass` shall not exceed 3.

]

[constr_3092] Usage of `configVariant` and `configClass` attributes [`configVariant` and `configClass` shall always exist as a pair for each existing `EcucAbstractConfigurationClass` (`EcucValueConfigurationClass` or `EcucMultiplicityConfigurationClass` depending on the context).

]

[constr_3119] Necessary content of `EcucDestinationUriDefs` that are referenced by an `EcucContainerDef` [The `EcucDestinationUriDef` that is referenced by the `EcucContainerDef` in the role `destinationUri` shall define at least the analogous set of `containers`, `parameters` and `references` defined by the `EcucDestinationUriPolicy` of the `EcucDestinationUriDef` that is referenced by the `EcucUriReferenceDef` that targets the `EcucContainerDef`.

]

[constr_3120] Applicable attributes when `destinationUriNestingContract` is set to `targetContainer` [If the `destinationUriNestingContract` is set to `targetContainer`, the attributes `parameter` and `reference` shall not exist.

]

[constr_3200] Restriction on values of `EcucDefinitionElement.relatedTraceItem` in the VSMD [The value of `EcucDefinitionElement.relatedTraceItem` in the VSMD shall never start with 'ECUC_'.

]

[constr_3217] Symbolic name reference shall point only to containers with a symbolic name value defined [If an `EcucReferenceValue` exists that refers in the role `definition` to an `EcucAbstractInternalReferenceDef` with the attribute `requiresSymbolicNameValue` set to true, then the `EcucContainerValue` that is the target of the reference shall refer to an `EcucParamConfContainerDef` in the role `definition` that contains a definition of an `EcucParameterDef` where the attribute `symbolicNameValue` exists and is set to true. The `EcucContainerValue` shall define an `EcucParameterValue` that refers to an `EcucParameterDef` where the attribute `symbolicNameValue` exists and is set to true.

]

[constr_3233] `EcucModuleDef` that relies on `EcucCommonAttributes` with `valueConfigClass` set to `Link/PostBuild` of another `EcucModuleDef` [If one

`EcucModuleDef` relies on the `EcucCommonAttributes` (parameters and references) with `valueConfigClass.configClass` set to `Link/PostBuild` of another `EcucModuleDef`, the values of these `EcucCommonAttributes` can only be changed at `Link/PostBuild` time if the corresponding `EcucModuleConfigurationValues` of the using `EcucModuleDef` has the `implementationConfigVariant` set to `VariantLinkTime/VariantPostBuild`, respectively.

}

[constr_3234] `EcucModuleDef` that relies on `EcucCommonAttributes` with `multiplicityConfigClass` set to `Link/PostBuild` of another `EcucModuleDef` [If one `EcucModuleDef` relies on the `EcucCommonAttributes` (parameters and references) with `multiplicityConfigClass.configClass` set to `Link/PostBuild` of another `EcucModuleDef`, the number of instances of these `EcucCommonAttributes` can only be changed at `Link/PostBuild` time if the corresponding `EcucModuleConfigurationValues` of the using `EcucModuleDef` has the `implementationConfigVariant` set to `VariantLinkTime/VariantPostBuild`, respectively.

}

[constr_3235] `EcucModuleDef` that relies on `EcucContainerDefs` with `multiplicityConfigClass` set to `Link/PostBuild` of another `EcucModuleDef` [If one `EcucModuleDef` relies on the `EcucContainerDefs` with `multiplicityConfigClass.configClass` set to `Link/PostBuild` of another `EcucModuleDef`, the number of instances of these `EcucContainerDefs` can only be changed at `Link/PostBuild` time if the corresponding `EcucModuleConfigurationValues` of the using `EcucModuleDef` has the `implementationConfigVariant` set to `VariantLinkTime/VariantPostBuild`, respectively.

}

[constr_3236] `EcucModuleDef` that relies on `EcucCommonAttributes` with `postBuildVariantValue` set to true of another `EcucModuleDef` [If one `EcucModuleDef` relies on the `EcucCommonAttributes` (parameters and references) with `postBuildVariantValue` set to true of another `EcucModuleDef`, the values of these `EcucCommonAttributes` can only differ in different post-build variants if the implementation of the using `EcucModuleDef` supports post-build variations.

}

[constr_3237] `EcucModuleDef` that relies on `EcucCommonAttributes` with `postBuildVariantMultiplicity` set to true of another `EcucModuleDef` [If one `EcucModuleDef` relies on the `EcucCommonAttributes` (parameters and references) with `postBuildVariantMultiplicity` set to true of another `EcucModuleDef`, the number of instances of these `EcucCommonAttributes` can only differ

in different post-build variants if the implementation of the using `EcucModuleDef` supports post-build variations.

]

[constr_3238] `EcucModuleDef` that relies on `EcucContainerDef` with `postBuildVariantMultiplicity` set to true of another `EcucModuleDef` [If one `EcucModuleDef` relies on the `EcucContainerDefs` with `postBuildVariantMultiplicity` set to true of another `EcucModuleDef`, the number of instances of these `EcucContainerDefs` can only differ in different post-build variants if the implementation of the using `EcucModuleDef` supports post-build variations.

]

[constr_3307] ShortNames of `PredefinedVariants` referenced by `EcucPostBuildVariantRefs` [All `PredefinedVariants` that are referenced by `EcucPostBuildVariantRefs` shall have different `shortNames`.

]

[constr_3449] Impact of `postBuildVariantUsed` value set to FALSE [If the value of the `EcucModuleConfigurationValues.postBuildVariantUsed` is set to FALSE or if it is not defined, it is not possible to add a post-build variant at post-build configuration time.

]

[constr_3450] `postBuildVariantUsed` value in case of post build `VariationPoints` [If the configuration values of a BSW module contain at least one post build `VariationPoint`, the value of the `postBuildVariantUsed` for the `EcucModuleConfigurationValues` shall be set to TRUE.

]

[constr_3451] `EcucModuleConfigurationValues.postBuildVariantUsed` value setting restriction in case `postBuildVariantSupport` is set to TRUE [If `EcucModuleDef.postBuildVariantSupport` is set to TRUE, then `EcucModuleConfigurationValues.postBuildVariantUsed` can be either TRUE or FALSE.

]

[constr_3452] `EcucModuleConfigurationValues.postBuildVariantUsed` value setting restriction in case `postBuildVariantSupport` is set to FALSE [If `EcucModuleDef.postBuildVariantSupport` is set to FALSE, then `EcucModuleConfigurationValues.postBuildVariantUsed` shall be FALSE.

]

[constr_3509] **Applicability of `scope` attribute** [The usage of the attribute `scope` is prohibited for `EcucModuleDef` and for sub-classes of `EcucContainerDef` (i.e. `EcucChoiceContainerDef` and `EcucParamConfContainerDef`).

]

[constr_3570] **`EcucDefinitionElement.lowerMultiplicity` always required** [The attribute `EcucDefinitionElement.lowerMultiplicity` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3571] **`EcucCommonAttributes.origin` always required** [The attribute `EcucCommonAttributes.origin` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3572] **`EcucParameterDef.symbolicNameValue` always required** [The attribute `EcucParameterDef.symbolicNameValue` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3573] **`EcucAbstractConfigurationClass.configClass` always required** [The attribute `EcucAbstractConfigurationClass.configClass` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3574] **`EcucAbstractConfigurationClass.configVariant` always required** [The attribute `EcucAbstractConfigurationClass.configVariant` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3575] **`EcucEnumerationLiteralDef.origin` always required** [The attribute `EcucEnumerationLiteralDef.origin` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3576] **`EcucInstanceReferenceDef.destinationContext` always required** [The attribute `EcucInstanceReferenceDef.destinationContext` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3577] **EcucInstanceReferenceDef.destinationType** always required [The attribute `EcucInstanceReferenceDef.destinationType` shall always be defined **when the ECU Configuration Parameter definition is complete.**

]

[constr_3578] **EcucForeignReferenceDef.destinationType** always required [The attribute `EcucForeignReferenceDef.destinationType` shall always be defined **when the ECU Configuration Parameter definition is complete.**

]

[constr_3579] **EcucReferenceDef.destination** always required [The attribute `EcucReferenceDef.destination` shall always be defined **when the ECU Configuration Parameter definition is complete.**

]

[constr_3580] **EcucUriReferenceDef.destinationUri** always required [The attribute `EcucUriReferenceDef.destinationUri` shall always be defined **when the ECU Configuration Parameter definition is complete.**

]

[constr_3581] **EcucDestinationUriDefSet.destinationUriDef** always required [The attribute `EcucDestinationUriDefSet.destinationUriDef` shall always be defined **when the ECU Configuration Parameter definition is complete.**

]

[constr_3582] **EcucDestinationUriDef.destinationUriPolicy** always required [The attribute `EcucDestinationUriDef.destinationUriPolicy` shall always be defined **when the ECU Configuration Parameter definition is complete.**

]

[constr_3583] **EcucDestinationUriPolicy.destinationUriNestingContract** always required [The attribute `EcucDestinationUriPolicy.destinationUriNestingContract` shall always be defined **when the ECU Configuration Parameter definition is complete.**

]

[constr_3584] **EcucQuery.ecucQueryExpression** always required [The attribute `EcucQuery.ecucQueryExpression` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3585] **EcucConditionFormula.ecucQuery** always required [The attribute `EcucConditionFormula.ecucQuery` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3586] **EcucConditionFormula.ecucQueryString** always required [The attribute `EcucConditionFormula.ecucQueryString` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3587] **EcucValidationCondition.validationFormula** always required [The attribute `EcucValidationCondition.validationFormula` shall always be defined **when the ECU Configuration Parameter definition is complete**.

]

[constr_3588] **EcucValueCollection.ecuExtract** always required [The attribute `EcucValueCollection.ecuExtract` shall always be defined **at code generation time**.

]

[constr_3589] **EcucModuleConfigurationValues.ecucDefEdition** always required [The attribute `EcucModuleConfigurationValues.ecucDefEdition` shall always be defined **at code generation time**.

]

[constr_3590] **EcucModuleConfigurationValues.implementationConfigVariant** always required [The attribute `EcucModuleConfigurationValues.implementationConfigVariant` shall always be defined **at code generation time**.

]

[constr_3591] **EcucModuleConfigurationValues.definition** always required [The attribute `EcucModuleConfigurationValues.definition` shall always be defined **at code generation time**.

]

[constr_3592] **EcucContainerValue.definition** always required [The attribute `EcucContainerValue.definition` shall always be defined **at code generation time**.]

}

[constr_3593] **EcucParameterValue.definition** always required [The attribute `EcucParameterValue.definition` shall always be defined **at code generation time**.]

}

[constr_3594] **EcucNumericalParamValue.value** always required [The attribute `EcucNumericalParamValue.value` shall always be defined **at code generation time**.]

}

[constr_3595] **EcucTextualParamValue.value** always required [The attribute `EcucTextualParamValue.value` shall always be defined **at code generation time**.]

}

[constr_3596] **EcucAddInfoParamValue.value** always required [The attribute `EcucAddInfoParamValue.value` shall always be defined **at code generation time**.]

}

[constr_3597] **EcucAbstractReferenceValue.definition** always required [The attribute `EcucAbstractReferenceValue.definition` shall always be defined **at code generation time**.]

}

[constr_3598] **EcucInstanceReferenceValue.value** always required [The attribute `EcucInstanceReferenceValue.value` shall always be defined **at code generation time**.]

}

[constr_3599] **EcucReferenceValue.value** always required [The attribute `EcucReferenceValue.value` shall always be defined **at code generation time**.]

}

[constr_3793] Usage of KeepLocalPduBuffer

Status: DRAFT

⌈All Pdus that belong to the same Pdu flow shall have `KeepLocalPduBuffer` either set to `TRUE` or set to `FALSE`.

⌋

[constr_3794] Usage of PduBufferAlignment

Status: DRAFT

⌈All Pdus that belong to the same Pdu flow shall have `PduBufferAlignment` either set to `TRUE` or set to `FALSE`.

⌋

[constr_5015] Multiplicity of `multiplicityConfigClass` ⌈The multiplicity of the attribute `EcucCommonAttributes.multiplicityConfigClass` shall not exceed 3.

⌋

[constr_5059] Ordering of `MetaDataItems` of a `MetaDataType` ⌈The `MetaDataItems` of a `MetaDataType` shall be ordered according to their `MetaDataItemLength`. `MetaDataItems` with greater `MetaDataItemLength` going first.

⌋

[constr_5108] `CddModuleId` range restriction ⌈The range of `CddModuleId` is restricted to the value 255 and to the range of values 2048..4095.

⌋

[constr_5325] Existence of `upperMultiplicityInfinite` and `upperMultiplicity` is mutually exclusive ⌈The existence of the elements `upperMultiplicityInfinite` and `upperMultiplicity` shall be mutually exclusive.

⌋

[constr_5342] `EcucDefinitionElement.upperMultiplicity` or `EcucDefinitionElement.upperMultiplicityInfinite` always required ⌈Exactly one of the attributes `EcucDefinitionElement.upperMultiplicity` or `EcucDefinitionElement.upperMultiplicityInfinite` shall always be defined **when the ECU Configuration Parameter definition is complete**.

⌋

[constr_5345] Restriction for a reference destination in case of multiple aggregated `EcucParamConfContainerDefs` [An `EcucReferenceDef` or `EcucChoiceReferenceDef` is not allowed to reference an `EcucParamConfContainerDef` as destination if

- this `EcucParamConfContainerDef` is aggregated by several `EcucParamConfContainerDefs` as `subContainer` and
- the `EcucParamConfContainerDef` structures in which the referenced `EcucParamConfContainerDef` is aggregated are different compared to the `EcucParamConfContainerDef` structure in which the `EcucReferenceDef` or `EcucChoiceReferenceDef` is located in.

]

[constr_5365] Origin information in parameter and reference definitions [Each instance of the subclass of `EcucCommonAttributes` or `EcucContainerDef` shall provide a value for the `origin` attribute and this attribute shall be either:

- 'AUTOSAR_ECUC' - in case that the parameter definition is standardized by AUTOSAR
- vendor specific value - in case that the parameter definition is vendor specific. For vendor specific origins no rules are defined by AUTOSAR and the vendor is free to choose the value (e.g. 'VendorXYZ_v1.3').

]

[constr_5500] Applicability of the `multiplicityConfigClass` attribute [The `multiplicityConfigClass` attribute is applicable only to `EcucContainerDefs` which have `upperMultiplicity` greater than `lowerMultiplicity`.

]

[constr_5502] Introduction of new `EcucParameterValues` of type `EcucFunctionNameDef` at post-build time [In case a new `EcucParameterValues` of type `EcucFunctionNameDef` (see [TPS_ECUC_02033]) is introduced at post-build time, it's value shall be one of the existing function names (e.g. callouts). This means that it is not allowed to introduce new functions at post-build time.

]

[constr_5504] Removing an instance of the `EcucContainerDef` at post-build time [Only instances of `EcucContainerDefs` with `multiplicityConfigClass.configClass` set to `PostBuild` in the `multiplicityConfigClass.configVariant VariantPostBuild` which are not referenced or are exclusively referenced by `EcucAbstractReferenceDefs` with `valueConfigClass.configClass` set to `PostBuild` in the `valueConfigClass.configVariant VariantPostBuild` and

have been introduced at post-build time (not part of the initial configuration before post-build updates) can be removed at post-build time.

]

[constr_5505] Configuration class of the elements of the `EcucQueryExpression`

[The elements of the `EcucQueryExpression` involved in one calculation formula shall have lower or equal configuration class (where `PreCompile` configuration class is considered to be the lowest and `PostBuild` the highest) with respect to the context element in which the calculation is performed (e.g. a `Link` configuration parameter can not calculate its value based on a `PostBuild` parameters value).

]

[constr_5506] Applicability of `postBuildVariantMultiplicity` attribute

[The `postBuildVariantMultiplicity` attribute of `EcucContainerDef` is applicable only to `EcucContainerDefs` which have `upperMultiplicity` greater than `lowerMultiplicity`.

]

[constr_5507] Value of `EcucContainerDef.postBuildVariantMultiplicity` if `postBuildVariantSupport` is set to false

[If `postBuildVariantSupport` is set to `false`, every `EcucContainerDef` in this `EcucModuleDef` with `upperMultiplicity` greater than `lowerMultiplicity` shall have its `postBuildVariantMultiplicity` attribute set to `false`.

]

[constr_5508] Applicability of `postBuildVariantMultiplicity` attribute

[The `postBuildVariantMultiplicity` attribute is applicable only to `EcucCommonAttributes` which have `upperMultiplicity` greater than `lowerMultiplicity`.

]

[constr_5509] Value of `postBuildVariantMultiplicity` if `postBuildVariantSupport` is set to false

[If `postBuildVariantSupport` is set to `false`, every `EcucCommonAttributes` in this `EcucModuleDef` with `upperMultiplicity` greater than `lowerMultiplicity` shall have its `postBuildVariantMultiplicity` attribute set to `false`.

]

[constr_5510] Value of `postBuildVariantValue` if `postBuildVariantSupport` is set to false

[If `postBuildVariantSupport` is set to `false`, every `Ecuc-`

`CommonAttributes` in this `EcucModuleDef` shall have its `postBuildVariantValue` attribute set to `false`.

}

[constr_5512] `postBuildVariantValue` attribute of `symbolicNameValue` parameters [The values of `EcucParameterDefs` with `symbolicNameValue` attribute set to `true` shall have their `postBuildVariantValue` set to `false`.

}

[constr_5514] Applicability of the `multiplicityConfigClass` attribute [The `multiplicityConfigClass` attribute is applicable only to `EcucCommonAttributes` which have `upperMultiplicity` greater than `lowerMultiplicity`.

}

[constr_5520] `valueConfigClass` attribute of `symbolicNameValue` parameters [The values of `EcucParameterDefs` with `symbolicNameValue` attribute set to `true` shall have their `valueConfigClass.configClass` set to `PreCompile` or `PublishedInformation` for all `valueConfigClass.configVariants`.

}

[constr_5521] `multiplicityConfigClass` attribute of `symbolicNameValue` parameters [The values of `EcucParameterDefs` with `symbolicNameValue` attribute set to `true` shall have their `multiplicityConfigClass.configClass` set to `PreCompile` for all `multiplicityConfigClass.configVariants`.

}

[constr_5522] `postBuildVariantMultiplicity` attribute of `symbolicNameValue` parameters [The values of `EcucParameterDefs` with `symbolicNameValue` attribute set to `true` shall have their `postBuildVariantMultiplicity` set to `false`.

}

[constr_5523] Allowed `configClasses` for paired `configVariants` [`PublishedInformation configClass` is supported by all `configVariants` where [TPS_ECUC_02071] applies. Additionally, `VariantPreCompile configVariant` supports `PreCompile configClass`, `VariantLinkTime configVariant` supports `PreCompile` and `Link configClasses`, and `VariantPostBuild configVariant` supports `PreCompile`, `Link` and `PostBuild configClasses`.

}

2.4 CP_TPS_ECUResourceTemplate

[constr_3500] category of `HwAttributeDef` shall not be extended [In contrast to the general rule that `category` can be extended by user-specific values it is **not allowed** to extend the meaning of the attribute `category` of meta-class `HwAttributeDef`

]

[constr_3511] `HwType` shall not have a reference to another `HwType` [A `HwType` (being a `HwDescriptionEntity`) shall not have a reference to another `HwType` in the role `hwType`. The definition of `HwTypes` is not hierarchical.

]

[constr_3512] No support of multiple instantiation [An essential constraint is that each `HwElement` can only be target of one `nestedElement` reference. This means that there is no concept of multiple instantiation of hardware elements. If the same hardware element shall be used several times (using the `nestedElement` reference) each occurrence has to have its own description. This is also true for nested elements of the referenced nested element.

]

[constr_3513] Scope of connections [Each hardware connection shall only connect features which both are in the hierarchical scope of the hardware element. The hierarchical scope encloses

- all features belonging to the hardware element containing the connection
- all features belonging to hardware elements which are referenced directly and indirectly in the `nestedElement` relation from the hardware element containing connection.

]

[constr_11001] Multiplicity of `HwAttributeValue.hwAttributeDef` [For each `HwAttributeValue` the reference in the role `hwAttributeDef` shall exist.

]

[constr_11002] Multiplicity of `HwElementConnector.hwElement` [For each `HwElementConnector` there shall exist exactly 2 references in the role `hwElement`.

]

[constr_11003] Multiplicity of `HwPinGroupConnector.hwPinGroup` [For each `HwPinGroupConnector` there shall exist exactly 2 references in the role `hwPinGroup`.

]

[constr_11004] Multiplicity of `HwPinConnector.hwPin` [For each `HwPinConnector` there shall exist exactly 2 references in the role `hwPin`.

]

[constr_11005] Multiplicity of `HwAttributeDef.isRequired` [For each `HwAttributeDef` the attribute `isRequired` shall exist.

]

2.5 CP_TPS_SoftwareComponentTemplate

[constr_1000] End-to-end protection is limited to sender/receiver communication

Status: OBSOLETE

Imposition time: IT_CpgExe

[A `VariableDataPrototype` referenced in the roles

- `EndToEndProtectionVariablePrototype.sender`
- `EndToEndProtectionVariablePrototype.receiver`

shall be aggregated in the role `dataElement` at a `SenderReceiverInterface`.

]

[constr_1004] Mapping of `ApplicationDataTypes` in the scope of single `AtomicSwComponentTypes`

Imposition time: IT_CpgExe

[In the scope of `AtomicSwComponentType.internalBehavior.dataTypeMapping`, each `ApplicationDataType` shall be mapped to exactly one `ImplementationDataType`.

]

[constr_1005] Compatibility of `ImplementationDataTypes` mapped to the same `ApplicationDataType`

Imposition time: IT_CpgExe

[It is required that `ImplementationDataTypes` which are taken for connecting corresponding elements of `PortInterfaces` and thus refer to compatible `ApplicationDataTypes` are also compatible among each other (so that RTE is able to cope with possible connections by converting the data accordingly).

[constr_1006] Applicable data categories, depending on specific model elements related to data definition properties

Imposition time: IT_RteGen

Category	Applicable to ...												Use Case				Description
	<code>ApplicationArrayType</code>	<code>ApplicationRecordDataType</code>	<code>ApplicationPrimitiveDataType</code>	<code>ApplicationRecordElement</code>	<code>ApplicationArrayElement</code>	<code>ApplicationValueSpecification</code>	<code>ApplicationRuleBasedValueSpecification</code>	<code>ImplementationDataType</code>	<code>ImplementationDataTypeElement</code>	<code>SwSystemconst</code>	<code>McDataInstance</code>	<code>Calibration</code>	<code>Measurement</code>	<code>Communication Port Interfaces</code>	<code>RTE + BSW</code>		
VALUE			x	x	x	x	x	x	x	x	x	x	x	x		Contains a single value.	
VAL_BLK		x	x	x	x	x				x	x		x			A value block defines values stored together within one calibration parameter object. It is similar to an value array but it stores the values by means of an axis instead (only important for calibration data handling).	
DATA_REFERENCE								x	x	x				x ⁴	x	Contains an address of another <code>DataPrototype</code> (whose type is given via <code>SwDataDefProps.swPointerTargetProps</code>).	
FUNCTION_REFERENCE								x	x	x					x	Contains an address of a function prototype (whose signature is given via <code>SwDataDefProps.swPointerTargetProps.functionPointerSignature</code>).	
TYPE_REFERENCE								x	x	x				x	x	The element is defined via reference to another data type (via <code>SwDataDefProps.implementationDataType</code>).	

⁴[constr_1295] applies!

[constr_1007] Allowed attributes of SwDataDefProps for Application-DataTypes

Imposition time: IT_CpgExe

[

Attributes of SwDataDefProps	Attribute Existence per ApplicationDataType.category												
	VALUE	VAL_BLK	STRUCTURE	ARRAY	STRING	BOOLEAN	COM_AXIS	RES_AXIS	CURVE	MAP	CUBOID	CUBE_4	CUBE_5
additionalNativeTypeQualifier													
annotation	*	*	*	*	*	*	*	*	*	*	*	*	*
baseType													
compuMethod	0..1	0..1				0..1			0..1	0..1	0..1	0..1	0..1
dataConstr.dataConstrRule.physConstrs	0..1	0..1		0..1		0..1			0..1	0..1	0..1	0..1	0..1
dataConstr.dataConstrRule.internalConstrs	d/c ⁵	d/c		d/c		d/c			d/c	d/c	d/c	d/c	d/c
displayFormat	0..1	0..1		0..1	0..1	0..1			0..1	0..1	0..1	0..1	0..1
displayPresentation	0..1	0..1		0..1			0..1	0..1	0..1	0..1	0..1	0..1	0..1
implementationDataType													
invalidValue	0..1				0..1								
stepSize	0..1	0..1		0..1			0..1	0..1	0..1	0..1	0..1	0..1	0..1
swAddrMethod	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swAlignment													
swBitRepresentation													
swCalibrationAccess	0..1	0..1	0..1	0..1	0..1	0..1	1	1	1	1	1	1	1
swCalprmAxisSet							1	1	1	1	1	1	1
swComparisonVariable													
swDataDependency													
swHostVariable													
swImplPolicy	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swIntendedResolution	0..1												
swInterpolationMethod	0..1						0..1	0..1	0..1	0..1	0..1	0..1	0..1
swIsVirtual													
swPointerTargetProps													
swRecordLayout	0..1	0..1 ⁶			0..1		1	1	1	1	1	1	1
swRefreshTiming	0..1	0..1			0..1	0..1							
swTextProps					1								
swValueBlockSize		1											
swValueBlockSizeMult		1											
unit	0..1	0..1							0..1	0..1	0..1	0..1	0..1
valueAxisDataType		0..1					0..1	0..1	0..1	0..1	0..1	0..1	0..1

]

⁵don't care

⁶This is required by [TPS_SWCT_01179].

[constr_1009] SwDataDefProps applicable to ImplementationDataTypes

Imposition time: IT_CpgExe

[

Attributes of SwDataDefProps	Root Element				Attribute Existence per Category						
	ImplementationDataType	ImplementationDataTypeElement	SwPointerTargetProps	SwServiceArg	VALUE	DATA_REFERENCE	FUNCTION_REFERENCE	TYPE_REFERENCE	STRUCTURE	UNION	ARRAY
additionalNativeTypeQualifier	x	x	x	x	0..1	0..1	0..1	0..1	0..1	0..1	0..1
annotation	x	x	x	x	*	*	*	*	*	*	*
baseType	x	x	x	x	1						
compuMethod	x	x	x	x	0..1			0..1			
dataConstr.dataConstrRule.physConstrs	x	x	x	x	d/c ⁷			d/c			d/c
dataConstr.dataConstrRule.internalConstrs	x	x	x	x	0..1			0..1			0..1
displayFormat	x	x			0..1				0..1	0..1	0..1
displayPresentation	x	x			0..1						0..1
implementationDataType	x	x	x	x				1			
invalidValue	x	x	x		0..1			0..1	0..1 ⁸		0..1 ⁹
stepSize	x	x			0..1						
swAddrMethod	x	x	x		0..1	0..1	0..1	0..1	0..1	0..1	0..1
swAlignment	x				0..1	0..1	0..1		0..1	0..1	0..1
swBitRepresentation											
swCalibrationAccess	x	x			0..1			0..1	0..1	0..1	0..1
swCalprmAxisSet											
swComparisonVariable											
swDataDependency											
swHostVariable											
swImplPolicy	x		x	x	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swIntendedResolution											
swInterpolationMethod											
swIsVirtual											
swPointerTargetProps	x	x	x	x		1	1				



⁷don't care

⁸There is a use case for the definition of an `invalidValue` for category `ARRAY` and therefore category `STRUCTURE` is also supported for the sake of symmetry.

⁹This represents an exception such that it would make sense to use an entire `ArrayValueSpecification` as the `invalidValue` because a string semantically is more than just a bunch of characters in a row.



Attributes of SwDataDefProps	Root Element				Attribute Existence per Category						
	ImplementationDataType	ImplementationDataTypeElement	SwPointerTargetProps	SwServiceArg	VALUE	DATA_REFERENCE	FUNCTION_REFERENCE	TYPE_REFERENCE	STRUCTURE	UNION	ARRAY
swPointerTargetProps .swDataDefProps	x	x	x	x		1					
swPointerTargetProps .functionPointerSignature	x	x	x	x			1				
swRecordLayout											
swRefreshTiming	x	x	x	x	0..1				0..1	0..1	0..1
swTextProps											
swValueBlockSize											
swValueBlockSizeMult											
unit											
valueAxisDataType											

]

[constr_1010] If nativeDeclaration does not exist

Imposition time: IT_CpgExe

[If `nativeDeclaration` does not exist in the `SwBaseType`, it is required that the `shortName` (e.g. "uint8") of the corresponding `ImplementationDataType` is equal to a name of one of the Platform or Standard Types predefined in AUTOSAR code.

]

[constr_1011] category of SwBaseType

Imposition time: IT_CpgExe

[For the attribute `SwBaseType.category` only the values `FIXED_LENGTH` and `VOID` are supported.

]

[constr_1012] Value of category is FIXED_LENGTH

Imposition time: IT_CpgExe

[If

- the value of the attribute `SwBaseType.category` is set to `FIXED_LENGTH` and

- the `SwBaseType` is **not** referenced in the role `ApplicationPrimitive-DataType.swDataDefProps.swTextProps.baseType`,

then the attribute `baseTypeSize` shall be filled with content.

]

[constr_1015] Prioritization of `SwDataDefProps`

Imposition time: IT_CpgExe

[

Attributes of <code>SwDataDefProps</code>	Usage For			Place of Setting										
	RTE	A2L	Other Usage	ApplicationDataType	ImplementationDataType	DataPrototype	InstantiationDataDefProps	ParameterAccess	SwServiceArg	FlatInstanceDescriptor	McDataInstance	SwSystemconst	PerInstanceMemory	ComSpec networkRepresentation
<code>additionalNativeTypeQualifier</code>	x		x		D	I			D		S			
<code>annotation</code>			x	D	A	A	A	A	D		A	D		A
<code>baseType</code>	x	x	x		D	I	I	I	D		S	M		D
<code>compuMethod</code>	x	x	x	D	AI	I	I		I	AI	S	D		D
<code>dataConstr</code>	x	x	x	D	C	D	D	I	D		S	D		
<code>displayFormat</code>		x		D	D	D	D	I	D		S	D		
<code>displayPresentation</code>	x	x	x	D	D	D	D				S			
<code>implementationDataType</code>	x		x		D	I	I	I	D					
<code>invalidValue</code>	x	x		D	D	I	I				S			D
<code>stepSize</code>		x		D	D	D	D	D		D	S			
<code>swAddrMethod</code>	x	x	x	D	D	D	D			D			D	
<code>swAlignment</code>	x		x		D	D	D							
<code>swBitRepresentation</code>		x	x								D			
<code>swCalibrationAccess</code>	x	x		D	D	D	D		D	D	S	D		
<code>swCalprmAxisSet</code>	x	x		D		I	I	I			S			
<code>swCalprmAxisSet.swCalprmAxis/SwAxisGrouped.swCalprmRef</code>		x					D	D			S			
<code>swCalprmAxisSet.swCalprmAxis/SwAxisIndividual.swVariableRef</code>		x					D	D			S			
<code>swCalprmAxisSet.swCalprmAxis/SwAxisGrouped.sharedAxisType</code>		x		D							S			
<code>swCalprmAxisSet.swCalprmAxis/SwAxisIndividual.inputVariableType</code>		x		D							S			
<code>swCalprmAxisSet/SwAxisIndividual.unit</code>		opt.		D		I	I	I	I		S			
<code>swComparisonVariable</code>		x						D			S			
<code>swDataDependency</code>		x	x			D	D				S			
<code>swHostVariable</code>		x	x								D			

▽



Attributes of SwDataDefProps	Usage For			Place of Setting											
	RTE	A2L	Other Usage	ApplicationDataType	ImplementationDataType	DataPrototype	InstantiationDataDefProps	ParameterAccess	SwServiceArg	FlatInstanceDescriptor	McDataInstance	SwSystemconst	PerInstanceMemory	ComSpec networkRepresentation	
swImplPolicy	x		x	D	D	D			D						
swIntendedResolution			x	D ¹⁰											
swInterpolationMethod			x	D	I	D	D	D			S				
swIsVirtual		x				D	D				S				
swPointerTargetProps			x		D	I			D						
swRecordLayout	x	x	x	D		I	I	I			S				
swRefreshTiming		x		D	D	D	D		D	D	D				
swTextProps		x	x	D	I	I	I	I			S				
swValueBlockSize		x	x	D	I	I	I	I			S				
swValueBlockSizeMult		x	x	D	I	I	I	I			S				
unit		x	x	D	I	I	I		I		S	D			
valueAxisDataType		x	x	D	I	I	I	I			S				

[constr_1016] Restriction of `invalidValue` for `ImplementationDataType` and `ImplementationDataTypeElement`

Imposition time: IT_CpgExe

[`invalidValue` for `ImplementationDataType` and `ImplementationDataTypeElement` is restricted to be either a compatible `NumericalValueSpecification`, `TextValueSpecification` (caution, [constr_1284] applies) or a `ConstantReference` that in turn points to a compatible `ValueSpecification`.

¹⁰ `swIntendedResolution` is used only in an early phase of the definition of data types, namely in the context of the definition of so-called blueprints. To that extent, `swIntendedResolution` represents a non-binding requirement that shall later be considered for the definition of an appropriate `CompuMethod`.

[constr_1017] Supported combinations of `swImplPolicy` and `swCalibrationAccess`

Imposition time: IT_CpgExe

[

<code>swImplPolicy</code>	<code>swCalibrationAccess</code>		
	<code>notAccessible</code>	<code>readOnly</code>	<code>readWrite</code>
<code>fixed</code>	yes	not supported	not supported
<code>const</code>	yes	yes	not supported
<code>standard</code>	yes	yes	yes
<code>queued</code>	yes	not supported	not supported
<code>measurementPoint</code>	not supported	yes	not supported

]

[constr_1018] `dataElement` with `swImplPolicy` set to `measurementPoint` shall not be referenced by a `VariableAccess` aggregated by `RunnableEntity` in the role `dataReadAccess`

Imposition time: IT_CpgExe

[Due to the nature of `dataElements` characterized by setting the `swImplPolicy` to `measurementPoint`, such `dataElements` shall not be referenced by a `VariableAccess` aggregated by `RunnableEntity` in the role `dataReadAccess`.

]

[constr_1020] `ParameterDataPrototype` needs to be of compatible data type as referenced in `sharedAxisType`

Imposition time: IT_CpgExe

[Finally, the `ParameterDataPrototype` assigned in `swCalprmRef` shall be typed by data type compatible to `sharedAxisType`.

]

[constr_1022] Limits shall be defined for each direction of `CompuMethod`

Imposition time: IT_CpgExe

[In case that both domains are specified in the `CompuMethod` both shall have explicitly defined limits.

]

[constr_1024] Stepwise definition of `CompuMethods`

Imposition time: IT_CpgExe

[In a bound model, the intervals (i.e. determined by attributes `CompuScale.lowerLimit` and `CompuScale.upperLimit`) defined by `CompuScales` used in the context

of a given `CompuMethod` of all values of `category` except `BITFIELD_TEXTTABLE` shall **not** overlap.

For `CompuMethods` of `category` `BITFIELD_TEXTTABLE`, the combination of the interval created by attributes `CompuScale.upperLimit`, `CompuScale.lowerLimit` and `CompuScale.mask` shall be unique in the context of the enclosing `CompuMethod`.

]

[constr_1025] Avoid division by zero in rational formula

Imposition time: IT_CpgExe

[The rational formula shall not yield any division by zero.

]

[constr_1026] Compatibility of Units

Imposition time: IT_CpgExe

[If a `SwDataDefProps` references a `Unit` and the `SwDataDefProps` has a reference to either of/or both

- a `CompuMethod` that in turn references a `Unit`
- a `DataConstr` that in turn references a `Unit`

then the `Units` referenced from

- `SwDataDefProps`
- `SwDataDefProps.compuMethod`
- `SwDataDefProps.dataConstr`

shall be compatible.

]

[constr_1029] ConstantSpecificationMapping and ConstantSpecification

Imposition time: IT_CpgExe

[It is required that the `ConstantSpecification` referenced from a `ConstantSpecificationMapping` in the role `applConstant` shall fulfill the criteria defined in [TPS_SWCT_01871] (i.e. be defined in the *application domain*, `applConstant`) and the other `ConstantSpecification` referenced in the role `implConstant` shall fulfill the criteria defined in [TPS_SWCT_01872] (i.e. be defined in the *implementation domain*, `implConstant`).

]

[constr_1033] Communication scenarios for sender/receiver communication

Imposition time: IT_CompSwcT

[For sender/receiver communication, it is not allowed to create a communication scenario where n sender are connected to m receivers where m and n are **both** greater than 1.

]

[constr_1035] Recursive definition of [CompositionSwComponentType](#)

Imposition time: IT_CompSwcT

[The recursive definition of a [CompositionSwComponentType](#) that eventually contains a [SwComponentPrototype](#) typed by the same [CompositionSwComponentType](#) shall not be feasible.

]

[constr_1036] Connect kinds of [PortInterfaces](#)

Imposition time: IT_RteGen

[It shall not be possible to connect [PortPrototypes](#) typed by [PortInterfaces](#) of different kinds.

Subclasses of [DataInterface](#) make an exception to this rule and can be used for creating connections to each other.

]

[constr_1037] Client shall not be connected to multiple servers

Imposition time: IT_RteGen

[A client shall not be connected to multiple servers such that an operation call would be handled by more than one server.

]

[constr_1038] Reference to [ApplicationError](#)

Imposition time: IT_CpgExe

[A [possibleError](#) referenced by a [ClientServerOperation](#) shall be owned by the [ClientServerInterface](#) that also owns the [ClientServerOperation](#).

]

[constr_1039] Relevance of `swImplPolicy`

Imposition time: IT_RteGen

[It is not possible to define a mapping between an element where the `swImplPolicy` is set to `queued` and another element where the `swImplPolicy` is set differently.

]

[constr_1040] Conversion of `SenderReceiverInterfaces`

Imposition time: IT_RteGen

[The conversion of elements of `SenderReceiverInterfaces` is possible if one of the following conditions applies:

- The `AutosarDataTypes` of the referred `DataPrototypes` are compatible.
- A conversion of the data is available.
- A `DataPrototypeMapping.firstToSecondDataTransformation` is defined.

]

[constr_1041] Conversion of `ClientServerInterfaces`

Imposition time: IT_RteGen

[Either the `AutosarDataTypes` of the referred `ArgumentDataPrototypes` are compatible or a conversion of the data is available.

]

[constr_1043] Allowed combinations of a specific *Type of `PortInterface`*, a specific *Type of `PortPrototype`*, and a specific *Type of `ComSpec`*

Imposition time: IT_CpgExe

[

Type of <code>PortPrototype</code>	Type of <code>ComSpec</code>	Role of Element	Type of <code>PortInterface</code>	Role of Type-Ref
PPortPrototype	NonqueuedSenderComSpec	dataElement	SenderReceiverInterface	providedInterface
PPortPrototype	QueuedSenderComSpec	dataElement	SenderReceiverInterface	providedInterface
RPortPrototype	NonqueuedReceiverComSpec	dataElement	SenderReceiverInterface	requiredInterface
RPortPrototype	QueuedReceiverComSpec	dataElement	SenderReceiverInterface	requiredInterface
PRPortPrototype	NonqueuedSenderComSpec	dataElement	SenderReceiverInterface	providedRequiredInterface





Type of PortPrototype	Type of ComSpec	Role of Element	Type of PortInterface	Role of Type-Ref
PRPortPrototype	Nonqueue-dReceiverComSpec	dataElement	SenderReceiverInterface	providedRequiredInterface
PRPortPrototype	QueuedReceiverComSpec	dataElement	SenderReceiverInterface	providedRequiredInterface
PRPortPrototype	QueuedSenderComSpec	dataElement	SenderReceiverInterface	providedRequiredInterface
PPortPrototype	NvProvideComSpec	nvData	NvDataInterface	providedInterface
RPortPrototype	NvRequireComSpec	nvData	NvDataInterface	requiredInterface
PRPortPrototype	NvProvideComSpec	nvData	NvDataInterface	providedRequiredInterface
PRPortPrototype	NvRequireComSpec	nvData	NvDataInterface	providedRequiredInterface
PPortPrototype	ModeSwitchSenderComSpec	modeGroup	ModeSwitchInterface	providedInterface
RPortPrototype	ModeSwitchReceiverComSpec	modeGroup	ModeSwitchInterface	requiredInterface
PRPortPrototype	ModeSwitchSenderComSpec	modeGroup	ModeSwitchInterface	providedRequiredInterface
PRPortPrototype	ModeSwitchReceiverComSpec	modeGroup	ModeSwitchInterface	providedRequiredInterface
PPortPrototype	ParameterProvideComSpec	parameter	ParameterInterface	providedInterface
RPortPrototype	ParameterRequireComSpec	parameter	ParameterInterface	requiredInterface
PPortPrototype	ServerComSpec	operation	ClientServerInterface	providedInterface
RPortPrototype	ClientComSpec	operation	ClientServerInterface	requiredInterface
PRPortPrototype	ServerComSpec	operation	ClientServerInterface	providedRequiredInterface
PRPortPrototype	ClientComSpec	operation	ClientServerInterface	providedRequiredInterface

]

[constr_1044] Applicability of DataFilter

Imposition time: IT_CpgExe

[According to the origin of DataFilter, i.e. [5], DataFilters can only be applied to values with an integer base type.

]

[constr_1046] Applicability of [TPS_SWCT_01845]

Imposition time: IT_CpgExe

[[TPS_SWCT_01845] applies **only** if the value of the attribute isService is set to false.

]

[constr_1047] Compatibility of `ApplicationPrimitiveDataTypes`

Imposition time: IT_RteGen

[Instances of `ApplicationPrimitiveDataType` are compatible if and only if one of the following conditions applies:

1. All the following sub conditions apply:
 - (a) They have the same `category`.
 - (b) The `swDataDefProps` (after consideration of [constr_1015]) attached to the M1 data types are compatible.
2. In the context of using the `ApplicationPrimitiveDataType`, a `DataPrototypeMapping` exists that refers to a `DataPrototype` typed by one of the `ApplicationPrimitiveDataTypes` in the role `firstDataPrototype` and to another `DataPrototype` typed by the other `ApplicationPrimitiveDataType` in the role `secondDataPrototype`.
3. In the context of using the `ApplicationPrimitiveDataType`, a `DataPrototypeMapping` exists that refers to a `DataPrototype` typed by the `ApplicationPrimitiveDataType` in the role `secondDataPrototype` and to another `DataPrototype` typed by an `ApplicationCompositeDataType` in the role `firstDataPrototype` and additionally for the side of the `ApplicationCompositeDataType` a corresponding `ApplicationCompositeDataType-SubElementRef` exists in the role `firstElement` that in turn references an `ApplicationCompositeElementDataPrototype`.

]

[constr_1048] Compatibility of `ApplicationRecordDataTypes`

Imposition time: IT_RteGen

[Instances of `ApplicationRecordDataTypes` are compatible if and only if one of the following conditions applies:

1. All *elements at the same record position* are of compatible `AutosarDataTypes` (either `ApplicationCompositeDataTypes` or `ApplicationPrimitiveDataTypes`).
2. For each `ApplicationRecordDataType.element`, the attribute `isOptional` shall either
 - not exist on both sides or
 - be set to the value `false` if it only exists on one side or
 - have the identical value on both sides.
3. In the context of a `DataPrototypeMapping`, for each `ApplicationRecordElement` of the required `ApplicationRecordDataType` a `SubElementMapping` exists such that a `ApplicationCompositeDataType-`

`SubElementRef` in the role `firstElement` or `secondElement` exists that references the required `ApplicationRecordElement` **and** a corresponding `ApplicationCompositeDataTypeSubElementRef` exists in the **other** role (i.e. `secondElement` or `firstElement`) that in turn references an `ApplicationRecordElement` of the provided `ApplicationRecordDataType`.

]

[constr_1049] Compatibility of `ApplicationArrayDataTypes`

Imposition time: IT_RteGen

[Instances of `ApplicationArrayDataType` are compatible if and only if one of the following conditions applies:

1. All the following sub conditions apply:
 - (a) Their `elements` are of a compatible `AutosarDataTypes` (either `ApplicationCompositeDataTypes` or `ApplicationPrimitiveDataTypes`).
 - (b) The attributes `maxNumberOfElements` and `arraySizeSemantics` (given the existence) have identical values.
2. In the context of a `DataPrototypeMapping`, for the `ApplicationArrayElement` of the required `ApplicationArrayDataType` a `SubElementMapping` exists such that a `ApplicationCompositeDataTypeSubElementRef` in the role `firstElement` or `secondElement` exists that references the required `ApplicationArrayElement` **and** a corresponding `ApplicationCompositeDataTypeSubElementRef` exists in the **other** role (i.e. `secondElement` or `firstElement`) that in turn references an `ApplicationArrayElement` of the provided `ApplicationArrayDataType`.

]

[constr_1050] Compatibility of `ImplementationDataTypes`

Imposition time: IT_RteGen

[Instances of `ImplementationDataType` are compatible if and only if after all type-references are resolved one of the following rules apply:

1. All the following sub conditions apply:
 - (a) They have the same `category`.
 - (b) They have the identical structure (this refers to `ImplementationDataTypeElement` and their `subElements`).
 - (c) The attributes `arraySize` and `arraySizeSemantics` have (given the existence) identical values.

- (d) For each `ImplementationDataType.subElement`, the attribute `isOptional` shall either
- not exist on both sides or
 - be set to the value `false` if it only exists on one side or
 - have the identical value on both sides.
- (e) The `swDataDefProps` (after consideration of [\[constr_1015\]](#)) attached to the M1 data types are compatible.

2. In the context of using the `ImplementationDataType`, a `DataPrototypeMapping` exists that refers to a `DataPrototype` typed by one of the `ImplementationDataTypes` in the role `firstDataPrototype` and to another `DataPrototype` typed by the other `ImplementationDataType` in the role `secondDataPrototype`.
3. In the context of using the `ImplementationDataType`, a `DataPrototypeMapping` exists that refers to a `DataPrototype` typed by the `ImplementationDataTypes` in the role `secondDataPrototype` and to another `DataPrototype` typed by an `ImplementationDataType` with a `subElement` in the role `firstDataPrototype` and additionally for the side of the `ImplementationDataType` with a `subElement` a corresponding `ImplementationDataTypeSubElementRef` exists in the role `firstElement` that in turn references an `ImplementationDataTypeElement`.

]

[constr_1051] Compatibility of `SwDataDefProps`

Imposition time: IT_RteGen

[`SwDataDefProps` are compatible if and only if:

1. They refer to compatible `Unit` definitions, or neither of them has an associated `Unit`.
2. They refer to compatible conversion methods or neither of them associates such a method.
3. They both aggregate a `ValueSpecification` in the role `invalidValue` or neither of them aggregates a `ValueSpecification` in the role `invalidValue`.
4. If existent (see previous condition), one of the following conditions apply to `ValueSpecifications` aggregated in the role `invalidValue` for being considered compatible (after following and resolving indirections created by `ConstantReference`):
 - (a) both are `ApplicationValueSpecifications` and the values are compatible according to [\[TPS_GST_02501\]](#).

- (b) both are `NumericalValueSpecifications` and the values are compatible according to [TPS_GST_02501].
 - (c) both are `TextValueSpecifications` and the values are identical.
 - (d) both are `ArrayValueSpecifications` and the values are effectively identical, e.g. if one `ArrayValueSpecification` specifies all values explicitly and the other `ArrayValueSpecification` specifies values based on a rule then the yield of both `ArrayValueSpecifications` (i.e. element for element) shall be identical.
 - (e) both are `RecordValueSpecifications` and the values are identical.
 - (f) if one is a `NumericalValueSpecification` and the other one is an `ApplicationValueSpecification` then the check for compatibility shall apply the `CompuMethod` on the physical value such that a comparison on the implementation level becomes possible. [TPS_GST_02501] applies¹¹.
5. They refer to compatible data constraints `dataConstr`.
 6. They refer to compatible `swRecordLayouts`

All other attributes (e.g. `swCalibrationAccess` do not affect compatibility).

]

[constr_1052] Compatibility of `Units`

Imposition time: IT_RteGen

[Two `Unit` definitions are compatible if and only if:

1. They have compatible (see [TPS_GST_02501]) values of attributes `factorSiToUnit` and `offsetSiToUnit`.
2. One of the following conditions is fulfilled:
 - They refer to compatible definitions of `PhysicalDimension`.
 - Neither of them associates a `PhysicalDimension`.
 - One `Unit` refers to a `PhysicalDimension` with `shortName` `NoDimension` where all exponents are set to 0 and the other `Unit` does not refer to a `PhysicalDimension`.

]

¹¹if one is a `NumericalValueSpecification` and the other one is an `ApplicationValueSpecification` and the application of the `CompuMethod` on the side of the `ApplicationValueSpecification` does not yield a valid number a comparison is not possible.

[constr_1053] Compatibility of `PhysicalDimensions` in the context of the creation of a `SwConnector`

Imposition time: IT_RteGen

[In the context of the creation of a `SwConnector`, two `PhysicalDimension` definitions are compatible if and only if the values of

- `lengthExp`
- `massExp`
- `timeExp`
- `currentExp`
- `temperatureExp`
- `molarAmountExp`
- `luminousIntensityExp`

are identical and **either**

- the `shortNames` are identical **or**
- a `PhysicalDimensionMapping` exists that maps one of the `PhysicalDimensions` in the role `firstPhysicalDimension` and the other `PhysicalDimension` in the role `secondPhysicalDimension`.

]

[constr_1054] No `DataConstr` available at the provider

Imposition time: IT_RteGen

[If the provider defines no constraints, it is only compatible with a receiver which also defines no constraints at all.

]

[constr_1055] `ImplementationDataType` has category `VALUE`

Imposition time: IT_CpgExe

[The attributes `baseType` shall refer to a compatible `SwBaseType`.

]

[constr_1056] `ImplementationDataType` has category `TYPE_REFERENCE`

Imposition time: IT_CpgExe

[The `ImplementationDataTypes` referenced by the attributes `SwDataDefProps.implementationDataType` shall be compatible.

]

[constr_1057] ImplementationDataType has category DATA_REFERENCE

Imposition time: IT_CpgExe

[The attributes `SwDataDefProps.swPointerTargetProps` shall have identical `targetCategory` and shall refer to `SwDataDefProps` where all attributes are identical.

]

[constr_1058] ImplementationDataType has category FUNCTION_REFERENCE

Imposition time: IT_CpgExe

[The attributes `SwDataDefProps.swPointerTargetProps.functionPointerSignature` shall refer to `BswModuleEntries` which each resolve to the **same function signature**.

]

[constr_1059] Compatibility of data types with category VALUE

Imposition time: IT_RteGen

[An `ApplicationDataType` of category `VALUE` shall (after all indirections created by `ImplementationDataTypes` of category `TYPE_REFERENCE` are resolved) only be mapped/connected to an `ImplementationDataType` which also has category `VALUE`.

]

[constr_1060] Compatibility of data types with category ARRAY, VAL_BLK

Imposition time: IT_CpgExe

[

ApplicationDataType	ImplementationDataType: Array of uint8	ImplementationDataType: Array of other
<code>ApplicationArrayDataType</code> of category <code>ARRAY, VAL_BLK</code> , <code>arraySizeSemantics = fixedSize</code>	<code>ImplementationDataType</code> of category <code>ARRAY</code> , with <code>ImplementationDataTypeElement</code> with <code>arraySizeSemantics = fixedSize</code>	<code>ImplementationDataType</code> of category <code>ARRAY</code> , with <code>ImplementationDataTypeElement</code> with <code>arraySizeSemantics = fixedSize</code>
<code>ApplicationArrayDataType</code> of category <code>ARRAY, VAL_BLK</code> , <code>arraySizeSemantics = variableSize</code>	<code>ImplementationDataType</code> of category <code>ARRAY</code> , with <code>ImplementationDataTypeElement</code> with <code>arraySizeSemantics = variableSize</code> or <code>Variable-Size Array Data Type</code>	<code>Variable-Size Array Data Type</code>

]

[constr_1061] Compatibility of data types with category STRUCTURE

Imposition time: IT_CpgExe

[An `ApplicationDataType` of category `STRUCTURE` shall (after all indirections created by `ImplementationDataTypes` of category `TYPE_REFERENCE` are resolved) only be mapped/connected to an `ImplementationDataType` of category `STRUCTURE`.

]

[constr_1063] Compatibility of data types with category BOOLEAN

Imposition time: IT_CpgExe

[An `ApplicationDataType` of category `BOOLEAN` shall (after all indirections created by `ImplementationDataTypes` of category `TYPE_REFERENCE` are resolved) only be mapped/connected to an `ImplementationDataType` of category `VALUE`.

]

[constr_1064] Compatibility of data types with category COM_AXIS, RES_AXIS, CURVE, MAP, CUBOID, CUBE_4, or CUBE_5

Imposition time: IT_CpgExe

[An `ApplicationDataType` of category

- `COM_AXIS`,
- `RES_AXIS`,
- `CURVE`,
- `MAP`,
- `CUBOID`,
- `CUBE_4`, or
- `CUBE_5`

shall (after all indirections created by `ImplementationDataTypes` of category `TYPE_REFERENCE` are resolved) only be mapped/connected to an `ImplementationDataType` of category

- `STRUCTURE` or
- `ARRAY`.

]

[constr_1066] Forbidden mappings to ImplementationDataType

Imposition time: IT_CpgExe

[An `ApplicationDataType` shall never be mapped to

- an `ImplementationDataType` of category
 - UNION,
 - DATA_REFERENCE, or
 - FUNCTION_REFERENCE,
- or to an `ImplementationDataType` that contains `subElements` of category
 - UNION,
 - DATA_REFERENCE, or
 - FUNCTION_REFERENCE.

]

[constr_1068] Compatibility of `VariableDataPrototypes` or `ParameterDataPrototypes` typed by primitive data types

Imposition time: IT_RteGen

[Two `VariableDataPrototypes` or `ParameterDataPrototypes` of `ApplicationPrimitiveDataTypes` or `ImplementationDataTypes` of category VALUE, BOOLEAN, or STRING are compatible if and only if one of the following conditions applies:

1. All the following subconditions apply:
 - (a) They are typed by (read "refer to") compatible `AutosarDataTypes`
 - (b) The two `VariableDataPrototypes` or `ParameterDataPrototypes` have identical `shortNames`. This is required to map `VariableDataPrototypes` in unordered `SenderReceiverInterfaces`, `NvDataInterfaces` and `ParameterInterfaces`.
 - (c) The attribute `swImplPolicy` is either set to `queued` for both or none of the `VariableDataPrototypes`.
2. In the context of a `DataPrototypeMapping`, one of the applicable `VariableDataPrototypes` or `ParameterDataPrototypes` is referenced by the `DataPrototypeMapping` in the role `firstDataPrototype` and the other `VariableDataPrototypes` or `ParameterDataPrototypes` is referenced by the same `DataPrototypeMapping` in the role `secondDataPrototype`.

]

[constr_1069] Compatibility of `PortPrototypes` of different `DataInterfaces` in the context of `AssemblySwConnectors`

Imposition time: IT_RteGen

[`PortPrototypes` of different `DataInterfaces` are compatible if and only if

1. One of the following conditions applies:
 - (a) For each `VariableDataPrototype` or `ParameterDataPrototype` defined in the context of the `DataInterface` of the required `PortPrototype` a compatible (see [constr_1068]) `VariableDataPrototype` or `ParameterDataPrototype` exists in the `DataInterface` of the provided `PortPrototype`.

The `shortNames` of `VariableDataPrototypes` and `ParameterDataPrototypes` are used to identify the pair.
 - (b) A `VariableAndParameterInterfaceMapping.dataMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `VariableDataPrototypes` or `ParameterDataPrototypes` in the role `firstDataPrototype` and the other in the role `secondDataPrototype`.
2. For each such pair, the values of their `isService` attributes are identical.

]

[constr_1070] Compatibility of `PortPrototypes` of different `DataInterfaces` in the context of `DelegationSwConnectors`*Imposition time:* IT_RteGen[`PortPrototypes` of different `DataInterfaces` are compatible if and only if

1. One of the following conditions applies:
 - (a) For each `VariableDataPrototype` or `ParameterDataPrototype` defined in the context of the `DataInterface` of the required inner `PortPrototype` a compatible `VariableDataPrototype` or `ParameterDataPrototype` exists in the `DataInterface` of the required outer `PortPrototype`.

The `shortName` of `VariableDataPrototypes` and `ParameterDataPrototypes` are used to identify the pair.

[constr_1071] defines which `PortInterface` elements are compatible depending on the `PortInterface` type and the `swImplPolicy` attributes of the `PortInterface` elements.
 - (b) A `VariableAndParameterInterfaceMapping.dataMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `VariableDataPrototypes` or `ParameterDataPrototypes` in the role `firstDataPrototype` and the other in the role `secondDataPrototype`.

2. One of the following conditions applies:

- (a) For at least one `VariableDataPrototype` or `ParameterDataPrototype` defined in the context of the `SenderReceiverInterface`, `NvDataInterface` or `ParameterInterface` of the provided inner `PortPrototype`, a compatible `VariableDataPrototype` or `ParameterDataPrototype` exists in the `SenderReceiverInterface`, `NvDataInterface` or `ParameterInterface` of the provided outer `PortPrototype`.

The `shortNames` of `VariableDataPrototypes` and `ParameterDataPrototypes` are used to identify the pair.

[[constr_1071](#)] defines which `PortInterface` elements are compatible depending on the `PortInterface` type and the `swImplPolicy` attributes of the `PortInterface` elements.

- (b) A `VariableAndParameterInterfaceMapping.dataMapping` exists for which the following conditions apply:
- It is (if a corresponding `SwConnector` already exists) referenced by the corresponding `SwConnector`.
 - It references one of the two `VariableDataPrototypes` or `ParameterDataPrototypes` in the role `firstDataPrototype` and the other in the role `secondDataPrototype`.

3. For each such pair, the values of their `isService` attributes are identical.

4. For each such pair, either

- no meta-data are defined on both sides or
- both sides define a `SenderReceiverInterface.metaDataItemSet` and the content of the aggregated `MetaDataItemSet` is identical on both sides.

In this context, "identical" means that the respective `MetaDataItemSets` define ordered collections of `MetaDataItems` where the corresponding `MetaDataItem.metaDataItemType.value` have identical content.

]

[constr_1071] compatibility of `ParameterDataPrototype` and `VariableDataPrototype`

Imposition time: IT_RteGen

[

Provided Port Required Outer Port Provided Inner Port Required Outer Port		Required Port / Required Inner Port / Provided Outer Port / Provided Outer Port						
<code>PortInterface</code>		Prm			S/R		NvD	
Interface Element		PDP			VDP		VDP	
<code>SwImplPolicyEnum</code>		<code>fixed</code>	<code>const</code>	<code>standard</code>	<code>standard</code>	<code>queued</code>	<code>standard</code>	
Prm	PDP	<code>fixed</code>	yes	yes	yes	yes	no	yes
		<code>const</code>	no	yes	yes	yes	no	yes
		<code>standard</code>	no	no	yes	yes	no	yes
S/R	VDP	<code>standard</code>	no	no	no	yes	no	yes
		<code>queued</code>	no	no	no	no	yes	no
NvD	VDP	<code>standard</code>	no	no	no	yes	no	yes

]

[constr_1072] Compatibility of `ModeSwitchInterfaces` in the context of an `AssemblySwConnector`

Imposition time: IT_RteGen

[`PortPrototypes` of different `ModeSwitchInterfaces` are compatible if and only if

1. One of the following conditions applies:
 - (a) For the `ModeDeclarationGroupPrototype` defined in the context of the `ModeSwitchInterface` of the required `PortPrototype` a compatible `ModeDeclarationGroupPrototype` exists in the `ModeSwitchInterface` of the provided `PortPrototype`.
 - (b) A `ModeInterfaceMapping.modeMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `ModeDeclarationGroupPrototypes` in the role `firstModeGroup` and the other in the role `secondModeGroup`.
2. For each such pair, the values of their `isService` attributes are identical.

]

[constr_1073] Compatibility of `ModeSwitchInterfaces` in the context of an `DelegationSwConnector`

Imposition time: IT_RteGen

[`PortPrototypes` of different `ModeSwitchInterfaces` are compatible if and only if

1. One of the following conditions applies:
 - (a) For the `ModeDeclarationGroupPrototype` defined in the context of the `ModeSwitchInterface` of the inner `PortPrototype` a compatible `ModeDeclarationGroupPrototype` exists in the `ModeSwitchInterface` of the outer `PortPrototype`.
 - (b) A `ModeInterfaceMapping.modeMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `ModeDeclarationGroupPrototypes` in the role `firstModeGroup` and the other in the role `secondModeGroup`.
2. For each such pair, the values of their `isService` attributes are identical.

]

[constr_1074] Compatibility of `ModeDeclarationGroupPrototypes`

Imposition time: IT_RteGen

[`ModeDeclarationGroupPrototypes` are compatible if and only if one of the following conditions applies:

1. They are typed by (read "refer to") compatible `ModeDeclarationGroups`.
2. A `ModeDeclarationGroupPrototypeMapping` exists that identifies the differently named `ModeDeclarationGroupPrototypes` that correlate with each other. [constr_1210] applies.

]

[constr_1075] Compatibility of `ModeDeclarationGroups`

Imposition time: IT_RteGen

[`ModeDeclarationGroups` are compatible if and only if one of the following conditions applies:

1. All the following subconditions apply:
 - (a) They define an identical number of `ModeDeclarations`.
 - (b) Each `ModeDeclaration` on the required side corresponds to a `ModeDeclaration` on the provided side with an identical `shortName`.

- (c) The `initialModes` on both sides refer to `ModeDeclarations` with identical `shortNames`.
 - (d) The attribute `ModeDeclarationGroup.modeUserErrorBehavior.errorReactionPolicy` has identical values on both sides.
 - (e) The attribute `ModeDeclarationGroup.modeManagerErrorBehavior.errorReactionPolicy` has identical values on both sides.
 - (f) The attribute `ModeDeclarationGroup.modeUserErrorBehavior.defaultMode` either does not exist on both sides or refers on both sides to `ModeDeclarations` with identical `shortNames`.
 - (g) The attribute `ModeDeclarationGroup.modeManagerErrorBehavior.defaultMode` either does not exist on both sides or refers on both sides to `ModeDeclarations` with identical `shortNames`.
 - (h) one of the following subconditions applies:
 - the attribute `category` has the value `ALPHABETIC_ORDER` on both sides.
 - the attribute `category` has the value `EXPLICIT_ORDER` on both sides **and** the matching `ModeDeclarations` according to 1(b) have the identical values of the attributes `ModeDeclaration.value` **and** also the value of `ModeDeclarationGroup.onTransitionValue` matches on both sides.
2. A `ModeDeclarationMapping` is applied which identifies the corresponding `ModeDeclarations`.

In addition, the compatibility of corresponding `ModeTransitions` shall be checked, i.e. [`constr_1194`] and [`constr_1245`] apply.

]

[`constr_1076`] Compatibility of `ArgumentDataPrototypes`

Imposition time: IT_RteGen

[Two `ArgumentDataPrototypes` are compatible if and only if

1. They are typed by compatible `AutosarDataTypes` **or** a `ClientServerOperationMapping.argumentMapping` exists that references one `ArgumentDataPrototype` in the role `firstDataPrototype` and the other `ArgumentDataPrototype` in the role `secondDataPrototype`.
2. They have the same value of the argument `direction` (`in`, `out` or `inout`), i.e. [`constr_1268`] applies.

]

[constr_1077] Compatibility of `ApplicationErrors`

Imposition time: IT_RteGen

[Two `ApplicationErrors` are compatible if and only if one of the following conditions applies:

1. All the following subconditions apply:
 - (a) They have the same `shortName`.
 - (b) They have the same attributes. Especially the `errorCode` shall be identical in both `ApplicationErrors`.
2. A `ClientServerInterfaceMapping.errorMapping` exists that references one of the `ApplicationErrors` in the role `firstApplicationError` and the other `ApplicationErrors` in the role `secondApplicationError`.

]

[constr_1078] Compatibility of `ClientServerOperations`

Imposition time: IT_RteGen

[Two `ClientServerOperations` are considered compatible if their signatures match. In particular, they are compatible if and only if

1. They have the same number of `ArgumentDataPrototypes`.
2. The n-th arguments of both `ClientServerOperations` are compatible. This implies ordering of `ArgumentDataPrototypes`.
3. They have identical values of attribute `diagArgIntegrity` or the attribute `diagArgIntegrity` does not exist on both sides.
4. They have the same `shortName` (again allows for mapping in `PortInterfaces`).
5. The required `ClientServerOperation` specifies a compatible `ApplicationError` for each `ApplicationError` that is possibly raised by the provided `ClientServerOperation`, maybe more. Thereby, `ClientServerOperations` that refer to a `possibleError` that represents the value `E_OK` are compatible to `ClientServerOperations` that do refer to `possibleErrors` where none of them represents the value `E_OK`.

]

[constr_1079] Compatibility of `ClientServerInterfaces` in the context of an `AssemblySwConnector`

Imposition time: IT_RteGen

[`ClientServerInterfaces` are compatible if and only if

1. One of the following conditions applies:

- (a) For each `ClientServerOperation` defined in the context of the `ClientServerInterface` of the required `PortPrototype` a compatible `ClientServerOperation` exists in the `ClientServerInterface` of the provided `PortPrototype`. The `shortNames` of `ClientServerOperations` are used to identify the pair.
 - (b) A `ClientServerInterfaceMapping.operationMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `ClientServerOperations` in the role `firstOperation` and the other in the role `secondOperation`.
2. For each such pair, the values of their `isService` attributes are identical.

]

[constr_1080] Compatibility of `ClientServerInterfaces` in the context of an `DelegationSwConnector`*Imposition time:* IT_RteGen[`ClientServerInterfaces` are compatible if and only if

1. One of the following conditions applies:
 - (a) For each `ClientServerOperation` defined in the context of the `ClientServerInterface` of the required inner `PortPrototype` a compatible `ClientServerOperation` exists in the `ClientServerInterface` of the required outer `PortPrototype`. The `shortNames` of `ClientServerOperations` are used to identify the pair.
 - (b) A `ClientServerInterfaceMapping.operationMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `ClientServerOperations` in the role `firstOperation` and the other in the role `secondOperation`.
2. One of the following conditions applies:
 - (a) For at least one `ClientServerOperation` defined in the context of the `ClientServerInterface` of the provided inner `PortPrototype` a compatible `ClientServerOperation` exists in the `ClientServerInterface` of the provided outer `PortPrototype`. The `shortNames` of `ClientServerOperations` are used to identify the pair.
 - (b) A `ClientServerInterfaceMapping.operationMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.

- ii. It references one of the two `ClientServerOperations` in the role `firstOperation` and the other in the role `secondOperation`.
3. For each such pair, the values of their `isService` attributes are identical.

]

[constr_1081] Compatibility of `TriggerInterfaces` in the context of an `AssemblySwConnector`*Imposition time:* IT_RteGen[`TriggerInterfaces` are compatible if and only if

1. One of the following conditions applies:
 - (a) For each `Trigger` defined in the context of the `TriggerInterface` of the required `PortPrototype` a compatible `Trigger` exists in the `TriggerInterface` of the provided `PortPrototype`. The `shortNames` of `Trigger` are used to identify the pair.
 - (b) A `TriggerInterfaceMapping.triggerMapping` exists for which the following conditions apply:
 - i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `Triggers` in the role `firstTrigger` and the other in the role `secondTrigger`.
2. For each such pair, the values of their `isService` attributes are identical.

]

[constr_1082] Compatibility of `TriggerInterfaces` in the context of an `DelegationSwConnector`*Imposition time:* IT_RteGen[`TriggerInterfaces` are compatible if and only if all the following conditions apply:

1. One of the following subconditions applies:
 - (a) For each `Trigger` defined in the context of the `TriggerInterface` of the **required** inner `PortPrototype` a compatible `Trigger` exists in the `TriggerInterface` of the **required** outer `PortPrototype`. The `shortNames` of `Trigger` are used to identify the pair.
 - (b) For at least one `Trigger` defined in the context of the `TriggerInterface` of the **provided** outer `PortPrototype` a compatible `Trigger` exists in the `TriggerInterface` of the **provided** inner `PortPrototype`. The `shortNames` of `Trigger` are used to identify the pair.
 - (c) A `TriggerInterfaceMapping.triggerMapping` exists for which all the following conditions apply:

- i. It is referenced by the corresponding `SwConnector`.
 - ii. It references one of the two `Triggers` in the role `firstTrigger` and the other in the role `secondTrigger`.
 2. For each such pair, the values of their `isService` attributes are identical.
-]

[constr_1083] Compatibility of `Triggers`

Imposition time: IT_RteGen

[`Triggers` are compatible if one of the following conditions is fulfilled:

- They have an identical `shortName`.
 - A `TriggerMapping` exists that references one of the `Triggers` in the role `firstTrigger` and the other `Trigger` in the role `secondTrigger`.
-]

[constr_1084] delegation of a provided outer `PortPrototype`

Imposition time: IT_RteGen

[The delegation of a provided outer `PortPrototype` is properly defined if the following criteria are fulfilled:

1. For each `VariableDataPrototype` or `ParameterDataPrototype` present in the
 - `SenderReceiverInterface`,
 - `NvDataInterface`, or
 - `ParameterInterface`of the provided outer `PortPrototype`, at least one connection via
 - `DelegationSwConnector` to a provided inner `PortPrototype` **or**
 - `PassThroughSwConnector` to a required outer `PortPrototype`with a compatible `VariableDataPrototype` or `ParameterDataPrototype` in the
 - `SenderReceiverInterface`,
 - `NvDataInterface`, or
 - `ParameterInterface`of the
 - provided inner `PortPrototype` **or**

- required outer `PortPrototype`

exists.

Either the `shortNames` of `VariableDataPrototypes` or `ParameterDataPrototypes` are used to identify the pair, or a `PortInterfaceMapping` defines which differently named `PortInterface` elements correlate with each other.

2. For each `VariableDataPrototype` provided by a `PPortPrototype` that is typed by a
 - `SenderReceiverInterface` or
 - `NvDataInterface`

and that is referenced in the role `outerPort` by a `DelegationSwConnector`, a corresponding `VariableDataPrototype` owned by an `innerPort` shall be provided by either

- a `PPortPrototype` or
- a `PRPortPrototype`.

Either the `shortNames` of `VariableDataPrototypes` are used to identify the pair, or a `PortInterfaceMapping` defines which differently named `PortInterface` elements correlate with each other.

3. For the `ModeDeclarationGroupPrototype` present in the `ModeSwitchInterface` of the provided outer `PortPrototype`, exactly one connection via
 - `DelegationSwConnector` to a provided inner `PortPrototype` **or**
 - `PassThroughSwConnector` to a required outer `PortPrototype`

with a compatible `ModeDeclarationGroupPrototype` in the `ModeSwitchInterface` of the

- provided inner `PortPrototype` **or**
- required outer `PortPrototype`

exists.

Either the `shortNames` of `ModeDeclarationGroupPrototypes` are used to identify the pair, or a `PortInterfaceMapping` defines which differently named `PortInterface` elements correlate with each other.

4. For each `ClientServerOperation` present in the `ClientServerInterface` of the provided outer `PortPrototype`, exactly one connection via
 - `DelegationSwConnector` to a provided inner `PortPrototype` **or**
 - `PassThroughSwConnector` to a required outer `PortPrototype`

with a compatible `ClientServerOperation` in the `ClientServerInterface` of the

- provided inner `PortPrototype` **or**
- required outer `PortPrototype`

exists.

Either the `shortNames` of `ClientServerOperations` are used to identify the pair, or a `PortInterfaceMapping` defines which differently named `PortInterface` elements correlate with each other.

5. For each `Trigger` present in the `TriggerInterface` of the provided outer `PortPrototype`, exactly one connection via

- `DelegationSwConnector` to a provided inner `PortPrototype` **or**
- `PassThroughSwConnector` to a required outer `PortPrototype`

with a compatible `Trigger` in the `TriggerInterface` of the provided

- inner `PortPrototype` **or**
- required outer `PortPrototype`

exists.

Either the `shortNames` of `Triggers` are used to identify the pair, or a `PortInterfaceMapping` defines which differently named `PortInterface` elements correlate with each other.

]

[constr_1085] Compatibility in the case of a flat ECU extract

Imposition time: `IT_EcuExt`

[`PortPrototypes` of different

- `SenderReceiverInterfaceS`,
- `NvDataInterfaces`, and
- `ParameterInterfaces`

are compatible if and only if for at least one

- `VariableDataPrototype` **or**
- `ParameterDataPrototype`

defined in the context of the

- `SenderReceiverInterfaceS`,
- `NvDataInterfaces`, and

- `ParameterInterfaces`

of the `RPortPrototype`, a compatible

- `VariableDataPrototype` or
- `ParameterDataPrototype`

exists in the

- `SenderReceiverInterfaces`,
- `NvDataInterfaces`, and
- `ParameterInterfaces`

of the provided `PortPrototype`.

The compatibility of `PortInterface` elements depends on the kind of `PortInterface` and the `swImplPolicy` attributes of the `PortInterface` elements.

Either the `shortNames` of `VariableDataPrototypes` and `ParameterDataPrototypes` are used to identify the pair, or a `PortInterfaceMapping` defines which differently named `PortInterface` elements correlate with each other.

]

[constr_1086] `SwConnector` between two specific `PortPrototypes`

Imposition time: `IT_RteGen`

[Each pair of `PortPrototypes` can only be connected by one and only one `SwConnector`.

]

[constr_1087] `AssemblySwConnector` inside `CompositionSwComponentType`

Imposition time: `IT_CompSwcT`

[An `AssemblySwConnector` owned by a specific `CompositionSwComponentType` shall only connect `PortPrototypes` of `SwComponentPrototypes` that are owned by the same `CompositionSwComponentType`.

]

[constr_1088] `DelegationSwConnector` inside `CompositionSwComponentType`

Imposition time: `IT_CompSwcT`

[A `DelegationSwConnector` owned by a specific `CompositionSwComponentType` shall only connect a `PortPrototype` of a `SwComponentPrototype` that is

owned by the same `CompositionSwComponentType` that also owns the connected delegation `PortPrototype`.

]

[constr_1091] RTEEvents that may reference a WaitPoint

Imposition time: IT_CpgExe

[A `WaitPoint` shall only be referenced from the listed `RTEEvents`:

- `DataReceivedEvent`
- `DataSendCompletedEvent`
- `ModeSwitchedAckEvent`
- `AsynchronousServerCallReturnsEvent`

]

[constr_1092] Restrictions for the ParameterSwComponentType

Imposition time: IT_CpgExe

[The following restrictions exist for a `ParameterSwComponentType`:

- it shall never aggregate a `SwcInternalBehavior` and
- the only aggregated `PortPrototypes` shall be `PPortPrototypes` of type `ParameterInterface`.

]

[constr_1093] Definition of textual strings

Imposition time: IT_CpgExe

[An `ApplicationPrimitiveDataType` of category `STRING` shall have a `swTextProps` which determines the `arraySizeSemantics` and `swMaxTextSize`.

]

[constr_1095] Values of nDataSets vs. reliability

Imposition time: IT_RteGen

[If the value of `nDataSets` is greater than 0, the value of `reliability` shall not be set to `errorCorrection`.

]

[constr_1096] SwcModeSwitchEvent and WaitPoint

Imposition time: IT_CpgExe

[A [RunnableEntity](#) that has a [WaitPoint](#) shall not be referenced by a [SwcModeSwitchEvent](#).

]

[constr_1097] RunnableEntity that has a WaitPoint

Imposition time: IT_RteGen

[A [RunnableEntity](#) that has a [WaitPoint](#) shall not be referenced by an [RTEEvent](#) that has a reference in the role [disabledMode](#).

]

[constr_1098] Mode switch and mode disabling

Imposition time: IT_RteGen

[A [SwcModeSwitchEvent](#) shall not simultaneously reference to the same [ModeDeclaration](#) in both the roles [mode](#) and [disabledMode](#).

]

[constr_1100] Unconnected RPortPrototype typed by a DataInterface

Imposition time: IT_RteGen

[For any element in an unconnected [RPortPrototype](#) typed by a [DataInterface](#), there shall be a [requiredComSpec](#) that defines an [initValue](#).

]

[constr_1101] Mode-related communication

Imposition time: IT_RteGen

[An [RPortPrototype](#) typed by [ModeSwitchInterface](#) shall not be referenced by more than one [SwConnector](#).

]

[constr_1102] ApplicationError in the scope of one SwComponentType

Imposition time: IT_CpgExe

[If a [SwComponentType](#) has [PortPrototypes](#) typed by different [ClientServerInterfaces](#) with equal [shortName](#) and [ApplicationErrors](#) defined then the following condition applies: [ApplicationErrors](#) with the same [shortName](#) shall have **identical values** of [errorCodes](#).

]

[constr_1103] NonqueuedReceiverComSpec and enableUpdate

Imposition time: IT_CpgExe

[A `NonqueuedReceiverComSpec` that has the value of attribute `enableUpdate` set to `true` may not reference a `dataElement` that in turn is referenced by a `VariableAccess` in the role `dataReadAccess`.

]

[constr_1104] Trigger communication shall not implement an n:1 pattern

Imposition time: IT_RteGen

[An `RPortPrototype` typed by a `TriggerInterface` shall not be connected to `PortPrototypes` typed by `TriggerInterfaces` such that a given `Trigger` in the `TriggerInterface` of the `RPortPrototype` is connected to more than one compatible (see [constr_1081], [constr_1082], and [constr_1251]) `Trigger` in the `TriggerInterfaces` of the connected `PortPrototypes`.

]

[constr_1105] Value of arraySize

Imposition time: IT_CpgExe

[The value of the attribute `arraySize` of an `ImplementationDataTypeElement` owned by an `ImplementationDataType` or `ImplementationDataTypeElement` of category `ARRAY` shall be greater than 0 unless attribute `ImplementationDataTypeElement.arraySizeHandling` exists and is set to the value `inheritedFromArrayElementTypeSize`.

]

[constr_1106] Structure shall have at least one element

Imposition time: IT_CpgExe

[An `ImplementationDataType` or `ImplementationDataTypeElement` of category `STRUCTURE` shall own at least one `ImplementationDataTypeElement`.

]

[constr_1107] Union shall have at least one element

Imposition time: IT_CpgExe

[An `ImplementationDataType` or `ImplementationDataTypeElement` of category `UNION` shall own at least one `ImplementationDataTypeElement`.

]

[constr_1108] Existence and value of attribute `ApplicationError.errorCode`

Imposition time: IT_CpgExe

[Attribute `ApplicationError.errorCode` shall exist and its value shall not exceed the closed interval 1..63.

The following exception applies: **only** if attribute `possibleError` is supposed to represent the error code `E_OK`, the value 0 shall be allowed.

]

[constr_1109] Mapping of `SwComponentPrototypes` typed by a `SensorActuatorSwComponentType`

Imposition time: IT_RteGen

[A `SwComponentPrototype` typed by a `SensorActuatorSwComponentType` needs to be mapped and run on exactly that ECU that contains the `HwElement` corresponding to the `HwType` that its `SensorActuatorSwComponentType` refers to in case it accesses the hardware via the I/O hardware abstraction layer.

]

[constr_1111] Constraints of `dataId` in PROFILE_01

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_01, there shall be only one element in the set and the applicable range of values is [0 .. 65535].

]

[constr_1112] Constraints of `dataIdMode` in PROFILE_01

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_01, the applicable range of values for `dataIdMode` is [0 .. 3].

]

[constr_1113] Existence of attributes of meta-class `EndToEndDescription` in PROFILE_01

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_01, the following attributes of meta-class `EndToEndDescription` shall exist:

- `dataLength`
- `dataId`

}

[constr_1114] Constraints of `crcOffset` in PROFILE_01*Status:* OBSOLETE*Imposition time:* IT_CpgExe

[In PROFILE_01, the applicable range of values for `crcOffset` is [0 .. 65535]. For the value of this attribute the constraint $value \bmod 4 = 0$ applies.

}

[constr_1115] Constraints of `counterOffset` in PROFILE_01*Status:* OBSOLETE*Imposition time:* IT_CpgExe

[In PROFILE_01, the applicable range of values for `counterOffset` is [0 .. 65535]. For the value of this attribute the constraint $value \bmod 4 = 0$ applies.

}

[constr_1116] Constraints of `dataLength` in PROFILE_01*Status:* OBSOLETE*Imposition time:* IT_CpgExe

[In PROFILE_01, the applicable range of values for `dataLength` is [0 .. 240]. For the value of this attribute the constraint $value \bmod 8 = 0$ applies.

}

[constr_1117] Constraints of `maxDeltaCounterInit` in PROFILE_01*Status:* OBSOLETE*Imposition time:* IT_CpgExe

[In PROFILE_01, the applicable range of values for `EndToEndDescription.maxDeltaCounterInit` is [0 .. 14].

}

[constr_1118] Existence of attributes of meta-class `EndToEndDescription` in PROFILE_02*Status:* OBSOLETE*Imposition time:* IT_CpgExe

[In PROFILE_02, only the following attributes of meta-class `EndToEndDescription` shall exist:

- `dataLength`
- `dataId`

}

[constr_1119] Constraints of `dataLength` in PROFILE_02

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_02, the applicable range of values for `dataLength` is [0 .. 65535]. For the value of this attribute the constraint $value \bmod 8 = 0$ applies.

]

[constr_1120] Constraints of `dataId` in PROFILE_02

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_02, there shall be exactly ordered 16 elements in the set and the applicable range of values is [0 .. 255].

]

[constr_1121] Constraints of `maxDeltaCounterInit` in PROFILE_02

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_02, the applicable range of values for `EndToEndDescription.maxDeltaCounterInit` and `ReceiverComSpec.maxDeltaCounterInit` is [0 .. 15].

]

[constr_1126] Compatibility of `DataConstrs`

Imposition time: IT_RteGen

[The `DataConstr` (e.g. the limits) defined by the type of the providing data element shall be within the constraints defined by the type of the requiring data element.

For client-server communication, the following rules apply:

- For `arguments` with attribute `direction` set to the value `in`, the client shall take the role of the *provider* and the server shall take the role of the *requiring side*.
- For `arguments` with attribute `direction` set to the value `inout` the `DataConstr` shall be equal on both sides.
- For `arguments` with attribute `direction` set to the value `out`, the server shall take the role of the *provider* and the client shall take the role of the *requiring side*.

]

[constr_1128] Queue length of `ClientServerOperations` associated with the same `RunnableEntity`

Imposition time: IT_CpgExe

[If two or more `OperationInvokedEvents` reference a single `RunnableEntity` the value of the `ServerComSpec` attribute `queueLength` shall be **identical** for all `ServerComSpecs` owned by `PPortPrototypes` of the enclosing `SwComponentType` that reference one of the `ClientServerOperations` that are also referenced by the `OperationInvokedEvents`.

]

[constr_1129] `swImplPolicy` and `NonqueuedReceiverComSpec`

Imposition time: IT_CpgExe

[The attribute `swImplPolicy` of a `dataElement` referenced by a `NonqueuedReceiverComSpec` **shall not** be set to the value `queued`.

]

[constr_1130] `swImplPolicy` and `QueuedReceiverComSpec`

Imposition time: IT_CpgExe

[The attribute `swImplPolicy` of a `dataElement` referenced by a `QueuedReceiverComSpec` **shall** be set to the value `queued`.

]

[constr_1131] `swImplPolicy` and `NonqueuedSenderComSpec`

Imposition time: IT_CpgExe

[The attribute `swImplPolicy` of a `dataElement` referenced by a `NonqueuedSenderComSpec` **shall not** be set to the value `queued`.

]

[constr_1132] `swImplPolicy` and `QueuedSenderComSpec`

Imposition time: IT_CpgExe

[The attribute `swImplPolicy` of a `dataElement` referenced by a `QueuedSenderComSpec` **shall** be set to the value `queued`.

]

[constr_1134] Allowed structure of TEXTTABLE

Imposition time: IT_CpgExe

[The existence of `physConstrs` is not allowed and `compuInternalToPhys` shall exist with `compuScales` consisting of `upperLimit` and `lowerLimit`.

]

[constr_1135] Limit of vt in BITFIELD_TEXTTABLE

Imposition time: IT_CpgExe

[The separator for splitting the string representing the value is "|" and is therefore forbidden to appear in `vt`.

]

[constr_1137] Applicability of ParameterInterface

Imposition time: IT_RteGen

[A `PPortPrototype` typed by a `ParameterInterface` can **only** be owned by a `ParameterSwComponentType` or a `CompositionSwComponentType`.

]

[constr_1138] SwcServiceDependency.assignedPort and DiagEventDebounceMonitorInternal

Imposition time: IT_RteGen

[If a `SwcServiceDependency` aggregates `DiagnosticEventNeeds` in the role `serviceNeeds`, then an `assignedPort` with attribute `role` set to the value `CallbackGetFaultDetectCounter` shall only exist if the monitor implements internal debouncing, i.e. concrete subclass `DiagEventDebounceMonitorInternal` is aggregated in the role `DiagnosticEventNeeds.diagEventDebounceAlgorithm`.

]

[constr_1140] Combination of invalidValue with the attribute handleInvalid

Imposition time: IT_CpgExe

[The combination of setting the attribute `handleInvalid` of the meta-class `InvalidationPolicy` owned by `SenderReceiverInterface` to value `replace` **and** of setting the value of the attribute `initValue` owned by a corresponding `NonqueuedReceiverComSpec` effectively to the value of the `invalidValue` (owned by a corresponding `SwDataDefProps`) is not supported.

]

[constr_1141] Applicability of the `scope` attribute

Imposition time: IT_CpgExe

[The attribute `scope` of meta-class `VariableAccess` shall **only** be applied with respect to the aggregation of `VariableAccess` in the following roles:

- `dataReadAccess`
- `dataWriteAccess`
- `dataSendPoint`
- `dataReceivePointByValue`
- `dataReceivePointByArgument`

]

[constr_1142] `category` of `CompuMethod` shall not be extended

Imposition time: IT_CpgExe

[In contrast to the general rule that `category` can be extended by user-specific values it is **not allowed** to extend the meaning of the attribute `category` of meta-class `CompuMethod`.

]

[constr_1144] `SensorActuatorSwComponentType`, `EcuAbstractionSwComponentType`, and `ComplexDeviceDriverSwComponentType` may only reference a `HwType`

Imposition time: IT_CpgExe

[The attribute `sensorActuator` of `SensorActuatorSwComponentType`, the attribute `hardwareElement` of `EcuAbstractionSwComponentType`, and the attribute `hardwareElement` of `ComplexDeviceDriverSwComponentType` may **only** reference a `HwType`. References to other subclasses of `HwDescriptionEntity` are not allowed.

]

[constr_1146] Applicability of a `symbol` for a `CompuScale` in C code

Imposition time: IT_CpgExe

[The `symbol` attribute shall only be provided for `CompuScales` where the `category` of the enclosing `CompuMethod` is one of the following:

- `TEXTTABLE`
- `SCALE_LINEAR_AND_TEXTTABLE`
- `SCALE_RATIONAL_AND_TEXTTABLE`

- BITFIELD_TEXTTABLE

]

[constr_1147] Standardized values for the attribute `category` of meta-class `PortGroup`

Imposition time: IT_CompSwcT

[The following values of the attribute `category` of meta-class `PortGroup` are reserved by the AUTOSAR standard:

- `MODE_MANAGEMENT`: This represents the usage of the `PortGroup` for the purpose of mode management
- `PARTIAL_NETWORKING`: This represents the usage of the `PortGroup` for the purpose of partial networking

.

]

[constr_1148] `PortInterfaces` of `PortPrototypes` used to connect to `NvBlockSwComponentTypes`

Imposition time: IT_RteGen

[`PortInterfaces` of `PortPrototypes` used to connect to `NvBlockSwComponentTypes` as well as the `PortInterfaces` used in the context of `NvBlockSwComponentTypes` shall **always** set the value of the attribute `isService` to `false`.

]

[constr_1149] `PortPrototypes` used for NV data management

Imposition time: IT_RteGen

[A `PortPrototype` typed by a `ClientServerInterface` used for NV data management, i.e. the interaction of `ApplicationSwComponentTypes` with `NvBlockSwComponentTypes`, shall be typed by `ClientServerInterfaces` that are compatible to the particular `ClientServerInterfaces` derived from [6]. [constr_1148] applies.

This rule shall be imposed.

]

[constr_1150] Usage of `valueType` for `PortDefinedArgumentValue`

Imposition time: IT_RteGen

[The `valueType` (typically this boils down to integer values used to specify an "id") associated with `PortDefinedArgumentValue` shall be of `category VALUE` or

`TYPE_REFERENCE`. The latter case is only supported if the value of `category` of the target data type is set to `VALUE`.

]

[constr_1151] Applicability of `PortInterfaceMapping`

Imposition time: IT_RteGen

[A `PortInterfaceMapping` is only applicable and valid for a `SwConnector` if the two `PortPrototypes` which are referenced by the `SwConnector` are typed by the same two `PortInterfaces` which are mapped by the `PortInterfaceMapping`.

]

[constr_1152] `category` of `ApplicationArrayElement` and `AutosarDataType` referenced in the role `type` shall be kept in sync

Imposition time: IT_CpgExe

[The value of `category` of an `ApplicationArrayElement` shall always be identical to the value of `category` of the `AutosarDataType` referenced by the `ApplicationArrayElement`.

]

[constr_1153] Applicability of compatibility requirements for `CompuScales`

Imposition time: IT_RteGen

[Compatibility requirements for `CompuScales` shall only apply for `CompuScales` where the `category` of the enclosing `CompuMethod` is one of the following:

- TEXTTABLE
- SCALE_LINEAR_AND_TEXTTABLE
- SCALE_RATIONAL_AND_TEXTTABLE
- TAB_NOINTP
- BITFIELD_TEXTTABLE
- LINEAR
- RAT_FUNC
- IDENTICAL

.

]

[constr_1154] Compatibility of [CompuScales](#) for sender-receiver communication and similar use cases

Imposition time: IT_RteGen

[For sender-receiver communication and similar use cases, it is required that the set of [CompuScales](#) defined in the [CompuMethod](#) of the provider of the communication (i.e. on the side of the [PPortPrototype](#)) shall be a subset of the set of [CompuScales](#) defined in the [CompuMethod](#) on the required side (i.e. on the side of the [RPortPrototype](#)).

]

[constr_1155] Compatibility of [CompuScales](#) for client-server communication

Imposition time: IT_RteGen

[For client-server communication, the following rules apply:

For [arguments](#) of direction IN the [CompuScales](#) defined in the [CompuMethod](#) of the client (i.e. on the side of the [RPortPrototype](#)) shall be a subset of the set of [CompuScales](#) defined in the [CompuMethod](#) supported at the server (i.e. on the side of the [PPortPrototype](#)).

For [arguments](#) of the direction OUT the set of [CompuScales](#) defined in the [CompuMethod](#) of the server (i.e. on the side of the [PPortPrototype](#)) shall be a subset of the set of [CompuScales](#) defined in the [CompuMethod](#) supported at the client (i.e. on the side of the [RPortPrototype](#)).

For [arguments](#) of direction INOUT the set of [CompuScales](#) defined in the [CompuMethod](#) of server and client shall be identical.

]

[constr_1156] Relevance of "names" of [CompuScales](#)

Imposition time: IT_RteGen

[[CompuScales](#) which contribute to tabular conversion by having a [compuConst](#) are compatible **if and only if** the "names" of the [compuScales](#), (namely [shortLabel](#), [vt](#) and [symbol](#), according to the priority rules communicated in [TPS_SWCT_01431]) are equal.

If the scale has no [compuConst](#), "names" of [CompuScales](#) are not relevant for compatibility.

]

[constr_1158] Applicable `categorys` for attribute `ImplementationDataType.swDataDefProps.compuMethod`

Imposition time: IT_CpgExe

[

	IDENTICAL	LINEAR	SCALE_LINEAR	SCALE_LINEAR_AND_TEXTTABLE	RAT_FUNC	SCALE_RATIONAL_AND_TEXTTABLE	TEXTTABLE	TAB_NOINTP	BITFIELD_TEXTTABLE
<code>VALUE</code>							x		x
<code>TYPE_REFERENCE</code>							x		x

]

[constr_1159] Consistency of `VariableAndParameterInterfaceMapping` with respect to the referenced `DataInterfaces`

Imposition time: IT_RteGen

[Within one `VariableAndParameterInterfaceMapping` all `firstDataPrototypes` shall belong to one and only one `DataInterface` and all `secondDataPrototypes` shall belong to one other and only one other `DataInterface`.

]

[constr_1161] Applicability of the attribute `Ref.index`

Imposition time: IT_CpgExe

[The usage of attribute `Ref.index` is limited to references to the following meta-classes:

- `ApplicationArrayElement`
- Sub-classes of `AbstractImplementationDataTypeElement`.

]

[constr_1163] Compatibility of `CompuMethods`

Imposition time: IT_RteGen

[Two `CompuMethod` definitions are compatible if and only if all attributes **except**

- `shortName`

- `desc`
- `introduction`
- `longName`
- `adminData`
- `annotation`
- `displayFormat`

are **identical and** the `compuScales` and `units` are compatible.

]

[constr_1164] Number of **arguments** owned by a **RunnableEntity**

Imposition time: IT_CpgExe

[If a given `RunnableEntity` owns `RunnableEntityArguments` in the role `argument`, then the number of these `RunnableEntityArguments` shall be identical to the number of applicable `portArgValues` of the `PortAPIOption` that references the `PortPrototype` that in turn is referenced by the `OperationInvokedEvent` that references the `RunnableEntity` **plus** the number of `ArgumentDataPrototypes` aggregated in the role `argument` by the `ClientServerOperation` referenced by said `OperationInvokedEvent`.

]

[constr_1165] Applicability of **RunnableEntityArgument**

Imposition time: IT_CpgExe

[The existence of a `RunnableEntityArgument` is limited to `RunnableEntity`s triggered by a `ClientServerOperation`.

]

[constr_1166] Restrictions of **ModeRequestTypeMap**

Imposition time: IT_CpgExe

[For every `ModeDeclarationGroup` referenced by a `ModeDeclarationGroup-Prototype` used in a `PortPrototype` typed by a `ModeSwitchInterface` a `ModeRequestTypeMap` shall exist that points to the `ModeDeclarationGroup` and also to an eligible `ImplementationDataType`.

The `ModeRequestTypeMap` shall be aggregated by a `DataTypeMappingSet` which is referenced from the `SwcInternalBehavior` that is owned by the `Application-SwcComponentType` that also owns the `PortPrototype`.

]

[constr_1167] ImplementationDataTypes used as ModeRequestTypeMap.implementationDataType

Imposition time: IT_CpgExe

[The `ImplementationDataType` referenced by a `ModeRequestTypeMap` shall either be

- of category `VALUE` or
- of category `TYPE_REFERENCE` that in turn references an `ImplementationDataType` of category `VALUE`.

The `baseType` referenced by the `ImplementationDataType` shall have set the value of the attribute `BaseTypeDirectDefinition.baseTypeEncoding` to `NONE`.

]

[constr_1168] Compatibility of ImplementationDataTypes used in the ModeRequestTypeMap

Imposition time: IT_RteGen

[Both `ImplementationDataTypes` shall fulfill [constr_1167].

In addition to that, the possible numbers used for representing `ModeDeclarations` on the side of the mode manager shall match the supported range of the `ImplementationDataType` used for representing `ModeDeclarations` on the side of the mode user (see [constr_1075]).

]

[constr_1169] Allowed values for Trigger.swImplPolicy

Imposition time: IT_CpgExe

[The **only** allowed values for the attribute `Trigger.swImplPolicy` are either `STANDARD` (in which case the `Trigger` processing does not use a queue) or `QUEUED` (in which case the processing of `Triggers` positively uses a queue).

]

[constr_1170] Existence of attribute EndToEndDescription.maxDeltaCounterInit for PROFILE_01

Status: OBSOLETE

Imposition time: IT_CpgExe

[If the value of attribute `EndToEndDescription.category` is set to `PROFILE_01` and either

- the condition described in [TPS_SWCT_01850] concerning the referenced `VariableDataPrototype` is not fulfilled or

- attribute `RPortPrototype.requiredComSpec.maxDeltaCounterInit` does not exist,

then attribute `EndToEndProtection.endToEndProfile.maxDeltaCounterInit` **shall exist**.

]

[constr_1171] Existence of attribute `EndToEndDescription.maxDeltaCounterInit` for `PROFILE_02`

Status: OBSOLETE

Imposition time: IT_CpgExe

[If the value of `EndToEndDescription.category` is set to `PROFILE_02` **and either**

- the condition described in [TPS_SWCT_01850] concerning the referenced `VariableDataPrototype` is not fulfilled **or**
- attribute `RPortPrototype.requiredComSpec.maxDeltaCounterInit` does not exist,

then attribute `EndToEndProtection.endToEndProfile.maxDeltaCounterInit` **shall exist**.

]

[constr_1172] Allowed values of `SwCalibrationAccessEnum` for `ModeDeclarationGroupPrototype`

Imposition time: IT_CpgExe

[The only allowed values of `swCalibrationAccess` aggregated by `ModeDeclarationGroupPrototype` are

- `notAccessible` and
- `readOnly`.

]

[constr_1173] Applicability of `AutosarParameterRef` referencing a `VariableDataPrototype`

Imposition time: IT_CpgExe

[A reference from `AutosarParameterRef` to `VariableDataPrototype` is **only** applicable if the `AutosarParameterRef` is used in the context of `SwAxisGrouped`.

]

[constr_1174] PortInterfaces used in the context of CompositionSwComponentTypes cannot refer to AUTOSAR services

Imposition time: IT_CompSwcT

[CompositionSwComponentTypes shall not own PortPrototypes typed by PortInterfaces where the attribute isService is set to true.

]

[constr_1175] Depending on its category, CompuMethod shall refer to a unit

Imposition time: IT_CpgExe

[As a CompuMethod specifies the conversion between the physical world and the numerical values, it shall refer to a unit unless the CompuMethod's category is one of TEXTTABLE, BITFIELD_TEXTTABLE, or IDENTICAL.

]

[constr_1176] Compatibility of CompuScales of category LINEAR and RAT_FUNC

Imposition time: IT_RteGen

[CompuScales of category LINEAR and RAT_FUNC are considered compatible if they yield the same conversion.

]

[constr_1177] Allowed targetCategory for SwPointerTargetProps

Imposition time: IT_CpgExe

[If the value of attribute targetCategory exists, then it shall be set to one of the following values:

- TYPE_REFERENCE
- FUNCTION_REFERENCE
- VALUE (only applicable if the SwPointerTargetProps.swDataDefProps refers to a SwBaseType where attribute nativeDeclaration is set to the value "void")

]

[constr_1178] Existence of attributes of SwDataDefProps in the context of ImplementationDataType

Imposition time: IT_CpgExe

[For the sake of removing possible sources of ambiguity, SwDataDefProps used in the context of ImplementationDataType can **only have one of**

- baseType

- `swPointerTargetProps`
- `implementationDataType`

]

[constr_1181] Numerical values used in `ModeDeclaration.value` and `ModeDeclarationGroup.onTransitionValue`*Imposition time:* IT_CpgExe

[The numerical values used to define the `value` attributes and the `onTransitionValue` attribute of a `ModeDeclarationGroup` shall not overlap.

]

[constr_1182] Allowed values for `InternalTriggeringPoint.swImplPolicy`*Imposition time:* IT_RteGen

[The **only** allowed values for the attribute `swImplPolicy` of meta-class `InternalTriggeringPoint` are either `STANDARD` (in which case the processing of the internal triggering does not use a queue) or `QUEUED` (in which case the processing of internal triggering positively uses a queue).

]

[constr_1183] `EndToEndProtectionVariablePrototypes` aggregated by `EndToEndProtection`*Status:* OBSOLETE*Imposition time:* IT_CpgExe

[All `EndToEndProtectionVariablePrototypes` aggregated by the same `EndToEndProtection` shall refer to the identical `sender`.

]

[constr_1184] Consistency of `rootDataPrototype` and `base` in the context of `ApplicationCompositeElementInPortInterfaceInstanceRef`*Imposition time:* IT_RteGen

[The `rootDataPrototype` referenced by `ApplicationCompositeElementInPortInterfaceInstanceRef` shall be owned by the applicable subclass of `DataInterface` referenced in the role `base`.

This implies that the `rootDataPrototype` shall be a `ParameterDataPrototype` if the `base` is a `ParameterInterface`. Otherwise, the `rootDataPrototype` shall be a `VariableDataPrototype`.

]

[constr_1185] Consistency of data types in the context of `ApplicationCompositeElementInPortInterfaceInstanceRef`

Imposition time: IT_RteGen

[The definition of attributes `contextDataPrototype` and `targetDataPrototype` shall (via the type-prototype pattern) be enclosed in the context of the definition of the data type used to type `rootDataPrototype`.

]

[constr_1186] Consistency of data types in the context of `ArVariableInImplementationDataInstanceRef`

Imposition time: IT_RteGen

[The definition of attributes `contextDataPrototype` and `targetDataPrototype` shall be enclosed in the context of the definition of the data type used to type `rootVariableDataPrototype`.

]

[constr_1187] Compatibility of `VariableDataPrototypes` or `ParameterDataPrototypes` typed by composite data types

Imposition time: IT_RteGen

[`DataPrototypes` of `ApplicationCompositeDataTypes` or `ImplementationDataTypes` of category `STRUCTURE` or `ARRAY` are compatible if one of the following conditions evaluates to true:

1. The underlying `ApplicationCompositeDataTypes` or `ImplementationDataTypes` of category `STRUCTURE` or `ARRAY` are identical
2. The underlying `ApplicationCompositeDataTypes` or `ImplementationDataTypes` of category `STRUCTURE` or `ARRAY` fulfill the following condition:
 - They consist of the same number of elements **and**
 - They are composed of compatible `AutosarDataTypes` (either `ApplicationCompositeDataTypes` or `ImplementationDataTypes` of category `STRUCTURE` or `ARRAY` **OR** `ApplicationPrimitiveDataTypes` or `ImplementationDataTypes` of category `VALUE`, `BOOLEAN`, or `STRING`) **in the same order and**
 - All attributes match exactly, except for the `shortName` of the M1 `AutosarDataType`.
3. In the context of a `DataPrototypeMapping`, for each `ApplicationCompositeElementDataPrototype` of the required `DataPrototype` a `SubElementMapping` exists such that a `ApplicationCompositeDataTypeSubElementRef` in the role `firstElement` or `secondElement` exists that references the required `ApplicationCompositeElementDataPrototype` **and**

a corresponding `ApplicationCompositeDataTypeSubElementRef` exists in the **other** role (i.e. `secondElement` or `firstElement`) that in turn references an `ApplicationCompositeElementDataPrototype` of the provided `ApplicationCompositeDataType`.

4. If and only if the `DataPrototype` is **not** typed by an `ApplicationDataType` but by an `ImplementationDataType`: in the context of a `DataPrototypeMapping`, for each `ImplementationDataTypeElement` of the required `DataPrototype` a `SubElementMapping` exists such that a `ImplementationDataTypeSubElementRef` in the role `firstElement` or `secondElement` exists that references the required `ImplementationDataTypeElement` **and** a corresponding `ImplementationDataTypeSubElementRef` exists in the **other** role (i.e. `secondElement` or `firstElement`) that in turn references an `ImplementationDataTypeElement` of the provided `ImplementationDataType`.

]

[constr_1188] Existence of `ReceiverComSpec.replaceWith`

Imposition time: IT_CpgExe

[The aggregation of `VariableAccess` in the role `ReceiverComSpec.replaceWith` shall exist **if and only if at least one of the following conditions is fulfilled**:

- Attribute `ReceiverComSpec.handleOutOfRange` is set to the value `externalReplacement`.
- Attribute `SenderReceiverInterface.invalidationPolicy.handleInvalid` is set to the value `externalReplacement`.

]

[constr_1190] Only one mapping for composite to primitive use case

Imposition time: IT_RteGen

[In the case described by [TPS_SWCT_01195] only one `subElementMapping` shall exist at the enclosing `DataPrototypeMapping`.

]

[constr_1191] Value of `Limit` shall yield a numerical value

Imposition time: IT_CpgExe

[After all variability is bound, the content obtained from a limit shall yield a numerical value.

]

[constr_1192] Compatibility of "IDENTICAL" to "RAT_FUNC" or "LINEAR"

Imposition time: IT_RteGen

[Similar to [constr_1176], a `CompuScale` where the `category` of the enclosing `CompuMethod` is set to `IDENTICAL` is considered compatible to a `CompuScale` where the `category` of the enclosing `CompuMethod` is set to `RAT_FUNC` or `LINEAR` if the following rule applies:

$$int = \frac{N_0 + N_1 * phys + N_i * phys^i}{D_0 + D_1 * phys + D_i * phys^i} = phys$$

]

[constr_1193] `ModeDeclaration` shall be referenced by at least one `ModeTransition` in the role `enteredMode`

Imposition time: IT_RteGen

[For each `ModeDeclaration` at least one `ModeTransition` shall reference the `ModeDeclaration` in the role `enteredMode`.

This constraint shall apply **only** if there is at least one `ModeTransition` defined in the context of the enclosing `ModeDeclarationGroup` and it shall **not** apply to the `initialMode`.

]

[constr_1194] Identical `ModeTransitions`

Imposition time: IT_RteGen

[Two `ModeDeclarationGroups` contain identical `modeTransitions` if and only if

1. For each `ModeTransition` defined in the context of the mode provider one `ModeTransition` with the same `shortName` is defined in the context of the mode user.
2. Each pair of `ModeTransitions` in both `ModeDeclarationGroups` identified by their respective `shortName` have identical targets (in terms of the `shortName` of the referenced `ModeDeclaration`) of the references `enteredMode` and `exitedMode`.

]

[constr_1195] `SwcModeSwitchEvent` and the definition of `ModeTransition`

Imposition time: IT_RteGen

[For each pair of `ModeDeclarations` referenced by a `SwcModeSwitchEvent` with attribute `activation` set to `onTransition` a `ModeTransition` shall be defined in the corresponding direction (i.e. from `exitedMode` to `enteredMode`). This constraint

shall only apply if the respective `ModeDeclarationGroup` defines at least one `modeTransition`.

]

[constr_1196] Existence of `networkRepresentation` vs. `compositeNetworkRepresentation`

Imposition time: IT_CpgExe

[If a `ReceiverComSpec` or `SenderComSpec` aggregates `networkRepresentation` it shall **not** aggregate `compositeNetworkRepresentation` (and vice versa).

]

[constr_1197] Existence of `compositeNetworkRepresentation` shall be comprehensive

Imposition time: IT_CpgExe

[If at least one `compositeNetworkRepresentation` exists then for each leaf `ApplicationCompositeElementDataPrototype` of the affected `ApplicationCompositeDataType` exactly one `compositeNetworkRepresentation` shall be defined.

For each such `compositeNetworkRepresentation`, attributes `leafElement` and `networkRepresentation` shall exist.

]

[constr_1200] Queued communication is not applicable for `dataElements` owned by `PRPortPrototype`

Imposition time: IT_CpgExe

[The `swImplPolicy` shall not be set to `queued` for any `dataElement` owned by a `PRPortPrototype`.

]

[constr_1202] Supported connections by `AssemblySwConnector` between `PortPrototypes` typed by a `SenderReceiverInterface` or `NvDataInterface`

Imposition time: IT_CompSwcT

[

	<code>RPortPrototype</code>	<code>PPortPrototype</code>	<code>PRPortPrototype</code>
<code>RPortPrototype</code>	No	Yes	Yes
<code>PPortPrototype</code>	Yes	No	Yes
<code>PRPortPrototype</code>	Yes	Yes	Yes

]

[constr_1203] Supported connections by [DelegationSwConnector](#) between [PortPrototypes](#) typed by a [SenderReceiverInterface](#) or [NvDataInterface](#)

Imposition time: IT_CompSwcT

[

innerPort	outerPort		
	RPortPrototype	PPortPrototype	PRPortPrototype
RPortPrototype	Yes	No	Yes
PPortPrototype	No	Yes	Yes
PRPortPrototype	Yes	Yes	Yes

]

[constr_1204] Supported connections by [AssemblySwConnector](#) between [PortPrototypes](#) typed by a [ClientServerInterface](#), [ModeSwitchInterface](#), or [TriggerInterface](#)

Imposition time: IT_CompSwcT

[

	RPortPrototype	PPortPrototype	PRPortPrototype
RPortPrototype	No	Yes	Yes
PPortPrototype	Yes	No	No
PRPortPrototype	Yes	No	No

]

[constr_1205] Supported connections by [DelegationSwConnector](#) between [PortPrototypes](#) typed by a [ClientServerInterface](#), [ModeSwitchInterface](#), or [TriggerInterface](#)

Imposition time: IT_CompSwcT

[

innerPort	outerPort		
	RPortPrototype	PPortPrototype	PRPortPrototype
RPortPrototype	Yes	No	No
PPortPrototype	No	Yes	No
PRPortPrototype	No	Yes	No

]

[constr_1209] Mapping of ModeDeclarations of mode user to ModeDeclaration of mode manager

Imposition time: IT_RteGen

[A configuration that maps **several** ModeDeclarations representing modes of a mode user to **one** ModeDeclaration representing a mode of a mode manager shall be rejected.

]

[constr_1210] Mapping of ModeDeclarations of mode user to all ModeDeclarations of mode manager

Imposition time: IT_RteGen

[If a ModeDeclarationMapping exists that references a ModeDeclaration representing a mode of the mode manager, then ModeDeclarationMappings shall exist that map all modes of the mode manager to modes of the mode user.

]

[constr_1211] Constraints of maxNoNewOrRepeatedData in PROFILE_01

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_01, the applicable range of values for EndToEndDescription.maxNoNewOrRepeatedData is [0 .. 14].

]

[constr_1212] Constraints of syncCounterInit in PROFILE_01

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_01, the applicable range of values for EndToEndDescription.syncCounterInit is [0 .. 14].

]

[constr_1213] Constraints of maxNoNewOrRepeatedData in PROFILE_02

Status: OBSOLETE

Imposition time: IT_CpgExe

[In PROFILE_02, the applicable range of values for EndToEndDescription.maxNoNewOrRepeatedData and ReceiverComSpec.maxNoNewOrRepeatedData is [0 .. 15].

]

[constr_1214] Constraints of `syncCounterInit` in `PROFILE_02`

Status: OBSOLETE

Imposition time: IT_CpgExe

[In `PROFILE_02`, the applicable range of values for `EndToEndDescription.syncCounterInit` and `ReceiverComSpec.syncCounterInit` is [0 .. 15].

]

[constr_1215] Existence of attribute `EndToEndDescription.maxNoNewOrRepeatedData` for `PROFILE_01`

Status: OBSOLETE

Imposition time: IT_CpgExe

[If the value of attribute `EndToEndDescription.category` is set to `PROFILE_01` and either

- the condition described in [TPS_SWCT_01851] concerning the referenced `VariableDataPrototype` is not fulfilled or
- attribute `RPortPrototype.requiredComSpec.maxNoNewOrRepeatedData` does not exist,

then attribute `EndToEndProtection.endToEndProfile.maxNoNewOrRepeatedData` shall exist.

]

[constr_1216] Existence of attribute `EndToEndDescription.syncCounterInit` for `PROFILE_01`

Status: OBSOLETE

Imposition time: IT_CpgExe

[If the value of attribute `EndToEndDescription.category` is set to `PROFILE_01` and either

- the condition described in [TPS_SWCT_01852] concerning the referenced `VariableDataPrototype` is not fulfilled or
- attribute `RPortPrototype.requiredComSpec.syncCounterInit` does not exist,

then the attribute `EndToEndProtection.endToEndProfile.syncCounterInit` shall exist.

]

[constr_1217] Existence of attribute `EndToEndDescription.maxNoNewOrRepeatedData` for `PROFILE_02`

Status: OBSOLETE

Imposition time: IT_CpgExe

[If the value of attribute `EndToEndDescription.category` is set to `PROFILE_02` and either

- the condition described in [TPS_SWCT_01851] concerning the referenced `VariableDataPrototype` is not fulfilled or
- attribute `RPortPrototype.requiredComSpec.maxNoNewOrRepeatedData` does not exist,

then attribute `EndToEndProtection.endToEndProfile.maxNoNewOrRepeatedData` shall exist.

]

[constr_1218] Existence of attribute `EndToEndDescription.syncCounterInit` for `PROFILE_02`

Status: OBSOLETE

Imposition time: IT_CpgExe

[If the value of attribute `EndToEndDescription.category` is set to `PROFILE_02` and either

- the condition described in [TPS_SWCT_01852] concerning the referenced `VariableDataPrototype` is not fulfilled or
- attribute `RPortPrototype.requiredComSpec.syncCounterInit` does not exist,

then the attribute `EndToEndProtection.endToEndProfile.syncCounterInit` shall exist.

]

[constr_1219] Invalidation depends on the value of `swImplPolicy`

Imposition time: IT_CpgExe

[If the value of `swImplPolicy` of a `SenderReceiverInterface.dataElement` is set to the value `SwImplPolicyEnum.queued`, then the enclosing `SenderReceiverInterface` shall not aggregate in the role `invalidationPolicy` an `InvalidationPolicy`

- that references the `dataElement` and
- where the value of `InvalidationPolicy.handleInvalid` is set to anything else than `HandleInvalidEnum.dontInvalidate`.

]

[constr_1220] Compatibility of `SwBaseType`

Imposition time: IT_RteGen

[Two `SwBaseTypes` are compatible if and only if attributes

- `baseTypeSize` respectively
- `byteOrder`,
- `memAlignment`,
- `baseTypeEncoding`, and
- `nativeDeclaration`

have identical values.

]

[constr_1221] `DataPrototype` is typed by an `ApplicationPrimitiveDataType`

Imposition time: IT_CpgExe

[If a `DataPrototype` is typed by an `ApplicationPrimitiveDataType`, its `initValue` shall be provided by an `ApplicationValueSpecification`.

If the underlying `ApplicationPrimitiveDataType` represents an enumeration, the value provided shall match to one of the applicable text values (`vt`, `shortLabel`, `symbol`) defined by the applicable `CompuScales`.

]

[constr_1222] `category` of an `AutosarDataType` used to type a `DataPrototype` is set to `STRING`

Imposition time: IT_CpgExe

[If the `category` of an `AutosarDataType` used to type a `DataPrototype` is set to `STRING`, the `ApplicationValueSpecification` used to initialize the `DataPrototype` shall be of `category STRING`.

]

[constr_1223] `DataPrototype` is typed by an `ApplicationRecordDataType`

Imposition time: IT_CpgExe

[If a `DataPrototype` is typed by an `ApplicationRecordDataType`, the corresponding `initValue` shall be provided by a `RecordValueSpecification`.

]

[constr_1224] DataPrototype is typed by an ApplicationArrayDataType

Imposition time: IT_CpgExe

[If a `DataPrototype` is typed by an `ApplicationArrayDataType`, the corresponding `initValue` shall be provided by an `ArrayValueSpecification` (that may contain an `ApplicationRuleBasedValueSpecification`).

]

[constr_1225] DataPrototype is typed by an ImplementationDataType that references a CompuMethod of category TEXTTABLE or BITFIELD_TEXTTABLE

Imposition time: IT_CpgExe

[If a `DataPrototype` is typed by an `ImplementationDataType` that references a `CompuMethod` of category `TEXTTABLE` or `BITFIELD_TEXTTABLE` the applicable `ValueSpecification` shall be a `TextValueSpecification`.

In this case the value provided shall match to one of the applicable text values (`vt`, `shortLabel`, `symbol`) defined by the applicable `CompuScales`.

]

[constr_1226] Applicable range for ExecutableEntityActivationReason.bitPosition

Imposition time: IT_CpgExe

[The value of attribute `ExecutableEntityActivationReason.bitPosition` shall be in the range of 0 .. 31.

]

[constr_1227] Value of attribute ExecutableEntityActivationReason.bitPosition shall be unique

Imposition time: IT_CpgExe

[The value of attributes `ExecutableEntityActivationReason.bitPosition` and `ExecutableEntityActivationReason.symbol` shall be unique in the context of the enclosing `RunnableEntity`.

]

[constr_1228] RTEEvent that is referenced by a WaitPoint in the role trigger shall not reference ExecutableEntityActivationReason

Imposition time: IT_RteGen

[An `RTEEvent` that is referenced by a `WaitPoint` in the role `trigger` shall not reference `ExecutableEntityActivationReason` in the role `activationReason-Representation`.

]

[constr_1229] category of ImplementationDataType boils down to VALUE

Imposition time: IT_CpgExe

[An `ImplementationDataType` qualifies as an Integral Primitive Type if and only if either

- its `category` is `VALUE` or `TYPE_REFERENCE` that eventually boils down to `VALUE` or
- its `category` is `ARRAY` and it has only one `subElement` and one of the following conditions applies:
 - `subElement.category` is set to `VALUE` or `TYPE_REFERENCE` that eventually boils down to `VALUE` and the `subElement` refers to a `SwBaseType` where `baseTypeSize` is set to the value 8 and the `baseTypeEncoding` is set to `NONE`.
 - `subElement.category` is set to `TYPE_REFERENCE` and the `swDataDefProps.implementationDataType` literally represents the Platform Data Type named "uint8".
 - `subElement.category` is set to `TYPE_REFERENCE` and the attribute `swDataDefProps.implementationDataType.shortName` is set to "uint8" and `swDataDefProps.baseType.baseTypeDefinition.nativeDeclaration` does not exist.

]

[constr_1230] ApplicationDataType that qualifies for Integral Primitive Type

Imposition time: IT_CpgExe

[An `ApplicationDataType` qualifies as an Integral Primitive Type if and only if **all** the following conditions apply:

- `ApplicationDataType.category` is set to `BOOLEAN`, `VALUE`, `STRING`, or `ARRAY`
- in the applicable scope a `DataTypeMap` is available that refers to the given `ApplicationDataType`
- the found `DataTypeMap` refers to an `ImplementationDataType` that fulfills the requirements of [constr_1229]

]

[constr_1231] ConsistencyNeeds aggregated by CompositionSwComponentType

Imposition time: IT_CompSwcT

[If `ConsistencyNeeds` are aggregated by a `CompositionSwComponentType` the associations stereotyped `<<instanceRef>>` may only refer to context and target elements within the context of this `CompositionSwComponentType`.

]

[constr_1232] ConsistencyNeeds aggregated by AtomicSwComponentType

Imposition time: IT_CpgExe

[If `ConsistencyNeeds` are aggregated by a `AtomicSwComponentType` the associations stereotyped `<<instanceRef>>` may only refer to context and target elements within the context of this `AtomicSwComponentType`.

]

[constr_1233] InstantiationTimingEventProps shall only reference TimingEvent

Imposition time: IT_RteGen

[An `InstantiationTimingEventProps` shall only reference `TimingEvent` in the role `refinedEvent`. A reference to other kinds of `RTEEvents` is not supported.

]

[constr_1234] Value of RunnableEntity.symbol

Imposition time: IT_RteGen

[The value of a `RunnableEntity.symbol` owned by an `NvBlockSwComponentType` that is triggered by an `OperationInvokedEvent` shall only be taken from the set of API names associated with the `NvM`.

]

[constr_1237] Scope of mapped ClientServerOperations in the context of a ClientServerOperationMapping

Imposition time: IT_RteGen

[All `ClientServerOperations` referenced by a `ClientServerOperationMapping` in the role `firstOperation` shall belong to exactly one `ClientServerInterface`.

All `ClientServerOperations` referenced by a `ClientServerOperationMapping` in the role `secondOperation` shall belong to exactly one other `ClientServerInterface`.

]

[constr_1238] Scope of mapped `ApplicationErrors` in the context of a `ClientServerOperationMapping`

Imposition time: IT_RteGen

[All `ApplicationErrors` referenced by a `ClientServerApplicationErrorMapping` in the role `firstApplicationError` shall belong to exactly one `ClientServerInterface`.

All `ApplicationErrors` referenced by a `ClientServerApplicationErrorMapping` in the role `secondApplicationError` shall belong to exactly one other `ClientServerInterface`.

]

[constr_1240] Consistency of `ArgumentDataPrototypes` within the context of a `ClientServerOperationMapping`

Imposition time: IT_RteGen

[Unless a `ClientServerOperationMapping.firstToSecondDataTransformation` exists, for each `argument` owned by

- a `ClientServerOperationMapping.firstOperation` and
- `ClientServerOperationMapping.secondOperation`,

a reference in the role

- `ClientServerOperationMapping.argumentMapping.firstDataPrototype` or
- `ClientServerOperationMapping.argumentMapping.secondDataPrototype`

shall exist, originated by one of the `ClientServerOperationMapping.argumentMappings` owned by the mentioned `ClientServerOperationMapping`.

]

[constr_1241] Compound Primitive Data Types and `invalidValue`

Imposition time: IT_CpgExe

[Compound Primitive Data Types that have set the value of `category` other than `STRING` shall **not** define `invalidValue`.

]

[constr_1242] Restriction of `invalidValue` for `ApplicationPrimitiveDataType` of category `STRING`

Imposition time: IT_CpgExe

[`invalidValue` for `ApplicationPrimitiveDataType` of category `STRING` (`[constr_1241]` applies) is restricted to be either a compatible `ApplicationValueSpecification` or a `ConstantReference` that in turn points to a compatible `ApplicationValueSpecification`.

]

[constr_1243] `NumericalOrText` shall either define `vf` or `vt`

Imposition time: IT_CpgExe

[Within the context of one `NumericalOrText`, **either** the attribute `vf` **or** the attribute `vt` shall be defined. The existence of both attributes at the same time is not permitted.

]

[constr_1244] `DataPrototypes` used in application software shall not be typed by `C` enums

Imposition time: IT_CpgExe

[A `ImplementationDataType` that is used to type a `DataPrototype` owned by an `AtomicSwComponentType` shall not set `swDataDefProps.additionalNativeTypeQualifier` to `enum`.

]

[constr_1245] Consideration of `ModeTransitions` for the compatibility of `ModeDeclarationGroups`

Imposition time: IT_RteGen

[One of the following conditions for the consideration of `ModeTransitions` for the compatibility of `ModeDeclarationGroups` shall apply:

- **Either** the mode provider **or** the mode user define `ModeTransitions`.
- The `ModeTransitions` defined in the context of the mode provider are **identical** to the `ModeTransitions` defined in the context of the mode user **or** a `ModeDeclarationMapping` mapping is applied.

]

[constr_1246] Consistency of `firstMode` and `secondMode` in the scope of one `ModeDeclarationMappingSet`

Imposition time: IT_RteGen

[Within the scope of one `ModeDeclarationMappingSet`,

- all `firstModes` shall belong to one and only one `ModeDeclarationGroup` and
- all `secondModes` shall belong to one and only one **other** `ModeDeclarationGroup`.

]

[constr_1247] Consistency of `ModeDeclarationMappingSet` with respect to the referenced `firstModeGroup` and `secondModeGroup`*Imposition time:* IT_RteGen

[If a `ModeDeclarationGroupPrototypeMapping.modeDeclarationMappingSet` exists, then

- the `ModeDeclarationGroup` owning the `modeDeclarations` referenced in the role `firstMode` shall be the `type` of the `ModeDeclarationGroupPrototypeMapping.firstModeGroup` and
- the `ModeDeclarationGroup` owning the `modeDeclarations` referenced in the role `secondMode` shall be the `type` of the `ModeDeclarationGroupPrototypeMapping.secondModeGroup`.

]

[constr_1248] Compatibility of `PortPrototypes` of different `DataInterfaces` in the context of a `PassThroughSwConnector`*Imposition time:* IT_RteGen

[`PortPrototypes` of different `DataInterfaces` are considered compatible if and only if

1. For **at least one** `VariableDataPrototype` or `ParameterDataPrototype` defined in the context of the `DataInterface` of the required outer `PortPrototype` a compatible `VariableDataPrototype` or `ParameterDataPrototype` exists in the `DataInterface` of the provided outer `PortPrototype`.

Either the `shortName` of `VariableDataPrototypes` and `ParameterDataPrototypes` are used to identify the pair **or** a `PortInterfaceMapping` exists that defines which differently named elements of `PortInterfaces` correlate with each other.

2. For each such pair, the values of the `PortInterface.isService` attributes are identical.

]

[constr_1249] Compatibility of ModeSwitchInterfaces in the context of a PassThroughSwConnector

Imposition time: IT_RteGen

[PortPrototypes of different ModeSwitchInterfaces are considered compatible if and only if

1. For the ModeDeclarationGroupPrototype defined in the context of the ModeSwitchInterface of the required outer PortPrototype a compatible ModeDeclarationGroupPrototype exists in the ModeSwitchInterface of the provided outer PortPrototype.

Either the shortNames of the ModeDeclarationGroupPrototypes are used to identify the pair **or** a ModeInterfaceMapping exists that maps the corresponding ModeDeclarationGroupPrototypes.

2. For each such pair, the values of the PortInterface.isService attributes are identical.

]

[constr_1250] Compatibility of ClientServerInterfaces in the context of a PassThroughSwConnector

Imposition time: IT_RteGen

[PortPrototypes of different ClientServerInterfaces are considered compatible if and only if

1. For **at least one** ClientServerOperation defined in the context of the ClientServerInterface of the provided outer PortPrototype a compatible ClientServerOperation exists in the ClientServerInterface of the required outer PortPrototype.

Either the shortNames of the ClientServerOperations are used to identify the pair **or** a ClientServerInterfaceMapping exists that maps the corresponding ClientServerOperations.

2. For each such pair, the values of the PortInterface.isService attributes are identical.

]

[constr_1251] Compatibility of PortPrototypes of TriggerInterfaces in the context of a PassThroughSwConnector

Imposition time: IT_RteGen

[PortPrototypes of different TriggerInterfaces are considered compatible if and only if

1. For **at least one** `Trigger` defined in the context of the `TriggerInterface` of the required outer `PortPrototype` a compatible `Trigger` exists in the `TriggerInterface` of the provided outer `PortPrototype`.

Either the `shortName` of `Triggers` are used to identify the pair **or** a `TriggerInterfaceMapping` exists that refers to one of the `Triggers` in the role `firstTrigger` and to the other in the role `secondTrigger`.

2. For each such pair, the values of the `PortInterface.isService` attributes are identical.

]

[constr_1252] Creation of a loop involving a `PassThroughSwConnector` is not allowed

Imposition time: IT_CompSwcT

[A `PassThroughSwConnector` is not allowed if the required outer `PortPrototype` is directly or indirectly connected to the provided outer `PortPrototype` without the placement of a `SwComponentPrototype` typed by an `AtomicSwComponentType` in the chain of `SwConnectors`.

]

[constr_1253] Allowed multiplicities for attributes of `VariationPointProxy` depending on the applicable binding time and the value of `VariationPointProxy.category`

Imposition time: IT_CpgExe

[

BindingTime	category	Allowed Attribute Multiplicity
PreBuild	VALUE	<code>valueAccess</code> [1], <code>implementationDataType</code> [0..1]
	CONDITION	<code>conditionAccess</code> [1]
PostBuild	VALUE	<code>postBuildValueAccess</code> [1], <code>implementationDataType</code> [1]
	CONDITION	<code>postBuildVariantCondition</code> [1..*], <code>conditionAccess</code> [0..1]

]

[constr_1254] Definition of a pointer to a pointer

Imposition time: IT_CpgExe

[AUTOSAR does **not** support the definition of a pointer to a pointer by defining an `ImplementationDataType` of category `DATA_REFERENCE` that aggregates `SwDataDefProps` in the role `swDataDefProps` that in turn aggregate `SwPointerTargetProps` in the role `swPointerTargetProps` with attribute `targetCategory` set to `DATA_REFERENCE` that in turn aggregates `SwDataDefProps` in the role `swDataDefProps` that aggregates `SwPointerTargetProps` in the role `swPointer-`

TargetProps that references an ImplementationDataType of category e.g. VALUE.

]

[constr_1255] ApplicationPrimitiveDataTypes of category BOOLEAN and STRING

Imposition time: IT_CpgExe

[If a Unit is referenced from within SwDataDefProps and/or PhysConstrs owned by an ApplicationPrimitiveDataTypes of category BOOLEAN and STRING it is required that this Unit represents a meaningless unit, i.e. the referenced physicalDimension shall not define any exponent value other than 0.

]

[constr_1256] Acknowledgement feedback in n:1 writer case

Imposition time: IT_CpgExe

[Within the scope of one SwcInternalBehavior, it is **not** allowed that two or more aggregated RunnableEntitys own either dataSendPoints or dataWriteAccesss that in turn point to the identical accessedVariable.autosarVariable.targetDataPrototype if the attribute transmissionAcknowledge exists in the context of the SenderComSpec owned by the dataSendPoint.accessedVariable.autosarVariable.portPrototype (or the respective construct for dataWriteAccess) that also refers to said dataElement.

]

[constr_1257] No WaitPoints allowed

Imposition time: IT_RteGen

[A RunnableEntity referenced by an InitEvent in the role startOnEvent shall not aggregate a.

]

[constr_1258] Value of minimumStartInterval for RunnableEntitys triggered by an InitEvent

Imposition time: IT_RteGen

[The value of the attribute ExecutableEntity.minimumStartInterval for a RunnableEntitys that is triggered by an InitEvent shall always be set to 0.

]

[constr_1259] Aggregation of `AsynchronousServerCallPoint` and `AsynchronousServerCallResultPoint`

Imposition time: IT_RteGen

[A `RunnableEntity` referenced by an `InitEvent` in the role `startOnEvent` may aggregate an `AsynchronousServerCallPoint` but it shall not aggregate an `AsynchronousServerCallResultPoint`.

]

[constr_1260] No mode disabling for `InitEvents`

Imposition time: IT_RteGen

[An `InitEvent` shall not have a reference to a `ModeDeclaration` in the role `disabledMode`.

]

[constr_1261] Applicability for `EndToEndDescription.dataIdNibbleOffset`

Status: OBSOLETE

Imposition time: IT_CpgExe

[`EndToEndDescription.dataIdNibbleOffset` shall be used **only** if `EndToEndDescription.dataIdMode` is set to the value 3 **and** at the same time `EndToEndDescription.category` is set to `PROFILE_01`.

]

[constr_1263] Existence of `ModeErrorBehavior.defaultMode`

Imposition time: IT_RteGen

[The optional attribute `ModeErrorBehavior.defaultMode` **shall exist** if the value of the attribute `ModeErrorBehavior.errorReactionPolicy` is set to `defaultMode`.

]

[constr_1268] `ArgumentDataPrototype.direction` shall be preserved in a `ClientServerOperationMapping`

Imposition time: IT_RteGen

[Within the context of a `ClientServerOperationMapping`, the value of the argument `ArgumentDataPrototype.direction` of two mapped `ArgumentDataPrototype` shall be identical.

]

[constr_1269] Number of arguments shall be preserved in a ClientServerOperationMapping

Imposition time: IT_RteGen

[Within the context of a `ClientServerOperationMapping`, the number of arguments of `firstOperation` and `secondOperation` shall be identical.

]

[constr_1270] ArgumentDataPrototype shall be mapped only once in a ClientServerOperationMapping

Imposition time: IT_RteGen

[Within the context of a `ClientServerOperationMapping`, each argument shall only be referenced **once** in the role `firstDataPrototype` or `secondDataPrototype`.

]

[constr_1271] RecordValueSpecification.fields shall be identical to the number of ApplicationRecordDataType.elements

Imposition time: IT_CpgExe

[The initialization of a `DataPrototype` typed by an `ApplicationRecordDataType` by means of a `RecordValueSpecification` shall exactly match the structure of the `ApplicationRecordDataType`.

For this means, it is required that the number of `RecordValueSpecification.fields` shall be identical to the number of `ApplicationRecordDataType.elements`.

]

[constr_1272] RecordValueSpecification.fields shall be identical to the number of subElements of ImplementationDataType of category STRUCTURE

Imposition time: IT_CpgExe

[The initialization of an `DataPrototype` typed by an `ImplementationDataType` of category `STRUCTURE` by means of a `RecordValueSpecification` shall exactly match the structure of the `ImplementationDataType` of category `STRUCTURE`.

For this means, it is required that the number of `RecordValueSpecification.fields` shall be identical to the number of `ImplementationDataType.subElements`.

]

[constr_1273] Rules for the initialization of `ApplicationArrayType` by means of `ArrayValueSpecification`

Imposition time: IT_CpgExe

[The following rules apply for the initialization of a `DataPrototype` typed by an `ApplicationArrayType` by means of an `ArrayValueSpecification`:

- If the attribute `ApplicationArrayType.element.arraySizeSemantics` is set to **fixedSize** then the `ArrayValueSpecification` shall exactly match the structure of the `ApplicationArrayType`.

This means that the number of `ArrayValueSpecification.elements` shall be identical to the value of `ApplicationArrayType.element.maxNumberOfElements`.

- If the attribute `ApplicationArrayType.element.arraySizeSemantics` is set to **variableSize** and the `ArrayValueSpecification` **does not define** attribute `intendedPartialInitializationCount` then `ArrayValueSpecification` shall **exactly** match the structure of the `ApplicationArrayType`.

This means that the number of `ArrayValueSpecification.elements` shall be identical to the value of `ApplicationArrayType.element.maxNumberOfElements`.

- If the attribute `ApplicationArrayType.element.arraySizeSemantics` is set to **variableSize** and the `ArrayValueSpecification` specifies a value for attribute `intendedPartialInitializationCount` then `ArrayValueSpecification` shall contain **exactly** `intendedPartialInitializationCount` elements.

This includes the case that the value of `intendedPartialInitializationCount` is set to 0 (i.e. "empty" initialization) and the case that the `intendedPartialInitializationCount` is set to the value of the respective `ApplicationArrayElement.maxNumberOfElements` (i.e. "full" initialization).

]

[constr_1274] Rules for the initialization of array-shaped `ImplementationDataType` with a fixed size by means of `ArrayValueSpecification`

Imposition time: IT_CpgExe

[The following rule applies for the initialization of a `DataPrototype` typed by an `ImplementationDataType` of category `ARRAY` where attribute `ImplementationDataType.subElement.arraySizeSemantics` is set to **fixedSize** by means of an `ArrayValueSpecification`: the `ArrayValueSpecification` shall exactly match the structure of the `ImplementationDataType`.

This means that the number of `ArrayValueSpecification.elements` shall be identical to the value of `ImplementationDataType.subElement.arraySize`.

]

[constr_1277] `SwDataDefProps.swImplPolicy` of a `VariableDataPrototype` referenced by a `VariableAccess` aggregated in the role `dataReceivePointByValue`

Imposition time: IT_CpgExe

[The `SwDataDefProps.swImplPolicy` of a `VariableDataPrototype` referenced by a `VariableAccess` aggregated in the role `dataReceivePointByValue` shall not be set to `queued`.

]

[constr_1278] `PhysConstrs` references a `Unit`

Imposition time: IT_RteGen

[`DataConstrs` are only compatible if the `DataConstr.dataConstrRule.physConstrs.unit` are compatible or neither `DataConstr.dataConstrRule.physConstrs.unit` exist.

]

[constr_1279] Unmapped elements of `ApplicationCompositeDataTypes` or `ImplementationDataTypes` and the attribute `swImplPolicy`

Imposition time: IT_RteGen

[If the attribute `swImplPolicy` is set to `queued`, then it is not allowed to have unmapped elements of `ApplicationCompositeDataTypes` or `ImplementationDataTypes` of category `STRUCTURE` or `ARRAY` on the "target" end.

]

[constr_1280] Unmapped `dataElement` on the "target" end shall have an `initValue`

Imposition time: IT_RteGen

[If elements of `ApplicationCompositeDataTypes` or `ImplementationDataTypes` of category `STRUCTURE` or `ARRAY` are not considered in a `SubElementMapping` and the `NonqueuedReceiverComSpec` is aggregated by an `AbstractRequiredPortPrototype` referenced by the "target" end, then the enclosing `dataElement` shall have an `initValue`.

]

[constr_1282] Restriction concerning the usage of `RuleBasedValueSpecification` or a `ReferenceValueSpecification` for the specification of an `invalidValue`

Imposition time: IT_CpgExe

[The aggregation of a `RuleBasedValueSpecification` or a `ReferenceValueSpecification` for the definition of a `ApplicationPrimitiveDataType.swDataDefProps.invalidValue` is not supported.

]

[constr_1284] Limitation of the use of `TextValueSpecification`

Imposition time: IT_CpgExe

[`TextValueSpecification` shall **only** be used in the context of an `AutosarDataType` that references a `CompuMethod` in the role `ImplementationDataType.swDataDefProps.compuMethod` of category `TEXTTABLE` and `BITFIELD_TEXTTABLE`.

]

[constr_1285] Applicability of roles vs. `PortPrototypes`

Imposition time: IT_RteGen

[The aggregation of `AutosarVariableRef` aggregated by `NvBlockDataMapping` in the roles `writtenNvData`, `writtenReadNvData`, or `readNvData` is subject to limitation, depending on the applicable subclass of `PortPrototype`:

- The role `writtenNvData` shall only be used if the corresponding `PortPrototype` is a `RPortPrototype`
- The role `writtenReadNvData` shall only be used if the corresponding `PortPrototype` is a `PRPortPrototype`
- The role `readNvData` shall only be used if the corresponding `PortPrototype` is a `PPortPrototype`

]

[constr_1286] `serverArgumentImplPolicy` and `ArgumentDataPrototype` typed by primitive data types

Imposition time: IT_CpgExe

[The value of the attribute `ArgumentDataPrototype.serverArgumentImplPolicy` shall **not** be set to `useVoid` for an `ArgumentDataPrototype` of `direction in` that is typed by an `AutosarDataType` that boils down to a primitive C data type (see [TPS_SWCT_01565]).

]

[constr_1287] Compatibility of `SenderReceiverInterfaces` with respect to `invalidationPolicy`

Imposition time: IT_RteGen

[`VariableDataPrototypes` defined in the context of the `SenderReceiverInterface` are only compatible if the `invalidationPolicies` have the same value.

]

[constr_1288] Allowed Attributes vs. `category` for `DataPrototypes` typed by `ImplementationDataTypes`

Imposition time: IT_CpgExe

[

Attributes of SwDataDefProps	Root Element			Attribute Existence per Category						
	DataPrototype	InstantiationDataDefProps	ParameterAccess	VALUE	DATA_REFERENCE	FUNCTION_REFERENCE	TYPE_REFERENCE	STRUCTURE	UNION	ARRAY
<code>additionalNativeTypeQualifier</code>										
<code>annotation</code>	x	x	*	*	*	*	*	*	*	*
<code>baseType</code>										
<code>compuMethod</code>										
<code>dataConstr.dataConstrRule.physConstrs</code>	x	x		d/c ¹²			d/c			d/c
<code>dataConstr.dataConstrRule.internalConstrs</code>	x	x		0..1			0..1			0..1
<code>displayFormat</code>	x	x		0..1			0..1	0..1	0..1	0..1
<code>displayPresentation</code>	x	x		0..1			0..1			0..1
<code>implementationDataType</code>										
<code>invalidValue</code>										
<code>stepSize</code>	x	x		0..1						0..1
<code>swAddrMethod</code>	x	x		0..1	0..1	0..1	0..1	0..1	0..1	0..1
<code>swAlignment</code>	x	x		0..1	0..1	0..1	0..1	0..1	0..1	0..1
<code>swBitRepresentation</code>										
<code>swCalibrationAccess</code>	x	x		0..1			0..1	0..1	0..1	0..1
<code>swCalprmAxisSet</code>										
<code>swComparisonVariable</code>										
<code>swDataDependency</code>										
<code>swHostVariable</code>										
<code>swImplPolicy</code>	x			0..1	0..1	0..1	0..1	0..1	0..1	0..1
<code>swIntendedResolution</code>										

▽

¹²don't care



Attributes of SwDataDefProps	Root Element			Attribute Existence per Category						
	DataPrototype	InstantiationDataDefProps	ParameterAccess	VALUE	DATA_REFERENCE	FUNCTION_REFERENCE	TYPE_REFERENCE	STRUCTURE	UNION	ARRAY
swInterpolationMethod										
swIsVirtual										
swPointerTargetProps										
swPointerTargetProps.swDataDefProps										
swPointerTargetProps.functionPointerSignature										
swRecordLayout										
swRefreshTiming	x	x		0..1			0..1	0..1	0..1	0..1
swTextProps										
swValueBlockSize										
swValueBlockSizeMult										
unit										
valueAxisDataType										



[constr_1289] Allowed Attributes vs. category for DataPrototypes typed by ApplicationDataTypes

Imposition time: IT_CpgExe



Attributes of SwDataDefProps	Root El.			Attribute Existence per Category												
	DataPrototype	InstantiationDataDefProps	ParameterAccess	VALUE	VAL_BLK	STRUCTURE	ARRAY	STRING	BOOLEAN	COM_AXIS	RES_AXIS	CURVE	MAP	CUBOID	CUBE_4	CUBE_5
additionalNativeTypeQualifier																
annotation	x	x	x	*	*	*	*	*	*	*	*	*	*	*	*	*
baseType																
compuMethod																





Attributes of SwDataDefProps	Root EI.			Attribute Existence per Category												
	DataPrototype	InstantiationDataDefProps	ParameterAccess	VALUE	VAL_BLK	STRUCTURE	ARRAY	STRING	BOOLEAN	COM_AXIS	RES_AXIS	CURVE	MAP	CUBOID	CUBE_4	CUBE_5
dataConstr.dataConstrRule.physConstrs	x	x		0..1	0..1		0..1		0..1			0..1	0..1	0..1	0..1	0..1
dataConstr.dataConstrRule.internalConstrs	x	x		d/c ¹³	d/c		d/c		d/c			d/c	d/c	d/c	d/c	d/c
displayFormat	x	x		0..1	0..1		0..1	0..1	0..1			0..1	0..1	0..1	0..1	0..1
displayPresentation	x	x		0..1	0..1		0..1			0..1	0..1	0..1	0..1	0..1	0..1	0..1
implementationDataType																
invalidValue																
stepSize	x	x	x	0..1	0..1		0..1			0..1	0..1	0..1	0..1	0..1	0..1	0..1
swAddrMethod	x	x		0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swAlignment	x	x		0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swBitRepresentation																
swCalibrationAccess	x	x		0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swCalprmAxisSet																
swCalprmAxisSet.swCalprmAxis/SwAxisGrouped.swCalprmRef		x	x				0..1				0..1	0..1	0..1	0..1	0..1	0..1
swCalprmAxisSet.swCalprmAxis/SwAxisIndividual.swVariableRef		x	x				0..1		0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swCalprmAxisSet.swCalprmAxis/SwAxisGrouped.sharedAxisType																
swCalprmAxisSet.swCalprmAxis/SwAxisIndividual.inputVariableType																
swCalprmAxisSet.swCalprmAxis/SwAxisIndividual.unit																
swComparisonVariable			x									0..1	0..1	0..1	0..1	0..1
swDataDependency	x	x		0..1								0..1	0..1	0..1	0..1	0..1
swHostVariable																
swImplPolicy	x			0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1
swIntendedResolution																
swInterpolationMethod	x	x	x	0..1						0..1	0..1	0..1	0..1	0..1	0..1	0..1
swIsVirtual	x	x		0..1					0..1			0..1	0..1	0..1	0..1	0..1
swPointerTargetProps																
swRecordLayout																
swRefreshTiming	x	x		0..1	0..1		0..1	0..1								
swTextProps																
swValueBlockSize																
swValueBlockSizeMult																
unit																



¹³don't care

△

Attributes of SwDataDefProps	Root EI.			Attribute Existence per Category												
	DataPrototype	InstantiationDataDefProps	ParameterAccess	VALUE	VAL_BLK	STRUCTURE	ARRAY	STRING	BOOLEAN	COM_AXIS	RES_AXIS	CURVE	MAP	CUBOID	CUBE_4	CUBE_5
valueAxisDataType																

]

[constr_1290] Limitation on the number of PPortComSpecs in the context of one PPortPrototype

Imposition time: IT_CpgExe

[Within the context of one PPortPrototype, there can only be **one** (sub-class of) PPortComSpec that references a given

- dataElement (in the case of SenderComSpec),
- operation (in the case of ServerComSpec),
- modeGroup (in the case of ModeSwitchSenderComSpec),
- variable (in the case of NvProvideComSpec), or
- parameter (in the case of ParameterProvideComSpec).

]

[constr_1291] Limitation on the number of RPortComSpecs in the context of one RPortPrototype

Imposition time: IT_CpgExe

[Within the context of one RPortPrototype, there can only be **one** RPortComSpec that references a given

- dataElement (in the case of ReceiverComSpec),
- operation (in the case of ClientComSpec),
- modeGroup (in the case of ModeSwitchReceiverComSpec),
- variable (in the case of NvRequireComSpec), or
- parameter (in the case of ParameterRequireComSpec).

]

[constr_1292] Limitation on the number of RPortComSpecs/PPortComSpecs in the context of one PRPortPrototype

Imposition time: IT_CpgExe

[Within the context of one PRPortPrototype, there can only be **one** RPortComSpec and **one** PPortComSpec that references a given

- dataElement (in the case of ReceiverComSpec/SenderComSpec),
- operation (in the case of ClientComSpec/ServerComSpec),
- modeGroup (in the case of ModeSwitchReceiverComSpec/ModeSwitch-SenderComSpec), or
- variable (in the case of NvRequireComSpec/NvProvideComSpec).

]

[constr_1295] PortInterfaces and category DATA_REFERENCE

Imposition time: IT_CpgExe

[A DataPrototype defined in the context of a PortInterface used by an

- ApplicationSwComponentType or
- SensorActuatorSwComponentType

that is (after potential indirections via TYPE_REFERENCE are resolved) either typed by or mapped to an ImplementationDataType of category DATA_REFERENCE shall only be used if either the provider or the requester of the information represents

- a ServiceSwComponentType,
- a ComplexDeviceDriverSwComponentType,
- a ParameterSwComponentType,
- an NvBlockSwComponentType, or
- an EcuAbstractionSwComponentType.

]

[constr_1296] DataPrototypes used as explicitInterRunnableVariable or implicitInterRunnableVariable and category DATA_REFERENCE

Imposition time: IT_CpgExe

[A VariableDataPrototype shall not be aggregated by SwcInternalBehavior in either the role:

- explicitInterRunnableVariable, or
- implicitInterRunnableVariable

if the `VariableDataPrototype` (after potential indirections via `TYPE_REFERENCE` are resolved) is either typed by, or mapped to, an:

- `ImplementationDataType` of category `DATA_REFERENCE`, or
- `ImplementationDataType` that contains `subElements` that (after potential indirections via `TYPE_REFERENCE` are resolved) are of category `DATA_REFERENCE`.

]

[constr_1298] Existence of attributes if `category` of a `ModeDeclarationGroup` is set to `EXPLICIT_ORDER`

Imposition time: IT_CpgExe

[The attributes `ModeDeclarationGroup.onTransitionValue` and `ModeDeclaration.value` (for each `ModeDeclaration`) shall be set if the `category` of a `ModeDeclarationGroup` is set to `EXPLICIT_ORDER`.

]

[constr_1299] Existence of attributes if `category` of a `ModeDeclarationGroup` is set to other than `EXPLICIT_ORDER`

Imposition time: IT_CpgExe

[The attributes `ModeDeclarationGroup.onTransitionValue` or `ModeDeclaration.value` (for any `ModeDeclaration`) shall **not** be set if the `category` of a `ModeDeclarationGroup` is set to any value **other than** `EXPLICIT_ORDER`.

]

[constr_1300] Primitive `DataPrototype` on the "source" end shall not be mapped to element of a composite data type on the "target" end of the `SwConnector`

Imposition time: IT_RteGen

[The usage of `DataPrototypeMapping` or `SubElementMapping` does not support the following configuration:

- The `AutosarDataPrototype` contained in the `PortPrototype` on the "source" end of an `SwConnector` is typed by an `ApplicationPrimitiveDataType` of category `VALUE` or `ImplementationDataType` of category `VALUE` or category `TYPE_REFERENCE` that eventually resolves to category `VALUE`.
- The `DataPrototypeMapping` aggregates a `subElementMapping` that refers to a `ImplementationDataTypeElement` or `ApplicationCompositeElementDataPrototype` contained in the `PortPrototype` on the "target" end.

]

[constr_1301] Existence of `RoleBasedDataTypeAssignment.role` vs. `RoleBasedDataAssignment.role`

Imposition time: IT_RteGen

[The usage of a `RoleBasedDataTypeAssignment` with attribute `role` set to the value `temporaryRamBlock` is only allowed if **no** `RoleBasedDataAssignment` defined with attribute `role` set to value `defaultValue` exists in the owning `SwcServiceDependency`.

]

[constr_1302] Restriction of data invalidation

Imposition time: IT_CpgExe

[Data invalidation is only applicable for one of the following cases applicable on the **receiving** side:

1. `VariableDataPrototypes` typed by either an `ApplicationPrimitiveDataType` or an `ImplementationDataType` of category `VALUE` or `TYPE_REFERENCE` that boils down to category `VALUE` that have defined an `invalidValue`.
2. `VariableDataPrototypes` typed by either an `ApplicationCompositeDataType` or an `ImplementationDataType` of category `STRUCTURE`, or `ARRAY` or of category `TYPE_REFERENCE` that boils down to category `STRUCTURE`, or `ARRAY` that have **at least one** primitive element with an `invalidValue`.

]

[constr_1303] Applicability of `TextTableMapping` depending on the value of `CompuMethod.category`

Imposition time: IT_RteGen

[If a `DataPrototypeMapping` aggregates a `TextTableMapping` then only certain combinations of the value of the applicable `CompuMethod.category` are supported:

- `category` of `firstDataPrototype`: `TEXTTABLE`,
`category` of `secondDataPrototype`: `TEXTTABLE`
- `category` of `firstDataPrototype`: `SCALE_LINEAR_AND_TEXTTABLE`,
`category` of `secondDataPrototype`: `TEXTTABLE`
- `category` of `firstDataPrototype`: `TEXTTABLE`,
`category` of `secondDataPrototype`: `SCALE_LINEAR_AND_TEXTTABLE`
- `category` of `firstDataPrototype`: `BITFIELD_TEXTTABLE`,
`category` of `secondDataPrototype`: `TEXTTABLE`
- `category` of `firstDataPrototype`: `TEXTTABLE`,
`category` of `secondDataPrototype`: `BITFIELD_TEXTTABLE`

- `category` of `firstDataPrototype`: `BITFIELD_TEXTTABLE`,
`category` of `secondDataPrototype`: `BITFIELD_TEXTTABLE`

]

[constr_1304] Existence of attribute `bitfieldTextTableMaskFirst`*Imposition time:* `IT_RteGen`

[The attribute `bitfieldTextTableMaskFirst` shall be defined **only if** the `firstDataPrototype` of a `DataPrototypeMapping` refers to a `CompuMethod` that has the value of `category` set to `BITFIELD_TEXTTABLE`.

]

[constr_1305] Existence of attribute `bitfieldTextTableMaskSecond`*Imposition time:* `IT_RteGen`

[The attribute `bitfieldTextTableMaskSecond` shall be defined **only if** the `secondDataPrototype` of a `DataPrototypeMapping` refers to a `CompuMethod` that has the value of `category` set to `BITFIELD_TEXTTABLE`.

]

[constr_1306] Limitation of `TextTableMapping` for `CompuMethods` that have the value of `category` set to `BITFIELD_TEXTTABLE`*Imposition time:* `IT_RteGen`

[For any `TextTableMapping` where both `firstDataPrototype` and `secondDataPrototype` refer to `CompuMethods` that have the value of `category` set to `BITFIELD_TEXTTABLE` **and** where the attribute `TextTableMapping.valuePair` exists the value of attribute `TextTableMapping.identicalMapping` shall be set to `false`.

]

[constr_1307] Consistency of values and masks in `TextTableMapping`*Imposition time:* `IT_RteGen`

[If a `TextTableMapping` element defines bit masks as `bitfieldTextTableMaskFirst` or `bitfieldTextTableMaskSecond` then all contained `TextTableMapping.valuePair.firstValues` as well as all `TextTableMapping.valuePair.secondValues` shall **not** specify a value that would be ruled out when - depending on the given value of `TextTableMapping.mappingDirection` - the relevant bit mask is applied.

]

[constr_1308] Existence of `NvBlockNeeds.cyclicWritingPeriod`

Imposition time: IT_RteGen

[The attribute `NvBlockNeeds.cyclicWritingPeriod` shall exist if and only if the attribute `NvBlockNeeds.storeCyclic` exists and its value is set to `true`.

]

[constr_1309] Existence of `NvBlockDescriptor.timingEvent`

Imposition time: IT_RteGen

[The attribute `NvBlockDescriptor.timingEvent` shall exist if and only if the `NvBlockDescriptor.nvBlockNeeds.storeCyclic` exists and is set to the value `true`.

]

[constr_1310] Existence of attributes of meta-class `NvBlockNeeds`

Imposition time: IT_RteGen

[If in the context of an `ApplicationSwComponentType` the attribute `SwcServiceDependency.serviceNeeds` is implemented by an `NvBlockNeeds` then the following attributes

- `NvBlockNeeds.storeCyclic`
- `NvBlockNeeds.cyclicWritingPeriod`
- `NvBlockNeeds.storeEmergency`
- `NvBlockNeeds.storeImmediate`
- `NvBlockNeeds.storeOnChange`

shall only exist if in the context of the same `SwcServiceDependency` a `SwcServiceDependency.assignedPort` exists that has the attribute `role` set to the value `NvDataPort`.

]

[constr_1311] Appearance of safety-related possible values of `MemorySection.option` or `SwAddrMethod.option`

Imposition time: IT_RteGen

[Any given collection of values stored in the attributes `MemorySection.option` or `SwAddrMethod.option` according to [TPS_SWCT_01456] shall at most include a single value out of the following list:

- **safetyQM**
- **safetyAsila**

- `safetyAsilB`
- `safetyAsilC`
- `safetyAsilD`

]

[constr_1312] PortPrototypes typed by a ParameterInterface*Imposition time:* IT_CpgExe

[PortPrototypes typed by a ParameterInterface can either be PPortPrototypes or RPortPrototypes. The usage of PRPortPrototypes that are typed by a ParameterInterface is not supported.

]

[constr_1313] Completeness of TextTableMapping for the values of a given bit mask on the sender side*Imposition time:* IT_RteGen

[If a DataPrototypeMapping contains one or more TextTableMapping(s) where the DataPrototype on the **sender side** refers to a CompuMethod of category BITFIELD_TEXTTABLE then all DataPrototypeMapping.textTableMapping shall aggregate a collection of TextTableMapping.valuePair where each possible value of the **sender bit mask**¹⁴ is represented by exactly one TextTableValuePair.firstValue ([TPS_SWCT_01163]) or TextTableValuePair.secondValue ([TPS_SWCT_01164]).

]

[constr_1314] Profile VSA_LINEAR for ApplicationArrayDataType*Imposition time:* IT_CpgExe

[If the dynamicArraySizeProfile of ApplicationArrayDataType is set to VSA_LINEAR, the contained ApplicationArrayElement shall fulfill **all** the following conditions:

- The attribute ApplicationArrayElement.arraySizeSemantics shall set to the value `variableSize`.
- The attribute ApplicationArrayElement.maxNumberOfElements shall be defined.
- The attribute ApplicationArrayElement.arraySizeHandling shall be set to the value `allIndicesSameArraySize`.

¹⁴Depending on the applicable case this means either `bitfieldTextTableMaskFirst` (applies if [TPS_SWCT_01163] is in place) or `bitfieldTextTableMaskSecond` for the case of [TPS_SWCT_01164].

- The `ApplicationArrayElement` shall be typed by an `ApplicationDataType` that is not an `ApplicationArrayDataType` where the attribute `dynamicArraySizeProfile` exists.

]

[constr_1315] Profile `VSA_SQUARE` for `ApplicationArrayDataType`

Imposition time: IT_CpgExe

[If the `dynamicArraySizeProfile` of `ApplicationArrayDataType` is set to `VSA_SQUARE`, the contained `ApplicationArrayElement` shall fulfill **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall not be defined.
- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `inheritedFromArrayElementTypeSize`.
- The `ApplicationArrayElement` shall be typed by an `ApplicationArrayDataType`.

The referred `ApplicationArrayDataType` shall refer over a chain (under consideration of the number of dimensions of the "root" `ApplicationArrayDataType`) of nested `ApplicationArrayDataTypes` with `ApplicationArrayElements` to an `ApplicationDataType` that is **not** an `ApplicationArrayDataType` where the attribute `dynamicArraySizeProfile` exists.

The last `ApplicationArrayDataType` in that chain shall have an `ApplicationArrayElement` that fulfills **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall be defined.
- The attribute `ApplicationArrayElement.arraySizeHandling` set to the value `allIndicesSameArraySize`.

All `ApplicationArrayDataTypes` before shall have an `ApplicationArrayElement` that fulfills **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall not be defined.

- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `inheritedFromArrayElementTypeSize`.
- The `ApplicationArrayElement` shall be typed by an `ApplicationArray-DataType`.

]

[constr_1316] Profile `VSA_RECTANGULAR` for `ApplicationArrayDataType`

Imposition time: IT_CpgExe

[If the `dynamicArraySizeProfile` of `ApplicationArrayDataType` is set to `VSA_RECTANGULAR` the contained `ApplicationArrayElement` shall fulfill **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall be defined.
- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.
- The `ApplicationArrayElement` shall be typed by an `ApplicationArray-DataType`.

The referred `ApplicationArrayDataType` shall refer over a chain (under consideration of the number of dimensions of the "root" `ApplicationArrayDataType`) of nested `ApplicationArrayDataTypes` with `ApplicationArrayElements` to an `ApplicationDataType` that is **not** an `ApplicationArrayDataType` where the attribute `dynamicArraySizeProfile` exists.

The last `ApplicationArrayDataType` in that chain shall have an `Application-ArrayElement` that fulfills **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall be defined.
- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

All `ApplicationArrayDataTypes` before shall have an `ApplicationArrayElement` that fulfills **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall set to the value `variableSize`
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall be defined.

- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.
- The `ApplicationArrayElement` shall be typed by an `ApplicationArray-DataType`.

]

[constr_1317] Profile `VSA_FULLY_FLEXIBLE` for `ApplicationArrayDataType`

Imposition time: IT_CpgExe

[If the `dynamicArraySizeProfile` of `ApplicationArrayDataType` is set to `VSA_FULLY_FLEXIBLE`, the contained `ApplicationArrayElement` shall fulfill **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall be defined.
- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `allIndicesDifferentArraySize`.
- The `ApplicationArrayElement` shall be typed by an `ApplicationArray-DataType`.

The referred `ApplicationArrayDataType` shall refer over a chain (under consideration of the number of dimensions of the "root" `ApplicationArrayDataType`) of nested `ApplicationArrayDataTypes` with `ApplicationArrayElements` to an `ApplicationDataType` that is **not** an `ApplicationArrayDataType` where the attribute `dynamicArraySizeProfile` exist.

The last `ApplicationArrayDataType` in that chain shall have an `Application-ArrayElement` that fulfills **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall be defined.
- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

All `ApplicationArrayDataTypes` before shall have an `ApplicationArrayElement` that fulfills **all** the following conditions:

- The attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ApplicationArrayElement.maxNumberOfElements` shall be defined.

- The attribute `ApplicationArrayElement.arraySizeHandling` shall be set to the value `allIndicesDifferentArraySize`.
- The `ApplicationArrayElement` shall be typed by an `ApplicationArray-DataType`.

]

[constr_1318] Profile VSA_LINEAR for ImplementationDataType*Imposition time:* IT_CpgExe

[If the value of attribute `ImplementationDataType.dynamicArraySizeProfile` is set to `VSA_LINEAR`, the `ImplementationDataType` shall aggregate a VSA Payload `ImplementationDataTypeElement` that fulfills all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall not be defined.
- The attribute `ImplementationDataTypeElement.category` shall be set to `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySize` shall not be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall not be defined.

The VSA Payload `ImplementationDataTypeElement` shall immediately aggregate another `ImplementationDataTypeElement` that shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

]

[constr_1319] Profile VSA_SQUARE for ImplementationDataType*Imposition time:* IT_CpgExe

[If the value of attribute `ImplementationDataType.dynamicArraySizeProfile` is set to `VSA_SQUARE`, the `ImplementationDataType` shall aggregate a VSA Payload `ImplementationDataTypeElement` that fulfills all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall not be defined.

- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySize` shall not be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall not be defined.

The VSA Payload `ImplementationDataTypeElement` shall immediately aggregate another `ImplementationDataTypeElement` (representing the first dimension) that shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySize` shall not be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `inheritedFromArrayElementTypeSize`.

All **intermediate** `ImplementationDataTypeElements` in the aggregation chain that do not terminate the chain shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySize` shall not be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `inheritedFromArrayElementTypeSize`.

The **terminating** `ImplementationDataTypeElement` in the aggregation chain shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

]

[constr_1320] Profile VSA_RECTANGULAR for ImplementationDataType

Imposition time: IT_CpgExe

[If the value of attribute `ImplementationDataType.dynamicArraySizeProfile` is set to `VSA_RECTANGULAR`, the `ImplementationDataType` shall aggregate a VSA Payload `ImplementationDataTypeElement` that fulfills all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall not be defined.
- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySize` shall not be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall not be defined.

The VSA Payload `ImplementationDataTypeElement` shall immediately aggregate another `ImplementationDataTypeElement` (representing the first dimension) that shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

All **intermediate** `ImplementationDataTypeElements` in the aggregation chain that do not terminate the chain shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

The **terminating** `ImplementationDataTypeElement` in the aggregation chain shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

]

[constr_1321] Profile `VSA_FULLY_FLEXIBLE` for `ImplementationDataType`

Imposition time: IT_CpgExe

[If the value of attribute `ImplementationDataType.dynamicArraySizeProfile` is set to the value `VSA_FULLY_FLEXIBLE`, the `ImplementationDataType` shall aggregate a VSA Payload `ImplementationDataTypeElement` that fulfills all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall not be defined.
- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySize` shall not be defined
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall not be defined.

The VSA Payload `ImplementationDataTypeElement` shall immediately aggregate another `ImplementationDataTypeElement` (representing the first dimension) that shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.category` shall be set to `STRUCTURE`
- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesDifferentArraySize`.

The `ImplementationDataTypeElement` shall aggregate another `ImplementationDataTypeElement` that fulfills the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall not be defined.

- The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
- The attribute `ImplementationDataTypeElement.arraySize` shall not be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall not be defined.

The **aggregation chain is continued** by a (possible empty) sequence of a pair of `ImplementationDataTypeElements` with the following characteristics:

- The first `ImplementationDataTypeElement` in the pair shall fulfill all the following conditions:
 - The attribute `ImplementationDataTypeElement.category` shall be set to `STRUCTURE`.
 - The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
 - The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
 - The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesDifferentArraySize`.
- The second `ImplementationDataTypeElement` in the pair shall fulfill all the following conditions:
 - The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall not be defined.
 - The attribute `ImplementationDataTypeElement.category` shall be set to the value `ARRAY`.
 - The attribute `ImplementationDataTypeElement.arraySize` shall not be defined.
 - The attribute `ImplementationDataTypeElement.arraySizeHandling` shall not be defined.

The **terminating** `ImplementationDataTypeElement` in the aggregation chain shall fulfill all the following conditions:

- The attribute `ImplementationDataTypeElement.arraySizeSemantics` shall be set to the value `variableSize`.
- The attribute `ImplementationDataTypeElement.arraySize` shall be defined.
- The attribute `ImplementationDataTypeElement.arraySizeHandling` shall be set to the value `allIndicesSameArraySize`.

]

[constr_1322] Size Indicator for undefined `dynamicArraySizeProfile`

Imposition time: IT_CpgExe

[If the `ImplementationDataType.dynamicArraySizeProfile` does not exist but the `ImplementationDataType` is mapped to an `ApplicationArrayDataType` where the attribute `ApplicationArrayDataType.dynamicArraySizeProfile` exists, then the `ImplementationDataType` shall have the category `STRUCTURE`, representing a Variable-Size Array Data Type with Size Indicator enabled.

]

[constr_1363] Existence of attributes of `DiagnosticValueNeeds`

Imposition time: IT_CpgExe

[if `DiagnosticValueNeeds` is aggregated by a `SwcServiceDependency` in the role `serviceNeeds` then the attributes

- `DiagnosticValueNeeds.diagnosticValueAccess`
- `DiagnosticValueNeeds.dataLength`
- `DiagnosticValueNeeds.fixedLength`

shall **not** exist.

]

[constr_1375] Existence of attributes of `CompuMethod` and related meta-classes depending on the value of the `category`

Imposition time: IT_CpgExe

[

	Attribute Existence per Category									
Attributes of <code>CompuMethod</code>	IDENTICAL	LINEAR	SCALE_LINEAR	RAT_FUNC	SCALE_RAT_FUNC	TEXTTABLE	BITFIELD_TEXTTABLE	SCALE_LINEAR_AND_TEXTTABLE	SCALE_RATIONAL_AND_TEXTTABLE	TAB_NOINTP



△

<code>compuInternalToPhys</code>		D(1)	D(1)	D(2)	D(2)	D	D	D(8)	D(2)	D
<code>compuPhysToInternal</code>		D(1)	D(1)	D(2)	D(2)				D(2,3)	
Attributes of meta-classes related to CompuMethod										
<code>compuDefaultValue</code>		O(6)	O(6)	O(6)	O(6)	O(6)	O(6)	O(6)	O(6)	O(6)
<code>CompuScale</code>		D/ 1..1	D/ 1..n	D/ 1..1	D/ 1..n	D/ 1..n	D/ 1..n	D/ 1..n	D/ 1..n	D/1..n
<code>CompuScale.compuInverseValue</code>				O(2)	O(2)	O(5)		O(2,5)	O(2,5)	O(5)
<code>CompuScale.lowerLimit</code>		O	D	D(4)	D(4)	D	D	D	D(4)	D
<code>CompuScale.mask</code>							D			
<code>CompuScale.shortLabel</code>						O(7)	O(7)	O(7)	O(7)	
<code>CompuScale.a2lDisplayText</code>						O	O	O	O	
<code>CompuScale.symbol</code>						O(7)	O(7)	O(7)	O(7)	
<code>CompuScale.upperLimit</code>		O	D	D(4)	D(4)	D	D	D	D(4)	D
<code>CompuConst</code>						D/vt	D/vt	D/vt	D/vt	D/vt or vf
<code>CompuRationalCoeffs</code>		D	D	D	D			D	D	
<code>CompuRationalCoeffs.compuDenominator</code>		D/1 _v	D/1 _v	D	D			D/1 _v	D	
<code>CompuRationalCoeffs.compuNumerator</code>		D/2 _v	D/2 _v	D	D			D/2 _v	D	

]

[constr_1381] Appearance of core-related possible values of `MemorySection.option` or `SwAddrMethod.option`

Imposition time: IT_RteGen

[Any given collection of values stored in the attributes `MemorySection.option` or `SwAddrMethod.option` according to [TPS_SWCT_01456] shall at most include a single value out of the following list:

- `coreGlobal`
- `coreLocal`

]

[constr_1382] Mutually exclusive existence of attributes `SwVariableRefProxy.autosarVariable` vs. `SwVariableRefProxy.mcDataInstanceVar`

Imposition time: IT_CpgExe

[In any given AUTOSAR model, the aggregations `SwVariableRefProxy.autosarVariable` and `SwVariableRefProxy.mcDataInstanceVar` shall never exist at the same time.

]

[constr_1383] Existence of `CompuMethod` and `DataConstr` for `ImplementationDataTypes` of category `TYPE_REFERENCE`

Imposition time: IT_CpgExe

[The existence of `ImplementationDataType.swDataDefProps.compuMethod` and `ImplementationDataType.swDataDefProps.dataConstr` for `ImplementationDataTypes` of category `TYPE_REFERENCE` is only allowed, if the respective `ImplementationDataType`, after all type references are resolved, ends up in an `ImplementationDataType` of category `VALUE`.

]

[constr_1384] Definition of `invalidValue` for `DataPrototype` typed by `ApplicationPrimitiveDataType` of category `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5`, `COM_AXIS`, `RES_AXIS`, and `VAL_BLK`

Imposition time: IT_CpgExe

[An `invalidValue` shall not be specified for a `DataPrototype` typed by `ApplicationPrimitiveDataType` of category `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5`, `COM_AXIS`, `RES_AXIS`, and `VAL_BLK`.

]

[constr_1385] `DataPrototype` is typed by an `ImplementationDataType`

Imposition time: IT_CpgExe

[If a `DataPrototype` is typed by an `ImplementationDataType`, its `initValue` shall not be provided by an `ApplicationValueSpecification`.

]

[constr_1386] `PortDefinedArgumentValue` shall only be defined for `AbstractProvidedPortPrototype`

Imposition time: IT_RteGen

[A `PortAPIOption` which aggregates at least one `PortDefinedArgumentValue` in the role `portArgValue` shall reference an `AbstractProvidedPortPrototype` typed by a `ClientServerInterface` in the role `port`.

]

[constr_1388] `VariationPointProxy` of category `VALUE` shall not mix "pre-build" and "post-build" use-cases

Imposition time: IT_CpgExe

[If the value of `category` of the `VariationPointProxy` is set to `VALUE` then there can only be one value yield from the evaluation of a `VariationPointProxy`. In other

words, a `VariationPointProxy` of category `VALUE` shall not mix the "pre-build" and "post-build" use-cases.

]

[constr_1389] Restriction regarding the value of `category` of `VariationPointProxy.implementationDataType`

Imposition time: IT_CpgExe

[`VariationPointProxy.implementationDataType` shall **not** be of category `STRUCTURE`, `ARRAY`, `UNION`, `FUNCTION_REFERENCE`, and `DATA_REFERENCE`.

The `VariationPointProxy.implementationDataType` shall be of category `VALUE` or `TYPE_REFERENCE` that, after all references are resolved, yields an `ImplementationDataType` of category `VALUE`.

]

[constr_1390] Restriction to the value of `SenderReceiverInterface.invalidationPolicy.handleInvalid`

Imposition time: IT_CpgExe

[If the value of `SenderReceiverInterface.invalidationPolicy.handleInvalid` is set to any value other than `HandleInvalidEnum.dontInvalidate` then the `invalidValue` shall not be within the interval defined by the `CompuMethod` of the applicable `dataElement`.

]

[constr_1391] Compatibility of `Units` in the context of assignment using an `ApplicationValueSpecification`

Imposition time: IT_CpgExe

[If an `ApplicationValueSpecification` is used in the context of an assignment to an `AutosarDataPrototype`, then the `ApplicationValueSpecification.swValueCont.unit` shall be compatible to the `Unit` used in the definition of the given `AutosarDataPrototype`, i.e. `AutosarDataType.swDataDefProps.unit`.

]

[constr_1392] Compatibility of `Units` in the context of assignment using an `ApplicationRuleBasedValueSpecification`

Imposition time: IT_CpgExe

[If an `ApplicationRuleBasedValueSpecification` is used in the context of an assignment to an `AutosarDataPrototype` then the `ApplicationRuleBasedValueSpecification.swValueCont.unit` shall be compatible to the `Unit` used

in the definition of the given `AutosarDataPrototype`, i.e. `AutosarDataType.sw-DataDefProps.unit`.

]

[constr_1393] Existence of `RuleBasedValueCont.unit`

Imposition time: IT_CpgExe

[For every `RuleBasedValueCont`, the reference `unit` shall exist.

]

[constr_1395] `NvBlockDataMapping` shall be complete

Imposition time: IT_RteGen

[If an `NvBlockDataMapping` refers to *sub-elements* or *leaf* elements of the `Nv-DataInterface.nvData` in the context of a particular `PortPrototype`, then **all remaining** *sub-elements* or *leaf* elements **shall effectively be mapped** according to [TPS_SWCT_01659] by means of a collection of `NvBlockDataMappings`.

]

[constr_1396] Restriction for the value of attribute `category` for non-terminating `ImplementationDataTypeElements` taken to model a Variable-Size Array Data Type

Imposition time: IT_CpgExe

[The value of attribute `category` for non-terminating `ImplementationDataTypeElements` taken to model a Variable-Size Array Data Type shall **not** be set to `TYPE_REFERENCE`.

]

[constr_1397] Existence of attributes of `TransformerHardErrorEvent`

Imposition time: IT_CpgExe

[For any given `TransformerHardErrorEvent`, **either** the attribute `TransformerHardErrorEvent.operation` **or** `TransformerHardErrorEvent.requiredTrigger` shall exist.

]

[constr_1398] Existence of attributes of `BaseTypeDirectDefinition`

Imposition time: IT_CpgExe

[If the value of attribute `BaseTypeDirectDefinition.baseTypeEncoding` is set to `UTF-16` then the attribute `BaseTypeDirectDefinition.byteOrder` shall exist.

The only allowed values of `BaseTypeDirectDefinition.byteOrder` in this case are `mostSignificantByteFirst` and `mostSignificantByteLast`.

]

[constr_1399] Standardized values of `ModeDeclarationGroup.category`

Imposition time: IT_CpgExe

[The AUTOSAR standard defines the following values of the attribute `ModeDeclarationGroup.category` with a standardized meaning:

- EXPLICIT_ORDER
- ALPHABETIC_ORDER

[TPS_SWCT_01010] defines the meaning of these values.

It is **not allowed** to define any custom or project-specific value of the attribute `ModeDeclarationGroup.category`.

]

[constr_1400] Reference to a specific `DataTransformation`

Imposition time: IT_RteGen

[A specific `DataTransformation` shall only be referenced by either

- a `DataPrototypeMapping` in the role `firstToSecondDataTransformation` (and potentially `secondToFirstDataTransformation`) **or**
- an `ISignal` in the role `dataTransformation` **or**
- an `ISignalGroup` in the role `comBasedSignalGroupTransformation` **or**
- a `ClientServerOperationMapping` in the role `firstToSecondDataTransformation`

]

[constr_1401] Restrictions on the relation between `DataPrototypeMapping` and `DataTransformation`

Imposition time: IT_RteGen

[A `VariableDataPrototype` in the context of a `PortPrototype` shall **not** be referenced by a `DataPrototypeMapping` that references a `DataTransformation` while a `DataMapping` exists that points to this `VariableDataPrototype` (via the `SystemSignal`) that also refers to an `ISignal` that in turn references a `DataTransformation`.

]

[constr_1402] Applicability of core-related possible values of `MemorySection.option` or `SwAddrMethod.option` related to `SwAddrMethod.sectionInitializationPolicy`

Imposition time: IT_CpgExe

[If the attribute `SwAddrMethod.option` or `MemorySection.option` is set to `core-Local` then the attribute `SwAddrMethod.sectionInitializationPolicy` of the same `SwAddrMethod` respectively the `MemorySection.swAddrmethod` shall be either set to `INIT` or `CLEARED`.

]

[constr_1403] `NvBlockDataMappings` to a given `nvData` shall be unambiguous

Imposition time: IT_RteGen

[If an `NvBlockDataMapping` exists that **directly** and **completely** maps a specific `NvDataInterface.nvData` in the context of a particular `PortPrototype`, then **no** other `NvBlockDataMapping` which maps sub-elements of the `NvDataInterface.nvData` shall exist.

]

[constr_1404] All `NvDataInterface.nvData` of `PortPrototypes` in the context of a specific `SwcServiceDependency` shall be mapped to the same `NvBlockDescriptor`

Imposition time: IT_RteGen

[In the context of a given `SwcServiceDependency` (which, in turn, is owned by an `AtomicSwComponentType`), **all** `NvDataInterface.nvData` of `PortPrototypes` referenced by a `RoleBasedPortAssignment` with attribute `RoleBasedPortAssignment.role` set to `NvDataPort` shall be connected (either directly or via the definition of suitable `PortInterfaceMappings`) to `NvDataInterface.nvData` (on the side of the `NvBlockSwComponentType`) that are **completely mapped** (via `NvBlockDataMappings`) to the **identical** `NvBlockDescriptor.ramBlock`.

]

[constr_1407] Definition of `SwDataDefProps.dataConstr` depending on the capabilities of the data type

Imposition time: IT_CpgExe

[The definition of a `SwDataDefProps.dataConstr` according to [constr_1288] and [constr_1289] is only supported for a `DataPrototype` of category `ARRAY` if the corresponding `ApplicationArrayDataType` or `ImplementationDataType` of category `ARRAY` also supports the specification of a `SwDataDefProps.dataConstr`.

]

[constr_1408] Definition of `SwDataDefProps.displayFormat` depending on the capabilities of the data type

Imposition time: IT_CpgExe

[The definition of a `SwDataDefProps.displayFormat` according to [constr_1288] and [constr_1289] is only supported for a `DataPrototype` of category ARRAY if the corresponding `ApplicationArrayDataType` or `ImplementationDataType` of category ARRAY also supports the specification of a `SwDataDefProps.displayFormat`.

]

[constr_1409] Definition of `SwDataDefProps.dataConstr` depending on the capabilities of the element data type

Imposition time: IT_CpgExe

[The definition of a `SwDataDefProps.dataConstr` according to [constr_1007] and [constr_1009] is only supported for an `ApplicationArrayDataType` or an `ImplementationDataType` of category ARRAY if the aggregated `ApplicationArrayDataType.element` or `ImplementationDataType.subElement` also supports the specification of a `SwDataDefProps.dataConstr`.

]

[constr_1410] Definition of `SwDataDefProps.displayFormat` depending on the capabilities of the element data type

Imposition time: IT_CpgExe

[The definition of a `SwDataDefProps.displayFormat` according to [constr_1007] and [constr_1009] is only supported for an `ApplicationArrayDataType` or an `ImplementationDataType` of category ARRAY if the aggregated `ApplicationArrayDataType.element` or `ImplementationDataType.subElement` also supports the specification of a `SwDataDefProps.displayFormat`.

]

[constr_1413] Definition of `SwDataDefProps.stepSize` depending on the capabilities of the data type

Imposition time: IT_CpgExe

[The definition of a `SwDataDefProps.stepSize` according to [constr_1288] and [constr_1289] is only supported for a `DataPrototype` of category ARRAY if the corresponding `ApplicationArrayDataType` or `ImplementationDataType` of category ARRAY also supports the specification of a `SwDataDefProps.stepSize`.

]

[constr_1414] Definition of `SwDataDefProps.stepSize` depending on the capabilities of the element data type

Imposition time: IT_CpgExe

[The definition of a `SwDataDefProps.stepSize` according to [constr_1007] and [constr_1009] is only supported for an `ApplicationArrayDataType` or an `ImplementationDataType` of category ARRAY if the aggregated `ApplicationArrayDataType.element` or `ImplementationDataType.subElement` also supports the specification of a `SwDataDefProps.stepSize`.

]

[constr_1415] Supported values of `ModeSwitchEventTriggeredActivity.role`

Imposition time: IT_RteGen

[The only supported value of `ModeSwitchEventTriggeredActivity.role` is `WriteBlock`.

]

[constr_1416] Existence of `ApplicationArrayElement.maxNumberOfElements`

Imposition time: IT_CpgExe

[The attribute `ApplicationArrayElement.maxNumberOfElements` shall exist for all `ApplicationArrayElements` defined in the scope of an `ApplicationArrayDataType` where the attribute `ApplicationArrayDataType.dynamicArraySizeProfile` does not exist.

]

[constr_1417] Invalid connection between `NvBlockSwComponentType` and other `AtomicSwComponentType` (I)

Imposition time: IT_RteGen

[A configuration where an `RPortPrototype` owned by an `AtomicSwComponentType` is simultaneously and directly connected to `AbstractProvidedPortPrototypes` of a collection of `AtomicSwComponentTypes` where at least one in the collection is an `NvBlockSwComponentType` for a matching set of `dataElements` in all these `PortPrototypes` shall be considered invalid.

]

[constr_1418] Invalid connection between `NvBlockSwComponentType` and other `AtomicSwComponentType` (II)

Imposition time: IT_RteGen

[A configuration where a `PRPortPrototype` owned by an `AtomicSwComponentType` is connected to a `PPortPrototype` owned by an `NvBlockSwComponentType` for a matching set of `dataElements` in all these `PortPrototypes` shall be considered invalid.

]

[constr_1420] Existence of `SwAxisIndividual.inputVariableType`

Imposition time: IT_CpgExe

[If the reference `SwAxisIndividual.inputVariableType` does not exist then either:

- `SwAxisIndividual.dataConstr`
- `SwAxisIndividual.unit`

or

- `SwAxisIndividual.dataConstr`
- `SwAxisIndividual.compuMethod.unit`

shall exist.

]

[constr_1422] Value of `category` is `VOID`

Imposition time: IT_CpgExe

[If the value of the attribute `SwBaseType.category` is set to `VOID` then the attribute `baseTypeSize` and `baseTypeEncoding` shall not exist.

]

[constr_1423] Completeness of references `ArVariableInImplementationDataInstanceRef.contextDataPrototype`

Imposition time: IT_CpgExe

[The reference `ArVariableInImplementationDataInstanceRef.contextDataPrototype` shall be defined for

- each *leaf* (i.e. the end of a chain of aggregating elements) `ImplementationDataTypeElement` of `category TYPE_REFERENCE` in a chain of referencing `ImplementationDataTypes` which is not the `targetDataPrototype`

- and each `ImplementationDataTypeElement` owned by an `ImplementationDataType` or `ImplementationDataTypeElement` of category `ARRAY` in a chain of referencing `ImplementationDataTypes`

starting from the `ImplementationDataTypes` of the `rootVariableDataPrototype` down to the leaf `ImplementationDataTypeElement` which is typed (directly or indirectly via `ImplementationDataType` of category `TYPE_REFERENCE`) by the `ImplementationDataType` of the `targetDataPrototype`.

]

[constr_1424] Existence of `ArVariableInImplementationDataInstanceRef.contextDataPrototype`

Imposition time: IT_CpgExe

[The attribute `ArVariableInImplementationDataInstanceRef.contextDataPrototype` shall only exist for an `ImplementationDataTypeElement` category `TYPE_REFERENCE` or `ARRAY`.

]

[constr_1425] Definition of `swCalprmAxisSet.swCalprmAxis` / `SwAxisIndividual.swVariableRef` depending on the capabilities of the data type

Imposition time: IT_CpgExe

[The definition of a `swCalprmAxisSet.swCalprmAxis` / `SwAxisIndividual.swVariableRef` in the context of an `InstantiationDataDefProps` or a `ParameterAccess` is only supported for a `DataPrototype` of category `ARRAY` if the data type of the `ApplicationArrayElement` also supports the specification of a `swCalprmAxisSet.swCalprmAxis` / `SwAxisIndividual.swVariableRef` according to [constr_1289].

Thereby, multiple `ApplicationArrayDataTypes` might be nested to express multiple array dimensions.

]

[constr_1426] Consistency of array sizes for axes and input variable array

Imposition time: IT_CpgExe

[The number of array dimension defined by `ApplicationArrayDataTypes` and the values of the `maxNumberOfElements` attributes for the array of elements of category `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, `CUBE_5`, `COM_AXIS`, or `RES_AXIS` shall be **identical** to the number of array dimension and according value of the `maxNumberOfElements` of the `VariableDataPrototype` referenced by `SwAxisIndividual.swVariableRef.autosarVariable`.

]

[constr_1427] Definition of `swCalprmAxisSet.swCalprmAxis` / `SwAxisGrouped.swCalprmRef` depending on the capabilities of the data type

Imposition time: IT_CpgExe

[The definition of a `swCalprmAxisSet.swCalprmAxis` / `SwAxisGrouped.swCalprmRef` in the context of an `InstantiationDataDefProps` or a `ParameterAccess` is only supported for a `DataPrototype` of category `ARRAY` if the data type of the `ApplicationArrayElement` also supports the specification of a `swCalprmAxisSet.swCalprmAxis` / `SwAxisGrouped.swCalprmRef` according to [constr_1289].

Thereby, multiple `ApplicationArrayDataTypes` might be nested to express multiple array dimensions.

]

[constr_1428] Consistency of array sizes for arrays of elements of category `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, or `CUBE_5` arrays and used group axes arrays

Imposition time: IT_CpgExe

[The number of array dimension defined by `ApplicationArrayDataTypes` and the values of attribute `maxNumberOfElements` attributes for the array of elements of category `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, or `CUBE_5` needs to be identical to the number of array dimension and according value of the `maxNumberOfElements` of the `DataPrototype` referenced by `SwAxisGrouped.swCalprmRef.arParameter`.

]

[constr_1429] Access to data within `PortPrototypes` from within `RunnableEntities`

Imposition time: IT_CpgExe

[For a `VariableAccess` that is aggregated in the roles

- `RunnableEntity.dataWriteAccess`
- `RunnableEntity.dataReadAccess`
- `RunnableEntity.dataSendPoint`
- `RunnableEntity.dataReceivePointByArgument`
- `RunnableEntity.dataReceivePointByValue`

the existence of the following attributes is not allowed:

- `VariableAccess.accessedVariable.autosarVariable.contextDataPrototype`
- `VariableAccess.accessedVariable.autosarVariable.rootVariableDataPrototype`

- `VariableAccess.accessedVariable.autosarVariableInImpl-Datatype`
- `VariableAccess.accessedVariable.localVariable`

In other words: in this case, only the references

- `VariableAccess.accessedVariable.autosarVariable.portPrototype` and
- `VariableAccess.accessedVariable.autosarVariable.targetDataPrototype`

shall exist and the latter shall **exclusively** refer to a `VariableDataPrototype` that is aggregated as either

- `SenderReceiverInterface.dataElement` or
- `NvDataInterface.nvData`.

]

[constr_1430] Access to local data from within `RunnableEntity`s

Imposition time: IT_CpgExe

[For `VariableAccess` that is aggregated in the roles

- `RunnableEntity.writtenLocalVariable`
- `RunnableEntity.readLocalVariable`

the existence of the following attributes is not allowed:

- `VariableAccess.accessedVariable.autosarVariableInImpl-Datatype`
- `VariableAccess.accessedVariable.autosarVariable`

In other words, **only** the reference `VariableAccess.accessedVariable.localVariable` shall be used in this case.

]

[constr_1431] Access to parameters from within `RunnableEntity`s

Imposition time: IT_CpgExe

[For a `ParameterAccess` that is aggregated in the role `RunnableEntity.parameterAccess` the existence of the following attributes is not allowed:

- `ParameterAccess.accessedParameter.autosarParameter.contextDataPrototype`
- `ParameterAccess.accessedParameter.autosarParameter.rootParameterDataPrototype`

In other words: in this case, **one** of the following alternatives is allowed to exist:

- a combination of
 - `ParameterAccess.accessedParameter.autosarParameter.port-Prototype` and
 - `ParameterAccess.accessedParameter.autosarParameter.targetDataPrototype` that **exclusively** refers to a `ParameterDataPrototype` aggregated by a `ParameterInterface` in the role `parameter`.
- `ParameterAccess.accessedParameter.localParameter` that refers to a `ParameterDataPrototype` that is either aggregated as
 - `InternalBehavior.constantMemory` or
 - `SwcInternalBehavior.perInstanceParameter` or
 - `SwcInternalBehavior.sharedParameter`.

]

[constr_1432] Multiplicity of `CommunicationBufferLocking`

Imposition time: IT_RteGen

[In a concrete aggregated set of `PortAPIOption.supportedFeature`, `CommunicationBufferLocking` shall exist.

]

[constr_1434] `CompuScales` shall not have identical `CompuScale Value Symbolic Names`

Imposition time: IT_CpgExe

[In a `CompuMethod` that is subject to [constr_1146], no two `CompuScales` shall have identical `CompuScale Value Symbolic Names` (according to [TPS_SWCT_01696]).

]

[constr_1438] `ApplicationArrayElement.indexDataType` needs to refer to a `CompuMethod` of category `TEXTTABLE`

Imposition time: IT_CpgExe

[The reference `ApplicationArrayElement.indexDataType` shall only point to an `ApplicationPrimitiveDataType` that in turn refers to a `CompuMethod` of category `TEXTTABLE`.

]

[constr_1439] Requirements on `ApplicationArrayElement` if attribute `indexDataType` exists

Imposition time: IT_CpgExe

[If `ApplicationArrayElement.indexDataType` exists then the attribute `ApplicationArrayElement.arraySizeSemantics` shall be set to the value `fixedSize` and attribute `arraySizeHandling` shall not exist.

]

[constr_1440] Size of the `CompuMethod` of category `TEXTTABLE` referenced by `ApplicationArrayElement.indexDataType`

Imposition time: IT_CpgExe

[The interval defined by the `CompuScales` contained in the `CompuMethod` referenced by `ApplicationArrayElement.indexDataType` shall start at 0 and include all integer values until `ApplicationArrayElement.maxNumberOfElements` - 1.

]

[constr_1442] category `TYPE_REFERENCE` shall not be used for modeling the "payload" of a `Wrapped Union Data Type`

Imposition time: IT_CpgExe

[For the modeling of the "payload" part of a `Wrapped Union Data Type` it shall not be possible to use an `ImplementationDataTypeElement` of category `TYPE_REFERENCE` that finally (i.e. after all possible indirections are resolved) boils down to category `UNION`.

]

[constr_1444] Limited applicability of `Wrapped Union Data Type`

Imposition time: IT_CpgExe

[There is no support for the usage of `Wrapped Union Data Type` in `PortInterfaceMappings`, and `Diagnostics`.

]

[constr_1445] Initialization of the `Member Selector` of a `Wrapped Union Data Type`

Imposition time: IT_CpgExe

[The `initValue` for the `Member Selector` shall **never be set to any value other than 1**.

]

[constr_1446] No definition of `invalidValue` for a Wrapped Union Data Type

Imposition time: IT_CpgExe

[The definition of an `invalidValue` for a `DataPrototype` typed by a `Wrapped Union Data Type` is not supported.

]

[constr_1468] Limitation on the number of `SwcExclusiveAreaPolicys`

Imposition time: IT_CpgExe

[An `ExclusiveArea` shall only be referenced by **at most** one `SwcExclusiveAreaPolicy`.

]

[constr_1469] Applicability of constraints depending on the existence of a data transformation

Imposition time: IT_RteGen

[[`constr_1269`], [`constr_1270`], [`constr_1268`], and [`constr_1240`] shall **not** apply under the following conditions:

- A reference from the respective `ClientServerOperationMapping` to a `DataTransformation` in the role `firstToSecondDataTransformation` exists.
- The value of the attribute `dataTransformationKind` of the referenced `DataTransformation` is set to `DataTransformationKindEnum.asymmetricFromByteArray` or `DataTransformationKindEnum.asymmetricToByteArray`.

]

[constr_1516] Completeness of references `ArParameterInImplementationDataInstanceRef.contextDataPrototype`

Imposition time: IT_CpgExe

[The reference `ArParameterInImplementationDataInstanceRef.contextDataPrototype` shall be defined for

- each *leaf* (i.e. the end of a chain of aggregating elements) `ImplementationDataTypeElement` of category `TYPE_REFERENCE` in a chain of referencing `ImplementationDataTypes` which is not the `targetDataPrototype`
- and each `ImplementationDataTypeElement` owned by an `ImplementationDataType` or `ImplementationDataTypeElement` of category `ARRAY` in a chain of referencing `ImplementationDataTypes`

starting from the `ImplementationDataTypes` of the `rootParameterDataPrototype` down to the leaf `ImplementationDataTypeElement` which is typed (directly or indirectly via `ImplementationDataType` of category `TYPE_REFERENCE`) by the `ImplementationDataType` of the `targetDataPrototype`.

]

[constr_1517] Existence of `ArParameterInImplementationDataInstanceRef.contextDataPrototype`

Imposition time: IT_CpgExe

[The attribute `ArParameterInImplementationDataInstanceRef.contextDataPrototype` shall only exist for an `ImplementationDataTypeElement` category `TYPE_REFERENCE` or `ARRAY`.

]

[constr_1518] Consistency of data types in the context of `ArParameterInImplementationDataInstanceRef`

Imposition time: IT_RteGen

[The definition of attributes `contextDataPrototype` and `targetDataPrototype` shall be enclosed in the context of the definition of the data type used to type `rootParameterDataPrototype`.

]

[constr_1519] Existence of attributes vs. category of `ApplicationValueSpecification`

Imposition time: IT_CpgExe

[

Attribute of <code>ApplicationValueSpecification</code>	Attribute Existence per Category										
	VALUE	VAL_BULK	STRING	BOOLEAN	COM_AXIS	RES_AXIS	CURVE	MAP	CUBOID	CUBE_4	CUBE_5
<code>swValueCont</code>	D	D	D	D	D	D	D	D	D	D	D
<code>swValueCont.unit</code>	O	O	O	O	O	O	O	O	O	O	O
<code>swValueCont.swValuesPhys</code>	D	D	D	D	D	D	D	D	D	D	D
<code>swValueCont.swArraysizes</code>		D			D	D	D	D	D	D	D
<code>swAxisCont</code>						D	O(1)	O(1)	O(1)	O(1)	O(1)
<code>swAxisCont.unit</code>						O	O	O	O	O	O
<code>swAxisCont.category</code>						D	D	D	D	D	D
<code>swAxisCont.swAxisIndex</code>						D	D	D	D	D	D
<code>swAxisCont.swArraysizes</code>						D	D	D	D	D	D
<code>swAxisCont.swValuesPhys</code>						D	O(1)	O(1)	O(1)	O(1)	O(1)

]

[constr_1520] Semantics of `ObdRatioServiceNeeds.rateBasedMonitoredEvent`

Imposition time: IT_RteGen

[In the context of an `SwcServiceDependency`, each `DiagnosticEventNeeds` referenced in the role `rateBasedMonitoredEvent` shall only be referenced by at most a single `ObdRatioServiceNeeds`.

]

[constr_1521] Reference from `AsynchronousServerCallReturnsEvent` to `AsynchronousServerCallResultPoint`

Imposition time: IT_CpgExe

[In the context of a `RunnableEntity`, a given `AsynchronousServerCallResultPoint` shall only be referenced by one `AsynchronousServerCallReturnsEvent` in the role `eventSource`.

]

[constr_1523] No mode disabling for `OperationInvokedEvents`

Imposition time: IT_RteGen

[An `OperationInvokedEvent` shall not have a reference to a `ModeDeclaration` in the role `disabledMode`.

]

[constr_1538] Restriction for reference `ReceiverComSpec.dataElement`

Imposition time: IT_CpgExe

[The reference `ReceiverComSpec.dataElement` **shall not** refer to an `ArgumentDataPrototype` or `ParameterDataPrototype`.

]

[constr_1539] Restriction for `SenderComSpec.dataElement`

Imposition time: IT_CpgExe

[The reference `SenderComSpec.dataElement` **shall not** refer to an `ArgumentDataPrototype` or `ParameterDataPrototype`.

]

[constr_1540] Existence of [ClientComSpec.operation](#)

Imposition time: IT_CpgExe

[The reference [ClientComSpec.operation](#) **shall exist** if the [AbstractRequiredPortPrototype](#) that owns the [ClientComSpec](#) is typed by a [ClientServerInterface](#)..

]

[constr_1541] Existence of [ServerComSpec.operation](#)

Imposition time: IT_CpgExe

[The reference [ServerComSpec.operation](#) **shall exist** if the [AbstractProvidedPortPrototype](#) that owns the [ServerComSpec](#) is typed by a [ClientServerInterface](#).

]

[constr_1544] Standardized values and multiplicities for the modeling of [SwAxisIsGeneric](#) for the definition of a fix axis

Imposition time: IT_CpgExe

[

category of swAxisType	category of SwGenericAxisParamType	Multiplicity of swGenericAxisParam	Multiplicity of vf
FIX_AXIS_PAR	OFFSET	1	1
	SHIFT	1	1
FIX_AXIS_PAR_DIST	OFFSET	1	1
	DISTANCE	1	1
FIX_AXIS_PAR_LIST	LIST	1	1..*

]

[constr_1545] No initialization for fix axis

Imposition time: IT_CpgExe

[An [ApplicationValueSpecification](#) taken to initialize an [ApplicationPrimitiveDataType](#) that contains a fix axis shall not contain initial values for the axis index of the fix axis inside the [ApplicationPrimitiveDataType](#).

]

[constr_1583] PortInterfaceMapping for DataPrototype typed by Compound Primitive Data Type

Imposition time: IT_CpgExe

[There is one very limited use case to apply [PortInterfaceMapping](#) for a [DataPrototype](#) typed by a Compound Primitive Data Type: adjustment of the [shortName](#) of the [DataPrototype](#). Everything else is **not supported**.

]

[constr_1592] Definition of SwDataDefProps.displayPresentation depending on the capabilities of the data type

Imposition time: IT_CpgExe

[The definition of a [SwDataDefProps.displayPresentation](#) according to [[constr_1288](#)] and [[constr_1289](#)] shall only be applied for a [DataPrototype](#) of category [ARRAY](#) if the corresponding [ApplicationArrayDataType](#) or [ImplementationDataType](#) of category [ARRAY](#) supports the specification of a [SwDataDefProps.displayPresentation](#).

]

[constr_1602] Definition of SwDataDefProps.displayPresentation depending on the capabilities of the element

Imposition time: IT_CpgExe

[The definition of a [SwDataDefProps.displayPresentation](#) according to [[constr_1007](#)] and [[constr_1009](#)] is only supported for an [ApplicationArrayDataType](#) or an [ImplementationDataType](#) of category [ARRAY](#) if the aggregated [ApplicationArrayDataType.element](#) or [ImplementationDataType.subElement](#) also supports the specification of a [SwDataDefProps.displayPresentation](#).

]

[constr_1607] Only Wrapped Union Data Types in PortInterface

Imposition time: IT_CpgExe

[Within the scope of a [PortInterface](#) the usage of a Union data type is only supported

- for Wrapped Union Data Types.
- for a [PortInterface](#) that is used to type a [PortPrototype](#) that does not appear as a context in an `instanceRef` owned by a [DataMapping](#). See also [[constr_1441](#)].

.

]

[constr_1608] Existence of `rootParameterDataPrototype`

Imposition time: IT_CpgExe

[The reference `rootParameterDataPrototype` shall exist if and only if

- `AutosarDataType` of the `autosarParameter` is a composite data type and
- `targetDataPrototype` refers to a `DataPrototype` inside the `rootParameterDataPrototype`.

]

[constr_1609] Existence of `rootVariableDataPrototype`

Imposition time: IT_CpgExe

[The reference `rootVariableDataPrototype` shall exist if and only if

- the `AutosarDataType` of the `autosarVariable` is a composite data type and
- the `targetDataPrototype` refers to a `DataPrototype` inside the `rootVariableDataPrototype`.

]

[constr_1610] Existence of `SwDataDefProps.swValueBlockSize` and `SwDataDefProps.swValueBlockSizeMult`

Imposition time: IT_CpgExe

[Attributes `SwDataDefProps.swValueBlockSize` and `SwDataDefProps.swValueBlockSizeMult` shall not exist at the same time in the context of a given `SwDataDefProps`.

]

[constr_1611] Existence of `ImplementationDataTypeSubElementRef.implementationDataTypeElement` as opposed to `ImplementationDataTypeSubElementRef.parameterImplementationDataTypeElement`

Imposition time: IT_RteGen

[For any given `ImplementationDataTypeSubElementRef`, either the aggregation

- `ImplementationDataTypeSubElementRef.implementationDataTypeElement` or
- `ImplementationDataTypeSubElementRef.parameterImplementationDataTypeElement`

]

[constr_1622] Value of `TimingEvent.offset` vs. `TimingEvent.period`

Imposition time: IT_RteGen

[If a value is defined for attribute `TimingEvent.offset` then this value shall be greater than 0 and less or equal than the value of attribute `TimingEvent.period` of the respective `TimingEvent`.

]

[constr_1631] Applicability of `DataPrototypeMapping.secondToFirstDataTransformation`

Imposition time: IT_RteGen

[The reference to `DataTransformation` in the role `DataPrototypeMapping.secondToFirstDataTransformation` shall only exist if reference `DataPrototypeMapping.firstToSecondDataTransformation` exists and refers to a `DataTransformation` where attribute `dataTransformationKind` exists and is **not** set to the value `symmetric`.

]

[constr_1632] Restriction for `firstToSecondDataTransformation` and `secondToFirstDataTransformation`

Imposition time: IT_RteGen

[If both the reference `firstToSecondDataTransformation` and the reference `secondToFirstDataTransformation` exist in the context of the same `DataPrototypeMapping` then

- the `firstToSecondDataTransformation` shall refer to a `DataTransformation` with attribute `dataTransformationKind` set to `asymmetricToByteArray` and
- the `secondToFirstDataTransformation` shall refer to a `DataTransformation` with attribute `dataTransformationKind` set to `asymmetricFromByteArray`.

]

[constr_1634] Allowed combinations of [ApplicationDataType.category](#) vs. [CompuMethod.category](#)

Imposition time: IT_CpgExe

[

	IDENTICAL	LINEAR	SCALE_LINEAR	SCALE_LINEAR_AND_TEXTTABLE	RAT_FUNC	SCALE_RATIONAL_AND_TEXTTABLE	TEXTTABLE	TAB_NOINTP	BITFIELD_TEXTTABLE
VALUE	X	X	X	X	X	X	X	X	X
VAL_BLK	X	X	X	X	X	X	X	X	X
BOOLEAN							X		
CURVE	X	X	X	X	X	X	X	X	X
MAP	X	X	X	X	X	X	X	X	X
CUBOID	X	X	X	X	X	X	X	X	X
CUBE_4	X	X	X	X	X	X	X	X	X
CUBE_5	X	X	X	X	X	X	X	X	X

]

[constr_1635] Relevance of attribute [isOptional](#)

Imposition time: IT_RteGen

[If a [SubElementMapping](#) is defined for the elements of a structured data type then the attribute [isOptional](#)¹⁵ shall either not exist for the [firstElement](#) and [secondElement](#) or it shall have the identical value for the [firstElement](#) and [secondElement](#).

]

[constr_1636] Mapping of data types that represent an Optional Element Structure

Imposition time: IT_CpgExe

[An [ApplicationRecordDataType](#) with at least one [element](#) where attribute [isOptional](#) is set to `true` shall only be mapped to an [ImplementationDataType](#) that fulfills the structural requirements to represent an Optional Element Structure (see [TPS_SWCT_01774]).

]

¹⁵this is valid for both [ApplicationRecordElement](#) and [ImplementationDataTypeElement](#)

[constr_1637] Existence of `ImplementationDataTypeElement.isOptional` vs. `ImplementationDataType.isStructWithOptionalElement`

Imposition time: IT_CpgExe

[If one `ImplementationDataType.subElement` sets attribute `isOptional` to the value `true` then the enclosing `ImplementationDataType` shall also set attribute `isStructWithOptionalElement` to `true`.

]

[constr_1638] First `ImplementationDataTypeElement` of `ImplementationDataType` that represents an Optional Element Structure

Imposition time: IT_CpgExe

[The first `ImplementationDataTypeElement` of `ImplementationDataType` that represents an Optional Element Structure, i.e. the `availabilityBitfield` according to [TPS_SWCT_01774], shall not set attribute `isOptional` to `true`.

]

[constr_1639] `ImplementationDataTypeElement` with attribute `isOptional` set to `True`

Imposition time: IT_CpgExe

[An `ImplementationDataTypeElement` where attribute `isOptional` is set to `True` shall set the value of attribute `category` to either of the following values:

- `VALUE`
- `TYPE_REFERENCE`

]

[constr_1640] No use of Optional Element Structure for interaction with the diagnostic stack

Imposition time: IT_RteGen

[An `SwcServiceDependency` that aggregates a diagnostic-related subclass of `ServiceNeeds` shall not refer to any `PortPrototype` by means of either a `RoleBasedPortAssignment` or `RoleBasedDataAssignment` where the respective `PortInterface` contains any `DataPrototype` typed by an Optional Element Structure.

]

[constr_1662] Compatibility of `ApplicationRecordDataType` and `ImplementationDataType` that both represent an Optional Element Structure

Imposition time: IT_CpgExe

[An `ApplicationRecordDataType` that represents an Optional Element Structure shall (after all indirections created by `ImplementationDataTypes` of category `TYPE_REFERENCE` are resolved) only be mapped/connected to an `ImplementationDataType` of category `STRUCTURE` that represents an Optional Element Structure if corresponding pairs of elements have the same value of the attribute `isOptional`.

]

[constr_1679] Existence of attribute `RoleBasedDataAssignment.usedDataElement.localVariable` for `RoleBasedDataAssignment.role = signalBasedDiagnostics`

Imposition time: IT_RteGen

[If the attribute `RoleBasedDataAssignment.role` is set to the value `signalBasedDiagnostics` then the reference `RoleBasedDataAssignment.usedDataElement.localVariable` shall not exist.

]

[constr_1680] Existence of attribute `RoleBasedDataAssignment.usedDataElement.localVariable` for `RoleBasedDataAssignment.role = AppModeRequestInterface`

Imposition time: IT_RteGen

[If the attribute `RoleBasedDataAssignment.role` is set to the value `AppModeRequestInterface`, then the reference `RoleBasedDataAssignment.usedDataElement.localVariable` shall not exist.

]

[constr_1681] Existence of attribute `RoleBasedDataAssignment.usedDataElement.localVariable` for `RoleBasedDataAssignment.role = VerificationStatus`

Imposition time: IT_RteGen

[If the attribute `RoleBasedDataAssignment.role` is set to the value `VerificationStatus` then the reference `RoleBasedDataAssignment.usedDataElement.localVariable` shall not exist.

]

[constr_1682] Existence of the attribute `RoleBasedDataAssignment.usedDataElement.localVariable` for the value `RoleBasedDataAssignment.role = V2xFacVdp`

Imposition time: IT_RteGen

[If the attribute `RoleBasedDataAssignment.role` is set to the value `V2xFacVdp` then the reference `RoleBasedDataAssignment.usedDataElement.localVariable` shall not exist.

]

[constr_1694] Allowed target of `SwDataDefProps.implementationDataType`

Imposition time: IT_CpgExe

[The reference `SwDataDefProps.implementationDataType` shall only refer to an `ImplementationDataType`. Any other subclass of `AbstractImplementationDataType` is not supported as a reference target.

]

[constr_1712] Existence of attribute `ArrayValueSpecification.intendedPartialInitializationCount`

Imposition time: IT_CpgExe

[An `ArrayValueSpecification` where attribute `intendedPartialInitializationCount` exists shall only be applied for the initialization of an `ApplicationArrayDataType` where attribute `arraySizeSemantics` is set to `variableSize`.

]

[constr_1713] `NvBlockDescriptor.writingStrategy.usedDataElement` shall refer to `AutosarDataPrototype`

Imposition time: IT_RteGen

[The reference `NvBlockDescriptor.writingStrategy.usedDataElement` shall only refer to an `AutosarDataPrototype`.

]

[constr_1714] `AutosarDataPrototype` shall only be referenced by a single `NvBlockDescriptor.writingStrategy`

Imposition time: IT_RteGen

[If an `AutosarDataPrototype` in the context of a `PortPrototype` is referenced from a `NvBlockDescriptor.writingStrategy` then this `AutosarDataPrototype` shall not be referenced from any other `NvBlockDescriptor.writingStrategy`.

]

[constr_1715] Possible values of attribute `NvBlockDescriptor.writingStrategy.role`

Imposition time: IT_RteGen

[The attribute `NvBlockDescriptor.writingStrategy.role` shall only have one of the following values (see [TPS_SWCT_01586]):

- `storeAtShutdown`
- `storeImmediate`
- `storeOnChange`

]

[constr_1716] Consistency of attribute `NvBlockDescriptor.writingStrategy.role` set to `storeAtShutdown`

Imposition time: IT_RteGen

[The existence of `NvBlockDescriptor.writingStrategy` where attribute `role` is set to `storeAtShutdown` is only supported if `NvBlockDescriptor.nvBlockNeeds.storeAtShutdown` exists and is set to `true`.

]

[constr_1717] Consistency of attribute `NvBlockDescriptor.writingStrategy.role` set to `storeImmediate`

Imposition time: IT_RteGen

[The existence of `NvBlockDescriptor.writingStrategy` where attribute `role` is set to `storeImmediate` is only supported if `NvBlockDescriptor.nvBlockNeeds.storeImmediate` exists and is set to `true`.

]

[constr_1718] Inheritance of `SwDataDefProps.dataConstr` from an array data type to the array elements

Imposition time: IT_CpgExe

[A `SwDataDefProps.dataConstr` specified for an `ApplicationArrayDataType` or `ImplementationDataType` of category `ARRAY` applies to all array leaf elements represented by (potentially multiple levels of) `ApplicationArrayDataType.element` or `ImplementationDataType.subElement`.

In this case, the `ApplicationArrayDataType.element` or `ImplementationDataType.subElement` shall not have an own `SwDataDefProps.dataConstr`. This also applies for multi-dimensional array data types.

]

[constr_1719] Inheritance of `SwDataDefProps.displayFormat` from an array data type to the array elements

Imposition time: IT_CpgExe

[A `SwDataDefProps.displayFormat` specified for an `ApplicationArrayDataType` or `ImplementationDataType` of category ARRAY applies to all array leaf elements represented by (potentially multiple levels of) `ApplicationArrayDataType.element` or `ImplementationDataType.subElement`.

In this case, the `ApplicationArrayDataType.element` or `ImplementationDataType.subElement` shall not have an own `SwDataDefProps.displayFormat`. This also applies for multi-dimensional array data types.

]

[constr_1720] Inheritance of `SwDataDefProps.stepSize` from an array data type to the array elements

Imposition time: IT_CpgExe

[A `SwDataDefProps.stepSize` specified for an `ApplicationArrayDataType` or `ImplementationDataType` of category ARRAY applies to all array leaf elements represented by (potentially multiple levels of) `ApplicationArrayDataType.element` or `ImplementationDataType.subElement`.

In this case, the `ApplicationArrayDataType.element` or `ImplementationDataType.subElement` shall not have an own `SwDataDefProps.stepSize`. This also applies for multi-dimensional array data types.

]

[constr_1724] Usage of attribute `ClientServerOperation.diagArgIntegrity`

Imposition time: IT_RteGen

[With the exception of the context of a `ServiceSwComponentType`, the attribute `ClientServerOperation.diagArgIntegrity` shall only have the value `true` if the `ClientServerInterface` containing the respective `ClientServerOperation` is used to type a `PPortPrototype` that is referenced by a `RoleBasedPortAssignment` aggregated by a `SwcServiceDependency` that in turn aggregates `DiagnosticRoutineNeeds`.

]

[constr_1726] Ordering of `MetaDataItemSet.metaDataItem`

Imposition time: IT_CpgExe

[The ordering of the elements of `MetaDataItemSet.metaDataItem` shall be **descending** with respect to the value of `MetaDataItem.length`, such that the `MetaDataItem` with the largest value of attribute `length` is located in the first position and

the `MetaDataItem` with the smallest value of attribute `length` is located in the last position.

]

[constr_1735] Limitation of the aggregation of `AutosarVariableRef` in the context of an `NvBlockDataMapping` owned by a `BulkNvDataDescriptor`

Imposition time: IT_RteGen

[Any `NvBlockDataMapping` owned by a `BulkNvDataDescriptor` shall only aggregate an `AutosarVariableRef` in the role `readNvData` and `nvRamBlockElement` (that in turn refers to the `BulkNvDataDescriptor.bulkNvBlock`).

]

[constr_1741] Restriction to explicit sending semantics for the usage of `Data Services` in the context of a `SwcServiceDependency` that aggregates `DiagnosticValueNeeds` that in turn is referenced by a `DiagnosticIoControlNeeds`

Imposition time: IT_RteGen

[A `dataElement`

- that is referenced by a `RoleBasedDataAssignment` (where the attribute `role` is set to `signalBasedDiagnostics`) owned by a `SwcServiceDependency` that aggregates `DiagnosticValueNeeds` that in turn is referenced by a `DiagnosticIoControlNeeds`
- **shall also be referenced** by a `VariableAccess` aggregated in the role `dataSendPoint` by a given `RunnableEntity` that in turn belongs to the enclosing `SwcInternalBehavior`.
- **shall not be referenced** by a `VariableAccess` aggregated in the role `dataWriteAccess` by a given `RunnableEntity` that in turn belongs to the enclosing `SwcInternalBehavior`.

]

[constr_1754] Aggregation of `NumericalRuleBasedValueSpecification`

Imposition time: IT_CpgExe

[Each `ArrayValueSpecification` shall only aggregate at most one `NumericalRuleBasedValueSpecification` in the role `element`.

If one `NumericalRuleBasedValueSpecification` is aggregated then it shall be the only aggregated element, i.e. no further `ValueSpecification` shall exist in the same aggregation where an `NumericalRuleBasedValueSpecification` is aggregated.

]

[constr_1755] Aggregation of CompositeRuleBasedValueSpecification

Imposition time: IT_CpgExe

[Each `ArrayValueSpecification` shall only aggregate at most one `CompositeRuleBasedValueSpecification` in the role element.

If one `CompositeRuleBasedValueSpecification` is aggregated then it shall be the only aggregated element, i.e. no further `ValueSpecification` shall exist in the same aggregation where an `CompositeRuleBasedValueSpecification` is aggregated.

]

[constr_1771] Existence of SwValueCont.unit

Imposition time: IT_CpgExe

[For every `SwValueCont`, the reference `unit` shall exist

]

[constr_1773] Value of attribute dataSendPoint.returnValueProvision

Imposition time: IT_CpgExe

[All `RunnableEntity.dataSendPoint` that refer to the same `accessedVariable` shall define the identical value for attribute `returnValueProvision`.

]

[constr_1774] Value of attribute dataReceivePointByArgument.returnValueProvision

Imposition time: IT_CpgExe

[All `RunnableEntity.dataReceivePointByArgument` that refer to the same `accessedVariable` shall define the identical value for attribute `returnValueProvision`.

]

[constr_1775] Value of attribute serverCallPoint.returnValueProvision

Imposition time: IT_CpgExe

[All `RunnableEntity.serverCallPoint` that refer to the same `operation` shall define the identical value of attribute `returnValueProvision`.

]

[constr_1776] Value of attribute `asynchronousServerCallResultPoint.returnValueProvision`

Imposition time: IT_CpgExe

[All `RunnableEntity.asynchronousServerCallResultPoint` that refer to the same `AsynchronousServerCallPoint.operation` shall define the identical value of attribute `returnValueProvision`.

]

[constr_1777] Value of attribute `externalTriggeringPoint.returnValueProvision`

Imposition time: IT_CpgExe

[All `RunnableEntity.externalTriggeringPoint` that refer to the same `trigger` shall define the identical value of attribute `returnValueProvision`.

]

[constr_1778] Value of attribute `modeSwitchPoint.returnValueProvision`

Imposition time: IT_CpgExe

[All `RunnableEntity.modeSwitchPoint` that refer to the same `modeGroup` shall define the identical value of attribute `returnValueProvision`.

]

[constr_1779] Scope of the definition of an `AbstractRuleBasedValueSpecification`

Imposition time: IT_CpgExe

[An `AbstractRuleBasedValueSpecification` shall only be defined in the context of an `ArrayValueSpecification` or a `ConstantSpecification`. If the `AbstractRuleBasedValueSpecification` is defined in the context of a `ConstantSpecification` then a reference to this `ConstantSpecification` shall only be created in the context of an `ArrayValueSpecification`.

]

[constr_1783] Existence of attribute `ImplementationDataTypeElement.arrayImplPolicy`

Imposition time: IT_CpgExe

[Attribute `ImplementationDataTypeElement.arrayImplPolicy` shall only exist if the enclosing `ImplementationDataType` or `ImplementationDataTypeElement` is of category `ARRAY`.

]

[constr_1860] Multiplicity of `DelegationSwConnector.innerPort`

Imposition time: IT_CompSwcT

[For each `DelegationSwConnector`, the reference `DelegationSwConnector.innerPort` shall exist.

]

[constr_1861] Multiplicity of `DelegationSwConnector.outerPort`

Imposition time: IT_CompSwcT

[For each `DelegationSwConnector`, the reference `DelegationSwConnector.outerPort` shall exist.

]

[constr_1862] Multiplicity of `PassThroughSwConnector.requiredOuterPort`

Imposition time: IT_CompSwcT

[For each `PassThroughSwConnector`, the reference `PassThroughSwConnector.requiredOuterPort` shall exist.

]

[constr_1863] Multiplicity of `PassThroughSwConnector.providedOuterPort`

Imposition time: IT_CompSwcT

[For each `PassThroughSwConnector`, the reference `PassThroughSwConnector.providedOuterPort` shall exist.

]

[constr_1864] Multiplicity of `InstantiationRTEEventProps.refinedEvent`

Imposition time: IT_RteGen

[For each `InstantiationRTEEventProps`, the instance-reference `InstantiationRTEEventProps.refinedEvent` shall exist.

]

[constr_1865] Existence of `InvalidationPolicy.dataElement`

Imposition time: IT_CpgExe

[For each `InvalidationPolicy`, the reference `InvalidationPolicy.dataElement` shall exist.

]

[constr_1866] Existence of `MetaDataItem.length`*Imposition time:* IT_CpgExe[For each `MetaDataItem`, attribute `length` shall exist.

]

[constr_1867] Existence of `MetaDataItem.metaDataType`*Imposition time:* IT_CpgExe[For each `MetaDataItem`, attribute `metaDataType` shall exist.

]

[constr_1868] Existence of `MetaDataItemSet.dataElement`*Imposition time:* IT_CpgExe[For each `MetaDataItemSet` that aggregates at least one `metaDataItem`, at least one reference to a `dataElement` shall exist.

]

[constr_1869] Existence of attribute `ArgumentDataPrototype.direction`*Imposition time:* IT_CpgExe[For each `ArgumentDataPrototype`, attribute `direction` shall be defined.

]

[constr_1871] Existence of attribute `ModeRequestTypeMap.implementationDataType`*Imposition time:* IT_CpgExe[For each `ModeRequestTypeMap`, attribute `implementationDataType` shall exist.

]

[constr_1872] Existence of attribute `ModeRequestTypeMap.modeGroup`*Imposition time:* IT_CpgExe[For each `ModeRequestTypeMap`, attribute `modeGroup` shall exist.

]

[constr_1873] Existence of `DataPrototypeMapping.firstDataPrototype`*Imposition time:* IT_RteGen

[For each `DataPrototypeMapping`, the reference in the role `firstDataPrototype` shall exist.

]

[constr_1874] Existence of `DataPrototypeMapping.secondDataPrototype`*Imposition time:* IT_RteGen

[For each `DataPrototypeMapping`, the reference in the role `secondDataPrototype` shall exist.

]

[constr_1875] Existence of reference `ClientServerOperationMapping.firstOperation`*Imposition time:* IT_RteGen

[For each `ClientServerOperationMapping`, the reference in the role `firstOperation` shall exist.

]

[constr_1876] Existence of reference `ClientServerOperationMapping.secondOperation`*Imposition time:* IT_RteGen

[For each `ClientServerOperationMapping`, the reference in the role `secondOperation` shall exist.

]

[constr_1877] Existence of reference `ModeDeclarationGroupPrototypeMapping.firstModeGroup`*Imposition time:* IT_RteGen

[For each `ModeDeclarationGroupPrototypeMapping`, the reference in the role `firstModeGroup` shall exist.

]

[constr_1878] Existence of reference `ModeDeclarationGroupPrototypeMapping.secondModeGroup`*Imposition time:* IT_RteGen

[For each `ModeDeclarationGroupPrototypeMapping`, the reference in the role `secondModeGroup` shall exist.

]

[constr_1879] Existence of reference `ModeDeclarationMapping.firstMode`*Imposition time:* IT_RteGen

[For each `ModeDeclarationMapping`, at least one reference `firstMode` shall exist.

]

[constr_1880] Existence of reference `ModeDeclarationMapping.secondMode`*Imposition time:* IT_RteGen

[For each `ModeDeclarationMapping`, the reference `secondMode` shall exist.

]

[constr_1881] Existence of reference `TriggerMapping.firstTrigger`*Imposition time:* IT_RteGen

[For each `TriggerMapping`, the reference `firstTrigger` shall exist.

]

[constr_1882] Existence of reference `TriggerMapping.secondTrigger`*Imposition time:* IT_RteGen

[For each `TriggerMapping`, the reference `secondTrigger` shall exist.

]

[constr_1883] Existence of `ApplicationCompositeDataTypeSubElementRef.applicationCompositeElement`*Imposition time:* IT_RteGen

[For each `ApplicationCompositeDataTypeSubElementRef`, the reference `applicationCompositeElement` shall exist.

]

[constr_1884] Existence of attribute `TextTableMapping.identicalMapping`*Imposition time:* IT_RteGen[For each `TextTableMapping`, the attribute `identicalMapping` shall exist.

]

[constr_1885] Existence of attribute `TextTableMapping.mappingDirection`*Imposition time:* IT_RteGen[For each `TextTableMapping`, the attribute `mappingDirection` shall exist.

]

[constr_1886] Existence of attribute `TextTableValuePair.firstValue`*Imposition time:* IT_RteGen[For each `TextTableValuePair`, the attribute `firstValue` shall exist.

]

[constr_1887] Existence of attribute `TextTableValuePair.secondValue`*Imposition time:* IT_RteGen[For each `TextTableValuePair`, the attribute `secondValue` shall exist.

]

[constr_1888] Existence of attribute `DataTransformation.executeDespiteDataUnavailability`*Imposition time:* IT_RteGen[For each `DataTransformation`, the attribute `executeDespiteDataUnavailability` shall exist.

]

[constr_1889] Existence of attribute `QueuedReceiverComSpec.queueLength`*Imposition time:* IT_CpgExe[For each `QueuedReceiverComSpec`, attribute `queueLength` shall exist.

]

[constr_1890] Existence of attribute `DataFilter.dataFilterType`*Imposition time:* IT_CpgExe[For each `DataFilter`, attribute `dataFilterType` shall exist.

]

[constr_1892] Existence of attribute `TransmissionAcknowledgementRequest.timeout`*Imposition time:* IT_CpgExe

[For each `TransmissionAcknowledgementRequest`, attribute `timeout` shall exist.

]

[constr_1894] Existence of attribute `ModeSwitchSenderComSpec.queueLength`*Imposition time:* IT_CpgExe

[For each `ModeSwitchSenderComSpec`, attribute `queueLength` shall exist.

]

[constr_1895] Existence of attribute `ModeSwitchSenderComSpec.modeGroup`*Imposition time:* IT_CpgExe

[For each `ModeSwitchSenderComSpec`, attribute `modeGroup` shall exist.

]

[constr_1896] Existence of attribute `ModeSwitchReceiverComSpec.modeGroup`*Imposition time:* IT_CpgExe

[For each `ModeSwitchReceiverComSpec`, attribute `modeGroup` shall exist.

]

[constr_1897] Existence of reference `ParameterProvideComSpec.parameter`*Imposition time:* IT_CpgExe

[For each `ParameterProvideComSpec`, the reference `parameter` shall exist.

]

[constr_1898] Existence of reference `ParameterRequireComSpec.parameter`*Imposition time:* IT_CpgExe

[For each `ParameterRequireComSpec`, the reference `parameter` shall exist.

]

[constr_1899] Existence of reference `NvRequireComSpec.variable`*Imposition time:* IT_CpgExe

[For each `NvRequireComSpec`, the reference `variable` shall exist.

]

[constr_1900] Existence of reference `NvProvideComSpec.variable`*Imposition time:* IT_CpgExe[For each `NvProvideComSpec`, the reference `variable` shall exist.

]

[constr_1901] Existence of attribute `EndToEndDescription.category`*Status:* OBSOLETE*Imposition time:* IT_CpgExe[For each `EndToEndDescription`, attribute `category` shall exist.

]

[constr_1902] Existence of attribute `EndToEndProtection.endToEndProfile`*Status:* OBSOLETE*Imposition time:* IT_CpgExe[For each `EndToEndProtection`, attribute `endToEndProfile` shall exist.

]

[constr_1903] Existence of reference `DataTypeMap.applicationDataType`*Imposition time:* IT_CpgExe[For each `DataTypeMap`, reference `applicationDataType` shall exist.

]

[constr_1904] Existence of reference `DataTypeMap.implementationDataType`*Imposition time:* IT_CpgExe[For each `DataTypeMap`, reference `implementationDataType` shall exist.

]

[constr_1905] Existence of attribute `SwTextProps.arraySizeSemantics`*Imposition time:* IT_CpgExe[For each `SwTextProps`, attribute `arraySizeSemantics` shall exist.

]

[constr_1906] Existence of attribute `SwTextProps.swMaxTextSize`*Imposition time:* IT_CpgExe[For each `SwTextProps`, attribute `swMaxTextSize` shall exist.

]

[constr_1907] Existence of attribute `ApplicationArrayType.element`

Imposition time: IT_RteGen

[For each `ApplicationArrayType`, the aggregation of `ApplicationArrayElement` in the role `element` shall exist.

]

[constr_1908] Existence of attribute `ApplicationRecordDataType.element`

Imposition time: IT_RteGen

[For each `ApplicationRecordDataType`, the aggregation of `ApplicationRecordElement` in the role `element` shall exist.

]

[constr_1909] Existence of attribute `ImplementationProps.symbol`

Imposition time: IT_CpgExe

[For each `ImplementationProps`, the attribute `symbol` shall exist.

]

[constr_1910] Existence of attribute `BaseType.baseTypeDefinition`

Imposition time: IT_CpgExe

[For each `BaseType` (which will be utilized in the form of `SwBaseType`), the aggregation in the role `baseTypeDefinition` shall exist.

]

[constr_1911] Existence of `ArVariableInImplementationDataInstanceRef.targetDataPrototype`

Imposition time: IT_CpgExe

[For each `ArVariableInImplementationDataInstanceRef`, the reference `targetDataPrototype` shall exist.

]

[constr_1912] Existence of reference `ArParameterInImplementationDataInstanceRef.targetDataPrototype`

Imposition time: IT_CpgExe

[For each `ArParameterInImplementationDataInstanceRef`, the reference `targetDataPrototype` shall exist.

]

[constr_1913] Existence of attribute `CompuRationalCoeffs.compuDenominator`*Imposition time:* IT_CpgExe

[For each `CompuRationalCoeffs`, the attribute `compuDenominator` shall exist.
]

[constr_1914] Existence of attribute `CompuRationalCoeffs.compuNumerator`*Imposition time:* IT_CpgExe

[For each `CompuRationalCoeffs`, the attribute `compuNumerator` shall exist.
]

[constr_1915] Existence of attribute `PhysicalDimensionMapping.firstPhysicalDimension`*Imposition time:* IT_CpgExe

[For each `PhysicalDimensionMapping`, attribute `firstPhysicalDimension` shall exist.
]

[constr_1916] Existence of attribute `PhysicalDimensionMapping.secondPhysicalDimension`*Imposition time:* IT_CpgExe

[For each `PhysicalDimensionMapping`, attribute `secondPhysicalDimension` shall exist.
]

[constr_1917] Existence of `ConstantSpecification.valueSpec`*Imposition time:* IT_CpgExe

[For each `ConstantSpecification`, the aggregation of `ValueSpecification` in the role `valueSpec` shall exist.
]

[constr_1918] Existence of `RecordValueSpecification.field`*Imposition time:* IT_CpgExe

[For each `RecordValueSpecification`, the aggregation of `ValueSpecification` in the role `field` shall exist.
]

[constr_1919] Existence of `TextValueSpecification.value`*Imposition time:* IT_CpgExe[For each `TextValueSpecification`, attribute `value` shall exist.

]

[constr_1920] Existence of `NumericalValueSpecification.value`*Imposition time:* IT_CpgExe[For each `NumericalValueSpecification`, attribute `value` shall exist.

]

[constr_1921] Existence of `ReferenceValueSpecification.referenceValue`*Imposition time:* IT_CpgExe[For each `ReferenceValueSpecification`, attribute `referenceValue` shall exist.

]

[constr_1922] Existence of `ApplicationRuleBasedValueSpecification.category`*Imposition time:* IT_CpgExe[For each `ApplicationRuleBasedValueSpecification`, attribute `category` shall exist.

]

[constr_1923] Existence of `RuleBasedAxisCont.ruleBasedValues`*Imposition time:* IT_CpgExe[For each `RuleBasedAxisCont`, attribute `ruleBasedValues` shall exist.

]

[constr_1924] Existence of `RuleBasedValueCont.ruleBasedValues`*Imposition time:* IT_CpgExe[For each `RuleBasedValueCont`, attribute `ruleBasedValues` shall exist.

]

[constr_1925] Existence of `NumericalRuleBasedValueSpecification.ruleBasedValues`*Imposition time:* IT_CpgExe[For each `NumericalRuleBasedValueSpecification`, attribute `ruleBasedValues` shall exist.

]

[constr_1926] Existence of `RuleBasedValueSpecification.rule`*Imposition time:* IT_CpgExe[For each `RuleBasedValueSpecification`, attribute `rule` shall exist.

]

[constr_1927] Existence of `RuleBasedValueSpecification.arguments`*Imposition time:* IT_CpgExe[For each `RuleBasedValueSpecification`, the aggregation of `RuleArguments` in the role `arguments` shall exist.

]

[constr_1928] Existence of `CompositeRuleBasedValueSpecification.rule`*Imposition time:* IT_CpgExe[For each `CompositeRuleBasedValueSpecification`, attribute `rule` shall exist.

]

[constr_1929] Existence of `CompositeRuleBasedValueSpecification.argument`*Imposition time:* IT_CpgExe[For each `CompositeRuleBasedValueSpecification`, the aggregation of `CompositeValueSpecification` in the role `argument` shall exist.

]

[constr_1930] Existence of `ConstantReference.constant`*Imposition time:* IT_CpgExe[For each `ConstantReference`, attribute `constant` shall exist.

]

[constr_1931] Existence of `ConstantSpecificationMapping.applConstant`

Imposition time: IT_CpgExe

[For each `ConstantSpecificationMapping`, the reference to meta-class `ConstantSpecification` in the role `applConstant` shall exist.

]

[constr_1932] Existence of `ConstantSpecificationMapping.implConstant`

Imposition time: IT_CpgExe

[For each `ConstantSpecificationMapping`, the reference to meta-class `ConstantSpecification` in the role `implConstant` shall exist.

]

[constr_1933] Existence of `CalibrationParameterValue.initializedParameter`

Imposition time: IT_CpgExe

[For each `CalibrationParameterValue`, the reference to meta-class `ConstantSpecification` in the role `initializedParameter` shall exist.

]

[constr_1935] Existence of attribute `SwcInternalBehavior.supportsMultipleInstantiation`

Imposition time: IT_CpgExe

[For each `SwcInternalBehavior`, attribute `supportsMultipleInstantiation` shall exist.

]

[constr_1936] Existence of attribute `RunnableEntity.symbol`

Imposition time: IT_CpgExe

[For each `RunnableEntity`, attribute `symbol` shall exist.

]

[constr_1938] Existence of attribute `RunnableEntityArgument.symbol`

Imposition time: IT_CpgExe

[For each `RunnableEntityArgument`, attribute `symbol` shall exist.

]

[constr_1939] Existence of attribute ExecutableEntityActivationReason.bitPosition*Imposition time:* IT_CpgExe

[For each ExecutableEntityActivationReason, attribute bitPosition shall exist.

]

[constr_1940] Existence of attribute AsynchronousServerCallReturnsEvent.eventSource*Imposition time:* IT_CpgExe

[For each AsynchronousServerCallReturnsEvent, attribute eventSource shall exist.

]

[constr_1941] Existence of attribute DataSendCompletedEvent.eventSource*Imposition time:* IT_CpgExe

[For each DataSendCompletedEvent, attribute eventSource shall exist.

]

[constr_1942] Existence of attribute DataWriteCompletedEvent.eventSource*Imposition time:* IT_CpgExe

[For each DataWriteCompletedEvent, attribute eventSource shall exist.

]

[constr_1943] Existence of attribute DataReceivedEvent.data*Imposition time:* IT_CpgExe

[For each DataReceivedEvent, attribute data shall exist.

]

[constr_1944] Existence of attribute DataReceiveErrorEvent.data*Imposition time:* IT_CpgExe

[For each DataReceiveErrorEvent, attribute data shall exist.

]

[constr_1945] Existence of attribute `OperationInvokedEvent.operation`*Imposition time:* IT_CpgExe[For each `OperationInvokedEvent`, attribute `operation` shall exist.

]

[constr_1946] Existence of attribute `SwcModeSwitchEvent.activation`*Imposition time:* IT_RteGen[For each `SwcModeSwitchEvent`, attribute `activation` shall exist.

]

[constr_1947] Existence of reference `SwcModeSwitchEvent.mode`*Imposition time:* IT_RteGen[For each `SwcModeSwitchEvent`, the reference to `ModeDeclaration` in the role `mode` shall exist.

]

[constr_1948] Existence of attribute `ModeSwitchedAckEvent.eventSource`*Imposition time:* IT_RteGen[For each `ModeSwitchedAckEvent`, attribute `eventSource` shall exist.

]

[constr_1949] Existence of attribute `ExternalTriggerOccurredEvent.trigger`*Imposition time:* IT_RteGen[For each `ExternalTriggerOccurredEvent`, attribute `trigger` shall exist.

]

[constr_1950] Existence of attribute `InternalTriggerOccurredEvent.eventSource`*Imposition time:* IT_RteGen[For each `InternalTriggerOccurredEvent`, the attribute `eventSource` shall exist.

]

[constr_1951] Existence of attribute `WaitPoint.timeout`*Imposition time:* IT_RteGen[For each `WaitPoint`, attribute `timeout` shall exist.

]

[constr_1952] Existence of reference `WaitPoint.trigger`*Imposition time:* IT_CpgExe[For each `WaitPoint`, the reference to `RTEEvent` in the role `trigger` shall exist.

]

[constr_1953] Existence of attribute `SwcExclusiveAreaPolicy.apiPrinciple`*Imposition time:* IT_RteGen[For each `SwcExclusiveAreaPolicy` that refers to an `exclusiveArea`, attribute `apiPrinciple` shall exist.

]

[constr_1954] Existence of attribute `VariableAccess.accessedVariable`*Imposition time:* IT_CpgExe[For each `VariableAccess`, attribute `accessedVariable` shall exist.

]

[constr_1955] Existence of attribute `ServerCallPoint.operation`*Imposition time:* IT_CpgExe[For each `ServerCallPoint`, attribute `operation` shall exist.

]

[constr_1956] Existence of attribute `ServerCallPoint.timeout`*Imposition time:* IT_RteGen[For each `ServerCallPoint`, attribute `timeout` shall exist.

]

[constr_1957] Existence of attribute `AsynchronousServerCallResultPoint.asynchronousServerCallPoint`

Imposition time: IT_CpgExe

[For each `AsynchronousServerCallResultPoint`, the reference to `AsynchronousServerCallPoint` in the role `asynchronousServerCallPoint` shall exist.

]

[constr_1958] Existence of attribute `ParameterAccess.accessedParameter`

Imposition time: IT_CpgExe

[For each `ParameterAccess`, attribute `accessedParameter` shall exist.

]

[constr_1959] Existence of attribute `InstantiationDataDefProps.swDataDefProps`

Imposition time: IT_CpgExe

[For each `InstantiationDataDefProps`, attribute `swDataDefProps` shall exist.

]

[constr_1960] Existence of attribute `PortAPIOption.port`

Imposition time: IT_CpgExe

[For each `PortAPIOption`, attribute `port` shall exist.

]

[constr_1961] Existence of attribute `PortDefinedArgumentValue.value`

Imposition time: IT_RteGen

[For each `PortDefinedArgumentValue`, attribute `value` shall exist.

]

[constr_1962] Existence of attribute `PortDefinedArgumentValue.valueType`

Imposition time: IT_RteGen

[For each `PortDefinedArgumentValue`, attribute `valueType` shall exist.

]

[constr_1963] Existence of attribute `CommunicationBufferLocking.supportBufferLocking`*Imposition time:* IT_RteGen

[For each `CommunicationBufferLocking`, attribute `supportBufferLocking` shall exist.

]

[constr_1964] Existence of attribute `PerInstanceMemory.type`*Imposition time:* IT_CpgExe

[For each `PerInstanceMemory`, attribute `type` shall exist.

]

[constr_1965] Existence of attribute `PerInstanceMemory.typeDefinition`*Imposition time:* IT_CpgExe

[For each `PerInstanceMemory`, attribute `typeDefinition` shall exist.

]

[constr_1966] Existence of attribute `Implementation.swVersion`*Imposition time:* IT_RteGen

[For each `Implementation`, attribute `swVersion` shall exist.

]

[constr_1967] Existence of attribute `Implementation.vendorId`*Imposition time:* IT_RteGen

[For each `Implementation`, attribute `vendorId` shall exist.

]

[constr_1968] Existence of attribute `Implementation.codeDescriptor`*Imposition time:* IT_RteGen

[For each `Implementation`, at least one aggregation of `Code` in the role `codeDescriptor` shall exist.

]

[constr_1969] Existence of attribute `SwcImplementation.behavior`*Imposition time:* IT_RteGen[For each `SwcImplementation`, attribute `behavior` shall exist.

]

[constr_1970] Existence of attribute `PerInstanceMemorySize.alignment`*Imposition time:* IT_RteGen[For each `PerInstanceMemorySize`, attribute `alignment` shall exist.

]

[constr_1971] Existence of attribute `PerInstanceMemorySize.perInstanceMemory`*Imposition time:* IT_RteGen[For each `PerInstanceMemorySize`, the reference to `PerInstanceMemory` in the role `perInstanceMemory` shall exist.

]

[constr_1972] Existence of attribute `PerInstanceMemorySize.size`*Imposition time:* IT_RteGen[For each `PerInstanceMemorySize`, attribute `size` shall exist.

]

[constr_1973] Existence of attribute `ModeDeclarationGroup.initialMode`*Imposition time:* IT_CpgExe[For each `ModeDeclarationGroup`, the reference to `ModeDeclaration` in the role `initialMode` shall exist.

]

[constr_1974] Existence of attribute `ModeDeclarationGroup.modeDeclaration`*Imposition time:* IT_CpgExe[For each `ModeDeclarationGroup`, at least one `ModeDeclaration` shall be aggregated in the role `modeDeclaration`.

]

[constr_1975] Existence of attribute `ModeTransition.enteredMode`

Imposition time: IT_RteGen

[For each `ModeTransition`, the reference to `ModeDeclaration` in the role `enteredMode` shall exist.

]

[constr_1976] Existence of attribute `ModeTransition.exitedMode`

Imposition time: IT_RteGen

[For each `ModeTransition`, the reference to `ModeDeclaration` in the role `exitedMode` shall exist.

]

[constr_1977] Existence of attribute `ModeErrorBehavior.errorReactionPolicy`

Imposition time: IT_RteGen

[For each `ModeErrorBehavior`, the attribute `errorReactionPolicy` shall exist.

]

[constr_1978] Existence of attribute `SwcModeManagerErrorEvent.modeGroup`

Imposition time: IT_RteGen

[For each `SwcModeManagerErrorEvent`, the instance reference to `ModeDeclaration` in the role `modeGroup` shall exist.

]

[constr_1979] Existence of the reference `SwcBswMapping.bswBehavior`

Imposition time: IT_RteGen

[For each `SwcBswMapping`, the reference to `BswInternalBehavior` in the role `bswBehavior` shall exist.

]

[constr_1980] Existence of the reference `SwcBswMapping.swcBehavior`

Imposition time: IT_RteGen

[For each `SwcBswMapping`, the reference to `BswInternalBehavior` in the role `swcBehavior` shall exist.

]

[constr_1981] Existence of attribute `NvBlockDescriptor.nvBlockNeeds`

Imposition time: IT_RteGen

[For each `NvBlockDescriptor`, attribute `nvBlockNeeds` shall exist.

]

[constr_1982] Existence of attribute `ModeSwitchEventTriggeredActivity.role`

Imposition time: IT_RteGen

[For each `ModeSwitchEventTriggeredActivity`, attribute `role` shall exist.

]

[constr_1983] Existence of attribute `ModeSwitchEventTriggeredActivity.swcModeSwitchEvent`

Imposition time: IT_RteGen

[For each `ModeSwitchEventTriggeredActivity`, attribute `swcModeSwitchEvent` shall exist.

]

[constr_1984] Existence of instance reference `NvBlockDataMapping.nvRamBlockElement`

Imposition time: IT_RteGen

[For each `NvBlockDataMapping`, the instance reference to `ModeDeclaration` in the role `nvRamBlockElement` shall exist.

]

[constr_1985] Existence of the reference `SupervisedEntityNeeds.toleratedFailedCycles`

Imposition time: IT_RteGen

[For each `SupervisedEntityNeeds`, the reference to `BswInternalBehavior` in the role `toleratedFailedCycles` shall exist.

]

[constr_1986] Existence of the reference `DiagnosticRoutineNeeds.diagRoutineType`

Imposition time: IT_RteGen

[For each `DiagnosticRoutineNeeds`, the attribute `diagRoutineType` shall exist.

]

**[constr_1987] Existence of instance reference [RapidPrototypingScenario](#).
[hostSystem](#)***Imposition time:* IT_RteGen

[For each [RapidPrototypingScenario](#), the instance reference to [ModeDeclaration](#) in the role [hostSystem](#) shall exist.

]

[constr_1988] Existence of attribute [RptProfile.maxServicePointId](#)*Imposition time:* IT_RteGen

[For each [RptProfile](#), attribute [maxServicePointId](#) shall exist.

]

[constr_1989] Existence of attribute [RptProfile.minServicePointId](#)*Imposition time:* IT_RteGen

[For each [RptProfile](#), attribute [minServicePointId](#) shall exist.

]

[constr_1990] Existence of attribute [RptProfile.servicePointSymbolPost](#)*Imposition time:* IT_RteGen

[For each [RptProfile](#), attribute [servicePointSymbolPost](#) shall exist.

]

[constr_1991] Existence of attribute [RptProfile.servicePointSymbolPre](#)*Imposition time:* IT_RteGen

[For each [RptProfile](#), attribute [servicePointSymbolPre](#) shall exist.

]

[constr_1992] Existence of attribute [RptProfile.stimEnabler](#)*Imposition time:* IT_RteGen

[For each [RptProfile](#), attribute [stimEnabler](#) shall exist.

]

[constr_1993] Existence of attribute [RptImplPolicy.rptEnablerImplType](#)*Imposition time:* IT_RteGen

[For each [RptImplPolicy](#), attribute [rptEnablerImplType](#) shall exist

]

[constr_1994] Existence of attribute `RptImplPolicy.rptPreparationLevel`*Imposition time:* IT_RteGen

[For each `RptImplPolicy`, attribute `rptPreparationLevel` shall exist
]

[constr_1995] Existence of attribute `RptSwPrototypingAccess.rptHookAccess`*Imposition time:* IT_RteGen

[For each `RptSwPrototypingAccess`, attribute `rptHookAccess` shall exist.
]

[constr_1996] Existence of attribute `RptSwPrototypingAccess.rptReadAccess`*Imposition time:* IT_RteGen

[For each `RptSwPrototypingAccess`, attribute `rptReadAccess` shall exist.
]

[constr_1997] Existence of attribute `RptSwPrototypingAccess.rptWriteAccess`*Imposition time:* IT_RteGen

[For each `RptSwPrototypingAccess`, attribute `rptWriteAccess` shall exist.
]

[constr_1998] Existence of attribute `RptExecutableEntityProperties.maxRptEventId`*Imposition time:* IT_RteGen

[For each `RptExecutableEntityProperties`, attribute `maxRptEventId` shall exist.
]

[constr_1999] Existence of attribute `RptExecutableEntityProperties.minRptEventId`*Imposition time:* IT_RteGen

[For each `RptExecutableEntityProperties`, attribute `minRptEventId` shall exist.
]

[constr_2000] Compatibility of `ClientServerOperations` triggering the same `RunnableEntity`

Imposition time: IT_CpgExe

[The `ClientServerOperations` are considered compatible if

- the number of `arguments` (which can be `ArgumentDataPrototypes` or related `PortDefinedArgumentValues`) is equal and
- the corresponding `arguments` (i.e. first `argument` on both sides, second `argument` on both sides, etc.) are compatible or both are typed by "new-world" Variable-Size Array Data Types where the data types of the array elements are compatible (but the array sizes may differ).
- and the respective values of `PortAPIOption.errorHandling` are identical.

In particular, this means that:

- for combinations of `ArgumentDataPrototypes` and `ArgumentDataPrototypes` where the `serverArgumentImplPolicy` is set to `useArgumentType` the referred `ImplementationDataTypes` shall be compatible.

In case of data types of category `STRUCTURE` all by order matching `ImplementationDataTypeElements` shall be named equally.

- for combinations of `PortDefinedArgumentValues` and `ArgumentDataPrototypes` where the `serverArgumentImplPolicy` is set to `useArgumentType` the referred `ImplementationDataTypes` shall be compatible.

In case of `ImplementationDataTypeElements` of category `STRUCTURE` all by order matching `ImplementationDataTypeElements` of the structure shall be named equally.

- for `ArgumentDataPrototypes` where the `serverArgumentImplPolicy` is set to `useVoid` an arbitrary `ImplementationDataType` is referred to.

In addition, it is required that the **return value defined on both sides shall match** (in terms of `Std_ReturnType` vs. `void`) and also the `possibleErrors` are compatible.

]

[constr_2002] Referenced `VariableDataPrototype` from `AutosarVariableRef` of `VariableAccess` in role `dataReadAccess`

Imposition time: IT_CpgExe

[A `VariableAccess` in the role `dataReadAccess` shall refer to an `RPortPrototype` or `PRPortPrototype` that is typed by either a `SenderReceiverInterface` or a `NvDataInterface`.

]

[constr_2003] Referenced `VariableDataPrototype` from `AutosarVariableRef` of `VariableAccess` in role `dataWriteAccess`

Imposition time: IT_CpgExe

[A `VariableAccess` in the role `dataWriteAccess` shall refer to a `PPortPrototype` or `PRPortPrototype` that is typed by either a `SenderReceiverInterface` or a `NvDataInterface`.

]

[constr_2004] Referenced `VariableDataPrototype` from `AutosarVariableRef` of `VariableAccess` in role `dataSendPoint`

Imposition time: IT_CpgExe

[A `VariableAccess` in the role `dataSendPoint` shall refer to a `PPortPrototype` or `PRPortPrototype` that is typed by either a `SenderReceiverInterface` or a `NvDataInterface`.

]

[constr_2005] Referenced `VariableDataPrototype` from `AutosarVariableRef` of `VariableAccess` in role `dataReceivePointByValue` or `dataReceivePointByArgument`

Imposition time: IT_CpgExe

[A `VariableAccess` in the role `dataReceivePointByValue` or `dataReceivePointByArgument` shall refer to an `RPortPrototype` or `PRPortPrototype` that is typed by either a `SenderReceiverInterface` or an `NvDataInterface`.

]

[constr_2006] Number of `AsynchronousServerCallResultPoint` referencing to one `AsynchronousServerCallPoint`

Imposition time: IT_CpgExe

[The `AsynchronousServerCallPoint` may be referenced by at most one `AsynchronousServerCallResultPoint`.

If the reference exists, this means that only the `RunnableEntity` with this `AsynchronousServerCallResultPoint` can fetch the result of the asynchronous server invocation of this particular `AsynchronousServerCallPoint`.

]

[constr_2007] Consistency of `typeDefinition` attribute

Imposition time: IT_CpgExe

[All `PerInstanceMemorys` of the same `SwcInternalBehavior` with identical `type` attribute shall define an identical `typeDefinition` attribute as well.

]

[constr_2009] Supported kinds of `PortPrototypes` of a `NvBlockSwComponentType`

Imposition time: IT_RteGen

[With respect to external communication, `NvBlockSwComponentType` is limited to the definition of the following kinds of `PortPrototype`:

- `PortPrototypes` typed by either `NvDataInterfaces` or `ClientServerInterfaces`
- `RPortPrototypes` typed by `ModeSwitchInterfaces`

]

[constr_2010] Connections between `SwComponentPrototypes` of type `NvBlockSwComponentType`

Imposition time: IT_RteGen

[The existence of `SwConnectors` that refer to `PortPrototypes` belonging to `SwComponentPrototypes` where both are typed by `NvBlockSwComponentType` is not permitted.

]

[constr_2011] Connections between `SwComponentPrototypes` typed by `NvBlockSwComponentType` and `SwComponentPrototypes` typed by other `AtomicSwComponentTypes`

Imposition time: IT_RteGen

[A `PortPrototype` typed by an `NvDataInterface` owned by a `SwComponentPrototype` typed by an `NvBlockSwComponentType` shall be connected to a `PortPrototype` typed by **either** an `NvDataInterface` **or** a `SenderReceiverInterface` owned by a `SwComponentPrototype` that is typed by an other subclass of `AtomicSwComponentType`.

]

[constr_2012] Compatibility of `ImplementationDataTypes` used for `ramBlock` and `romBlock`

Imposition time: IT_RteGen

[The `ramBlock` and the `romBlock` shall have compatible `ImplementationDataTypes` to ensure, that the NVRAM Block default values in the ROM Block can be copied into the RAM Block.

]

[constr_2013] Compatibility of `ImplementationDataTypes` for `NvBlockDataMapping`

Imposition time: IT_RteGen

[Unless both the attribute `bitfieldTextTableMaskNvBlockDescriptor` and attribute `bitfieldTextTableMaskPortPrototype` is defined in the context of a given `NvBlockDataMapping`, the `NvBlockDataMapping` is only valid if the `ImplementationDataType` of the referenced `VariableDataPrototype` or `ImplementationDataTypeElement` in the role `nvRamBlockElement` is compatible to the `ImplementationDataType` used to type the `DataPrototype` aggregated by `NvBlockDataMapping` in the role `writtenNvData`, `writtenReadNvData`, or `readNvData`.

]

[constr_2014] Limitation of `NvBlockDescriptor.clientServerPort.role`

Imposition time: IT_RteGen

[The value of attribute `NvBlockDescriptor.clientServerPort.role` shall be set to a valid name of one of the Standardized AUTOSAR (client/server) Interfaces used for the NVRAM Manager, as described by [TPS_SWCT_02501], [TPS_SWCT_02502], [TPS_SWCT_02503] and [TPS_SWCT_02504].

]

[constr_2015] Limitation of `SwcInternalBehavior` of a `NvBlockSwComponentType`

Imposition time: IT_RteGen

[The `SwcInternalBehavior` of a `NvBlockSwComponentType` is only permitted to define

- `OperationInvokedEvents`
- `RunnableEntitys` triggered by `OperationInvokedEvents` (server `RunnableEntitys`)
- `RunnableEntitys` which defines only the mandatory attributes `symbol` and `canBeInvokedConcurrently`

- `PortAPIOptions` defining `PortDefinedArgumentValues`
- `TimingEvents` (which may include references to `ModeDeclarations` in the role `disabledMode`)
- `DataReceivedEvents` (which may include references to `ModeDeclarations` in the role `disabledMode`)
- `SwcModeSwitchEvents`
- `RunnableEntities` triggered by `TimingEvents`
- `RunnableEntities` triggered by `DataReceivedEvents`
- `RunnableEntities` triggered by `SwcModeSwitchEvents`
- `DataTypeMappingSet`

]

[constr_2016] Connections between `SwComponentPrototypes` of type `ServiceProxySwComponentType`*Imposition time:* IT_RteGen

[A connection between `PortPrototypes` belonging to `SwComponentPrototypes` where both are typed by `ServiceProxySwComponentType` is not permitted.

]

[constr_2017] Ports of `ServiceProxySwComponentTypes`*Imposition time:* IT_RteGen

[`ServiceProxySwComponentType` is only permitted to define

- `RPortPrototypes` that are typed by `SenderReceiverInterface` or
- `PortPrototypes` that are typed by a `PortInterface` where the `isService` attribute is set to true.

]

[constr_2018] Supported remote communication of a `ServiceProxySwComponentType`*Imposition time:* IT_RteGen

[For remote communication, `ServiceProxySwComponentType` can have only `RPortPrototypes` typed by `SenderReceiverInterfaces` in a 1:n communication scenario.

]

[constr_2019] ServiceSwComponentType shall have service ports only

Imposition time: IT_RteGen

[In the case of `ServiceSwComponentType`, all aggregated `PortPrototypes` need to have an `<<isOfType>>` relationship to a `PortInterface` which has its `isService` attribute set to `true`.

The exceptions described in

- [TPS_SWCT_01572],
- [TPS_SWCT_01579],
- [TPS_SWCT_01831] and
- [TPS_SWCT_01580]

apply.

]

[constr_2020] dataReadAccess can not be used for queued communication

Imposition time: IT_CpgExe

[The `swImplPolicy` of the `VariableDataPrototype` referenced by a `VariableAccess` in role `dataReadAccess` shall **not** be set to `queued`.

]

[constr_2021] WaitPoint referencing a DataReceivedEvent can not be used for non-queued communication

Imposition time: IT_CpgExe

[A `WaitPoint` referencing a `DataReceivedEvent` is permitted **if and only if** the `swImplPolicy` of the `VariableDataPrototype` referenced by this `DataReceivedEvent` is set to `queued`.

]

[constr_2022] Mutually exclusive use of SynchronousServerCallPoints and AsynchronousServerCallPoints

Imposition time: IT_CpgExe

[A `ClientServerOperation` of a particular `RPortPrototype` shall be mutually exclusive referenced by either a `SynchronousServerCallPoints` or an `AsynchronousServerCallPoints`.

]

[constr_2023] Consistency of `timeout` values

Imposition time: IT_RteGen

[The `timeout` values of all `ServerCallPoints` referencing the same instance of `ClientServerOperation` in a `RPortPrototype` shall be identical.

]

[constr_2024] `enableTakeAddress` is restricted to single instantiation

Imposition time: IT_CpgExe

[The definition of a `PortAPIOption` with `enableTakeAddress` set to `true` is only permitted for software-components where the attribute `SwcInternalBehavior.supportsMultipleInstantiation` is set to `false`.

]

[constr_2026] Referenced `VariableDataPrototype` from `AutosarVariableRef` of `VariableAccess` in role `writtenLocalVariable` and `readLocalVariable`

Imposition time: IT_CpgExe

[A `VariableDataPrototype` in the `localVariable` reference needs to be owned by the same `SwcInternalBehavior` as this `RunnableEntity` belongs to, and the referenced `VariableDataPrototype` has to be defined in the role `implicitInterRunnableVariable` or `explicitInterRunnableVariable`.

]

[constr_2027] `SwcServiceDependency` shall be defined for service ports only

Imposition time: IT_RteGen

[A `PortPrototype` that is referenced by a `SwcServiceDependency` via `assignedPort` or via `assignedData` shall be typed by a `PortInterface` that has `isService` set to `true`.

This rule does **not** apply to `PortPrototypes` referenced by a `RoleBasedPortAssignment` where the attribute `role` is set to any of the following values:

- `NvMService`
- `NvMNotifyJobFinished`
- `NvMNotifyInitBlock`
- `NvMAdmin`
- `NvMMirror`
- `NvDataPort`

Furthermore, the rule does **not** apply to the case described in [TPS_SWCT_01579], [TPS_SWCT_01831], [TPS_SWCT_01580], and [TPS_SWCT_01572].

]

[constr_2028] **staticMemory** is restricted to single instantiation

Imposition time: IT_RteGen

[The `staticMemory` is only supported if the attribute `supportsMultipleInstantiation` of the owning `SwcInternalBehavior` is set to `false`.

]

[constr_2030] **AsynchronousServerCallResultPoint** combined with **WaitPoint** shall belong to the same **RunnableEntity**

Imposition time: IT_CpgExe

[A `WaitPoint` referencing a `AsynchronousServerCallReturnsEvent` as well as a `AsynchronousServerCallResultPoint` referenced by said `AsynchronousServerCallReturnsEvent` shall be aggregated by the same `RunnableEntity`.

]

[constr_2031] Value of **TimingEvent.period** shall be greater than 0

Imposition time: IT_RteGen

[Attribute `TimingEvent.period` shall exist and its value shall be greater than 0.

]

[constr_2033] Timeout of **DataSendCompletedEvent**

Imposition time: IT_RteGen

[The `timeout` value of a `WaitPoint` associated with a `DataSendCompletedEvent` shall have the same value as the corresponding value of `TransmissionAcknowledgementRequest.timeout`.

]

[constr_2034] **SwAddrMethod** referenced by **RunnableEntitys**, **BswCalledEntitys**, or **BswSchedulableEntitys**

Imposition time: IT_CpgExe

[`RunnableEntitys`, `BswCalledEntitys`, and `BswSchedulableEntitys` shall not reference a `SwAddrMethod` which attribute `memoryAllocationKeywordPolicy` is set to `addrMethodShortNameAndAlignment`.

]

[constr_2035] swImplPolicy for VariableDataPrototype in SenderReceiverInterface

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `VariableDataPrototype` owned by a `SenderReceiverInterface` shall be either `standard`, `queued`, or `measurementPoint`.

]

[constr_2036] swImplPolicy for VariableDataPrototype in NvDataInterface

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `VariableDataPrototype` owned by a `NvDataInterface` shall be `standard`.

]

[constr_2037] swImplPolicy for VariableDataPrototype in the role ramBlock

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `VariableDataPrototype` aggregated in the role `NvBlockDescriptor.ramBlock` shall be `standard`.

]

[constr_2038] swImplPolicy for VariableDataPrototype in the role implicitInterRunnableVariable

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `VariableDataPrototype` aggregated in the role `SwcInternalBehavior.implicitInterRunnableVariable` shall be `standard`.

]

[constr_2039] swImplPolicy for VariableDataPrototype in the role explicitInterRunnableVariable

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `VariableDataPrototype` aggregated in the role `SwcInternalBehavior.explicitInterRunnableVariable` shall be `standard`.

]

[constr_2040] swImplPolicy for VariableDataPrototype in the role arTypedPerInstanceMemory

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `VariableDataPrototype` aggregated in the role `SwcInternalBehavior.arTypedPerInstanceMemory` shall be `standard` or `measurementPoint`.

]

[constr_2041] swImplPolicy for VariableDataPrototype in the role staticMemory

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `VariableDataPrototype` aggregated in the role `InternalBehavior.staticMemory` shall be `standard` or `measurementPoint`.

]

[constr_2042] swImplPolicy for ParameterDataPrototype in ParameterInterface

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `ParameterDataPrototype` owned by a `ParameterInterface` shall be either `standard`, `const`, or `fixed`.

]

[constr_2043] swImplPolicy for ParameterDataPrototype in the role romBlock

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` a `ParameterDataPrototype` aggregated in the role `NvBlockDescriptor.romBlock` shall be `standard`.

]

[constr_2044] swImplPolicy for ParameterDataPrototype in the role sharedParameter

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `ParameterDataPrototype` aggregated in the role `SwcInternalBehavior.sharedParameter` shall be `standard` or `const`.

]

[constr_2045] swImplPolicy for ParameterDataPrototype in the role perInstanceParameter

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `ParameterDataPrototype` in the role `SwcInternalBehavior.perInstanceParameter` shall be `standard` or `const`.

]

[constr_2046] swImplPolicy for ParameterDataPrototype in the role constantMemory

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of a `ParameterDataPrototype` aggregated in the role `InternalBehavior.constantMemory` shall be `standard`, `const`, or `fixed`.

]

[constr_2047] swImplPolicy for ArgumentDataPrototype

Imposition time: IT_CpgExe

[The overriding value of attribute `swImplPolicy` of an `ArgumentDataPrototype` shall be `standard`.

]

[constr_2049] Different ModeDeclarationGroups shall have different shortNames.

Imposition time: IT_CpgExe

[A software component is not allowed to type multiple `PortPrototypes` with `ModeSwitchInterfaces` where the contained `ModeDeclarationGroupPrototypes` are referencing `ModeDeclarationGroups` with identical `shortNames` but different `ModeDeclarations`.

]

[constr_2050] Mandatory information of a SwAxisCont

Imposition time: IT_CpgExe

[If the attribute `swAxisCont` is defined for an `ApplicationValueSpecification` the `SwAxisCont` shall define

- one `swAxisIndex` value and
- one `swArraysize` value

per dimension, even in the case when the owning `ApplicationValueSpecification` defines only the content of a single dimensional object of (for example) `category CURVE`.

]

[constr_2052] Values of `swArraysizes` and the number of values provided by `swValuesPhys` shall be consistent.

Imposition time: IT_CpgExe

[`swValuesPhys` shall define as many values as the attribute `swArraysizes` (if this attribute exists) defines.

In other words, in the bound model the number of descendants (`v`, or `vf`, or `vt`, or `vtf`) shall be identical to the number of elements of the related `DataPrototype` typed by an `ApplicationPrimitiveDataType`.

If several `swArraysizes` values are provided, the values have to be multiplied in order to get the total number of `swValuesPhys` values.

]

[constr_2053] Consistency between `role IUMPRNumerator` and `ObdRatioServiceNeeds.connectionType`

Imposition time: IT_RteGen

[If a `SwcServiceDependency` with a `ObdRatioServiceNeeds` is defined and the attribute `connectionType` of the contained `ObdRatioServiceNeeds` is set to `ObdRatioConnectionKindEnum.apiUse`, a `RoleBasedPortAssignment` with the `role` value `IUMPRNumerator` shall be defined.

If the attribute `connectionType` of the contained `ObdRatioServiceNeeds` is set to `ObdRatioConnectionKindEnum.observer`, the `role` value `IUMPRNumerator` is not applicable.

]

[constr_2054] Valid targets of `rptSystem`

Imposition time: IT_RteGen

[The `System` referenced in the role `rptSystem` shall be of `category RPT_SYSTEM`.

]

[constr_2055] Valid targets of `byPassPoint` and `rptHook` reference, depending on the value of attribute `category`

Imposition time: IT_RteGen

[

Category	Meaning	Specific properties
SW_COMPONENT_PROTOTYPE	Adds one <code>SwComponentPrototype</code> to an Rapid Prototyping Scenario.	The <code>byPassPoint</code> and <code>rptArHook</code> shall reference a <code>SwComponentPrototypes</code> .
DATA_PROTOTYPE	Adds one instance of a <code>DataPrototype</code> to an Rapid Prototyping Scenario.	The <code>byPassPoint</code> and <code>rptArHook</code> shall reference a <code>DataPrototype</code> instances in <code>Port-Prototypes</code> .
RUNNABLE_ENTITY	Adds one <code>RunnableEntity</code> to an Rapid Prototyping Scenario.	The <code>byPassPoint</code> and <code>rptArHook</code> shall reference a <code>RunnableEntity</code> instances.
ACCESS_POINTS	Adds one <code>VariableAccess</code> , <code>ParameterAccess</code> , <code>ServerCallPoint</code> , <code>AsynchronousServerCallResultPoint</code> , <code>InternalTriggeringPoint</code> , <code>ModeSwitchPoint</code> or <code>ExternalTriggeringPoint</code> to a Rapid Prototyping Scenario.	The <code>byPassPoint</code> and <code>rptArHook</code> shall reference a <code>VariableAccess</code> , <code>ParameterAccess</code> , <code>ServerCallPoint</code> , <code>AsynchronousServerCallResultPoint</code> , <code>InternalTriggeringPoint</code> , <code>ModeSwitchPoint</code> , <code>ModeAccessPoint</code> or <code>ExternalTriggeringPoint</code> instances.

]

[constr_2056] Consistency of `RapidPrototypingScenario` with respect to `rptSystem` and `rptArHook` references

Imposition time: IT_RteGen

[Within one `RapidPrototypingScenario` all `rptSystem` references shall point to instances in one and only one `System`, and if existent, all `rptArHook` shall point to instances in one other and only one other `System`.

]

[constr_2057] Mandatory information of a `RuleBasedAxisCont`

Imposition time: IT_CpgExe

[If the attribute `swAxisCont` is defined for an `ApplicationRuleBasedValueSpecification` the `RuleBasedAxisCont` shall define one `swAxisIndex` value and one `swArraysize` value per dimension, even in the case when the owning `ApplicationRuleBasedValueSpecification` defines only the content of a single dimensional object like a `CURVE`.

]

[constr_2058] Mandatory information of a `RuleBasedValueCont`

Imposition time: IT_CpgExe

[If the attribute `swValueCont` is defined for an `ApplicationRuleBasedValueSpecification` the `RuleBasedValueCont` shall always define the attribute `swAr-`

raysize if the [ApplicationRuleBasedValueSpecification](#) is of category CURVE, MAP, CUBOID, CUBE_4, CUBE_5, COM_AXIS, RES_AXIS, or VAL_BLK.

]

[constr_2535] Target of an [autosarParameter](#) in [AutosarParameterRef](#) shall refer to a parameter

Imposition time: IT_CpgExe

[Except for the specifically described cases where [\[constr_1173\]](#), applies the target of [autosarParameter](#) (which in fact is an instance ref) in [AutosarParameterRef](#) shall either be or be nested in [ParameterDataPrototype](#). This means that the target shall either be a [ParameterDataPrototype](#) or an [ApplicationCompositeElementDataPrototype](#) that in turn is owned by a [ParameterDataPrototype](#).

]

[constr_2536] Target of an [autosarVariable](#) in [AutosarVariableRef](#) shall refer to a variable

Imposition time: IT_CpgExe

[The target of [autosarVariable](#) (which in fact is an instance ref) in [AutosarVariableRef](#) shall either be or be nested in [VariableDataPrototype](#). This means that the target shall either be a [VariableDataPrototype](#) or an [ApplicationCompositeElementDataPrototype](#) that in turn is owned by a [VariableDataPrototype](#).

]

[constr_2544] Limits need to be consistent

Imposition time: IT_CpgExe

[

- The limits of [ApplicationDataType](#) shall be inside the definition range of the [CompuMethod](#)

The [CompuMethod](#) needs to be applicable for limits of an [ApplicationDataType](#). The reason is that the internal representation of the limits for the [ApplicationDataType](#) are calculated by applying the [CompuMethod](#).

- The such defined internal limits of the [ApplicationDataType](#) shall be within or equal the [internalConstrs](#) of the mapped [ImplementationDataType](#).
- The limits of the [ImplementationDataType](#) shall be within or equal to the limits defined by the size of the [BaseType](#).

]

[constr_2545] `invalidValue` shall fit in the specified ranges

Imposition time: IT_CpgExe

[The `invalidValue` shall be in the range of the `ImplementationDataType`.

]

[constr_2548] Data constraint of value axis shall match

Imposition time: IT_CpgExe

[The values compliant to `SwDataDefProps.dataConstr` shall also be compliant to `SwDataDefProps.valueAxisDataType.swDataDefProps.dataConstr`.

In other words `SwDataDefProps.dataConstr` win over but are not allowed to relax `SwDataDefProps.valueAxisDataType.swDataDefProps.dataConstr` but are not allowed.

]

[constr_2549] Units of input axis shall be consistent

Imposition time: IT_CpgExe

[The units specified in the context of an input axis shall be compatible, even if there is a precedence rule.

]

[constr_2550] Units of value axis shall be consistent

Imposition time: IT_CpgExe

[The units specified in the context of value axis shall be the same, even if there is a precedence rule.

]

[constr_2561] Application of `DataConstrRule.constrLevel`

Imposition time: IT_CpgExe

[`DataConstrRule.constrLevel` is limited to

0: This represents so called "hard limits". They shall always be specified.

1: This represents so called "soft limits". Soft limits may be violated after confirmation by the user of an MCD-System.

Other values may exist, but the semantics is outside the AUTOSAR scope.

]

[constr_3688] Existence of attribute `RoleBasedDataAssignment.usedDataElement.localVariable` for `RoleBasedDataAssignment.role = ServerServiceOffer`

Imposition time: IT_RteGen

[If the attribute `RoleBasedDataAssignment.role` is set to the value `ServerServiceOffer`, then the reference `RoleBasedDataAssignment.usedDataElement.localVariable` shall not exist.

]

[constr_3689] Existence of attribute `RoleBasedDataAssignment.usedDataElement.localVariable` for `RoleBasedDataAssignment.role = ClientEventSubscription`

Imposition time: IT_RteGen

[If the attribute `RoleBasedDataAssignment.role` is set to the value `ClientEventSubscription`, then the reference `RoleBasedDataAssignment.usedDataElement.localVariable` shall not exist.

]

[constr_4002] Unambiguous mapping of modes to data types

Imposition time: IT_CpgExe

[Within one `DataTypeMappingSet`, a `ModeDeclarationGroup` shall not be mapped to different `ImplementationDataTypes`.

]

[constr_4003] Semantics of `SwcModeSwitchEvent`

Imposition time: IT_RteGen

[If the value of `SwcModeSwitchEvent.activation` is `onTransition`, then `SwcModeSwitchEvent` shall refer to two different `ModeDeclarations` belonging to the same instance of `ModeDeclarationGroup`.

Their order defines the direction of the transition from one mode into another. In all other cases `SwcModeSwitchEvent` shall refer to exactly one `ModeDeclaration`.

]

[constr_4004] Context of `SenderReceiverAnnotation`

Imposition time: IT_CpgExe

[A `SenderReceiverAnnotation` shall only be aggregated by a `PortPrototype` typed by a `SenderReceiverInterface`.

]

[constr_4005] Context of [ClientServerAnnotation](#)

Imposition time: IT_CpgExe

[A [ClientServerAnnotation](#) shall only be aggregated by a [PortPrototype](#) typed by a [ClientServerInterface](#).

]

[constr_4006] Context of [ParameterPortAnnotation](#)

Imposition time: IT_CpgExe

[A [ParameterPortAnnotation](#) shall only be aggregated by a [PPortPrototype](#) owned by a [ParameterSwComponentType](#).

]

[constr_4007] Context of [ModePortAnnotation](#)

Imposition time: IT_CpgExe

[A [ModePortAnnotation](#) shall only be aggregated by a [PortPrototype](#) typed by a [ModeSwitchInterface](#).

]

[constr_4008] Context of [TriggerPortAnnotation](#)

Imposition time: IT_CpgExe

[A [TriggerPortAnnotation](#) shall only be aggregated by a [PortPrototype](#) typed by a [TriggerInterface](#).

]

[constr_4009] Context of [NvDataPortAnnotation](#)

Imposition time: IT_CpgExe

[An [NvDataPortAnnotation](#) shall only be aggregated by a [PortPrototype](#) typed by an [NvDataInterface](#).

]

[constr_4010] Context of [DelegatedPortAnnotation](#)

Imposition time: IT_CompSwcT

[A [DelegatedPortAnnotation](#) shall only be aggregated by a [PortPrototype](#) aggregated by a [CompositionSwComponentType](#).

]

[constr_4012] Timeout of ModeSwitchedAckEvent

Imposition time: IT_RteGen

[The timeout value of a `WaitPoint` associated with a `ModeSwitchedAckEvent` shall be equal to the corresponding `ModeSwitchedAckRequest.timeout`.

]

[constr_4082] RunnableEntity.reentrancyLevel shall not be set.

Imposition time: IT_CpgExe

[The optional attribute `reentrancyLevel` shall not be set for a `RunnableEntity`. This attribute would define more specific reentrancy features than the mandatory attribute `canBeInvokedConcurrently`. These features are currently only supported for Basic Software.

]

[constr_5234] Existence of attribute E2EProfileCompatibilityProps.transitToInvalidExtended is mandatory for each EndToEndTransformationComSpecProps

Imposition time: IT_RteGen

[For each `EndToEndTransformationComSpecProps`, a reference in the role `e2eProfileCompatibilityProps` to meta-class `E2EProfileCompatibilityProps` shall exist and the referenced `E2EProfileCompatibilityProps` shall define a value for the attribute `transitToInvalidExtended`.

]

[constr_10000] Existence of attribute RptExecutableEntityProperties.rptExecutionControl

Imposition time: IT_RteGen

[For each `RptExecutableEntityProperties`, attribute `rptExecutionControl` shall exist.

]

[constr_10001] Existence of attribute RptExecutableEntityProperties.rptServicePoint

Imposition time: IT_RteGen

[For each `RptExecutableEntityProperties`, attribute `rptServicePoint` shall exist.

]

[constr_10005] Existence of attribute `NotAvailableValueSpecification.defaultPattern`

Imposition time: IT_CpgExe

[For each `NotAvailableValueSpecification`, attribute `defaultPattern` shall exist.

]

[constr_10006] Valid interval of attribute `NotAvailableValueSpecification.defaultPattern`

Imposition time: IT_CpgExe

[The valid interval for attribute `NotAvailableValueSpecification.defaultPattern` is 0..255.

]

[constr_10009] Aggregation of `ApplicationRuleBasedValueSpecification`

Imposition time: IT_CpgExe

[Each `ArrayValueSpecification` shall only aggregate at most one `ApplicationRuleBasedValueSpecification` in the role element.

If one `ApplicationRuleBasedValueSpecification` is aggregated then it shall be the only aggregated element, i.e. no further `ValueSpecification` shall exist in the same aggregation where an `ApplicationRuleBasedValueSpecification` is aggregated.

]

[constr_10016] Applicability of `OsTaskExecutionEvent`

Imposition time: IT_CpgExe

[An `OsTaskExecutionEvent` is only applicable for a `SwcInternalBehavior` in the context of a `ComplexDeviceDriverSwComponentType`, `EcuAbstractionSwComponentType`, or `ServiceSwComponentType`.

]

[constr_10018] Existence of attribute `SwAxisCont.swAxisIndex`

Imposition time: IT_CpgExe

[For each `SwAxisCont`, attribute `swAxisIndex` shall exist.

]

[constr_10019] Existence of attribute `SwAxisCont.swValuesPhys`*Imposition time:* IT_CpgExe[For each `SwAxisCont`, attribute `swValuesPhys` shall exist.

]

[constr_10020] Existence of attribute `RoleBasedDataTypeAssignment.usedImplementationDataType`*Imposition time:* IT_RteGen[For each `RoleBasedDataTypeAssignment`, attribute `usedImplementationDataType` shall exist.

]

[constr_10032] Restrictions for the usage of `ServiceDependency.diagnosticRelevance`*Imposition time:* IT_RteGen[The attribute `ServiceDependency.diagnosticRelevance` shall only be used for a `SwcServiceDependency` that aggregates a `BswMgrNeeds`.

]

[constr_10033] Existence of `MemorySection.swAddrmethod`*Imposition time:* IT_CpgExe[For each `MemorySection`, attribute `swAddrmethod` shall existence.

]

[constr_10034] Existence of `MemorySection.alignment`*Imposition time:* IT_CpgExe[For each `MemorySection`, attribute `alignment` shall exist if the attribute `MemorySection.swAddrmethod.memoryAllocationKeywordPolicy` is set to `MemoryAllocationKeywordPolicyType.addrMethodShortNameAndAlignment`.

]

[constr_10040] Value of `ApplicationValueSpecification.swAxisCont.category`*Imposition time:* IT_CpgExe[The value of attribute `ApplicationValueSpecification.swAxisCont.category` shall not be set to `fixAXIS`.

]

[constr_10041] Value of `ApplicationRuleBasedValueSpecification.swAxisCont.category`

Imposition time: IT_CpgExe

[The value of `ApplicationValueSpecification.swAxisCont.category` shall not be set to `fixAXIS`

]

[constr_10067] Creation of `AssemblySwConnector` for service communication

Imposition time: IT_RteGen

[If an `AssemblySwConnector` is created between two `PortPrototypes` and the affected `PortInterfaces` set the attribute `isService` to the value `true`, then at least one of the `SwComponentPrototypes` shall be typed by a `ServiceSwComponentType`.

]

[constr_10068] Standardized values for `SectionInitializationPolicyType`

Imposition time: IT_CpgExe

[The following values for `SectionInitializationPolicyType` are reserved by the AUTOSAR standard:

INIT To be used for (explicitly or not explicitly) initialized variables.

CLEARED To be used for not explicitly initialized variables.

POWER-ON-CLEARED To be used for variables that are not explicitly initialized (cleared) during normal start-up. Instead these are cleared only after power on reset.

]

[constr_10071] Allowed multiplicities of `SenderComSpec` attributes for communication between `ApplicationSwComponentType` and `NvBlockSwComponentType`

Imposition time: IT_RteGen

[

Sender	<code>ApplicationSwComponentType</code>	
Receiver	<code>NvBlockSwComponentType</code>	
Queuing Configuration	non-queued	queued
<code>SenderComSpec.transmissionAcknowledge</code>	d/c	
<code>SenderComSpec.dataElement</code>	1	
<code>SenderComSpec.handleOutOfRange</code>	d/c	



△

Sender	ApplicationSwComponentType	
Receiver	NvBlockSwComponentType	
Queuing Configuration	non-queued	queued
SenderComSpec.usesEndToEndProtection	d/c	
SenderComSpec.transmissionProps.dataUpdatePeriod	0..1	
SenderComSpec.transmissionProps.minimumSendInterval	0..1	
SenderComSpec.transmissionProps.transmissionMode	0..1	
SenderComSpec.networkRepresentation	d/c	
SenderComSpec.compositeNetworkRepresentation	d/c	
NonqueuedSenderComSpec.dataFilter	d/c	
NonqueuedSenderComSpec.initValue	0..1	

]

[constr_10072] Allowed multiplicities of [SenderComSpec](#) attributes for communication between [NvBlockSwComponentType](#) and [ApplicationSwComponentType](#)

Imposition time: IT_RteGen

[

Sender	NvBlockSwComponentType	
Receiver	ApplicationSwComponentType	
Queuing Configuration	non-queued	queued
ReceiverComSpec.replaceWith	0	
ReceiverComSpec.dataElement	1	
ReceiverComSpec.receptionProps.dataUpdatePeriod	0	
ReceiverComSpec.receptionProps.timeout	0	
ReceiverComSpec.usesEndToEndProtection	0	
ReceiverComSpec.maxDeltaCounterInit	0	
ReceiverComSpec.handleOutOfRange	0	
ReceiverComSpec.handleOutOfRangeStatus	0	
ReceiverComSpec.maxNoNewOrRepeatedData	0	
ReceiverComSpec.syncCounterInit	0	
ReceiverComSpec.transformationComSpecProps	0	
ReceiverComSpec.networkRepresentation	0	
ReceiverComSpec.compositeNetworkRepresentation	0	
QueuedReceiverComSpec.queueLength		
NonqueuedReceiverComSpec.filter	0	
NonqueuedReceiverComSpec.timeoutSubstitutionValue	0	
NonqueuedReceiverComSpec.initValue	0..1	
NonqueuedReceiverComSpec.aliveTimeout	0	
NonqueuedReceiverComSpec.enableUpdate	0	
NonqueuedReceiverComSpec.handleDataStatus	0	
NonqueuedReceiverComSpec.handleNeverReceived	0..1	
NonqueuedReceiverComSpec.handleTimeoutType	0	

]

[constr_10073] Existence of DataReceiveErrorEvent

Imposition time: IT_CpgExe

[A `DataReceiveErrorEvent` shall only exist if it latest refers to a given `VariableDataPrototype` in the role `data` where either

- the `VariableDataPrototype` is referenced from a `NonqueuedReceiverComSpec` in the role `dataElement` and the attribute `aliveTimeout` of the `NonqueuedReceiverComSpec` exists and is set to a value > 0 or
- the `VariableDataPrototype` is aggregated by a `SenderReceiverInterface` where attribute `invalidationPolicy.handleInvalid` exists and is set to the value `keep`.

]

[constr_10074] Consistency of attribute NvBlockDescriptor.writingStrategy.role set to storeOnChange

Imposition time: IT_RteGen

[The existence of `NvBlockDescriptor.writingStrategy` where attribute `role` is set to `storeOnChange` is only supported if `NvBlockDescriptor.nvBlockNeeds.storeOnChange` exists and is set to `true`.

]

[constr_10075] Existence of CompositeRuleBasedValueSpecification.argument vs. compoundPrimitiveArgument

Imposition time: IT_CpgExe

[For every `CompositeRuleBasedValueSpecification`, at most one of the aggregations

- `argument`
- `compoundPrimitiveArgument`

]

[constr_10087] Restriction for the existence of a SubElementMapping

Imposition time: IT_RteGen

[The existence of a `DataPrototypeMapping.subElementMapping` is only supported if the `PortPrototypes` that are referenced by the respective `SwConnector` are typed by a `DataInterface`.

]

[constr_10096] Shared axis shall not be a fixed axis

Imposition time: IT_CpgExe

[An `ApplicationPrimitiveDataType` of category `COM_AXIS` shall not contain the definition of an `SwCalprmAxis` of category `FIX_AXIS`.

]

[constr_10097] Buffer locking is only supported if `returnValueProvision` is set to `returnValueProvided`

Imposition time: IT_CpgExe

[Setting the value of attribute `PortAPIOption.supportedFeature.supportBufferLocking` to value `supportsBufferLocking` is only supported if the `AbstractAccessPoints` that refer to values in the respective `PortAPIOption.port` do **not** define `AbstractAccessPoint.returnValueProvision` **or** set the value of `AbstractAccessPoint.returnValueProvision` to `returnValueProvided`.

]

[constr_10099] Allowed values of the attribute `SwDataDefProps.swImplPolicy` vs. `DataPrototypes` and their roles

Imposition time: IT_CpgExe

[

Attribute of <code>SwImplPolicyEnum</code>	<code>VariableDataPrototype</code>							<code>ParameterDataPrototype</code>					Misc.
	<code>VariableDataPrototype in SenderReceiverInterface</code>	<code>VariableDataPrototype in NvDataInterface</code>	<code>VariableDataPrototype in role ramBlock</code>	<code>VariableDataPrototype in role implicitInterRunnableVariable</code>	<code>VariableDataPrototype in role explicitInterRunnableVariable</code>	<code>VariableDataPrototype in role artypedPerInstanceMemory</code>	<code>VariableDataPrototype in role staticMemory</code>	<code>ParameterDataPrototype in ParameterInterface</code>	<code>ParameterDataPrototype in role romBlock</code>	<code>ParameterDataPrototype in role sharedParameter</code>	<code>ParameterDataPrototype in role perInstanceParameter</code>	<code>ParameterDataPrototype in role constantMemory</code>	<code>ArgumentDataPrototype</code>
<code>const</code>								X		X	X	X	
<code>fixed</code>								X				X	
<code>measurementPoint</code>	X					X	X						
<code>queued</code>	X												
<code>standard</code>	X	X	X	X	X	X	X	X	X	X	X	X	X

]

[constr_10104] RoleBasedPortAssignment where attribute **role** is set to **CallbackGetFaultDetectCounter** shall refer to a **PPortPrototype** in the role **portPrototype**

Imposition time: IT_RteGen

[If a **SwcServiceDependency** aggregates both

- a **DiagnosticEventNeeds** that in turn aggregates **DiagEventDebounceMonitorInternal** in the role **diagEventDebounceAlgorithm** and
- a **RoleBasedPortAssignment** in the role **assignedPort** where attribute **role** is set to **CallbackGetFaultDetectCounter**,

then the target of the reference **SwcServiceDependency.assignedPort.portPrototype** shall be a **PPortPrototype**.

]

[constr_10118] Structural consistency of the modeling of InvalidationPolicy

Imposition time: IT_CpgExe

[A **dataElement** referenced by an **InvalidationPolicy** shall be owned by the **SenderReceiverInterface** that also owns the **InvalidationPolicy**.

]

[constr_10119] SenderReceiverInterface.dataElement shall be referenced by at most one **InvalidationPolicy**

Imposition time: IT_CpgExe

[Any **SenderReceiverInterface.dataElement** shall be referenced by at most one **InvalidationPolicy** in the role **InvalidationPolicy.dataElement**.

]

[constr_10120] Structural consistency of the modeling of MetaDataItemSet

Imposition time: IT_CpgExe

[A **dataElement** referenced by an **MetaDataItemSet** in the role **dataElement** shall be owned by the **SenderReceiverInterface** that also owns the **MetaDataItemSet**.

]

[constr_10121] `SenderReceiverInterface.dataElement` shall be referenced by at most one `MetaDataItemSet`

Imposition time: IT_CpgExe

[Any `SenderReceiverInterface.dataElement` shall be referenced by at most one `MetaDataItemSet` in the role `MetaDataItemSet.dataElement`.

]

[constr_10123] Existence of attribute `DtcStatusChangeNotificationNeeds.notificationTime`

Imposition time: IT_RteGen

[Attribute `DtcStatusChangeNotificationNeeds.notificationTime` shall only exist if the enclosing `SwcServiceDependency` contains a `RoleBasedPortAssignment` where attribute role is set to the value `ClearDtcNotification`.

]

[constr_10196] Definition of `invalidValue` for `DataPrototype` is typed by an `ImplementationDataType` that references a `CompuMethod` of category `TEXTTABLE` or `BITFIELD_TEXTTABLE`

Imposition time: IT_CpgExe

[If an `invalidValue` is defined for a `DataPrototype` that is typed by an `ImplementationDataType` that references or inherits (see [constr_1015]) a `CompuMethod` of category `TEXTTABLE` or `BITFIELD_TEXTTABLE`, the applicable `ValueSpecification` shall be a `TextValueSpecification` if the value fits into the intervals defined by the `CompuMethod`.

In this case the value provided shall match to one of the applicable text values (`vt`, `shortLabel`, `symbol`) defined by the applicable `CompuScales`.

]

[constr_10372] Relation between *Type of `PortPrototype`*, *Type of `ComSpec`*, and *Type of `PortInterface`*

Imposition time: IT_CpgExe

[With respect to [constr_1043], if a *Type of `PortPrototype`* aggregates a *Type of `ComSpec`*, then the *Type of `PortPrototype`* shall

- reference a *Type of `PortInterface`* in the role *Role of Type-Ref* and
- the *Role of Element* that is referenced from the *Type of `ComSpec`* shall be aggregated by the exact same *Type of `PortInterface`* that is also referenced by the enclosing *Type of `PortPrototype`* in the role *Role of Type-Ref*.

]

[constr_10373] ImplementationDataType of category VALUE shall not refer to SwBaseType of category VOID

Imposition time: IT_CpgExe

[An `ImplementationDataType` where attribute `category` is set to `VALUE` shall not reference (in the role `swDataDefProps.baseType`) a `SwBaseType` where attribute `category` is set to `VOID`.

]

[constr_10383] Supported value encodings for SwBaseType in the context of PortInterfaces where attribute isService is set to false

Imposition time: IT_CpgExe

[The supported value encodings for the usage within a `PortInterface` where attribute `isService` is set to `false` are:

- 2C: Two's complement
- IEEE754: floating-point numbers
- ISO-8859-1: single-byte coded character
- ISO-8859-2: single-byte coded character
- WINDOWS-1252: single-byte coded character
- UTF-8: UCS Transformation Format 8
- UTF-16: Character encoding for Unicode code points based on 16 bit code units, see [7]
- UCS-2: Universal Character Set 2
- NONE: Unsigned Integer
- `BOOLEAN`: This represents an integer to be interpreted as boolean.

]

[constr_10415] Initial value on the level of an ImplementationDataTypeElement where attribute isOptional is set to the value True

Imposition time: IT_CpgExe

[The initial value used on the level of an `ImplementationDataTypeElement` where attribute `isOptional` is set to the value `True` shall **not** be initialized using a `NotAvailableValueSpecification`.

]

[constr_10424] Reference from `MemorySection` to `ExecutableEntity`

Imposition time: IT_CpgExe

[Each `ExecutableEntity` shall only be referenced by exactly one `MemorySection`.

]

[constr_10433] Existence of attributes of `ApplicationDataType` depending on the `category`

Imposition time: IT_CpgExe

[

Attributes of <code>Application-DataType</code>	Owner				Attribute Existence per <code>ApplicationDataType.category</code>												
	<code>ApplicationRecordDataType</code>	<code>ApplicationRecordElement</code>	<code>ApplicationArrayDataType</code>	<code>ApplicationArrayElement</code>	VALUE	VAL_BLK	STRUCTURE	ARRAY	STRING	BOOLEAN	COM_AXIS	RES_AXIS	CURVE	MAP	CUBOID	CUBE_4	CUBE_5
<code>element</code>	x						1..*										
<code>isOptional</code>		x					0..1										
<code>element</code>			x					1									
<code>dynamicArraySizeProfile</code>			x					0..1									
<code>arraySizeHandling</code>				x				0..1									
<code>arraySizeSemantics</code>				x				0..1									
<code>maxNumberOfElements</code>				x				1									
<code>swDataDefProps</code>	x	x	x	x	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1	0..1

]

[constr_10434] Existence of attributes of `ImplementationDataType` depending on the `category`

Imposition time: IT_CpgExe

[

Attributes of ImplementationDataType	Attribute Existence per Category						
	VALUE	DATA_REFERENCE	FUNCTION_REFERENCE	TYPE_REFERENCE	STRUCTURE	UNION	ARRAY
<code>dynamicArraySizeProfile</code>							0..1
<code>isStructWithOptionalElement</code>					0..1		
<code>typeEmitter</code>	0..1	0..1	0..1	0..1	0..1	0..1	0..1
<code>symbolProps</code>	0..1	0..1	0..1	0..1	0..1	0..1	0..1
<code>swDataDefProps</code>	0..1	0..1	0..1	0..1	0..1	0..1	0..1
<code>subElement</code>					1..*	1..*	1
<code>subElement.isOptional</code>					0..1		
<code>subElement.arraySize</code>							0..1
<code>subElement.arraySizeSemantics</code>							0..1
<code>subElement.arraySizeHandling</code>							0..1
<code>subElement.arrayImplPolicy</code>							0..1

]

[constr_10435] Existence of attributes of `ImplementationDataTypeElement` depending on the `category`

Imposition time: IT_CpgExe

[

Attributes of ImplementationDataTypeElement	Attribute Existence per Category						
	VALUE	DATA_REFERENCE	FUNCTION_REFERENCE	TYPE_REFERENCE	STRUCTURE	UNION	ARRAY
<code>swDataDefProps</code>	0..1	0..1	0..1	0..1	0..1	0..1	0..1
<code>subElement</code>					1..*	1..*	1
<code>subElement.isOptional</code>					0..1		
<code>subElement.arraySize</code>							0..1
<code>subElement.arraySizeSemantics</code>							0..1
<code>subElement.arraySizeHandling</code>							0..1

▽



Attributes of ImplementationDataTypeElement	Attribute Existence per Category						
	VALUE	DATA_REFERENCE	FUNCTION_REFERENCE	TYPE_REFERENCE	STRUCTURE	UNION	ARRAY
<code>subElement.arrayImplPolicy</code>							0..1

]

[constr_10439] Initialization of a `DataPrototype` typed by a Compound Primitive Data Type

Imposition time: IT_CpgExe

[If a `DataPrototype` that is typed by a Compound Primitive Data Type according to [TPS_SWCT_01179] needs to be initialized by a constant value, then the initialization shall only be provided in the form of an `ApplicationValueSpecification`.

]

[constr_10502] Number of elements of `ApplicationValueSpecification.swValueCont.swArraysizesize` vs. `ApplicationValueSpecification.category`

Imposition time: IT_ValSpec

[

Value of <code>category</code>	Number of values in <code>swValueCont.swArraysizesize</code>
<code>CURVE</code>	1
<code>MAP</code>	2
<code>CUBOID</code>	3
<code>CUBE_4</code>	4
<code>CUBE_5</code>	5
<code>COM_AXIS</code>	1
<code>RES_AXIS</code>	1
<code>VAL_BLK</code>	1..*

]

[constr_10503] ApplicationValueSpecification where attribute category is set to MAP, CUBOID, CUBE_4, or CUBE_5 and ROW_DIR SwRecordLayout

Imposition time: IT_ValSpec

[In the context of an `ApplicationValueSpecification` where attribute `category` is set to `MAP`, `CUBOID`, `CUBE_4`, or `CUBE_5` that is applied to a `DataPrototype` typed by an `ApplicationPrimitiveDataType` where the `swDataDefProps.swRecordLayout` refers to a `SwRecordLayout` with a `ROW_DIR` approach, the value of `ApplicationValueSpecification.swValueCont.swArraysize.v[i]` (i.e., counting up from the first element of `swArraysize.v`) shall be identical to the number of axis points of the respective `SwCalprmAxisSet.swCalprmAxis` where attribute `swAxisIndex` is set to `i`:

- If the respective `SwCalprmAxis` is a `SwAxisGrouped`, then the number of axis points shall be retrieved from the attribute `subElement.arraySize` of the `ImplementationDataType` that is referenced by a `DataTypeMap` that also references the `ApplicationDataType` referenced in the role `SwAxisGrouped.sharedAxisType`.
- If the respective `SwCalprmAxis` is a `SwAxisIndividual`, the number of axis points is identical to the value of attribute `SwAxisIndividual.swMaxAxisPoints`.

]

[constr_10504] ApplicationValueSpecification where attribute category is set to VAL_BLK and ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSizeMult exists for ROW_DIR SwRecordLayout

Imposition time: IT_ValSpec

[If the attribute `ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSizeMult` exists, then the value of `ApplicationValueSpecification.swValueCont.swArraysize` can be identical to the value of `ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSizeMult` if the referenced `ApplicationPrimitiveDataType.swDataDefProps.swRecordLayout` defines a row-first `ROW_DIR`.

]

[constr_10505] ApplicationValueSpecification where attribute category is set to MAP, CUBOID, CUBE_4, or CUBE_5 and COLUMN_DIR SwRecordLayout

Imposition time: IT_ValSpec

[In the context of an `ApplicationValueSpecification` where attribute `category` is set to `MAP`, `CUBOID`, `CUBE_4`, or `CUBE_5` that is applied to a `DataPrototype` typed by an `ApplicationPrimitiveDataType` where the `swDataDefProps.swRecordLayout` refers to a `SwRecordLayout` with a `COLUMN_DIR` approach, the value of `ApplicationValueSpecification.swValueCont.swArraysize.v[-i]` (i.e., counting down from the last element of `swArraysize.v`) shall be

identical to the number of axis points of the respective `SwCalprmAxisSet.swCalprmAxis` where attribute `swAxisIndex` is set to i :

- If the respective `SwCalprmAxis` is a `SwAxisGrouped`, then the number of axis points shall be retrieved from the attribute `subElement.arraySize` of the `ImplementationDataType` that is referenced by a `DataTypeMap` that also references the `ApplicationDataType` referenced in the role `SwAxisGrouped.sharedAxisType`.
- If the respective `SwCalprmAxis` is a `SwAxisIndividual`, the number of axis points is identical to the value of attribute `SwAxisIndividual.swMaxAxisPoints`.

]

[constr_10506] ApplicationValueSpecification where attribute `category` is set to `VAL_BLK` and `ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSizeMult` exists for `COLUMN_DIR` `SwRecordLayout`

Imposition time: IT_ValSpec

[If the attribute `ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSizeMult` exists, then the value of `ApplicationValueSpecification.swValueCont.swArraysize` can be taken over from the reversed values of `ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSizeMult` if the referenced `ApplicationPrimitiveDataType.swDataDefProps.swRecordLayout` defines a column-first `COLUMN_DIR` layout.

]

[constr_10507] ApplicationValueSpecification where attribute `category` is set to `VAL_BLK` and `ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSize` exists

Imposition time: IT_ValSpec

[If the attribute `ApplicationPrimitiveDataType.swDataDefProps.swValueBlockSize` exists, then the value of `ApplicationValueSpecification.swValueCont.swArraysize` shall contain a single v and the value of v shall be identical to the value of attribute `swValueBlockSize`.

]

[constr_10520] Multiplicity of `AssemblySwConnector.provider`

Imposition time: IT_CompSwcT

[For each `AssemblySwConnector`, the reference `AssemblySwConnector.provider` shall exist.

]

[constr_10521] Multiplicity of `AssemblySwConnector.requester`

Imposition time: IT_CompSwcT

[For each `AssemblySwConnector`, the reference `AssemblySwConnector.requester` shall exist.

]

[constr_10525] Existence of attribute `ApplicationValueSpecification.category`

Imposition time: IT_CpgExe

[For each `ApplicationValueSpecification`, attribute `category` shall exist.

]

[constr_10527] Existence of `RoleBasedDataAssignment.usedDataElement.autosarVariable` for `RoleBasedDataAssignment.role = ramBlock`

Imposition time: IT_RteGen

[If the attribute `RoleBasedDataAssignment.role` is set to the value `ramBlock`, then the reference `RoleBasedDataAssignment.usedDataElement.autosarVariable` shall not exist.

]

[constr_10529] Existence of `AsynchronousServerCallResultPoint` for `AsynchronousServerCallPoint` where attribute `timeout` is defined

Imposition time: IT_CpgExe

[For each `AsynchronousServerCallPoint` where attribute `timeout` exists, an `AsynchronousServerCallResultPoint` shall exist that references the `AsynchronousServerCallPoint` in the role `asynchronousServerCallPoint`.

]

[constr_10532] Restriction for `SenderComSpec.transmissionProps.onChangeDataPrototype`

Imposition time: IT_CpgExe

[If the `SenderComSpec.dataElement` refers to an `AutosarDataPrototype` aggregated by a `SenderReceiverInterface` in the role `dataElement`, then a `DataPrototypeReference` aggregated in the role `SenderComSpec.transmissionProps.onChangeDataPrototype` shall only exist as

- a `DataPrototypeInPortInterfaceRef` that aggregates a `DataPrototypeInSenderReceiverInterfaceInstanceRef` in the role `dataPrototypeInSenderReceiverInterface` or
- an `ImplementationDataTypeElementInPortInterfaceRef`.

]

[constr_10533] Existence of `TransmissionComSpecProps.onChangeDataPrototype.dataPrototypeInSenderReceiverInterface.rootDataPrototypeInSr`*Imposition time:* IT_CpgExe

[If all of the following conditions apply:

- the `SenderComSpec.dataElement` refers to an `AutosarDataPrototype` aggregated by a `SenderReceiverInterface` in the role `dataElement` and
- the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype.dataPrototypeInSenderReceiverInterface` exists,

then the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype.dataPrototypeInSenderReceiverInterface.rootDataPrototypeInSr` shall **not** exist.

]

[constr_10534] Existence of `TransmissionComSpecProps.onChangeDataPrototype.rootDataPrototype`*Imposition time:* IT_CpgExe

[If all of the following conditions apply:

- the `SenderComSpec.dataElement` refers to an `AutosarDataPrototype` aggregated by a `SenderReceiverInterface` in the role `dataElement` and
- the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype` exists,

then the aggregation in the role `TransmissionComSpecProps.onChangeDataPrototype.rootDataPrototype` shall **not** exist

]

[constr_10538] Existence of attribute `ReceiverComSpec.dataElement`*Imposition time:* IT_CpgExe[For each `ReceiverComSpec`, attribute `dataElement` shall exist.

]

[constr_10539] Existence of attribute `SenderComSpec.dataElement`*Imposition time:* IT_CpgExe[For each `SenderComSpec`, attribute `dataElement` shall exist.

]

[constr_10542] RunnableEntity is referenced by an OperationInvokedEvent

Imposition time: IT_CpgExe

[A [RunnableEntity](#) that is referenced by one or more (according to [TPS_SWCT_-01225]) [OperationInvokedEvents](#) in the role [startOnEvent](#) shall **not** be referenced in the same role ([startOnEvent](#)) by any other subclass of [RTEEvent](#).

]

[constr_10543] Uniqueness of reference PortAPIOption.port

Imposition time: IT_CpgExe

[Any [PortPrototype](#) may be referenced **at most once** in the role [PortAPIOption.port](#).

]

[constr_10544] Ownership of reference PortAPIOption.port

Imposition time: IT_CpgExe

[A [PortPrototype](#) referenced in the role [PortAPIOption.port](#) shall be owned by the same [AtomicSwComponentType](#) that also owns the [SwcInternalBehavior](#) that in turn owns the [PortAPIOption](#) from which the [PortPrototype](#) is referenced.

]

[constr_10548] Uniqueness of ReceiverComSpec.dataElement

Imposition time: IT_CpgExe

[Within the context of an [AbstractRequiredPortPrototype](#), no two [ReceiverComSpecs](#) shall exist where the target of the reference in the role [dataElement](#) is identical.

]

[constr_10549] Uniqueness of SenderComSpec.dataElement

Imposition time: IT_CpgExe

[Within the context of an [AbstractProvidedPortPrototype](#), no two [SenderComSpecs](#) shall exist where the target of the reference in the role [dataElement](#) is identical.

]

[constr_10550] Uniqueness of `ClientComSpec.operation`

Imposition time: IT_CpgExe

[Within the context of an `AbstractRequiredPortPrototype`, no two `ClientComSpecs` shall exist where the target of the reference in the role `operation` is identical.

]

[constr_10551] Uniqueness of `ServerComSpec.operation`

Imposition time: IT_CpgExe

[Within the context of an `AbstractProvidedPortPrototype`, no two `ServerComSpecs` shall exist where the target of the reference in the role `operation` is identical.

]

[constr_10552] Uniqueness of `ModeSwitchSenderComSpec.modeGroup`

Imposition time: IT_CpgExe

[Within the context of an `AbstractProvidedPortPrototype`, no two `ModeSwitchSenderComSpecs` shall exist where the target of the reference in the role `modeGroup` is identical.

]

[constr_10553] Uniqueness of `ModeSwitchReceiverComSpec.modeGroup`

Imposition time: IT_CpgExe

[Within the context of an `AbstractRequiredPortPrototype`, no two `ModeSwitchReceiverComSpecs` shall exist where the target of the reference in the role `modeGroup` is identical.

]

[constr_10554] Uniqueness of `ParameterProvideComSpec.parameter`

Imposition time: IT_CpgExe

[Within the context of an `AbstractProvidedPortPrototype`, no two `ParameterProvideComSpecs` shall exist where the target of the reference in the role `parameter` is identical.

]

[constr_10555] Uniqueness of `ParameterRequireComSpec.parameter`

Imposition time: IT_CpgExe

[Within the context of an `AbstractRequiredPortPrototype`, no two `ParameterRequireComSpecs` shall exist where the target of the reference in the role `parameter` is identical.

]

[constr_10556] Uniqueness of `NvRequireComSpec.variable`

Imposition time: IT_CpgExe

[Within the context of an `AbstractRequiredPortPrototype`, no two `NvRequireComSpecs` shall exist where the target of the reference in the role `variable` is identical.

]

[constr_10557] Uniqueness of `NvProvideComSpec.variable`

Imposition time: IT_CpgExe

[Within the context of an `AbstractProvidedPortPrototype`, no two `NvProvideComSpecs` shall exist where the target of the reference in the role `variable` is identical.

]

[constr_10558] `SwBaseType` associated with corresponding `ApplicationRecordElement` and `ImplementationDataTypeElement`

Imposition time: IT_CpgExe

[If

- an `ApplicationRecordElement` is implicitly (i.e. by position in the enclosing `ApplicationRecordDataType`) mapped to an `ImplementationDataTypeElement` of category VALUE and
- the `ApplicationRecordElement` typed by an `ApplicationPrimitiveDataType` and a `DataTypeMap` exists that maps the `ApplicationPrimitiveDataType` to an `ImplementationDataType` of category VALUE,

then the affected `ImplementationDataType` of category VALUE shall reference the **identical** `SwBaseType` as the affected `ImplementationDataTypeElement`.

]

[constr_10559] Uniqueness of `DataPrototypeMapping.firstDataPrototype` and `secondDataPrototype`

Imposition time: IT_RteGen

[Within the context of a `VariableAndParameterInterfaceMapping`, **no two** `DataPrototypeMappings` shall exist where the targets of the combination of references in the roles `firstDataPrototype` and `secondDataPrototype` are identical.

]

[constr_10560] Uniqueness of `ClientServerOperationMapping.firstOperation` and `secondOperation`

Imposition time: IT_RteGen

[Within the context of a `ClientServerInterfaceMapping`, **no two** `ClientServerOperationMappings` shall exist where the targets of the combination of references in the roles `firstOperation` and `secondOperation` are identical.

]

[constr_10561] Uniqueness of `ClientServerApplicationErrorMapping.firstApplicationError` and `secondApplicationError`

Imposition time: IT_RteGen

[Within the context of a `ClientServerInterfaceMapping`, **no two** `ClientServerApplicationErrorMappings` shall exist where the targets of the combination of references in the roles `firstApplicationError` and `secondApplicationError` are identical.

]

[constr_10562] Uniqueness of `ModeDeclarationGroupPrototypeMapping.firstModeGroup` and `secondModeGroup`

Imposition time: IT_RteGen

[Within the context of a `ModeInterfaceMapping`, **no two** `ModeDeclarationGroupPrototypeMappings` shall exist where the targets of the combination of references in the roles `firstModeGroup` and `secondModeGroup` are identical.

]

[constr_10563] Uniqueness of `ModeDeclarationMapping.firstMode` and `secondMode`

Imposition time: IT_RteGen

[Within the context of a `ModeDeclarationMappingSet`, no two `ModeDeclarationMappings` shall exist where the targets of the combination of references in the roles `firstMode` and `secondMode` are identical.

]

[constr_10564] Uniqueness of `TriggerMapping.firstTrigger` and `secondTrigger`

Imposition time: IT_RteGen

[Within the context of a `TriggerInterfaceMapping`, no two `TriggerMappings` shall exist where the targets of the combination of references in the roles `firstTrigger` and `secondTrigger` are identical.

]

[constr_10565] Uniqueness of `SubElementMapping.firstElement` and `secondElement`

Imposition time: IT_RteGen

[Within the context of a `DataPrototypeMapping`, no two `SubElementMappings` shall exist where the targets of the combination of references in the roles `firstElement` and `secondElement` are identical.

]

[constr_10575] No multiple instantiation of `NvBlockSwComponentType`

Imposition time: IT_RteGen

[For each `NvBlockSwComponentType`, attribute `internalBehavior.supportsMultipleInstantiation` shall **always** be set to false.

]

[constr_10606] Existence of `ConstantSpecificationMapping` or `CalibrationParameterValue` for `ApplicationValueSpecification` or `ApplicationRuleBasedValueSpecification` of category `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, and `CUBE_5`

Imposition time: IT_RteGen

[Any `ApplicationValueSpecification` or `ApplicationRuleBasedValueSpecification` of category `CURVE`, `MAP`, `CUBOID`, `CUBE_4`, and `CUBE_5` shall be referenced from

- a `ConstantSpecificationMapping` in the role `applConstant` and/or

- a `CalibrationParameterValue` in the role `applInitValue`.

]

[constr_10607] Number of `ConstantSpecificationMappings` that are allowed to reference a `ApplicationValueSpecification` or `ApplicationRuleBasedValueSpecification` in the context of an `InternalBehavior`

Imposition time: IT_RteGen

[Within the collection of all `ConstantSpecificationMappings` owned by `ConstantSpecificationMappingSets` referenced by a single `InternalBehavior`, at most one `ConstantSpecificationMapping` shall refer to any given `ApplicationValueSpecification` or `ApplicationRuleBasedValueSpecification`.

]

[constr_10608] Number of `ConstantSpecificationMappings` that are allowed to reference a `ApplicationValueSpecification` or `ApplicationRuleBasedValueSpecification` in the context of a `ParameterSwComponentType`

Imposition time: IT_RteGen

[Within the collection of all `ConstantSpecificationMappings` owned by `ConstantSpecificationMappingSets` referenced by a single `ParameterSwComponentType`, at most one `ConstantSpecificationMapping` shall refer to any given `ApplicationValueSpecification` or `ApplicationRuleBasedValueSpecification`.

]

[constr_10610] Compatibility of `PhysicalDimensions` in the context is the creation of an `ApplicationValueSpecification`

Imposition time: IT_CpgExe

[In the context of the creation of an `ApplicationValueSpecification`, two `PhysicalDimension` definitions are compatible if and only if the values of

- `lengthExp`
- `massExp`
- `timeExp`
- `currentExp`
- `temperatureExp`
- `molarAmountExp`
- `luminousIntensityExp`

are identical and **either**

- the `shortNames` are identical **or**
- a `PhysicalDimensionMapping` exists that maps one of the `PhysicalDimensions` in the role `firstPhysicalDimension` and the other `PhysicalDimension` in the role `secondPhysicalDimension`.

]

2.6 CP_TPS_SystemTemplate

[constr_1001] Value of `dataId` shall be unique

Status: OBSOLETE

Imposition time: IT_SysDesc

[The value of the `dataId` shall be unique within the scope of the `System`.

]

[constr_1002] End-to-end protection does not support n:1 communication

Status: OBSOLETE

Imposition time: IT_SysDesc

[As the n:1 communication scenario implies that probably not all senders use the same `dataId` this scenario is explicitly not supported.

]

[constr_1198] `TriggerToSignalMapping.systemSignals` eligible for a `TriggerToSignalMapping` in case no `DataTransformation` is used

Imposition time: IT_EcuExt

[The `ISignal` that is referenced by a `SystemSignal` that in turn is referenced by a `TriggerToSignalMapping` in the role `systemSignal` shall have the length attribute set to 0 if the `ISignal` does not reference a `DataTransformation` in the role `dataTransformation`.

]

[constr_1199] `ISignals` relating to `systemSignals` eligible for a `TriggerToSignalMapping` shall use update bit in case no `DataTransformation` is used

Imposition time: IT_SysDesc

[An `ISignal`

- that is used to reference a `systemSignal` that in turn is referenced by a `TriggerToSignalMapping` and
- does not reference a `DataTransformation` in the role `dataTransformation`

shall be referenced by an `ISignalToIPduMapping` where the attribute `updateIndicationBitPosition` is defined.

]

[constr_1265] DoIpGidSynchronizationNeeds can only exist once per ECU_EXTRACT

Imposition time: IT_EcuExt

[Within the context of one `System` of `category` ECU_EXTRACT, there can only be at most one `DoIpGidSynchronizationNeeds`.

]

[constr_1266] DoIpGidNeeds can only exist once per ECU_EXTRACT

Imposition time: IT_EcuExt

[Within the context of one `System` of `category` ECU_EXTRACT, there can only be at most one `DoIpGidNeeds`.

]

[constr_1267] DoIpActivationLineNeeds can only exist once per ECU_EXTRACT

Imposition time: IT_EcuExt

[Within the context of one `System` of `category` ECU_EXTRACT, there can only be at most one `DoIpActivationLineNeeds`.

]

[constr_1367] periodicResponseUudt.periodicResponseUudt shall only refer to a DcmIPdu

Imposition time: IT_SysDesc

[If the role `periodicResponseUudt` exists then every `PduTriggering` referenced in the role `periodicResponseUudt` shall only refer to a `DcmIPdu`.

]

[constr_1368] Limitation of the target of references from `DiagnosticConnection`

Imposition time: IT_SysDesc

[`DiagnosticConnection` shall only reference (via the indirection created by `TpConnectionIdent`) the following sub-classes of the meta-class `TpConnection`:

- `CanTpConnection`
- `FlexrayTpConnection`
- `FlexrayArTpConnection`
- `DoIpTpConnection`

]

[constr_1369] `CommunicationConnectors` shall be attached to the same `CommunicationCluster`

Imposition time: IT_SysDesc

[All `CommunicationConnectors` referenced from `GlobalTimeMaster` and `GlobalTimeSlaves` aggregated in one `GlobalTimeDomain` shall be referenced in the role `commConnector` by the same `PhysicalChannel` aggregated by the same `CommunicationCluster`.

]

[constr_1370] Consistency of `GlobalTimeDomain`

Imposition time: IT_SysDesc

[The `GlobalTimeSlave` referenced in the role `GlobalTimeGateway.slave` and the `GlobalTimeMaster` referenced in the role `GlobalTimeGateway.master` shall **not** be aggregated by the same `GlobalTimeDomain`.

]

[constr_1371] Consistency of attribute `host`

Imposition time: IT_SysDesc

[Within the context of an aggregating `GlobalTimeDomain`, the `CommunicationConnectors` referenced in the role `GlobalTimeGateway.master.communicationConnector` and `GlobalTimeGateway.slave.communicationConnector` shall be aggregated by the same `EcuInstance` that is referenced in the role `GlobalTimeGateway.host`.

]

[constr_1372] Consistency of attribute pduTriggering

Imposition time: IT_SysDesc

[Within the context of an aggregating `GlobalTimeDomain`, the `pduTriggering` shall be owned by `PhysicalChannel` that is also referencing the `CommunicationConnectors` referenced in the roles `GlobalTimeSlave.communicationConnector` and `GlobalTimeMaster.communicationConnector`.

]

[constr_1373] GlobalTimeMaster with attribute isSystemWideGlobalTimeMaster set to TRUE

Imposition time: IT_SysDesc

[`GlobalTimeMaster` with attribute `isSystemWideGlobalTimeMaster` set to TRUE shall not be referenced in the role `GlobalTimeGateway.master`.

]

[constr_1374] Only fan-out possible for GlobalTimeGateway

Imposition time: IT_SysDesc

[For all `GlobalTimeGateways` that refer to the same `EcuInstance` the condition applies that no two `GlobalTimeGateways` shall refer to the same `GlobalTimeMaster`.

]

[constr_1387] Transmission of Variable-Size Array Data Types by means of a Transformer

Imposition time: IT_SysDesc

[If a Transformer is used for the transmission of a Variable-Size Array Data Types then the Variable-Size Array Data Type shall be a "new-world" variable-size array data type according to [TPS_SWCT_01644] and [TPS_SWCT_01645]. "Old-world" dynamic-size array data types according to [TPS_SWCT_01641] and [TPS_SWCT_01642] are not supported.

]

[constr_1441] In AUTOSAR, the transmission of union data types over the network is only supported by the SOME/IP Transformer

Imposition time: IT_SysDesc

[If an `ImplementationDataType` according to [TPS_SWCT_01700], i.e. of category STRUCT that encloses an `ImplementationDataTypeElement` of category UNION, is used to directly or (via a `DataTypeMap`) indirectly type an `AutosarDataPrototype` and the latter is mapped to a `SystemSignal` then the `ISignal` that ref-

erences that `SystemSignal` shall aggregate `SOMEIPTransformationISignal-Props` in the role `transformationISignalProps`.

]

[constr_1463] Applicable values for `J1939Cluster.networkId`

Imposition time: IT_SysDesc

[The values of the attribute `J1939Cluster.networkId` shall always be within the interval 1..4.

]

[constr_1641] Consistent assignment of TLV data ids to `ApplicationRecordDataType`

Imposition time: IT_SysDesc

[For every `ApplicationRecordDataType` where direct members set the attribute `ApplicationRecordElement.isOptional` to the value `True` references to all direct members of this `ApplicationRecordDataType` shall be created on the basis of the definition of `TlvDataIdDefinition`.

]

[constr_1642] Consistent assignment of TLV data ids to `ImplementationDataType` or `ImplementationDataTypeElement`

Imposition time: IT_SysDesc

[For every `ImplementationDataType` or `ImplementationDataTypeElement` of category `STRUCTURE` where direct members set the attribute `ImplementationDataTypeElement.isOptional` to the value `True` references to all direct members of this `ImplementationDataType` resp `ImplementationDataTypeElement` shall be created on the basis of the definition of `TlvDataIdDefinition`.

]

[constr_1643] Completeness of the existence of a set of `TlvDataIdDefinition.tlvArguments`

Imposition time: IT_SysDesc

[If the reference `TlvDataIdDefinition.tlvArguments` exists for one `argument` of a given `ClientServerOperation` then further `TlvDataIdDefinition.tlvArguments` shall exist for all `arguments` of the given `ClientServerOperation` and all affected `TlvDataIdDefinitions` shall be referenced by the same `SOMEIPTransformationISignalProps` via `TlvDataIdDefinitionSet`.

]

[constr_1644] Completeness of the existence of a set of [TlvDataIdDefinition.tlvRecordElements](#)

Imposition time: IT_SysDesc

[If the reference [TlvDataIdDefinition.tlvRecordElement](#) exists for one element of a given [ApplicationRecordDataType](#) then further [TlvDataIdDefinition.tlvRecordElement](#) shall exist for all elements of the given [ApplicationRecordDataType](#) and all affected [TlvDataIdDefinitions](#) shall be referenced by the same [SOMEIPTransformationISignalProps](#) via [TlvDataIdDefinitionSet](#).

]

[constr_1645] Completeness of the existence of a set of [TlvDataIdDefinition.tlvImplementationDataTypeElements](#)

Imposition time: IT_SysDesc

[Completeness of the existence of a set of [TlvDataIdDefinition.tlvImplementationDataTypeElements](#) If the reference [TlvDataIdDefinition.tlvImplementationDataTypeElement](#) exists for one [subElement](#) of a given [ImplementationDataType](#) or [ImplementationDataTypeElement](#) then further [TlvDataIdDefinition.tlvImplementationDataTypeElement](#) shall exist for all [subElements](#) of the given [ImplementationDataType](#) or [ImplementationDataTypeElement](#) and all affected [TlvDataIdDefinitions](#) shall be referenced by the same [SOMEIPTransformationISignalProps](#) via [TlvDataIdDefinitionSet](#).

]

[constr_1646] Scope of the uniqueness of the value of [TlvDataIdDefinition.id](#) for references to [ArgumentDataPrototype](#)

Imposition time: IT_SysDesc

[For all [TlvDataIdDefinition](#) that are referencing [ArgumentDataPrototypes](#) of a given [ClientServerOperation](#) in the role [tlvArgument](#) the attribute [TlvDataIdDefinition.id](#) shall exist and have a unique value in the context of respective [arguments](#) of the enclosing [ClientServerOperation](#) where attribute [direction](#) is set to the value [in/inout](#) or [out/inout](#).

Note: an [argument](#) where attribute [direction](#) is set to the value [in](#) may have the same data id as an [argument](#) where attribute [direction](#) is set to the value [out](#) since the two are transferred in separate messages.

]

[constr_1647] Scope of the uniqueness of the value of `TlvDataIdDefinition.id` for references to `ApplicationRecordElement`

Imposition time: IT_SysDesc

[For all `TlvDataIdDefinition` that are referencing `ApplicationRecordElements` of a given `ApplicationDataType` in the role `tlvRecordElement` the attribute `TlvDataIdDefinition.id` shall exist and have a unique value in the context of respective enclosing `ApplicationRecordDataType`.

]

[constr_1648] Scope of the uniqueness of the value of `TlvDataIdDefinition.id` for references to `ImplementationDataTypeElement`

Imposition time: IT_SysDesc

[For all `TlvDataIdDefinition` that are referencing `ImplementationDataTypeElements` of a given `ImplementationDataType/ImplementationDataTypeElement` in the role `tlvImplementationDataTypeElement` the attribute `TlvDataIdDefinition.id` shall exist and have a unique value in the context of respective enclosing `ImplementationDataType` or `ImplementationDataTypeElement`.

]

[constr_1649] `TlvDataIdDefinition` referencing `ArgumentDataPrototype`

Imposition time: IT_SysDesc

[Each `ArgumentDataPrototype` shall be referenced at most once in the role `tlvArgument` in the context of the same `SOMEIPTransformationISignalProps`.

]

[constr_1650] `TlvDataIdDefinition` referencing `ApplicationRecordElement`

Imposition time: IT_SysDesc

[Each `ApplicationRecordElement` shall be referenced at most once in the role `tlvRecordElement` in the context of the same `SOMEIPTransformationISignalProps`.

]

[constr_1651] TlvDataIdDefinition referencing ImplementationDataTypeElement

Imposition time: IT_SysDesc

[Each `ImplementationDataTypeElement` shall be referenced at most once in the role `tlvImplementationDataTypeElement` in the context of the same `SOMEIPTransformationISignalProps`.

]

[constr_1652] Definition of static length fields sizes in case of TLV usage

Imposition time: IT_SysDesc

[If `TlvDataIdDefinitions` are defined for a `SOMEIPTransformationISignalProps`, the attributes `sizeOfArrayLengthFields`, `sizeOfStructLengthFields`, `sizeOfStringLengthFields` and `sizeOfUnionLengthFields` shall be greater than 0.

]

[constr_1653] Identical values for length fields sizes in case of TLV usage

Imposition time: IT_SysDesc

[If `TlvDataIdDefinitions` are defined for a `SOMEIPTransformationISignalProps`, the attributes `sizeOfArrayLengthFields`, `sizeOfStructLengthFields`, `sizeOfStringLengthFields` and `sizeOfUnionLengthFields` shall have an identical value.

]

[constr_1654] No definition of length field sizes on DataPrototype level in case of TLV usage

Imposition time: IT_SysDesc

[If `TlvDataIdDefinitions` are defined for a `SOMEIPTransformationISignalProps`, the attributes `sizeOfArrayLengthFields`, `sizeOfStructLengthFields` and `sizeOfUnionLengthFields` shall not be defined on `DataPrototype` level but only on `ISignal` level.

]

[constr_1655] The mutual existence of LinMasters in the LinSlave EcuExtract

Imposition time: IT_EcuExt

[A `LinMaster` shall not be part of the `EcuExtract` of a corresponding `LinSlave`.

]

[constr_1656] No application-level write access to `LinErrorResponse.responseError` on Lin slave

Imposition time: IT_SysDesc

[The `SystemSignal` referenced in the role `systemSignal` by the `ISignal` referenced by the `ISignalTriggering` that in turn is referenced in the role `LinErrorResponse.responseError` shall not be referenced by a `DataMapping` that allows for writing to the `SystemSignal`.

]

[constr_1657] Existence of `LinPhysicalChannel.scheduleTable`

Imposition time: IT_SysDesc

[In any given Ecu Extract that contains a `LinSlave`, the `LinPhysicalChannel` that relates to the respective `LinSlave` via `commConnector.commController` shall not aggregate a `LinScheduleTable`.

]

[constr_1669] Existence of `PduTriggering.secOcCryptoMapping`

Imposition time: IT_SysDesc

[The reference `PduTriggering.secOcCryptoMapping` shall only exist if the `PduTriggering` also references a `SecuredIPdu` in the role `ipdu`.

]

[constr_1670] Prohibition of usage of `TlsCryptoMapping` in case of UDP socket connections

Imposition time: IT_SysDesc

[A `TlsCryptoServiceMapping` may only be referenced by an `ApplicationEndpoint` in the role `tlsCryptoMapping` if that `ApplicationEndpoint` aggregates a `TcpTp` in the role `tpConfiguration`.

]

[constr_1671] Supported values of `TlsCryptoServiceMapping.category`

Imposition time: IT_SysDesc

[The only supported values of attribute `TlsCryptoServiceMapping.category` are:

- **TLS_SERVER**: the `TlsCryptoServiceMapping` assumes the role of the *server* in the TLS connection.
- **TLS_CLIENT**: the `TlsCryptoServiceMapping` assumes the role of the *client* in the TLS connection.

]

[constr_1672] Existence of `TlsCryptoCipherSuite.certificate` and `TlsCryptoCipherSuite.pskIdentity` in the server role*Imposition time:* IT_SysDesc**[Either**

- the reference to `CryptoServiceCertificate` in the role `TlsCryptoCipherSuite.certificate`
- the aggregation of `TlsPskIdentity` in the role `TlsCryptoCipherSuite.pskIdentity`

shall exist if the `TlsCryptoCipherSuite` is aggregated by a `TlsCryptoServiceMapping` that has attribute `category` set to the value `TLS_SERVER`.

]

[constr_2025] Uniqueness of `symbol` attributes*Imposition time:* IT_EcuExt

[With the exception of `RunnableEntities` that are subject to [constr_1234] (`RunnableEntities` owned by `NvBlockSwComponentTypes`), in the context of a single `EcuInstance` the values of the `RunnableEntity.symbol` in combination with the attribute `symbol` of the meta-class `SymbolProps` owned by `AtomicSwComponentType` of all deployed `RunnableEntities` shall be unique such that no two (or more) combinations of `RunnableEntity.symbol` and the `symbol` of the meta-class `SymbolProps` owned by `AtomicSwComponentType` in the role `symbolProps` share the same value.

]

[constr_3000] valid `SenderRecCompositeTypeMappings`*Imposition time:* IT_EcuExt

[All `SenderRecRecordElementMappings` or `SenderRecArrayElementMappings` aggregated in the context of a given `SenderReceiverToSignalGroupMapping` shall reference a `SystemSignal` that is also referenced in the role `systemSignal` by the `SystemSignalGroup` that is referenced by the enclosing `SenderReceiverToSignalGroupMapping` in the role `signalGroup`.

]

[constr_3002] valid `swcToImplMapping`*Imposition time:* IT_EcuExt

[The referenced `SwcImplementation` refers to a `SwcInternalBehavior` that is part of a `AtomicSwComponentType`. The same `AtomicSwComponentType` shall be the type of the referenced `SwComponentPrototype`.

SwcToImplMapping.componentImplementation.behavior.component == SwcToImplMapping.component.type

]

[constr_3003] Number of CAN channels

Imposition time: IT_SysDesc

[CAN clusters shall aggregate exactly one [PhysicalChannel](#).

]

[constr_3004] Clustering and separation shall be exclusive

Imposition time: IT_SysDesc

[Clustering and separation shall be exclusive, i.e. it SHALL NOT be possible that two [SwComponentPrototypes](#) A and B are associated both by a [ComponentClustering](#) and by a [ComponentSeparation](#) at the same time.

]

[constr_3005] valid [EcuResourceEstimation](#)

Imposition time: IT_SysDesc

[The same [EcuInstance](#) shall be referenced directly from the [EcuResourceEstimation](#) and from the [SwcToEcuMapping](#):

[EcuResourceEstimation.swCompToEcuMapping.ecuInstance](#) == [EcuResourceEstimation.ecuInstance](#)

]

[constr_3006] valid [EcuMapping](#)

Imposition time: IT_SysDesc

[The referenced [hwCommunicationController](#) and [hwCommunicationPort](#) shall be part of the referenced [ecu](#).

[ECUMapping.ecu.nestedElement](#) contains [ECUMapping.commControllerMapping.hwCommunicationController](#)

[ECUMapping.ecu.nestedElement](#) contains [ECUMapping.hwPortMapping.hwCommunicationPort](#)

]

[constr_3007] selectorFieldCodes for dynamic part alternatives

Imposition time: IT_SysDesc

[The `selectorFieldCodes` for the dynamic part alternatives within one `Multi-plexedIPdu` shall differ from each other.

]

[constr_3008] EcuInstance subelements

Imposition time: IT_SysDesc

[The `CommunicationConnector` and the `CommunicationController` that is referenced by the `CommunicationConnector` shall be owned by the same `EcuInstance`.

]

[constr_3009] Overlapping of ISignals is prohibited

Imposition time: IT_SysDesc

[`ISignals` mapped to an `ISignalIPdu` shall not overlap.

]

[constr_3010] ISignalIPdu length shall not be exceeded

Imposition time: IT_SysDesc

[The combined length of all `ISignals` and `updateIndicationBitPositions` that are mapped into an `ISignalIPdu` shall not exceed the defined `Pdu length`.

]

[constr_3011] Overlapping of updateIndicationBits of ISignals is prohibited

Imposition time: IT_SysDesc

[The `updateIndicationBitPosition` for an `ISignal` in an `ISignalIPdu` shall not overlap with other `updateIndicationBitPositions` or `ISignal` locations.

]

[constr_3012] Overlapping of Pdus is prohibited

Imposition time: IT_SysDesc

[`Pdus` mapped to a `FlexrayFrame` shall NOT overlap.

]

[constr_3013] FlexrayFrame length shall not be exceeded

Imposition time: IT_SysDesc

[The combined length of all Pdu that are mapped into a FlexrayFrame shall not exceed the defined FlexrayFrame length.

]

[constr_3014] Overlapping of updateIndicationBits for Pdu is prohibited

Imposition time: IT_SysDesc

[The updateIndicationBitPosition for a Pdu in a FlexrayFrame shall NOT overlap with other updateIndicationBitPositions and Pdu locations.

]

[constr_3015] Number of LIN channels

Imposition time: IT_SysDesc

[LIN clusters shall aggregate exactly one LinPhysicalChannel.

]

[constr_3018] Number of FlexRay channels

Imposition time: IT_SysDesc

[A FlexrayCluster shall use either one FlexrayPhysicalChannel with channelName set to either channelA or channelB or else two FlexrayPhysicalChannels with one channelName channelA and one channelName channelB.

]

[constr_3019] In the flat ECU extract each required interface shall be satisfied by connected provided interfaces

Imposition time: IT_EcuExt

[In case of the flat System with category ECU_EXTRACT all VariableDataPrototypes specified by the SenderReceiverInterface of the RPortPrototype need to be supplied by some of the PPortPrototypes being connected with SwConnectors.

]

[constr_3020] communicationDirection of containedISignalIPduGroups

Imposition time: IT_SysDesc

[The value of the attribute `communicationDirection` of `containedISignalIPduGroup` shall be identical to the value of the attribute `communicationDirection` of the enclosing `ISignalIPduGroup`.

]

[constr_3021] Mapping of SensorActuatorSwComponents to SensorActuatorHwElements

Imposition time: IT_EcuExt

[Only `SwComponentPrototypes` that are typed by `SensorActuatorSwComponentType` shall be mapped to a `HwElement` with `category` `SensorActuator` via the `controlledHwElement` relation.

]

[constr_3025] Usage of NPdus in TpConnections

Imposition time: IT_SysDesc

[In case several `TpConnections` use the same Frame ID for their communication needs only one `NPdu` element per Frame Id shall exist. This constraint applies for all supported AUTOSAR transport protocols (`CanTp`, `LinTp`, `FrTp`, `FrArTp` and `J1939Tp`).

]

[constr_3027] Existence of ecuExtractVersion

Imposition time: IT_EcuExt

[In case the category of the System is `SYSTEM_EXTRACT` or `ECU_EXTRACT` the `ecuExtractVersion` attribute shall be defined.

]

[constr_3028] FibexElements

Imposition time: IT_SysDesc

[Each `FibexElement` that is used in the System Description shall be referenced by the `System` element in the role `FibexElement`.

]

[constr_3029] Assign-Frame command usage

Imposition time: IT_SysDesc

[For the LIN 2.0 Assign-Frame command the [LinConfigurableFrame](#) list shall be used. For the LIN 2.1 Assign-Frame-PID-Range command the [LinOrderedConfigurableFrame](#) list shall be used.

]

[constr_3030] valid relationship between [ECUMapping](#) and [EcuInstance](#)

Imposition time: IT_SysDesc

[If an [EcuInstance](#) is assigned to a [HwElement](#) the [EcuInstance](#) shall belong to the same [System](#) as the [ECUMapping](#).

]

[constr_3031] Complete System Description does not have ports on the outermost composition

Imposition time: IT_SysDesc

[In a complete [System](#) with [category](#) ABSTRACT_SYSTEM_DESCRIPTION or [System](#) with [category](#) SYSTEM_DESCRIPTION this outermost [CompositionSwComponentType](#) has the unique feature that it doesn't have any outside ports, but all the SWC contained in it are connected to each other and fully specified by their [SwComponentTypes](#), [PortPrototypes](#), [PortInterfaces](#), [VariableDataPrototypes](#), [InternalBehavior](#) etc.

]

[constr_3036] [Pdus](#) in CAN and LIN Frames

Imposition time: IT_SysDesc

[CAN Frames and LIN Frames shall only contain one [Pdu](#).

]

[constr_3037] maximum [Frame frameLength](#) for CAN and LIN

Imposition time: IT_SysDesc

[For CAN and LIN the maximum [frameLength](#) is 8 bytes and 64 bytes in case of CAN FD.

]

[constr_3038] maximum `Frame` `frameLength` for FlexRay

Imposition time: IT_SysDesc

[For FlexRay the maximum `frameLength` is 254 bytes.

]

[constr_3039] `pncIdentifier` range

Imposition time: IT_SysDesc

[The `pncIdentifier` value shall be in the range of 8..63 for normal CAN and in the range of 8..511 for CAN FD, FlexRay and Ethernet.

]

[constr_3040] Restriction of `pncIdentifier` values

Imposition time: IT_SysDesc

[The `pncIdentifier` value shall be within the range described by `pncVectorOffset` and `pncVectorLength`.

]

[constr_3044] CBV configuration in case partial network is used

Imposition time: IT_SysDesc

[In case a partial network is used the control bit vector (CBV) shall be defined in Byte 0 of the `NmPdu` (`nmCbvPosition` = 0).

]

[constr_3045] Signal content evaluation vs. Mode evaluation

Imposition time: IT_SysDesc

[The mode evaluation and the signal content evaluation shall not be used in the same `IPdu`. A mix of these two types is not allowed.

]

[constr_3046] Consistency of `TransmissionModeCondition.iSignalInIPdu`

Imposition time: IT_SysDesc

[The `ISignalToIPduMapping` referenced by the `TransmissionModeCondition` in the role `iSignalInIPdu` shall belong to the same `ISignalIPdu` as the `TransmissionModeCondition`.

]

[constr_3047] Uniqueness of `macMulticastAddresses`

Imposition time: IT_SysDesc

[A `macMulticastAddress` shall be unique in a particular `EthernetCluster`.
]

[constr_3048] Range of `vlanIdentifier`

Imposition time: IT_SysDesc

[The allowed values of `vlanIdentifier` range from 0 to 4095.
]

[constr_3050] `J1939Cluster` uses exactly one `CanPhysicalChannel`

Imposition time: IT_SysDesc

[A `J1939Cluster` shall aggregate exactly one `CanPhysicalChannel`.
]

[constr_3051] Restriction of `ISignalMapping` references

Imposition time: IT_SysDesc

[If the `sourceSignal` references an `ISignal` then the `targetSignal` shall also reference an `ISignal`.
]

[constr_3052] Complete `ISignalMapping` of `ISignalGroup` signals

Imposition time: IT_SysDesc

[If an `ISignalMapping` to an `ISignal` that is a member of a `ISignalGroup` exists then (see [TPS_SYST_01120]) an `ISignalMapping` to the enclosing `ISignalGroup` shall exist as well.
]

[constr_3053] Complete `ISignalMapping` of target `ISignalGroup`

Imposition time: IT_SysDesc

[If an `ISignalGroup` is referenced by a `targetSignal` then [TPS_SYST_02162] applies for each of the contained `ISignal` of that `ISignalGroup`.
]

[constr_3057] Maximal one `BusspecificNmEcu` per `NmEcu` and bus system is allowed to be defined

Imposition time: IT_SysDesc

[For each `NmEcu`, at most one `BusspecificNmEcu` per bus system (FlexRay/Can/Udp/J1939) is allowed to be defined.

]

[constr_3058] References from `SenderRecArrayElementMapping` and from `SenderRecRecordElementMapping` to `SystemSignals` are not allowed within a `SenderReceiverCompositeElementToSignalMapping`

Imposition time: IT_EcuExt

[The reference from `SenderRecArrayElementMapping` to `SystemSignal` and from `SenderRecRecordElementMapping` to `SystemSignal` shall not exist if the enclosing `SenderRecCompositeTypeMapping` is owned by a `SenderReceiverCompositeElementToSignalMapping`.

]

[constr_3060] Allowed Attributes for `networkRepresentationProps` and `physicalProps`

Imposition time: IT_SysDesc

[

Attributes of SwDataDefProps	SystemSignal.physicalProps	ISignal.networkProps
<code>additionalNativeTypeQualifier</code>	NA	NA
<code>annotation</code>	NA	NA
<code>baseType</code>	NA	D
<code>baseType.category</code>	NA	M
<code>BaseTypeDirectDefinition.baseTypeEncoding</code>	NA	D
<code>BaseTypeDirectDefinition.byteOrder</code>	NA	NA
<code>BaseTypeDirectDefinition.baseTypeSize</code>	NA	0..1
<code>BaseTypeDirectDefinition.memAlignment</code>	NA	NA
<code>BaseTypeDirectDefinition.nativeDeclaration</code>	NA	NA
<code>compuMethod</code>	D	I
<code>dataConstr</code>	D	M
<code>displayFormat</code>	D	M
<code>implementationDataType</code>	NA	NA
<code>invalidValue</code>	NA	D
<code>stepSize</code>	NA	NA
<code>swAddrMethod</code>	NA	NA
<code>swAlignment</code>	NA	NA
<code>swBitRepresentation</code>	NA	NA
<code>swCalibrationAccess</code>	NA	NA
<code>swCalprmAxisSet</code>	NA	NA
<code>swComparisonVariable</code>	NA	NA
<code>swDataDependency</code>	NA	NA
<code>swHostVariable</code>	NA	NA
<code>swImplPolicy</code>	NA	NA
<code>swIntendedResolution</code>	NA	NA
<code>swInterpolationMethod</code>	NA	NA
<code>swIsVirtual</code>	NA	NA
<code>swPointerTargetProps</code>	NA	NA
<code>swRecordLayout</code>	NA	NA
<code>swRefreshTiming</code>	NA	NA
<code>swTextProps</code>	NA	NA
<code>swValueBlockSize</code>	NA	NA
<code>unit</code>	D	M
<code>valueAxisDataType</code>	NA	NA

]

[constr_3062] The `EcuInstance` that is referenced from a specific `CouplingElement` shall be connected to the same `EthernetCluster` as the specific `CouplingElement`

Imposition time: IT_SysDesc

[The `EcuInstance` referenced from a specific `CouplingElement` in the role `ecuInstance` shall be connected via the `CommunicationConnector` and a `Eth-`

`ernetPhysicalChannel` that refers the `CommunicationConnector` to the `EthernetCluster` referenced by the specific `CouplingElement` in the role `communicationCluster`.

]

[constr_3067] `initValue` defined in the context of `ISignal`

Imposition time: IT_SysDesc

[The definition of an `initValue` in the context of an `ISignal` shall only be a `NumericalValueSpecification`, `TextValueSpecification` or `ArrayValueSpecification` that aggregates elements of type `NumericalValueSpecification` or `TextValueSpecification`.

]

[constr_3068] `DoIpPowerModeStatusNeeds` in the category `ECU_EXTRACT`

Imposition time: IT_EcuExt

[If and only if `DoIP` (i.e. any of the subclasses of `DoIpServiceNeeds` are present) is used on an Ecu then the `DoIpPowerModeStatusNeeds` shall exist exactly once in a `System` of category `ECU_EXTRACT`.

]

[constr_3069] Allowed `CanNmCluster.nmNidPosition` values

Imposition time: IT_SysDesc

[If defined, the value of `CanNmCluster.nmNidPosition` shall only be set to either 0 or 1.

]

[constr_3070] Allowed `CanNmCluster.nmCbvPosition` values

Imposition time: IT_SysDesc

[If defined, the value of `CanNmCluster.nmCbvPosition` shall only be set to either 0 or 1.

]

[constr_3071] CanNmCluster.nmCbvPosition and CanNmCluster.nmNidPosition shall never have the same value

Imposition time: IT_SysDesc

[CanNmCluster.nmCbvPosition and CanNmCluster.nmNidPosition shall never have the same value.

]

[constr_3073] nmVoteInformation only valid for FrNm

Imposition time: IT_SysDesc

[The nmVoteInformation attribute is only valid for FrNm.

]

[constr_3074] No TransmissionAcknowledgementRequest for multiple senders

Imposition time: IT_EcuExt

[If more than one SenderComSpec exist (in different PortPrototypes on atomic level) that refer to data elements effectively mapped to the same SystemSignal it is not allowed that any SenderComSpec aggregates transmissionAcknowledge.

]

[constr_3078] Allowed UdpNmCluster.nmNidPosition values

Imposition time: IT_SysDesc

[If defined, the value of UdpNmCluster.nmNidPosition shall only be set to either 0 or 1.

]

[constr_3079] Allowed UdpNmCluster.nmCbvPosition values

Imposition time: IT_SysDesc

[If defined, the value of UdpNmCluster.nmCbvPosition shall only be set to either 0 or 1.

]

[constr_3080] UdpNmCluster.nmCbvPosition and UdpNmCluster.nmNidPosition shall never have the same value

Imposition time: IT_SysDesc

[UdpNmCluster.nmCbvPosition and UdpNmCluster.nmNidPosition shall never have the same value.

]

[constr_3081] Value of category in [GeneralPurposePdu](#)

Imposition time: IT_SysDesc

[The attribute [category](#) of [GeneralPurposePdu](#) can have the following values:

- SD (Service Discovery)
- GLOBAL_TIME
- DoIP

]

[constr_3082] Value of category in [GeneralPurposeIPdu](#)

Imposition time: IT_SysDesc

[The attribute [category](#) of [GeneralPurposeIPdu](#) can have the following values:

- XCP
- SOMEIP_SEGMENTED_IPDU
- DLT
- IDS

]

[constr_3083] Exactly one [AtomicSwComponentType](#) on an [EcuInstance](#) may use [GeneralCallbackEventDataChanged](#) / [GeneralCallbackEventStatusChange](#)

Imposition time: IT_EcuExt

[The Dem only supports exactly one [AtomicSwComponentType](#) using [GeneralCallbackEventDataChanged](#) / [GeneralCallbackEventStatusChange](#) on one [EcuInstance](#).

]

[constr_3084] Service port in the role [PowerTakeOff](#)

Imposition time: IT_EcuExt

[Within the context of one [EcuInstance](#), there can only be one service port that uses the role [PowerTakeOff](#) in the [RoleBasedPortAssignment.role](#).

]

[constr_3085] Service port in the role CallbackDCMRequestServices

Imposition time: IT_EcuExt

[Within the context of one `EcuInstance`, there can only be one service port that uses the role `CallbackDCMRequestServices` in the `RoleBasedPortAssignment.role`.

]

[constr_3086] Role of `SystemSignal` in n:1 sender-receiver communication

Imposition time: IT_EcuExt

[In case of n:1 communications

- if `DataTransformation` is used each sender shall be mapped to the same `SystemSignal`
- if `DataTransformation` is not used each sender shall be mapped
 - to the same `SystemSignal` in case of a primitive `DataType` on the sender side,
 - to the same `SystemSignalGroup` in case of a composite `DataType` on the sender side.

]

[constr_3090] `TpSdu` transmission on a `PhysicalChannel`

Imposition time: IT_SysDesc

[The `IPdu` that is referenced by a `TpConnection` in the role `tpSdu` shall be referenced by exactly one `PduTriggering` aggregated on the `PhysicalChannel` of the `TpConnection`.

]

[constr_3094] Consistent `ISignalPort.communicationDirection` for `ISignalTriggerings` of `ISignalGroups` and contained `ISignals`

Imposition time: IT_SysDesc

[In case the `ISignals` contained in an `ISignalGroup` are referenced by an `ISignalTriggering`, the `communicationDirection` of the `ISignalPort` referenced by the `ISignal`'s `ISignalTriggering` shall be identical to the `communicationDirection` of the `ISignalPort` referenced by the containing `ISignalGroup`'s `ISignalTriggering`.

]

[constr_3095] canControllerFdAttributes and canControllerFdRequirements are mutually exclusive

Imposition time: IT_SysDesc

[The existence of `canControllerFdAttributes` and `canControllerFdRequirements` is mutually exclusive.

]

[constr_3096] Allowed values for `diagnosticMessageType`

Imposition time: IT_SysDesc

[The allowed values of `diagnosticMessageType` range from 1..57.

]

[constr_3097] Overlapping of segments of one `MultiplexedIPdu` is not allowed

Imposition time: IT_SysDesc

[The segments defined by the `SegmentPosition` elements of one and the same `MultiplexedIPdu` - aggregated via `StaticPart` and `DynamicPart` - shall not overlap.

]

[constr_3098] Defined segments of one `MultiplexedIPdu` shall not exceed the length of the `MultiplexedIPdu`

Imposition time: IT_SysDesc

[The segments defined by the `SegmentPosition` elements of one and the same `MultiplexedIPdu` - aggregated via `StaticPart` and `DynamicPart` - shall not exceed the length of the `MultiplexedIPdu`.

]

[constr_3099] Defined segments in a `DynamicPart` shall not exceed the length of any `DynamicPartAlternative.iPdu`

Imposition time: IT_SysDesc

[The segments defined by the `SegmentPosition` elements aggregated in the `DynamicPart` of a `MultiplexedIPdu` shall not exceed the length of any `DynamicPartAlternative.iPdu`.

]

[constr_3100] Defined segments in a `StaticPart` shall not exceed the length of the `StaticPart.iPdu`

Imposition time: IT_SysDesc

[The segments defined by the `SegmentPosition` elements aggregated in the `StaticPart` of a `MultiplexedIPdu` shall not exceed the length of the `StaticPart.iPdu`

]

[constr_3101] Signal representation of selector field for `DynamicPartAlternative`

Imposition time: IT_SysDesc

[Every `ISignalIPdu` that is referenced by the `DynamicPartAlternative` shall contain an `ISignal` that represents the selector field. The selector field signal shall be located at the position that is described by the `selectorFieldLength` and `selectorFieldStartPosition`.

]

[constr_3102] Restriction on usage of `J1939NodeName` attributes

Imposition time: IT_SysDesc

[A `J1939NmCluster` shall not aggregate two `J1939NmNodes` with identical `J1939NodeName` attributes.

]

[constr_3103] Range of `ecuInstance`

Imposition time: IT_SysDesc

[The allowed values of `ecuInstance` range from 0 to 7.

]

[constr_3104] Range of `function`

Imposition time: IT_SysDesc

[The allowed values of `function` range from 0 to 255.

]

[constr_3105] Range of `functionInstance`

Imposition time: IT_SysDesc

[The allowed values of `functionInstance` range from 0 to 31.

]

[constr_3106] Range of `identityNumber`*Imposition time:* IT_SysDesc[The allowed values of `identityNumber` range from 0 to 2097151.

]

[constr_3107] Range of `industryGroup`*Imposition time:* IT_SysDesc[The allowed values of `industryGroup` range from 0 to 7.

]

[constr_3108] Range of `manufacturerCode`*Imposition time:* IT_SysDesc[The allowed values of `manufacturerCode` range from 0 to 2047.

]

[constr_3109] Range of `vehicleSystem`*Imposition time:* IT_SysDesc[The allowed values of `vehicleSystem` range from 0 to 127.

]

[constr_3110] Range of `vehicleSystemInstance`*Imposition time:* IT_SysDesc[The allowed values of `vehicleSystemInstance` range from 0 to 15.

]

[constr_3111] `returnSignal` in `ClientServerToSignalMapping` is mandatory*Imposition time:* IT_EcuExt[A `ClientServerToSignalMapping` shall always have a `returnSignal` defined.

]

[constr_3112] Invalidation support for partial mapping of a data element typed by composite data type*Imposition time:* IT_EcuExt[If a `VariableDataPrototype` with a composite data type in a `PPortPrototype` is mapped to a `SystemSignalGroup` and only a subset of elements of the composite data type that are primitives is mapped to separate `SystemSignals` of the Sys-

temSignalGroup then at least one mapped primitive shall have an `invalidValue` defined.

]

[constr_3113] AbstractEthernetFrame shall not have a PduToFrameMapping

Imposition time: IT_SysDesc

[It is not allowed to map Pdus into AbstractEthernetFrames.

]

[constr_3114] FlatInstanceDescriptors pointing to the same ParameterDataPrototype shall have different postBuildVariantConditions

Imposition time: IT_EcuExt

[FlatInstanceDescriptors that are pointing as an atpTarget to the same ParameterDataPrototype instance shall have different postBuildVariantConditions.

]

[constr_3115] FlatInstanceDescriptors pointing to the same ParameterDataPrototype instance

Imposition time: IT_EcuExt

[When several FlatInstanceDescriptors point to the same ParameterDataPrototype instance as an atpTarget in the context of a ParameterInterface the different FlatInstanceDescriptors shall point to the PPortPrototype of the owning ParameterSwComponentType. In this case the PPortPrototype typed by the ParameterInterface is part of the context of the according AnyInstanceRef.

]

[constr_3116] Overlap of ClientIdRanges in the context of the enclosing System

Imposition time: IT_SysDesc

[The ClientIdRange defined for an EcuInstance shall not overlap with the ClientIdRange of any other EcuInstance in the context of the enclosing System.

]

[constr_3117] Allowed value of attribute clientId

Imposition time: IT_SysDesc

[Within the context of one ClientIdDefinition, the value of attribute clientId shall be in the range of ClientIdRange.lowerLimit and ClientIdRange.

`upperLimit` for the `ClientIdRange` that is aggregated by the `EcuInstance` onto which the `SwComponentPrototypes` included in the `ClientIdDefinition`. `clientServerOperation` are mapped.

]

[constr_3118] Valid reference target for `ClientIdDefinition.clientServerOperation.contextPort`

Imposition time: IT_SysDesc

[In the context of the definition of a `ClientIdDefinition`, the reference `clientServerOperation.contextPort` shall only refer to an `RPortPrototype`.

]

[constr_3121] The length of transformer chains is limited to 255 transformers

Imposition time: IT_SysDesc

[The maximum number of `DataTransformation.transformerChain` references in the context of one `DataTransformation` shall be limited to 255.

]

[constr_3122] At most one transformer of each transformer class inside a transformer chain

Imposition time: IT_SysDesc

[If the value of a `transformerClass` of a `TransformationTechnology` referenced by a `DataTransformation` does not equal `custom`, it shall be different from all other `transformerClass` values of `TransformationTechnologies` referenced by the same `DataTransformation`.

]

[constr_3123] Serializer transformer shall be the first in a chain

Imposition time: IT_SysDesc

[A serializer transformer (`TransformationTechnology` with attribute `transformerClass` set to `serializer`) shall be the first transformer in a transformer chain.

]

[constr_3124] Applicability of `needsOriginalData`

Imposition time: IT_SysDesc

[The attribute `needsOriginalData` of a `TransformationTechnology` shall only be used for the non-first transformers in the transformer chain.

]

[constr_3125] Value of attribute `inPlace` for the first transformer in a chain

Imposition time: IT_SysDesc

[The attribute `inPlace` shall be set to `false` if the `TransformationTechnology` of the `BufferProperties` is referenced as first reference in the ordered list of references `transformerChain` from a `DataTransformation`.

]

[constr_3127] Certain `ISignals` always need a reference to `DataTransformation`

Imposition time: IT_SysDesc

[An `ISignal` which references a `SystemSignal` which is referenced by a `SystemSignalGroup` in the role `transformingSystemSignal` shall always reference a `DataTransformation`.

]

[constr_3128] SOME/IP transformer configuration

Imposition time: IT_SysDesc

[For each `TransformationDescription` variant that is a `SOMEIPTransformationDescription`

- attribute `protocol` of `TransformationTechnology` shall be set to `SOMEIP`
- attribute `version` of `TransformationTechnology` shall be set to `1.0.0`
- attribute `transformerClass` of `TransformationTechnology` shall be set to `serializer`
- attribute `headerLength` of `BufferProperties` shall be set to `64` (bits).

]

[constr_3129] Byte Order of SOME/IP transformer

Imposition time: IT_SysDesc

[The attribute `byteOrder` of `SOMEIPTransformationDescription` shall be different from `opaque`.

]

[constr_3130] Range of Interface Version

Imposition time: IT_SysDesc

[The value of the attribute `interfaceVersion` shall be in the range [0; 255]

]

[constr_3132] Required COM Based Transformation for `comBasedSignalGroupTransformation`

Imposition time: IT_SysDesc

[If a `ISignalGroup` has a reference to the `DataTransformation` element in the role `comBasedSignalGroupTransformation` then this `DataTransformation` shall be the handled by the COM Based Transformer [8].

]

[constr_3133] `physicalLayerType` of connected `CouplingPorts`

Imposition time: IT_SysDesc

[The `physicalLayerType` of two `CouplingPorts` which are connected via a `CouplingPortConnection` shall be equal.

]

[constr_3134] The connection of two `CouplingPorts` with `connectionNegotiationBehavior` set to `master` is forbidden

Imposition time: IT_SysDesc

[The `connectionNegotiationBehavior` of two `CouplingPorts` which are connected via a `CouplingPortConnection` shall not be both set to `master`.

]

[constr_3135] The connection of two `CouplingPorts` with `connectionNegotiationBehavior` set to `slave` is forbidden

Imposition time: IT_SysDesc

[The `connectionNegotiationBehavior` of two `CouplingPorts` which are connected via a `CouplingPortConnection` shall not be both set to `slave`.

]

[constr_3136] Allowed payload of SecuredIPdus

Imposition time: IT_SysDesc

[SecuredIPdus are allowed to reference PduTriggerings of ISignalIPdus, ContainerIPdus, DcmIPdus, MultiplexedIPdus, GeneralPurposeIPdus with category SOMEIP_SEGMENTED_IPDU and UserDefinedIPdus.

]

[constr_3137] IPduPort.rxSecurityVerification is configurable on the receiver side

Imposition time: IT_SysDesc

[The IPduPort.rxSecurityVerification attribute shall only be used in IPduPorts with the communicationDirection = in.

]

[constr_3138] IPduPort.rxSecurityVerification validness

Imposition time: IT_SysDesc

[The IPduPort.rxSecurityVerification information is only valid for SecuredIPdus.

]

[constr_3140] No ByteOrderEnum.opaque allowed for System.containerIPduHeaderByteOrder

Imposition time: IT_SysDesc

[The values of System.containerIPduHeaderByteOrder are restricted to ByteOrderEnum.mostSignificantByteFirst and ByteOrderEnum.mostSignificantByteLast. I.e. the value ByteOrderEnum.opaque is not allowed.

]

[constr_3141] Only IPdus shall be part of a ContainerIPdu

Imposition time: IT_SysDesc

[The PduTriggering which is referenced in the role ContainerIPdu.containedPduTriggering or ContainerIPdu.containedIPduTriggeringProps.containedPduTriggering shall refer to a subclass of an IPdu in the role PduTriggering.iPdu.

]

[constr_3142] Mandatory headerIdLongHeader for longHeader

Imposition time: IT_SysDesc

[For each IPdu which is assigned to a ContainerIPdu in the role ContainerIPdu.containedPduTriggering or ContainerIPdu.containedIPduTriggering-Props.containedPduTriggering with ContainerIPdu.headerType = longHeader the ContainedIPduProps.headerIdLongHeader shall be defined.

]

[constr_3143] Mandatory headerIdShortHeader for shortHeader

Imposition time: IT_SysDesc

[For each IPdu which is assigned to a ContainerIPdu in the role ContainerIPdu.containedPduTriggering or ContainerIPdu.containedIPduTriggering-Props.containedPduTriggering with ContainerIPdu.headerType = shortHeader the ContainedIPduProps.headerIdShortHeader shall be defined.

]

[constr_3144] Mandatory IPdu.containedIPduProps for contained IPdus

Imposition time: IT_SysDesc

[For each IPdu which is assigned to a ContainerIPdu in the role ContainerIPdu.containedPduTriggering, the IPdu.containedIPduProps shall be defined.

]

[constr_3146] Partial Networking timing constraint

Imposition time: IT_SysDesc

[For Partial Networking the following timing constraints shall be ensured:

- CAN / Ethernet: $(pnResetTime + pncPrepareSleepTimer) < nmNetworkTimeout$
- FlexRay: $(pnResetTime + pncPrepareSleepTimer) < nmReadySleepTime$

]

[constr_3148] executeDespiteDataUnavailability setting in case an E2E Transformer is used

Imposition time: IT_SysDesc

[A transformer chain using E2E shall be configured with `DataTransformation.executeDespiteDataUnavailability = TRUE`.

]

[constr_3149] TransformationTechnology.needsOriginalData settings for E2E Transformer

Imposition time: IT_SysDesc

[The TransformationTechnology.needsOriginalData attribute of a TransformationTechnology element of an E2E transformer shall be set to FALSE.

]

[constr_3151] BufferProperties.headerLength settings for an E2E transformer used in combination with a SOME/IP transformer

Imposition time: IT_SysDesc

[The BufferProperties.headerLength for an E2E transformer located in a transformer chain with a SOME/IP transformer shall be configured with the following values depending on the value of the EndToEndTransformationDescription.profile-Name attribute:

1. PROFILE_01: BufferProperties.headerLength = 16 bits
2. PROFILE_02: BufferProperties.headerLength = 16 bits
3. PROFILE_04: BufferProperties.headerLength = 96 bits
4. PROFILE_05: BufferProperties.headerLength = 24 bits
5. PROFILE_06: BufferProperties.headerLength = 40 bits
6. PROFILE_07: BufferProperties.headerLength = 160 bits
7. PROFILE_08: BufferProperties.headerLength = 128 bits
8. PROFILE_11: BufferProperties.headerLength = 16 bits
9. PROFILE_22: BufferProperties.headerLength = 16 bits
10. PROFILE_04m: BufferProperties.headerLength = 128 bits
11. PROFILE_07m: BufferProperties.headerLength = 192 bits
12. PROFILE_08m: BufferProperties.headerLength = 160 bits
13. PROFILE_44: BufferProperties.headerLength = 96 bits
14. PROFILE_44m: BufferProperties.headerLength = 128 bits

]

[constr_3152] BufferProperties.headerLength settings for any transformer used in combination with a COM Based transformer

Imposition time: IT_SysDesc

[A transformer used in a transformer chain with a COM Based transformer shall be configured with the following values:

- `BufferProperties.headerLength = 0`

]

[constr_3153] E2E header field reservation required by COM Based transformer

Imposition time: IT_SysDesc

[A COM Based transformer that is used in a transformer chain with an E2E transformer requires that the following amount of space is allocated for the E2E header fields using a proper `ISignalGroup` layout according to [TPS_SYST_02068]:

PROFILE_01: if `dataIdMode == lower12Bit`: 16 bits

PROFILE_01: if `dataIdMode != lower12Bit`: 12 bits

PROFILE_02: 16 bits

PROFILE_04: 96 bits

PROFILE_05: 24 bits

PROFILE_06: 40 bits

PROFILE_07: 160 bits

PROFILE_08: 128 bits

PROFILE_11: if `dataIdMode == lower12Bit`: 16 bits

PROFILE_11: if `dataIdMode == all16Bit`: 12 bits

PROFILE_22: 16 bits

PROFILE_04m: 128 bits

PROFILE_07m: 192 bits

PROFILE_08m: 160 bits

PROFILE_44: 96 bits

PROFILE_44m: 128 bits

PROFILE_76: 40 bits

]

[constr_3155] Allowed values for `EndToEndTransformationDescription.upperHeaderBitsToShift`

Imposition time: IT_SysDesc

[The value of of the `EndToEndTransformationDescription.upperHeaderBitsToShift` attribute depends on the used serializing transformer:

COM based transformer: 0 (no bits are shifted)

SOME/IP transformer: 64 (to support the header shift of SOME/IP).

Custom transformer: no restriction (depends on header length and placement of custom transformer)

]

[constr_3156] Allowed values for `EndToEndTransformationISignalProps.dataId` in PROFILE_01 and PROFILE_11

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_01 or PROFILE_11 then the value of the `EndToEndTransformationISignalProps.dataId` attribute shall be in the range of 0-65535.

]

[constr_3157] Allowed values for `EndToEndTransformationISignalProps.dataId` in PROFILE_01 and PROFILE_11 in case `dataIdMode` is set to `lower12Bit`

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_01 or PROFILE_11 and the value of `EndToEndTransformationDescription.dataIdMode` attribute has a value of `lower12Bit` then the value of the `EndToEndTransformationISignalProps.dataId` attribute shall be in the range of 256-65535.

]

[constr_3158] Allowed values for `EndToEndTransformationDescription.maxDeltaCounter` in PROFILE_01 and PROFILE_11

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_01 or PROFILE_11 then the attribute `maxDeltaCounter` shall be in the range 1-14.

]

[constr_3159] Allowed values for `EndToEndTransformationDescription.maxDeltaCounter` in PROFILE_04, PROFILE_04m PROFILE_44 and PROFILE_44m

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_04, PROFILE_04m, PROFILE_44, or PROFILE_44m the value of `maxDeltaCounter` attribute shall be in the range 1-65535.

]

[constr_3160] `EndToEndTransformationISignalProps.dataId` in PROFILE_02 and PROFILE_22

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_02 or PROFILE_22 then the multiplicity of the `dataId` attribute shall be 16 and the value of each instance shall be in the range 0..255.

]

[constr_3161] `EndToEndTransformationISignalProps.dataLength` in PROFILE_01, PROFILE_02, PROFILE_05, PROFILE_11, PROFILE_22

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_01, PROFILE_02, PROFILE_05, PROFILE_11, or PROFILE_22 then the multiplicity of the `EndToEndTransformationISignalProps.dataLength` attribute shall be 1.

]

[constr_3162] `EndToEndTransformationISignalProps.minDataLength` and `EndToEndTransformationISignalProps.maxDataLength` in PROFILE_01, PROFILE_02, PROFILE_05, PROFILE_11, PROFILE_22

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_01, PROFILE_02, PROFILE_05, PROFILE_11, or PROFILE_22 then the multiplicity of the attributes `EndToEndTransformationISignalProps.minDataLength` and `EndToEndTransformationISignalProps.maxDataLength` shall be 0.

]

[constr_3163] `EndToEndTransformationISignalProps.minDataLength` and `EndToEndTransformationISignalProps.maxDataLength` in PROFILE_04,

PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, and PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_04, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 then the multiplicity of the attributes `EndToEndTransformationISignalProps.minLength` and `EndToEndTransformationISignalProps.maxLength` shall be 1.

]

[constr_3164] `EndToEndTransformationISignalProps.dataLength` in PROFILE_04, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, and PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_04, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 then the multiplicity of the attribute `EndToEndTransformationISignalProps.dataLength` shall be 0.

]

[constr_3165] Effect of `EndToEndTransformationDescription.upperHeaderBitsToShift` value in PROFILE_01, PROFILE_11

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_01 or PROFILE_11 and the serializing transformer is different than the ComBasedTransformer then:

1. `EndToEndTransformationDescription.crcOffset` shall be set to the same value of `upperHeaderBitsToShift`.
2. `EndToEndTransformationDescription.counterOffset` shall be set to the value of `upperHeaderBitsToShift + 8`.
3. (if used) `EndToEndTransformationDescription.dataIdNibbleOffset` shall be set to the value of `upperHeaderBitsToShift + 12`.

]

[constr_3166] EndToEndTransformationDescription.upperHeaderBitsToShift in PROFILE_02

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_02 then the value of the `upperHeaderBitsToShift` attribute shall be 0.

]

[constr_3167] Effect of EndToEndTransformationDescription.upperHeaderBitsToShift value in PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m and PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 the value of the `EndToEndTransformationDescription.offset` attribute shall be equal to the value of the `EndToEndTransformationDescription.upperHeaderBitsToShift` attribute.

]

[constr_3169] EndToEndTransformationDescription.offset value in PROFILE_02, PROFILE_22 and PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_02, PROFILE_22, or PROFILE_76 then the value of the `EndToEndTransformationDescription.offset` attribute shall be 0.

]

[constr_3172] Effect of EndToEndTransformationDescription.profileBehavior value in PROFILE_01

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_01 and the value of the `profileBehavior` attribute is R4_2 then:

- the value of the `EndToEndTransformationDescription.maxNoNewOrRepeatedData` attribute shall be 14.
- the value of the `EndToEndTransformationDescription.syncCounterInit` attribute shall be 1.

]

[constr_3173] Effect of `EndToEndTransformationDescription.profileBehavior` value in PROFILE_02

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_02 and the value of the `profileBehavior` attribute is R4_2 then:

- the value of the `EndToEndTransformationDescription.maxNoNewOrRepeatedData` attribute shall be 15.
- the value of the `EndToEndTransformationDescription.syncCounterInit` attribute shall be 1.

]

[constr_3174] `EndToEndTransformationDescription` settings not allowed in PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_11, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m and PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_11, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 then:

1. the multiplicity of the `EndToEndTransformationDescription.maxNoNewOrRepeatedData` attribute shall be 0.
2. the multiplicity of the `EndToEndTransformationDescription.syncCounterInit` attribute shall be 0.
3. the multiplicity of the `EndToEndTransformationDescription.profileBehavior` attribute shall be 0.

]

[constr_3182] Restriction on `TransformationTechnology.transformationDescriptionVariationPoint`

Imposition time: IT_SysDesc

[The `EndToEndTransformationDescription.profileName` attribute shall not be subject to variability for a given `ISignal` / `ISignalGroup`, i.e., the value of the `EndToEndTransformationDescription.profileName` attribute shall be the same in all different variants.

]

[constr_3183] ISignalGroup with transformationISignalProps

Imposition time: IT_SysDesc

[An ISignalGroup that aggregates transformationISignalProps shall reference the DataTransformation in the role comBasedSignalGroupTransformation.

]

[constr_3184] Only one EndToEndTransformationISignalProps.dataId element in PROFILE_01 and PROFILE_11

Imposition time: IT_SysDesc

[If the EndToEndTransformationDescription.profileName attribute has a value of PROFILE_01 or PROFILE_11 then the multiplicity of the EndToEndTransformationISignalProps.dataId attribute shall be 1.

]

[constr_3185] Multiplicity of EndToEndTransformationDescription.dataIdMode in PROFILE_01 and PROFILE_11

Imposition time: IT_SysDesc

[If the EndToEndTransformationDescription.profileName attribute is set to PROFILE_01 or PROFILE_11 then the multiplicity of the EndToEndTransformationDescription.dataIdMode attribute shall be 1.

]

[constr_3186] Multiplicity of EndToEndTransformationDescription.dataIdMode in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76

Imposition time: IT_SysDesc

[If the EndToEndTransformationDescription.profileName attribute is set to a value of PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 then the multiplicity of the EndToEndTransformationDescription.dataIdMode attribute shall be 0.

]

[constr_3187] Multiplicity of `EndToEndTransformationDescription.counterOffset` in PROFILE_01 and PROFILE_11

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to PROFILE_01 or PROFILE_11 then the multiplicity of the `EndToEndTransformationDescription.counterOffset` attribute shall be 1.

]

[constr_3188] Multiplicity of `EndToEndTransformationDescription.counterOffset` in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to a value of PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 then the multiplicity of the `EndToEndTransformationDescription.counterOffset` attribute shall be 0.

]

[constr_3189] Multiplicity of `EndToEndTransformationDescription.crcOffset` in PROFILE_01 and PROFILE_11

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to PROFILE_01 or PROFILE_11 then the multiplicity of the `EndToEndTransformationDescription.crcOffset` attribute shall be 1.

]

[constr_3190] Multiplicity of `EndToEndTransformationDescription.crcOffset` in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to a value of PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 then the multiplicity of the `EndToEndTransformationDescription.crcOffset` attribute shall be 0.

]

[constr_3191] Multiplicity of `EndToEndTransformationDescription.dataIdNibbleOffset` in PROFILE_01, PROFILE_11 and `dataIdMode` equal to `lower12Bit`

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to PROFILE_01 or PROFILE_11 and the value of the `EndToEndTransformationDescription.dataIdMode` attribute is set to `lower12Bit` then the multiplicity of the `EndToEndTransformationDescription.dataIdNibbleOffset` attribute shall be 1.

]

[constr_3192] Multiplicity of `EndToEndTransformationDescription.dataIdNibbleOffset` in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m and PROFILE_76 or `dataIdMode` different from `lower12Bit`

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to a value of PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 or the `EndToEndTransformationDescription.dataIdMode` attribute is set to value different from `lower12Bit` then the multiplicity of the `EndToEndTransformationDescription.dataIdNibbleOffset` attribute shall be 0.

]

[constr_3193] Multiplicity of `EndToEndTransformationDescription.offset` in PROFILE_01 and PROFILE_11

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to PROFILE_01 or PROFILE_11 then the multiplicity of the `EndToEndTransformationDescription.offset` attribute shall be 0.

]

[constr_3194] Multiplicity of `EndToEndTransformationDescription.offset` in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to a value PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07,

PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, or PROFILE_76 then the multiplicity of the `EndToEndTransformationDescription.offset` attribute shall be 1.

]

[constr_3195] Allowed values for `EndToEndTransformationDescription.maxDeltaCounter` in PROFILE_02 and PROFILE_22

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_02 or PROFILE_22 then the attribute `maxDeltaCounter` shall be in the range 1-15.

]

[constr_3196] Allowed values for `EndToEndTransformationDescription.maxDeltaCounter` in PROFILE_05

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_05 then the attribute `maxDeltaCounter` shall be in the range 1-255.

]

[constr_3197] Allowed values for `EndToEndTransformationDescription.maxDeltaCounter` in PROFILE_06

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_06 then the attribute `maxDeltaCounter` shall be in the range 1-255.

]

[constr_3198] Uniqueness of `PncMapping.shortLabel`

Imposition time: IT_SysDesc

[If the optional `shortLabel` attribute is used it shall be unique in the `System` scope.

]

[constr_3199] ISignal that has dataTypePolicy set to transformingISignal shall reference a DataTransformation

Imposition time: IT_SysDesc

[In a complete model every ISignal that has dataTypePolicy set to transformingISignal shall reference a DataTransformation.

]

[constr_3202] LinFrameTriggering to LinUnconditionalFrame reference restriction in LinEventTriggeredFrame context

Imposition time: IT_SysDesc

[Within a PhysicalChannel a LinUnconditionalFrame shall be referenced by only one LinFrameTriggering to allow a derivation of the identifier of a substituted Frame if the LinUnconditionalFrame is referenced by a LinEventTriggeredFrame in the role linUnconditionalFrame.

]

[constr_3203] LinFrameTriggering to LinSporadicFrame reference restriction in LinSporadicFrame context

Imposition time: IT_SysDesc

[Within a PhysicalChannel a LinUnconditionalFrame shall be referenced by only one LinFrameTriggering to allow a derivation of the identifier of a substituted Frame if the LinUnconditionalFrame is referenced by a LinSporadicFrame in the role substitutedFrame.

]

[constr_3204] LinUnconditionalFrames associated with a LinSporadicFrame

Imposition time: IT_SysDesc

[A LinUnconditionalFrame associated with a LinSporadicFrame shall not be allocated in the same LinScheduleTable as the LinSporadicFrame.

]

[constr_3205] Existence of FramePort for a FrameTriggering that references a LinSporadicFrame

Imposition time: IT_SysDesc

[A FrameTriggering that references a LinSporadicFrame shall not have a reference to a FramePort.

]

[constr_3206] Existence of `FramePort` for a `FrameTriggering` that references a `LinEventTriggeredFrame`

Imposition time: IT_SysDesc

[A `FrameTriggering` that references a `LinEventTriggeredFrame` shall not have a reference to a `FramePort`.

]

[constr_3208] `executeDespiteDataUnavailability` usage restriction

Imposition time: IT_SysDesc

[In the set of more than one `ISignal` which reference the same `SystemSignal` in the role `systemSignal`, there shall be no `ISignal` which references a `DataTransformation` where `executeDespiteDataUnavailability` is set to true.

]

[constr_3209] `CanFrameTriggerings` with identical PGN

Imposition time: IT_SysDesc

[For all `CanFrameTriggerings` where the attribute `identifier` contains the identical PGN (as defined in section 5.2 Protocol Data Unit in [9]) the attribute `j1939requestable` shall also have an identical value.

]

[constr_3210] `J1939TpPgs` with identical `pgn` value

Imposition time: IT_SysDesc

[For all `J1939TpPgs` where the attribute `pgn` has an identical value the attribute `requestable` shall also have an identical value.

]

[constr_3211] `PduTriggerings` with `triggerIPduSendCondition`

Imposition time: IT_SysDesc

[Only `PduTriggerings` with references to `ISignalIPdus` are allowed to contain a `triggerIPduSendCondition`.

]

[constr_3212] Limitation of `DoIpTpConnection.tpSdu`

Imposition time: IT_SysDesc

[`DoIpTpConnection` shall only reference `PduTriggerings` of `DcmIPdus` or `UserDefinedIPdus` in the role `tpSdu`.

]

[constr_3213] TransformationISignalProps.csErrorReaction setting in case that the serializer transformerClass and Client/Server communication is used

Imposition time: IT_SysDesc

[In TransformationISignalProps the attribute csErrorReaction shall be set if the TransformationISignalProps specifies the details for a TransformationTechnology with transformerClass equal to serializer and the ISignal that aggregates the TransformationISignalProps transports a client/server communication.

]

[constr_3214] TransformationISignalProps.csErrorReaction setting in case that a transformerClass different from serializer is used or the Client/Server communication is not used

Imposition time: IT_SysDesc

[In TransformationISignalProps the attribute csErrorReaction shall not be used if the TransformationISignalProps specifies the details for a TransformationTechnology with transformerClass not equal to serializer or the ISignal that aggregates the TransformationISignalProps does not transport a client/server communication.

]

[constr_3215] TransformationTechnology.version and TransformationTechnology.protocol settings for request and response of a client/server communication

Imposition time: IT_SysDesc

[TransformationTechnology.version and TransformationTechnology.protocol shall be identical for ISignals that are derived from the same ClientServerOperation. This means that all ISignals that refer to ClientServerToSignalMapping.callSignal or to ClientServerToSignalMapping.returnSignal of the same ClientServerToSignalMapping shall have the same TransformationTechnology.protocol and TransformationTechnology.version defined.

]

[constr_3218] Range of Size of Array Length Fields

Imposition time: IT_SysDesc

[The value of attribute sizeOfArrayLengthFields of SOMEIPTransformationISignalProps shall be either 0, 1, 2 or 4.

]

[constr_3219] The mutual existence of `LinSlaves` in the `LinMaster EcuExtract`

Imposition time: IT_EcuExt

[`LinSlaves` shall not be part of the `EcuExtract` of the corresponding `LinMaster`.

]

[constr_3220] Range of Size of Structure Length Fields

Imposition time: IT_SysDesc

[The value of attribute `sizeofStructLengthFields` of `SOMEIPTransformationISignalProps` shall be either 0, 1, 2 or 4.

]

[constr_3221] Range of Size of Union Length Fields

Imposition time: IT_SysDesc

[The value of attribute `sizeofUnionLengthFields` of `SOMEIPTransformationISignalProps` shall be either 0, 1, 2 or 4.

]

[constr_3222] No `ByteOrderEnum.opaque` allowed for `PduToFrameMapping.packingByteOrder`

Imposition time: IT_SysDesc

[The values of `PduToFrameMapping.packingByteOrder` are restricted to `ByteOrderEnum.mostSignificantByteFirst` and `ByteOrderEnum.mostSignificantByteLast`. I.e. the value `ByteOrderEnum.opaque` is not allowed.

]

[constr_3223] No `ByteOrderEnum.opaque` allowed for `MultiplexedIPdu.selectorFieldByteOrder`

Imposition time: IT_SysDesc

[The values of `MultiplexedIPdu.selectorFieldByteOrder` are restricted to `ByteOrderEnum.mostSignificantByteFirst` and `ByteOrderEnum.mostSignificantByteLast`. I.e. the value `ByteOrderEnum.opaque` is not allowed.

]

[constr_3224] No ByteOrderEnum.opaque allowed for SegmentPosition.segmentByteOrder.

Imposition time: IT_SysDesc

[The values of `SegmentPosition.segmentByteOrder` are restricted to `ByteOrderEnum.mostSignificantByteFirst` and `ByteOrderEnum.mostSignificantByteLast`. I.e. the value `ByteOrderEnum.opaque` is not allowed.

]

[constr_3225] LinFrameTriggering.linChecksum not allowed for LinSpodicFrames

Imposition time: IT_SysDesc

[The `linChecksum` attribute of a `LinFrameTriggering` that references a `LinSpodicFrame` shall not be set.

]

[constr_3226] LinFrameTriggering.linChecksum for LinEventTriggeredFrames

Imposition time: IT_SysDesc

[Within a `PhysicalChannel` the `linChecksum` attribute of a `LinFrameTriggering` that references a `LinEventTriggeredFrame` shall have the same value as the `linChecksum` attribute of each `LinFrameTriggering` that references a `LinUnconditionalFrame` that in turn is referenced by that `LinEventTriggeredFrame`.

]

[constr_3227] NmNode.nmPassiveModeEnabled setting

Imposition time: IT_SysDesc

[`NmNode.nmPassiveModeEnabled` shall be set to the same value in all `NmClusters` with the same bus protocol in the scope of one `NmEcu`.

]

[constr_3229] SwComponentPrototype mapped to an ApplicationPartition and EcuInstance

Imposition time: IT_EcuExt

[If the `SwcToEcuMapping.ecuInstance` exists then a `SwComponentPrototype` that is mapped to an `ApplicationPartition` via the `SwcToApplicationPartitionMapping` shall only be mapped by an `ApplicationPartitionToEcuPartitionMapping` to an `EcuPartition` that is aggregated by the `EcuInstance` referenced by means of `SwcToEcuMapping.ecuInstance`.

]

[constr_3230] Usage of `SenderRecRecordElementMapping.applicationRecordElement`

Imposition time: IT_EcuExt

[`SenderRecRecordElementMapping.applicationRecordElement` shall only be used if the referenced context element (`VariableDataPrototype` that is referenced by the `SenderReceiverToSignalGroupMapping.dataElement`) is typed by an `ApplicationDataType`.

]

[constr_3231] Usage of `IndexedArrayElement.applicationArrayElement`

Imposition time: IT_EcuExt

[`IndexedArrayElement.applicationArrayElement` shall only be used if the referenced context element (`VariableDataPrototype` that is referenced by the `SenderReceiverToSignalGroupMapping.dataElement`) is typed by an `ApplicationDataType`.

]

[constr_3232] `ApplicationPartition` is allowed to be mapped to only one `EcuPartition`

Imposition time: IT_EcuExt

[Each `ApplicationPartition` shall be mapped at most once to an `EcuPartition` via the `ApplicationPartitionToEcuPartitionMapping`.

]

[constr_3239] Consistent mapping of software-component to `J1939NmNode`

Imposition time: IT_SysDesc

[The value of attribute `J1939NmNode.nodeName.function` of a `J1939NmNode` referenced by `J1939ControllerApplicationToJ1939NmNodeMapping` in the role `j1939NmNode` shall be identical to the value of `J1939ControllerApplication.functionId`.

]

[constr_3240] Consistent mapping of `J1939ControllerApplication` to `EcuInstance`

Imposition time: IT_SysDesc

[A `SwComponentPrototype` that is referenced by a `J1939ControllerApplication` mapped to a specific `J1939NmNode` shall only be mapped to an `EcuInstance` that in turn owns the same `J1939NmNode`.

]

[constr_3243] FrameTriggering.pduTriggering condition

Imposition time: IT_SysDesc

[A `FrameTriggering` shall reference a `PduTriggering` if the `PduTriggering` references a `Pdu` that is referenced by a `PduToFrameMapping` which in turn is aggregated by the `Frame` that is referenced by that `FrameTriggering`.

]

[constr_3244] Usage of `SenderRecRecordElementMapping.implementationRecordElement`

Imposition time: IT_EcuExt

[`SenderRecRecordElementMapping.implementationRecordElement` shall only be used if the referenced context element (`VariableDataPrototype` that is referenced by the `SenderReceiverToSignalGroupMapping.dataElement`) is typed by an `ImplementationDataType`.

]

[constr_3245] Usage of `IndexedArrayElement.implementationArrayElement`

Imposition time: IT_EcuExt

[`IndexedArrayElement.implementationArrayElement` shall only be used if the referenced context element (`VariableDataPrototype` that is referenced by the `SenderReceiverToSignalGroupMapping.dataElement`) is typed by an `ImplementationDataType`.

]

[constr_3246] `Frame.packingByteOrder` mix within a `Frame` is not allowed

Imposition time: IT_SysDesc

[All `PduToFrameMappings` within a `Frame` shall have the same `packingByteOrder` value.

]

[constr_3247] Byte order mix within a `MultiplexedIPdu` is not allowed

Imposition time: IT_SysDesc

[The `segmentByteOrder` of all `SegmentPositions` and the `selectorFieldByteOrder` shall have the same value in the `MultiplexedIPdu`.

]

[constr_3248] Category of HwElement for ECUMapping

Imposition time: IT_SysDesc

[The HwElement which is referenced from ECUMapping in the role ecu shall be of category MicroController

]

[constr_3249] Category of HwElement for SwcToEcuMapping

Imposition time: IT_EcuExt

[The HwElement which is referenced from SwcToEcuMapping in the role processingUnit shall be of category "ProcessingUnit".

]

[constr_3250] PduTriggering.iSignalTriggering condition

Imposition time: IT_SysDesc

[A PduTriggering shall reference an ISignalTriggering if the ISignalTriggering references an ISignal or an ISignalGroup that is referenced by an ISignalToIPduMapping which in turn is aggregated by the Pdu that is referenced by that PduTriggering.

]

[constr_3252] ISignalTriggering.iSignalPort reference condition

Imposition time: IT_SysDesc

[An ISignalTriggering shall only reference an ISignalPort if the CommunicationConnector aggregating that ISignalPort is referenced by the PhysicalChannel which in turn aggregates that ISignalTriggering.

]

[constr_3253] PduTriggering.iPduPort reference condition

Imposition time: IT_SysDesc

[A PduTriggering shall only reference an IPduPort if the CommunicationConnector aggregating that IPduPort is referenced by the PhysicalChannel which in turn aggregates that PduTriggering.

]

[constr_3254] FrameTriggering.framePort reference condition

Imposition time: IT_SysDesc

[A `FrameTriggering` shall only reference a `FramePort` if the `CommunicationConnector` aggregating that `FramePort` is referenced by the `PhysicalChannel` which in turn aggregates that `FrameTriggering`.

]

[constr_3255] FrameTriggering.pduTriggering reference condition with regard to the PhysicalChannel

Imposition time: IT_SysDesc

[A `FrameTriggering` shall only reference a `PduTriggering` in the role `pduTriggering` if both the `FrameTriggering` and `PduTriggering` are aggregated by the same `PhysicalChannel`.

]

[constr_3256] PduTriggering.iSignalTriggering reference condition with regard to the PhysicalChannel

Imposition time: IT_SysDesc

[A `PduTriggering` shall only reference an `ISignalTriggering` in the role `iSignalTriggering` if both the `PduTriggering` and `ISignalTriggering` are aggregated by the same `PhysicalChannel`.

]

[constr_3257] TimeSyncTechnology of servers and clients in a time synchronized network.

Status: OBSOLETE

Imposition time: IT_SysDesc

[`TimeSyncClientConfiguration.timeSyncTechnology` shall have the same value as the `TimeSyncServerConfiguration.timeSyncTechnology` that is referenced in the `TimeSyncClientConfiguration.orderedMaster` list.

]

[constr_3258] Restriction on ISignal.length in case iSignalType is set to array

Imposition time: IT_SysDesc

[If `ISignal.iSignalType` is set to `array` then `ISignal.length` shall be a multiple of 8.

]

[constr_3261] GlobalTimeDomain.pduTriggering category

Imposition time: IT_SysDesc

[The `Pdu` that is referenced by the `PduTriggering` that in turn is referenced by `GlobalTimeDomain` in the role `pduTriggering` shall be a `GeneralPurposePdu` of category `GLOBAL_TIME`.

]

[constr_3262] ConsumedEventGroup.eventGroupIdentifier is mandatory

Imposition time: IT_SysDesc

[The `ConsumedEventGroup.eventGroupIdentifier` is mandatory.

]

[constr_3263] Restriction of usage of SwcToEcuMapping in a System

Imposition time: IT_SysDesc

[For all `SwcToEcuMappings` in a `System` the following restriction applies: No two `SwcToEcuMappings` shall have the exact same reference to

- `SwComponentPrototype`
- `EcuInstance`
- `processingUnit`
- `controlledHwElement`

]

[constr_3264] Server side ClientServerToSignalMappings in case of a n:1 inter-ECU client-server communication

Imposition time: IT_SysDesc

[If within the `System` with `category` `SYSTEM_DESCRIPTION` or `SYSTEM_EXTRACT` the `ClientServerToSignalMappings` for inter-ECU n:1 client-server communication are placed on the provider (server) side, then each of these `ClientServerToSignalMappings` shall (in the hierarchy of `SwComponentPrototypes`) refer to a "unique communication path" w.r.t. the `EcuInstances` the client `SwComponentPrototypes` are mapped to.

]

[constr_3265] TransformationTechnology.hasInternalState setting for an E2E transformer

Imposition time: IT_SysDesc

[The value of `hasInternalState` shall be set to true for a `TransformationTechnology` with `transformerClass` set to `safety`.

]

[constr_3266] TransformationTechnology.hasInternalState setting for a SOME/IP Transformer

Imposition time: IT_SysDesc

[The value of `hasInternalState` shall be set to true for a SOME/IP Transformer if the `ISignal` that is referencing this transformer is mapped into an `ISignalIPdu` and this `ISignalIPdu` is referenced by a `PduTriggering` that in turn is referenced by a `SomeipTpConnection` in the role `tpSdu`.

]

[constr_3267] PduTriggerings in Service Discovery StaticSocketConnections

Imposition time: IT_SysDesc

[SD `StaticSocketConnections` defined according to [TPS_SYST_02414] and [TPS_SYST_02415] shall only refer to `PduTriggerings` which point to `GeneralPurposePdus` of category SD.

]

[constr_3268] Service Discovery StaticSocketConnection aggregation by a SocketAddress

Imposition time: IT_SysDesc

[Each SD `StaticSocketConnection` defined according to [TPS_SYST_02414] and [TPS_SYST_02415] shall be aggregated by a `SocketAddress` that in turn aggregates an `ApplicationEndpoint` that defines a Udp Port.

]

[constr_3269] Service Discovery StaticSocketConnection remoteAddress reference to a TpPort

Imposition time: IT_SysDesc

[Each SD `StaticSocketConnection` defined according to [TPS_SYST_02414] and [TPS_SYST_02415] shall refer with the `remoteAddress` reference to an `ApplicationEndpoint` with Udp Port `portNumber` set to 0. This means that any remote

port number is accepted for receiving and for sending, i.e., that the remote port number is configured at runtime.

]

[constr_3270] Service Discovery `SocketConnection` `remoteAddress` reference to an IP Address

Imposition time: IT_SysDesc

[Each SD `StaticSocketConnection` defined according to [TPS_SYST_02414] and [TPS_SYST_02415] shall refer with the `remoteAddress` reference to an `ApplicationEndpoint` that points to a `NetworkEndpoint` that defines an IP Address ANY (IPv4 or IPv6). This means that any remote IP address is accepted for receiving and for sending, i.e., that the remote IP address is configured at runtime.

]

[constr_3272] `SoConIPduIdentifier.headerId` setting for SD `StaticSocketConnections`

Imposition time: IT_SysDesc

[The `SoConIPduIdentifier.headerId` of SD `StaticSocketConnections` defined in [TPS_SYST_02414] and [TPS_SYST_02415] shall always be set to 0x FFFF8100 for SD messages.

]

[constr_3273] Service Discovery multicast `StaticSocketConnection`'s aggregation by an `ApplicationEndpoint`

Imposition time: IT_SysDesc

[The SD `StaticSocketConnection` for multicast defined in [TPS_SYST_02415] shall be aggregated by an `ApplicationEndpoint` that points to a `NetworkEndpoint` that defines an IP Multicast Address.

]

[constr_3274] Service Discovery unicast `StaticSocketConnection`'s aggregation by an `ApplicationEndpoint`

Imposition time: IT_SysDesc

[The SD `StaticSocketConnection` for unicast defined in [TPS_SYST_02414] shall be aggregated by an `ApplicationEndpoint` that points to a `NetworkEndpoint` that defines an IP Unicast Address.

]

[constr_3276] Prohibition of usage of `allowedIPv6ExtHeaders` in IPv4 `SocketAddress`

Imposition time: IT_SysDesc

[IPv4 `SocketAddress` shall not define `allowedIPv6ExtHeaders`. An IPv4 `SocketAddress` aggregates an `ApplicationEndpoint` that refers to a `NetworkEndpoint` that has an `Ipv4Configuration` as `networkEndpointAddress`.

]

[constr_3277] Restriction of usage of `IPv6ExtHeaderFilterLists` in IPv6 `SocketAddress`

Imposition time: IT_SysDesc

[All `SocketAddresses` related to the same IPv6 `NetworkEndpoint` shall all reference either no or exactly the same `IPv6ExtHeaderFilterList` with the `allowedIPv6ExtHeaders` attribute.

]

[constr_3278] Usage of `SOMEIPTransformationProps.sizeOfArrayLengthField`

Imposition time: IT_SysDesc

[The attribute `sizeOfArrayLengthField` of `SOMEIPTransformationProps` shall only be defined if the `DataPrototypeTransformationProps` is defined for a static size array according to [TPS_SYST_02121].

]

[constr_3279] Usage of `SOMEIPTransformationProps.sizeOfStructLengthField`

Imposition time: IT_SysDesc

[The attribute `sizeOfStructLengthField` of `SOMEIPTransformationProps` shall only be defined if the `DataPrototypeTransformationProps` is defined for a structure according to [TPS_SYST_02121].

]

[constr_3280] Usage of `SOMEIPTransformationProps.sizeOfUnionLengthField`

Imposition time: IT_SysDesc

[The attribute `sizeOfUnionLengthField` of `SOMEIPTransformationProps` shall only be defined if the `DataPrototypeTransformationProps` is defined for a union according to [TPS_SYST_02121].

]

[constr_3281] Usage of `SOMEIPTransformationProps.alignment`

Imposition time: IT_SysDesc

[The attribute `alignment` of `SOMEIPTransformationProps` shall only be defined if the `DataPrototypeTransformationProps` is defined for a variable data length data element according to [TPS_SYST_02121].

]

[constr_3282] SOME/IP Transformation settings for arrays in the context of an `ISignal`

Imposition time: IT_SysDesc

[In the context of an `ISignal` the usage of `DataPrototypeTransformationProps.transformationProps.sizeOfArrayLengthField` is only allowed if the `SOMEIPTransformationISignalProps.sizeOfArrayLengthFields` is not defined.

]

[constr_3283] SOME/IP Transformation settings for structures in the context of an `ISignal`

Imposition time: IT_SysDesc

[In the context of an `ISignal` the usage of `DataPrototypeTransformationProps.transformationProps.sizeOfStructLengthField` is only allowed if the `SOMEIPTransformationISignalProps.sizeOfStructLengthFields` is not defined.

]

[constr_3284] SOME/IP Transformation settings for unions in the context of an `ISignal`

Imposition time: IT_SysDesc

[In the context of an `ISignal` the usage of `DataPrototypeTransformationProps.transformationProps.sizeOfUnionLengthField` is only allowed if the `SOMEIPTransformationISignalProps.sizeOfUnionLengthFields` is not defined.

]

[constr_3285] Alignment of variable data length data elements in the context of an ISignal

Imposition time: IT_SysDesc

[The definition of `DataPrototypeTransformationProps.transformationProps.alignment` is only allowed if the `SOMEIPTransformationDescription.alignment` is not defined.

]

[constr_3297] Prohibition of usage of `allowedTcpOptions` in Udp `SocketAddress`

Imposition time: IT_SysDesc

[Udp `SocketAddress` shall not define `allowedTcpOptions`. A Udp `SocketAddress` aggregates an `ApplicationEndpoint` that has a `UdpTp` defined as `tpConfiguration`.

]

[constr_3298] `Ipv6Configuration.ipv6Address` range in case of `enableAnycast`

Imposition time: IT_SysDesc

[If `Ipv6Configuration.enableAnycast` is set to true then the `Ipv6Configuration.ipv6Address` needs to be in the unicast addressing range.

]

[constr_3299] `SocketAddress.pathMtuDiscoveryEnabled` setting dependency

Imposition time: IT_SysDesc

[`SocketAddress.pathMtuDiscoveryEnabled` shall only be set to TRUE if `EthernetCommunicationConnector.pathMtuEnabled` == TRUE.

]

[constr_3311] Usage of `SocketAddress.flowLabel`

Imposition time: IT_SysDesc

[`SocketAddress.flowLabel` shall only be used if the aggregated `ApplicationEndpoint` refers to a `NetworkEndpoint` with an `Ipv6Configuration`.

]

[constr_3312] Consistency of `vlanPriority` and `EthernetCommunicationConnector`

Imposition time: IT_SysDesc

[A `GlobalTimeEthMaster` refers to an `EthernetCommunicationConnector` in the role `communicationConnector`. If that `EthernetCommunicationConnector` is referenced by an `EthernetPhysicalChannel` in the role `commConnector` and the `EthernetPhysicalChannel` has a `vLan` tag defined via the `VlanConfig` then the `GlobalTimeDomain` of the `GlobalTimeEthMaster` shall aggregate `EthGlobalTimeDomainProps` in the role `globalTimeDomainProperty` and the attribute `EthGlobalTimeDomainProps.vlanPriority` shall exist.

]

[constr_3313] E2E transformer configuration

Imposition time: IT_SysDesc

[For each `TransformationDescription` variant that is a `EndToEndTransformationDescription`

- attribute `protocol` of `TransformationTechnology` shall be set to `E2E`
- attribute `version` of `TransformationTechnology` shall be set to `1.0.0`
- attribute `transformerClass` of `TransformationTechnology` shall be set to `safety`

]

[constr_3316] Allowed values for `EndToEndTransformationDescription.maxDeltaCounter` in `PROFILE_07`, `PROFILE_08`, `PROFILE_07m` and `PROFILE_08m`

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of `PROFILE_07`, `PROFILE_08`, `PROFILE_07m`, or `PROFILE_08m` the value of `maxDeltaCounter` attribute shall be in the range 1-4'294'967'295.

]

[constr_3317] Assuring the same data interpretation on the sender and receiver sides in case of serialization based on the `ImplementationDataTypes`

Imposition time: IT_SysDesc

[In order to assure the same interpretation of the serialized data by the SOME/IP transformers on the sender and receiver sides in case of serialization based on either a primitive or a composite `ImplementationDataType`, the same `SwBaseType` shall be defined

- for this primitive `DataPrototype` or

- for each primitive `DataPrototype` of the leaf elements of the composite `DataPrototype` starting from the first element until and including the last element that is requested by the receiver,

by the `ImplementationDataTypes` that either types the corresponding `PortPrototypes` on the top level Software Composition of the communicating `EcuInstances`, or it is mapped to the `ApplicationDataType` that types it.

]

[constr_3318] Allowed use of `ISignal.networkRepresentationProps`

Imposition time: IT_SysDesc

[If a reference from `ISignal` to `DataTransformation` in the role `dataTransformation` exists, this `ISignal` SHALL NOT aggregate `SwDataDefProps` in the role `networkRepresentationProps`.

]

[constr_3319] Existence of `DataPrototypeTransformationProps.networkRepresentationProps`

Imposition time: IT_SysDesc

[`ISignal.transformationISignalProps.dataPrototypeTransformationProps.networkRepresentationProps` shall either

- not exist at all or
- shall be defined for all leaf elements of the root `DataPrototype` transmitted in the `ISignal`

]

[constr_3322] Consistent setting of `SoConIPduIdentifier.pduCollectionSemantics` in the context of one `SocketAddress`

Imposition time: IT_SysDesc

[The value of the attribute `SoConIPduIdentifier.pduCollectionSemantics` shall be identical for all referenced `SoConIPduIdentifiers` within the context of a given `SocketAddress`.

]

[constr_3323] Relation between `NmCluster.nmPncParticipation` and `PncMapping.pncGroup`

Imposition time: IT_SysDesc

[If a `PncMapping` references an `ISignalIPduGroup` in role `pncGroup` which in turn

- contains (either directly or via one of its subordinate `ISignalIPduGroups` referenced in role `containedISignalIPduGroup`) `ISignalIPdus` that are referenced by a `PduTriggering` in role `iPdu` which in turn
- is composed by a `PhysicalChannel` in role `pduTriggering` which in turn
- is composed by `CommunicationCluster` in role `physicalChannel` which in turn
- is referenced by an `NmCluster` in role `communicationCluster`,

then this `NmCluster` shall have its `nmPncParticipation` attribute set to TRUE unless the `PhysicalChannel` is referenced in the role `managedPhysicalChannel`.

]

[constr_3324] Category of `SecureCommunicationFreshnessProps` and `SecureCommunicationAuthenticationProps`

Imposition time: IT_SysDesc

[`SecureCommunicationFreshnessProps` that is referenced by a `SecuredIPdu` in the role `freshnessProps` shall have the same `category` value as the `SecureCommunicationAuthenticationProps` that is referenced by the same `SecuredIPdu` in the role `authenticationProps`.

]

[constr_3325] `SecureCommunicationFreshnessProps`, `SecureCommunicationAuthenticationProps` and `CryptoServicePrimitive` attribute value settings for standardized AUTOSAR security profiles

Imposition time: IT_SysDesc

[

Attributes	PROFILE_01	PROFILE_02	PROFILE_03
<code>algorithmFamily</code>	CRYPTO_ALGOFAM_AES	CRYPTO_ALGOFAM_AES	CRYPTO_ALGOFAM_AES
<code>algorithmMode</code>	CRYPTO_ALGOMODE_CM CMAC	CRYPTO_ALGOMODE_CM CMAC	CRYPTO_ALGOMODE_CM CMAC
<code>length</code>	128 bits	128 bits	128 bits
<code>authInfoTxLength</code>	24 bits	24 bits	28 bits
<code>freshnessValueLength</code>	Not specified	0 bits	64 bits
<code>freshnessValueTxLength</code>	8 bits	0 bits	4 bits

]

[constr_3326] Allowed values for `EndToEndTransformationDescription.dataIdMode` in PROFILE_11

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_11 then the value of the `EndToEndTransformationDescription.dataIdMode` attribute shall be set to `all16Bit` or `lower12Bit`.

]

[constr_3327] Effect of `EndToEndTransformationDescription.upperHeaderBitsToShift` value in PROFILE_22

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute has a value of PROFILE_22 and the serializing transformer is different than the ComBased Transformer, then `EndToEndTransformationDescription.offset` shall be set to the same value of `upperHeaderBitsToShift`.

]

[constr_3328] `SomeipTpConnection.transportPdu` reference restriction

Imposition time: IT_SysDesc

[A `PduTriggering` that is referenced by a `SomeipTpConnection` in the role `transportPdu` shall reference a `GeneralPurposeIPdu` with category SOMEIP_SEGMENTED_IPDU in the role `iPdu`.

]

[constr_3329] `SomeipTpConnection.tpSdu` reference restriction

Imposition time: IT_SysDesc

[A `PduTriggering` that is referenced by a `SomeipTpConnection` in the role `tpSdu` shall reference an `IPdu` in the role `iPdu`.

]

[constr_3330] Same `transportPdu` shall not be used in different `SomeipTpConnections`

Imposition time: IT_SysDesc

[A `PduTriggering` that is referencing a `GeneralPurposeIPdu` with category SOMEIP_SEGMENTED_IPDU in the role `iPdu` shall be referenced at most once by a `SomeipTpConnection` in the role `transportPdu`.

]

[constr_3331] Standardized values for the attribute `category` of meta-class `EthernetCommunicationConnector`

Imposition time: IT_SysDesc

[The following values of the attribute `category` of meta-class `EthernetCommunicationConnector` are reserved by the AUTOSAR standard:

- WIRED: This represents the usage of the `EthernetCommunicationConnector` in case of a wired ethernet connection
- WIRELESS: This represents the usage of the `EthernetCommunicationConnector` in case of a wireless ethernet connection
- CAN_XL: This represents the tunneling of Ethernet frames handled by the `EthernetCommunicationConnector` through CAN XL.

]

[constr_3332] Standardized values for the attribute `category` of meta-class `EthernetCommunicationController`

Imposition time: IT_SysDesc

[The following values of the attribute `category` of meta-class `EthernetCommunicationController` are reserved by the AUTOSAR standard:

- WIRED: This represents the usage of the `EthernetCommunicationController` in case of a wired ethernet connection
- WIRELESS: This represents the usage of the `EthernetCommunicationController` in case of a wireless ethernet connection
- CAN_XL: This represents the tunneling of Ethernet frames handled by the `EthernetCommunicationController` through CAN XL.

]

[constr_3333] Standardized values for the attribute `category` of meta-class `EthernetPhysicalChannel`

Imposition time: IT_SysDesc

[The following values of the attribute `category` of meta-class `EthernetPhysicalChannel` are reserved by the AUTOSAR standard:

- WIRED: This represents the usage of the `EthernetPhysicalChannel` in case of a wired ethernet connection
- WIRELESS: This represents the usage of the `EthernetPhysicalChannel` in case of a wireless ethernet connection

]

[constr_3334] Allowed references between EthernetPhysicalChannel and EthernetCommunicationConnector

Imposition time: IT_SysDesc

[An EthernetPhysicalChannel is only allowed to reference EthernetCommunicationConnectors in the role commConnector that have the same category value as the referencing EthernetPhysicalChannel.

]

[constr_3335] Allowed references between EthernetCommunicationConnector and EthernetCommunicationController

Imposition time: IT_SysDesc

[An EthernetCommunicationConnector is only allowed to reference an EthernetCommunicationController in the role commController that has the same category value as the referencing EthernetCommunicationConnector.

]

[constr_3336] EthernetPhysicalChannel.soAdConfig in case of WIRELESS EthernetPhysicalChannel

Imposition time: IT_SysDesc

[If EthernetPhysicalChannel has the category WIRELESS then the EthernetPhysicalChannel shall not aggregate the SoAdConfig.

]

[constr_3337] IPduPort.useAuthDataFreshness is configurable on the receiver side

Imposition time: IT_SysDesc

[The IPduPort.useAuthDataFreshness attribute shall only be used in IPduPorts with the communicationDirection = in.

]

[constr_3338] IPduPort.useAuthDataFreshness validness

Imposition time: IT_SysDesc

[The IPduPort.useAuthDataFreshness information is only valid for SecuredIPdus.

]

[constr_3339] Relation between `authDataFreshnessStartPosition`, `authDataFreshnessLength` and `useAuthDataFreshness`

Imposition time: IT_SysDesc

[If `authDataFreshnessStartPosition` and `authDataFreshnessLength` are set to a value for a `SecuredIPdu` then the `useAuthDataFreshness` shall be set as well to a value on all `IPduPorts` with `communicationDirection` = in that are referenced by a `PduTriggering` of the `SecuredIPdu`.

]

[constr_3364] `headerLength` shall be a multiple of 8

Imposition time: IT_SysDesc

[The header length in bits specified by `headerLength` shall be a multiple of 8.

]

[constr_3365] `EthernetPhysicalChannels` with different `category` values are not allowed within an `EthernetCluster`

Imposition time: IT_SysDesc

[A mix of `EthernetPhysicalChannels` with different `category` values within an `EthernetCluster` is currently not supported by AUTOSAR.

]

[constr_3373] Limitation on the number of `PhysicalChannels` that are referencing a `CommunicationConnector`

Imposition time: IT_SysDesc

[A `CommunicationConnector` shall only be referenced by at most one `PhysicalChannel`.

]

[constr_3378] Maximal one `AliasNameAssignment` allowed per `FlatInstanceDescriptor`

Imposition time: IT_EcuExt

[In a given instance of `AliasNameSet` in the bound system there shall be at most one `aliasName` per `FlatInstanceDescriptor`.

]

[constr_3379] Multiple `SocketAddress` entries with the same IP Address, Protocol and Port in the context of a given `EcuInstance`

Imposition time: IT_SysDesc

[If there are two or more `SocketAddress` entities within the scope of one `SoAdConfig` in the scope of one `EcuInstance` that have the same static (fixed at configuration time) IP Address, Protocol and Port in the aggregated `ApplicationEndpoint` and `NetworkEndpoint`, (e.g., 192.168.1.1, Tcp and 10000, respectively) then only one of these `SocketAddress` elements shall be referenced by `ProvidedServiceInstances/ConsumedServiceInstances` in the role `localUnicastAddress`.

]

[constr_3383] Standardized values for the attribute `category` of meta-class `GeneralPurposeConnection`

Imposition time: IT_SysDesc

[The following values of the attribute `category` of meta-class `GeneralPurposeConnection` are reserved by the AUTOSAR standard:

- `XcpChannel`

]

[constr_3384] `PduTriggerings` referenced by `GeneralPurposeConnection` shall be defined on the same `PhysicalChannel`

Imposition time: IT_SysDesc

[The `PduTriggerings` that are referenced by the `GeneralPurposeConnection` in the role `pduTriggering` shall be defined on the same `PhysicalChannel`.

]

[constr_3385] `XcpChannel` is allowed to reference exactly two `PduTriggerings`

Imposition time: IT_SysDesc

[In case that the `category` of meta-class `GeneralPurposeConnection` is set to the value `XcpChannel` the `GeneralPurposeConnection` is allowed to reference exactly two `PduTriggerings` in the role `pduTriggering`.

]

[constr_3386] XcpChannel is only allowed to reference PduTriggerings of GeneralPurposeIPdus with category XCP

Imposition time: IT_SysDesc

[In case that the `category` of meta-class `GeneralPurposeConnection` is set to the value `XcpChannel` the `GeneralPurposeConnection` is allowed to reference `PduTriggerings` of `GeneralPurposeIPdus` with category XCP.

]

[constr_3399] Existence of `securedAreaOffset` and `securedAreaLength`

Imposition time: IT_SysDesc

[If the `securedAreaOffset` is defined then the `securedAreaLength` shall be defined as well and vice versa.

]

[constr_3402] Mandatory `offset` if `noHeader` is used

Imposition time: IT_SysDesc

[For each `IPdu` which is assigned to a `ContainerIPdu` in the role `ContainerIPdu.containedPduTriggering` or `ContainerIPdu.containedIPduTriggeringProps.containedPduTriggering` with `ContainerIPdu.headerType = noHeader` the `ContainedIPduProps.offset` shall be defined.

]

[constr_3403] Usage of `ContainerIPdu.rxAcceptContainedIPdu` if `noHeader` is used

Imposition time: IT_SysDesc

[If the `ContainerIPdu.headerType` is set to `noHeader` then the `ContainerIPdu.rxAcceptContainedIPdu` attribute value shall be set to `acceptConfigured`.

]

[constr_3404] Usage of `ContainedIPduProps.updateIndicationBitPosition`

Imposition time: IT_SysDesc

[`ContainedIPduProps.updateIndicationBitPosition` is only allowed to be set to a value if the `headerType` of the `ContainerIPdu` that contains the `IPdu` with `ContainerIPdu.containedPduTriggering` or `ContainerIPdu.containedIPduTriggeringProps.containedPduTriggering` is set to `noHeader`.

]

[constr_3405] Dynamic Length IPdu inside of a static configured Container-IPdu

Imposition time: IT_SysDesc

[Only the last contained IPdu (according to the `ContainedIPduProps.offset`) of a `ContainerIPdu` with static container layout (i.e., a `ContainerIPdu` with `headerType` set to `noHeader`) is allowed to be a dynamic length IPdu (i.e, a contained IPdu that at runtime may exhibit a length different from the one statically configured via `Pdu.length` of the respective `Pdu`). All other contained IPdus of a `ContainerIPdu` with static container layout have to be static length IPdus.

]

[constr_3406] All signals before `authDataFreshnessStartPosition` shall have a static length

Imposition time: IT_SysDesc

[In case that

- an `ISignalIPdu` is referenced by the `SecuredIPdu` with the `payload` reference via the `PduTriggering` and
- the `authDataFreshnessStartPosition` and `authDataFreshnessLength` define the area in the `ISignalIPdu` that is taken to verify and generate the Freshness then

all `ISignals` that are mapped into the `ISignalIPdu` in front of the configured `authDataFreshnessStartPosition` shall have a static length.

]

[constr_3407] Freshness Value in Authentic IPdu is not allowed to be used in case of `ContainerIPdu` with a dynamic layout

Imposition time: IT_SysDesc

[If a `ContainerIPdu` that is referenced by the `SecuredIPdu` with the `payload` reference via the `PduTriggering` contains a dynamic layout (i.e. `ContainerIPdu.headerType` is set to `longHeader` or `shortHeader`) and multiple contained IPdus then each `IPduPort` that is referenced by the `PduTriggering` of the `SecuredIPdu` shall have the attribute `useAuthDataFreshness` set to `false`.

]

[constr_3435] Applicability of `CouplingPort.macMulticastAddress`

Imposition time: IT_SysDesc

[The reference `CouplingPort.macMulticastAddress` is only applicable if the `CouplingPort` is aggregated by a `CouplingElement` with `couplingType = switch`.

]

[constr_3436] Value range of `minimumTxContainerQueueSize` and `minimumRxContainerQueueSize`

Imposition time: IT_SysDesc

[If defined, the value of `minimumTxContainerQueueSize` and `minimumRxContainerQueueSize` shall be in the range of 0..255.

]

[constr_3437] `invalidValue` defined in the context of `ISignal`

Imposition time: IT_SysDesc

[The definition of `SwDataDefProps.invalidValue` aggregated by an `ISignal` in the role `networkRepresentationProps` shall only be a `NumericalValueSpecification`, `TextValueSpecification` or `ArrayValueSpecification` that aggregates elements of type `NumericalValueSpecification` or `TextValueSpecification`.

]

[constr_3438] `timeoutSubstitutionValue` defined in the context of `ISignal`

Imposition time: IT_SysDesc

[The definition of an `timeoutSubstitutionValue` in the context of an `ISignal` shall only be a `NumericalValueSpecification`, `TextValueSpecification` or `ArrayValueSpecification` that aggregates elements of type `NumericalValueSpecification` or `TextValueSpecification`.

]

[constr_3448] Restriction for usage of `Pdu.hasDynamicLength`

Imposition time: IT_SysDesc

[The `Pdu.hasDynamicLength` attribute is only relevant for `UserDefinedPdu`, `UserDefinedIPdu`, `J1939DcmIPdu`.

]

[constr_3454] Unique headerIdLongHeader for acceptConfigured

Imposition time: IT_SysDesc

[For a ContainerIPdu with ContainerIPdu.rxAcceptContainedIPdu = RxAcceptContainedIPduEnum.acceptConfigured and ContainerIPdu.headerType = longHeader the following shall apply: All referenced IPdus (via ContainerIPdu.containedPduTriggering or ContainerIPdu.containedIPduTriggeringProps.containedPduTriggering) shall have a unique ContainedIPduProps.headerIdLongHeader within the scope of this ContainerIPdu.

]

[constr_3455] Unique headerIdShortHeader for acceptConfigured

Imposition time: IT_SysDesc

[For a ContainerIPdu with ContainerIPdu.rxAcceptContainedIPdu = RxAcceptContainedIPduEnum.acceptConfigured and ContainerIPdu.headerType = shortHeader the following shall apply: All referenced IPdus (via ContainerIPdu.containedPduTriggering or ContainerIPdu.containedIPduTriggeringProps.containedPduTriggering) shall have a unique ContainedIPduProps.headerIdShortHeader within the scope of this ContainerIPdu.

]

[constr_3456] Existence of ProvidedServiceInstance.loadBalancingPriority and ProvidedServiceInstance.loadBalancingWeight

Imposition time: IT_SysDesc

[The attributes ProvidedServiceInstance.loadBalancingPriority and ProvidedServiceInstance.loadBalancingWeight shall either not exist or be defined both.

]

[constr_3457] Uniqueness of ConsumedEventGroup.eventGroupIdentifier in the scope of a ConsumedServiceInstance

Imposition time: IT_SysDesc

[Each ConsumedEventGroup that is aggregated by a ConsumedServiceInstance shall have a unique eventGroupIdentifier value in the scope of the aggregating ConsumedServiceInstance.

]

[constr_3458] FlatInstanceDescriptor.rtePluginProps shall only reference a EcucContainerValue representing a RteRipsPlugin

Imposition time: IT_EcuExt

[FlatInstanceDescriptor.rtePluginProps shall only reference an EcucContainerValue which defines the identity of the RTE Implementation Plug-In. This requires that the according EcucContainerValue's definition references a EcucContainerDef having a destinationUri set to /AUTOSAR/EcucDestinationUriDefSets/RteRipsUriDefSet/RteRipsPlugin

]

[constr_3460] Full definition of transferProperty for group signal

Imposition time: IT_SysDesc

[If at least one of the ISignals belonging to an ISignalGroup has a transferProperty defined (via their respective ISignalToIPduMapping) then all other ISignals belonging to the same ISignalGroup shall have a transferProperty defined as well.

]

[constr_3461] TransferProperty for group signals if ISignalGroup has transferProperty=pending

Imposition time: IT_SysDesc

[If the ISignalToIPduMapping refers to an ISignalGroup in the role iSignalGroup and the transferProperty is set to pending then the group signals of this ISignalGroup shall either

- have no transferProperty defined (via their respective ISignalToIPduMapping) or
- every ISignal belonging to the ISignalGroup shall have the transferProperty=pending defined.

]

[constr_3464] Allowed Pdu type on BusMirrorChannelMapping.targetChannel

Imposition time: IT_SysDesc

[Each PduTriggering that is referenced by BusMirrorChannelMapping in the role targetPduTriggering is only allowed to reference a GeneralPurposeIPdu of category BUS_MIRRORING.

]

[constr_3465] Identical `BusMirrorChannel.busMirrorNetworkId` for `BusMirrorChannels` referencing the same `PhysicalChannel`

Imposition time: IT_SysDesc

[The attribute `BusMirrorChannel.busMirrorNetworkId` shall be identical in all `BusMirrorChannels` that are referencing the same `PhysicalChannel` in the scope of the `System`.

]

[constr_3466] Unique `BusMirrorChannel.busMirrorNetworkIds` for each specialization of `PhysicalChannel`

Imposition time: IT_SysDesc

[The attribute `BusMirrorChannel.busMirrorNetworkId` associated with `PhysicalChannels` that have the same specialization (e.g. all `CanPhysicalChannels`) shall have unique `BusMirrorChannel.busMirrorNetworkIds` within the scope of the `System`).

]

[constr_3467] `CanPhysicalChannel` as destination channel of `BusMirrorChannelMappingCan`

Imposition time: IT_SysDesc

[The `BusMirrorChannel` that is aggregated by `BusMirrorChannelMappingCan` shall only reference a `CanPhysicalChannel` in the role `targetChannel`.

]

[constr_3468] `BusMirrorChannelMappingCan.targetPduTriggering` restriction

Imposition time: IT_SysDesc

[`BusMirrorChannelMappingCan` is allowed to reference only one single `PduTriggering` in the role `targetPduTriggering`.

]

[constr_3469] `CanFrameTriggering.txMask` setting for the destination frame

Imposition time: IT_SysDesc

[The `CanFrameTriggering` of a `Frame` that contains a `Pdu` of which the `PduTriggering` is referenced by `BusMirrorChannelMappingCan` in the role `targetPduTriggering` shall set the `txMask` to 0.

]

[constr_3470] PaddingValue used to transmit the Pdu on a Can-Fd destination bus

Imposition time: IT_SysDesc

[In case that the `BusMirrorChannelMappingCan` references a `PduTriggering` in the role `targetPduTriggering` and

- the `CanFrameTriggering` of the `Frame` that contains this `targetPduTriggering` has the `canFrameTxBehavior` set to `canFd` and
- the `CanFrameTriggering` has a reference to an "out" `FramePort` (i.e. the Frame is transmitted by an Ecu on a Can-Fd destination bus) and
- the `CommunicationController` of the transmitting `EcuInstance` that is referenced via the `CommunicationConnector` by the `PhysicalChannel` on which the `targetPduTriggering` is located then the `CanControllerFdConfiguration.paddingValue` or `CanControllerFdConfigurationRequirements.paddingValue` shall have the value 0.

]

[constr_3471] FlexrayPhysicalChannel as destination channel of BusMirrorChannelMappingFlexray

Imposition time: IT_SysDesc

[The `BusMirrorChannel` that is aggregated by `BusMirrorChannelMappingFlexray` shall only reference a `FlexrayPhysicalChannel` in the role `targetChannel`.

]

[constr_3472] Number of BusMirrorChannels derived for one FlexrayCluster

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, only one `BusMirrorChannel` shall be derived. I.e. if both channels A and B are derived, only one of the two `FlexrayPhysicalChannels` of one `FlexrayCluster` shall be referenced by a `BusMirrorChannel` in the `System`.

]

[constr_3473] BusMirrorChannelMappingFlexray.targetPduTriggering restriction

Imposition time: IT_SysDesc

[The `FlexrayFrameTriggering` of a `Frame` that contains a `Pdu` of which the `PduTriggering` is referenced by `BusMirrorChannelMappingFlexray` in the role

`targetPduTriggering` shall have the `allowDynamicLSduLength` attribute set to true.

]

[constr_3474] `EthernetPhysicalChannel` as destination channel of `BusMirrorChannelMappingIp`

Imposition time: IT_SysDesc

[The `BusMirrorChannel` that is aggregated by `BusMirrorChannelMappingIp` shall only reference an `EthernetPhysicalChannel` in the role `targetChannel`.

]

[constr_3475] `BusMirrorChannelMappingIp.targetPduTriggering` restriction

Imposition time: IT_SysDesc

[`BusMirrorChannelMappingIp` is allowed to reference only one single `PduTriggering` in the role `targetPduTriggering`.

]

[constr_3476] `UserDefinedPhysicalChannel` as destination channel of `BusMirrorChannelMappingUserDefined`

Imposition time: IT_SysDesc

[The `BusMirrorChannel` that is aggregated by `BusMirrorChannelMappingUserDefined` shall only reference a `UserDefinedPhysicalChannel` in the role `targetChannel`.

]

[constr_3477] `BusMirrorChannelMappingUserDefined.targetPduTriggering` restriction

Imposition time: IT_SysDesc

[`BusMirrorChannelMappingUserDefined` is allowed to reference only one single `PduTriggering` in the role `targetPduTriggering`.

]

[constr_3479] `PhysicalChannel` is not allowed to be a `managedPhysicalChannel` and a managing `PhysicalChannel`

Imposition time: IT_SysDesc

[If a `PhysicalChannel` is referenced in role `managedPhysicalChannel`, then it shall not be the source of another `managedPhysicalChannel` relation.

]

[constr_3480] `PhysicalChannel` shall be referenced in the role `managedPhysicalChannel` only once

Imposition time: IT_SysDesc

[A `PhysicalChannel` shall be referenced in the role `managedPhysicalChannel` only up to once.

]

[constr_3481] `UdpNmCluster` is not allowed to reference a `managedPhysicalChannel` in the role `vlan`

Imposition time: IT_SysDesc

[If an `EthernetPhysicalChannel` is target of a `managedPhysicalChannel` reference, then no `UdpNmCluster` shall reference this `managedPhysicalChannel` in the role `vlan`.

]

[constr_3482] `NmCluster` is not allowed to reference a `CommunicationCluster` that aggregates a `managedPhysicalChannel`

Imposition time: IT_SysDesc

[If a `PhysicalChannel`, except `EthernetPhysicalChannel`, is target of a `managedPhysicalChannel`, then the aggregating `CommunicationCluster` shall not be referenced by any `NmCluster` in the role `communicationCluster`.

]

[constr_3484] `PncMapping` that refers a `managedPhysicalChannel` shall also refer the managing `PhysicalChannel`

Imposition time: IT_SysDesc

[If a `PncMapping` refers to a `PhysicalChannel` (either directly in the role `physicalChannel` or indirectly by referencing an `ISignalIPduGroup` in the role `pncGroup`) and this `PhysicalChannel` is referenced in the role `managedPhysicalChannel`, then the according managing `PhysicalChannel` (the source of the `managedPhysicalChannel` reference) shall also be referenced by the `PncMapping`

(either directly in the role `physicalChannel` or indirectly by referencing an `ISignalIPduGroup` in the role `pncGroup`).

]

[constr_3488] Value range of `ContainedIPduProps.priority`

Imposition time: IT_SysDesc

[If defined, the value of `ContainedIPduProps.priority` shall be in the range of 0..255.

]

[constr_3489] `ContainedIPduProps.priority` is only applicable if a `ContainerIPdu` header is used

Imposition time: IT_SysDesc

[`ContainedIPduProps.priority` is only applicable if the `headerType` of the `ContainerIPdu` is set to `shortHeader` or `longHeader`.

]

[constr_3490] `ContainedIPduProps.priority` is only applicable if `collectionSemantics` is set to `lastIsBest`

Imposition time: IT_SysDesc

[`ContainedIPduProps.priority` is only applicable if `ContainedIPduProps.collectionSemantics` is set to `lastIsBest`.

]

[constr_3501] Role of `SystemSignal` in 1:n communication

Imposition time: IT_EcuExt

[In case of 1:n communication the `VariableDataPrototype` in the `PPortPrototype` of the `SwComponentPrototype` shall be mapped to only one `SystemSignal`.

]

[constr_3506] Mapping of composite data type to `SystemSignals` in `SystemSignalGroup`

Imposition time: IT_EcuExt

[Either all or a subset of elements of a composite data type shall be mapped to `SystemSignals` which shall be members of one `SystemSignalGroup` if no data transformation (except COM Based Transformer) is used.

There are two exceptions to this rule:

- it is allowed to map an array `VariableDataPrototype` consisting of `UINT8` elements to exactly one `SystemSignal` in the context of one `SenderReceiverToSignalMapping` (see [TPS_SYST_01037]).
- in case the COM Based Transformer [8] is used it is the integral part of the approach to have a fixed mapping of the individual elements of composite data types to `SystemSignals` in a `SystemSignalGroup` ([TPS_SYST_02058]).

]

[constr_3508] Value of `nmReadySleepTime`*Imposition time:* IT_SysDesc

[The `nmReadySleepTime` value shall be a multiple of `cycle * nmRepetitionCycle`.

]

[constr_3514] No two `ISignalToIPduMappings` shall reference the identical `ISignal`*Imposition time:* IT_SysDesc

[No two `ISignalToIPduMappings` shall reference the identical `ISignal` in the role `iSignal` in the scope of one System.

]

[constr_3515] Fully filled `EthernetPriorityRegeneration` table*Imposition time:* IT_SysDesc

[In case the `CouplingPortDetails.ethernetPriorityRegeneration` is defined it shall contain exactly 8 elements of `EthernetPriorityRegeneration`, one for each value of `ingressPriority` (0-7).

]

[constr_3516] limitation of `Frame.frameLength` for CAN L-PDUs*Imposition time:* IT_SysDesc

[The `Frame.frameLength` of CAN PDUs shall be restricted to

- 0..8 for classic CAN L-PDUs;
- 0..8, 12, 16, 20, 24, 32, 48, 64 for CAN FD L-PDUs and
- 1..2048 for CAN XL L-PDUs.

]

[constr_3517] Consistent setting of `ContainedIPduProps.collectionSemantics` in the context of one `ContainerIPdu`

Imposition time: IT_SysDesc

[The value of the attribute `ContainedIPduProps.collectionSemantics` shall be identical for all contained `IPdus` within the context of a given `ContainerIPdu`.

]

[constr_3518] Range of `CanControllerFdConfiguration.paddingValue` and `CanControllerFdConfigurationRequirements.paddingValue`

Imposition time: IT_SysDesc

[The value given for `CanControllerFdConfiguration.paddingValue` and `CanControllerFdConfigurationRequirements.paddingValue` shall be in the range from 0 to 255.

]

[constr_3519] Value of `category` of `GlobalTimeDomain`

Imposition time: IT_SysDesc

[The attribute `category` of `GlobalTimeDomain` can have the following value:

- SYNCHRONIZED: this time base does not depend on the existence of another time base

]

[constr_3521] `defaultVlan` and `vlanMembership`

Imposition time: IT_SysDesc

[If a `CouplingPort` refers to an `EthernetPhysicalChannel` in the role `defaultVlan` the `CouplingPort` shall also have a `vlanMembership` defined. This `VlanMembership` shall point to the same `EthernetPhysicalChannel` in the role `vlan` as the `defaultVlan`.

]

[constr_3523] `CouplingPort` and `PncMapping` in the scope of an `EthernetPhysicalChannel`

Imposition time: IT_SysDesc

[If

- a `CouplingPort` referring to an `EthernetPhysicalChannel` – via a `VlanMembership` – references at least one `PncMapping`
- and that `PncMapping` contains PDUs – via the assignment of `PncMapping.pncGroup` – that are transported on this `EthernetPhysicalChannel`

then every `CouplingPort` referring to that `EthernetPhysicalChannel` shall reference at least one `PncMapping` as well.

]

[constr_3524] Definition of `couplingPortRole` on `CouplingPort` for managed `CouplingElement`

Imposition time: IT_SysDesc

[A managed `CouplingElement` shall have either

- at most one `CouplingPort` with `couplingPortRole` set to `hostPort` or
- at least one `CouplingPort` with `couplingPortRole` set to `upLinkPort`.

]

[constr_3525] Connection of `CouplingPort` with `couplingPortRole` set to `upLinkPort`

Imposition time: IT_SysDesc

[A `CouplingPort` with `couplingPortRole` set to `upLinkPort` shall be connected to exactly one other `CouplingPort` with `couplingPortRole` set to `upLinkPort`.

]

[constr_3533] `EndToEndTransformationISignalProps.dataLength` shall be a multiple of 8

Imposition time: IT_SysDesc

[The value of `EndToEndTransformationISignalProps.dataLength`, `EndToEndTransformationISignalProps.maxDataLength`, and `EndToEndTransformationISignalProps.minDataLength` shall be a multiple of 8.

]

[constr_3534] `EthernetPhysicalChannel` shall only be referenced by one `VlanMembership`

Imposition time: IT_SysDesc

[An `EthernetPhysicalChannel` shall only be referenced by one `VlanMembership` in the role `VlanMembership.vlan` in the scope of one `CouplingPort`.

]

[constr_3535] EthernetCommunicationController shall aggregate at most one CouplingPort

Imposition time: IT_SysDesc

[An EthernetCommunicationController is allowed to aggregate at most one CouplingPort.

]

[constr_3545] Mandatory reference to a Pnc in case of anyPartialNetworkActive or allPartialNetworksActive

Imposition time: IT_SysDesc

[If the SignalServiceTranslationProps.serviceControl equals anyPartialNetworkActive or allPartialNetworksActive, then the reference SignalServiceTranslationProps.controlPnc shall point to at least one PncMappingIdent.

]

[constr_3546] Mandatory reference to a ConsumedEventGroup in case of serviceControl

Imposition time: IT_SysDesc

[For a provided translated service instance, if the SignalServiceTranslationProps.serviceControl equals serviceDiscovery then the reference SignalServiceTranslationProps.controlConsumedEventGroup shall point to at least one ConsumedEventGroup.

]

[constr_3548] EndToEnd profile for both ends of safeTranslation

Imposition time: IT_SysDesc

[If the SignalServiceTranslationEventProps.safeTranslation equals true then both, the signal-based payload as well as the service-oriented payload shall have an EndToEnd profile defined.

]

[constr_3549] Secure payload for both ends in case of secureTranslation

Imposition time: IT_SysDesc

[If the SignalServiceTranslationEventProps.secureTranslation equals true then both, the signal-based payload as well as the service-oriented payload shall have a secure communication defined.

]

[constr_3559] ConsumedServiceInstance.blocklistedVersion is restricted to the usage of minorVersion

Status: DRAFT

Imposition time: IT_SysDesc

[The `majorVersion` attribute shall not be used in the `SomeipServiceVersion` that is aggregated by the `ConsumedServiceInstance` in the role `blocklistedVersion`.

]

[constr_3560] minimumMinorVersion and ConsumedServiceInstance.minorVersion value

Status: DRAFT

Imposition time: IT_SysDesc

[The `ConsumedServiceInstance.minorVersion` shall not have the value `ANY` if `versionDrivenFindBehavior = minimumMinorVersion`.

]

[constr_3600] Setting of EthernetCommunicationController.slaveActAsPassiveCommunicationSlave

Imposition time: IT_SysDesc

[The attribute `EthernetCommunicationController.slaveActAsPassiveCommunicationSlave` may only be set to `TRUE`, if the following conditions apply:

- the `EthernetCommunicationController` is not referenced by any `NmNode` in the role `controller`
- the `EthernetCommunicationController` aggregates at least one `CouplingPort`
- the `couplingPortRole` of that `CouplingPort` is set to `standardPort`
- the `physicalLayerType` of that `CouplingPort` is set to either `_100BASE_T1`, `_1000BASE_T1` or `_10BASE_T1S`

In all other cases the attribute `slaveActAsPassiveCommunicationSlave` shall be set to `FALSE` or shall not be defined.

]

[constr_3601] Mandatory attributes of EthernetWakeupSleepOnDataLineConfig

Imposition time: IT_EcuExt

[The following attributes of `EthernetWakeupSleepOnDataLineConfig` shall be defined:

- `wakeupLocalEnabled`
- `wakeupRemoteEnabled`

]

[constr_3602] Existence of `wakeupForwardLocalEnabled`*Imposition time:* IT_SysDesc

[The attribute `wakeupForwardLocalEnabled` shall be defined if `wakeupRemoteEnabled` is set to TRUE.

]

[constr_3603] Existence of `wakeupLocalDurationTime`*Imposition time:* IT_SysDesc

[The attribute `wakeupLocalDurationTime` shall be defined if `wakeupForwardLocalEnabled` is set to TRUE.

]

[constr_3604] Existence of `wakeupForwardRemoteEnabled`*Imposition time:* IT_SysDesc

[The attribute `wakeupForwardRemoteEnabled` shall be defined if `wakeupLocalEnabled` is set to TRUE.

]

[constr_3605] Existence of `wakeupLocalDetectionTime`*Imposition time:* IT_SysDesc

[The attribute `wakeupLocalDetectionTime` shall be defined if `wakeupForwardRemoteEnabled` is set to TRUE.

]

[constr_3606] Values of `wakeupLocalDurationTime` and `wakeupLocalDetectionTime`*Imposition time:* IT_SysDesc

[If defined, then the value of `wakeupLocalDurationTime` shall be greater than the value of `wakeupLocalDetectionTime`.

]

[constr_3607] Existence of `sleepRepetitionDelayOfSleepRequest`

Imposition time: IT_SysDesc

[The attribute `sleepRepetitionDelayOfSleepRequest` shall be defined if `sleepRepetitionsOfSleepRequest` is defined and has a value greater than 0.

]

[constr_3608] Existence of `wakeupRepetitionDelayOfWakeupRequest`

Imposition time: IT_SysDesc

[The attribute `wakeupRepetitionDelayOfWakeupRequest` shall only be defined if `wakeupRepetitionsOfWakeupRequest` is defined and has a value greater than 0.

]

[constr_3609] Values of `wakeupLocalDurationTime` in the context of a `CouplingElement`

Imposition time: IT_SysDesc

[All `CouplingPorts` which have the reference `wakeupSleepOnDatalineConfig` defined and

- where the `CouplingPorts` are aggregated by the same `CouplingElement` and
- where the referenced `EthernetWakeupSleepOnDatalineConfig` has the attribute `wakeupLocalDurationTime` defined

shall refer to `EthernetWakeupSleepOnDatalineConfigs` where the value of `wakeupLocalDurationTime` is identical for all referencing `CouplingPorts`.

]

[constr_3610] Values of `wakeupLocalDetectionTime` in the context of a `CouplingElement`

Imposition time: IT_SysDesc

[All `CouplingPorts` which have the reference `wakeupSleepOnDatalineConfig` defined and

- where the `CouplingPorts` are aggregated by the same `CouplingElement` and
- where the referenced `EthernetWakeupSleepOnDatalineConfig` has the attribute `wakeupLocalDetectionTime` defined

shall refer to `EthernetWakeupSleepOnDatalineConfigs` where the value of `wakeupLocalDetectionTime` is identical for all referencing `CouplingPorts`.

]

[constr_3611] Existence of `EthernetCommunicationController.slaveQualifiedUnexpectedLinkDownTime`

Imposition time: IT_SysDesc

[The attribute `slaveQualifiedUnexpectedLinkDownTime` shall be defined if `slaveActAsPassiveCommunicationSlave` is set to TRUE.

]

[constr_3615] Existence of `EthernetCluster.couplingPortSwitchoffDelay`

Imposition time: IT_SysDesc

[The attribute `EthernetCluster.couplingPortSwitchoffDelay` shall be defined if at least one `EcuInstance` connected to that `EthernetCluster` has the attribute `ethSwitchPortGroupDerivation` set to TRUE.

]

[constr_3616] Value of `EthernetCluster.couplingPortSwitchoffDelay`

Imposition time: IT_SysDesc

[If defined, the value of `EthernetCluster.couplingPortSwitchoffDelay` shall be greater than `UdpNmCluster.nmNetworkTimeout` + `UdpNmCluster.nmWaitBusSleepTime` of the respective `EthernetCluster`.

]

[constr_3617] Existence of `EthernetCluster.couplingPortStartupActiveTime`

Imposition time: IT_SysDesc

[The attribute `EthernetCluster.couplingPortStartupActiveTime` shall be defined if at least one `EcuInstance` connected to that `EthernetCluster` has the attribute `ethSwitchPortGroupDerivation` set to TRUE.

]

[constr_3618] Value of `EthernetCluster.couplingPortStartupActiveTime`

Imposition time: IT_SysDesc

[If defined, the value of `EthernetCluster.couplingPortStartupActiveTime` shall be greater than `UdpNmCluster.nmNetworkTimeout` + `UdpNmCluster.nmWaitBusSleepTime` of the respective `EthernetCluster`.

]

[constr_3620] `GlobalTimeDomain.networkSegmentId` only applicable to Global Time sub domains

Imposition time: IT_SysDesc

[The aggregation `GlobalTimeDomain.networkSegmentId` shall only be defined if the `GlobalTimeDomain` is itself referenced in the role `GlobalTimeDomain.globalTimeSubDomain`.

]

[constr_3621] Value range of `GlobalTimeDomain.networkSegmentId`

Imposition time: IT_SysDesc

[If defined, the value of `GlobalTimeDomain.networkSegmentId` shall be in the range 0..255.

]

[constr_3651] No `element` in case `translationTarget` is primitive

Imposition time: IT_SysDesc

[If `SignalServiceTranslationEventProps.translationTarget` refers to a `VariableDataPrototype` that is typed by a primitive `AutosarDataType` then the reference `SignalServiceTranslationElementProps.element` shall not be defined.

]

[constr_3652] Allowed sub-classes of `DataPrototypeReference` in the context of signal/service translation

Imposition time: IT_SysDesc

[If a `DataPrototypeReference` in the role `SignalServiceTranslationElementProps.element` is used then following sub-classes are supported:

- if the reference target is typed by an `ApplicationDataType` then the `DataPrototypeInSenderReceiverInterfaceInstanceRef` shall be used and shall target an `ApplicationCompositeElementDataPrototype`.
- if the reference target is typed by an `ImplementationDataType` then the `ImplementationDataPrototypeElementInPortInterfaceRef` shall be used.

]

[constr_3653] Consistent `translationTarget` and `element` in case `ApplicationDataType` is used

Imposition time: IT_SysDesc

[If the `SignalServiceTranslationEventProps.translationTarget` refers to a `VariableDataPrototype` that is typed by an `ApplicationDataType` (`target-`

DataPrototype of the VariableDataPrototypeInSystemInstanceRef) then every SignalServiceTranslationElementProps.element reference that is defined in the context of the SignalServiceTranslationEventProps shall have that VariableDataPrototype as the rootDataPrototypeInSr of the DataPrototypeInSenderReceiverInterfaceInstanceRef.

]

[constr_3654] Consistent translationTarget and element in case ImplementationDataType is used

Imposition time: IT_SysDesc

[If the SignalServiceTranslationEventProps.translationTarget refers to a VariableDataPrototype that is typed by an ImplementationDataType (targetDataPrototype of the VariableDataPrototypeInSystemInstanceRef) then every SignalServiceTranslationElementProps.element reference that is defined in the context of the SignalServiceTranslationEventProps shall have that VariableDataPrototype as the rootDataPrototype of the ImplementationDataTypeElementInPortInterfaceRef.

]

[constr_3655] Supported filter types for primitive SignalServiceTranslationElementProps

Imposition time: IT_SysDesc

[If the target for SignalServiceTranslationElementProps is defined as primitive according to [TPS_SYST_03062] then the following values for dataFilterType are supported:

- always
- maskedNewDiffersMaskedOld
- maskedNewDiffersX
- maskedNewEqualsX
- never
- newIsOutside
- newIsWithin
- oneEveryN.

]

[constr_3656] Supported filter types for composite `SignalServiceTranslationElementProps`

Imposition time: IT_SysDesc

[If the target for `SignalServiceTranslationElementProps` is defined as composite according to [TPS_SYST_03062] then the following values for `dataFilterType` are supported:

- `always`
- `never`
- `oneEveryN`.

]

[constr_3668] Existence of `TlsCryptoCipherSuite.cipherSuiteShortLabel`

Imposition time: IT_SysDesc

[If a `TlsCryptoCipherSuite.cipherSuiteShortLabel` is defined then:

- the attribute `TlsCryptoCipherSuite.cipherSuiteId` shall be defined as well
- the value of `TlsCryptoCipherSuite.cipherSuiteShortLabel` shall match the *Description* value corresponding to the *Value* field defined in `TlsCryptoCipherSuite.cipherSuiteId` according to `TlsCryptoCipherSuite` Parameter set defined in [10].

]

[constr_3669] `eventMulticastSubscriptionAddress` shall refer to a multicast address

Imposition time: IT_SysDesc

[The reference `ConsumedServiceInstance.eventMulticastSubscriptionAddress` shall refer to an `ApplicationEndpoint` which in turn refers to a `NetworkEndpoint` that represents a multicast address.

]

[constr_3670] No support for parallel `localUnicastAddress` and `eventMulticastSubscriptionAddress`

Imposition time: IT_SysDesc

[If a `eventMulticastSubscriptionAddress` is defined for a `ConsumedServiceInstance` then there shall not be a `localUnicastAddress` defined at the same `ConsumedServiceInstance`.

]

[constr_3671] remoteMulticastSubscriptionAddress shall refer to a multicast address

Imposition time: IT_SysDesc

[The reference `ProvidedServiceInstance.remoteMulticastSubscriptionAddress` shall refer to an `ApplicationEndpoint` which in turn refers to a `NetworkEndpoint` that represents a multicast address.

]

[constr_3672] No support for methods in multicast subscription at the client

Imposition time: IT_SysDesc

[If a `ConsumedServiceInstance` aggregates a `PduActivationRoutingGroup` in the role `methodActivationRoutingGroup`, then the `ConsumedServiceInstance` shall not define a `eventMulticastSubscriptionAddress`.

]

[constr_3673] No support for methods in multicast subscription at the server static configuration

Imposition time: IT_SysDesc

[If a `ProvidedServiceInstance` aggregates a `PduActivationRoutingGroup` in the role `methodActivationRoutingGroup`, then the `ProvidedServiceInstance.remoteMulticastSubscriptionAddress` shall not be defined.

]

[constr_3685] Allowed values for each element of pncFilterArrayMask

Imposition time: IT_SysDesc

[The value for each element of `CommunicationConnector.pncFilterArrayMask` shall be in the range between 0 and 255.

]

[constr_3686] Allowed number of entries for pncFilterArrayMask

Imposition time: IT_SysDesc

[The number of `CommunicationConnector.pncFilterArrayMask` elements shall be:

- `NmCluster.pncClusterVectorLength`, if defined
- `System.pncVectorLength`, otherwise.

]

[constr_3687] Limited value range for `NmCluster.pncClusterVectorLength`

Imposition time: IT_SysDesc

[The value of `NmCluster.pncClusterVectorLength` shall be equal or smaller than `System.pncVectorLength`.

]

[constr_3695] `canControllerXlAttributes` and `canControllerXlRequirements` are mutually exclusive

Imposition time: IT_SysDesc

[The existence of `canControllerXlAttributes` and `canControllerXlRequirements` is mutually exclusive.

]

[constr_3696] Mandatory attributes of `CanControllerXlConfiguration`

Imposition time: IT_SysDesc

[A `CanControllerConfiguration` configuring a CAN XL controller shall aggregate `CanControllerXlConfiguration` with the following attributes defined:

- `errorSignalingEnabled`
- `propSeg`
- `syncJumpWidth`
- `timeSeg1`
- `timeSeg2`
- `trcvPwmModeEnabled`

]

[constr_3697] Latest existence time of `CanControllerXlConfiguration` and `CanControllerXlConfigurationRequirements`

Imposition time: IT_SysDesc

[In case that a CAN XL controller is configured, then either `CanControllerXlConfiguration` or `CanControllerXlConfigurationRequirements` shall exist within their aggregating class `CanControllerConfiguration` or `CanControllerConfigurationRequirements`.

]

[constr_3698] Value of `errorSignalingEnabled`

Imposition time: IT_SysDesc

[The attribute `errorSignalingEnabled` shall be set to FALSE if `trcvPwmModeEnabled` is set to TRUE.

]

[constr_3699] Existence of `pwmL`

Imposition time: IT_SysDesc

[The attribute `pwmL` shall be defined if `trcvPwmModeEnabled` is set to TRUE.

]

[constr_3700] Existence of `pwmO`

Imposition time: IT_SysDesc

[The attribute `pwmO` shall be defined if `trcvPwmModeEnabled` is set to TRUE.

]

[constr_3701] Existence of `pwmS`

Imposition time: IT_SysDesc

[The attribute `pwmS` shall be defined if `trcvPwmModeEnabled` is set to TRUE.

]

[constr_3702] Relevant attributes of `EthernetCommunicationController` for CAN_XL

Imposition time: IT_SysDesc

[If the category of `EthernetCommunicationController` is equal to CAN_XL, then only the following attributes of this meta-class are relevant:

- `macLayerType`
- `macUnicastAddress`

]

[constr_3703] Reference to `CanControllerXlConfiguration` in case of category CAN_XL

Imposition time: IT_SysDesc

[If the category of `EthernetCommunicationController` is equal to CAN_XL, then the reference `canXlConfig` of `EthernetCommunicationController` shall refer to the `CanCommunicationController` aggregating the `CanControllerConfiguration` which in turn aggregates the `CanControllerXlConfiguration` that is

used for tunneling of the Ethernet frames associated with the aforementioned `EthernetCommunicationController`.

]

[constr_3704] Existence of `CanXlFrameTriggeringProps`

Imposition time: IT_SysDesc

[If the class `CanXlFrameTriggeringProps` is aggregated by a `CanFrameTriggering`, then the `CanCommunicationController` – which is referenced through `commController` by a `CanCommunicationConnector` which in turn is referenced through `commConnector` by a `CanPhysicalChannel` that aggregates the aforementioned `CanFrameTriggering` – shall aggregate at least one of

- `CanControllerConfiguration` with `CanControllerXlConfiguration` aggregated or
- `CanControllerConfigurationRequirements` with `CanControllerXlConfigurationRequirements` aggregated.

]

[constr_3705] Allowed values for `priorityId`

Imposition time: IT_SysDesc

[The value for `priorityId` shall be in the range between 0 and 2047.

]

[constr_3706] Allowed values for `sduType`

Imposition time: IT_SysDesc

[The value for `sduType` shall be in the range between 0 and 255.

]

[constr_3707] Allowed values for `vcid`

Imposition time: IT_SysDesc

[The value for `vcid` shall be in the range between 0 and 255.

]

[constr_3708] No UDP network management in case of Ethernet tunneling through CAN XL

Imposition time: IT_SysDesc

[For an `EthernetPhysicalChannel` that is connected to an `EthernetCommunicationController` of category `CAN_XL` (i.e. an `EthernetPhysicalChannel` tunneled through CAN XL), no UDP network management shall be configured.

]

[constr_3713] Allowed values for `acceptanceField`

Imposition time: IT_SysDesc

[The value for `acceptanceField` shall be in the range between 0 and 4294967295.

]

[constr_3714] Multiple top level PNC-coordinators shall be allowed

Imposition time: IT_SysDesc

[Multiple top level PNC-coordinators shall only be allowed if no network path across all networks exist that connects a `CommunicationConnector` with `pncGatewayType` `PncGatewayTypeEnum.active` to another `CommunicationConnector` with `pncGatewayType` `PncGatewayTypeEnum.active` where both `CommunicationConnectors` belong to different top level PNC-coordinators.

]

[constr_3716] `SecuredIPdu.dynamicRuntimeLengthHandling` for dynamic length `Pdus`

Imposition time: IT_SysDesc

[If a `PduTriggering` is referenced from a `SecuredIPdu` in the role `payload` and the `Pdu` referenced by the `PduTriggering` in the role `iPdu` qualifies according to [TPS_SYST_03085] to be of dynamic length, then the `SecuredIPdu` shall have the attribute `SecuredIPdu.dynamicRuntimeLengthHandling` set to true.

]

[constr_3717] `SecuredIPdu.dynamicRuntimeLengthHandling` for gateway operation with `IPduMapping.pduMaxLength` defined

Imposition time: IT_SysDesc

[If a `PduTriggering` refers to a `SecuredIPdu` in the role `iPdu` and that `PduTriggering` is used in an `IPduMapping` where a `pduMaxLength` value is defined (either in the role `IPduMapping.sourceIPdu` or `TargetIPduRef.targetIPdu`), then

the `SecuredIPdu` shall have the attribute `SecuredIPdu.dynamicRuntimeLengthHandling` set to true.

]

[constr_3718] Minimum length of `SecuredIPdus`

Imposition time: IT_SysDesc

[If a `SecuredIPdu` has the attribute `useAsCryptographicIPdu` set to false, then the `length` attribute of that `SecuredIPdu` shall be at least the sum of the `payloadPdu.length` and `SecuredIPdu.authenticationProps.authInfoTxLength`.

]

[constr_3726] Upper multiplicity of aggregation in the role `CouplingPort.macSecProps`

Status: DRAFT

Imposition time: IT_SysDesc

[In the context of `CouplingPort`, the aggregation in the role `macSecProps` shall exist at most once.

]

[constr_3735] Existence of `DdsCpServiceInstance.ddsServiceQosProfile`

Imposition time: IT_EcuExt

[For each `DdsCpServiceInstance`, the reference in the role `ddsServiceQosProfile` shall exist.

Note: This profile applies to the all 4 topics used for methods and fields defined into the `DdsCpServiceInstance` (e.g `ddsMethodRequestTopic`, `ddsMethodReplyTopic`), `ddsFieldRequestTopic`, `ddsFieldReplyTopic`).

]

[constr_3736] `ISignal` that has `dataTypePolicy` set to `ddsSignal` shall be referenced by a `DdsCpISignalToDdsTopicMapping`

Imposition time: IT_SysDesc

[Every `ISignal` that has `dataTypePolicy` set to `ddsSignal` shall be referenced by a `DdsCpISignalToDdsTopicMapping`.

]

[constr_3737] ISignal referenced from DdsCpISignalToDdsTopicMapping

Imposition time: IT_SysDesc

[Every ISignal that has dataTypePolicy set to any value different to ddsSignal shall NOT be referenced by a DdsCpISignalToDdsTopicMapping.

]

[constr_3738] ISignal that has dataTypePolicy set to ddsSignal or to ddsService shall not reference a DataTransformation

Imposition time: IT_SysDesc

[In a complete model every ISignal that has dataTypePolicy set to ddsSignal or to ddsService shall NOT reference to any DataTransformation.

]

[constr_3739] Value of ISignal.dataTypePolicy for all ISignals associated with a DdsCpServiceInstance

Imposition time: IT_EcuExt

[For all ISignals that are referenced by an ISignalToIPduMapping where the enclosing ISignalIPdu is only referenced by PduTriggerings that are in turn referenced in one of the roles:

- DdsCpServiceInstanceEvent.ddsEvent
- DdsCpServiceInstanceOperation.ddsOperationRequestTriggering
- DdsCpServiceInstanceOperation.ddsOperationResponseTriggering

The value of attribute ISignal.dataTypePolicy shall be set to ddsService.

]

[constr_3740] Existence of DdsCpServiceInstanceEvent.ddsEventTopic

Imposition time: IT_EcuExt

[For each DdsCpServiceInstanceEvent, the reference in the role ddsEventTopic shall exist.

]

[constr_3741] Exclusive setting of `channelSynchronousWakeup` or `pncSynchronousWakeup`

Imposition time: IT_SysDesc

[At most one of `EcuInstance.channelSynchronousWakeup` or `EcuInstance.pncSynchronousWakeup` shall be set to TRUE.

]

[constr_3742] Value for `createEcuWakeupSource` in the context of a `CommunicationCluster`

Imposition time: IT_SysDesc

[The attribute `CommunicationConnector.createEcuWakeupSource` shall be set to the same value for all `CommunicationConnectors` in the scope of one `EcuInstance` which are referenced by `PhysicalChannels` that belong to the same `CommunicationCluster`.

]

[constr_3743] Allowed values for `IEEE1722TpConnection.uniqueStreamId`

Status: DRAFT

Imposition time: IT_SysDesc

[The value for `IEEE1722TpConnection.uniqueStreamId` shall be in the range between 0 and 65535.

]

[constr_3744] Allowed values for `IEEE1722TpConnection.version`

Status: DRAFT

Imposition time: IT_SysDesc

[The value for `IEEE1722TpConnection.version` shall be in the range between 0 and 7.

]

[constr_3745] `category` of `GeneralPurposePdu` referenced in the role `IEEE1722TpConnection.pdu`

Status: DRAFT

Imposition time: IT_EcuExt

[The `GeneralPurposePdu` referenced by the `PduTriggering` which in turn is referenced in the role `pdu` by the `IEEE1722TpConnection` shall have the `category` set to IEEE1722TP.

]

[constr_3746] category of GeneralPurposePdu referenced in the role IEEE1722TpAvConnection.sdu

Status: DRAFT

Imposition time: IT_EcuExt

[The `GeneralPurposePdu` referenced by the `PduTriggering` which in turn is referenced in the role `IEEE1722TpAvConnection.sdu` by the `IEEE1722TpAvConnection` shall have the `category` set to `IEEE1722TP_STREAM`.

]

[constr_3747] Existence of attribute IEEE1722TpConnection.uniqueStreamId

Status: DRAFT

Imposition time: IT_SysDesc

[For each `IEEE1722TpConnection`, the attribute `uniqueStreamId` shall exist.

]

[constr_3748] Existence of attribute IEEE1722TpConnection.macAddressStreamId

Status: DRAFT

Imposition time: IT_SysDesc

[For each `IEEE1722TpConnection`, the attribute `macAddressStreamId` shall exist.

]

[constr_3749] Existence of attribute IEEE1722TpConnection.version

Status: DRAFT

Imposition time: IT_SysDesc

[For each `IEEE1722TpConnection`, the attribute `version` shall exist.

]

[constr_3750] Existence of attribute IEEE1722TpConnection.pdu

Status: DRAFT

Imposition time: IT_EcuExt

[For each `IEEE1722TpConnection`, the reference `pdu` shall exist.

]

[constr_3751] Allowed values for IEEE1722TpAcfBus.busId*Status:* DRAFT*Imposition time:* IT_SysDesc

[The value for IEEE1722TpAcfBus.busId shall be in the range between 0 and 31.
]

[constr_3752] Existence of attribute IEEE1722TpAcfBus.busId*Status:* DRAFT*Imposition time:* IT_SysDesc

[For each IEEE1722TpAcfBus, the attribute busId shall exist.
]

[constr_3753] Existence of attribute IEEE1722TpAcfLinPart.linIdentifier*Status:* DRAFT*Imposition time:* IT_SysDesc

[For each IEEE1722TpAcfLinPart, the attribute linIdentifier shall exist.
]

[constr_3754] Existence of attribute IEEE1722TpAcfCan.messageType*Status:* DRAFT*Imposition time:* IT_SysDesc

[For each IEEE1722TpAcfCan, the attribute messageType shall exist.
]

[constr_3755] Consistent aggregation of IEEE1722TpAcfCanPart*Status:* DRAFT*Imposition time:* IT_SysDesc

[An IEEE1722TpAcfCan shall only aggregate IEEE1722TpAcfCanParts in the role IEEE1722TpAcfCan.acfPart.
]

[constr_3756] Consistent aggregation of IEEE1722TpAcfLinPart*Status:* DRAFT*Imposition time:* IT_SysDesc

[An IEEE1722TpAcfLin shall only aggregate IEEE1722TpAcfLinParts in the role IEEE1722TpAcfLin.acfPart.
]

[constr_3757] Allowed values for IEEE1722TpAcfLinPart.linIdentifier

Status: DRAFT

Imposition time: IT_SysDesc

[The value for IEEE1722TpAcfLinPart.linIdentifier shall be in the range between 0 and 63.

]

[constr_3758] Allowed values for IEEE1722TpAcfCanPart.canIdentifier

Status: DRAFT

Imposition time: IT_SysDesc

[The value for IEEE1722TpAcfCanPart.canIdentifier shall be in the range between 0 and 536870911.

]

[constr_3759] Existence of attribute IEEE1722TpAcfCanPart.canIdentifier for IEEE1722Tp ACF stream transmission

Status: DRAFT

Imposition time: IT_SysDesc

[If an IEEE1722TpAcfCanPart is part of an IEEE1722TpAcfConnection which, according to [TPS_SYST_03109], is transmitted in that IEEE1722TpAcfConnection and

the IEEE1722TpAcfCanPart refers to a PduTriggering in the role sdu which in turn refers to a Pdu that is NOT a GeneralPurposePdu of category IEEE1722TP_ID_RANGE,

then the attribute IEEE1722TpAcfCanPart.canIdentifier shall exist.

]

[constr_3760] Existence of attribute IEEE1722TpAcfCanPart.canIdentifierRange or canIdentifierMask for IEEE1722Tp ACF stream reception

Status: DRAFT

Imposition time: IT_SysDesc

[If an IEEE1722TpAcfCanPart is part of an IEEE1722TpAcfConnection which, according to [TPS_SYST_03110], is received in that IEEE1722TpAcfConnection and

the IEEE1722TpAcfCanPart refers to a PduTriggering in the role sdu which in turn refers to a Pdu that is NOT a GeneralPurposePdu of category IEEE1722TP_ID_RANGE,

then the attribute `IEEE1722TpAcfCanPart.canIdentifierRange` or `canIdentifierMask` shall exist.

]

[constr_3761] Identical `EthernetPhysicalChannel` owning `PduTriggerings` referenced by `IEEE1722TpConnection.pdu` and `IEEE1722TpAvConnection.sdu`

Status: DRAFT

Imposition time: IT_EcuExt

[The `PduTriggerings` referenced in the roles `IEEE1722TpConnection.pdu` and `IEEE1722TpAvConnection.sdu` shall be owned by the same `EthernetPhysicalChannel`.

]

[constr_3762] Usage of `CouplingElementSwitchDetails` only on an Ethernet switch

Status: DRAFT

Imposition time: IT_SysDesc

[If a `CouplingElement` aggregates a `CouplingElementSwitchDetails` in the role `CouplingElement.couplingElementDetails`, then that `CouplingElement` shall have the attribute `couplingType` set to the value `CouplingElementEnum.switch`.

]

[constr_3763] Allowed value for `maxDeltaCounter` in the context of a `profileName`

Imposition time: IT_SysDesc

[An `EndToEndTransformationComSpecProps` that is associated with an `EndToEndTransformationDescription` as described in [TPS_SYST_02275] shall not contain a `maxDeltaCounter` value that is outside the value range imposed by the profile defined in `EndToEndTransformationDescription.profileName`.

The profile specific value ranges are listed in [constr_3158], [constr_3195], [constr_3159], [constr_3196], [constr_3197], and [constr_3316].

]

[constr_3764] Applicability of `CouplingPort.macAddressVlanAssignment`

Imposition time: IT_SysDesc

[The aggregation `CouplingPort.macAddressVlanAssignment` shall only exist if the `CouplingPort` is aggregated by a `CouplingElement` with `couplingType = CouplingElementEnum.switch`.

]

[constr_3765] Applicability of `MacAddressVlanMembership.vlan`

Imposition time: IT_SysDesc

[The reference `MacAddressVlanMembership.vlan` shall only exist if the `CouplingPort` aggregating this `MacAddressVlanMembership` is aggregated by a `CouplingElement` with `switchMacAddressLearningMode = SwitchMacAddressLearningEnum.independentVlanLearning`.

]

[constr_3766] Valid `MacAddressVlanMembership.vlan` target `EthernetPhysicalChannel`

Imposition time: IT_SysDesc

[If an `EthernetPhysicalChannel` is referenced by a `CouplingPort.macAddressVlanAssignment.vlan`, then that `EthernetPhysicalChannel` shall also be referenced by the same `CouplingPort` via `CouplingPort.vlanMembership.vlan`

]

[constr_3767] `NmNode.nmVariant` setting to `slavePassive`

Imposition time: IT_SysDesc

[`NmNode.nmVariant` shall only be set to `NmVariantEnum.slavePassive` if an `EthernetCommunicationController` is referenced in the role `NmNode.controller` and the attribute `slaveActAsPassiveCommunicationSlave` in the referenced `EthernetCommunicationController` is set to true.

]

[constr_3768] `NmNode.nmVariant` setting to `slaveActive`

Imposition time: IT_SysDesc

[`NmNode.nmVariant` shall only be set to `NmVariantEnum.slaveActive` if a `LinSlave` is referenced in the role `NmNode.controller`.

]

[constr_3769] NmNode.nmVariant setting to full

Imposition time: IT_SysDesc

[NmNode.nmVariant shall only be set to NmVariantEnum.full if a CommunicationController is referenced in the role NmNode.controller and the attribute nmPassiveModeEnabled in the referenced NmEcu is not present or is set to false.

]

[constr_3770] NmNode.nmVariant setting to passive

Imposition time: IT_SysDesc

[NmNode.nmVariant shall only be set to NmVariantEnum.passive if a CommunicationController is referenced in the role NmNode.controller and the attribute nmPassiveModeEnabled in the referenced NmEcu is set to true.

]

[constr_3771] Range of NmCluster.nmLightTimeout

Imposition time: IT_SysDesc

[The value given for NmCluster.nmLightTimeout shall be in the range from 0 to 255.

]

[constr_3779] Number of ISignal.receptionDefaultValue elements

Imposition time: IT_SysDesc

[At most one entry of ISignal.receptionDefaultValue shall be defined at each ISignal. The definition of ISignal.receptionDefaultValue shall adhere to [constr_3780].

]

[constr_3780] ISignal.receptionDefaultValue definition in case that the SOME/IP Serializer receives less data than expected

Imposition time: IT_SysDesc

[If an ISignal.receptionDefaultValue is provided for the case defined in [TPS_SYST_03122], then the ISignal.receptionDefaultValue shall only be defined by

- a NumericalValueSpecification or
- a TextValueSpecification

or by

- a RecordValueSpecification or

- an `ArrayValueSpecification` or
- a `CompositeRuleBasedValueSpecification`

that (after further nesting levels consisting of `RecordValueSpecification` and `ArrayValueSpecification` are resolved) only contain

- `NumericalValueSpecification`
- `TextValueSpecification`.

]

[constr_3781] Each PNC assigned to multiple `PhysicalChannels` shall have a top level PNC-Coordinator

Imposition time: IT_SysDesc

[In a `System`, if a PNC is assigned to multiple `PhysicalChannels` according to [TPS_SYST_03080], then this PNC shall have at least one top level PNC-Coordinator according to [TPS_SYST_03082].

]

[constr_3782] Consistent `framePreemptionSupport` setting in the scope of one `CouplingPortConnection`

Imposition time: IT_SysDesc

[For each `CouplingPortConnection` the value of `CouplingPort.couplingPortDetails.framePreemptionSupport` shall be identical for both, `CouplingPortConnection.firstPort` and `CouplingPortConnection.secondPort`.

]

[constr_3783] Definition of `CouplingPortFifo.trafficClassPreemptionSupport` only in context of an Ethernet switch

Imposition time: IT_SysDesc

[If a `CouplingPort` is aggregated by a `CouplingElement` with `CouplingElement.couplingType` equal to `CouplingElementEnum.switch` and `CouplingPort.couplingPortDetails.framePreemptionSupport` is set to true, then the attribute `CouplingPortFifo.trafficClassPreemptionSupport` shall be defined.

]

[constr_3784] Applicable `CouplingPortFifo` as predecessor for `portScheduler = enhancedTrafficShaper`

Imposition time: IT_SysDesc

[A `CouplingPortScheduler` with `CouplingPortScheduler.portScheduler` equals to `EthernetCouplingPortSchedulerEnum.enhancedTrafficShaper` shall only refer to `CouplingPortFifo` in the role `CouplingPortScheduler.predecessor` where the `CouplingPortFifo` has a `CouplingPortFifo.shaper` of kind `CouplingPortEnhancedTrafficShaper`.

]

[constr_3785] Exclusive definition of `etsAvailableBandwidthInPercent` or `etsAvailableBandwidthInWeightValue`

Imposition time: IT_SysDesc

[A `CouplingPortEnhancedTrafficShaper` shall either define an `CouplingPortEnhancedTrafficShaper.etsAvailableBandwidthInPercent` or an `CouplingPortEnhancedTrafficShaper.etsAvailableBandwidthInWeightValue` value, but not both.

]

[constr_3786] Consistent usage of either `etsAvailableBandwidthInPercent` or `etsAvailableBandwidthInWeightValue` for `portScheduler = enhancedTrafficShaper`

Imposition time: IT_SysDesc

[All the `CouplingPortFifo` referenced by the same `CouplingPortScheduler` with `CouplingPortScheduler.portScheduler` equals to `EthernetCouplingPortSchedulerEnum.enhancedTrafficShaper` (according to [constr_3784]) shall define in their `CouplingPortEnhancedTrafficShaper` the same kind of value. All shall use either an `CouplingPortEnhancedTrafficShaper.etsAvailableBandwidthInPercent` or an `CouplingPortEnhancedTrafficShaper.etsAvailableBandwidthInWeightValue` value.

]

[constr_3787] Existence of `CouplingPortTrafficClassAssignment.trafficClass`

Imposition time: IT_SysDesc

[Every `CouplingPortTrafficClassAssignment` shall have a `trafficClass` attribute defined.

]

[constr_3788] Existence of `CouplingPortFifo.assignedTrafficClass`

Imposition time: IT_SysDesc

[For each `CouplingPortFifo`, exactly one value of attribute `CouplingPortFifo.assignedTrafficClass` shall exist.

]

[constr_3789] Allowed values for `CouplingPortFifo.assignedTrafficClass`

Imposition time: IT_SysDesc

[The allowed values for `CouplingPortFifo.assignedTrafficClass` are 0..65535.

]

[constr_3790] Existence of `CouplingPortDetails.defaultTrafficClass`

Imposition time: IT_SysDesc

[For each `CouplingPortDetails`, the attribute `CouplingPortDetails.defaultTrafficClass` shall exist.

]

[constr_3791] Allowed values for `CouplingPortDetails.defaultTrafficClass`

Imposition time: IT_SysDesc

[The allowed values for `CouplingPortDetails.defaultTrafficClass` are 0..65535.

]

[constr_3792] `FrameMapping` between identical bus systems

Status: DRAFT

Imposition time: IT_SysDesc

[The `FrameTriggerings` referenced in the role `sourceFrame` and `targetFrame` shall be owned by `PhysicalChannels` which in turn are owned by `CommunicationClusters` of the same kind.

]

[constr_4000] Local communication of mode switches

Imposition time: IT_EcuExt

[Ports with `ModeSwitchInterfaces` cannot be connected across ECU boundaries.

]

[constr_5029] J1939NmCluster is not allowed to reference a TtcanCluster

Imposition time: IT_SysDesc

[A [J1939NmCluster](#) is not allowed to reference a [TtcanCluster](#) in the role [communicationCluster](#).

]

[constr_5030] Uniqueness of LinOrderedConfigurableFrame.index

Imposition time: IT_SysDesc

[[LinOrderedConfigurableFrame.index](#) shall always be set and be unique in the context of the aggregating [LinCommunicationConnector](#).

]

[constr_5031] Uniqueness of FramePid.index

Imposition time: IT_SysDesc

[[FramePid.index](#) shall always be set and be unique in the context of the aggregating [AssignFrameIdRange](#).

]

[constr_5032] Maximal one NmConfig per System is allowed to be defined

Imposition time: IT_SysDesc

[Each [System](#) element is allowed to reference at most one [NmConfig](#) element with the [fibexElement](#) reference.

]

[constr_5049] Ethernet switch packet to traffic class assignment restriction

Imposition time: IT_SysDesc

[Every [CouplingPortTrafficClassAssignment](#) shall have at least one [priority](#) attribute defined.

]

[constr_5050] VariableDataPrototype of COM Based Transformer

Imposition time: IT_SysDesc

[The [VariableDataPrototype](#) of [TPS_SYST_02058] shall be typed by an [ApplicationRecordDataType](#) or an [ImplementationDataType](#) of category STRUCTURE.

]

[constr_5051] Existence of `CanFrameTriggering.identifier` in case of bus mirror target

Imposition time: IT_SysDesc

[The `CanFrameTriggering` of a `Frame` that contains a `Pdu` of which the `PduTriggering` is referenced by `BusMirrorChannelMappingCan` in the role `targetPduTriggering` shall not define an `identifier`.

]

[constr_5053] Existence of `ISignalPort.handleInvalid`

Imposition time: IT_SysDesc

[If the `ISignalPort` has a `networkRepresentationProps.invalidValue` defined then the `ISignalPort.communicationDirection` shall equal `in`.

]

[constr_5054] `externalReplacement` not applicable for `ISignalPort.handleInvalid`

Imposition time: IT_SysDesc

[In the context of `ISignalPort.handleInvalid` the value `externalReplacement` shall not be used.

]

[constr_5055] `DataMapping` of elements of `PRPortPrototypes` is not supported

Imposition time: IT_EcuExt

[A `DataMapping` shall not map elements of `PRPortPrototypes` to `SystemSignals`

]

[constr_5058] Value range for `CryptoServiceQueue.queueSize`

Imposition time: IT_SysDesc

[If the `CryptoServiceQueue.queueSize` is defined it shall have a value which is equal or greater than 1.

]

[constr_5060] Mapping of a `SecuredIPdu` into a `LinFrame` is not allowed

Imposition time: IT_SysDesc

[The mapping of a `SecuredIPdu` into a `LinFrame` with a `PduToFrameMapping` is not allowed.

]

[constr_5061] EthernetCommunicationConnectors and referencing SocketAddresses shall be in the same VLAN

Imposition time: IT_SysDesc

[Each `EthernetCommunicationConnector` that is referenced by a `SocketAddress` in the role `connector` or `multicastConnector` shall be referenced by the same `EthernetPhysicalChannel` that aggregates the `SoAdConfig` that in turn aggregates the `SocketAddress`.

]

[constr_5062] SOME/IP ProvidedServiceInstances of the same serviceInterface on one EcuInstance

Imposition time: IT_SysDesc

[Different `ProvidedServiceInstances` with the same `serviceIdentifier` and the same `majorVersion` and different `instanceIdentifiers` shall not be mapped to the same UDP/TCP port number and IP address combination that is represented by referenced `ApplicationEndpoint` and its referenced `NetworkEndpoint`.

]

[constr_5063] ProvidedServiceInstance.serviceIdentifier is mandatory

Imposition time: IT_SysDesc

[The `ProvidedServiceInstance.serviceIdentifier` is mandatory.

]

[constr_5064] ProvidedServiceInstance.majorVersion is mandatory

Imposition time: IT_SysDesc

[The `ProvidedServiceInstance.majorVersion` is mandatory.

]

[constr_5065] ProvidedServiceInstance.minorVersion is mandatory

Imposition time: IT_SysDesc

[The `ProvidedServiceInstance.minorVersion` is mandatory.

]

[constr_5066] ProvidedServiceInstance.instanceIdentifier is mandatory

Imposition time: IT_SysDesc

[The `ProvidedServiceInstance.instanceIdentifier` is mandatory.

]

[constr_5067] ProvidedServiceInstance shall be unique in respect of serviceIdentifier, instanceIdentifier, majorVersion

Imposition time: IT_SysDesc

[On a VLAN each `ProvidedServiceInstance` shall have a different `serviceIdentifier`, `instanceIdentifier` and `majorVersion` value combination.

]

[constr_5068] ProvidedServiceInstance.localUnicastAddress shall be IP Unicast

Imposition time: IT_SysDesc

[If defined, the `ProvidedServiceInstance.localUnicastAddress` shall point to an IP Unicast address.

]

[constr_5069] ProvidedServiceInstance.remoteUnicastAddress shall be IP Unicast

Imposition time: IT_SysDesc

[The `ProvidedServiceInstance.remoteUnicastAddress` shall point to an IP Unicast address.

]

[constr_5071] EventHandler.eventMulticastAddress reference target

Imposition time: IT_SysDesc

[The `ApplicationEndpoint` that is referenced by an `EventHandler` in the role `eventMulticastAddress` shall reference a `NetworkEndpoint` that defines an IP Multicast Address.

]

[constr_5072] EventHandler without defined eventMulticastAddress

Imposition time: IT_SysDesc

[If an `EventHandler` that is aggregated by a `ProvidedServiceInstance` does not have a defined `eventMulticastAddress` then the `multicastThreshold` shall be set to the value 0 (IP Unicast only).

]

[constr_5073] PduActivationRoutingGroup with eventGroupControlType set to activationUnicast or triggerUnicast or activationAndTriggerUnicast that is aggregated by an EventHandler

Imposition time: IT_SysDesc

[An EventHandler that aggregates a PduActivationRoutingGroup with the PduActivationRoutingGroup.eventGroupControlType set to activationUnicast or triggerUnicast or activationAndTriggerUnicast shall be aggregated by a ProvidedServiceInstance that has a localUnicastAddress reference that points to an IP Unicast Address.

]

[constr_5074] PduActivationRoutingGroup with eventGroupControlType set to activationMulticast that is aggregated by an EventHandler

Imposition time: IT_SysDesc

[An EventHandler that aggregates a PduActivationRoutingGroup with the PduActivationRoutingGroup.eventGroupControlType set to activationMulticast shall have an eventMulticastAddress reference that points to a "remote" IP Multicast Address. The ProvidedServiceInstance that aggregates the EventHandler shall have a localUnicastAddress reference to a "local" UDP ApplicationEndpoint.

]

[constr_5075] Allowed references of SoConIPduIdentifiers by PduActivationRoutingGroup with eventGroupControlType set to activationMulticast and allowed SoConIPduIdentifier references

Imposition time: IT_SysDesc

[A PduActivationRoutingGroup with eventGroupControlType set to activationMulticast is allowed to reference SoConIPduIdentifiers only in the iPduIdentifierUdp role.

]

[constr_5076] PduActivationRoutingGroup with iPduIdentifierTcp reference that is aggregated by a ProvidedServiceInstance

Imposition time: IT_SysDesc

[If the PduActivationRoutingGroup contains the iPduIdentifierTcp reference then the aggregating ProvidedServiceInstance shall contain a localUnicastAddress reference to an ApplicationEndpoint that defines a TCP address.

]

[constr_5077] PduActivationRoutingGroup with iPduIdentifierUdp reference that is aggregated by a ProvidedServiceInstance

Imposition time: IT_SysDesc

[If the PduActivationRoutingGroup contains the iPduIdentifierUdp reference then the aggregating ProvidedServiceInstance shall contain a localUnicastAddress reference to an ApplicationEndpoint that defines a UDP address.

]

[constr_5078] PduTriggerings referenced by a PduActivationRoutingGroup shall be on the same VLAN as the referencing PduActivationRoutingGroup

Imposition time: IT_SysDesc

[Each PduTriggering referenced by a PduActivationRoutingGroup via SoConIPduIdentifier shall be aggregated by the same VLAN (EthernetPhysicalChannel) to which the AbstractServiceInstance that aggregates the PduActivationRoutingGroup belongs via the localUnicastAddress.

]

[constr_5079] Service communication is restricted to one VLAN

Imposition time: IT_SysDesc

[All SocketAddress elements that are referenced by a AbstractServiceInstance with the localUnicastAddress and remoteUnicastAddress shall belong to the same VLAN (EthernetPhysicalChannel).

]

[constr_5080] ApplicationEndpoints referenced by EventHandlers and by the aggregating ProvidedServiceInstance shall be in the same VLAN

Imposition time: IT_SysDesc

[The ApplicationEndpoint that is referenced by an EventHandler in the role eventMulticastAddress shall belong to the same VLAN (EthernetPhysicalChannel) as the ApplicationEndpoint that is referenced by the localUnicastAddress reference from the ProvidedServiceInstance that aggregates the EventHandler.

]

[constr_5081] ConsumedServiceInstance.serviceIdentifier is mandatory

Imposition time: IT_SysDesc

[The ConsumedServiceInstance.serviceIdentifier is mandatory.

]

[constr_5082] ConsumedServiceInstance.majorVersion is mandatory*Imposition time:* IT_SysDesc[The `ConsumedServiceInstance.majorVersion` is mandatory.

]

[constr_5083] ConsumedServiceInstance.minorVersion is mandatory*Imposition time:* IT_SysDesc[The `ConsumedServiceInstance.minorVersion` is mandatory.

]

[constr_5084] ConsumedServiceInstance.instanceIdentifier is mandatory*Imposition time:* IT_SysDesc[The `ConsumedServiceInstance.instanceIdentifier` is mandatory.

]

[constr_5085] ConsumedServiceInstance.localUnicastAddress shall be IP Unicast*Imposition time:* IT_SysDesc[If defined, the `ConsumedServiceInstance.localUnicastAddress` shall point to an IP Unicast address.

]

[constr_5086] ConsumedServiceInstance.remoteUnicastAddress shall be IP Unicast*Imposition time:* IT_SysDesc[The `ConsumedServiceInstance.remoteUnicastAddress` shall point to an IP Unicast address.

]

[constr_5087] PduActivationRoutingGroup with eventGroupControlType set to activationUnicast or triggerUnicast or activationAndTriggerUnicast that is referenced by a ConsumedEventGroup*Imposition time:* IT_SysDesc[A `ConsumedEventGroup` that aggregates a `PduActivationRoutingGroup` with the `PduActivationRoutingGroup.eventGroupControlType` set to `activationUnicast` or `triggerUnicast` or `activationAndTriggerUnicast` shall be

aggregated by a `ConsumedServiceInstance` that has a `localUnicastAddress` reference that points to an IP Unicast Address.

]

[constr_5088] `PduActivationRoutingGroup` with `ipPduIdentifierTcp` reference that is aggregated by a `ConsumedServiceInstance`

Imposition time: IT_SysDesc

[If the `PduActivationRoutingGroup` contains the `ipPduIdentifierTcp` reference then the aggregating `ConsumedServiceInstance` shall contain a `localUnicastAddress` reference to an `ApplicationEndpoint` that defines a TCP address.

]

[constr_5089] `PduActivationRoutingGroup` with `ipPduIdentifierUdp` reference that is aggregated by a `ConsumedServiceInstance`

Imposition time: IT_SysDesc

[If the `PduActivationRoutingGroup` contains the `ipPduIdentifierUdp` reference then the aggregating `ConsumedServiceInstance` shall contain a `localUnicastAddress` reference to an `ApplicationEndpoint` that defines a UDP address.

]

[constr_5090] `ApplicationEndpoints` referenced by `ConsumedEventGroups` and by the aggregating `ConsumedServiceInstance` shall be in the same VLAN

Imposition time: IT_SysDesc

[The `ApplicationEndpoint` that is referenced by an `ConsumedEventGroup` in the role `eventMulticastAddress` shall belong to the same VLAN (`EthernetPhysicalChannel`) as the `ApplicationEndpoint` that is referenced by the `localUnicastAddress` reference from the `ConsumedServiceInstance` that aggregates the `ConsumedEventGroup`.

]

[constr_5091] Relevance of `tcpRole` attribute

Imposition time: IT_SysDesc

[The attribute `tcpRole` shall only exist if the `StaticSocketConnection` is aggregated by a `SocketAddress` that defines a TCP Port in the aggregated `ApplicationEndpoint`.

]

[constr_5092] Local and remoteAddress of a StaticSocketConnection shall define the same transport protocol

Imposition time: IT_SysDesc

[The transport protocol that is defined by the `SocketAddress` that aggregates the `StaticSocketConnection` shall be the same in the `SocketAddress` that is referenced by the same `StaticSocketConnection` in the role `remoteAddress`.

]

[constr_5093] pncGatewayType and PhysicalChannel

Imposition time: IT_SysDesc

[When multiple `CommunicationConnectors` with `pncGatewayType` set to a value other than `none` are referenced by the same `PhysicalChannel` then only up to one `CommunicationConnector` shall have the `pncGatewayType` set to `active`.

]

[constr_5094] pncGatewayType and ECU

Imposition time: IT_SysDesc

[When an ECU is connected to more than one `PhysicalChannel` and has a relation to a Partial Network then all `CommunicationConnectors` of this ECU where this Partial Network is related to shall have the `pncGatewayType` value either set to `none` or to a value different than none (i.e. `active` or `passive`).

]

[constr_5095] Relationship between the timing behavior of the ConsumedEventGroup retry and the timing behavior of an Offer message

Imposition time: IT_SysDesc

[The timing behavior for a retry to a `ConsumedEventGroup` (`subscribeEventgroupRetryMax`, `subscribeEventgroupRetryDelay`) shall not overlap to the timing behavior (`SomeipSdServerServiceInstanceConfig.offerCyclicDelay`) of the corresponding `ProvidedServiceInstance`.

]

[constr_5096] ConsumedEventGroup with value subscribeEventgroupRetryMax set to 255

Imposition time: IT_SysDesc

[Retry to a `ConsumedEventGroup` with value `subscribeEventgroupRetryMax` set to 255 is only allowed if the `SomeipSdServerServiceInstanceConfig.of-`

`ferCyclicDelay` is set 0 and `serviceOfferTimeToLive` is set to 0xfffff of the corresponding `ProvidedServiceInstance`.

]

[constr_5097] `DltLogChannel.txPduTriggering` and `DltLogChannel.rxPduTriggering` shall point to `GeneralPurposeIPdus` of category DLT

Imposition time: IT_SysDesc

[`DltLogChannel` shall only reference `PduTriggerings` that are pointing to `GeneralPurposeIPdus` of category DLT in the roles `txPduTriggering` and `rxPduTriggering`.

]

[constr_5100] Compatibility of two `MetaDataItemSets`

Imposition time: IT_SysDesc

[Under the condition that sender and receiver typed by a `SenderReceiverInterface` use meta-data and are mapped to the same `EcuInstance` the following condition applies: two `MetaDataItemSets` are compatible if all of the following conditions are fulfilled:

- They aggregate the same number of `MetaDataItems`.
- The value of `MetaDataItem.length` of corresponding `MetaDataItems` is identical.
- The value of `MetaDataItem.metaDataItemType` of corresponding `MetaDataItems` is identical.

]

[constr_5101] Consistent Definition of meta-data

Imposition time: IT_SysDesc

[If the `dataElement` referenced by a `SenderReceiverToSignalMapping` is also referenced by a `MetaDataItemSet` in the role `dataElement` and the mapping via `SystemSignal`, `ISignal`, and `ISignalToIPduMapping` down to an `ISignalIPdu` exists then all other `dataElements` that are also mapped to the same `ISignalIPdu` shall either

- not be referenced by a `MetaDataItemSet` in the role `dataElement` (i.e. does not make use of meta-data) or
- the definition of meta-data in the context of the affected `SenderReceiverInterfaces` is compatible (according to the definition of compatible specification of meta-data described in [constr_5100]).

]

[constr_5104] Assignment of a FlexrayFrame where allowDynamicLSduLength is set to true

Imposition time: IT_SysDesc

[FlexrayFrames which are referenced by a FlexrayFrameTriggering where allowDynamicLSduLength is set to true shall always be assigned to the dynamic segment.

]

[constr_5105] Mapping of Pdu with dynamic length in a FlexrayFrame

Imposition time: IT_SysDesc

[Only the last Pdu in a FlexrayFrame is allowed to qualify according to [TPS_SYST_-03085] to be of dynamic length.

]

[constr_5106] ISignalGroup and ISignal referenced from ISignalTriggering

Imposition time: IT_SysDesc

[Either an ISignalGroup and all ISignals referenced from the ISignalGroup are also referenced from ISignalTriggerings aggregated at the same PhysicalChannel or neither the ISignalGroup nor any of the ISignals referenced by the ISignalGroup shall be referenced from ISignalTriggerings.

]

[constr_5110] Search for a collection of ServiceInstances is not supported

Imposition time: IT_SysDesc

[The ConsumedServiceInstance.instanceIdentifier is not allowed to be set to the value ANY or ALL.

]

[constr_5111] Existence of references TlvDataIdDefinition.tlvArgument, TlvDataIdDefinition.tlvRecordElement, and TlvDataIdDefinition.tlvImplementationDataTypeElement

Imposition time: IT_SysDesc

[For each TlvDataIdDefinition, only one out of the following references shall exist:

- reference to ArgumentDataPrototype in the role tlvArgument
- reference to ApplicationRecordElement in the role tlvRecordElement

- reference to `ImplementationDataTypeElement` in the role `tlvImplementationDataTypeElement`.

]

[constr_5112] `ImplementationDataType` needs to be defined if a "new-world" variable-size `ApplicationArrayDataType` is mapped to a single `SystemSignal`

Imposition time: IT_EcuExt

[A `SenderReceiverInterface.dataElement` that is typed by a "new-world" variable-size `ApplicationArrayDataType` according to [TPS_SWCT_01644] (see definition in Software Component Template [2]) is only allowed to be mapped to a single `SystemSignal` by the `SenderReceiverToSignalMapping` if a `DataTypeMap` exists that points to both the `ApplicationArrayDataType` and an `ImplementationDataType` that fulfills the conditions of a "new-world" dynamic size array data type according to [TPS_SWCT_01645] (see definition in Software Component Template [2]).

]

[constr_5113] Mapping of "old-world" variable size arrays to a single `SystemSignal` is not supported.

Imposition time: IT_EcuExt

[The `SenderReceiverToSignalMapping` is not allowed to map a `dataElement` that is typed by an "old-world" variable size array defined by [TPS_SWCT_01641] and [TPS_SWCT_01642] (see definition in Software Component Template [2]) to a single `SystemSignal`.

]

[constr_5114] Semantics of `InterpolationRoutine.isDefault`

Imposition time: IT_SysDesc

[For each `SwRecordLayout` that is referenced by one or more `InterpolationRoutineMappings` that are aggregated by `InterpolationRoutineMappingSets` that are referenced from a `System` in the role `interpolationRoutineMappingSet`, only one of the collection of aggregated `InterpolationRoutines` shall have attribute `isDefault` set to True.

]

[constr_5116] Uniqueness of the symbols of software-components and BSW modules

Imposition time: IT_EcuExt

[For all `SwComponentPrototypes` typed by an `ApplicationSwComponentType`, `NvBlockSwComponentType` or `SensorActuatorSwComponentType` mapped to a given `EcuInstance` by means of `SwcToEcuMapping` respectively `SwcToApplicationPartitionMapping` and `ApplicationPartitionToEcuPartitionMapping` the following restriction applies:

The symbolic name of an `AtomicSwComponentType` referenced by a respective `SwComponentPrototype` in the role `type` shall not overlap with the module implementation prefix (MIP) of any of the basic software-modules existing on the `EcuInstance`.

The symbolic name of an `AtomicSwComponentType` is derived from the value of

- `AtomicSwComponentType.symbol`, or if this attribute does not exist
- `AtomicSwComponentType.shortName`.

]

[constr_5117] Client-Server communication over Ethernet

Imposition time: IT_SysDesc

[A `SystemSignal` that is referenced by a `ClientServerToSignalMapping` in the role `callSignal` or `returnSignal` shall only be referenced by an `ISignal` that in turn is referenced by an `ISignalTriggering` aggregated by an `EthernetPhysicalChannel`.

]

[constr_5118] Value range of `UdpProps.udpTtl`

Imposition time: IT_SysDesc

[If defined, the value of `UdpProps.udpTtl` shall be in the range of 1..255.

]

[constr_5119] Value range of `TcpProps.tcpTtl`

Imposition time: IT_SysDesc

[If defined, the value of `TcpProps.tcpTtl` shall be in the range of 1..255.

]

[constr_5120] Value range of `TcpProps.tcpDelayedAckTimeout`*Imposition time:* IT_SysDesc

[If defined, the value of `TcpProps.tcpDelayedAckTimeout` shall be in the range of 0..0.5.

]

[constr_5121] Value range of `TcpProps.tcpSynMaxRtx`*Imposition time:* IT_SysDesc

[If defined, the value of `TcpProps.tcpSynMaxRtx` shall be in the range of 0..255.

]

[constr_5122] Value range of `TcpProps.tcpMaxRtx`*Imposition time:* IT_SysDesc

[If defined, the value of `TcpProps.tcpMaxRtx` shall be in the range of 0..255.

]

[constr_5123] Value range of `TcpProps.tcpKeepAliveProbesMax`*Imposition time:* IT_SysDesc

[If defined, the value of `TcpProps.tcpKeepAliveProbesMax` shall be in the range of 0..65535.

]

[constr_5124] Value range of `TcpProps.tcpReceiveWindowMax`*Imposition time:* IT_SysDesc

[If defined, the value of `TcpProps.tcpReceiveWindowMax` shall be in the range of 0..65535.

]

[constr_5125] Value range of `TcpIpIcmpv4Props.tcpIpIcmpV4Ttl`*Imposition time:* IT_SysDesc

[If defined, the value of `TcpIpIcmpv4Props.tcpIpIcmpV4Ttl` shall be in the range of 1..255.

]

[constr_5126] Value range of `Ipv4ArpProps.tcpIpArpNumGratuitousArpOnStartup`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv4ArpProps.tcpIpArpNumGratuitousArpOnStartup` shall be in the range of 0..255.

]

[constr_5127] Value range of `Ipv4FragmentationProps.tcpIpIpNumFragments`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv4FragmentationProps.tcpIpIpNumFragments` shall be in the range of 0..255.

]

[constr_5128] Value range of `Ipv4FragmentationProps.tcpIpIpNumReassDgrams`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv4FragmentationProps.tcpIpIpNumReassDgrams` shall be in the range of 0..65535.

]

[constr_5129] Value range of `Ipv6FragmentationProps.tcpIpIpReassembly-BufferCount`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6FragmentationProps.tcpIpIpReassembly-BufferCount` shall be in the range of 0..255.

]

[constr_5130] Value range of `Ipv6FragmentationProps.tcpIpIpReassembly-BufferSize`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6FragmentationProps.tcpIpIpReassembly-BufferSize` shall be in the range of 1500..65535.

]

[constr_5131] Value range of `Ipv6FragmentationProps.tcpIpIpReassemblyTimeout`

Imposition time: IT_SysDesc

[If defined, the value of `Ipv6FragmentationProps.tcpIpIpReassemblyTimeout` shall be in the range of 0.001..100.

]

[constr_5132] Value range of `Ipv6FragmentationProps.tcpIpIpReassemblySegmentCount`

Imposition time: IT_SysDesc

[If defined, the value of `Ipv6FragmentationProps.tcpIpIpReassemblySegmentCount` shall be in the range of 1..255.

]

[constr_5133] Value range of `Ipv6FragmentationProps.tcpIpIpTxFragmentBufferCount`

Imposition time: IT_SysDesc

[If defined, the value of `Ipv6FragmentationProps.tcpIpIpTxFragmentBufferCount` shall be in the range of 1..1000.

]

[constr_5134] Value range of `Ipv6FragmentationProps.tcpIpIpTxFragmentBufferSize`

Imposition time: IT_SysDesc

[If defined, the value of `Ipv6FragmentationProps.tcpIpIpTxFragmentBufferSize` shall be in the range of 1500..65535.

]

[constr_5135] Value range of `Dhcpv6Props.tcpIpDhcpV6CnfDelayMin` and `Dhcpv6Props.tcpIpDhcpV6CnfDelayMax`

Imposition time: IT_SysDesc

[If defined, the value of `Dhcpv6Props.tcpIpDhcpV6CnfDelayMin` and the value of `Dhcpv6Props.tcpIpDhcpV6CnfDelayMax` shall be in the range of 0..100 and the value of `Dhcpv6Props.tcpIpDhcpV6CnfDelayMax` shall be greater than the value of `Dhcpv6Props.tcpIpDhcpV6CnfDelayMin`.

]

[constr_5136] Value range of `Dhcpv6Props.tcpIpDhcpV6InfDelayMin` and `Dhcpv6Props.tcpIpDhcpV6InfDelayMax`

Imposition time: IT_SysDesc

[If defined, the value of `Dhcpv6Props.tcpIpDhcpV6InfDelayMin` and the value of `Dhcpv6Props.tcpIpDhcpV6InfDelayMax` shall be in the range of 0..100 and the value of `Dhcpv6Props.tcpIpDhcpV6InfDelayMax` shall be greater than the value of `Dhcpv6Props.tcpIpDhcpV6InfDelayMin`.

]

[constr_5137] Value range of `Dhcpv6Props.tcpIpDhcpV6SolDelayMin` and `Dhcpv6Props.tcpIpDhcpV6SolDelayMax`

Imposition time: IT_SysDesc

[If defined, the value of `Dhcpv6Props.tcpIpDhcpV6SolDelayMin` and the value of `Dhcpv6Props.tcpIpDhcpV6SolDelayMax` shall be in the range of 0..100 and the value of `Dhcpv6Props.tcpIpDhcpV6SolDelayMax` shall be greater than the value of `Dhcpv6Props.tcpIpDhcpV6SolDelayMin`.

]

[constr_5138] Value range of `Ipv6NdpProps.tcpIpNdpSlaacDadNumberOfTransmissions`

Imposition time: IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpSlaacDadNumberOfTransmissions` shall be in the range of 0..254.

]

[constr_5139] Value range of `Ipv6NdpProps.tcpIpNdpSlaacDadRetransmissionDelay`

Imposition time: IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpSlaacDadRetransmissionDelay` shall be in the range of 0..10.

]

[constr_5140] Value range of `Ipv6NdpProps.tcpIpNdpDefaultReachableTime`

Imposition time: IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpDefaultReachableTime` shall be in the range of 0..120.

]

[constr_5141] Value range of `Ipv6NdpProps.tcpIpNdpDefaultRetransTimer`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpDefaultRetransTimer` shall be in the range of 0..60.

]

[constr_5142] Value range of `Ipv6NdpProps.tcpIpNdpNumUnicastSolicitations`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpNumUnicastSolicitations` shall be in the range of 0..255.

]

[constr_5143] Value range of `Ipv6NdpProps.tcpIpNdpNumMulticastSolicitations`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpNumMulticastSolicitations` shall be in the range of 0..255.

]

[constr_5144] Value range of `Ipv6NdpProps.tcpIpNdpDelayFirstProbeTimeValue`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpDelayFirstProbeTimeValue` shall be in the range of 0..60.

]

[constr_5145] Value range of `Ipv6NdpProps.tcpIpNdpMinRandomFactor`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpMinRandomFactor` shall be in the range of 0..100.

]

[constr_5146] Value range of `Ipv6NdpProps.tcpIpNdpMaxRandomFactor`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpMaxRandomFactor` shall be in the range of 0..100.

]

[constr_5147] Value range of `Ipv6NdpProps.tcpIpNdpDestinationCacheSize`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpDestinationCacheSize` shall be in the range of 1..254.

]

[constr_5148] Value range of `Ipv6NdpProps.tcpIpNdpPrefixListSize`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpPrefixListSize` shall be in the range of 1..254.

]

[constr_5149] Value range of `Ipv6NdpProps.tcpIpNdpDefaultRouterListSize`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpDefaultRouterListSize` shall be in the range of 2..254.

]

[constr_5151] Value range of `Ipv6NdpProps.tcpIpNdpMaxRtrSolicitations`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpMaxRtrSolicitations` shall be in the range of 0..255.

]

[constr_5152] Value range of `Ipv6NdpProps.tcpIpNdpMaxRtrSolicitationDelay`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpMaxRtrSolicitationDelay` shall be in the range of 0.001..60.

]

[constr_5153] Value range of `Ipv6NdpProps.tcpIpNdpRtrSolicitationInterval`*Imposition time:* IT_SysDesc

[If defined, the value of `Ipv6NdpProps.tcpIpNdpRtrSolicitationInterval` shall be in the range of 0.001..60.

]

[constr_5154] Value range of `TcpIpIcmpv6Props.tcpIpIcmpV6HopLimit`

Imposition time: IT_SysDesc

[If defined, the value of `TcpIpIcmpv6Props.tcpIpIcmpV6HopLimit` shall be in the range of 1..255.

]

[constr_5157] Mixing of Point-To-Point and Multi-Drop is not allowed in a `CouplingPortConnection`

Imposition time: IT_SysDesc

[The `CouplingPortConnection` is allowed to reference a `CouplingPort` either:

- in the role `firstPort` and/or `secondPort` or
- in the role `nodePort`

]

[constr_5158] Usage of `plcaProps` only allowed on 10BASE-T1S networks

Imposition time: IT_SysDesc

[A `CouplingPort` is allowed to aggregate `plcaProps` only if:

- the `CouplingPort.physicalLayerType` is set to 10BASE-T1S
- the `CouplingPort.macLayerType` is set to xMII
- the `CouplingPort` is referenced by a `CouplingPortConnection` with the `nodePort` reference.

]

[constr_5159] Mandatory `CouplingPortConnection` settings if multi-drop feature is used

Imposition time: IT_SysDesc

[If a `CouplingPortConnection` uses the `nodePort` reference then the attribute `CouplingPortConnection.plcaLocalNodeCount` and the attribute `CouplingPortConnection.plcaTransmitOpportunityTimer` shall be set to a value.

]

[constr_5160] Mandatory `PlcaProps` settings if multi-drop feature is used

Imposition time: IT_SysDesc

[If a `CouplingPort` is referenced by a `CouplingPortConnection` in the role `nodePort` then the `CouplingPort` shall aggregate the `PlcaProps` and the following attributes shall be set to a value:

- `plcaMaxBurstCount`
- `plcaMaxBurstTimer`
- `plcaLocalNodeId`

]

[constr_5162] Valid `TextTableMapping` in the context of `Sender-RecRecordElementMapping`*Imposition time:* `IT_EcuExt`

[The aggregation of a `TextTableMapping` at `SenderRecRecordElementMapping` is only valid if the `SenderRecRecordElementMapping` also references a `SystemSignal` in the role `systemSignal`.

]

[constr_5163] Existence of attribute `IPSecRule.headerType`*Imposition time:* `IT_SysDesc`

[For each `IPSecRule`, the attribute `headerType` shall exist.

]

[constr_5164] Existence of attribute `IPSecRule.ipProtocol`*Imposition time:* `IT_SysDesc`

[For each `IPSecRule`, the attribute `ipProtocol` shall exist.

]

[constr_5165] Existence of attribute `IPSecRule.policy`*Imposition time:* `IT_SysDesc`

[For each `IPSecRule`, the attribute `policy` shall exist.

]

[constr_5166] Existence of `IPduMapping.pduMaxLength`*Imposition time:* `IT_SysDesc`

[If several `IPduMappings` refer to the same `PduTriggering` in `IPduMapping.sourceIPdu`, then all of these `IPduMappings` shall provide either no `IPduMapping.pduMaxLength` value, or the same `IPduMapping.pduMaxLength` value.

]

[constr_5167] pncGatewayType and ECU over the whole system

Imposition time: IT_SysDesc

[Only one PNC Gateway ECU in the whole System shall exist that sets on all its CommunicationConnectors the pncGatewayType to active.

]

[constr_5168] pncGatewayType passive and connected ECUs

Imposition time: IT_SysDesc

[For all CommunicationConnectors with pncGatewayType set to passive belonging to one PNC Gateway ECU, all connected counterpart CommunicationConnectors, where pncGatewayType is set to active shall belong to one ECU, if dynamicPncToChannelMappingEnabled is set to TRUE for at least one of the affected CommunicationConnectors.

]

[constr_5170] nmPassiveModeEnabled and dynamicPncToChannelMappingEnabled

Imposition time: IT_SysDesc

[If nmPassiveModeEnabled is set to TRUE on a NmNode then dynamicPncToChannelMappingEnabled shall be set to FALSE on the according CommunicationConnector referring to the same CommunicationController.

]

[constr_5175] RtePluginProps shall reference at least one EcucContainerValue representing a RteRipsPlugin

Imposition time: IT_EcuExt

[If a FlatInstanceDescriptor owns are RtePluginProps this RtePluginProps shall define the associatedRtePlugin reference and/or the associatedCrossSwClusterComRtePlugin reference.

]

[constr_5176] Existence of CpSoftwareCluster of category HOST_SOFTWARE_CLUSTER on one EcuInstance

Imposition time: IT_SwCluSysDesc

[On each EcuInstance, exactly one CpSoftwareCluster of category HOST_SOFTWARE_CLUSTER shall exist.

]

[constr_5177] Validity of reference `CpSoftwareClusterToEcuInstanceMapping.swCluster`

Imposition time: IT_SwCluSysDesc

[A `CpSoftwareClusterToEcuInstanceMapping` that references a given `CpSoftwareCluster` in the role `CpSoftwareClusterToEcuInstanceMapping.swCluster` shall be aggregated by the same `System` (in the role `System.mapping.swMapping`) that also refers to the referenced `CpSoftwareCluster` in the role `System.swCluster`.

]

[constr_5178] Existence of attribute `CpSoftwareClusterResource.globalResourceId`

Imposition time: IT_ResPool

[For each `CpSoftwareClusterResource`, attribute `globalResourceId` shall exist.

]

[constr_5179] Existence of attribute `CpSoftwareClusterResource.isMandatory`

Imposition time: IT_ResPool

[For each `CpSoftwareClusterResource`, attribute `isMandatory` shall exist.

]

[constr_5180] Allowed values for `CpSoftwareClusterResource.globalResourceId`

Imposition time: IT_ResPool

[Attribute `CpSoftwareClusterResource.globalResourceId` shall not be set to 0.

]

[constr_5181] Existence of attribute `CpSoftwareClusterServiceResource.category`

Imposition time: IT_ResPool

[For each `CpSoftwareClusterServiceResource`, attribute `category` shall exist.

]

[constr_5182] PRPortPrototypes are excluded as CpSoftwareCluster interfaces

Imposition time: IT_SwCluSysDesc

[A CpSoftwareClusterCommunicationResource is not allowed to be mapped by a PortElementToCommunicationResourceMapping to an element of a PortInterface in the context of a PRPortPrototype.

]

[constr_5183] PortElementToCommunicationResourceMapping shall reference exactly one element of a PortInterface

Imposition time: IT_SwCluSysDesc

[For any given PortElementToCommunicationResourceMapping, either the reference

- parameterDataPrototype or
- modeDeclarationGroupPrototype or
- trigger or
- clientServerOperation or
- variableDataPrototype

shall exist.

]

[constr_5184] CpSoftwareClusterServiceResource can be provided only once on an EcuInstance

Imposition time: IT_SwCluSysDesc

[A CpSoftwareClusterServiceResource shall not be mapped by several CpSoftwareClusterToResourceMappings to CpSoftwareClusters in the provider role if the CpSoftwareClusters are mapped to the same EcuInstance by CpSoftwareClusterToEcuInstanceMappings.

]

[constr_5185] Existence of attribute BinaryManifestProvideResource.globalResourceId

Imposition time: IT_BinObjMetaData

[For each BinaryManifestProvideResource, attribute globalResourceId shall exist.

]

[constr_5186] Existence of attribute `BinaryManifestProvideResource.resourceGuardValue`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestProvideResource`, attribute `resourceGuardValue` shall exist.

]

[constr_5187] Existence of attribute `BinaryManifestProvideResource.supportsMultipleNotifierSets`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestProvideResource`, attribute `supportsMultipleNotifierSets` shall exist.

]

[constr_5188] Existence of attribute `BinaryManifestProvideResource.numberOfNotifierSets`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestProvideResource`, attribute `numberOfNotifierSets` shall exist.

]

[constr_5189] Existence of reference `BinaryManifestProvideResource.resourceDefinition`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestProvideResource`, the reference in the role `resourceDefinition` shall exist.

]

[constr_5190] Existence of aggregation `BinaryManifestProvideResource.item`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestProvideResource`, the aggregation in the role `item` shall exist at least once.

]

[constr_5191] Consequence of attribute `BinaryManifestProvideResource.item.category`

Imposition time: IT_BinObjMetaData

[The following values of attribute `BinaryManifestProvideResource.item.category` shall require the existence of aggregations:

- If `category` is set to `PROVIDER_HANDLE` and the attribute `isUnused` is not set to true then the aggregation `BinaryManifestProvideResource.item.value` shall exist
- If `category` is set to `NOTIFIER_HANDLE` and the attribute `isUnused` is not set to true then the aggregation `BinaryManifestProvideResource.item.defaultValue` shall exist
- If `category` is set to `AUXILARY_ACTUAL_NUMBER_NOTIFIER_SETS` then the aggregation `BinaryManifestProvideResource.item.defaultValue` shall exist

]

[constr_5192] Existence of attribute `BinaryManifestRequireResource.globalResourceId`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestRequireResource`, attribute `globalResourceId` shall exist.

]

[constr_5193] Existence of attribute `BinaryManifestRequireResource.resourceGuardValue`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestRequireResource`, attribute `resourceGuardValue` shall exist.

]

[constr_5194] Existence of reference `BinaryManifestRequireResource.resourceDefinition`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestRequireResource`, the reference in the role `resourceDefinition` shall exist.

]

[constr_5195] Existence of aggregation `BinaryManifestRequireResource.item`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestRequireResource`, the aggregation in the role `item` shall exist at least once.

]

[constr_5196] Consequence of attribute `BinaryManifestRequireResource.item.category`

Imposition time: IT_BinObjMetaData

[The following values of attribute `BinaryManifestRequireResource.item.category` shall require the existence of aggregations:

- If `category` is set to `PROVIDER_HANDLE` then the aggregation `BinaryManifestRequireResource.item.defaultValue` shall exist
- If `category` is set to `NOTIFIER_HANDLE` then the aggregation `BinaryManifestRequireResource.item.value` shall exist

]

[constr_5197] Existence of aggregation `BinaryManifestResourceDefinition.itemDefinition`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestResourceDefinition`, the aggregation in the role `itemDefinition` shall exist at least once.

]

[constr_5198] Allowed `BinaryManifestResource.resourceDefinition`

Imposition time: IT_BinObjMetaData

[An `BinaryManifestResourceDefinition` shall only be referenced from a `BinaryManifestResource` that is aggregated in the same `CpSoftwareClusterBinaryManifestDescriptor` as the referenced `BinaryManifestResourceDefinition`.

]

[constr_5199] Consequence of attribute `BinaryManifestItem.auxiliaryField.category`

Imposition time: IT_BinObjMetaData

[If attribute `BinaryManifestItem.auxiliaryField.category` is set to value `AUXILARY_CONNECTED_SW_CLUSTER_ID` then attribute `BinaryManifestItem.auxiliaryField.defaultValue` shall exist.

]

[constr_5200] Existence of attribute `BinaryManifestItemDefinition.category`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestItemDefinition`, attribute `category` shall exist.

]

[constr_5201] Existence of attribute `BinaryManifestItemDefinition.size`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestItemDefinition`, attribute `size` shall exist.

]

[constr_5202] Existence of attribute `BinaryManifestItemNumericalValue.value`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestItemNumericalValue`, attribute `value` shall exist.

]

[constr_5203] Existence of attribute `BinaryManifestItemPointerValue.symbol`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestItemPointerValue`, attribute `symbol` shall exist.

]

[constr_5204] Existence of attribute `BinaryManifestMetaDataField.category`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestMetaDataField`, attribute `category` shall exist.

]

[constr_5205] Existence of attribute `BinaryManifestMetaDataField.size`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestMetaDataField`, attribute `size` shall exist.

]

[constr_5206] Existence of attribute `BinaryManifestMetaDataField.symbol`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestMetaDataField`, attribute `symbol` shall exist .

]

[constr_5207] Existence of attribute `BinaryManifestMetaDataField.address`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestMetaDataField`, attribute `address` shall exist.

]

[constr_5208] Existence of `System.swCluster`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` SW_CLUSTER_SYSTEM_DESCRIPTION, the reference `System.swCluster` shall exist at least once.

]

[constr_5209] Existence of reference `CpSoftwareCluster.swComponentAssignment.swComponent`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` SW_CLUSTER_SYSTEM_DESCRIPTION, the reference `System.swCluster.swComponentAssignment.swComponent` shall exist.

]

[constr_5210] Existence of reference `SystemMapping.portElementToComResourceMapping`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` SW_CLUSTER_SYSTEM_DESCRIPTION, the reference `System.mapping.portElementToComResourceMapping` shall exist at least once.

]

[constr_5211] Existence of reference `PortElementToCommunicationResourceMapping.communicationResource`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` `SW_CLUSTER_SYSTEM_DESCRIPTION`, the reference `System.mapping.portElementToComResourceMapping.communicationResource` shall exist at least once.

]

[constr_5212] Existence of reference `SystemMapping.resourceToApplicationPartitionMapping`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` `SW_CLUSTER_SYSTEM_DESCRIPTION`, the reference `System.mapping.resourceToApplicationPartitionMapping` shall exist.

]

[constr_5213] Existence of reference `CpSoftwareClusterResourceToApplicationPartitionMapping.applicationPartition`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` `SW_CLUSTER_SYSTEM_DESCRIPTION`, the reference `System.mapping.resourceToApplicationPartitionMapping.applicationPartition` shall exist.

]

[constr_5214] Existence of reference `CpSoftwareClusterResourceToApplicationPartitionMapping.resource`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` `SW_CLUSTER_SYSTEM_DESCRIPTION`, the reference `System.mapping.resourceToApplicationPartitionMapping.resource` shall exist.

]

[constr_5215] Existence of reference `CpSoftwareClusterToResourceMapping.serviceResource`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` `SW_CLUSTER_SYSTEM_DESCRIPTION`, the reference `System.mapping.softwareClusterToResourceMapping.serviceResource` shall exist.

]

[constr_5216] Existence of reference `CpSoftwareClusterToResourceMapping.requester` and/or `provider`

Imposition time: IT_SwCluSysDesc

[In a `System` with `category` `SW_CLUSTER_SYSTEM_DESCRIPTION`, at least one of the references `System.mapping.softwareClusterToResourceMapping.requester` or `System.mapping.softwareClusterToResourceMapping.provider` shall exist.

]

[constr_5217] Existence of attribute `BinaryManifestMetaDataField.value`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestMetaDataField` of `category` `IMMUTABLE_TABLES_CHECKSUM`, attribute `value` shall exist.

]

[constr_5218] Existence of attribute `BinaryManifestItemPointerValue.address`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestItemPointerValue`, attribute `address` shall exist.

]

[constr_5219] `CpSoftwareCluster` shall only be mapped to one `EcuInstance`

Imposition time: IT_SwCluSysDesc

[Within the context of one `CpSoftwareCluster`, for all `CpSoftwareCluster.swComponentAssignment.swComponent` (and nested instances of `SwComponentPrototypes`) that are referenced by a `SwcToEcuMapping` in the role `component` the following condition shall be fulfilled: all referencing `SwcToEcuMappings` shall refer to the same `EcuInstance` in the role `ecuInstance` and this `EcuInstance` shall also be referenced in the role `ecuInstance` by all `CpSoftwareClusterToEcuInstanceMappings` that also refer to said `CpSoftwareCluster` in the role `swCluster`.

]

[constr_5220] Multiplicity of `EndToEndTransformationISignalProps.sourceId` in `PROFILE_04m`, `PROFILE_07m`, `PROFILE_08m` and `PROFILE_44m`

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to `PROFILE_04m`, `PROFILE_07m`, `PROFILE_08m`, or `PROFILE_44m` then the multiplic-

ity of the `EndToEndTransformationISignalProps.sourceId` attribute shall be 1.

]

[constr_5221] Multiplicity of `EndToEndTransformationISignalProps.sourceId` in PROFILE_01, PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_11, PROFILE_22, and PROFILE_76

Imposition time: IT_SysDesc

[If the `EndToEndTransformationDescription.profileName` attribute is set to PROFILE_01, PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_11, PROFILE_22, or PROFILE_76 then the multiplicity of the `EndToEndTransformationISignalProps.sourceId` attribute shall be 0.

]

[constr_5222] Mandatory elements of `UdpNmCluster`

Imposition time: IT_SysDesc

[The following attributes shall always be defined for the `UdpNmCluster`:

- `nmMsgCycleTime`
- `nmMessageTimeoutTime`
- `nmNetworkTimeout`
- `nmRemoteSleepIndicationTime`
- `nmRepeatMessageTime`
- `nmWaitBusSleepTime`
- `communicationCluster`

]

[constr_5223] Mandatory elements of `UdpNmNode`

Imposition time: IT_SysDesc

[The following attributes shall always be defined for the `UdpNmNode`:

- `nmMsgCycleOffset`

]

[constr_5224] `UdpNmNode.nmMsgCycleOffset` < `UdpNmCluster.nmMsgCycleTime`

Imposition time: IT_SysDesc

[The value of `UdpNmNode.nmMsgCycleOffset` shall be smaller than the value of `UdpNmCluster.nmMsgCycleTime`.

]

[constr_5225] `UdpNmCluster.nmNetworkTimeout` multiple of `UdpNmCluster.nmMsgCycleTime`

Imposition time: IT_SysDesc

[The value of `UdpNmCluster.nmNetworkTimeout` shall be $n * \text{UdpNmCluster.nmMsgCycleTime}$ with $n > 1$.

]

[constr_5226] `UdpNmCluster.nmRepeatMessageTime` multiple of `UdpNmCluster.nmMsgCycleTime`

Imposition time: IT_SysDesc

[The value of `UdpNmCluster.nmRepeatMessageTime` shall be $n * \text{UdpNmCluster.nmMsgCycleTime}$.

]

[constr_5229] Existence of attribute `E2EProfileCompatibilityProps.transitToInvalidExtended` is mandatory for each `EndToEndTransformationDescription`

Imposition time: IT_SysDesc

[For each `EndToEndTransformationDescription`, a reference to `E2EProfileCompatibilityProps` in the role `e2eProfileCompatibilityProps` shall exist and the referenced `E2EProfileCompatibilityProps` shall define a value for the attribute `transitToInvalidExtended`.

]

[constr_5231] Allowed values for `SOMEIPTransformationProps.alignment` and `SOMEIPTransformationDescription.alignment`

Imposition time: IT_SysDesc

[The valid values for `SOMEIPTransformationProps.alignment` and `SOMEIPTransformationDescription.alignment` shall be 8, 16, 32, 64, 128 or 256.

]

[constr_5232] Triggering in case of application writing the selector field signal

Imposition time: IT_SysDesc

[If

- the `ISignal` representing the selector field is referenced by an `ISignalTriggering` and that `ISignalTriggering` refers to an `ISignalPort` where the `communicationDirection` is set to `out` and
- the `ISignal` representing the selector field is referring to a `SystemSignal` and that `SystemSignal` is either
 - referenced by a `SenderReceiverToSignalMapping` in the role `system-Signal` or
 - part of a `SystemSignalGroup` that in turn is referenced by a `Sender-ReceiverToSignalGroupMapping`

then any `ISignal` other than the `ISignal` representing the selector field shall be mapped into that dynamic part alternative `ISignalIPdu` using the `transferProperty` set to `pending`.

]

[constr_5233] Usage of `invalidValue` in case of application writing the selector field signal

Imposition time: IT_SysDesc

[If

- the `ISignal` representing the selector field is referenced by an `ISignalTriggering` and that `ISignalTriggering` refers to an `ISignalPort` where the `communicationDirection` is set to `out` and
- the `ISignal` representing the selector field is referring to a `SystemSignal` and that `SystemSignal` is either
 - referenced by a `SenderReceiverToSignalMapping` in the role `system-Signal` or
 - part of a `SystemSignalGroup` that in turn is referenced by a `Sender-ReceiverToSignalGroupMapping`

then

- the `ISignal` representing the selector field shall either
 - define no invalid value (`ISignal.networkRepresentationProps.invalidValue`) or
 - the `invalidValue` defined shall be different than any of the defined selector field values for that `MultiplexedIPdu`.

}

[constr_5235] Maximum `Frame.frameLength` of the used bus protocol shall not be exceeded*Imposition time:* IT_SysDesc

[The `Pdu.length` used for an `IPdu` and the `IPduMapping.pduMaxLength` used for a `targetIPdu` shall not exceed the limitation of the maximum `Frame.frameLength` of the used bus protocol (e.g. CAN2.0 max. `Frame.frameLength` == 8Byte, CAN-FD `Frame.frameLength` == 64byte).

}

[constr_5236] Restriction of `IPduMapping.pduMaxLength`*Imposition time:* IT_SysDesc

[`IPduMapping.pduMaxLength` shall be equal or greater than the maximum `Pdu.length` of `sourceIPdu` and `targetIPdu`. For a N:1 routing and 1:N routing, respectively, the maximum `Pdu.length` of all involved `Pdu`s shall be used to evaluate a proper `IPduMapping.pduMaxLength`.

}

[constr_5244] Value of attribute `SOMEIPTransformationISignalProps.sizeOfArrayLengthFields`*Imposition time:* IT_SysDesc

[If attribute `SOMEIPTransformationISignalProps.sizeOfArrayLengthFields` is configured, then the value of attribute `SOMEIPTransformationISignalProps.sizeOfArrayLengthFields` shall be at least as high as the number of bytes required to fit the maximum result of the individual length field computation of all variable-size arrays that are transported in the SOME/IP message.

In other words, for each variable-size array contained in the SOME/IP message, the numerical value of *maximum number of elements * sizeof(data type of array element)* shall be computed which yields the maximum number of bytes required to store the individual variable-size array.

The size of the attribute `SOMEIPTransformationISignalProps.sizeOfArrayLengthFields` shall be set such that the highest value (or bigger) obtained from the individual computations for the contained variable-size arrays can fit into the length field. The unit of attribute `SOMEIPTransformationISignalProps.sizeOfArrayLengthFields` is bytes.

}

[constr_5245] Value of attribute `SOMEIPTransformationISignalProps.sizeOfStringLengthFields`

Imposition time: IT_SysDesc

[If attribute `SOMEIPTransformationISignalProps.sizeOfStringLengthFields` is configured, then the value of attribute `SOMEIPTransformationISignalProps.sizeOfStringLengthFields` shall be at least as high as the number of bytes required to fit the maximum result of the individual length field computation of all strings that are transported in the SOME/IP message.

In other words, for each string contained in the SOME/IP message, the numerical value of *maximum number of characters in the string * maximum number of code units per character (of the used character encoding) * maximum number of bytes per code unit (of the used character encoding)* shall be computed which yields the maximum number of bytes required to store the individual string.

The size of the attribute `SOMEIPTransformationISignalProps.sizeOfStringLengthFields` shall be set such that the highest value (or bigger) obtained from the individual computations for the contained strings can fit into the length field. The unit of attribute `SOMEIPTransformationISignalProps.sizeOfStringLengthFields` is bytes.

]

[constr_5246] SOME/IP Transformation settings for strings in the context of an `ISignal`

Imposition time: IT_SysDesc

[In the context of an `ISignal` the usage of `DataPrototypeTransformationProps.transformationProps.sizeOfStringLengthField` is only allowed if the `SOMEIPTransformationISignalProps.sizeOfStringLengthFields` is not defined.

]

[constr_5247] Value of attribute `DataPrototypeTransformationProps.transformationProps.sizeOfArrayLengthField`

Imposition time: IT_SysDesc

[If the configuration of length field is done using `DataPrototypeTransformationProps.transformationProps.sizeOfArrayLengthField` then the value of attribute `DataPrototypeTransformationProps.transformationProps.sizeOfArrayLengthField` shall be at least as high as the number of bytes required to fit the result of the expression *maximum number of elements * sizeof(data type of array element)*.

]

[constr_5248] Value of attribute `DataPrototypeTransformationProps.transformationProps.sizeOfStringLengthField`

Imposition time: IT_SysDesc

[If the configuration of length field is done using `DataPrototypeTransformationProps.transformationProps.sizeOfStringLengthField` then the value of attribute `DataPrototypeTransformationProps.transformationProps.sizeOfStringLengthField` shall be at least as high as the number of bytes required to fit the result of the expression *maximum number of characters in the string * maximum number of code units per character (of the used character encoding) * maximum number of bytes per code unit (of the used character encoding)*.

]

[constr_5249] Existence of `Pdu.length`

Imposition time: IT_SysDesc

[For each `Pdu`, the attribute `length` shall exist.

]

[constr_5251] `CouplingPort.connectionNegotiationBehavior` shall exist

Imposition time: IT_SysDesc

[The attribute `CouplingPort.connectionNegotiationBehavior` shall be defined.

]

[constr_5252] `LinSlaveConfig.protocolVersion` shall exist

Imposition time: IT_SysDesc

[The attribute `LinSlaveConfig.protocolVersion` shall exist.

]

[constr_5253] Value range of `ISignal.length`

Imposition time: IT_SysDesc

[The value of `ISignal.length` shall be in the range of 0..34359738360 Bits.

]

[constr_5254] Value range of `MultiplexedIPdu.selectorFieldLength`

Imposition time: IT_SysDesc

[The value of `MultiplexedIPdu.selectorFieldLength` shall be in the range of 1..16 Bits.

]

[constr_5258] TriggerToSignalMapping.systemSignals eligible for a TriggerToSignalMapping in case DataTransformation is used

Imposition time: IT_SysDesc

[The `ISignal` that is referenced by a `SystemSignal` that in turn is referenced by a `TriggerToSignalMapping` in the role `systemSignal` shall have its `length` attribute set to the value of `BufferProperties.headerLength` attribute of the respective `TransformationTechnology` if the `ISignal` references a `DataTransformation` in the role `dataTransformation` that in turn references the `TransformationTechnology`.

]

[constr_5259] PduTriggerings and FrameTriggerings of SecuredIPdu with useAsCryptographicIPdu = true

Imposition time: IT_SysDesc

[In case that a `SecuredIPdu` is defined with `useAsCryptographicIPdu = true` as described by [TPS_SYST_02173] then:

- the `PduTriggering` of the `AuthenticPdu`
- the `PduTriggering` of the `CryptographicPdu`
- the `FrameTriggering` that references the `Frame` to which the `AuthenticPdu` is mapped
- the `FrameTriggering` that references the `Frame` to which the `CryptographicPdu` is mapped

shall be aggregated by the same `PhysicalChannel`.

]

[constr_5262] SystemSignal used for Trigger communication shall not be part of any SystemSignalGroup

Imposition time: IT_EcuExt

[A `SystemSignal` that is target of a `TriggerToSignalMapping` in the role `systemSignal` shall not be referenced by a `SystemSignalGroup` in the role `systemSignal`.

]

[constr_5263] NetworkEndpoint.networkEndpointAddress restriction for IPv4

Imposition time: IT_SysDesc

[A `NetworkEndpoint` shall not aggregate several `Ipv4Configurations` that have their `ipv4AddressSource` set to fixed.

]

[constr_5264] NetworkEndpoint.networkEndpointAddress restriction for IPv6

Imposition time: IT_SysDesc

[A `NetworkEndpoint` shall not aggregate several `Ipv6Configurations` that have their `ipv6AddressSource` set to fixed.

]

[constr_5265] NetworkEndpoint.networkEndpointAddress restriction

Imposition time: IT_SysDesc

[A `NetworkEndpoint` shall not aggregate an `Ipv4Configuration` and an `Ipv6Configuration` as `networkEndpointAddress` at the same time.

]

[constr_5266] VariableDataPrototype of NvDataInterface shall not be mapped to a SystemSignal

Imposition time: IT_EcuExt

[A `VariableDataPrototype` that is aggregated by a `NvDataInterface` shall not be referenced by

- `SenderReceiverToSignalGroupMapping` in the role `dataElement` and
- `SenderReceiverToSignalMapping` in the role `dataElement`.

]

[constr_5267] VariableDataPrototype of NvDataInterface shall not be mapped to a SystemSignal via a delegation to a PortPrototype with a SenderReceiverInterface

Imposition time: IT_EcuExt

[If a `VariableDataPrototype` that is aggregated by a

- `SenderReceiverInterface` and that `SenderReceiverInterface` is referenced by a `PortPrototype` of a `Composition` and

- that `PortPrototype` is connected by a delegation connector with an inner `PortPrototype` of a `NvBlockSwComponentType` and
- that `PortPrototype` is typed by a `NvDataInterface`

then this `PortPrototype` shall not be referenced by:

- `SenderReceiverToSignalGroupMapping` in the role `dataElement` and
- `SenderReceiverToSignalMapping` in the role `dataElement`.

]

[constr_5268] Existence of `ContainedIPduProps.containedPduTriggering` reference

Imposition time: IT_SysDesc

[If a `ContainedIPduProps` is aggregated at the `ContainerIPdu` in the role `ContainerIPdu.containedIPduTriggeringProps` then the reference `ContainedIPduProps.containedPduTriggering` shall exist.

]

[constr_5269] Exclusion of `ContainedIPduProps.containedPduTriggering` reference

Imposition time: IT_SysDesc

[If a `ContainedIPduProps` is aggregated at the `IPdu` in the role `IPdu.containedIPduProps` then the reference `ContainedIPduProps.containedPduTriggering` shall NOT exist.

]

[constr_5270] Exclusive usage of `ContainerIPdu.containedPduTriggering` and `ContainerIPdu.containedIPduTriggeringProps`

Imposition time: IT_SysDesc

[A `ContainerIPdu` shall only have either `ContainerIPdu.containedPduTriggering` OR `ContainerIPdu.containedIPduTriggeringProps` defined.

]

[constr_5271] Existence of attribute `BinaryManifestItem.isUnused`

Imposition time: IT_BinObjMetaData

[For each `BinaryManifestItem`, the attribute `isUnused` shall exist.

]

[constr_5272] Value of attribute `BinaryManifestItem.isUnused`

Imposition time: IT_BinObjMetaData

[The attribute `BinaryManifestItem.isUnused` shall only permitted to be set to true if the related `BinaryManifestItemDefinition` has its attribute `isOptional` set to true.

]

[constr_5273] One `ISignalTriggering` pair allowed per `EthernetPhysicalChannel` for a `ClientServerOperation`

Imposition time: IT_SysDesc

[For each `EthernetPhysicalChannel` at most one pair of

- `ISignalTriggering` that refers to an `ISignal` that in turn refers to a `SystemSignal` that is referenced by a specific `ClientServerToSignalMapping` in the role `callSignal`
- `ISignalTriggering` that refers to an `ISignal` that in turn refers to a `SystemSignal` that is referenced by the same `ClientServerToSignalMapping` in the role `returnSignal`

shall exist.

]

[constr_5274] `ISignalTriggerings` that represent the `callSignal` and `returnSignal` of the same `ClientServerOperation` on a `PhysicalChannel` shall be referenced by the same `ClientServerToSignalMapping`

Imposition time: IT_SysDesc

[If on an `EthernetPhysicalChannel` an `ISignalTriggering` that refers to an `ISignal` that in turn refers to a `SystemSignal` that is referenced by a specific `ClientServerToSignalMapping` in the role `callSignal` is defined, then another `ISignalTriggering` shall be aggregated by the same `EthernetPhysicalChannel` and that `ISignalTriggering` shall refer to an `ISignal` that in turn refers to a `SystemSignal` that is referenced by the same `ClientServerToSignalMapping` in the role `returnSignal`, and vice versa.

]

[constr_5306] Restriction of `DltLogChannel.logChannelId` attribute value

Imposition time: IT_SysDesc

[The `DltLogChannel.logChannelId` attribute value shall be composed of maximum four ASCII characters.

]

[constr_5307] Existence of `DltLogChannel.logChannelId`*Imposition time:* IT_SysDesc[For each `DltLogChannel`, the attribute `logChannelId` shall be defined.

]

[constr_5308] Existence of `DltLogChannel.nonVerboseMode`*Imposition time:* IT_SysDesc[For each `DltLogChannel`, the attribute `nonVerboseMode` shall be defined.

]

[constr_5309] Existence of `DltConfig.sessionIdSupport`*Imposition time:* IT_SysDesc[For each `DltConfig`, the attribute `sessionIdSupport` shall be defined.

]

[constr_5310] Existence of `DltConfig.timestampSupport`*Imposition time:* IT_SysDesc[For each `DltConfig`, the attribute `timestampSupport` shall be defined.

]

[constr_5311] Existence of `DltLogChannel.logTraceDefaultLogThreshold`*Imposition time:* IT_SysDesc[For each `DltLogChannel`, the attribute `logTraceDefaultLogThreshold` shall be defined.

]

[constr_5312] Existence of `DltLogChannel.defaultTraceState`*Imposition time:* IT_SysDesc[For each `DltLogChannel`, the attribute `defaultTraceState` shall be defined.

]

[constr_5313] Existence of `DltLogChannel.txPduTriggering`*Imposition time:* IT_SysDesc[For each `DltLogChannel`, the reference to `PduTriggering` in the role `txPduTriggering` shall be defined.

]

[constr_5314] DltLogChannel txPduTriggering and rxPduTriggering shall be on the same network

Imposition time: IT_SysDesc

[The `PduTriggerings` that are referenced by a `DltLogChannel` in the role `txPduTriggering` and `rxPduTriggering` shall be aggregated by the same `PhysicalChannel`.

]

[constr_5315] FlexrayArTpConnections within the same FlexrayArTpChannel not allowed to have the same address information

Imposition time: IT_SysDesc

[`FlexrayArTpConnections` that are aggregated by the same or reverse `FlexrayArTpChannel` are not allowed to reference the same pair of `FlexrayArTpNodes`.

]

[constr_5319] TCP endpoint using TLS_SERVER role can only serve provided service instances

Imposition time: IT_SysDesc

[An `ApplicationEndpoint` that refers to `TlsCryptoServiceMapping` with category `TLS_SERVER` in the role `tlsCryptoMapping` is only allowed to be referenced by `ProvidedServiceInstances` in the role `localUnicastAddress` in case that the `ProvidedServiceInstance` does not have a `remoteUnicastAddress` defined.

]

[constr_5320] TCP endpoint using TLS_CLIENT role can only serve consumed service instances

Imposition time: IT_SysDesc

[An `ApplicationEndpoint` that refers to `TlsCryptoServiceMapping` with category `TLS_CLIENT` in the role `tlsCryptoMapping` is only allowed to be referenced by `ConsumedServiceInstances` in the role `localUnicastAddress` in case that the `ConsumedServiceInstance` does not have a `remoteUnicastAddress` defined.

]

[constr_5321] Value range of Pdu.length

Imposition time: IT_SysDesc

[The value of `Pdu.length` shall be in the range of 0..4294967295 Bytes.

]

[constr_5322] Value range of `ISignalToIPduMapping.startPosition`

Imposition time: IT_SysDesc

[The value of `ISignalToIPduMapping.startPosition` shall be in the range of 0..4294967295 Bits.

]

[constr_5323] Value range of `ISignalToIPduMapping.updateIndicationBitPosition`

Imposition time: IT_SysDesc

[The value of `ISignalToIPduMapping.updateIndicationBitPosition` shall be in the range of 0..4294967295 Bits.

]

[constr_5326] Each local `SocketAddress` of an `EcuInstance` shall reference an `EthernetCommunicationConnector` in the role `connector` or `multicastConnector`

Imposition time: IT_SysDesc

[If an `EcuInstance` uses a `SocketAddress` as local address, the `SocketAddress` shall refer to an `EthernetCommunicationConnector` of the `EcuInstance`, either via `SocketAddress.connector` if the `SocketAddress` represents a unicast address, or via `SocketAddress.multicastConnector` if the `SocketAddress` represents a multicast address.

]

[constr_5327] Existence of attribute `CpSoftwareCluster.category`

Imposition time: IT_SwCluSysDesc

[For each `CpSoftwareCluster`, attribute `category` shall exist.

]

[constr_5328] Ecu Extract shall only contain outerPort `DataMappings`

Imposition time: IT_EcuExt

[The System with category `ECU_EXTRACT` shall only contain `DataMappings` for `VariableDataPrototypes`, `ClientServerOperations` or `Triggers` that are referenced in the context of a `PortPrototype` of the `SwComponentType` that in turn is referenced by the `RootSwCompositionPrototype`.

]

[constr_5329] SynchronousServerCallPoints for cross cluster communication are not supported

Imposition time: IT_SwCluSysDesc

[A `ClientServerOperation` in the context of `PortPrototype` which is referenced by a `PortElementToCommunicationResourceMapping` in the role `clientServerOperation` is not allowed

- to be referenced by a `SynchronousServerCallPoint.operation` or
- to be connected to another `ClientServerOperation` in the context of a `PortPrototype` that in turn is referenced by `SynchronousServerCallPoint.operation`

]

[constr_5330] ServiceInterface elements shall belong to exactly one Service Interface

Imposition time: IT_SysDesc

[If an element like

- a `VariableDataPrototype` that represents a `ServiceInterface` event
- a `ClientServerOperation` that represents a `ServiceInterface` method
- a `Collection` with `collectionSemantics` `SO_SERVICE_FIELD` that represents a `ServiceInterface` field
- a `Collection` with `collectionSemantics` `SO_SERVICE_FIRE_AND_FORGET_METHOD` that represents a "fire & forget" method

is referenced in the role `element` by a `Collection` that has the `collectionSemantics` set to `SO_SERVICE_INTERFACE` then this element shall not be referenced by any other `Collection` element that has the `collectionSemantics` `SO_SERVICE_INTERFACE` in the scope of the `System`.

]

[constr_5331] No IP multicast in case of TCP

Imposition time: IT_SysDesc

[The `ApplicationEndpoint` that is referenced in the role `eventMulticastAddress` from an `EventHandler` is only allowed to aggregate `UdpTp` in the role `tpConfiguration`.

]

[constr_5334] Supported values for `CryptoServiceKey.length`

Imposition time: IT_SysDesc

[The values defined for `CryptoServiceKey.length` shall be multiple of 8.

]

[constr_5335] `CpSoftwareCluster.softwareClusterId` shall be unique in the scope of an `EcuInstance`

Imposition time: IT_SwCluSysDesc

[The `softwareClusterId` shall be unique for each `CpSoftwareCluster` that is mapped to the same `EcuInstance` with the `CpSoftwareClusterToEcuInstanceMapping`.

]

[constr_5336] Existence of `CpSoftwareCluster.softwareClusterId`

Imposition time: IT_SwCluSysDesc

[For each `CpSoftwareCluster`, attribute `softwareClusterId` shall exist.

]

[constr_5337] All `CpSoftwareClusterToEcuInstanceMappings` that are referencing the same `EcuInstance` shall define the same `machineId`

Imposition time: IT_SysDesc

[All `CpSoftwareClusterToEcuInstanceMappings` that define a `machineId` and are referencing the same `EcuInstance` in the role `ecuInstance` shall have the same `CpSoftwareClusterToEcuInstanceMapping.machineId` value set.

]

[constr_5344] Applicable `transferProperty` for `GroupSignal` and `ISignalGroup`

Imposition time: IT_SysDesc

[

<code>transferProperty</code> on <code>ISignalGroup</code>	<code>transferProperty</code> on <code>GroupSignals</code>	Semantic
• not set	Not set or <code>pending</code> for all <code>GroupSignals</code>	Update of the Signal Group and update of <code>GroupSignals</code> will not trigger transmission of the <code>ISignalIPdu</code> .





	Subset of Group Signals has <code>transferProperty</code> set to either <code>triggered</code> or <code>triggeredWithoutRepetition</code> and the other Group Signals have <code>transferProperty</code> either not set or set to <code>pending</code> .	Update of Signal Group marks the <code>ISignalIPdu</code> for transmission.
	Subset of Group Signals has <code>transferProperty</code> set to either <code>triggeredOnChange</code> or <code>triggeredOnChangeWithoutRepetition</code> and the other Group Signals have <code>transferProperty</code> either not set or set to <code>pending</code> .	Update of Signal Group and change of a Group Signal that has <code>transferProperty</code> set to <code>triggeredOnChange</code> or <code>triggeredOnChangeWithoutRepetition</code> causes immediate transmission of the <code>ISignalIPdu</code> .
<ul style="list-style-type: none"> • <code>pending</code> 	Not set or <code>pending</code> for all Group Signals	Update of the Signal Group and update of Group Signals will not trigger transmission of the <code>ISignalIPdu</code> . See [TPS_SYST_02199].
<ul style="list-style-type: none"> • <code>triggered</code> • <code>triggeredWithoutRepetition</code> 	Not set or <code>pending</code> for all Group Signals	Update of the Signal Group marks the <code>ISignalIPdu</code> for transmission. See [TPS_SYST_02199].
	Subset of Group Signals has <code>transferProperty</code> set to either <code>triggered</code> or <code>triggeredWithoutRepetition</code> and the other Group Signals have <code>transferProperty</code> either not set or set to <code>pending</code> .	Update of Signal Group marks the <code>ISignalIPdu</code> for transmission. See [TPS_SYST_02200].
<ul style="list-style-type: none"> • <code>triggeredOnChange</code> • <code>triggeredOnChangeWithoutRepetition</code> 	Not set or <code>pending</code> for all Group Signals	Update of Signal Group causes immediate transmission of the <code>ISignalIPdu</code> . See [TPS_SYST_02199].
	Subset of Group Signals has <code>transferProperty</code> set to either <code>triggeredOnChange</code> or <code>triggeredOnChangeWithoutRepetition</code> and the other Group Signals have <code>transferProperty</code> either not set or set to <code>pending</code> .	Update of Signal Group and change of a Group Signal that has <code>transferProperty</code> set to <code>triggeredOnChange</code> or <code>triggeredOnChangeWithoutRepetition</code> causes immediate transmission of the <code>ISignalIPdu</code> . See [TPS_SYST_02200].

If the `ISignalToIPduMapping` refers to an `ISignalGroup` in the role `iSignalGroup` and the `ISignalIPdu` has an `EventControlledTiming` aggregated at the `TransmissionModeTiming` then combinations of `transferProperty` attribute settings for the `ISignalGroup` and the included `ISignals` are supported as defined in this table.

]

[constr_5359] `CpSoftwareClusterBinaryManifestDescriptor.softwareClusterId` shall be identical to `CpSoftwareCluster.softwareClusterId`

Imposition time: `IT_BinObjMetaData`

[The `CpSoftwareClusterBinaryManifestDescriptor.softwareClusterId` shall be identical to `CpSoftwareCluster.softwareClusterId` in case that the

`softwareClusterId` is set in the `CpSoftwareCluster` that is referenced via `CpSoftwareClusterBinaryManifestDescriptor.cpSoftwareCluster`.

]

[constr_5360] Cross cluster communication involving `NvBlockSwComponentType` is not supported

Imposition time: `IT_SwCluSysDesc`

[A `PortElementToCommunicationResourceMapping` that is referencing a `CpSoftwareClusterCommunicationResource` in the role `communicationResource` is not allowed to reference:

- a `VariableDataPrototype` in the role `variableDataPrototype` that is defined in the context of a `PortPrototype` of a `NvBlockSwComponentType` typed by a `NvDataInterface` or
- a `VariableDataPrototype` in the role `variableDataPrototype` which is connected to another `VariableDataPrototype` that is defined in the context of a `PortPrototype` of a `NvBlockSwComponentType` and typed by a `NvDataInterface` or
- a `ClientServerOperation` in the role `clientServerOperation` that is defined in the context of a `PortPrototype` of a `NvBlockSwComponentType` typed by a `ClientServerInterface` or
- a `ClientServerOperation` in the role `clientServerOperation` which is connected to another `ClientServerOperation` that is defined in the context of a `PortPrototype` of a `NvBlockSwComponentType` typed by a `ClientServerInterface`

]

[constr_5361] MACsec configuration is allowed only on switch ports

Imposition time: `IT_SysDesc`

[Only a `CouplingElement` with `couplingType` set to `switch` is allowed to aggregate a `CouplingPort` that in turn aggregates the `MacSecProps` in the role `macSecProps`.

]

[constr_5362] Relation between `ContainerIPdu` and contained `PduTriggerings` on sender side

Imposition time: `IT_SysDesc`

[In the scope of one `EcuInstance`, if a `PduTriggering` has a reference to an `IPduPort` where attribute `communicationDirection` is set to the value `out`, then that `PduTriggering` shall only be referenced at most once by any of

- `ContainerIPdu.containedPduTriggering`
- `ContainerIPdu.containedIPduTriggeringProps.containedPduTriggering`.

]

[constr_5369] Consistency between `SwcToApplicationPartitionMapping` and `CpSoftwareClusterToApplicationPartitionMapping`

Imposition time: IT_SwCluSysDesc

[If a `CpSoftwareClusterToApplicationPartitionMapping` exists between a `CpSoftwareCluster` and an `ApplicationPartition`, then all `SwComponentPrototypes` mapped to that `ApplicationPartition` by `SwcToApplicationPartitionMapping` shall be assigned to this `CpSoftwareCluster` (via `CpSoftwareCluster.swComponentAssignment` or `CpSoftwareCluster.swComposition`).

]

[constr_5370] Restriction for `SystemSignalToCommunicationResourceMapping` in case a `DataMapping` is defined for the mapped `SystemSignal`

Imposition time: IT_SwCluSysDesc

[If a `DataMapping` to a `SystemSignal` exists for the port element (e.g. `VariableDataPrototype`, `ClientServerOperation`) that is mapped by the `PortElementToCommunicationResourceMapping` to a `CpSoftwareClusterCommunicationResource` and a `SystemSignalToCommunicationResourceMapping` exists for the same `SystemSignal` then the `SystemSignalToCommunicationResourceMapping` shall map this `SystemSignal` to the same `CpSoftwareClusterCommunicationResource`.

]

[constr_5371] Restriction for `SystemSignalGroupToCommunicationResourceMapping` in case a `DataMapping` is defined for the mapped `SystemSignalGroup`

Imposition time: IT_SwCluSysDesc

[If a `SenderReceiverToSignalGroupMapping` to a `SystemSignalGroup` exists for the `VariableDataPrototype` that is mapped by the `PortElementToCommunicationResourceMapping` to a `CpSoftwareClusterCommunicationResource` and a `SystemSignalGroupToCommunicationResourceMapping` exists for the same `SystemSignalGroup` then the `SystemSignalGroupToCommunicationResourceMapping` shall map this `SystemSignalGroup` to the same `CpSoftwareClusterCommunicationResource`.

]

[constr_5374] IPdu shall only be referenced once from a FlexrayTpConnection in the role directTpSdu or reversedTpSdu on a FlexrayCluster

Imposition time: IT_SysDesc

Each IPdu that is referenced in the role directTpSdu or reversedTpSdu from a FlexrayTpConnection that is aggregated by a FlexrayTpConfig that references a FlexrayCluster shall not be referenced a second time in the role directTpSdu or reversedTpSdu from any FlexrayTpConnection that is aggregated by a FlexrayTpConfig that references the same FlexrayCluster.

]

[constr_5375] IPdu shall only be referenced once from a FlexrayArTpConnection in the role directTpSdu or reversedTpSdu on a FlexrayCluster

Imposition time: IT_SysDesc

Each IPdu that is referenced in the role directTpSdu or reversedTpSdu from a FlexrayArTpConnection that is aggregated by a FlexrayArTpConfig that references a FlexrayCluster shall not be referenced a second time in the role directTpSdu or reversedTpSdu from any FlexrayArTpConnection that is aggregated by a FlexrayArTpConfig that references the same FlexrayCluster.

]

[constr_5376] IPdu shall only be referenced once from a CanTpConnection in the role tpSdu on a CanCluster

Imposition time: IT_SysDesc

Each IPdu that is referenced in the role tpSdu from a CanTpConnection that is aggregated by a CanTpConfig that references a CanCluster shall not be referenced in the role tpSdu from a different CanTpConnection that is aggregated by a CanTpConfig that references the same CanCluster.

]

[constr_5377] IPdu shall only be referenced once from a LinTpConnection in the role linTpNSdu on a LinCluster

Imposition time: IT_SysDesc

Each IPdu that is referenced in the role linTpNSdu from a LinTpConnection that is aggregated by a LinTpConfig that references a LinCluster shall not be referenced in the role linTpNSdu from a different LinTpConnection that is aggregated by a LinTpConfig that references the same LinCluster.

]

[constr_5378] PduTriggering shall only be referenced once from a SomeipTpConnection in the role tpSdu

Imposition time: IT_SysDesc

[Each PduTriggering that is referenced in the role tpSdu from a SomeipTpConnection shall not be referenced in the role tpSdu from a different SomeipTpConnection.

]

[constr_5379] IPdu shall only be referenced once from a J1939TpPg in the role sdu on a J1939Cluster

Imposition time: IT_SysDesc

[Each IPdu that is referenced in the role sdu from a J1939TpPg that is aggregated by a J1939TpConfig that references a J1939Cluster shall not be referenced in the role sdu from a different J1939TpPg that is aggregated by a J1939TpConfig that references the same J1939Cluster.

]

[constr_5380] Assignment of the same event Pdu to several EventHandlers is forbidden in case one of the EventHandlers has the multicastThreshold set to a value greater than 0 in the context of an EcuInstance

Imposition time: IT_SysDesc

[SoConIPduIdentifiers with the same headerId shall not be referenced by PduActivationRoutingGroups of different EventHandlers if

- one or several of these EventHandlers has the multicastThreshold set to a value > 0 and
- all these EventHandlers are aggregated by ProvidedServiceInstances that reference ApplicationEndpoints with the localUnicastAddress reference that in turn are aggregated by SocketAddresses which contain a reference to the same EthernetCommunicationConnector in the role connector (i.e. the EventHandlers are located on the same EcuInstance).

except for the case that all these EventHandlers have the multicastThreshold set to the value 1.

]

[constr_5382] Relation between the value of attributes `offerCyclicDelay` and `serviceOfferTimeToLive` in the context of a `SomeipSdServerServiceInstanceConfig`

Imposition time: IT_SysDesc

[In the context of any given `SomeipSdServerServiceInstanceConfig`, if the value of attribute `offerCyclicDelay` exists, it shall be less or equal to the value of attribute `serviceOfferTimeToLive`.

]

[constr_5383] Relation between the value of attributes `initialRepetitionsBaseDelay` and `initialRepetitionsMax` and `serviceOfferTimeToLive` in the context of a `SomeipSdServerServiceInstanceConfig`

Imposition time: IT_SysDesc

[In the context of any given `SomeipSdServerServiceInstanceConfig`, if the value of attribute `initialRepetitionsMax` in `initialOfferBehavior` is greater than zero, the value of attribute `serviceOfferTimeToLive` shall be greater or equal to $\text{initialRepetitionsBaseDelay} * 2^{\text{initialRepetitionsMax}}$.

]

[constr_5384] Existence of `BusMirrorChannelMapping.mirroringProtocol`

Imposition time: IT_SysDesc

[For each `BusMirrorChannelMapping`, the attribute `mirroringProtocol` shall exist.

]

[constr_5385] Reception of `UserData` inside of a `NmPdu` by Applications is not supported

Imposition time: IT_SysDesc

[A `SystemSignal` that is referenced by an `ISignal` that in turn is mapped via an `ISignalToIPduMapping` into a `NmPdu` shall not be mapped by a `DataMapping` that references a `RPortPrototype` with the `contextPort` reference in the `VariableDataPrototypeInSystemInstanceRef` that the `DataMapping` aggregates.

]

[constr_5389] Dependency between `globalTimeTxPeriod` and `globalTimePortRole`

Imposition time: IT_SysDesc

[The attribute `EthGlobalTimeManagedCouplingPort.globalTimeTxPeriod` shall only be set to a value if the attribute `EthGlobalTimeManagedCouplingPort.globalTimePortRole` is set to `timeMaster` or `dynamic`.

]

[constr_5390] The `globalTimePortRole` shall not be configured to `timeSlave` several times in the same `GlobalTimeDomain`

Imposition time: IT_SysDesc

[The attribute `globalTimePortRole` shall not be set to `timeSlave` for two or more `EthGlobalTimeManagedCouplingPorts` that are aggregated by the same `GlobalTimeDomain` (via `globalTimeDomainProperty`).

]

[constr_5393] Existence of `clientId`

Imposition time: IT_SysDesc

[For each `ClientIdDefinition`, the attribute `clientId` shall exist.

]

[constr_5394] Existence of `clientServerOperation`

Imposition time: IT_SysDesc

[For each `ClientIdDefinition`, the attribute `clientServerOperation` shall exist.

]

[constr_5395] Existence of `physicalChannel`

Imposition time: IT_SysDesc

[Each `CommunicationCluster` shall aggregate at least one `PhysicalChannel` in the role `physicalChannel`.

]

[constr_5396] Existence of `ClientIdRange.lowerLimit`

Imposition time: IT_SysDesc

[For each `ClientIdRange`, the attribute `lowerLimit` shall exist.

]

[constr_5397] Existence of ClientIdRange.upperLimit*Imposition time:* IT_SysDesc

[For each `ClientIdRange`, the attribute `upperLimit` shall exist.

]

[constr_5398] Existence of CommunicationConnector.commController*Imposition time:* IT_SysDesc

[For each `CommunicationConnector`, the reference in the role `commController` shall exist.

]

[constr_5399] Existence of ecu*Imposition time:* IT_SysDesc

[For each `ECUMapping`, the reference to `HwElement` in the role `ecu` shall exist.

]

[constr_5400] Existence of ecuInstance*Imposition time:* IT_SysDesc

[For each `ECUMapping`, the reference to `EcuInstance` in the role `ecuInstance` shall exist.

]

[constr_5401] Existence of communicationController*Imposition time:* IT_SysDesc

[For each `CommunicationControllerMapping`, the reference to `CommunicationController` in the role `communicationController` shall exist.

]

[constr_5402] Existence of hwCommunicationController*Imposition time:* IT_SysDesc

[For each `CommunicationControllerMapping`, the reference to `HwElement` in the role `hwCommunicationController` shall exist.

]

[constr_5403] Existence of communicationConnector

Imposition time: IT_SysDesc

[For each `HwPortMapping`, the reference to `CommunicationConnector` in the role `communicationConnector` shall exist.

]

[constr_5404] Existence of hwCommunicationPort

Imposition time: IT_SysDesc

[For each `HwPortMapping`, the reference to `HwPinGroup` in the role `hwCommunicationPort` shall exist.

]

[constr_5405] Existence of actionPointOffset

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `actionPointOffset` shall exist.

]

[constr_5406] Existence of bit

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `bit` shall exist.

]

[constr_5407] Existence of casRxLowMax

Imposition time: IT_SysDesc

[For each `FlexrayCluster` the attribute `casRxLowMax` shall exist.

]

[constr_5408] Existence of coldStartAttempts

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `coldStartAttempts` shall exist.

]

[constr_5409] Existence of cycle

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `cycle` shall exist.

]

[constr_5410] Existence of `cycleCountMax`

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `cycleCountMax` shall exist.

]

[constr_5412] Existence of `dynamicSlotIdlePhase`

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `dynamicSlotIdlePhase` shall exist.

]

[constr_5414] Existence of `listenNoise`

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `listenNoise` shall exist.

]

[constr_5415] Existence of `macroPerCycle`

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `macroPerCycle` shall exist.

]

[constr_5416] Existence of `macrotickDuration`

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `macrotickDuration` shall exist.

]

[constr_5417] Existence of `maxWithoutClockCorrectionFatal`

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `maxWithoutClockCorrectionFatal` shall exist.

]

[constr_5418] Existence of `maxWithoutClockCorrectionPassive`

Imposition time: IT_SysDesc

[For each `FlexrayCluster`, the attribute `maxWithoutClockCorrectionPassive` shall exist.

]

[constr_5419] Existence of `minislotActionPointOffset`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `minislotActionPointOffset` shall exist.

]

[constr_5420] Existence of `minislotDuration`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `minislotDuration` shall exist.

]

[constr_5421] Existence of `networkIdleTime`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `networkIdleTime` shall exist.

]

[constr_5422] Existence of `networkManagementVectorLength`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `networkManagementVectorLength` shall exist.

]

[constr_5423] Existence of `numberOfMinislots`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `numberOfMinislots` shall exist.

]

[constr_5424] Existence of `numberOfStaticSlots`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `numberOfStaticSlots` shall exist.

]

[constr_5425] Existence of `offsetCorrectionStart`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `offsetCorrectionStart` shall exist.

]

[constr_5426] Existence of `payloadLengthStatic`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `payloadLengthStatic` shall exist.
]

[constr_5428] Existence of `staticSlotDuration`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `staticSlotDuration` shall exist.
]

[constr_5429] Existence of `symbolWindow`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `symbolWindow` shall exist.
]

[constr_5431] Existence of `syncFrameIdCountMax`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `syncFrameIdCountMax` shall exist.
]

[constr_5432] Existence of `transmissionStartSequenceDuration`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `transmissionStartSequenceDuration` shall exist.
]

[constr_5433] Existence of `wakeupRxIdle`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `wakeupRxIdle` shall exist.
]

[constr_5434] Existence of `wakeupRxLow`*Imposition time:* IT_SysDesc

[For each `FlexrayCluster`, the attribute `wakeupRxLow` shall exist.
]

[constr_5435] Existence of wakeupRxWindow*Imposition time:* IT_SysDesc

[For each FlexrayCluster, the attribute wakeupRxWindow shall exist.

]

[constr_5436] Existence of wakeupTxActive*Imposition time:* IT_SysDesc

[For each FlexrayCluster, the attribute wakeupTxActive shall exist.

]

[constr_5437] Existence of wakeupTxIdle*Imposition time:* IT_SysDesc

[For each FlexrayCluster, the attribute wakeupTxIdle shall exist.

]

[constr_5438] Existence of sampleClockPeriod*Imposition time:* IT_SysDesc

[For each FlexrayCluster, the attribute sampleClockPeriod shall exist.

]

[constr_5439] Existence of admitWithoutMessageId*Imposition time:* IT_SysDesc

[For each FlexrayFifoConfiguration, the attribute admitWithoutMessageId shall exist.

]

[constr_5440] Existence of baseCycle*Imposition time:* IT_SysDesc

[For each FlexrayFifoConfiguration, the attribute baseCycle shall exist.

]

[constr_5441] Existence of cycleRepetition*Imposition time:* IT_SysDesc

[For each FlexrayFifoConfiguration, the attribute cycleRepetition shall exist.

]

[constr_5442] Existence of `fifoDepth`*Imposition time:* IT_SysDesc

[For each `FlexrayFifoConfiguration`, the attribute `fifoDepth` shall exist.
]

[constr_5443] Existence of `msgIdMask`*Imposition time:* IT_SysDesc

[For each `FlexrayFifoConfiguration`, the attribute `msgIdMask` shall exist.
]

[constr_5444] Existence of `msgIdMatch`*Imposition time:* IT_SysDesc

[For each `FlexrayFifoConfiguration`, the attribute `msgIdMatch` shall exist.
]

[constr_5445] Existence of `fifoRange`*Imposition time:* IT_SysDesc

[Each `FlexrayFifoConfiguration` shall aggregate at least two `FlexrayFifoRanges` in the role `fifoRange`.
]

[constr_5446] Existence of `rangeMax`*Imposition time:* IT_SysDesc

[For each `FlexrayFifoRange`, the attribute `rangeMax` shall exist.
]

[constr_5447] Existence of `rangeMin`*Imposition time:* IT_SysDesc

[For each `FlexrayFifoRange`, the attribute `rangeMin` shall exist.
]

[constr_5448] Existence of `channelName`*Imposition time:* IT_SysDesc

[For each `FlexrayPhysicalChannel`, the attribute `channelName` shall exist.
]

[constr_5449] LinCommunicationController.protocolVersion shall exist

Imposition time: IT_SysDesc

[The attribute `LinCommunicationController.protocolVersion` shall exist.

]

[constr_5450] Existence of `index`

Imposition time: IT_SysDesc

[For each `LinOrderedConfigurableFrame`, the attribute shall `index` shall exist.

]

[constr_5451] Existence of `LinOrderedConfigurableFrame.frame` reference

Imposition time: IT_SysDesc

[For each `LinOrderedConfigurableFrame`, the reference to `LinFrame` in the role `frame` shall exist.

]

[constr_5452] Existence of `LinConfigurableFrame.frame` reference

Imposition time: IT_SysDesc

[For each `LinConfigurableFrame`, the reference to `LinFrame` in the role `frame` shall exist.

]

[constr_5453] Existence of `macMulticastAddress`

Imposition time: IT_SysDesc

[For each `MacMulticastGroup`, the attribute `macMulticastAddress` shall exist.

]

[constr_5454] Existence of `vlanIdentifier`

Imposition time: IT_SysDesc

[For each `VlanConfig`, the attribute `vlanIdentifier` shall exist.

]

[constr_5455] Existence of `couplingType`

Imposition time: IT_SysDesc

[For each `CouplingElement`, the attribute `couplingType` shall exist.

]

[constr_5456] Existence of communicationCluster*Imposition time:* IT_SysDesc

[For each `CouplingElement`, the reference `communicationCluster` shall exist.

]

[constr_5457] Existence of defaultPriority*Imposition time:* IT_SysDesc

[For each `VlanMembership`, the attribute `defaultPriority` shall exist.

]

[constr_5458] Existence of vlan*Imposition time:* IT_SysDesc

[For each `VlanMembership`, the reference `vlan` shall exist.

]

[constr_5459] Existence of dataLength*Imposition time:* IT_SysDesc

[For each `CouplingPortRatePolicy`, the attribute `dataLength` shall exist.

]

[constr_5460] Existence of policyAction*Imposition time:* IT_SysDesc

[For each `CouplingPortRatePolicy`, the attribute `policyAction` shall exist.

]

[constr_5461] Existence of timeInterval*Imposition time:* IT_SysDesc

[For each `CouplingPortRatePolicy`, the attribute `timeInterval` shall exist.

]

[constr_5462] Existence of ingressPriority*Imposition time:* IT_SysDesc

[For each `EthernetPriorityRegeneration`, the attribute `ingressPriority` shall exist.

]

[constr_5463] Existence of regeneratedPriority

Imposition time: IT_SysDesc

[For each EthernetPriorityRegeneration, the attribute regeneratedPriority shall exist.

]

[constr_5464] Existence of trafficClass

Imposition time: IT_SysDesc

[For each CouplingPortTrafficClassAssignment, the attribute trafficClass shall exist.

]

[constr_5465] Existence of softwareComposition

Imposition time: IT_SysDesc

[For each RootSwCompositionPrototype, the reference to CompositionSwComponentType in the role softwareComposition shall exist.

]

[constr_5466] Existence of SenderReceiverToSignalMapping.dataElement

Imposition time: IT_EcuExt

[For each SenderReceiverToSignalMapping, the reference to VariableDataPrototype in the role dataElement shall exist.

]

[constr_5467] Existence of SenderReceiverToSignalMapping.systemSignal

Imposition time: IT_EcuExt

[For each SenderReceiverToSignalMapping, the reference to SystemSignal in the role systemSignal shall exist.

]

[constr_5468] Existence of SenderReceiverToSignalGroupMapping.dataElement

Imposition time: IT_EcuExt

[For each SenderReceiverToSignalGroupMapping, the reference to VariableDataPrototype in the role dataElement shall exist.

]

[constr_5469] Existence of `SenderReceiverToSignalGroupMapping.signalGroup`

Imposition time: IT_EcuExt

[For each `SenderReceiverToSignalGroupMapping`, the reference to `SystemSignalGroup` in the role `signalGroup` shall exist.

]

[constr_5470] Existence of `SenderReceiverToSignalGroupMapping.typeMapping`

Imposition time: IT_EcuExt

[For each `SenderReceiverToSignalGroupMapping`, the aggregation of `SenderRecCompositeTypeMapping` in the role `typeMapping` shall exist.

]

[constr_5471] Existence of `SenderRecArrayElementMapping.indexedArrayElement`

Imposition time: IT_EcuExt

[For each `SenderRecArrayElementMapping`, the aggregation in the role `indexedArrayElement` shall exist.

]

[constr_5472] Existence of `IndexedArrayElement.index`

Imposition time: IT_EcuExt

[For each `IndexedArrayElement`, the attribute `index` shall exist.

]

[constr_5473] Existence of `ClientServerToSignalMapping.callSignal`

Imposition time: IT_EcuExt

[For each `ClientServerToSignalMapping`, the reference to `SystemSignal` in the role `callSignal` shall exist.

]

[constr_5474] Existence of `ClientServerToSignalMapping.clientServerOperation`

Imposition time: IT_EcuExt

[For each `ClientServerToSignalMapping`, the reference to `ClientServerOperation` in the role `clientServerOperation` shall exist.

]

[constr_5475] Existence of `SenderReceiverCompositeElementToSignalMapping.systemSignal`

Imposition time: IT_EcuExt

[For each `SenderReceiverCompositeElementToSignalMapping`, the reference to `SystemSignal` in the role `systemSignal` shall exist.

]

[constr_5476] Existence of `SenderReceiverCompositeElementToSignalMapping.typeMapping`

Imposition time: IT_EcuExt

[For each `SenderReceiverCompositeElementToSignalMapping`, the aggregation of `SenderRecCompositeTypeMapping` in the role `typeMapping` shall exist.

]

[constr_5477] Existence of `TriggerToSignalMapping.systemSignal`

Imposition time: IT_EcuExt

[For each `TriggerToSignalMapping`, the reference to `SystemSignal` in the role `systemSignal` shall exist.

]

[constr_5478] Existence of `TriggerToSignalMapping.trigger`

Imposition time: IT_EcuExt

[For each `TriggerToSignalMapping`, the reference to `Trigger` in the role `trigger` shall exist.

]

[constr_5479] Existence of `PncMapping.pncIdentifier`

Imposition time: IT_SysDesc

[For each `PncMapping`, the attribute `pncIdentifier` shall exist.

]

[constr_5480] Existence of `EcuResourceEstimation.ecuInstance`

Imposition time: IT_SysDesc

[For each `EcuResourceEstimation`, the reference to `EcuInstance` in the role `ecuInstance` shall exist.

]

[constr_5481] Existence of SwcToSwcSignal.dataElement

Imposition time: IT_SysDesc

[Each `SwcToSwcSignal` shall reference exactly two `VariableDataPrototypes` in the role `dataElement`.

]

[constr_5482] Existence of SwcToSwcOperationArguments.direction

Imposition time: IT_SysDesc

[For each `SwcToSwcOperationArguments`, the attribute `direction` shall exist.

]

[constr_5483] Existence of SwcToSwcOperationArguments.operation

Imposition time: IT_SysDesc

[Each `SwcToSwcOperationArguments` element shall reference exactly two `ClientServerOperations` in the role `operation`.

]

[constr_5484] Existence of ForbiddenSignalPath.physicalChannel

Imposition time: IT_SysDesc

[For each `ForbiddenSignalPath`, at least one reference to `PhysicalChannel` in the role `physicalChannel` shall exist.

]

[constr_5485] Existence of PermissibleSignalPath.physicalChannel

Imposition time: IT_SysDesc

[For each `PermissibleSignalPath`, at least one reference to `PhysicalChannel` in the role `physicalChannel` shall exist.

]

[constr_5486] Existence of SwcToEcuMapping.component

Imposition time: IT_SysDesc

[For each `SwcToEcuMapping`, the reference to `SwComponentPrototype` in the role `component` shall exist.

]

[constr_5487] Existence of `SwcToEcuMapping.ecuInstance`

Imposition time: IT_SysDesc

[For each `SwcToEcuMapping` the reference to `EcuInstance` in the role `ecuInstance` shall exist.

]

[constr_5488] Existence of `SwcToImplMapping.component`

Imposition time: IT_EcuExt

[For each `SwcToImplMapping`, the reference to `SwComponentPrototype` in the role `component` shall exist at least once.

]

[constr_5489] Existence of `SwcToImplMapping.componentImplementation`

Imposition time: IT_EcuExt

[For each `SwcToImplMapping`, the reference to `SwImplementation` in the role `componentImplementation` shall exist.

]

[constr_5491] Existence of `ComponentClustering.clusteredComponent`

Imposition time: IT_SysDesc

[For each `ComponentClustering`, at least one reference to `SwComponentPrototype` in the role `clusteredComponent` shall exist.

]

[constr_5492] Existence of `ComponentSeparation.separatedComponent`

Imposition time: IT_SysDesc

[For each `ComponentSeparation` always two references to `SwComponentPrototypes` in the role `separatedComponent` shall exist.

]

[constr_5493] Existence of `J1939ControllerApplication.functionId`

Imposition time: IT_SysDesc

[For each `J1939ControllerApplication`, the attribute `functionId` shall exist.

]

[constr_5494] Existence of `BusMirrorChannel.busMirrorNetworkId`*Imposition time:* IT_SysDesc[For each `BusMirrorChannel`, the attribute `busMirrorNetworkId` shall exist.

]

[constr_5495] Existence of `BusMirrorCanIdRangeMapping.destinationBaseId`*Imposition time:* IT_SysDesc[For each `BusMirrorCanIdRangeMapping`, the attribute `destinationBaseId` shall exist.

]

[constr_5496] Existence of `BusMirrorCanIdRangeMapping.sourceCanIdCode`*Imposition time:* IT_SysDesc[For each `BusMirrorCanIdRangeMapping`, the attribute `sourceCanIdCode` shall exist.

]

[constr_5497] Existence of `BusMirrorCanIdRangeMapping.sourceCanIdMask`*Imposition time:* IT_SysDesc[For each `BusMirrorCanIdRangeMapping`, the attribute `sourceCanIdMask` shall exist.

]

[constr_5498] Existence of `BusMirrorCanIdToCanIdMapping.remappedCanId`*Imposition time:* IT_SysDesc[For each `BusMirrorCanIdToCanIdMapping`, the attribute `remappedCanId` shall exist.

]

[constr_5499] Existence of `BusMirrorLinPidToCanIdMapping.remappedCanId`*Imposition time:* IT_SysDesc[For each `BusMirrorLinPidToCanIdMapping`, the attribute `remappedCanId` shall exist.

]

[constr_9100] Existence of `CanFrameTriggering.canAddressingMode`*Imposition time:* IT_SysDesc

[For each `CanFrameTriggering`, the attribute `canAddressingMode` shall exist.
]

[constr_9101] Existence of `RxIdentifierRange.lowerCanId`*Imposition time:* IT_SysDesc

[For each `RxIdentifierRange`, the attribute `lowerCanId` shall exist.
]

[constr_9102] Existence of `RxIdentifierRange.upperCanId`*Imposition time:* IT_SysDesc

[For each `RxIdentifierRange`, the attribute `upperCanId` shall exist.
]

[constr_9103] Existence of `communicationDirection`*Imposition time:* IT_SysDesc

[For each `CommConnectorPort`, the attribute `communicationDirection` shall exist.
]

[constr_9105] Existence of `DoIpTpConfig.tpConnection`*Imposition time:* IT_SysDesc

[For each `DoIpTpConfig`, the aggregation of at least one `DoIpTpConnection` in the role `tpConnection` shall exist.
]

[constr_9106] Existence of `DoIpTpConnection.doIpSourceAddress`*Imposition time:* IT_SysDesc

[For each `DoIpTpConnection`, the reference to `DoIpLogicAddress` in the role `doIpSourceAddress` shall exist.
]

[constr_9107] Existence of DoIpTpConnection.doIpTargetAddress

Imposition time: IT_SysDesc

[For each `DoIpTpConnection`, the reference to `DoIpLogicAddress` in the role `doIpTargetAddress` shall exist.

]

[constr_9108] Existence of DoIpTpConnection.tpSdu

Imposition time: IT_SysDesc

[For each `DoIpTpConnection`, the reference to `DoIpLogicAddress` in the role `tpSdu` shall exist.

]

[constr_9109] Existence of IPv6ExtHeaderFilterList.allowedIPv6ExtHeader

Imposition time: IT_SysDesc

[For each `IPv6ExtHeaderFilterList`, the attribute `allowedIPv6ExtHeader` shall exist.

]

[constr_9110] Existence of TcpOptionFilterList.allowedTcpOption

Imposition time: IT_SysDesc

[For each `TcpOptionFilterList`, the attribute `allowedTcpOption` shall exist.

]

[constr_9111] Existence of ApplicationEndpoint.networkEndpoint

Imposition time: IT_SysDesc

[For each `ApplicationEndpoint`, the reference to `NetworkEndpoint` in the role `networkEndpoint` shall exist.

]

[constr_9112] Existence of GenericTp.tpTechnology

Status: OBSOLETE

Imposition time: IT_SysDesc

[For each `GenericTp`, the attribute `tpTechnology` shall exist.

]

[constr_9113] Existence of `UdpTp.udpTpPort`

Imposition time: IT_SysDesc

[For each `UdpTp`, the aggregation of `TpPort` in the role `udpTpPort` shall exist.
]

[constr_9114] Existence of `TcpTp.tcpTpPort`

Imposition time: IT_SysDesc

[For each `TcpTp`, the aggregation of `TpPort` in the role `tcpTpPort` shall exist.
]

[constr_9115] Existence of `RtpTp.ssrc`

Status: OBSOLETE

Imposition time: IT_SysDesc

[For each `RtpTp`, the attribute `ssrc` shall exist.
]

[constr_9116] Existence of `RtpTp.tcpUdpConfig`

Status: OBSOLETE

Imposition time: IT_SysDesc

[For each `RtpTp`, the aggregation of `TcpUdpConfig` in the role `tcpUdpConfig` shall exist.
]

[constr_9119] Existence of `Ieee1722Tp.streamIdentifier`

Status: OBSOLETE

Imposition time: IT_SysDesc

[For each `Ieee1722Tp`, the attribute `streamIdentifier` shall exist.
]

[constr_9120] Existence of `HttpTp.protocolVersion`

Status: OBSOLETE

Imposition time: IT_SysDesc

[For each `HttpTp`, the attribute `protocolVersion` shall exist.
]

[constr_9121] Existence of `HttpTp.tcpTpConfig`

Status: OBSOLETE

Imposition time: IT_SysDesc

[For each `HttpTp`, the aggregation of `TcpTp` in the role `tcpTpConfig` shall exist.

]

[constr_9122] Existence of `NetworkEndpoint.networkEndpointAddress`

Imposition time: IT_SysDesc

[For each `NetworkEndpoint`, the aggregation of `NetworkEndpointAddress` in the role `networkEndpointAddress` shall exist.

]

[constr_9123] Existence of `MacMulticastConfiguration.macMulticastGroup`

Imposition time: IT_SysDesc

[For each `MacMulticastConfiguration`, the reference to `MacMulticastGroup` in the role `macMulticastGroup` shall exist.

]

[constr_9124] Existence of `FlexrayFrameTriggering.allowDynamicLSduLength`

Imposition time: IT_SysDesc

[For each `FlexrayFrameTriggering`, the attribute `allowDynamicLSduLength` shall exist.

]

[constr_9125] Existence of `FlexrayFrameTriggering.payloadPreambleIndicator`

Imposition time: IT_SysDesc

[For each `FlexrayFrameTriggering`, the attribute `payloadPreambleIndicator` shall exist.

]

[constr_9126] Existence of `FlexrayAbsolutelyScheduledTiming.slotID`

Imposition time: IT_SysDesc

[For each `FlexrayAbsolutelyScheduledTiming`, the attribute `slotID` shall exist.

]

[constr_9127] Existence of FlexrayAbsolutelyScheduledTiming.communicationCycle

Imposition time: IT_SysDesc

[For each FlexrayAbsolutelyScheduledTiming, the aggregation of CommunicationCycle in the role communicationCycle shall exist.

]

[constr_9128] Existence of CycleCounter.CycleCounter

Imposition time: IT_SysDesc

[For each CycleCounter, the attribute CycleCounter shall exist.

]

[constr_9129] Existence of CycleRepetition.BaseCycle

Imposition time: IT_SysDesc

[For each CycleRepetition, the attribute BaseCycle shall exist.

]

[constr_9130] Existence of CycleRepetition.CycleRepetition

Imposition time: IT_SysDesc

[For each CycleRepetition the attribute CycleRepetition shall exist.

]

[constr_9131] Existence of FrameTriggering.frame

Imposition time: IT_SysDesc

[For each FrameTriggering, the reference to Frame in the role frame shall exist.

]

[constr_9132] Existence of LinSporadicFrame.substitutedFrame

Imposition time: IT_SysDesc

[For each LinSporadicFrame, at least one reference to LinUnconditionalFrame in the role substitutedFrame shall exist.

]

[constr_9133] Existence of `LinEventTriggeredFrame.linUnconditionalFrame`*Imposition time:* IT_SysDesc

[For each `LinEventTriggeredFrame`, at least one reference to `LinUnconditionalFrame` in the role `linUnconditionalFrame` shall exist.

]

[constr_9134] Existence of `ScheduleTableEntry.delay`*Imposition time:* IT_SysDesc

[For each `ScheduleTableEntry` the attribute `delay` shall exist.

]

[constr_9135] Existence of `ScheduleTableEntry.positionInTable`*Imposition time:* IT_SysDesc

[For each `ScheduleTableEntry`, the attribute `positionInTable` shall exist.

]

[constr_9136] Existence of `ApplicationEntry.frameTriggering`*Imposition time:* IT_SysDesc

[For each `ApplicationEntry`, the reference to `FrameTriggering` in the role `frameTriggering` shall exist.

]

[constr_9137] Existence of `AssignFrameId.assignedFrameTriggering`*Imposition time:* IT_SysDesc

[For each `AssignFrameId`, the reference to `LinFrameTriggering` in the role `assignedFrameTriggering` shall exist.

]

[constr_9138] Existence of `UnassignFrameId.unassignedFrameTriggering`*Imposition time:* IT_SysDesc

[For each `UnassignFrameId`, the reference to `LinFrameTriggering` in the role `unassignedFrameTriggering` shall exist.

]

[constr_9139] Existence of AssignFrameIdRange.startIndex*Imposition time:* IT_SysDesc

[For each AssignFrameIdRange, the attribute startIndex shall exist.

]

[constr_9140] Existence of FramePid.index*Imposition time:* IT_SysDesc

[For each FramePid, the attribute index shall exist.

]

[constr_9141] Existence of FramePid.pid*Imposition time:* IT_SysDesc

[For each FramePid, the attribute pid shall exist.

]

[constr_9142] Existence of AssignNad.newNad*Imposition time:* IT_SysDesc

[For each AssignNad, the attribute newNad shall exist.

]

[constr_9143] Existence of ConditionalChangeNad.byte*Imposition time:* IT_SysDesc

[For each ConditionalChangeNad, the attribute byte shall exist.

]

[constr_9144] Existence of ConditionalChangeNad.id*Imposition time:* IT_SysDesc

[For each ConditionalChangeNad, the attribute id shall exist.

]

[constr_9145] Existence of ConditionalChangeNad.invert*Imposition time:* IT_SysDesc

[For each ConditionalChangeNad, the attribute invert shall exist.

]

[constr_9146] Existence of ConditionalChangeNad.mask*Imposition time:* IT_SysDesc

[For each ConditionalChangeNad, the attribute mask shall exist.

]

[constr_9147] Existence of ConditionalChangeNad.newNad*Imposition time:* IT_SysDesc

[For each ConditionalChangeNad, the attribute newNad shall exist.

]

[constr_9148] Existence of DataDumpEntry.byteValue*Imposition time:* IT_SysDesc

[For each DataDumpEntry, 5 byteValues shall be defined.

]

[constr_9149] Existence of FreeFormat.byteValue*Imposition time:* IT_SysDesc

[For each FreeFormat, 8 byteValues shall be defined.

]

[constr_9150] Existence of NmEcu.ecuInstance*Imposition time:* IT_SysDesc

[For each NmEcu, the reference to EcuInstance in the role ecuInstance shall exist.

]

[constr_9151] Existence of nmDataCycle*Imposition time:* IT_SysDesc

[For each FlexrayNmCluster, the attribute nmDataCycle shall exist.

]

[constr_9152] Existence of nmRemoteSleepIndicationTime*Imposition time:* IT_SysDesc

[For each FlexrayNmCluster, the attribute nmRemoteSleepIndicationTime shall exist.

]

[constr_9153] Existence of nmRepeatMessageTime*Imposition time:* IT_SysDesc

[For each `FlexrayNmCluster`, the attribute `nmRepeatMessageTime` shall exist.
]

[constr_9154] Existence of nmRepetitionCycle*Imposition time:* IT_SysDesc

[For each `FlexrayNmCluster`, the attribute `nmRepetitionCycle` shall exist.
]

[constr_9155] Existence of nmVotingCycle*Imposition time:* IT_SysDesc

[For each `FlexrayNmCluster`, the attribute `nmVotingCycle` shall exist.
]

[constr_9156] Existence of nmScheduleVariant*Imposition time:* IT_SysDesc

[For each `FlexrayNmClusterCoupling`, the attribute `nmScheduleVariant` shall exist.
]

[constr_9157] Existence of nmBusloadReductionActive*Imposition time:* IT_SysDesc

[For each `CanNmCluster`, the attribute `nmBusloadReductionActive` shall exist.
]

[constr_9158] Existence of nmImmediateNmTransmissions*Imposition time:* IT_SysDesc

[For each `CanNmCluster`, the attribute `nmImmediateNmTransmissions` shall exist.
]

[constr_9159] Existence of nmMessageTimeoutTime*Imposition time:* IT_SysDesc

[For each `CanNmCluster`, the attribute `nmMessageTimeoutTime` shall exist.
]

[constr_9160] Existence of nmMsgCycleTime*Imposition time:* IT_SysDesc[For each `CanNmCluster` the attribute `nmMsgCycleTime` shall exist.

]

[constr_9161] Existence of nmNetworkTimeout*Imposition time:* IT_SysDesc[For each `CanNmCluster`, the attribute `nmNetworkTimeout` shall exist.

]

[constr_9162] Existence of nmRemoteSleepIndicationTime*Imposition time:* IT_SysDesc[For each `CanNmCluster`, the attribute `nmRemoteSleepIndicationTime` shall exist.

]

[constr_9163] Existence of nmRepeatMessageTime*Imposition time:* IT_SysDesc[For each `CanNmCluster`, the attribute `nmRepeatMessageTime` shall exist.

]

[constr_9164] Existence of nmWaitBusSleepTime*Imposition time:* IT_SysDesc[For each `CanNmCluster`, the attribute `nmWaitBusSleepTime` shall exist.

]

[constr_9165] Existence of nmBusloadReductionEnabled*Imposition time:* IT_SysDesc[For each `CanNmClusterCoupling`, the attribute `nmBusloadReductionEnabled` shall exist.

]

[constr_9166] Existence of nmImmediateRestartEnabled*Imposition time:* IT_SysDesc

[For each `CanNmClusterCoupling`, the attribute `nmImmediateRestartEnabled` shall exist.

]

[constr_9167] Existence of J1939NodeName.arbitraryAddressCapable*Imposition time:* IT_SysDesc

[For each `J1939NodeName`, the attribute `arbitraryAddressCapable` shall exist.

]

[constr_9168] Existence of J1939NodeName.ecuInstance*Imposition time:* IT_SysDesc

[For each `J1939NodeName`, the attribute `ecuInstance` shall exist.

]

[constr_9169] Existence of J1939NodeName.function*Imposition time:* IT_SysDesc

[For each `J1939NodeName`, the attribute `function` shall exist.

]

[constr_9170] Existence of J1939NodeName.functionInstance*Imposition time:* IT_SysDesc

[For each `J1939NodeName`, the attribute `functionInstance` shall exist.

]

[constr_9171] Existence of J1939NodeName.identityNumber*Imposition time:* IT_SysDesc

[For each `J1939NodeName`, the attribute `identityNumber` shall exist.

]

[constr_9172] Existence of J1939NodeName.industryGroup*Imposition time:* IT_SysDesc

[For each `J1939NodeName`, the attribute `industryGroup` shall exist.

]

[constr_9173] Existence of J1939NodeName.manufacturerCode*Imposition time:* IT_SysDesc

[For each J1939NodeName, the attribute manufacturerCode shall exist.

]

[constr_9174] Existence of J1939NodeName.vehicleSystem*Imposition time:* IT_SysDesc

[For each J1939NodeName, the attribute vehicleSystem shall exist.

]

[constr_9175] Existence of J1939NodeName.vehicleSystemInstance*Imposition time:* IT_SysDesc

[For each J1939NodeName, the attribute vehicleSystemInstance shall exist.

]

[constr_9176] Existence of StaticPart.iPdu*Imposition time:* IT_SysDesc

[For each StaticPart, the reference to ISignalIPdu in role iPdu shall exist.

]

[constr_9177] Existence of DynamicPartAlternative.initialDynamicPart*Imposition time:* IT_SysDesc

[For each DynamicPartAlternative, the attribute initialDynamicPart shall exist.

]

[constr_9178] Existence of DynamicPartAlternative.initialDynamicPart*Imposition time:* IT_SysDesc

[For each DynamicPartAlternative the attribute initialDynamicPart shall exist.

]

[constr_9179] Existence of `DynamicPartAlternative.iPdu`*Imposition time:* IT_SysDesc

[For each `DynamicPartAlternative`, the reference to `ISignalIPdu` in role `iPdu` shall exist.

]

[constr_9180] Existence of `DynamicPartAlternative.selectorFieldCode`*Imposition time:* IT_SysDesc

[For each `DynamicPartAlternative`, the attribute `selectorFieldCode` shall exist.

]

[constr_9181] Existence of `MultiplexedPart.segmentPosition`*Imposition time:* IT_SysDesc

[For each `MultiplexedPart` the aggregation of `SegmentPosition` in role `segmentPosition` shall exist.

]

[constr_9182] Existence of `SegmentPosition.segmentByteOrder`*Imposition time:* IT_SysDesc

[For each `SegmentPosition`, the attribute `segmentByteOrder` shall exist.

]

[constr_9183] Existence of `SegmentPosition.segmentLength`*Imposition time:* IT_SysDesc

[For each `SegmentPosition`, the attribute `segmentLength` shall exist.

]

[constr_9184] Existence of `SegmentPosition.segmentPosition`*Imposition time:* IT_SysDesc

[For each `SegmentPosition`, the attribute `segmentPosition` shall exist.

]

[constr_9185] Existence of `TransmissionModeCondition.dataFilter`

Imposition time: IT_SysDesc

[For each `TransmissionModeCondition`, the aggregation of `DataFilter` in the role `dataFilter` shall exist.

]

[constr_9186] Existence of `TransmissionModeCondition.iSignalInIPdu`

Imposition time: IT_SysDesc

[For each `TransmissionModeCondition`, the reference to `ISignalToIPduMapping` in the role `iSignalInIPdu` shall exist.

]

[constr_9187] Existence of `ModeDrivenTransmissionModeCondition.modeDeclaration`

Imposition time: IT_SysDesc

[For each `ModeDrivenTransmissionModeCondition`, the reference to `ModeDeclaration` in the role `modeDeclaration` shall exist.

]

[constr_9188] Existence of `ModeDrivenTransmissionModeCondition.timePeriod`

Imposition time: IT_SysDesc

[For each `CyclicTiming`, the aggregation of `TimeRangeType` in the role `timePeriod` shall exist.

]

[constr_9189] Existence of `EventControlledTiming.numberOfRepetitions`

Imposition time: IT_SysDesc

[For each `EventControlledTiming`, the attribute `numberOfRepetitions` shall exist.

]

[constr_9190] Existence of `TimeRangeType.value`

Imposition time: IT_SysDesc

[For each `TimeRangeType`, the attribute `value` shall exist.

]

[constr_9191] Existence of `RelativeTolerance.relative`*Imposition time:* IT_SysDesc[For each `RelativeTolerance`, the attribute `relative` shall exist.

]

[constr_9192] Existence of `AbsoluteTolerance.absolute`*Imposition time:* IT_SysDesc[For each `AbsoluteTolerance`, the attribute `absolute` shall exist.

]

[constr_9193] Existence of `TriggerIPduSendCondition.modeDeclaration`*Imposition time:* IT_SysDesc[For each `TriggerIPduSendCondition`, the reference to `ModeDeclaration` in role `modeDeclaration` shall exist.

]

[constr_9194] Existence of `DcmIPdu.diagPduType`*Imposition time:* IT_SysDesc[For each `DcmIPdu`, the attribute `diagPduType` shall exist.

]

[constr_9195] Existence of `PduToFrameMapping.packingByteOrder`*Imposition time:* IT_SysDesc[For each `PduToFrameMapping`, the attribute `packingByteOrder` shall exist.

]

[constr_9196] Existence of `PduToFrameMapping.startPosition`*Imposition time:* IT_SysDesc[For each `PduToFrameMapping`, the attribute `startPosition` shall exist.

]

[constr_9197] Existence of `PduToFrameMapping.pdu`*Imposition time:* IT_SysDesc[For each `PduToFrameMapping`, the reference to `Pdu` in the role `pdu` shall exist.

]

[constr_9198] Existence of PduTriggering.iPdu*Imposition time:* IT_SysDesc

[For each PduTriggering, the reference to Pdu in the role iPdu shall exist.

]

[constr_9199] Existence of ISignalIPduGroup.communicationDirection*Imposition time:* IT_SysDesc

[For each ISignalIPduGroup, the attribute communicationDirection shall exist.

]

[constr_9200] Existence of ContainerIPdu.headerType*Imposition time:* IT_SysDesc

[For each ContainerIPdu the attribute headerType shall exist.

]

[constr_9201] Existence of ContainerIPdu.rxAcceptContainedIPdu*Imposition time:* IT_SysDesc

[For each ContainerIPdu the attribute rxAcceptContainedIPdu shall exist.

]

[constr_9202] Existence of ContainedIPduProps.collectionSemantics*Imposition time:* IT_SysDesc

[For each ContainedIPduProps the attribute collectionSemantics shall exist.

]

[constr_9203] Existence of SecuredIPdu.payload*Imposition time:* IT_SysDesc

[For each SecuredIPdu, the reference to PduTriggering in the role payload shall exist.

]

[constr_9204] Existence of SecuredIPdu.secureCommunicationProps*Imposition time:* IT_SysDesc

[For each `SecuredIPdu` the aggregation of `SecureCommunicationProps` in the role `secureCommunicationProps`, shall exist.

]

[constr_9205] Existence of SecureCommunicationProps.dataId*Imposition time:* IT_SysDesc

[For each `SecureCommunicationProps`, the attribute `dataId` shall exist.

]

[constr_9206] Existence of CryptoServiceKey.length*Imposition time:* IT_SysDesc

[For each `CryptoServiceKey`, the attribute `length` shall exist.

]

[constr_9207] Existence of EndToEndProtectionISignalIPdu.iSignalIPdu*Status:* OBSOLETE*Imposition time:* IT_SysDesc

[For each `EndToEndProtectionISignalIPdu`, the reference to `ISignalIPdu` in the role `iSignalIPdu` shall exist.

]

[constr_9208] Existence of EndToEndProtectionISignalIPdu.iSignalGroup*Status:* OBSOLETE*Imposition time:* IT_SysDesc

[For each `EndToEndProtectionISignalIPdu`, the reference to `ISignalGroup` in the role `iSignalGroup` shall exist.

]

[constr_9209] Existence of EndToEndProtectionISignalIPdu.dataOffset*Status:* OBSOLETE*Imposition time:* IT_SysDesc

[For each `EndToEndProtectionISignalIPdu`, the attribute `dataOffset` shall exist.

]

[constr_9210] Existence of `InitialSdDelayConfig.initialDelayMaxValue` aggregated by `SomeipSdClientServiceInstanceConfig`

Imposition time: IT_SysDesc

[For each `InitialSdDelayConfig` that is aggregated by a `SomeipSdClientServiceInstanceConfig` in the role `initialFindBehavior`, the attribute `initialDelayMaxValue` shall exist.

]

[constr_9211] Existence of `InitialSdDelayConfig.initialDelayMinValue` aggregated by `SomeipSdClientServiceInstanceConfig`

Imposition time: IT_SysDesc

[For each `InitialSdDelayConfig` that is aggregated by a `SomeipSdClientServiceInstanceConfig` in the role `initialFindBehavior`, the attribute `initialDelayMinValue` shall exist.

]

[constr_9212] Existence of `SomeipSdClientEventGroupTimingConfig.timeToLive`

Imposition time: IT_SysDesc

[For each `SomeipSdClientEventGroupTimingConfig`, the attribute `timeToLive` shall exist.

]

[constr_9213] Existence of `RequestResponseDelay.minValue` aggregated by `SomeipSdClientEventGroupTimingConfig`

Imposition time: IT_SysDesc

[For each `RequestResponseDelay` that is aggregated by a `SomeipSdClientEventGroupTimingConfig` in the role `requestResponseDelay`, the attribute `minValue` shall exist.

]

[constr_9214] Existence of `RequestResponseDelay.maxValue` aggregated by `SomeipSdClientEventGroupTimingConfig`

Imposition time: IT_SysDesc

[For each `RequestResponseDelay` that is aggregated by a `SomeipSdClientEventGroupTimingConfig` in the role `requestResponseDelay`, the attribute `maxValue` shall exist.

]

[constr_9215] Existence of `InitialSdDelayConfig.initialDelayMaxValue` aggregated by `SomeipSdServerServiceInstanceConfig`

Imposition time: IT_SysDesc

[For each `InitialSdDelayConfig` that is aggregated by a `SomeipSdServerServiceInstanceConfig` in the role `initialOfferBehavior`, the attribute `initialDelayMaxValue` shall exist.

]

[constr_9216] Existence of `InitialSdDelayConfig.initialDelayMinValue` aggregated by `SomeipSdServerServiceInstanceConfig`

Imposition time: IT_SysDesc

[For each `InitialSdDelayConfig` that is aggregated by a `SomeipSdServerServiceInstanceConfig` in the role `initialOfferBehavior`, the attribute `initialDelayMinValue` shall exist.

]

[constr_9217] Existence of `SomeipSdServerServiceInstanceConfig.serviceOfferTimeToLive`

Imposition time: IT_SysDesc

[For each `SomeipSdServerServiceInstanceConfig`, the attribute `serviceOfferTimeToLive` shall exist.

]

[constr_9218] Existence of `RequestResponseDelay.minValue` aggregated by `SomeipSdServerServiceInstanceConfig`

Imposition time: IT_SysDesc

[For each `RequestResponseDelay` that is aggregated by a `SomeipSdServerServiceInstanceConfig` in the role `requestResponseDelay`, the attribute `minValue` shall exist.

]

[constr_9219] Existence of `RequestResponseDelay.maxValue` aggregated by `SomeipSdServerServiceInstanceConfig`

Imposition time: IT_SysDesc

[For each `RequestResponseDelay` that is aggregated by a `SomeipSdServerServiceInstanceConfig` in the role `requestResponseDelay`, the attribute `maxValue` shall exist.

]

[constr_9220] Existence of `RequestResponseDelay.minValue` aggregated by `SomeipSdServerEventGroupTimingConfig`

Imposition time: IT_SysDesc

[For each `RequestResponseDelay` that is aggregated by a `SomeipSdServerEventGroupTimingConfig` in the role `requestResponseDelay`, the attribute `minValue` shall exist.

]

[constr_9221] Existence of `RequestResponseDelay.maxValue` aggregated by `SomeipSdServerEventGroupTimingConfig`

Imposition time: IT_SysDesc

[For each `RequestResponseDelay` that is aggregated by a `SomeipSdServerEventGroupTimingConfig` in the role `requestResponseDelay`, the attribute `maxValue` shall exist.

]

[constr_9222] Existence of `ISignal.dataTypePolicy`

Imposition time: IT_SysDesc

[For each `ISignal`, the attribute `dataTypePolicy` shall exist.

]

[constr_9223] Existence of `ISignal.length`

Imposition time: IT_SysDesc

[For each `ISignal`, the attribute `length` shall exist.

]

[constr_9224] Existence of `ISignal.systemSignal`

Imposition time: IT_SysDesc

[For each `ISignal`, the reference to `SystemSignal` in the role `systemSignal` shall exist.

]

[constr_9225] Existence of `ISignalGroup.systemSignalGroup`

Imposition time: IT_SysDesc

[For each `ISignalGroup`, the reference to `SystemSignalGroup` in the role `systemSignalGroup` shall exist.

]

[constr_9226] Existence of `TpConfig.communicationCluster`

Imposition time: IT_SysDesc

[For each `TpConfig`, the reference to `CommunicationCluster` in the role `communicationCluster` shall exist.

]

[constr_9227] Existence of `TpAddress.tpAddress`

Imposition time: IT_SysDesc

[For each `TpAddress`, the attribute `tpAddress` shall exist.

]

[constr_9228] Existence of `FlexrayTpConfig.pduPool`

Imposition time: IT_SysDesc

[For each `FlexrayTpConfig`, the aggregation of `FlexrayTpPduPool` in the role `pduPool` shall exist at least once.

]

[constr_9229] Existence of `FlexrayTpConfig.tpAddress`

Imposition time: IT_SysDesc

[For each `FlexrayTpConfig`, the aggregation of `TpAddress` in the role `tpAddress` shall exist at least once.

]

[constr_9230] Existence of `FlexrayTpConfig.tpEcu`

Imposition time: IT_SysDesc

[For each `FlexrayTpConfig`, the aggregation of `FlexrayTpEcu` in the role `tpEcu` shall exist at least once.

]

[constr_9231] Existence of `FlexrayTpConnection.directTpSdu`

Imposition time: IT_SysDesc

[For each `FlexrayTpConnection`, the reference to `IPdu` in the role `directTpSdu` shall exist.

]

[constr_9233] Existence of FlexrayTpConnection.receiver

Imposition time: IT_SysDesc

[For each FlexrayTpConnection, the reference to FlexrayTpNode in the role receiver shall exist at least once.

]

[constr_9234] Existence of FlexrayTpConnection.tpConnectionControl

Imposition time: IT_SysDesc

[For each FlexrayTpConnection, the reference to FlexrayTpConnectionControl in the role tpConnectionControl shall exist.

]

[constr_9235] Existence of FlexrayTpConnection.transmitter

Imposition time: IT_SysDesc

[For each FlexrayTpConnection, the reference to FlexrayTpNode in the role transmitter shall exist.

]

[constr_9236] Existence of FlexrayTpEcu.ecuInstance

Imposition time: IT_SysDesc

[For each FlexrayTpEcu, the reference to EcuInstance in the role ecuInstance shall exist.

]

[constr_9237] Existence of FlexrayTpEcu.fullDuplexEnabled

Imposition time: IT_SysDesc

[For each FlexrayTpEcu, the attribute fullDuplexEnabled shall exist.

]

[constr_9238] Existence of FlexrayArTpChannel.ackType

Imposition time: IT_SysDesc

[For each FlexrayArTpChannel, the attribute ackType shall exist.

]

[constr_9239] Existence of FlexrayArTpChannel.extendedAddressing*Imposition time:* IT_SysDesc

[For each FlexrayArTpChannel, the attribute extendedAddressing shall exist.
]

[constr_9240] Existence of FlexrayArTpChannel.maximumMessageLength*Imposition time:* IT_SysDesc

[For each FlexrayArTpChannel, the attribute maximumMessageLength shall exist.
]

[constr_9241] Existence of FlexrayArTpChannel.minimumSeparationTime*Imposition time:* IT_SysDesc

[For each FlexrayArTpChannel, the attribute minimumSeparationTime shall exist.
]

[constr_9242] Existence of FlexrayArTpChannel.multicastSegmentation*Imposition time:* IT_SysDesc

[For each FlexrayArTpChannel, the attribute multicastSegmentation shall exist.
]

[constr_9243] Existence of FlexrayArTpChannel.tpConnection*Imposition time:* IT_SysDesc

[For each FlexrayArTpChannel, the aggregation of FlexrayArTpConnection in the role tpConnection shall exist at least once.
]

[constr_9244] Existence of FlexrayArTpConnection.directTpSdu*Imposition time:* IT_SysDesc

[For each FlexrayArTpConnection, the reference to IPdu in the role directTpSdu shall exist.
]

[constr_9245] Existence of FlexrayArTpConnection.source

Imposition time: IT_SysDesc

[For each FlexrayArTpConnection, the reference to FlexrayArTpNode in the role source shall exist.

]

[constr_9246] Existence of FlexrayArTpConnection.target

Imposition time: IT_SysDesc

[For each FlexrayArTpConnection, at least one reference to FlexrayArTpNode in the role target shall exist.

]

[constr_9247] Existence of CanTpConfig.tpAddress

Imposition time: IT_SysDesc

[For each CanTpConfig, the aggregation of CanTpAddress in the role tpAddress shall exist at least once.

]

[constr_9248] Existence of CanTpConfig.tpChannel

Imposition time: IT_SysDesc

[For each CanTpConfig, the aggregation of CanTpChannel in the role tpChannel shall exist at least once.

]

[constr_9249] Existence of CanTpConfig.tpConnection

Imposition time: IT_SysDesc

[For each CanTpConfig, the aggregation of CanTpConnection in the role tpConnection shall exist at least once.

]

[constr_9250] Existence of CanTpConfig.tpEcu

Imposition time: IT_SysDesc

[For each CanTpConfig, the aggregation of CanTpEcu in the role tpEcu shall exist at least once.

]

[constr_9251] Existence of [CanTpConfig.tpNode](#)

Imposition time: IT_SysDesc

[For each [CanTpConfig](#), the aggregation of [CanTpNode](#) in the role [tpNode](#) shall exist at least once.

]

[constr_9252] Existence of [CanTpConnection.addressingFormat](#)

Imposition time: IT_SysDesc

[For each [CanTpConnection](#), the attribute [addressingFormat](#) shall exist.

]

[constr_9253] Existence of [CanTpConnection.canTpChannel](#)

Imposition time: IT_SysDesc

[For each [CanTpConnection](#), the reference to [CanTpChannel](#) in the role [canTpChannel](#) shall exist.

]

[constr_9254] Existence of [CanTpConnection.dataPdu](#)

Imposition time: IT_SysDesc

[For each [CanTpConnection](#), the reference to [NPdu](#) in the role [dataPdu](#) shall exist.

]

[constr_9255] Existence of [CanTpConnection.paddingActivation](#)

Imposition time: IT_SysDesc

[For each [CanTpConnection](#), the attribute [paddingActivation](#) shall exist.

]

[constr_9256] Existence of [CanTpConnection.tpSdu](#)

Imposition time: IT_SysDesc

[For each [CanTpConnection](#), the reference to [IPdu](#) in the role [tpSdu](#) shall exist.

]

[constr_9257] Existence of [CanTpAddress.tpAddress](#)

Imposition time: IT_SysDesc

[For each [CanTpAddress](#), the attribute [tpAddress](#) shall exist.

]

[constr_9258] Existence of `CanTpEcu.ecuInstance`*Imposition time:* IT_SysDesc[For each `CanTpEcu`, the attribute `ecuInstance` shall exist.

]

[constr_9259] Existence of `LinTpConfig.tpAddress`*Imposition time:* IT_SysDesc[For each `LinTpConfig`, at least one `TpAddress` shall be aggregated by `LinTpConfig` in the role `tpAddress`.

]

[constr_9260] Existence of `LinTpConnection.dataPdu`*Imposition time:* IT_SysDesc[For each `LinTpConnection`, the reference to `NPdu` in the role `dataPdu` shall exist.

]

[constr_9261] Existence of `LinTpConnection.linTpNSdu`*Imposition time:* IT_SysDesc[For each `LinTpConnection`, the reference to `IPdu` in the role `linTpNSdu` shall exist.

]

[constr_9262] Existence of `LinTpConnection.receiver`*Imposition time:* IT_SysDesc[For each `LinTpConnection`, at least one reference to `LinTpNode` in the role `receiver` shall exist.

]

[constr_9263] Existence of `LinTpConnection.transmitter`*Imposition time:* IT_SysDesc[For each `LinTpConnection`, the reference to `LinTpNode` in the role `transmitter` shall exist.

]

[constr_9264] Existence of J1939TpConfig.tpAddress*Imposition time:* IT_SysDesc

[For each [J1939TpConfig](#), at least one [TpAddress](#) shall be aggregated in the role [tpAddress](#).

]

[constr_9265] Existence of J1939TpConfig.tpConnection*Imposition time:* IT_SysDesc

[For each [J1939TpConfig](#), at least one [J1939TpConnection](#) shall be aggregated in the role [tpConnection](#).

]

[constr_9266] Existence of J1939TpConfig.tpNode*Imposition time:* IT_SysDesc

[For each [J1939TpConfig](#), at least one [J1939TpNode](#) shall be aggregated in the role [tpNode](#).

]

[constr_9267] Existence of J1939TpConnection.broadcast*Status:* OBSOLETE*Imposition time:* IT_SysDesc

[For each [J1939TpConnection](#), the attribute [broadcast](#) shall exist.

]

[constr_9268] Existence of J1939TpConnection.dataPdu*Imposition time:* IT_SysDesc

[For each [J1939TpConnection](#), the reference to [NPdu](#) in the role [dataPdu](#) shall exist.

]

[constr_9269] Existence of J1939TpConnection.flowControlPdu*Imposition time:* IT_SysDesc

[For each [J1939TpConnection](#), at least one reference to [NPdu](#) in the role [flowControlPdu](#).

]

[constr_9270] Existence of `TlsCryptoCipherSuite.version`*Imposition time:* IT_SysDesc[For each `TlsCryptoCipherSuite`, the attribute `version` shall exist.

]

[constr_9271] Existence of `TlsPskIdentity.pskIdentity`*Imposition time:* IT_SysDesc[For each `TlsPskIdentity`, the attribute `pskIdentity` shall exist.

]

[constr_9272] Existence of `TlsPskIdentity.preSharedKey`*Imposition time:* IT_SysDesc[For each `TlsPskIdentity`, the reference to `CryptoServiceKey` in the role `preSharedKey` shall exist.

]

[constr_9273] Existence of `DataTransformation.executeDespiteDataUnavailability`*Imposition time:* IT_SysDesc[For each `DataTransformation`, the attribute `executeDespiteDataUnavailability` shall exist.

]

[constr_9274] Existence of `DataTransformation.transformerChain`*Imposition time:* IT_SysDesc[For each `DataTransformation`, at least one reference to `TransformationTechnology` in the role `transformerChain` shall exist.

]

[constr_9275] Existence of `TransformationTechnology.bufferProperties`*Imposition time:* IT_SysDesc[For each `TransformationTechnology`, a `BufferProperties` element shall be aggregated by `TransformationTechnology` in the role `bufferProperties`.

]

[constr_9276] Existence of TransformationTechnology.protocol*Imposition time:* IT_SysDesc

[For each TransformationTechnology, the attribute protocol shall exist.

]

[constr_9277] Existence of TransformationTechnology.transformerClass*Imposition time:* IT_SysDesc

[For each TransformationTechnology, the attribute transformerClass shall exist.

]

[constr_9278] Existence of TransformationTechnology.version*Imposition time:* IT_SysDesc

[For each TransformationTechnology, the attribute version shall exist.

]

[constr_9279] Existence of BufferProperties.headerLength*Imposition time:* IT_SysDesc

[For each BufferProperties, the attribute headerLength shall exist.

]

[constr_9280] Existence of BufferProperties.inPlace*Imposition time:* IT_SysDesc

[For each BufferProperties, the attribute inPlace shall exist.

]

[constr_9281] Existence of TransformationISignalProps.dataPdu*Imposition time:* IT_SysDesc

[For each TransformationISignalProps, the reference to TransformationTechnology in the role transformer shall exist.

]

[constr_9282] Existence of `SOMEIPTransformationDescription.alignment`

Imposition time: IT_SysDesc

[For each `SOMEIPTransformationDescription`, the attribute `alignment` shall exist.

]

[constr_9283] Existence of `SOMEIPTransformationDescription.byteOrder`

Imposition time: IT_SysDesc

[For each `SOMEIPTransformationDescription`, the attribute `byteOrder` shall exist.

]

[constr_9284] Existence of `SOMEIPTransformationDescription.interfaceVersion`

Imposition time: IT_SysDesc

[For each `SOMEIPTransformationDescription`, the attribute `interfaceVersion` shall exist.

]

[constr_9285] Existence of `DataPrototypeInSenderReceiverInterfaceInstanceRef.targetDataPrototypeInSr`

Imposition time: IT_SysDesc

[For each `DataPrototypeInSenderReceiverInterfaceInstanceRef`, the reference to `DataPrototype` in the role `targetDataPrototypeInSr` shall exist.

]

[constr_9286] Existence of `DataPrototypeInClientServerInterfaceInstanceRef.targetDataPrototypeInCs`

Imposition time: IT_SysDesc

[For each `DataPrototypeInClientServerInterfaceInstanceRef`, the reference to `DataPrototype` in the role `targetDataPrototypeInCs` shall exist.

]

[constr_9287] Existence of EndToEndTransformationDescription.profileName

Imposition time: IT_SysDesc

[For each `EndToEndTransformationDescription`, the attribute `profileName` shall exist.

]

[constr_9288] Existence of TlvDataIdDefinition.id

Imposition time: IT_SysDesc

[For each `TlvDataIdDefinition`, the attribute `id` shall exist.

]

[constr_9289] Existence of FrameMapping.sourceFrame

Imposition time: IT_SysDesc

[For each `FrameMapping`, the reference to `FrameTriggering` in the role `sourceFrame` shall exist.

]

[constr_9290] Existence of FrameMapping.targetFrame

Imposition time: IT_SysDesc

[For each `FrameMapping`, the reference to `FrameTriggering` in the role `targetFrame` shall exist.

]

[constr_9291] Existence of Gateway.ecu

Imposition time: IT_SysDesc

[For each `Gateway`, the reference to `EcuInstance` in the role `ecu` shall exist.

]

[constr_9292] Existence of IPduMapping.sourceIPdu

Imposition time: IT_SysDesc

[For each `IPduMapping`, the reference to `PduTriggering` in the role `sourceIPdu` shall exist.

]

[constr_9293] Existence of IPduMapping.targetIPdu

Imposition time: IT_SysDesc

[Each IPduMapping shall aggregate a TargetIPduRef in the role targetIPdu.
]

[constr_9294] Existence of TargetIPduRef.targetIPdu

Imposition time: IT_SysDesc

[For each TargetIPduRef, the reference to PduTriggering in the role targetIPdu.
]

[constr_9295] Existence of PduMappingDefaultValue.defaultValueElement

Imposition time: IT_SysDesc

[For each PduMappingDefaultValue, at least one DefaultValueElement shall be aggregated by PduMappingDefaultValue in the role defaultValueElement.
]

[constr_9296] Existence of DefaultValueElement.elementPosition

Imposition time: IT_SysDesc

[For each DefaultValueElement, the attribute elementPosition shall exist.
]

[constr_9297] Existence of DefaultValueElement.elementByteValue

Imposition time: IT_SysDesc

[For each DefaultValueElement, the attribute elementByteValue shall exist.
]

[constr_9298] Existence of ISignalMapping.sourceSignal

Imposition time: IT_SysDesc

[For each ISignalMapping, the reference to ISignalTriggering in the role sourceSignal shall exist.
]

[constr_9299] Existence of `ISignalMapping.targetSignal`

Imposition time: IT_SysDesc

[For each `ISignalMapping`, the reference to `ISignalTriggering` in the role `targetSignal` shall exist.

]

[constr_9300] Existence of `FlatMap.instance`

Imposition time: IT_EcuExt

[For each `FlatMap`, at least one `FlatInstanceDescriptor` shall be aggregated by `FlatMap` in the role `instance`.

]

[constr_9301] Existence of `AliasNameAssignment.shortLabel`

Imposition time: IT_EcuExt

[For each `AliasNameAssignment`, the attribute `shortLabel` shall exist.

]

[constr_9302] Existence of `GlobalTimeDomain.domainId`

Imposition time: IT_SysDesc

[If a `GlobalTimeDomain` defines a `GlobalTimeDomain.globalTimeMaster` or `GlobalTimeDomain.slave`, then the attribute `GlobalTimeDomain.domainId` shall exist.

]

[constr_9303] Existence of `GlobalTimeMaster.communicationConnector`

Imposition time: IT_SysDesc

[For each `GlobalTimeMaster`, the reference to `CommunicationConnector` in the role `communicationConnector` shall exist.

]

[constr_9304] Existence of `GlobalTimeMaster.isSystemWideGlobalTimeMaster`

Imposition time: IT_SysDesc

[For each `GlobalTimeMaster`, the attribute `isSystemWideGlobalTimeMaster` shall exist.

]

[constr_9305] Existence of `GlobalTimeMaster.syncPeriod`*Imposition time:* IT_SysDesc[For each `GlobalTimeMaster`, the attribute `syncPeriod` shall exist.

]

[constr_9306] Existence of `GlobalTimeSlave.communicationConnector`*Imposition time:* IT_SysDesc[For each `GlobalTimeSlave`, the reference to `CommunicationConnector` in the role `communicationConnector` shall exist.

]

[constr_9307] Existence of `GlobalTimeGateway.master`*Imposition time:* IT_SysDesc[For each `GlobalTimeGateway`, the reference to `GlobalTimeMaster` in the role `master` shall exist.

]

[constr_9308] Existence of `GlobalTimeGateway.slave`*Imposition time:* IT_SysDesc[For each `GlobalTimeGateway`, the reference to `GlobalTimeSlave` in the role `slave` shall exist.

]

[constr_9309] Existence of `GlobalTimeCanMaster.syncConfirmationTimeout`*Imposition time:* IT_SysDesc[For each `GlobalTimeCanMaster`, the attribute `syncConfirmationTimeout` shall exist.

]

[constr_9310] Existence of `GlobalTimeCanSlave.crcValidated`*Imposition time:* IT_SysDesc[For each `GlobalTimeCanSlave`, the attribute `crcValidated` shall exist.

]

[constr_9311] Existence of EthGlobalTimeDomainProps.messageCompliance

Imposition time: IT_SysDesc

[For each EthGlobalTimeDomainProps, the attribute messageCompliance shall exist.

]

[constr_9312] Existence of EthGlobalTimeManagedCouplingPort.pdelayResponseEnabled

Imposition time: IT_SysDesc

[For each EthGlobalTimeManagedCouplingPort, the attribute pdelayResponseEnabled shall exist.

]

[constr_9313] Existence of GlobalTimeCouplingPortProps.propagationDelay

Imposition time: IT_SysDesc

[For each GlobalTimeCouplingPortProps, the attribute propagationDelay shall exist.

]

[constr_9314] Existence of GlobalTimeFrMaster.crcSecured

Imposition time: IT_SysDesc

[For each GlobalTimeFrMaster, the attribute crcSecured shall exist.

]

[constr_9315] Existence of GlobalTimeFrSlave.crcValidated

Imposition time: IT_SysDesc

[For each GlobalTimeFrSlave, the attribute crcValidated shall exist.

]

[constr_9317] StateDependentFirewall.firewallStateModeDeclaration reference restriction

Imposition time: IT_SysDesc

[Each StateDependentFirewall shall only reference ModeDeclarations in the role firewallStateModeDeclaration that are aggregated by the same ModeDeclarationGroup.

]

[constr_9318] Reception of `CanFrameTriggerings` with the same `identifier` by an `EcuInstance`

Imposition time: IT_SysDesc

[For all `CanFrameTriggerings` on the same `PhysicalChannel` that refer to a `FramePort` with the `communicationDirection = in` of the same `EcuInstance` the condition applies that no two of these `CanFrameTriggerings` shall have the same `identifier` and the same `canAddressingMode` assigned.

]

[constr_9319] Value of `BusMirrorChannelMappingCan.mirroringProtocol`

Imposition time: IT_SysDesc

[Within the scope of a `BusMirrorChannelMappingCan`, if the (see [constr_3468]) `PduTriggering` referenced in the role `BusMirrorChannelMappingCan.targetPduTriggering` is in turn referenced in the role `pduTriggering` by a `CanFrameTriggering` where the aggregation in the role `canXlFrameTriggeringProps` exists, then the value of attribute `mirroringProtocol` shall only be set to `MirroringProtocolEnum.version1`.

]

[constr_9320] Value of `BusMirrorChannelMappingFlexray.mirroringProtocol`

Imposition time: IT_SysDesc

[The value of attribute `BusMirrorChannelMappingFlexray.mirroringProtocol` shall only be set to `MirroringProtocolEnum.version1`.

]

[constr_9321] Same time base for all `BusMirrorChannelMappings` of one `EcuInstance`

Imposition time: IT_SysDesc

[All `BusMirrorChannelMappings` that are referencing the same `EcuInstance` in the role `ecuInstance` shall reference the same `GlobalTimeDomain` in the role `globalTimeDomain`.

]

[constr_9326] Exclusive existence of `ISignalTriggering.iSignal` and `ISignalTriggering.iSignalGroup`

Imposition time: IT_SysDesc

[Each `ISignalTriggering` shall either define an `ISignalTriggering.iSignal` or an `ISignalTriggering.iSignalGroup` reference.

]

[constr_9330] Derivation of network representation in case that several `DataMappings` are defined that map the same `SystemSignal` to different `VariableDataPrototypes`

Imposition time: IT_SysDesc

[If several `DataMappings` are defined that map the same `SystemSignal` to different `VariableDataPrototypes` then

- all `ISignals` that reference this `SystemSignal` shall define `networkRepresentationProps` or
- if `networkRepresentationProps` are not specified on the `ISignal` level (and are therefore derived from the `ImplementationDataType`) then the different `DataMappings` shall reference `VariableDataPrototypes` that in turn reference the identical `ImplementationDataType`.

]

[constr_9331] E2E protection of a `ClientServerOperation`

Imposition time: IT_SysDesc

[If an `ISignal` aggregates `EndToEndTransformationISignalProps` and references a `SystemSignal` that in turn is referenced by a `ClientServerToSignalMapping` in the role `callSignal`, then the `EndToEndTransformationISignalProps` settings and the `EndToEndTransformationDescription` settings defined in the `TransformationTechnology` that is referenced by the `EndToEndTransformationISignalProps` shall have the same values for the following attributes:

- `EndToEndTransformationDescription.profileName`
- `EndToEndTransformationDescription.offset`
- `EndToEndTransformationISignalProps.sourceId`

as for the `ISignal` that is referenced by the `SystemSignal` that in turn is referenced by the same `ClientServerToSignalMapping` in the role `returnSignal`.

]

[constr_9332] Existence of J1939TpConnection.tpProtocolType

Imposition time: IT_SysDesc

[For each J1939TpConnection, the attribute tpProtocolType shall exist.

]

[constr_9333] FibexElements in ECU_EXTRACT

Imposition time: IT_EcuExt

[Each FibexElement that is used in the ECU_EXTRACT shall be referenced by the System element in the role fibexElement.

]

[constr_9343] Allowed J1939ProtectedIPdu.payload reference target

Status: DRAFT

Imposition time: IT_SysDesc

[A J1939ProtectedIPdu is only allowed to reference a PduTriggering with the payload reference that in turn references an ISignalIPdu in the role iPdu to which an ISignalGroup is mapped that aggregates EndToEndTransformationISignalProps in the role transformationISignalProps which references an EndToEndTransformationDescription with profileName PROFILE_76.

]

[constr_9346] Existence of EthernetVlanTranslationTable.translatedVlanId

Imposition time: IT_SysDesc

[For each EthernetVlanTranslationTable, the attribute translatedVlanId shall exist.

]

[constr_9347] Range of EthernetVlanTranslationTable.ingressVlanId and EthernetVlanTranslationTable.translatedVlanId

Imposition time: IT_SysDesc

[If defined, the value of ingressVlanId and translatedVlanId shall be in the range 0..4095.

]

[constr_9348] EthernetVlanTranslationTable.translatedVlanId and vlanMembership

Imposition time: IT_SysDesc

[If a `CouplingPort` defines an `EthernetVlanTranslationTable` via the `CouplingPortDetails` then the `CouplingPort` shall have a `vlanMembership` defined that references an `EthernetPhysicalChannel` that has the same `vlanIdentifier` value defined as the `translatedVlanId` value in the `EthernetVlanTranslationTable`.

]

2.7 CP_TPS_TimingExtensions

[constr_4500] Restricted usage of Occurrence Expression functions

Imposition time: IT_SubClasTdEvAss

[The functions:

- `TIMEX_occurs`,
- `TIMEX_hasOccurred`,
- `TIMEX_timeSinceLastOccurrence`,
- `TIMEX_angleSinceLastOccurrence`,
- `TIMEX_modeActive`

shall only be used for an `TDEventOccurrenceExpressionFormula` applied to a `TDEventComplex`.

]

[constr_4502] Use references only as function operands

Imposition time: IT_SubClasTdEvAss

[The references to model elements (e.g. the *timing event* reference targeting `TimingDescriptionEvent`) do have specific semantics. The usage of these references within the expression is *only* allowed as operand of the functions mentioned above.

]

[constr_4503] Restricted usage of `AutosarOperationArgumentInstance` for Content Filter

Imposition time: IT_SubClasTdeEvAss

[If a content filter is defined for an atomic event then references to `AutosarOperationArgumentInstances` are only allowed if the atomic event is of type `TDEventOperation`. Only if such an atomic event occurs, the value of the operation arguments can be evaluated. Thus, also the scope of the atomic event shall be the same as the `AutosarOperationArgumentInstance`, meaning that they shall point to the same `ClientServerOperation`. Finally, references to an `AutosarOperationArgumentInstance` with argument direction "out" are only allowed, if the atomic event of type `TDEventOperation` refers either to the point in time when the operation call response has been sent (TD-EVENT-OPERATION-TYPE=OPERATION-CALL-RESPONSE-SENT) or to the point in time when the operation call response has been received (TD-EVENT-OPERATION-TYPE=OPERATION-CALL-RESPONSE-RECEIVED).

]

[constr_4504] Restriction of the `scope` of an `AgeConstraint`

Imposition time: IT_SubClasTdeEvAss

[An `AgeConstraint` may only reference either a:

- `TDEventVariableDataPrototype.tdeventVariableDataPrototypeType==variableDataPrototypeReceived`
- `TDEventTrigger.tdeventTriggerType==triggerActivated`

in the role `scope`

]

[constr_4505] Specifying minimum and maximum number of occurrences

Imposition time: IT_SubClasTdeEvAss

[The minimum and maximum number of occurrences shall be specified such that the following holds: $0 \leq \text{minNumberOfOccurrences} \leq \text{maxNumberOfOccurrences}$.

]

[constr_4506] Specifying minimum inter-arrival time and pattern length

Imposition time: IT_SubClasTdeEvAss

[The `minimumInterArrivalTime` and `patternLength` shall be specified such that the following holds: $0 < \text{minimumInterArrivalTime} \leq \text{patternLength}$.

]

[constr_4507] Specifying pattern length, pattern jitter and patter period

Imposition time: IT_SubClasTdEvAss

[The `patternLength`, `patternJitter` and `patternPeriod` shall be specified such that the following holds: $patternLength + patternJitter < patternPeriod$.

]

[constr_4508] Existence of `TDEventVfbPort.portPrototypeBlueprint`

Imposition time: IT_VfbTd

[The reference `TDEventVfbPort.portPrototypeBlueprint` shall exist only if the immediate parent is `ARPackage.category==BLUEPRINT`

]

[constr_4510] Specifying references to `RunnableEntity` and `VariableAccess`

Imposition time: IT_SwcTd

[A `RunnableEntity` and `VariableAccess` shall be referenced at the same time if and only if the value of `tdEventSwcInternalBehaviorType==runnableEntityVariableAccess`. These two references are **not** mutual exclusive.

]

[constr_4511] Validity of referencing `RunnableEntity`

Imposition time: IT_SwcTd

[A `RunnableEntity` shall be referenced if and only if the value of `tdEventSwcInternalBehaviorType` is either:

- `runnableEntityActivated`
- `runnableEntityStarted`
- `runnableEntityTerminated`
- `runnableEntityVariableAccess`

]

[constr_4512] Validity of referencing `VariableAccess`

Imposition time: IT_SwcTd

[A `VariableAccess` shall be referenced if and only if the value of `tdEventSwcInternalBehaviorType==runnableEntityVariableAccess`.

]

[constr_4513] SynchronizationTimingConstraint shall reference at least two events

Imposition time: IT_SubClasTdEvAss

[In the case, that the `SynchronizationTimingConstraint` is imposed on events then at least two (2) timing description events shall be referenced.

]

[constr_4514] SynchronizationTimingConstraint shall reference at least two event chains

Imposition time: IT_SubClasTdEvAss

[In the case, that the `SynchronizationTimingConstraint` is imposed on `TimingDescriptionEventChains` then at least two (2) `TimingDescriptionEventChains` shall be referenced.

]

[constr_4515] Orthogonality of stimulus and response in a TimingDescriptionEventChain

Imposition time: IT_SubClasTeAss

[The reference `TimingDescriptionEventChain.stimulus` and the reference `TimingDescriptionEventChain.response` shall not reference the same `TimingDescriptionEvent.shortName`.

]

[constr_4516] Completeness of a composed TimingDescriptionEventChain

Imposition time: IT_SubClasTeAss

[If a `TimingDescriptionEventChain` has > 0 segments: after [constr_4518] is applied, there shall be at least one end-to-end path from the parental `TimingDescriptionEventChain.stimulus`, through the segments, to the parental `TimingDescriptionEventChain.response`.

]

[constr_4518] Specifying end-points of a composed TimingDescriptionEventChain

Imposition time: IT_SubClasTeAss

[If a `TimingDescriptionEventChain` has > 0 segments: in *that* list of segments:

- at least one `segment.stimulus` shall reference the (parent) `TimingDescriptionEventChain.stimulus` in which it is referenced in the role `segment`
- at least one `segment.response` shall reference the (parent) `TimingDescriptionEventChain.response` in which it is referenced in the role `segment`

」

[constr_4519] Specifying `patternLength`*Imposition time:* IT_SubClasTdEvAss

「The `patternLength` shall be specified such that the following holds: $0 \leq \max(\text{offset}) \leq \text{patternLength}$.

」

[constr_4520] Specifying attribute `synchronizationConstraintType`*Imposition time:* IT_SubClasTdEvAss

「The attribute `synchronizationConstraintType` shall be specified if the `SynchronizationTimingConstraint` is imposed on events.

」

[constr_4521] Specifying attribute `synchronizationConstraintType`*Imposition time:* IT_SubClasTdEvAss

「The attribute `synchronizationConstraintType` shall be specified if the `SynchronizationTimingConstraint` is imposed on `TimingDescriptionEventChains`.

」

[constr_4522] `SynchronizationTimingConstraint` shall either reference events or event chains*Imposition time:* IT_SubClasTdEvAss

「The `SynchronizationTimingConstraint` shall either reference `TimingDescriptionEvents` or `TimingDescriptionEventChains`, but not both at the same time.

」

[constr_4523] Restriction of `maxCycleRepetitions` and `maxSlotsPerCycle` to Repetitive Execution Order Constraint*Imposition time:* IT_SwcTd

「The attributes

- `EOCExecutableEntityRefGroup.maxCycleRepetitions`
- `EOCExecutableEntityRefGroup.maxSlotsPerCycle`

shall exist only if *that* `EOCExecutableEntityRefGroup` is aggregated by an `ExecutionOrderConstraint.executionOrderConstraintType==repetitiveEOC` in the role `orderedElement`

]

[constr_4525] Precedence of successor relationships `successor` and `directSuccessor`

Imposition time: IT_SwcTd

[The successor relationships `successor` and `directSuccessor` take always precedence over the `ordered` multiplicity of the association `nestedElement`.

]

[constr_4526] Specifying `maxCycles` and `maxSlots` in a Repetitive Execution Order Constraint

Imposition time: IT_SwcTd

[The attributes `maxCycles` and `maxSlots` shall be specified only by the *root* group of executable entity references `EOCExecutableEntityRefGroup`.

]

[constr_4527] Referencing `TimingDescriptionEvent` in a Repetitive Execution Order Constraint

Imposition time: IT_SwcTd

[The `TimingDescriptionEvent` shall be specified only by the *root* group of executable entity references `EOCExecutableEntityRefGroup`.

]

[constr_4528] The *root* `EOCExecutableEntityRefGroup` shall reference only `EOCExecutableEntityRefGroups`

Imposition time: IT_SwcTd

[The *root* `EOCExecutableEntityRefGroup` shall reference only groups of executable entity references respectively event references grouped by the element `EOCExecutableEntityRefGroups`.

]

[constr_4529] Number of nested elements referenced by the root `EOCExecutableEntityRefGroup`

Imposition time: IT_SwcTd

[The number of nested elements referenced by the root `EOCExecutableEntityRefGroup` shall be exactly the number given by the attribute `maxCycles`.

]

[constr_4530] An `EOCExecutableEntityRefGroup` representing a cycle shall reference only `EOCExecutableEntityRefs` respectively `EOCEventRefs`

Imposition time: IT_SwcTd

[The `EOCExecutableEntityRefGroup` representing a cycle shall reference only `EOCExecutableEntityRefs`, respectively `EOCEventRefs`.

]

[constr_4531] Number of nested elements referenced by `EOCExecutableEntityRefGroup` representing a cycle

Imposition time: IT_SwcTd

[The number of nested elements referenced by a `EOCExecutableEntityRefGroup` representing a cycle shall be exactly the number given by the attribute `maxSlots`.

]

[constr_4532] Successor relationship is not self-referencing

Imposition time: IT_SwcTd

[The target and source of the successor relationships `successor` and `directSuccessor` shall not be the same. In other words an `EOCExecutableEntityRef` and `EOCExecutableEntityRefGroup` shall not reference itself as its logical or direct successor.

]

[constr_4533] Maximum number of successor relationships

Imposition time: IT_SwcTd

[The maximum number of successor relationships, namely `successor` or `directSuccessor`:

- between two `EOCExecutableEntityRefs`
- between two `EOCEventRefs`
- between two `EOCExecutableEntityRefGroups`

- between an `EOCExecutableEntityRef` and an `EOCExecutableEntityRefGroup`
- between an `EOCEventRef` and an `EOCExecutableEntityRefGroup`

is one (1).

]

[constr_4534] Maximum number of `directSuccessor` relationships

Imposition time: IT_SwcTd

[The number of `directSuccessor` relationships of a:

- `EOCExecutableEntityRef`
- `EOCEventRef`
- `EOCExecutableEntityRefGroup`

shall not exceed the number of independent execution units available in a system.

]

[constr_4536] Compatible recurrence of any `ExecutableEntity`

Imposition time: IT_SwcTd

[In an `ExecutionOrderConstraint` the `ExecutableEntities`, referenced by all `EOCExecutableEntityRefs` respectively all `EOCEventRefs`, shall be compatible with regard to their recurrence.

]

[constr_4537] References among elements in an `ExecutionOrderConstraint`

Imposition time: IT_SwcTd

[An `EOCExecutableEntityRef` respectively `EOCEventRef` or an `EOCExecutableEntityRefGroup` shall reference only `EOCExecutableEntityRefs`, respectively all `EOCEventRefs`, or `EOCExecutableEntityRefGroups` which are part of the same `ExecutionOrderConstraint`.

]

[constr_4538] Hierarchical Execution Order Constraint: `EOCExecutableEntityRef`, `EOCEventRef`, and `EOCExecutableEntityRefGroup` shall be target or source of a successor relationship

Imposition time: IT_SwcTd

[In a `ExecutionOrderConstraint.executionOrderConstraintType==hierarchicalEOC`, each:

- [EOCExecutableEntityRefGroup](#)
- [EOCExecutableEntityRef](#)
- [EOCEventRef](#)

which is not part of an [EOCExecutableEntityRefGroup](#) shall be target or source of at least one successor relationship.

]

[constr_4539] The successor relationships `successor` and `directSuccessor` shall not be used

Imposition time: IT_SwcTd

[The successor relationships `successor` and `directSuccessor` shall not be used in a `executionOrderConstraintType==repetitiveEOC`.

]

[constr_4540] `maxCycles` and `maxSlots` shall not be zero

Imposition time: IT_SwcTd

[If the attributes `maxCycles` and `maxSlots` are used, then the values of the attributes `maxCycles` and `maxSlots` shall be greater than zero (0).

]

[constr_4541] Existence of `EOCExecutableEntityRef.executable` in an Ordinary Execution Order Constraint

Imposition time: IT_SwcTd

[In an `ExecutionOrderConstraint.executionOrderConstraintType==ordinaryEOC`, in the tree of `orderedElements`, if the `orderedElement` is a `EOCExecutableEntityRef`, it shall reference an `ExecutableEntity` in the role `executable`.

]

[constr_4542] Existence of `EOCExecutableEntityRef.executable` in a Hierarchical Execution Order Constraint

Imposition time: IT_SwcTd

[In an `ExecutionOrderConstraint.executionOrderConstraintType==hierarchicalEOC`, in the tree of `orderedElements`, if the `orderedElement` is a `EOCExecutableEntityRef`, it shall reference an `ExecutableEntity` in the role `executable`.

]

[constr_4543] Maximum value of `minimumInterArrivalTime`

Imposition time: IT_SubClasTdEvAss

[The `minimumInterArrivalTime` shall be \leq the `period`.

]

[constr_4544] Specifying `patternLength`, `patternJitter` and `patternPeriod`

Imposition time: IT_SubClasTdEvAss

[The `patternLength`, `patternJitter` and `patternPeriod` shall be specified such that the following holds: $\text{patternLength} + \text{patternJitter} < \text{patternPeriod}$.

]

[constr_4545] Referring either `ExecutableEntitys` or `AbstractEvents`

Imposition time: IT_SwcTd

[An `ExecutionOrderConstraint` shall contain either only `EOCExecutableEntityRef` or only `EOCEventRef`, but not both. In the former case `ExecutableEntitys` are referenced and in the latter case `AbstractEvents` are referenced.

]

[constr_4546] Setting the attribute `isEvent`

Imposition time: IT_SwcTd

[The value of the attribute `isEvent` shall be set to:

- TRUE: when the `ExecutionOrderConstraint` refers only to `AbstractEvents`
- FALSE: when the `ExecutionOrderConstraint` refers only to `ExecutableEntitys`

as per [constr_4545]

]

[constr_4547] Restriction of `ExecutionOrderConstraint.permitMultipleReferencesToEE`

Imposition time: IT_SwcTd

[The attribute `permitMultipleReferencesToEE` shall exist only if `ExecutionOrderConstraint.isEvent==FALSE` as per [constr_4546]

]

[constr_4548] Existence of `EOCEventRef.event` in an Ordinary Execution Order Constraint

Imposition time: IT_SwcTd

[In an `ExecutionOrderConstraint.executionOrderConstraintType==ordinaryEOC`, in the tree of `orderedElements`, if the `orderedElement` is a `EOCEventRef`, it shall reference an `AbstractEvent` in the role `event`.

]

[constr_4549] Existence of `EOCEventRef.event` in a Hierarchical Execution Order Constraint

Imposition time: IT_SwcTd

[In an `ExecutionOrderConstraint.executionOrderConstraintType==hierarchicalEOC`, in the tree of `orderedElements`, if the `orderedElement` is a `EOCEventRef`, it shall reference an `AbstractEvent` in the role `event`.

]

[constr_4551] Use only Numericals in `TDEventOccurrenceExpression`

Imposition time: IT_SubClasTdEvAss

[The target data prototype of the instance references of `variable` and `argument` shall be `Numerical`.

]

[constr_4552] Restricted usage of `AutosarVariableInstance` for Content Filter

Imposition time: IT_SubClasTdEvAss

[If a content filter is defined for an atomic event then references to `AutosarVariableInstances` are only allowed if the atomic event is of type `TDEventVariableDataPrototype`. Only if such an atomic event occurs, the value of the variables can be evaluated. Thus, also the scope of the atomic event shall be the same as the `AutosarVariableInstance`, meaning that they shall point to the same `VariableDataPrototype`.

]

[constr_4554] Restriction of the referenced `TimingDescriptionEventChain` for a `letInterval`

Imposition time: IT_SwcTd

[The element `EOCExecutableEntityRefGroup.letInterval` shall be present only in a `ROOT_GROUP` (according to [constr_6909])

]

[constr_4559] Restriction of `TimingDescriptionEvent.category`

Imposition time: IT_SubClasTdEvAss

[Any `TimingDescriptionEvent.category` not in the list in [TPS_TIMEX_00056] shall be ignored.

]

[constr_4561] Usage of the category value `DISPATCH_ENTRY_POINT` in `TimingDescriptionEvent`

Imposition time: IT_SysTd

[The value `DISPATCH_ENTRY_POINT` of the attribute `category` of a `TimingDescriptionEvent` shall be set if and only if the timing description event plays the role of a stimulus event and the corresponding timing description event chain, referencing this timing description event, represents a dispatcher in the context of describing timing of a software cluster.

]

[constr_4562] Usage of the category value `DISPATCH_EXIT_POINT` in `TimingDescriptionEvent`

Imposition time: IT_SysTd

[The value `DISPATCH_EXIT_POINT` of the attribute `category` of a `TimingDescriptionEvent` shall be set if and only if the timing description event plays the role of a response event and the corresponding timing description event chain, referencing this timing description event, represents a dispatcher in the context of describing timing of a software cluster.

]

[constr_4565] Consistency of `TDCpSoftwareClusterMapping.timingDescription` and `TDCpSoftwareClusterResourceMapping.timingDescription`

Imposition time: IT_SysTd

[The references:

- `TDCpSoftwareClusterMapping.timingDescription`
- `TDCpSoftwareClusterResourceMapping.timingDescription`

shall (after [constr_6918] has been applied) refer to the same sub-class and `category` of `TimingDescription`

]

[constr_6816] Restricted usage of `TimingDescriptionEventChain.isPipeliningPermitted` in `TimingDescriptionEventChain`

Status: DRAFT

Imposition time: IT_SwcTd

[The attribute `isPipeliningPermitted` shall only exist if the `TimingDescriptionEventChain.category==SL_LET_INTERVAL`.

]

[constr_6817] Restricted usage of `TimingDescriptionEvent.clockReference`

Status: DRAFT

Imposition time: IT_SwcTd

[The reference `TimingDescriptionEvent.clockReference` shall exist if (and only if), the `TimingDescriptionEvent` is itself referenced:

- in the role `stimulus` or
- in the role `response`

by a `TimingDescriptionEventChain.category==SL_LET_INTERVAL`

]

[constr_6818] Existence of `EventTriggeringConstraint.event`

Imposition time: IT_SubClasTdeVAss

[For each `EventTriggeringConstraint`, the reference in the role `event` shall exist

]

[constr_6819] Existence of `PeriodicEventTriggering.jitter`

Imposition time: IT_SubClasTdeVAss

[For each `PeriodicEventTriggering`, the attribute `jitter` shall exist

]

[constr_6820] Existence of `PeriodicEventTriggering.minimumInterArrivalTime`

Imposition time: IT_SubClasTdeVAss

[For each `PeriodicEventTriggering`, the attribute `minimumInterArrivalTime` shall exist

]

[constr_6821] Existence of `PeriodicEventTriggering.period`

Imposition time: IT_SubClasTdEvAss

[For each `PeriodicEventTriggering`, the attribute `period` shall exist

]

[constr_6822] Existence of `SporadicEventTriggering.maximumInterArrivalTime`

Imposition time: IT_SubClasTdEvAss

[For each `SporadicEventTriggering`, the attribute `maximumInterArrivalTime` shall exist

]

[constr_6823] Existence of `SporadicEventTriggering.minimumInterArrivalTime`

Imposition time: IT_SubClasTdEvAss

[For each `SporadicEventTriggering`, the attribute `minimumInterArrivalTime` shall exist

]

[constr_6824] Existence of `ConcretePatternEventTriggering.patternLength`

Imposition time: IT_SubClasTdEvAss

[For each `ConcretePatternEventTriggering`, the attribute `patternLength` shall exist

]

[constr_6825] Existence of `BurstPatternEventTriggering.maxNumberOfOccurrences`

Imposition time: IT_SubClasTdEvAss

[For each `BurstPatternEventTriggering`, the attribute `maxNumberOfOccurrences` shall exist

]

[constr_6826] Existence of `BurstPatternEventTriggering.minimumInterArrivalTime`

Imposition time: IT_SubClasTdeVAss

[For each `BurstPatternEventTriggering`, the attribute `minimumInterArrivalTime` shall exist

]

[constr_6827] Existence of `BurstPatternEventTriggering.patternLength`

Imposition time: IT_SubClasTdeVAss

[For each `BurstPatternEventTriggering`, the attribute `patternLength` shall exist

]

[constr_6828] Existence of `ArbitraryEventTriggering.minimumDistance`

Imposition time: IT_SubClasTdeVAss

[For each `ArbitraryEventTriggering`, the reference in the role `minimumDistance` shall exist at least once

]

[constr_6829] Existence of `ArbitraryEventTriggering.maximumDistance`

Imposition time: IT_SubClasTdeVAss

[For each `ArbitraryEventTriggering`, the reference in the role `maximumDistance` shall exist at least once

]

[constr_6830] Existence of `ConfidenceInterval.lowerBound`

Imposition time: IT_SubClasTdeVAss

[For each `ConfidenceInterval`, the attribute `lowerBound` shall exist

]

[constr_6831] Existence of `ConfidenceInterval.propability`

Imposition time: IT_SubClasTdeVAss

[For each `ConfidenceInterval`, the attribute `propability` shall exist

]

[constr_6832] Existence of `ConfidenceInterval.upperBound`*Imposition time:* IT_SubClasTdEvAss[For each `ConfidenceInterval`, the attribute `upperBound` shall exist

]

[constr_6833] Existence of `ExecutionOrderConstraint.orderedElement`*Imposition time:* IT_SubClasTdEvAss[For each `ExecutionOrderConstraint`, the attribute `orderedElement` shall exist at least once

]

[constr_6834] Existence of `EOCExecutableEntityRefGroup.nestedElement`*Imposition time:* IT_SubClasTdEvAss[For each `EOCExecutableEntityRefGroup`, the reference in the role `nestedElement` shall exist at least once

]

[constr_6835] Existence of `ExecutionTimeConstraint.executionTimeType`*Imposition time:* IT_SwcTd[For each `ExecutionTimeConstraint`, the attribute `executionTimeType` shall exist

]

[constr_6836] Existence of `ExecutionTimeConstraint.executable`*Imposition time:* IT_SwcTd[For each `ExecutionTimeConstraint`, the reference to `ExecutableEntity` in the role `executable` shall exist

]

[constr_6837] Existence of `LatencyTimingConstraint.latencyConstraintType`*Imposition time:* IT_SubClasTdEvAss[For each `LatencyTimingConstraint`, the attribute `latencyConstraintType` shall exist

]

[constr_6838] Existence of `LatencyTimingConstraint.maximum`*Imposition time:* IT_SubClasTdEvAss

[For each `LatencyTimingConstraint`, the attribute `maximum` shall exist
]

[constr_6839] Existence of `LatencyTimingConstraint.minimum`*Imposition time:* IT_SubClasTdEvAss

[For each `LatencyTimingConstraint`, the attribute `minimum` shall exist
]

[constr_6841] Existence of `LatencyTimingConstraint.scope`*Imposition time:* IT_SubClasTdEvAss

[For each `LatencyTimingConstraint`, the reference in the role `scope` shall exist at least once
]

[constr_6842] Existence of `OffsetTimingConstraint.maximum`*Imposition time:* IT_SubClasTdEv

[For each `OffsetTimingConstraint`, the attribute `maximum` shall exist
]

[constr_6843] Existence of `OffsetTimingConstraint.minimum`*Imposition time:* IT_SubClasTdEv

[For each `OffsetTimingConstraint`, the attribute `minimum` shall exist
]

[constr_6844] Existence of `OffsetTimingConstraint.source`*Imposition time:* IT_SubClasTdEv

[For each `OffsetTimingConstraint`, the reference in the role `source` shall exist at least once
]

[constr_6845] Existence of `OffsetTimingConstraint.target`

Imposition time: IT_SubClasTdEv

[For each `OffsetTimingConstraint`, the reference in the role `target` shall exist at least once

]

[constr_6846] Existence of `SynchronizationTimingConstraint.synchronizationConstraintType`

Imposition time: IT_SubClasTdEv

[For each `SynchronizationTimingConstraint`, the attribute `synchronizationConstraintType` shall exist

]

[constr_6847] Existence of `SynchronizationTimingConstraint.tolerance`

Imposition time: IT_SubClasTdEv

[For each `SynchronizationTimingConstraint`, the attribute `tolerance` shall exist

]

[constr_6848] Existence of `VfbTiming.component`

Imposition time: IT_VfbTd

[For each `VfbTiming`, the reference to `SwComponentType` in the role `component` shall exist

]

[constr_6849] Existence of `SystemTiming.system`

Imposition time: IT_SysTd

[For each `SystemTiming`, the reference to `System` in the role `system` shall exist

]

[constr_6850] Existence of `BswModuleTiming.behavior`

Imposition time: IT_BswTd

[For each `BswModuleTiming`, the reference to `BswInternalBehavior` in the role `behavior` shall exist

]

[constr_6851] Existence of `BswCompositionTiming.implementation`

Imposition time: IT_BswTd

[For each `BswCompositionTiming`, the reference to `BswImplementation` in the role `implementation` shall exist at least once

]

[constr_6852] Existence of `EcuTiming.ecuConfiguration`

Imposition time: IT_EcuTd

[For each `EcuTiming`, the reference to `EcucValueCollection` in the role `ecu-Configuration` shall exist at least once

]

[constr_6853] Existence of `ModeInBswInstanceRef.contextModeDeclarationGroupPrototype`

Imposition time: IT_BswTd

[For each `ModeInBswInstanceRef`, the reference to `ModeDeclarationGroup-Prototype` in the role `contextModeDeclarationGroupPrototype` shall exist at least once.

]

[constr_6854] Existence of `ModeInBswInstanceRef.targetModeDeclaration`

Imposition time: IT_BswTd

[For each `ModeInBswInstanceRef`, the reference to `ModeDeclaration` in the role `targetModeDeclaration` shall exist at least once.

]

[constr_6855] Existence of `ModeInSwcInstanceRef.contextModeDeclarationGroupPrototype`

Imposition time: IT_SwcTd

[For each `ModeInSwcInstanceRef`, the reference to `ModeDeclarationGroup-Prototype` in the role `contextModeDeclarationGroupPrototype` shall exist at least once.

]

[constr_6856] Existence of `ModeInSwcInstanceRef.contextPort`*Imposition time:* IT_SwcTd

[For each `ModeInSwcInstanceRef`, the reference to `PortPrototype` in the role `contextPort` shall exist at least once.

]

[constr_6857] Existence of `ModeInSwcInstanceRef.targetModeDeclaration`*Imposition time:* IT_SwcTd

[For each `ModeInSwcInstanceRef`, the reference to `ModeDeclaration` in the role `targetModeDeclaration` shall exist at least once.

]

[constr_6858] Existence of `TDEventBswInternalBehavior.tdEventBswInternalBehaviorType`*Imposition time:* IT_BswTd

[For each `TDEventBswInternalBehavior`, the attribute `tdEventBswInternalBehaviorType` shall exist

]

[constr_6859] Existence of `TDEventBswInternalBehavior.bswModuleEntity`*Imposition time:* IT_BswTd

[For each `TDEventBswInternalBehavior`, the reference to `BswModuleEntity` in the role `bswModuleEntity` shall exist

]

[constr_6860] Existence of `TDEventBswModule.tdEventBswModuleType`*Imposition time:* IT_BswTd

[For each `TDEventBswModule`, the attribute `tdEventBswModuleType` shall exist

]

[constr_6861] Existence of `TDEventBswModule.bswModuleEntry`*Imposition time:* IT_BswTd

[For each `TDEventBswModule`, the reference to `BswModuleEntry` in the role `bswModuleEntry` shall exist

]

[constr_6862] Existence of `TDEventBswModeDeclaration.tdEventBswModeDeclarationType`*Imposition time:* IT_BswTd

[For each `TDEventBswModeDeclaration`, the attribute `tdEventBswModeDeclarationType` shall exist

]

[constr_6863] Existence of `TDEventBswModeDeclaration.modeDeclaration`*Imposition time:* IT_BswTd

[For each `TDEventBswModeDeclaration`, the reference to `ModeDeclarationGroupPrototype` in the role `modeDeclaration` shall exist

]

[constr_6864] Existence of `TDEventISignal.tdEventType`*Imposition time:* IT_EcuTd

[For each `TDEventISignal`, the attribute `tdEventType` shall exist

]

[constr_6865] Existence of `TDEventISignal.iSignal`*Imposition time:* IT_EcuTd

[For each `TDEventISignal`, the reference to `ISignal` in the role `iSignal` shall exist

]

[constr_6866] Existence of `TDEventISignal.physicalChannel`*Imposition time:* IT_EcuTd

[For each `TDEventISignal`, the reference to `PhysicalChannel` in the role `physicalChannel` shall exist

]

[constr_6867] Existence of `TDEventIPdu.tdEventType`*Imposition time:* IT_EcuTd

[For each `TDEventIPdu`, the attribute `tdEventType` shall exist

]

[constr_6868] Existence of TDEventIPdu.iPdu*Imposition time:* IT_EcuTd

[For each TDEventIPdu, the reference to iPdu in the role iPdu shall exist
]

[constr_6869] Existence of TDEventIPdu.physicalChannel*Imposition time:* IT_EcuTd

[For each TDEventIPdu, the reference to PhysicalChannel in the role physicalChannel shall exist
]

[constr_6870] Existence of TDEventFrame.tdEventType*Imposition time:* IT_EcuTd

[For each TDEventFrame, the attribute tdEventType shall exist
]

[constr_6871] Existence of TDEventFrame.frame*Imposition time:* IT_EcuTd

[For each TDEventFrame, the reference to Frame in the role frame shall exist
]

[constr_6872] Existence of TDEventFrame.physicalChannel*Imposition time:* IT_EcuTd

[For each TDEventFrame, the reference to PhysicalChannel in the role physicalChannel shall exist
]

[constr_6873] Existence of TDEventFrameEthernet.tdEventType*Imposition time:* IT_EcuTd

[For each TDEventFrameEthernet, the attribute tdEventType shall exist
]

[constr_6874] Existence of TDHeaderIdRange.maxHeaderId*Imposition time:* IT_EcuTd

[For each TDHeaderIdRange, the attribute maxHeaderId shall exist
]

[constr_6875] Existence of `TDHeaderIdRange.minHeaderId`*Imposition time:* IT_EcuTd[For each `TDHeaderIdRange`, the attribute `minHeaderId` shall exist

]

[constr_6876] Existence of `TDEventCycleStart.cycleRepetition`*Imposition time:* IT_EcuTd[For each `TDEventCycleStart`, the attribute `cycleRepetition` shall exist

]

[constr_6877] Existence of `TDEventFrClusterCycleStart.frCluster`*Imposition time:* IT_EcuTd[For each `TDEventFrClusterCycleStart`, the attribute `frCluster` shall exist

]

[constr_6878] Existence of `TDEventTTCanCycleStart.ttCanCluster`*Imposition time:* IT_EcuTd[For each `TDEventTTCanCycleStart`, the attribute `ttCanCluster` shall exist

]

[constr_6879] Existence of `TDEventOccurrenceExpression.formula`*Imposition time:* IT_SubClasTdEvAss[For each `TDEventOccurrenceExpression`, the attribute `formula` shall exist

]

[constr_6880] Existence of `AutosarVariableInstance.variableInstance`*Imposition time:* IT_SubClasTdEvAss[For each `AutosarVariableInstance`, the reference in the role `variableInstance` shall exist

]

[constr_6881] Existence of `AutosarOperationArgumentInstance.operationArgumentInstance`

Imposition time: IT_SubClasTdeVAss

[For each `AutosarOperationArgumentInstance`, the reference in the role `operationArgumentInstance` shall exist

]

[constr_6882] Existence of `TDEventSwcInternalBehavior.tdEventSwcInternalBehaviorType`

Imposition time: IT_SwcTd

[For each `TDEventSwcInternalBehavior`, the attribute `tdEventSwcInternalBehaviorType` shall exist

]

[constr_6883] Existence of `TDEventSwcInternalBehavior.runnable`

Imposition time: IT_SwcTd

[For each `TDEventSwcInternalBehavior`, the reference to `RunnableEntity` in the role `runnable` shall exist

]

[constr_6884] Existence of `TDEventSwcInternalBehaviorReference.referencedTDEventSwc`

Imposition time: IT_SwcTd

[For each `TDEventSwcInternalBehaviorReference`, the reference to `TDEventSwc` in the role `referencedTDEventSwc` shall exist

]

[constr_6885] Existence of `TDEventVfbPort.isExternal`

Imposition time: IT_VfbTd

[For each `TDEventVfbPort`, the attribute `isExternal` shall exist

]

[constr_6886] Existence of `TDEventVfbReference.referencedTDEventVfb`

Imposition time: IT_VfbTd

[For each `TDEventVfbReference`, the reference to `TDEventVfb` in the role `referencedTDEventVfb` shall exist

]

[constr_6887] Existence of TDEventVariableDataPrototype.tdEventVariableDataPrototypeType

Imposition time: IT_VfbTd

[For each TDEventVariableDataPrototype, the attribute tdEventVariableDataPrototypeType shall exist

]

[constr_6888] Existence of TDEventVariableDataPrototype.dataElement

Imposition time: IT_VfbTd

[For each TDEventVariableDataPrototype, the reference to VariableDataPrototype in the role dataElement

]

[constr_6889] Existence of TDEventOperation.tdEventOperationType

Imposition time: IT_VfbTd

[For each TDEventOperation, the attribute tdEventOperationType shall exist

]

[constr_6890] Existence of TDEventOperation.operation

Imposition time: IT_VfbTd

[For each TDEventOperation, the reference to ClientServerOperation in the role operation shall exist

]

[constr_6891] Existence of TDEventModeDeclaration.tdEventModeDeclarationType

Imposition time: IT_VfbTd

[For each TDEventModeDeclaration, the attribute tdEventModeDeclarationType shall exist

]

[constr_6892] Existence of TDEventModeDeclaration.modeDeclaration

Imposition time: IT_VfbTd

[For each TDEventModeDeclaration, the reference to ModeDeclarationGroupPrototype in the role modeDeclaration shall exist

]

[constr_6893] Existence of TDEventTrigger.tdEventTriggerType*Imposition time:* IT_VfbTd

[For each TDEventTrigger, the attribute tdEventTriggerType shall exist
]

[constr_6894] Existence of TDEventTrigger.trigger*Imposition time:* IT_VfbTd

[For each TDEventTrigger, the reference to Trigger in the role trigger shall exist
]

[constr_6895] Existence of TimingDescriptionEventChain.response*Imposition time:* IT_SubClasTdEvAss

[For each TimingDescriptionEventChain, the reference in the role response shall exist
]

[constr_6896] Existence of TimingDescriptionEventChain.stimulus*Imposition time:* IT_SubClasTdEvAss

[For each TimingDescriptionEventChain, the reference in the role stimulus shall exist
]

[constr_6897] Existence of TimingDescriptionEventChain.segment*Imposition time:* IT_SubClasTdEvAss

[For each TimingDescriptionEventChain, the reference in the role segment shall exist at least once
]

[constr_6898] Existence of ConcretePatternEventTriggering.offset*Imposition time:* IT_SubClasTdEvAss

[For each ConcretePatternEventTriggering, the attribute offset shall exist
]

[constr_6899] Existence of `ModeInSwcInstanceRef.base`

Imposition time: IT_SwcTd

[For each `ModeInSwcInstanceRef`, the reference to `SwComponentType` in the role `base` shall exist at least once.

]

[constr_6900] Dual existence of `TDEventVfb.port` and `TDEventVfb.portPrototypeBlueprint`

Status: DRAFT

Imposition time: IT_VfbTd

[The reference `TDEventVfbPort.port` and `TDEventVfbPort.portPrototypeBlueprint` shall not co-exist in a model

]

[constr_6901] Existence of `TDEventBsw.bswModuleDescription`

Status: DRAFT

Imposition time: IT_BswTd

[For each `BswModuleTiming`, the reference to a `BswModuleDescription` in the role `bswModuleDescription` shall exist

]

[constr_6906] Conformity of `stimulus` and `response` in a `TimingDescriptionEventChain`

Status: DRAFT

Imposition time: IT_SubClasTdEvAss

[The `TimingDescriptionEvents` referenced in the roles `stimulus` and `response` shall be of the same sub-class (of `TimingDescriptionEvent`)

]

[constr_6907] Restriction of `EOCExecutableEntityRefGroup.triggeringEvent`

Status: DRAFT

Imposition time: IT_SwcTd

[The `TimingDescriptionEvent` referenced in the role `EOCExecutableEntityRefGroup.triggeringEvent` shall exist only if the `EOCExecutableEntityRefGroup` is transitively aggregated by an `ExecutionOrderConstraint.executionOrderConstraintType==repetitiveEOC` in the role `orderedElement`

]

[constr_6908] Restriction of EOCExecutableEntityRefGroup.letDataExchangeParadigm

Status: DRAFT

Imposition time: IT_SwcTd

[The attribute `letDataExchangeParadigm` shall exist only if the `letInterval` in the same same `EOCExecutableEntityRefGroup` references a `TimingDescriptionEventChain.category==LET_INTERVAL`

]

[constr_6909] Singleton ROOT_GROUP in a Hierarchical Execution Order Constraint

Status: DRAFT

Imposition time: IT_SwcTd

[In a `ExecutionOrderConstraint.executionOrderConstraintType==hierarchicalEOC`, in the tree of `orderedElements`, there shall be only **one** `EOCExecutableEntityRefGroup.category==ROOT_GROUP`

]

[constr_6910] Referencing from a ROOT_GROUP in a Hierarchical Execution Order Constraint

Status: DRAFT

Imposition time: IT_SwcTd

[In a `ExecutionOrderConstraint.executionOrderConstraintType==hierarchicalEOC`, in the tree of `orderedElements`, in the singularly identifiable `ROOT_GROUP` (according to [constr_6909]):

- the `successor` shall not exist
- the `directSuccessor` shall not exist

]

[constr_6911] Referencing to a ROOT_GROUP in a Hierarchical Execution Order Constraint

Status: DRAFT

Imposition time: IT_SwcTd

[In a `ExecutionOrderConstraint.executionOrderConstraintType==hierarchicalEOC`, in the tree of `orderedElements`, the singularly identifiable `ROOT_GROUP` (according to [constr_6909]) shall not be referenced in the role:

- `successor` by another `EOCExecutableEntityRefGroup`
- `directSuccessor` by another `EOCExecutableEntityRefGroup`
- `nestedElement` by another `EOCExecutableEntityRefGroup`

]

[constr_6912] Mandatory specification of LET interval recurrence*Status:* DRAFT*Imposition time:* IT_SwcTd

[For a `TDEventComplex.category==LET_RELEASE`, there shall exist a `PeriodicEventTriggering` referencing that `TDEventComplex.category==LET_RELEASE` in the role `event`

]

[constr_6913] Restriction on RTEEvents used in an LET interval*Status:* DRAFT*Imposition time:* IT_SwcTd

[An `EOCExecutableEntityRefGroup` which references a `TimingDescription-EventChain.category==LET_INTERVAL` in the role `letInterval` **and** transitively references an `EOCEventRef` in the role `successor` **or** references an `EOCEventRef` in the role `nestedElement`, those `EOCEventRefs` shall reference either:

- `TimingEvent` in the role `event` or
- `BswTimingEvent` in the role `event`

]

[constr_6914] Restriction of the port context of an AgeConstraint*Status:* DRAFT*Imposition time:* IT_SubClasTdEvAss

[An `AgeConstraint.scope.port` shall reference only sub-classes of `AbstractRequiredPortPrototype`

]

[constr_6915] Affinity of ISignal in TDEventISignal*Status:* DRAFT*Imposition time:* IT_EcuTd

[The referenced `ISignal` in the role `TDEventISignal.iSignal` shall exist also in the list of `iSignals` aggregated by `TDEventISignal.physicalChannel.iSignalTriggering`

]

[constr_6916] Affinity of `Frame` in `TDEventFrame`

Status: DRAFT

Imposition time: IT_EcuTd

[The referenced `Frame` in the role `TDEventFrame.frame` shall exist also in the list of frames aggregated by `TDEventFrame.physicalChannel.frameTriggering`

]

[constr_6917] Affinity of `IPdu` in `TDEventIPdu`

Status: DRAFT

Imposition time: IT_EcuTd

[The referenced `IPdu` in the role `TDEventIPdu.iPdu` shall exist also in the list of `iPdus` aggregated by `TDEventIPdu.physicalChannel.pduTriggering`

]

[constr_6918] Referenced `TimingDescriptions` in `TDCpSoftwareClusterMapping` and `TDCpSoftwareClusterResourceMapping`

Status: DRAFT

Imposition time: IT_SysTd

[The references:

- `TDCpSoftwareClusterMapping.timingDescription`
- `TDCpSoftwareClusterResourceMapping.timingDescription`

shall refer to either:

- `TDEventComplex.category==DISPATCH_ENTRY_POINT`, or
- `TimingDescriptionEventChain.category==LET_INTERVAL`

]

[constr_6919] Referenced `CpSoftwareCluster` of `TDCpSoftwareClusterMapping`

Status: DRAFT

Imposition time: IT_SysTd

[The references:

- `TDCpSoftwareClusterMapping.provider`
- `TDCpSoftwareClusterMapping.requestor`

shall refer to a `CpSoftwareCluster.category==HOST_SOFTWARE_CLUSTER`

]

[constr_6920] Existence of `LatencyTimingConstraint.minimum` used in an LET interval

Status: DRAFT

Imposition time: IT_SwcTd

[For a `LatencyTimingConstraint` with:

- `latencyConstraintType==reaction`
- `scope.category==LET_INTERVAL`

the attribute `minimum` shall not exist.

]

[constr_6921] Disallow `TimingDescriptionEventChain` segmental circular-referencing

Status: DRAFT

Imposition time: IT_SubClassTeAss

[A `TimingDescriptionEventChain.segment` shall never reference the (parent) `TimingDescriptionEventChain` in which it is referenced in the role `segment`.

]

2.8 FO_TPS_GenericStructureTemplate

[constr_2501] Blueprint of blueprints are not supported [Note that objects modeled particularly as a "blueprint" (e.g. `PortPrototypeBlueprint`) also live in a package of category `BLUEPRINT`. Strictly speaking this means that they can be "blueprints" of "blueprints". This indirection is not intended and not supported.

]

[constr_2502] Merged model shall be compliant to the meta-model [A model merged from `<<atpSplitable>>` elements shall adhere to the consistency rules of the *meta-model*. Note that the required lower multiplicities depend on the process phase therefore the AUTOSAR schema sets them mainly to 0. This also applies to the bound model.

]

[constr_2504] Constraint to `bindingTime` [The tag `vh.latestBindingTime` *constraints* the value of the attribute `bindingTime` from [TPS_GST_00190]. Hence,

it defines the latest point in methodology which is allowed as value for `bindingTime` of this particular application of `<<atpVariation>>`.

}

[constr_2505] Multiplicity after binding [*if* `Phase` \geq `{partRole}.BindingTime` *then* number of `{partRole}'s` = *n*]

}

[constr_2507] EvaluatedVariantSet shall not refer to itself [An `EvaluatedVariantSet` shall not refer to itself directly or via other `EvaluatedVariantSet`].

}

[constr_2508] The shortName shall be unique in its name space [The content of `shortName` needs to be unique (case insensitive) within a the parent given name space].

Note that the check for uniqueness of `shortName` shall be performed case insensitively. This supports the good practice that names should not differ in upper / lower case only which would cause a lot of confusion.

The term "case insensitive" indicates that the characters in the sets

```
{a b c d e f g h i j k l m n o p q r s t u v w x y z}  
{A B C D E F G H I J K L M N O P Q R S T U V W X Y Z}
```

are respectively considered to be the same. In other words case-insensitive check for uniqueness of `shortNames` results in the fact that e.g. elements with `shortName` "X" and "x" are considered the same and shall not exist in the same name space.

}

[constr_2509] Uniqueness of ReferenceBase.shortLabel in the scope of an ARPackage [The `shortLabel` of any given `ReferenceBase` defined in the scope of an `ARPackage` shall be unique within the scope of the enclosing `ARPackage`].

}

[constr_2510] Only one default ReferenceBase [Only one `ReferenceBase` per `ARPackage` can be defined as default (`isDefault=true`)].

}

[constr_2511] Named reference bases shall be available [If there is a relative references, then one of the containing packages shall have a `referenceBase` with a `shortLabel` equal to the `base` of the reference.

]

[constr_2512] `shortName` uniqueness constraint for variants [`shortName` + `shortLabel` of a variant element shall be unique within the name space established by the surrounding `Identifiable`.

]

[constr_2514] `shortLabel` in `VariationPoint` shall be unique [The combination of `shortName` and `shortLabel` shall be unique within the next enclosing `Identifiable {WholeClass}`.

]

[constr_2515] Categories of packages shall not conflict [

	child + category (also indirect children)						
parent category	empty	BLUEPRINT	STANDARD	EXAMPLE	ICS	cus-tom1	cus-tom2
empty	ok	ok	ok	ok	ok	ok	ok
BLUEPRINT	ok	ok	conflict	conflict	conflict	conflict	conflict
STANDARD	ok	conflict	ok	conflict	conflict	conflict	conflict
EXAMPLE	ok	conflict	conflict	ok	conflict	conflict	conflict
ICS	ok	conflict	conflict	conflict	ok	conflict	conflict
custom1	ok	conflict	conflict	conflict	conflict	ok	conflict
custom2	ok	conflict	conflict	conflict	conflict	conflict	ok
	target package category (if category is empty, then the parent category applies)						
category of package that contains reference source element (if category is empty, then the parent category applies)	empty	BLUEPRINT	STANDARD	EXAMPLE	ICS	cus-tom1	cus-tom2
empty	ok	ok	ok	ok	ok	ok	ok
BLUEPRINT	ok	ok	ok	conflict	ok	conflict	conflict
STANDARD	ok	conflict	ok	conflict	conflict	conflict	conflict
EXAMPLE	ok	ok	ok	ok	ok	conflict	conflict
ICS	ok	conflict	ok	conflict ¹⁶	ok	conflict	conflict
custom1	ok	ok	ok	ok	ok	ok	ok
custom2	ok	ok	ok	ok	ok	ok	ok

Upper part of the table: If a non empty category is defined for a package, then all sub packages shall have empty category or the same category.

Lower part of the table: Additionally, the "Rules for references between elements in packages with specific categories" shall apply.

]

[constr_2516] Return type of an [AttributeValueVariationPoint](#) [When such a formula is evaluated by a software tool, and the return value of the formula is shall be compatible to the type of the attribute in the pure meta-model.

]

¹⁶see [\[constr_2573\]](#) for details

[constr_2517] `postBuildVariantCondition` only for `PostBuild` [Aggregation of `PostBuildVariantCondition` in `VariationPoint` is only allowed if the annotated model states `vh.latestBindingTime` to `PostBuild`.

]

[constr_2518] Binding time is constrained [Note that this binding time is again constrained by the value of the tag `vh.latestBindingTime`.

]

[constr_2519] `PredefinedVariants` need to be consistent [If a `PredefinedVariant` plus its `includedVariants` references more than one `SwSystemconstantValueSet` all `value` attributes in `SwSystemconstValues` for a particular `SwSystemconst` shall be identical.

]

[constr_2520] Nesting of lists shall be limited [The nesting of lists shall be limited to a reasonable depth such that it can safely be rendered on A4 pages. A reasonable approach is not to nest more than three levels.

]

[constr_2521] The `shortLabel` in `AttributeValueVariationPoint` shall be unique [The `shortLabel` shall be unique (case insensitive) within the next enclosing `Identifiable` and is used to individually address variation points in the *variant-rich M1 model*.

Note that the check for uniqueness of `shortLabel` shall be performed case insensitively. This supports the good practice that `shortLabels` should not differ in upper / lower case only which would cause a lot of confusion.

The term 'case insensitive' indicates that the characters in the sets

```
{a b c d e f g h i j k l m n o p q r s t u v w x y z}  
{A B C D E F G H I J K L M N O P Q R S T U V W X Y Z}
```

are respectively considered to be the same. In other words case-insensitive check for uniqueness of `shortLabel` results in the fact that e.g. elements with `shortLabel` 'X' and 'x' are considered the same and shall not exist in the same context.

]

[constr_2522] Notes should not be nested [Note even if it is possible to nest notes it is not recommended to do so, since it might lead to problems with the rendering of the note icon.

]

[constr_2523] Used languages need to be consistent [The used languages of an AUTOSAR file are specified in the top level `adminData`. All other elements shall be provided in the languages specified for the document.

]

[constr_2524] Non splitable elements in one file [If the *aggregation/attribute* is not `<<atpSplitable>>`, then all aggregated element(s) shall be described in the same physical file as the aggregating element.

]

[constr_2533] Documentation context is either a feature or an identifiable [One particular `DocumentationContext` shall be either a feature or an identifiable but not both at the same time. If this is desired, one should create multiple `DocumentationContext`.

]

[constr_2534] Practically `UnlimitedInteger` shall be limited such that it fits into 64 bit. [If a signed value is represented the min value can be down to -9223372036854775808 (`0x800000000000000014`) and the max value can be up to 9223372036854775807 (`0x7fffffffffffffffffffff`).

]

[constr_2538] Global reference is limited to certain elements [The ability to perform a global reference is limited to

- `Chapter`,
- `Topic1`,
- `Caption`,
- `Traceable`,
- `XrefTarget`,
- `Std`,
- `Xdoc`,
- `Xfile`

]

[constr_2547] Ordered collections cannot be split into different partial models [Ordered collections cannot be split. In other words: Contrary to the semantics of unordered collections - which can be distributed between partial models - ordered col-

lections can only be placed as a whole in one of the partial models. Otherwise the merge approach would influence the semantics of the collections.

」

[constr_2557] No `VariationPoints` where `vh.latestBindingTime` set to `BlueprintDerivationTime` in system configurations [Blueprints are **not** part of a system configuration. In consequence of this, in a system configuration there shall be no `VariationPoint` where `vh.latestBindingTime` is restricted to `BlueprintDerivationTime` by the meta-model.

」

[constr_2558] If `vh.latestBindingTime` is `BlueprintDerivationTime` then there shall only be `blueprintCondition` or `formalBlueprintGenerator` respectively `blueprintValue` [`VariationPoints` with `vh.latestBindingTime` restricted to `BlueprintDerivation` shall not have `swSyscond` nor `postBuildVariantCondition`.

」

[constr_2559] No nested `VariationPoint` [As `blueprintCondition` is a `DocumentationBlock` it could again contain `VariationPoints` and therefore would allow nesting of `VariationPoints`. This is not intended and shall not be used.

」

[constr_2567] Undefined Value in Attribute Value Blueprints [If a `blueprintValue` is specified, then the `value` defined by the `AttributeValueVariationPoint` is not used and should therefore at least contain one term `undefined` which is to be refined when deriving objects from this blueprint.

」

[constr_2572] Unique Control of Document Languages [The settings for multiple languages are specified in the top-Level `AdminData` only

」

[constr_2573] ICS shall not reference examples [ICS is like a productive Model and therefore shall not reference to an `EXAMPLE`. Such a reference would be useless since the target needs to be ignored in the ICS.

」

[constr_2575] blueprintValue in blueprints only [blueprintValue is only allowed in blueprints and may not be present in a system description.

]

[constr_2577] Binding Time in Aggregation Pattern [Within *VariationPoint*, the class *ConditionByFormula* has an attribute *bindingTime* which defines the *latest* binding time for this variation point. This binding time is further constrained by the UML tag *vh.latestBindingTime* that is attached to the aggregation see [TPS_GST_00190], [TPS_GST_00220], [TPS_GST_00221]):

ConditionByFormula.bindingTime ≤ *aggregation.vh.latestBindingTime*

]

[constr_2578] Binding Time in Association Pattern [Within *VariationPoint*, the class *ConditionByFormula* has an attribute *bindingTime* which defines the *latest* binding time for this variation point. This binding time is further constrained by the UML tag *vh.latestBindingTime* that is attached to the association (see [TPS_GST_00190], [TPS_GST_00220],[TPS_GST_00221]):

ConditionByFormula.bindingTime ≤ *association.vh.latestBindingTime*

]

[constr_2579] Binding Time in Attribute Value Pattern [The meta-class *AttributeValueVariationPoint* has an attribute *bindingTime* which defines the *latest* binding time for this variation point. This binding time is further constrained by the UML tag *vh.latestBindingTime* that is attached to the attribute (see [TPS_GST_00190], [TPS_GST_00220], [TPS_GST_00221]):

AttributeValueVariationPoint.bindingTime ≤ *attribute.vh.latestBindingTime*

]

[constr_2580] Binding Time in Property Set Pattern [The meta-class *VariationPoint* has an attribute *bindingTime* which defines the *latest* binding time for this variation point. This binding time is further constrained by the UML tag *vh.latestBindingTime* that is attached to the meta-class which is marked as *<<atpVariation>>* (see [TPS_GST_00190], [TPS_GST_00220], [TPS_GST_00221]):

VariationPoint.bindingTime ≤ *meta class.vh.latestBindingTime*

]

[constr_2581] Default life cycle state shall be defined properly [defaultLcState in LifeCycleInfoSet shall reference to a lcState defined in the LifeCycleStateDefinitionGroup referenced by usedLifeCycleStateDefinitionGroup.

}

[constr_2583] Used life cycle state shall be defined properly [defaultLcState in LifeCycleInfo shall reference to a lcState defined in the LifeCycleStateDefinitionGroup referenced by usedLifeCycleStateDefinitionGroup of the containing LifeCycleInfoSet.

}

[constr_2585] LifeCycleInfo shall be unambiguous [Within one particular LifeCycleInfoSet lifeCycleInfo.lcObject shall be unique. This ensures that the association of a LifeCycleState to a Referrable is unambiguous.

This constraint applies for a particular point in time under consideration of the period of viability according to [TPS_GST_00244].

}

[constr_2586] Constraints on LifeCyclePeriod [The attributes date, arReleaseVersion, productRelease in LifeCyclePeriod are mutually exclusive.

}

[constr_2587] No System in AnyInstanceRef [In consequence of [TPS_GST_00387] System shall not be contextElement nor target of an AnyInstanceRef. Otherwise atpBase would not be determined.

}

[constr_2594] Cyclic value assignments to SwSystemconst is not allowed [It is explicitly forbidden to assign values to SwSystemconst which in turn depend directly or indirectly on this value assignment.

}

[constr_2595] Footnotes should not be nested [Note that even if supported by the meta-model, footnotes shall not be nested. Nested footnotes might lead to problems with the processing of the footnote link. In other words LParagraph shall not be aggregated with role ft within a LParagraph which already has the role ft.

}

[constr_2596] Used colors of attributes color and bgcolor [The used colors of the attributes color and bgcolor shall base on the 6 digits RGB hex-code following

```
|#([a-fA-F0-9]{6})|
```

.
]

[constr_2599] Maximum one VariationPoints in <<atpMixed>> [In case an <<atpMixed>> meta-class is aggregated as <<atpVariation>> there shall not be more than one `VariationPoint` and the `VariationPoint` shall be the last aggregated element.

]

[constr_2601] Value of `AbstractEnumerationValueVariationPoint` [The formula of an `AbstractEnumerationValueVariationPoint` shall evaluate to a value for which a mapping is defined in the `EnumerationMappingTable` which is referenced by the attributes `base` and `enumTable`.

]

[constr_2602] Completeness of `AnyInstanceRef` referencing `ImplementationDataTypeElement` [If the `target` references an `ImplementationDataTypeElement` the `AnyInstanceRef` shall define a `contextElement` reference for

1. each leaf `ImplementationDataTypeElement` in a chain of referencing `ImplementationDataTypes` which is not the `target`
2. and each `ImplementationDataTypeElement` of category ARRAY in a chain of referencing `ImplementationDataTypes`

Thereby the contexts are created according [TPS_GST_00162] from the root to the leaf `ImplementationDataTypeElement` which is either typed (directly or indirectly via `ImplementationDataType` of category TYPE_REFERENCE) or owns the `target`.

]

[constr_2606] Existence of `upperMultiplicityInfinite` and `upperMultiplicity` of `AbstractMultiplicityRestriction` is mutually exclusive [The existence of the elements `upperMultiplicityInfinite` and `upperMultiplicity` of `AbstractMultiplicityRestriction` shall be mutually exclusive.

]

[constr_2607] `lowerMultiplicity` of `AbstractMultiplicityRestriction` shall be smaller or equal to `upperMultiplicity` [`lowerMultiplicity` of Ab-

`structMultiplicityRestriction` shall be smaller or equal to `upperMultiplicity`.

]

[constr_2626] `atpTarget` of InstanceRefs shall be consistent [The `atpTarget` of an instance ref shall either

- be an `atpFeature` owned by the `atpType` of the last `atpContextElement` or
- be an `atpFeature` owned by an `AtpStructureElement` owned by the `atpType` of the last `atpContextElement`.

]

[constr_2627] No reassigning of the same name within one LET Block [Within one LET block one name shall be assigned to an value at most once.

]

[constr_2628] Representation of `xml.xsd.type=double` data types [All data types with `xml.xsd.type=double` shall comply with IEEE 754 and are limited to what can be expressed by a 64 bit binary representation.

]

[constr_2629] Defined identity up to the root [If an element in the M1 model aggregates splittable elements on deeper levels, it shall have a defined identity, i.e. the identifying attributes (e.g. `shortName` or `shortLabel`); see [TPS_GST_00047]; shall be set in the M1 model.

]

[constr_2630] M1 elements with same identity but different type are not allowed [Splittable M1 elements with the same identity but different type shall not exist.

]

[constr_2631] Usage of value ANY for `AnyServiceInstanceId` [The value of a given `AnyServiceInstanceId` shall not be set to ANY.

]

[constr_2632] No postbuild variation for attribute values [The tag `vh.latestBindingTime` is limited to `preCompileTime` and earlier binding times, i.e.

(`blueprintDerivationTime`, `systemDesignTime` and `codeGenerationTime`) in the Attribute Value pattern.

]

[constr_2633] Existence of reference decorated with stereotype `<<isOfType>>`
[If a subclass of `AtpPrototype` defines a reference decorated with stereotype `<<isOfType>>` to a subclass of `AtpType`, then this reference shall always exist.

]

[constr_2634] Conditionals with ordered collections [Ordered collections shall not be split over different conditionals.

]

[constr_2635] No custom values for `Collection.category` [It is not allowed to define any custom or project-specific value of the attribute `Collection.category`.

]

[constr_2636] No custom values for `Collection.elementRole` [It is not allowed to define any custom or project-specific value of the attribute `Collection.elementRole`.

]

[constr_2637] Limits of `PositiveUnlimitedInteger` [For `PositiveUnlimitedInteger`, the min value can be down to 0 and the max value can be up to 18446744073709551615 (0xffffffffffffffff).]

]

[constr_2638] Variation points shall not exist in non-variant roles [Variation Points shall not exist if the aggregation is not stereotyped `<<atpVariation>>` in the AUTOSAR meta model at any time in the workflow.

]

[constr_2639] Restriction for the value of the first character in an `AnyVersionString` [The first character of the value of any attribute typed by `AnyVersionString` shall only be in the range 1..9.

]

[constr_2640] Restriction for the length of the value of an `AnyVersionString`
[The value of any attribute typed by `AnyVersionString` shall contain at least one character.

]

[constr_4055] ICS may not contain blueprints [Since an Implementation Conformance Statement always describes a set of one or more fully configured software modules, a package with category `ICS` it is not allowed to contain sub-packages at any level which have the category `BLUEPRINT`.

]

2.9 FO_TPS_StandardizationTemplate

[constr_2500] `PortInterfaces` shall be of same kind [Both objects (`PortInterfaces`) referenced by a blueprint mapping for port interfaces (represented by `BlueprintMapping`) shall be of the same kind (e.g. both shall be `SenderReceiverInterfaces`). In other words both interfaces shall be instances of the same meta class.

]

[constr_2526] `PortInterface` need to be compatible to the blueprints [`PortInterface` shall be compatible to their respective blueprints according to the compatibility rules.

]

[constr_2527] Blueprints shall live in package of a proper category [As explained in detail in the [11], model artifacts (in this case `PortPrototypeBlueprint` and incompletely specified `PortInterfaces`) created for the purpose of becoming blueprints shall reside in an `ARPackage` of category `BLUEPRINT`.

]

[constr_2528] `PortPrototypes` shall not refer to blueprints of a `PortInterface` [A port `PortPrototype` shall not reference a `PortInterface` which lives in a package of category `BLUEPRINT`.

]

[constr_2529] `PortPrototypeBlueprints` and derived `PortPrototypes` shall reference proper `PortInterfaces` [A `PortPrototypeBlueprint` may reference

a blueprint of `PortInterface`. According to [constr_2570], a system description shall not contain blueprints. Therefore the reference to the `PortInterface` may need to be rewritten when a `PortPrototype` is derived from the blueprint.

In this case the `PortInterface` referenced by the derived `PortPrototype` shall be compatible to the `PortInterface` (which is a blueprint) referenced by the `PortPrototypeBlueprint`.

According to [constr_2526] this can be ensured if the `PortInterface` referenced by the `PortPrototypeBlueprint` is the blueprint of the `PortInterface` referenced by the respective `PortPrototype`.

]

[constr_2546] References in derived model elements [Model elements derived from blueprints shall never refer to model elements that are blueprints.

]

[constr_2553] `shortName` shall follow the pattern defined in the Blueprint [The `shortName` respectively `symbol` of the derived objects shall follow the pattern defined in `namePattern` or `blueprintValue` of the blueprint according to [TPS_STDT_00086]

]

[constr_2554] Derived objects shall match the blueprints [Unless specified explicitly otherwise, the attributes of the blueprint shall appear in the derived objects. As an exception `namePattern` and `blueprintValue` may **not** be copied.

]

[constr_2556] No Blueprint Motivated `VariationPoints` in AUTOSAR Descriptions [AUTOSAR descriptions which are not blueprints shall not have `blueprintCondition`, `formalBlueprintGenerator` nor `blueprintValue`.

]

[constr_2563] `BswModuleDescription` blueprints should not have a `BswInternalBehavior` [A `BswModuleDescription` blueprint should not have a `BswInternalBehavior` since this is a matter of implementation and not subject to standardization. Exceptions might exist in vendor internal applications.

]

[constr_2565] Traceable shall not be nested [Due to the intended atomicity of requirements respectively specification items, `Traceable` shall not be nested.

]

[constr_2566] Blueprintmapping shall map appropriate elements [`BlueprintMapping` shall map elements which represent a valid pair of blueprint / derived object. In most of the cases this means that `blueprint` and `derivedObject` shall refer to objects of the same meta-class.

]

[constr_2568] SwComponentTypes shall be of same kind [Both objects (`SwComponentTypes`) referenced by a blueprint mapping for port interfaces (represented by `BlueprintMapping`) shall be of the same kind (e.g. both shall be `AtomicSwComponentTypes`). In other words both components shall be instances of the same meta class.

]

[constr_2569] Purely Blueprint Motivated VariationPoints [`VariationPoints` with `vh.latestBindingTime` set to `blueprintDerivationTime` shall have only `blueprintCondition` or `formalBlueprintGenerator` respectively `blueprintValue`.

]

[constr_2570] No Blueprints in system descriptions [There shall be no blueprints in system descriptions. In consequence of this blueprint elements shall be referenced only from blueprints and `AtpBlueprintMappings`. Due to `<<atpUriDef>>`, the references from `AtpBlueprintMapping` do not need to be resolved in system descriptions.

]

[constr_2571] Outgoing references from Blueprints [Note that outgoing references from Blueprints are basically not limited. Practically, references to objects living in a package of category EXAMPLE should not occur.

]

[constr_2589] In VFB Timing Blueprint TDEventVfbPort shall reference Port-PrototypeBlueprint [In a VFB Timing Blueprint `TDEventVfbPort` shall reference `PortPrototypeBlueprint`. In other words, a VFB Timing Description Event specified in a VFB Timing Blueprint shall always reference a Port Prototype Blueprint.

]

[constr_2590] One BlueprintPolicy is allowed [For each attribute of a blueprint, at most one `BlueprintPolicy` is allowed.

]

[constr_2591] BlueprintPolicyNotModifiable [If `BlueprintPolicyNotModifiable` is assigned to an attribute, then during blueprinting it is not allowed to modify the value of the attribute and all its contained content.

]

[constr_2592] No BlueprintPolicy [If no `BlueprintPolicy` is assigned to an attribute, then arbitrary modifications are allowed while deriving from the blueprint.

]

[constr_2593] Expression for identifying the attribute a BlueprintPolicy relates to [The expression language for identifying the related attribute of a `BlueprintPolicy` is a subset version of xpath, see [12]. For navigation over the model we use the names as they are used in XML.

]

[constr_2597] ClientServerOperationBlueprintMapping constrains number of arguments [The number of arguments of the `BswModuleEntry` referenced by a `bswModuleEntry` shall be identical to the number of `portDefinedArgumentBlueprints` of the owning `ClientServerInterfaceToBswModuleEntryBlueprintMapping` plus the number of `ArgumentDataPrototypes` aggregated in the role argument of the `clientServerOperation`

]

[constr_2598] ClientServerOperationBlueprintMapping constrains the types of arguments [The arguments in the ordered lists `bswModuleEntry` and the matching arguments in the set union of the ordered lists `portDefinedArgumentBlueprint` plus `clientServerOperation` shall result in the identical C data type definitions.

]

[constr_2603] Use of appliesTo in context of the specification level [On specification level 1 and 2 only the requirements table including the `appliesTo` attribute shall be used. On the specification levels 3 and 4 only the requirements table without the `appliesTo` shall be used. Exception: Documents of the foundation which are handled on specification level 3.

]

[constr_2604] Allowed up-traces in context of `appliesTo` values [Traces to documents of upper specification levels shall be conform to the values assigned to `appliesTo`.]

]

[constr_2608] Custom extensions shall be part of the `Documentation` that is referenced by the `Baseline` [If a `SpecElementReference` references a custom defined specification element, then this specification element shall be part of a `Documentation` that is referenced by the `Baseline` of this `Profile`.]

]

[constr_2609] Single revision per AUTOSAR standard [The `standardRevision` may only contain a single revision per AUTOSAR standard. E.g. it is allowed to combine the AUTOSAR standards "Foundation" in revision 1.0.0 with the "Classic Platform" in revision 4.3.0. However, it is not allowed to reference the revisions 4.2.2 and 4.3.0 of the "Classic Platform" in the same `Baseline`.]

]

[constr_2610] No `alternativeName` if matching via `shortName` [The `alternativeName` shall not be set if the referenced AUTOSAR Specification Element matches the rules of `Identifier`.]

]

[constr_2611] Referenced AUTOSAR Specification Elements shall be part of the `AUTOSAR Specification Baseline` [If the `SpecElementReference` references an AUTOSAR specification element then the `shortName` or `alternativeName` shall match the name of the AUTOSAR specification element in a specification that is part of the revision of the standard that is specified in `Baseline`.]

]

[constr_2612] `shortName` of `ConcreteClassTailoring` shall match the name of an AUTOSAR specified concrete meta-class [`shortName` of `ConcreteClassTailoring` shall match the name of an AUTOSAR specified concrete meta-class).

]

[constr_2613] `shortName` of `AbstractClassTailoring` shall match the name of an AUTOSAR specified abstract meta-class [`shortName` of `AbstractClassTailoring` shall match the name of an AUTOSAR specified abstract meta-class).

]

[constr_2614] PrimitiveAttributeCondition.attribute shall reference invariant owned PrimitiveAttributeTailoring, only [The following conditions need to evaluate to true for `PrimitiveAttributeCondition.attribute`:

- The referenced `PrimitiveAttributeTailoring` is owned by an `ClassContentConditional` that has no `condition` (invariant class content) **AND**
- The `ClassContentConditional` that owns the referenced `PrimitiveAttributeTailoring` and the `ClassContentConditional` that owns this `PrimitiveAttributeCondition` are owned by the same `ClassTailoring`.

]

[constr_2615] AggregationCondition.aggregation shall reference invariant owned AggregationTailoring, only [The following conditions need to evaluate to true for `AggregationCondition.aggregation`:

- The referenced `AggregationTailoring` is owned by an `ClassContentConditional` that has no `condition` (invariant class content) **AND**
- The `ClassContentConditional` that owns the referenced `AggregationTailoring` and the `ClassContentConditional` that owns this `AggregationCondition` are owned by the same `ClassTailoring`.

]

[constr_2616] ReferenceCondition.reference shall reference invariant owned ReferenceTailoring, only [The following conditions need to evaluate to true for `ReferenceCondition.reference`:

- The referenced `ReferenceTailoring` is owned by an `ClassContentConditional` that has no `condition` (invariant class content) **AND**
- The `ClassContentConditional` that owns the referenced `ReferenceTailoring` and the `ClassContentConditional` that owns this `ReferenceCondition` are owned by the same `ClassTailoring`.

]

[constr_2617] ClassTailoring.variationRestriction only applicable for «atpVariation» classes [If the tailored meta class is not marked with stereotype «atpVariation» then `ClassTailoring.variationRestriction` shall not be defined.

]

[constr_2618] ShortName of AttributeTailoring shall match owned or inherited attributes [The `shortName` shall match the name of an attribute that is owned or

inherited by the AUTOSAR meta-class which is identified by the `ClassTailoring` that owns this `AttributeTailoring`.

}

[constr_2619] No `AttributeTailoring` for Derived or Abstract Attributes [No `AttributeTailorings` are allowed for `Attributes` that are marked with stereotypes `<<atpDerived>>` or `<<atpAbstract>>`.

}

[constr_2620] `shortName` of `PrimitiveAttributeTailoring` shall be a primitive attribute in the referenced Baseline [The `shortName` of `PrimitiveAttributeTailoring` shall match the name of an AUTOSAR specified primitive attribute of the Meta-Class in the referenced Baseline.

}

[constr_2621] The `shortName` of `AggregationTailoring` shall match the name of an AUTOSAR specified aggregation of the meta-class [The `shortName` of `AggregationTailoring` shall match the name of an AUTOSAR specified aggregation of the meta-class).

}

[constr_2622] The `shortName` of `ReferenceTailoring` shall match the name of an AUTOSAR specified reference of the meta-class [The `shortName` of `ReferenceTailoring` shall match the name of an AUTOSAR specified reference of the meta-class).

}

[constr_2623] Referenced `SdgClass` shall be part of a `SdgDef` that is referenced by the `Baseline` [Referenced `SdgClass` shall be part of a `SdgDef` that is referenced by the `Baseline` of this Profile of Data Exchange Point.

}

[constr_2624] `AttributeTailoring.variationRestriction` only applicable for «`atpVariation`» attributes [If the tailored attribute is not marked with stereotype «`atpVariation`» then `AttributeTailoring.variationRestriction` shall not be defined.

}

[constr_2625] Permitted `LifeCycleState` combinations in a requirement up-trace [

	Trace to: <code>TraceableText.category=REQUIREMENT_ITEM</code>			
Trace from:	DRAFT	VALID	OBSOLETE	REMOVED
DRAFT	1	1		
VALID	x	1		
OBSOLETE	1	1	1	
REMOVED	1	1	1	1
Legend:				
x) A "not applicable" requirement - as per [TPS_STDT_00056] with <code>LifeCycleState==VALID</code> may uptrace to <code>LifeCycleState==DRAFT</code>				
1) Permitted				

]

A Mentioned Class Tables

Class	ARPackage			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::ARPackage			
Note	<p>AUTOSAR package, allowing to create top level packages to structure the contained ARElements.</p> <p>ARPackages are open sets. This means that in a file based description system multiple files can be used to partially describe the contents of a package.</p> <p>This is an extended version of MSR's SW-SYSTEM.</p>			
Base	<i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>CollectableElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	ARPackage.arPackage , AUTOSAR.arPackage			
Attribute	Type	Mult.	Kind	Note
arPackage	ARPackage	*	aggr	<p>This represents a sub package within an ARPackage, thus allowing for an unlimited package hierarchy.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=arPackage.shortName, arPackage.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.sequenceOffset=30</p>
element	PackageableElement	*	aggr	<p>Elements that are part of this package</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=element.shortName, element.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=20</p>
referenceBase	ReferenceBase	*	aggr	<p>This denotes the reference bases for the package. This is the basis for all relative references within the package. The base needs to be selected according to the base attribute within the references.</p> <p>Stereotypes: atpSplitable</p> <p>Tags: atp.Splitkey=referenceBase.shortLabel xml.sequenceOffset=10</p>

Table A.1: ARPackage

Class	AUTOSAR			
Package	M2::AUTOSARTemplates::AutosarTopLevelStructure			
Note	<p>Root element of an AUTOSAR description, also the root element in corresponding XML documents.</p> <p>Tags: xml.globalElement=true</p>			
Base	<i>ARObject</i>			
Attribute	Type	Mult.	Kind	Note
adminData	AdminData	0..1	aggr	<p>This represents the administrative data of an Autosar file.</p> <p>Stereotypes: atpSplitable</p> <p>Tags: atp.Splitkey=adminData xml.sequenceOffset=10</p>





Class	AUTOSAR			
arPackage	ARPackage	*	aggr	This is the top level package in an AUTOSAR model. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=arPackage.shortName, arPackage.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.sequenceOffset=30
fileInfoComment	FileInfoComment	0..1	aggr	This represents a possibility to provide a structured comment in an AUTOSAR file. Stereotypes: atpStructuredComment Tags: xml.roleElement=true xml.sequenceOffset=-10 xml.typeElement=false
introduction	DocumentationBlock	0..1	aggr	This represents an introduction on the Autosar file. It is intended for example to represent disclaimers and legal notes. Tags: xml.sequenceOffset=20

Table A.2: AUTOSAR

Class	AbsoluteTolerance			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	Maximum allowable deviation			
Base	<i>ARObject</i> , <i>TimeRangeTypeTolerance</i>			
Aggregated by	TimeRangeType.tolerance			
Attribute	Type	Mult.	Kind	Note
absolute	TimeValue	0..1	attr	Maximum allowable deviation in duration (in seconds)

Table A.3: AbsoluteTolerance

Class	<i>AbstractAccessPoint</i> (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::AccessCount			
Note	Abstract class indicating an access point from an ExecutableEntity.			
Base	<i>ARObject</i> , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	AsynchronousServerCallResultPoint , ExternalTriggeringPointIdent , InternalTriggeringPoint , ModeAccessPointIdent , ModeSwitchPoint , ParameterAccess , ServerCallPoint , VariableAccess			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
returnValueProvision	RteApiReturnValueProvisionEnum	0..1	attr	This attribute controls the provision of return values for RTE APIs that correspond to the enclosing access point.

Table A.4: AbstractAccessPoint

Class	AbstractCanCommunicationControllerAttributes (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	For the configuration of the CanController parameters two different approaches can be used: 1. Providing exact values which are taken by the ECU developer (CanControllerConfiguration). 2. Providing ranges of values which are taken as requirements and have to be respected by the ECU developer (CanControllerConfigurationRequirements).			
Base	ARObject			
Subclasses	CanControllerConfiguration , CanControllerConfigurationRequirements			
Aggregated by	AbstractCanCommunicationController.canControllerAttributes			
Attribute	Type	Mult.	Kind	Note
canControllerFdAttributes	CanControllerFdConfiguration	0..1	aggr	Bit timing related configuration of a CAN controller for payload and CRC of a CanFD frame. If this element exists the controller supports CanFD frames and the ECU developer shall take these values for the configuration of the CanFD controller.
canControllerFdRequirements	CanControllerFdConfigurationRequirements	0..1	aggr	Additional CanFD ranges of the bit timing related configuration of a CanFD controller. If this element exists the controller supports CanFD frames and the ECU developer shall take these ranges as requirements for the configuration of the CanFD controller.
canControllerXlAttributes	CanControllerXlConfiguration	0..1	aggr	Bit timing related configuration of a CAN controller for payload and CRC of a CanXL frame. If this element exists the controller supports CanXL frames and the ECU developer shall take these values for the configuration of the CanXL controller.
canControllerXlRequirements	CanControllerXlConfigurationRequirements	0..1	aggr	Additional CanXL ranges of the bit timing related configuration of a CanXL controller. If this element exists the controller supports CanXL frames and the ECU developer shall take these ranges as requirements for the configuration of the CanXL controller.

Table A.5: AbstractCanCommunicationControllerAttributes

Class	AbstractClassTailoring			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	Tailoring of abstract classes in the AUTOSAR meta-model			
Base	ARObject, ClassTailoring , DataFormatElementReference , Identifiable , MultilanguageReferrable , Referrable , SpecElementReference			
Aggregated by	AggregationTailoring.typeTailoring , DataFormatTailoring.classTailoring , ReferenceTailoring.typeTailoring			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.6: AbstractClassTailoring

Class	«atpMixedString» AbstractEnumerationValueVariationPoint (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling::AttributeValueVariationPoints			
Note	This is an abstract EnumerationValueVariationPoint. It is introduced to support the case that additional attributes are required for particular purposes.			
Base	ARObject, AttributeValueVariationPoint , FormulaExpression , SwSystemconstDependentFormula			
Subclasses				
Aggregated by	VariationPointProxy.valueAccess			
Attribute	Type	Mult.	Kind	Note





Class	«atpMixedString» AbstractEnumerationValueVariationPoint (abstract)			
base	Identifier	0..1	attr	This attribute reflects the base to be used in context of EnumerationMappingTable for this reference. Tags: xml.attribute=true
enumTable	Ref	0..1	attr	This represents the assigned enumeration table. Tags: xml.attribute=true

Table A.7: AbstractEnumerationValueVariationPoint

Class	AbstractEthernetFrame (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetFrame			
Note	Ethernet specific attributes to the Frame.			
Base	ARObject , CollectableElement , FibexElement , Frame , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	GenericEthernetFrame, Ieee1722TpEthernetFrame, UserDefinedEthernetFrame			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.8: AbstractEthernetFrame

Class	AbstractEvent (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::InternalBehavior			
Note	This meta-class represents the abstract ability to model an event that can be taken to implement application software or basic software in AUTOSAR.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	BswEvent , RTEEvent			
Attribute	Type	Mult.	Kind	Note
activationReasonRepresentation	ExecutableEntity ActivationReason	0..1	ref	If the activationReasonRepresentation is referenced from the enclosing AbstractEvent this shall be taken as an indication that the latter contributes to the activating vector of this ExecutableEntity that owns the referenced ExecutableEntityActivationReason.

Table A.9: AbstractEvent

Class	AbstractImplementationDataType (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::ImplementationDataTypes			
Note	This meta-class represents an abstract base class for different flavors of ImplementationDataType.			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , AutosarDataType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	ImplementationDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.10: AbstractImplementationDataType

Class	AbstractImplementationDataTypeElement (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::ImplementationDataTypes			
Note	This meta-class represents the ability to act as an abstract base class for specific derived meta-classes that support the modeling of ImplementationDataTypes for a particular language binding.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	ImplementationDataTypeElement			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.11: AbstractImplementationDataTypeElement

Class	AbstractMultiplicityRestriction (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::ModelRestrictionTypes			
Note	Restriction that specifies the valid number of occurrences of an element in the current context.			
Base	ARObject			
Subclasses	AttributeCondition , MultiplicityRestrictionWithSeverity , SdgAttribute			
Attribute	Type	Mult.	Kind	Note
lowerMultiplicity	PositiveInteger	0..1	attr	Specifies the minimal number of times an object shall occur. If this primitive attribute is not set, then the object is optional.
upperMultiplicity	PositiveInteger	0..1	attr	Specifies the maximum number of times an object may occur. If this primitive attribute is not set, then there is no limit with respect to the maximum occurrence.
upperMultiplicityInfinite	Boolean	0..1	attr	This explicitly specifies, that the upper multiplicity is NOT restricted. Note: The use of 'upperMultiplicityInfinite' and 'upperMultiplicity' is mutual exclusive.

Table A.12: AbstractMultiplicityRestriction

Class	AbstractProvidedPortPrototype (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	This abstract class provides the ability to become a provided PortPrototype.			
Base	ARObject , AtpBlueprintable , AtpFeature , AtpPrototype , Identifiable , MultilanguageReferrable , PortPrototype , Referrable			
Subclasses	PPortPrototype , PRPortPrototype			
Aggregated by	AtpClassifier.atpFeature , SwComponentType.port			
Attribute	Type	Mult.	Kind	Note
providedComSpec	PPortComSpec	*	aggr	Provided communication attributes per interface element (data element or operation). Stereotypes: atpSplitable Tags: atp.Splitkey=providedComSpec

Table A.13: AbstractProvidedPortPrototype

Class	AbstractRequiredPortPrototype (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	This abstract class provides the ability to become a required PortPrototype.			
Base	<i>ARObject</i> , <i>AtpBlueprintable</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PortPrototype</i> , <i>Referrable</i>			
Subclasses	PRRPortPrototype, RPortPrototype			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>SwComponentType.port</i>			
Attribute	Type	Mult.	Kind	Note
requiredComSpec	RPortComSpec	*	aggr	Required communication attributes, one for each interface element. Stereotypes: atpSplitable Tags: atp.Splitkey=requiredComSpec

Table A.14: AbstractRequiredPortPrototype

Class	AbstractRuleBasedValueSpecification (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This represents an abstract base class for all rule-based value specifications.			
Base	<i>ARObject</i> , <i>ValueSpecification</i>			
Subclasses	<i>ApplicationRuleBasedValueSpecification</i> , <i>CompositeRuleBasedValueSpecification</i> , <i>NumericalRuleBasedValueSpecification</i>			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, <i>ArrayValueSpecification.element</i> , <i>CalibrationParameterValue.applInitValue</i> , <i>CalibrationParameterValue.implInitValue</i> , <i>ConstantSpecification.valueSpec</i> , <i>CryptoServiceKey.developmentValue</i> , <i>DiagnosticEnvDataCondition.compareValue</i> , <i>DiagnosticEnvDataElementCondition.compareValue</i> , <i>FieldSenderComSpec.initValue</i> , <i>ISignal.initValue</i> , <i>ISignal.receptionDefaultValue</i> , <i>ISignal.timeoutSubstitutionValue</i> , <i>NonqueuedReceiverComSpec.initValue</i> , <i>NonqueuedReceiverComSpec.timeoutSubstitutionValue</i> , <i>NonqueuedSenderComSpec.initValue</i> , <i>NvProvideComSpec.ramBlockInitValue</i> , <i>NvProvideComSpec.romBlockInitValue</i> , <i>NvRequireComSpec.initValue</i> , <i>ParameterDataPrototype.initValue</i> , <i>ParameterProvideComSpec.initValue</i> , <i>ParameterRequireComSpec.initValue</i> , <i>PersistencyDataRequiredComSpec.initValue</i> , <i>PersistencyKeyValuePair.initValue</i> , <i>PortDefinedArgumentValue.value</i> , <i>PortPrototypeBlueprintInitValue.value</i> , <i>RecordValueSpecification.field</i> , <i>SomeipEventDeployment.eventReceptionDefaultValue</i> , <i>StateManagementCompareCondition.compareValue</i> , <i>SwDataDefProps.invalidValue</i> , <i>UserDefinedEventDeployment.eventReceptionDefaultValue</i> , <i>VariableDataPrototype.initValue</i>			
Attribute	Type	Mult.	Kind	Note
-	-	-	-	-

Table A.15: AbstractRuleBasedValueSpecification

Class	AbstractServiceInstance (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Provided and Consumed Ethernet Service Instances that are available at the ApplicationEndpoint.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>ConsumedServiceInstance</i> , <i>DdsCpServiceInstance</i> , <i>ProvidedServiceInstance</i>			
Aggregated by	ServiceInstanceCollectionSet.serviceInstance			
Attribute	Type	Mult.	Kind	Note





Class	AbstractServiceInstance (abstract)			
capabilityRecord	TagWithOptionalValue	*	aggr	A sequence of records to store arbitrary name/value pairs conveying additional information about the named service. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=capabilityRecord, capabilityRecord.variationPoint.shortLabel vh.latestBindingTime=postBuild
majorVersion	PositiveInteger	0..1	attr	Major Version of the ServiceInterface. Value can be set to a number that represents the Major Version of the service.
methodActivationRoutingGroup	PduActivationRoutingGroup	0..1	aggr	The ServiceDiscovery module is able to activate and deactivate the PDU routing for ClientServerOperations (SOME/IP methods). Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=methodActivationRoutingGroup.shortName, methodActivationRoutingGroup.variationPoint.shortLabel vh.latestBindingTime=postBuild
routingGroup	SoAdRoutingGroup	*	ref	The ServiceDiscovery module is able to activate and deactivate the PDU routing from and to TCP/IP-sockets. Tags: atp.Status=obsolete

Table A.16: AbstractServiceInstance

Class	AccessCount			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::AccessCount			
Note	This meta-class provides one count value for a AbstractAccessPoint.			
Base	ARObject			
Aggregated by	AccessCountSet.accessCount			
Attribute	Type	Mult.	Kind	Note
accessPoint	AbstractAccessPoint	0..1	ref	AbstractAccessPoint for which the count value is applicable.
value	PositiveInteger	0..1	attr	This attribute represents the number of determined accesses Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.17: AccessCount

Class	AccessCountSet			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::AccessCount			
Note	This meta-class provides a set of count values evaluated according to the rules of a specific countProfile.			
Base	ARObject			
Aggregated by	ResourceConsumption.accessCountSet			
Attribute	Type	Mult.	Kind	Note





Class	AccessCountSet			
accessCount	AccessCount	*	aggr	Count value for a AbstractAccessPoint. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=accessCount, accessCount.variation Point.shortLabel vh.latestBindingTime=preCompileTime
countProfile	NameToken	0..1	attr	This attribute defines the name of the count profile used to determine the AccessCount.value numbers.

Table A.18: AccessCountSet

Class	AdminData			
Package	M2::MSR::AsamHdo::AdminData			
Note	AdminData represents the ability to express administrative information and custom extensions for an element. This administration information is to be treated as meta-data such as revision id or state of the file. There are basically the following kinds of meta-data <ul style="list-style-type: none"> • The language and/or used languages. • Revision information covering e.g. revision number, state, release date, changes. Note that this information can be given in general as well as related to a particular company. • Document meta-data specific for a company Beside that a custom extension of model-data is possible by <ul style="list-style-type: none"> • Special data 			
Base	<i>ARObject</i>			
Aggregated by	AUTOSAR.adminData , Describable.adminData , Identifiable.adminData			
Attribute	Type	Mult.	Kind	Note
docRevision (ordered)	DocRevision	*	aggr	This allows to denote information about the current revision of the object. Note that information about previous revisions can also be logged here. The entries shall be sorted descendant by date in order to reflect the history. Therefore the most recent entry representing the current version is denoted first. Tags: xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=50 xml.typeElement=false xml.typeWrapperElement=false
language	LEnum	0..1	attr	This attribute specifies the master language of the document or the document fragment. The master language is the one in which the document is maintained and from which the other languages are derived from. In particular in case of inconsistencies, the information in the master language is priority. Tags: xml.sequenceOffset=20





Class	AdminData			
sdg	Sdg	*	aggr	<p>This property allows to keep special data which is not represented by the standard model. It can be utilized to keep e.g. tool specific data.</p> <p>Stereotypes: atpSplittable Tags: atp.Splitkey=sdg.sdgCaption.shortName xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=60 xml.typeElement=false xml.typeWrapperElement=false</p>
usedLanguages	MultilanguagePlainText	0..1	aggr	<p>This property specifies the languages which are provided in the document. Therefore it should only be specified in the top level admin data. For each language provided in the document there is one entry in MultilanguagePlainText. The content of each entry can be used for illustration of the language. The used language itself depends on the language attribute in the entry.</p> <p>Tags: xml.sequenceOffset=30</p>

Table A.19: AdminData

Class	AgeConstraint			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::AgeConstraint			
Note	Constrains the <i>scope</i> by a <i>minimum</i> and <i>maximum</i> time boundary.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
maximum	MultidimensionalTime	0..1	aggr	The received event referenced by <i>scope</i> should not exceed this upper bound.
minimum	MultidimensionalTime	0..1	aggr	The received event referenced by <i>scope</i> should not precede this lower bound.
scope	TimingDescriptionEvent	0..1	ref	TimingDescriptionEvent to be constrained.

Table A.20: AgeConstraint

Class	AggregationCondition			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	The AggregationCondition evaluates to true, if the referenced aggregation is accepted by all rules of this condition.			
Base	ARObject, AbstractCondition , AbstractMultiplicityRestriction , AttributeCondition			
Aggregated by	ClassContentConditional.condition , InvertCondition.condition			
Attribute	Type	Mult.	Kind	Note
aggregation	AggregationTailoring	1	ref	The aggregation that has to be accepted by the restrictions of this AggregationCondition

Table A.21: AggregationCondition

Class	AggregationTailoring			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	Tailoring of aggregations in the AUTOSAR meta-model			
Base	<i>ARObject</i> , <i>AttributeTailoring</i> , <i>DataFormatElementReference</i> , <i>DataFormatElementScope</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>SpecElementReference</i> , <i>SpecElementScope</i>			
Aggregated by	ClassContentConditional.attributeTailoring			
Attribute	Type	Mult.	Kind	Note
typeTailoring	ClassTailoring	*	aggr	Local class tailoring which is applied if the content is contained by this aggregation.

Table A.22: AggregationTailoring

Class	AliasNameAssignment			
Package	M2::AUTOSARTemplates::CommonStructure::FlatMap			
Note	<p>This meta-class represents the ability to associate an alternative name to a flat representations or an Identifiable.</p> <p>The usage of this name is defined outside of AUTOSAR. For example this name can be used by MCD tools or as a name for component instances in the ECU extract.</p> <p>Note that flatInstance and identifiable are mutually exclusive.</p>			
Base	<i>ARObject</i>			
Aggregated by	AliasNameSet.aliasName			
Attribute	Type	Mult.	Kind	Note
flatInstance	FlatInstanceDescriptor	0..1	ref	Assignment of a unique name to a flat representation. Tags: xml.sequenceOffset=60
identifiable	Identifiable	0..1	ref	Assignment of a unique name to an Identifiable. Tags: xml.sequenceOffset=50
label	MultilanguageLong Name	0..1	aggr	This represents an "Alias LongName". Tags: xml.sequenceOffset=20
shortLabel	String	0..1	attr	This attribute represents the alias name. It is modeled as string because the alias name is used outside of AUTOSAR and therefore no naming conventions can be applied within AUTOSAR. Stereotypes: atpIdentityContributor Tags: xml.sequenceOffset=10

Table A.23: AliasNameAssignment

Class	AliasNameSet			
Package	M2::AUTOSARTemplates::CommonStructure::FlatMap			
Note	<p>This meta-class represents a set of AliasNames. The AliasNameSet can for example be an input to the A2L-Generator.</p> <p>Tags: atp.recommendedPackage=AliasNameSets</p>			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>CollectableElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	AliasNameSet			
aliasName	AliasNameAssignment	*	aggr	AliasNames contained in the AliasNameSet. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=aliasName.shortLabel, aliasName.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.24: AliasNameSet

Class	AnalyzedExecutionTime			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::ExecutionTime			
Note	AnalyzedExecutionTime provides an analytic method for specifying the best and worst case execution time.			
Base	<i>ARObject</i> , ExecutionTime , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ResourceConsumption.executionTime			
Attribute	Type	Mult.	Kind	Note
bestCaseExecutionTime	MultidimensionalTime	0..1	aggr	The best case execution time (BCET) defines the minimum amount of time the related executable entity requires for its execution.
worstCaseExecutionTime	MultidimensionalTime	0..1	aggr	The worst case execution time (WCET) defines the maximum amount of time the related executable entity requires for its execution.

Table A.25: AnalyzedExecutionTime

Class	AnyInstanceRef			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::AnyInstanceRef			
Note	Describes a reference to any instance in an AUTOSAR model. This is the most generic form of an instance ref. Refer to the superclass notes for more details.			
Base	<i>ARObject</i> , AtpInstanceRef			
Aggregated by	ApmcInstanceReferenceValue.value, ApmcUpstreamDocInstanceReferenceValue.value, ApmcUriInstanceReferenceValue.value, Collection.collectedInstance , Collection.sourceInstance , DocumentationContext.feature , EcuInstanceReferenceValue.value , FlatInstanceDescriptor.ecuExtractReference , FlatInstanceDescriptor.upstreamReference , RptContainer.byPassPoint , RptHook.rptArHook , SecurityEventReportInstanceValue.object , ViewMap.firstElementInstance , ViewMap.secondElementInstance			
Attribute	Type	Mult.	Kind	Note
base	AtpClassifier	1	ref	This is the base from which navigation path begins. Stereotypes: atpDerived
contextElement (ordered)	AtpFeature	*	ref	This is one step in the navigation path specified by the instance ref.
target	AtpFeature	1	ref	This is the target of the instance ref.

Table A.26: AnyInstanceRef

Primitive	AnyServiceInstanceId
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes
Note	This is a positive integer or the literal ALL (the value ANY is technically supported but deprecated) which can be denoted in decimal, octal and hexadecimal. The value is between 0 and 65535. Tags: xml.xsd.customType=ANY-SERVICE-INSTANCE-ID xml.xsd.pattern=[1-9][0-9]*0[xX][0-9a-fA-F]+ 0[0-7]*0[bB][0-1]+ ANY ALL xml.xsd.type=string

Table A.27: AnyServiceInstanceId

Primitive	AnyVersionString
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes
Note	Tags: xml.xsd.customType=ANY-VERSION-STRING xml.xsd.pattern=[0-9]+ ANY xml.xsd.type=string

Table A.28: AnyVersionString

Class	ApplicationArrayDataType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes			
Note	An application data type which is an array, each element is of the same application data type. Tags: atp.recommendedPackage=ApplicationDataTypes			
Base	ARElement , ARObject , ApplicationCompositeDataType , ApplicationDataType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , AutosarDataType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dynamicArraySizeProfile	String	0..1	attr	Specifies the profile which the array will follow if it is a variable size array.
element	ApplicationArrayElement	0..1	aggr	This association implements the concept of an array element. That is, in some cases it is necessary to be able to identify single array elements, e.g. as input values for an interpolation routine.

Table A.29: ApplicationArrayDataType

Class	ApplicationArrayElement			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::DataPrototypes			
Note	Describes the properties of the elements of an application array data type.			
Base	ARObject , ApplicationCompositeElementDataPrototype , AtpFeature , AtpPrototype , DataPrototype , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApplicationArrayDataType.element , AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
arraySizeHandling	ArraySizeHandlingEnum	0..1	attr	The way how the size of the array is handled.
arraySizeSemantics	ArraySizeSemanticsEnum	0..1	attr	This attribute controls how the information about the array size shall be interpreted.





Class	ApplicationArrayElement			
indexDataType	ApplicationPrimitiveDataType	0..1	ref	This reference can be taken to assign a CompuMethod of category TEXTTABLE to the array. The texttable entries associate a textual value to an index number such that the element with that index number is represented by a symbolic name.
maxNumberOfElements	PositiveInteger	0..1	attr	The maximum number of elements that the array can contain. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.30: ApplicationArrayElement

Class	ApplicationCompositeDataType (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes			
Note	Abstract base class for all application data types composed of other data types.			
Base	ARElement , ARObject , ApplicationDataType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , AutosarDataType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	ApplicationArrayDataType , ApplicationRecordDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.31: ApplicationCompositeDataType

Class	ApplicationCompositeDataTypeSubElementRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This meta-class represents the specialization of SubElementMapping with respect to Application CompositeDataTypes.			
Base	ARObject , SubElementRef			
Aggregated by	SubElementMapping.firstElement , SubElementMapping.secondElement			
Attribute	Type	Mult.	Kind	Note
application Composite Element	ApplicationCompositeElementDataPrototype	0..1	iref	This represents the referenced ApplicationComposite DataPrototype. InstanceRef implemented by: ApplicationCompositeElementInPortInterfaceInstanceRef

Table A.32: ApplicationCompositeDataTypeSubElementRef

Class	ApplicationCompositeElementDataPrototype (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::DataPrototypes			
Note	This class represents a data prototype which is aggregated within a composite application data type (record or array). It is introduced to provide a better distinction between target and context in instance Refs.			
Base	ARObject, AtpFeature, AtpPrototype, DataPrototype, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	ApplicationArrayElement, ApplicationRecordElement			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
type	ApplicationDataType	0..1	tref	This represents the corresponding data type. Stereotypes: isOfType

Table A.33: ApplicationCompositeElementDataPrototype

Class	ApplicationCompositeElementInPortInterfaceInstanceRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface::InstanceRefs			
Note				
Base	ARObject, AtpInstanceRef			
Aggregated by	ApplicationCompositeDataTypesubElementRef.applicationCompositeElement, CompositeNetworkRepresentation.leafElement			
Attribute	Type	Mult.	Kind	Note
base	DataInterface	0..1	ref	This represents the SenderReceiverInterface that acts as the base in this InstanceRef definition Stereotypes: atpDerived Tags: xml.sequenceOffset=10
contextData Prototype (ordered)	ApplicationCompositeElementDataPrototype	*	ref	This represents a context ApplicationCompositeData Prototype Tags: xml.sequenceOffset=20
rootData Prototype	AutosarDataPrototype	0..1	ref	This refers to the dataPrototype which is typed by the ApplicationDatatype in which which the target can be found. Tags: xml.sequenceOffset=15
targetData Prototype	ApplicationCompositeElementDataPrototype	0..1	ref	This represents the referenced ApplicationComposite DataPrototype. Tags: xml.sequenceOffset=30

Table A.34: ApplicationCompositeElementInPortInterfaceInstanceRef

Class	ApplicationDataType (abstract)
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes
Note	<p>ApplicationDataType defines a data type from the application point of view. Especially it should be used whenever something "physical" is at stake.</p> <p>An ApplicationDataType represents a set of values as seen in the application model, such as measurement units. It does not consider implementation details such as bit-size, endianness, etc.</p> <p>It should be possible to model the application level aspects of a VFB system by using ApplicationData Types only.</p>
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable
Subclasses	ApplicationCompositeDataType, ApplicationPrimitiveDataType
Aggregated by	ARPackage.element





Class	ApplicationDataType (abstract)			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.35: ApplicationDataType

Class	ApplicationEndpoint			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	An application endpoint is the endpoint on an Ecu in terms of application addressing (e.g. socket). The application endpoint represents e.g. the listen socket in client-server-based communication.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SocketAddress.applicationEndpoint			
Attribute	Type	Mult.	Kind	Note
consumed ServiceInstance	ConsumedService Instance	*	aggr	Consumed service instances. Tags: atp.Status=obsolete
maxNumberOf Connections	PositiveInteger	0..1	attr	This attribute defines the maximal number of clients the Server is able to deal with in case of Service Discovery.
network Endpoint	NetworkEndpoint	0..1	ref	Reference to the network address.
priority	PositiveInteger	0..1	attr	Defines the frame priority where values from 0 (best effort) to 7 (highest) are allowed.
providedService Instance	ProvidedService Instance	*	aggr	Provided service instances. Tags: atp.Status=obsolete
tlsCrypto Mapping	TlsCryptoService Mapping	0..1	ref	This reference identifies the applicable TlsCryptoService Mapping that adds the ability for TLS-based encryption on the enclosing ApplicationEndpoint.
tpConfiguration	TransportProtocol Configuration	0..1	aggr	Configuration of the used transport protocol.

Table A.36: ApplicationEndpoint

Class	ApplicationEntry			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Schedule table entry for application messages.			
Base	ARObject, ScheduleTableEntry			
Aggregated by	LinScheduleTable.tableEntry			
Attribute	Type	Mult.	Kind	Note
frameTriggering	LinFrameTriggering	0..1	ref	Specifies the LinFrame that will be transmitted in this frame slot.

Table A.37: ApplicationEntry

Class	ApplicationError			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This is a user-defined error that is associated with an element of an AUTOSAR interface. It is specific for the particular functionality or service provided by the AUTOSAR software component.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ClientServerInterface.possibleError			





Class		ApplicationError		
Attribute	Type	Mult.	Kind	Note
errorCode	Integer	0..1	attr	The RTE generator is forced to assign this value to the corresponding error symbol. Note that for error codes certain ranges are predefined (see RTE specification).

Table A.38: ApplicationError

Class		ApplicationPartition		
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	ApplicationPartition to which SwComponentPrototypes are mapped at a point in time when the corresponding EcuInstance is not yet known or defined. In a later methodology step the Application Partition can be assigned to an EcuPartition. Tags: atp.recommendedPackage=ApplicationPartitions			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.39: ApplicationPartition

Class		ApplicationPartitionToEcuPartitionMapping		
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	Maps ApplicationPartitions to EcuPartitions. With this mapping an OEM has the option to predefine an allocation of Software Components to EcuPartitions in the System Design phase. The final and complete assignment is described in the OS Configuration.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	SystemMapping.applicationPartitionToEcuPartitionMapping			
Attribute	Type	Mult.	Kind	Note
application Partition	ApplicationPartition	*	ref	Reference to ApplicationPartitions that are mapped to an EcuPartition.
ecuPartition	EcuPartition	0..1	ref	Reference to EcuPartition to which the Application Partitions are assigned.

Table A.40: ApplicationPartitionToEcuPartitionMapping

Class		ApplicationPrimitiveDataType		
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes			
Note	A primitive data type defines a set of allowed values. Tags: atp.recommendedPackage=ApplicationDataTypes			
Base	ARElement, ARObject, ApplicationDataType, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.41: ApplicationPrimitiveDataType

Class	ApplicationRecordDataType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes			
Note	An application data type which can be decomposed into prototypes of other application data types. Tags: atp.recommendedPackage=ApplicationDataTypes			
Base	<i>ARElement, ARObject, ApplicationCompositeDataType, ApplicationDataType, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, AutosarDataType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	<i>ARPackage.element</i>			
Attribute	Type	Mult.	Kind	Note
element (ordered)	<i>ApplicationRecordElement</i>	*	aggr	Specifies an element of a record. The aggregation of ApplicationRecordElement is subject to variability with the purpose to support the conditional existence of elements inside a ApplicationrecordDataType. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=element.shortName, element.variation Point.shortLabel vh.latestBindingTime=preCompileTime

Table A.42: ApplicationRecordDataType

Class	ApplicationRecordElement			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::DataPrototypes			
Note	Describes the properties of one particular element of an application record data type.			
Base	<i>ARObject, ApplicationCompositeElementDataPrototype, AtpFeature, AtpPrototype, DataPrototype, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	<i>ApplicationRecordDataType.element, AtpClassifier.atpFeature</i>			
Attribute	Type	Mult.	Kind	Note
isOptional	Boolean	0..1	attr	This attribute represents the ability to declare the enclosing ApplicationRecordElement as optional. This means the that, at runtime, the ApplicationRecordElement may or may not have a valid value and shall therefore be ignored. The underlying runtime software provides means to set the ApplicationRecordElement as not valid at the sending end of a communication and determine its validity at the receiving end.

Table A.43: ApplicationRecordElement

Class	ApplicationRuleBasedValueSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This meta-class represents rule based values for DataPrototypes typed by ApplicationDataTypes (ApplicationArrayDataType or a compound ApplicationPrimitiveDataType which also boils down to an array-nature).			
Base	<i>ARObject, AbstractRuleBasedValueSpecification, CompositeRuleBasedValueArgument, ValueSpecification</i>			





Class		ApplicationRuleBasedValueSpecification		
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, CompositeRuleBasedValueSpecification.compoundPrimitiveArgument, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeIpEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
category	Identifier	0..1	attr	This represents the category of the RuleBasedValue Specification Tags: xml.sequenceOffset=-20
swAxisCont (ordered)	RuleBasedAxisCont	*	aggr	This represents the axis values of a Compound Primitive Data Type (curve or map). The first swAxisCont describes the x-axis, the second swAxisCont describes the y-axis, the third swAxisCont describes the z-axis. In addition to this, the axis can be denoted in swAxisIndex.
swValueCont	RuleBasedValueCont	0..1	aggr	This represents the values of an array or Compound Primitive Data Type. Stereotypes: atp.Splittable Tags: atp.Splitkey=swValueCont

Table A.44: ApplicationRuleBasedValueSpecification

Class		ApplicationSwComponentType		
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	The ApplicationSwComponentType is used to represent the application software. Tags: atp.recommendedPackage=SwComponentTypes			
Base	ARElement, ARObject, AtomicSwComponentType, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
-	-	-	-	-

Table A.45: ApplicationSwComponentType

Class		ApplicationValueSpecification		
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This meta-class represents values for DataPrototypes typed by ApplicationDataTypes (this includes in particular compound primitives). For further details refer to ASAM CDF 2.0. This meta-class corresponds to some extent with SW-INSTANCE in ASAM CDF 2.0.			
Base	ARObject, CompositeRuleBasedValueArgument, ValueSpecification			





Class	ApplicationValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, CompositeRuleBasedValueSpecification.compoundPrimitiveArgument, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeIpEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
category	Identifier	0..1	attr	Specifies to which category of ApplicationDataType this ApplicationValueSpecification can be applied (e.g. as an initial value), thus imposing constraints on the structure and semantics of the contained values, see [constr_1006] and [constr_1519].
swAxisCont (ordered)	SwAxisCont	*	aggr	This represents the axis values of a Compound Primitive Data Type (curve or map). The first swAxisCont describes the x-axis, the second swAxisCont describes the y-axis, the third swAxisCont describes the z-axis. In addition to this, the axis can be denoted in swAxisIndex.
swValueCont	SwValueCont	0..1	aggr	This represents the values of a Compound Primitive Data Type.

Table A.46: ApplicationValueSpecification

Class	ArParameterInImplementationDataInstanceRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements			
Note	This class represents the ability to navigate into an element inside of an ParameterDataPrototype typed by an ImplementationDatatype. Note that it shall not be used if the target is the ParameterDataPrototype itself (e.g. if the target is a primitive data type). Note that this class follows the pattern of an InstanceRef but is not implemented based on the abstract classes because the ImplementationDataType isn't either, especially because ImplementationDataType Element (intentionally) isn't derived from AtpPrototype.			
Base	ARObject			
Aggregated by	ImplementationDataTypeSubElementRef.parameterImplementationDataTypeElement			
Attribute	Type	Mult.	Kind	Note
contextData Prototype (ordered)	AbstractImplementationDataTypeElement	*	ref	This is a context in case there are subelements with explicit types. The reference has to be ordered to properly reflect the nested structure.
portPrototype	PortPrototype	0..1	ref	This reference points to the PortPrototype providing/receiving the root of the parameter.
rootParameter DataPrototype	ParameterData Prototype	0..1	ref	This refers to the ParameterDataPrototype typed by the implementationDataType in which the target can be found.
targetData Prototype	AbstractImplementationDataTypeElement	0..1	ref	This reference points to the target ImplementationDataTypeElement.

Table A.47: ArParameterInImplementationDataInstanceRef

Class	ArVariableInImplementationDataInstanceRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements			
Note	<p>This class represents the ability to navigate into a data element inside of an VariableDataPrototype which is typed by an ImplementationDatatype.</p> <p>Note that it shall not be used if the target is the VariableDataPrototype itself (e.g. if its a primitive).</p> <p>Note that this class follows the pattern of an InstanceRef but is not implemented based on the abstract classes because the ImplementationDataType isn't either, especially because ImplementationDataTypeElement isn't derived from AtpPrototype.</p>			
Base	ARObject			
Aggregated by	AutosarVariableRef.autosarVariableInImplDatatype, ImplementationDataTypeSubElementRef.implementationDataTypeElement			
Attribute	Type	Mult.	Kind	Note
contextData Prototype (ordered)	AbstractImplementationDataTypeElement	*	ref	<p>This is a context in case there are subelements with explicit types. The reference has to be ordered to properly reflect the nested structure.</p> <p>Tags: xml.sequenceOffset=30</p>
portPrototype	PortPrototype	0..1	ref	<p>This is the port providing/receiving the root of the variable</p> <p>Tags: xml.sequenceOffset=10</p>
rootVariableDataPrototype	VariableDataPrototype	0..1	ref	<p>This refers to the VariableDataPrototype typed by the ImplementationDatatype in which the target can be found.</p> <p>Tags: xml.sequenceOffset=20</p>
targetData Prototype	AbstractImplementationDataTypeElement	0..1	ref	<p>This reference points to the target ImplementationDataTypeElement.</p> <p>Tags: xml.sequenceOffset=40</p>

Table A.48: ArVariableInImplementationDataInstanceRef

Class	ArbitraryEventTriggering			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::EventTriggeringConstraint			
Note	<p>Describes that an event occurs occasionally, singly, irregularly or randomly.</p> <p>The primary purpose of this event triggering is to abstract event occurrences captured by data acquisition tools (background debugger, trace analyzer, etc.) during system runtime.</p>			
Base	ARObject, EventTriggeringConstraint, Identifiable, MultilanguageReferrable, Referrable, TimingConstraint, Traceable			
Aggregated by	TimingExtension.timingGuarantee, TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
confidence Interval	ConfidenceInterval	*	aggr	<p>List of confidence intervals.</p> <p>Tags: xml.sequenceOffset=30</p>
maximum Distance	MultidimensionalTime	*	aggr	<p>The nth array element describes the maximum distance that can be observed for a sample of n+1 event occurrences.</p> <p>This is an array with an identical number of elements as for the minimumDistance.</p> <p>Tags: xml.name=TIME-VALUE xml.roleElement=true xml.sequenceOffset=20 xml.typeElement=false</p>





Class	ArbitraryEventTriggering			
minimum Distance	MultidimensionalTime	*	aggr	<p>The nth array element describes the minimum distance that can be observed for a sample of n+1 event occurrences.</p> <p>This is an array with an identical number of elements as for the maximumDistance.</p> <p>Tags: xml.name=TIME-VALUE xml.roleElement=true xml.sequenceOffset=10 xml.typeElement=false</p>

Table A.49: ArbitraryEventTriggering

Class	ArgumentDataPrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	An argument of an operation, much like a data element, but also carries direction information and is owned by a particular ClientServerOperation.			
Base	ARObject , AtpFeature , AtpPrototype , AutosarDataPrototype , DataPrototype , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , ClientServerOperation.argument			
Attribute	Type	Mult.	Kind	Note
direction	ArgumentDirectionEnum	0..1	attr	This attribute specifies the direction of the argument prototype.
serverArgument ImplPolicy	ServerArgumentImplPolicyEnum	0..1	attr	<p>This defines how the argument type of the servers RunnableEntity is implemented.</p> <p>If the attribute is not defined this has the same semantics as if the attribute is set to the value useArgumentType for primitive arguments and structures.</p>

Table A.50: ArgumentDataPrototype

Enumeration	ArgumentDirectionEnum			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes			
Note	<p>Use cases:</p> <ul style="list-style-type: none"> Arguments in ClientServerOperation can have different directions that need to be formally indicated because they have an impact on how the function signature looks like eventually. Arguments in BswModuleEntry already determine a function signature, but the direction is used to specify the semantics, especially of pointer arguments. 			
Aggregated by	ArgumentDataPrototype.direction , SwServiceArg.direction			
Literal	Description			
in	<p>The argument value is passed to the callee.</p> <p>Tags: atp.EnumerationLiteralIndex=0</p>			
inout	<p>The argument value is passed to the callee but also passed back from the callee to the caller.</p> <p>Tags: atp.EnumerationLiteralIndex=1</p>			
out	<p>The argument value is passed from the callee to the caller.</p> <p>Tags: atp.EnumerationLiteralIndex=2</p>			

Table A.51: ArgumentDirectionEnum

Enumeration	ArraySizeHandlingEnum
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes
Note	This enumeration defines different ways to handle the sizes of variable size arrays.
Aggregated by	ApplicationArrayElement.arraySizeHandling , ImplementationDataTypeElement.arraySizeHandling
Literal	Description
allIndicesDifferent ArraySize	All elements of the variable size array may have different sizes. Tags: atp.EnumerationLiteralIndex=0
allIndicesSame ArraySize	All elements of the variable size array have the same size. Tags: atp.EnumerationLiteralIndex=1
inheritedFromArray ElementTypeSize	The size of all dimensions of the variable size array is determined by the size of the contained array element. Tags: atp.EnumerationLiteralIndex=2

Table A.52: ArraySizeHandlingEnum

Enumeration	ArraySizeSemanticsEnum
Package	M2::AUTOSARTemplates::CommonStructure::ImplementationDataTypes
Note	This type controls how the information about the number of elements in an ApplicationArrayDataType is to be interpreted.
Aggregated by	ApplicationArrayElement.arraySizeSemantics , DiagnosticDataElement.arraySizeSemantics , ImplementationDataTypeElement.arraySizeSemantics , SwTextProps.arraySizeSemantics
Literal	Description
fixedSize	This means that the ApplicationArrayDataType will always have a fixed number of elements. Tags: atp.EnumerationLiteralIndex=0
variableSize	This implies that the actual number of elements in the ApplicationArrayDataType might vary at run-time. The value of arraySize represents the maximum number of elements in the array. Tags: atp.EnumerationLiteralIndex=1

Table A.53: ArraySizeSemanticsEnum

Class	ArrayValueSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	Specifies the values for an array.			
Base	ARObject , CompositeValueSpecification , ValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, CompositeRuleBasedValueSpecification.argument, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeipEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note





Class	ArrayValueSpecification			
element (ordered)	ValueSpecification	*	aggr	The value for a single array element. All Value Specifications aggregated by ArrayValueSpecification shall have the same structure. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=element, element.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
intendedPartial Initialization Count	PositiveInteger	0..1	attr	This attribute shall only have a meaning for dynamic arrays and shall be taken as a sanity check: the number filled in the attribute shall be identical to the number of ArrayValueSpecification.element. If the attribute does not exist it means that no partial initialization is intended.

Table A.54: ArrayValueSpecification

Class	AssemblySwConnector			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	AssemblySwConnectors are exclusively used to connect SwComponentPrototypes in the context of a CompositionSwComponentType.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable , SwConnector			
Aggregated by	AtpClassifier.atpFeature , CompositionSwComponentType.connector			
Attribute	Type	Mult.	Kind	Note
provider	AbstractProvidedPort Prototype	0..1	iref	Instance of providing port. InstanceRef implemented by: PPortInComposition InstanceRef
requester	AbstractRequiredPort Prototype	0..1	iref	Instance of requiring port. InstanceRef implemented by: RPortInComposition InstanceRef

Table A.55: AssemblySwConnector

Class	AssignFrameId			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Schedule entry for an Assign Frame Id master request.			
Base	ARObject , LinConfigurationEntry , ScheduleTableEntry			
Aggregated by	LinScheduleTable.tableEntry			
Attribute	Type	Mult.	Kind	Note
assignedFrame Triggering	LinFrameTriggering	0..1	ref	The frame whose identifier is set by this assignment.

Table A.56: AssignFrameId

Class	AssignFrameIdRange			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	AssignFrameIdRange generates an assign frame PID range request.			
Base	ARObject , LinConfigurationEntry , ScheduleTableEntry			





Class	AssignFrameIdRange			
Aggregated by	LinScheduleTable.tableEntry			
Attribute	Type	Mult.	Kind	Note
framePid	FramePid	0..4	aggr	Optional assignment of frame_PID values that are included in the request. The frame_PIDs are ordered.
startIndex	Integer	0..1	attr	The startIndex sets the index to the first frame to assign a PID.

Table A.57: AssignFrameIdRange

Class	AssignNad			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Schedule entry for an Assign NAD master request.			
Base	ARObject , LinConfigurationEntry , ScheduleTableEntry			
Aggregated by	LinScheduleTable.tableEntry			
Attribute	Type	Mult.	Kind	Note
newNad	Integer	0..1	attr	The newly assigned NAD value.

Table A.58: AssignNad

Class	AsynchronousServerCallPoint			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ServerCall			
Note	An AsynchronousServerCallPoint is used for asynchronous invocation of a ClientServerOperation. IMPORTANT: a ServerCallPoint cannot be used concurrently. Once the client RunnableEntity has made the invocation, the ServerCallPoint cannot be used until the call returns (or an error occurs!) at which point the ServerCallPoint becomes available again.			
Base	ARObject , AbstractAccessPoint , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable , ServerCallPoint			
Aggregated by	AtpClassifier.atpFeature , RunnableEntity.serverCallPoint			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.59: AsynchronousServerCallPoint

Class	AsynchronousServerCallResultPoint			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ServerCall			
Note	If a RunnableEntity owns a AsynchronousServerCallResultPoint it is entitled to get the result of the referenced AsynchronousServerCallPoint. If it is associated with AsynchronousServerCallReturnsEvent, this RTEEvent notifies the completion of the required ClientServerOperation or a timeout. The occurrence of this event can either unblock a WaitPoint or can lead to the invocation of a RunnableEntity.			
Base	ARObject , AbstractAccessPoint , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , RunnableEntity.asynchronousServerCallResultPoint			
Attribute	Type	Mult.	Kind	Note
asynchronousServerCallPoint	AsynchronousServerCallPoint	0..1	ref	The referenced Asynchronous Server Call Point defines the asynchronous server call from which the results are returned.

Table A.60: AsynchronousServerCallResultPoint

Class	AsynchronousServerCallReturnsEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when an asynchronous server call is finished.			
Base	ARObject , AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
eventSource	AsynchronousServerCallResultPoint	0..1	ref	The referenced AsynchronousServerCallResultPoint raises this AsynchronousServerCallReturnsEvent when the asynchronous server call returns.

Table A.61: AsynchronousServerCallReturnsEvent

Class	AtomicSwComponentType (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	An atomic software component is atomic in the sense that it cannot be further decomposed and distributed across multiple ECUs.			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , SwComponentType			
Subclasses	ApplicationSwComponentType , ComplexDeviceDriverSwComponentType , EcuAbstractionSwComponentType , NvBlockSwComponentType , SensorActuatorSwComponentType , ServiceProxySwComponentType , ServiceSwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
internalBehavior	SwcInternalBehavior	0..1	aggr	The SwcInternalBehaviors owned by an AtomicSwComponentType can be located in a different physical file. Therefore the aggregation is <<atpSplittable>>. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=internalBehavior.shortName, internalBehavior.variationPoint.shortLabel, vh.latestBindingTime=preCompileTime
symbolProps	SymbolProps	0..1	aggr	This represents the SymbolProps for the AtomicSwComponentType . Stereotypes: atpSplittable Tags: atp.Splitkey=symbolProps.shortName

Table A.62: AtomicSwComponentType

Class	AtpBlueprintMapping (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::AbstractBlueprintStructure			
Note	This meta-class represents the ability to express a particular mapping between a blueprint and an element derived from this blueprint. Particular mappings are defined by specializations of this meta-class.			
Base	ARObject			
Subclasses	BlueprintMapping			
Aggregated by	BlueprintMappingSet.blueprintMap			
Attribute	Type	Mult.	Kind	Note
atpBlueprint	AtpBlueprint	1	ref	This represents the blueprint. Stereotypes: atpAbstract; atpUriDef Tags: xml.sequenceOffset=50





Class	<i>AtpBlueprintMapping</i> (abstract)			
atpBlueprintedElement	AtpBlueprintable	1	ref	This represents the bluprinted elements which shall be mapped to the blueprint. Stereotypes: atpAbstract Tags: xml.sequenceOffset=60

Table A.63: AtpBlueprintMapping

Class	<i>AtpClassifier</i> (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::AbstractStructure			
Note	A classifier classifies M0 instances according to their features. Or: a classifier is something that has instances - an M1 classifier has M0 instances.			
Base	<i>AObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>AtpStructureElement</i> , <i>AtpType</i>			
Attribute	Type	Mult.	Kind	Note
atpFeature	AtpFeature	*	aggr	This is a feature of the classifier. Stereotypes: atpDerived

Table A.64: AtpClassifier

Class	<i>AtpInstanceRef</i> (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::AbstractStructure			
Note	An M0 instance of a classifier may be represented as a tree rooted at that instance, where under each node come the sub-trees representing the instances which act as features under that node. An instance ref specifies a navigation path from any M0 tree-instance of the base (which is a classifier) to a leaf (which is an instance of the target).			
Base	<i>AObject</i>			
Subclasses	AnyInstanceRef , ApplicationCompositeElementInPortInterfaceInstanceRef , ComponentInCompositionInstanceRef , ComponentInSystemInstanceRef , DataPrototypeInPortInterfaceInstanceRef , DataPrototypeInSystemInstanceRef , InnerDataPrototypeGroupInCompositionInstanceRef , InnerPortGroupInCompositionInstanceRef , InnerRunnableEntityGroupInCompositionInstanceRef , InstanceEventInCompositionInstanceRef , ModeDeclarationGroupPrototypeInSystemInstanceRef , ModeGroupInAtomicSwcInstanceRef , ModelInBswModuleDescriptionInstanceRef , ModelInSwcInstanceRef , OperationArgumentInComponentInstanceRef , OperationInAtomicSwcInstanceRef , OperationInSystemInstanceRef , PModelInSystemInstanceRef , ParameterDataPrototypeInSystemInstanceRef , ParameterInAtomicSWCTypeInstanceRef , PortGroupInSystemInstanceRef , PortInCompositionTypeInstanceRef , RModelInAtomicSwcInstanceRef , RteEventInCompositionInstanceRef , RteEventInEcuInstanceRef , RteEventInSystemInstanceRef , RunnableEntityInCompositionInstanceRef , SwcServiceDependencyInSystemInstanceRef , TriggerInAtomicSwcInstanceRef , TriggerInSystemInstanceRef , VariableAccessInEcuInstanceRef , VariableDataPrototypeInCompositionInstanceRef , VariableDataPrototypeInSystemInstanceRef , VariableInAtomicSWCTypeInstanceRef , VariableInAtomicSwcInstanceRef , VariableInComponentInstanceRef			
Attribute	Type	Mult.	Kind	Note
atpBase	AtpClassifier	1	ref	This is the base from which the navigaion path starts. Stereotypes: atpAbstract; atpDerived
atpContextElement (ordered)	AtpPrototype	*	ref	This is one particular step in the navigation path. Stereotypes: atpAbstract
atpTarget	AtpFeature	1	ref	This is the target of the instance ref. In other words it is the terminal of the navigation path. Stereotypes: atpAbstract

Table A.65: AtpInstanceRef

Class	AtpPrototype (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::AbstractStructure			
Note	A prototype is a typed feature. A prototype in a classifier indicates that instances of that classifier will have a feature, and the structure of that feature is given by the its type. An instance of that type will play the role indicated by the feature in the owning classifier. A feature is not an instance but an indication of an instance-to-be.			
Base	<i>ARObject</i> , <i>AtpFeature</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>DataPrototype</i> , <i>ModeDeclarationGroupPrototype</i> , <i>PortPrototype</i> , <i>RootSwCompositionPrototype</i> , <i>SwComponentPrototype</i>			
Aggregated by	<i>AtpClassifier</i> .atpFeature			
Attribute	Type	Mult.	Kind	Note
atpType	AtpType	1	ref	This is the type of the feature. Stereotypes: atpAbstract

Table A.66: AtpPrototype

Class	AtpStructureElement (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::AbstractStructure			
Note	A structure element is both a classifier and a feature. As a feature, its structure is given by the feature it owns as a classifier.			
Base	<i>ARObject</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>AbstractAccessPoint</i> , <i>AbstractImplementationDataTypeElement</i> , <i>AsynchronousServerCallResultPoint</i> , <i>BswModuleDescription</i> , <i>BulkNvDataDescriptor</i> , <i>ClientServerOperation</i> , <i>DataPrototypeGroup</i> , <i>IdentCaption</i> , <i>InternalBehavior</i> , <i>InternalTriggeringPoint</i> , <i>ModeDeclaration</i> , <i>ModeDeclarationMapping</i> , <i>ModeSwitchPoint</i> , <i>ModeTransition</i> , <i>NvBlockDescriptor</i> , <i>ParameterAccess</i> , <i>PerInstanceMemory</i> , <i>PortGroup</i> , <i>PortPrototypeBlueprint</i> , <i>RTEEvent</i> , <i>RunnableEntity</i> , <i>RunnableEntityGroup</i> , <i>ServerCallPoint</i> , <i>SwConnector</i> , <i>SwcBswMapping</i> , <i>SwcServiceDependency</i> , <i>System</i> , <i>Trigger</i> , <i>VariableAccess</i>			
Aggregated by	<i>AtpClassifier</i> .atpFeature			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.67: AtpStructureElement

Class	AtpType (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::AbstractStructure			
Note	A type is a classifier that may serve to type prototypes. It is a reusable classifier.			
Base	<i>ARObject</i> , <i>AtpClassifier</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>AutosarDataType</i> , <i>ModeDeclarationGroup</i> , <i>ModeDeclarationMappingSet</i> , <i>PortInterface</i> , <i>SwComponentType</i>			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.68: AtpType

Class	AttributeTailoring (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	Tailoring of Attributes			
Base	<i>ARObject</i> , <i>DataFormatElementReference</i> , <i>DataFormatElementScope</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>SpecElementReference</i> , <i>SpecElementScope</i>			





Class	<i>AttributeTailoring</i> (abstract)			
Subclasses	AggregationTailoring , PrimitiveAttributeTailoring , ReferenceTailoring			
Aggregated by	ClassContentConditional.attributeTailoring			
Attribute	Type	Mult.	Kind	Note
multiplicity Restriction	MultiplicityRestrictionWithSeverity	0..1	aggr	Multiplicity restriction of the attribute Tags: xml.sequenceOffset=10
variation Restriction	VariationRestrictionWithSeverity	0..1	aggr	Restrictions on the usage of variant handling. Tags: xml.sequenceOffset=20

Table A.69: AttributeTailoring

Class	«atpMixedString» <i>AttributeValueVariationPoint</i> (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling::AttributeValueVariationPoints			
Note	This class represents the ability to derive the value of the Attribute from a system constant (by Sw SystemconstDependentFormula). It also provides a bindingTime.			
Base	<i>AObject</i> , <i>FormulaExpression</i> , <i>SwSystemconstDependentFormula</i>			
Subclasses	AbstractEnumerationValueVariationPoint , AbstractNumericalVariationPoint , BooleanValueVariationPoint , FloatValueVariationPoint , IntegerValueVariationPoint , PositiveIntegerValueVariationPoint , TimeValueVariationPoint , UnlimitedIntegerValueVariationPoint			
Aggregated by	VariationPointProxy.valueAccess			
Attribute	Type	Mult.	Kind	Note
bindingTime	BindingTimeEnum	0..1	attr	This is the binding time in which the attribute value needs to be bound. If this attribute is missing, the attribute is not a variation point. In particular this means that It needs to be a single value according to the type specified in the pure model. It is an error if it is still a formula. Tags: xml.attribute=true
blueprintValue	String	0..1	attr	This represents a description that documents how the value shall be defined when deriving objects from the blueprint. Tags: xml.attribute=true
sd	String	0..1	attr	This special data is provided to allow synchronization of Attribute value variation points with variant management systems. The usage is subject of agreement between the involved parties. Tags: xml.attribute=true
shortLabel	PrimitivIdentifier	0..1	attr	This allows to identify the variation point. It is also intended to allow RTE support for CompileTime Variation points. Tags: xml.attribute=true

Table A.70: AttributeValueVariationPoint

Class	<i>AutosarDataPrototype</i> (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::DataPrototypes			
Note	Base class for prototypical roles of an AutosarDataType.			
Base	<i>AObject</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>DataPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	ArgumentDataPrototype , ParameterDataPrototype , VariableDataPrototype			





Class	AutosarDataPrototype (abstract)			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
type	AutosarDataType	0..1	tref	This represents the corresponding data type. Stereotypes: isOfType

Table A.71: AutosarDataPrototype

Class	AutosarDataType (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes			
Note	Abstract base class for user defined AUTOSAR data types for software.			
Base	ARElement , ARObject , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	AbstractImplementationDataType , ApplicationDataType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
swDataDef Props	SwDataDefProps	0..1	aggr	The properties of this AutosarDataType. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.72: AutosarDataType

Class	AutosarOperationArgumentInstance			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventOccurrenceExpression			
Note	This class represents a reference to an argument instance. This way it is possible to reference an argument instance in the occurrence expression formula. The argument instance can target to one of the following arguments: <ul style="list-style-type: none"> • a whole argument used in an operation of a PortPrototype with ClientServerInterface • an element inside of a composite argument used in an operation of a PortPrototype with ClientServer Interface 			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TDEventOccurrenceExpression.argument , TimingExtensionResource.timingArgument			
Attribute	Type	Mult.	Kind	Note
operation Argument Instance	DataPrototype	0..1	iref	This is the reference to the instanceRef definition. InstanceRef implemented by: OperationArgumentInComponentInstanceRef

Table A.73: AutosarOperationArgumentInstance

Class	AutosarParameterRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements			
Note	<p>This class represents a reference to a parameter within AUTOSAR which can be one of the following use cases:</p> <p>localParameter:</p> <ul style="list-style-type: none"> • localParameter which is used as whole (e.g. sharedAxis for curve) <p>autosarVariable:</p> <ul style="list-style-type: none"> • a parameter provided via PortPrototype which is used as whole (e.g. parameterAccess) • an element inside of a composite local parameter typed by ApplicationDatatype (e.g. sharedAxis for a curve) • an element inside of a composite parameter provided via Port and typed by ApplicationDatatype (e.g. sharedAxis for a curve) <p>autosarParameterInImplDatatype:</p> <ul style="list-style-type: none"> • an element inside of a composite local parameter typed by ImplementationDatatype • an element inside of a composite parameter provided via PortPrototype and typed by ImplementationDatatype 			
Base	ARObject			
Aggregated by	InstantiationDataDefProps.parameterInstance , ParameterAccess.accessedParameter , RoleBasedDataAssignment.usedParameterElement , SwCalprmRefProxy.arParameter			
Attribute	Type	Mult.	Kind	Note
autosarParameter	DataPrototype	0..1	iref	<p>This instance reference is used if the calibration parameter is either imported via a port or is part of a composite data structure.</p> <p>InstanceRef implemented by: ParameterInAtomicSWCTypeInstanceRef</p>
localParameter	DataPrototype	0..1	ref	<p>In the majority of cases this reference goes to ParameterDataPrototypes rather than VariableDataPrototypes. Pointing the reference to a VariableDataPrototype is limited to special use cases, e.g. if the AutosarParameterRef is used in the context of an SwAxisGrouped.</p> <p>This reference is used if the arParameter is local to the current component.</p> <p>Of course, it would technically also be feasible to use an InstanceRef for this case. However, the InstanceRef would not have a contextElement (because the current instance is the context).</p> <p>Hence, the local instance is a special case which may provide further optimization. Therefore an explicit reference is provided for this case.</p>

Table A.74: AutosarParameterRef

Class	AutosarVariableInstance			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventOccurrenceExpression			
Note	<p>This class represents a reference to a variable instance within AUTOSAR. This way it is possible to reference a variable instance in the occurrence expression formula. The variable instance can target to one of the following variables:</p> <ul style="list-style-type: none"> • a variable provided via a PortPrototype as whole • an element inside of a composite variable provided via a PortPrototype 			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TDEventOccurrenceExpression.variable , TimingExtensionResource.timingVariable			





Class		AutosarVariableInstance		
Attribute	Type	Mult.	Kind	Note
variableInstance	DataPrototype	0..1	iref	This is the reference to the instanceRef definition. InstanceRef implemented by: VariableInComponent InstanceRef

Table A.75: AutosarVariableInstance

Class		AutosarVariableRef		
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements			
Note	<p>This class represents a reference to a variable within AUTOSAR which can be one of the following use cases:</p> <p>localVariable:</p> <ul style="list-style-type: none"> localVariable which is used as whole (e.g. InterRunnableVariable, inputValue for curve) <p>autosarVariable:</p> <ul style="list-style-type: none"> a variable provided via Port which is used as whole (e.g. dataAccesspoints) an element inside of a composite local variable typed by ApplicationDatatype (e.g. inputValue for a curve) an element inside of a composite variable provided via Port and typed by ApplicationDatatype (e.g. inputValue for a curve) <p>autosarVariableInImplDatatype:</p> <ul style="list-style-type: none"> an element inside of a composite local variable typed by ImplementationDatatype (e.g. nvramData mapping) an element inside of a composite variable provided via Port and typed by ImplementationDatatype (e.g. inputValue for a curve) 			
Base	<i>ARObject</i>			
Aggregated by	InstantiationDataDefProps.variableInstance , NvBlockDataMapping.nvRamBlockElement , NvBlockDataMapping.readNvData , NvBlockDataMapping.writtenNvData , NvBlockDataMapping.writtenReadNvData , RoleBasedDataAssignment.usedDataElement , SwVariableRefProxy.autosarVariable , VariableAccess.accessedVariable			
Attribute	Type	Mult.	Kind	Note
autosarVariable	DataPrototype	0..1	iref	This references a variable which is provided by a port and/or which is part of a CompositeDataType. InstanceRef implemented by: VariableInAtomicSWCTypeInstanceRef
autosarVariableInImplDatatype	ArVariableInImplementationDataInstanceRef	0..1	aggr	This is used if the target variable is inside of variableDataPrototype typed by an ImplementationDataType.
localVariable	VariableDataPrototype	0..1	ref	This reference is used if the variable is local to the current component. It would also be possible to use the instance reference here. Such an instance ref would not have a contextElement, since the current instance is the context. But the local instance is a special case which may provide further optimization. Therefore an explicit reference is provided for this case.

Table A.76: AutosarVariableRef

Class	BaseType (abstract)			
Package	M2::MSR::AsamHdo::BaseTypes			
Note	This abstract meta-class represents the ability to specify a platform dependent base type.			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	SwBaseType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
baseType Definition	BaseTypeDefinition	1	aggr	This is the actual definition of the base type. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false

Table A.77: BaseType

Class	BaseTypeDirectDefinition			
Package	M2::MSR::AsamHdo::BaseTypes			
Note	This BaseType is defined directly (as opposite to a derived BaseType)			
Base	ARObject, BaseTypeDefinition			
Aggregated by	BaseType.baseTypeDefinition			
Attribute	Type	Mult.	Kind	Note
baseType Encoding	BaseTypeEncodingString	0..1	attr	This specifies, how an object of the current BaseType is encoded, e.g. in an ECU within a message sequence. Tags: xml.sequenceOffset=90
baseTypeSize	PositiveInteger	0..1	attr	Describes the length of the data type specified in the container in bits. Tags: xml.sequenceOffset=70
byteOrder	ByteOrderEnum	0..1	attr	This attribute specifies the byte order of the base type. Tags: xml.sequenceOffset=110
memAlignment	PositiveInteger	0..1	attr	This attribute describes the alignment of the memory object in bits. E.g. "8" specifies, that the object in question is aligned to a byte while "32" specifies that it is aligned four byte. If the value is set to "0" the meaning shall be interpreted as "unspecified". Tags: xml.sequenceOffset=100
native Declaration	NativeDeclarationString	0..1	attr	This attribute describes the declaration of such a base type in the native programming language, primarily in the Programming language C. This can then be used by a code generator to include the necessary declarations into a header file. For example BaseType with shortName: "MyUnsignedInt" native Declaration: "unsigned short" Results in typedef unsigned short MyUnsignedInt; If the attribute is not defined the referring Implementation DataTypes will not be generated as a typedef by RTE. If a nativeDeclaration type is given it shall fulfill the characteristic given by basetypeEncoding and baseType Size.





Class	BaseTypeDirectDefinition			
				This is required to ensure the consistent handling and interpretation by software components, RTE, COM and MCM systems. △ Tags: xml.sequenceOffset=120

Table A.78: BaseTypeDirectDefinition

Class	Baseline			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint			
Note	Specification of the baseline of the AUTOSAR standard this Data Exchange Point relates to. The baseline is specified by listing the AUTOSAR products and their revisions. Custom defined functionality and deviations to the standard can be provided as well. All references to specification elements in this Data Exchange Point refer to specification elements that are part of this specification baseline.			
Base	ARObject			
Aggregated by	DataExchangePoint.referencedBaseline			
Attribute	Type	Mult.	Kind	Note
customSdgDef	SdgDef	*	ref	Reference to custom SdgDefs that extend the data format of this baseline, Tags: xml.sequenceOffset=30
custom Specification	Documentation	*	ref	Reference to custom specifications that extend this baseline, Tags: xml.sequenceOffset=20
standard Revision	String	*	attr	Specifies a combination of revisions of AUTOSAR standards that are used as the specification baseline of this Data Exchange Point. All standard specification elements that are referenced by this Profile of Data Exchange Point have to be part of specifications that belong to the defined AUTOSAR standards. Tags: xml.sequenceOffset=10

Table A.79: Baseline

Class	BinaryManifestAddressableObject (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class acts as an abstract base class for addressable objects in the context of the binary manifest of a CP software cluster.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	BinaryManifestItem, BinaryManifestMetaDataField			
Attribute	Type	Mult.	Kind	Note
address	Address	0..1	attr	This attribute specifies the address of the enclosing addressable object.
symbol	SymbolString	0..1	attr	This attribute specifies the symbol of the addressable object.

Table A.80: BinaryManifestAddressableObject

Class	BinaryManifestItem			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class represents the ability to describe a specific handle or auxiliary field in the context of binary manifest resource.			
Base	ARObject, BinaryManifestAddressableObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BinaryManifestItem.auxiliaryField, BinaryManifestResource.item			
Attribute	Type	Mult.	Kind	Note
auxiliaryField	BinaryManifestItem	*	aggr	This aggregation is used to define structured Binary ManifestItems. Tags: xml.sequenceOffset=20
defaultValue	BinaryManifestItem Value	0..1	aggr	This aggregation represents the definition of a default value for a binary manifest handle or an auxiliaryField. This value shall be taken if no connection for this resource is possible. Tags: xml.sequenceOffset=10
isUnused	Boolean	0..1	attr	If true, the handle or auxiliary field in the context of binary manifest resource relates to an optional BinaryManifest ItemDefinition and is not used.
value	BinaryManifestItem Value	0..1	aggr	This aggregation represents the definition of a value for a binary manifest handle or an auxiliaryField. This value shall be taken to establish a connection.

Table A.81: BinaryManifestItem

Class	BinaryManifestItemDefinition			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class provides the ability to define the handle definition or an auxiliary field of a binary manifest resource.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BinaryManifestItemDefinition.auxiliaryFieldDefinition, BinaryManifestResourceDefinition.itemDefinition			
Attribute	Type	Mult.	Kind	Note
auxiliaryField Definition	BinaryManifestItem Definition	*	aggr	This aggregation is used to define structured Binary ManifestItemDefinitions.
isOptional	Boolean	0..1	attr	If true, the handle definition or auxiliary field of a binary manifest resource is optional and may not be used in all BinaryManifestResources referring to this BinaryManifest ResourceDefinition.
size	PositiveInteger	0..1	attr	This attribute provides the ability to specify the size of the enclosing BinaryManifestResourceDefinition.

Table A.82: BinaryManifestItemDefinition

Class	BinaryManifestItemNumericalValue			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class has the ability to provide a numerical value for a binary manifest item.			
Base	ARObject, BinaryManifestItemValue			
Aggregated by	BinaryManifestItem.defaultValue, BinaryManifestItem.value			
Attribute	Type	Mult.	Kind	Note
value	Numerical	0..1	attr	This attribute specifies the actual numerical value to be used in the binary manifest handle.

Table A.83: BinaryManifestItemNumericalValue

Class	BinaryManifestItemPointerValue			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class has the ability to provide a value for a pointer in the context of a binary manifest item.			
Base	<i>ARObject</i> , <i>BinaryManifestItemValue</i>			
Aggregated by	BinaryManifestItem.defaultValue , BinaryManifestItem.value			
Attribute	Type	Mult.	Kind	Note
address	Address	0..1	attr	This attribute represents the address value of the enclosing pointer value.
symbol	SymbolString	0..1	attr	This attribute represents the symbol associated with the binary manifest handle.

Table A.84: BinaryManifestItemPointerValue

Class	BinaryManifestMetaDataField			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class provides the ability to define a meta-data field for the binary manifest descriptor.			
Base	<i>ARObject</i> , <i>BinaryManifestAddressableObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	CpSoftwareClusterBinaryManifestDescriptor metaDataField			
Attribute	Type	Mult.	Kind	Note
size	PositiveInteger	0..1	attr	The value of this attribute represents the size of the meta-data field in bytes.
value	VerbatimString	0..1	attr	This attribute specifies the value of the meta-data field.

Table A.85: BinaryManifestMetaDataField

Class	BinaryManifestProvideResource			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class represents a provided resource in the binary manifest.			
Base	<i>ARObject</i> , <i>BinaryManifestResource</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	CpSoftwareClusterBinaryManifestDescriptor provideResource			
Attribute	Type	Mult.	Kind	Note
numberOfNotifierSets	PositiveInteger	0..1	attr	This attribute provides an upper limit for the number of notifiers for this resource.
supportsMultipleNotifierSets	Boolean	0..1	attr	This attribute indicates whether the enclosing BinaryManifestResource supports multiple notifiers sets.

Table A.86: BinaryManifestProvideResource

Class	BinaryManifestRequireResource			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class represents a required resource in the binary manifest.			
Base	<i>ARObject</i> , <i>BinaryManifestResource</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	CpSoftwareClusterBinaryManifestDescriptor requireResource			
Attribute	Type	Mult.	Kind	Note
connectionIsMandatory	Boolean	0..1	attr	This attribute indicates whether the connection of the enclosing BinaryManifestResource is mandatory.

Table A.87: BinaryManifestRequireResource

Class	BinaryManifestResource (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class acts as an abstract base class for specializations.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	BinaryManifestProvideResource , BinaryManifestRequireResource			
Attribute	Type	Mult.	Kind	Note
globalResourceId	PositiveInteger	0..1	attr	A unique identifiers per resource used for the connection process. The identifier is required to be unique in the scope of a single machine. If software clusters are designed to be reused on multiple machines the uniqueness requirements applies for all the intended machines.
item (ordered)	BinaryManifestItem	*	aggr	This aggregation represents the collection of binary manifest handles owned by the enclosing binary manifest resource.
resource	CpSoftwareClusterResource	0..1	ref	This reference identifies the CpSoftwareClusterResource (on design level) that corresponds to the BinaryManifestResource (on integration level).
resourceDefinition	BinaryManifestResourceDefinition	0..1	ref	this reference identifies the definition of the BinaryManifestResource. The definition provides configuration information that is shared among all BinaryManifestResources that refer to the BinaryManifestResourceDefinition.
resourceGuardValue	String	0..1	attr	This attribute specifies the guard value of the enclosing binary manifest resource.

Table A.88: BinaryManifestResource

Class	BinaryManifestResourceDefinition			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	This meta-class represents the ability to specify a resource definition that provides information that can be shared by all resources that refer to the respective resource definition.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CpSoftwareClusterBinaryManifestDescriptor.resourceDefinition			
Attribute	Type	Mult.	Kind	Note
itemDefinition (ordered)	BinaryManifestItemDefinition	*	aggr	This aggregation specifies the collection of handle definitions in the context of the enclosing binary manifest resource definitions.

Table A.89: BinaryManifestResourceDefinition

Class	BlueprintMapping			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::BlueprintDedicated::GenericBlueprint			
Note	This meta-class represents the ability to map two an object and its blueprint.			
Base	ARObject, AtpBlueprintMapping			
Aggregated by	BlueprintMappingSet.blueprintMap			
Attribute	Type	Mult.	Kind	Note
blueprint	AtpBlueprint	1	ref	This represents the mapped blueprint.
derivedObject	AtpBlueprintable	1	ref	This represents the object which was derived from the blueprint.

Table A.90: BlueprintMapping

Class	BlueprintPolicy (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::AbstractBlueprintStructure			
Note	This meta-class represents the ability to indicate whether blueprintable elements will be modifiable or not modifiable.			
Base	ARObject			
Subclasses	BlueprintPolicyModifiable, BlueprintPolicyNotModifiable			
Aggregated by	AtpBlueprint.blueprintPolicy			
Attribute	Type	Mult.	Kind	Note
attributeName	String	1	attr	This identifies the related attribute of a BlueprintPolicy. For navigation over the model a subset of xpath expressions is used.

Table A.91: BlueprintPolicy

Class	BlueprintPolicyNotModifiable			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::AbstractBlueprintStructure			
Note	The class represents that the related attribute is not modifiable during the blueprinting.			
Base	ARObject, BlueprintPolicy			
Aggregated by	AtpBlueprint.blueprintPolicy			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.92: BlueprintPolicyNotModifiable

Class	BswAsynchronousServerCallPoint			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Represents an asynchronous procedure call point via the BSW Scheduler.			
Base	ARObject, BswModuleCallPoint , Referrable			
Aggregated by	BswModuleEntity.callPoint			
Attribute	Type	Mult.	Kind	Note
calledEntry	BswModuleClientServerEntry	0..1	ref	The entry to be called.

Table A.93: BswAsynchronousServerCallPoint

Class	BswAsynchronousServerCallResultPoint			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	The callback point for an BswAsynchronousServerCallPoint i.e. the point at which the result can be retrieved from the BSW Scheduler.			
Base	ARObject, BswModuleCallPoint , Referrable			
Aggregated by	BswModuleEntity.callPoint			
Attribute	Type	Mult.	Kind	Note
asynchronousServerCallPoint	BswAsynchronousServerCallPoint	0..1	ref	The call point invoking the call to which the result belongs.

Table A.94: BswAsynchronousServerCallResultPoint

Class	BswAsynchronousServerCallReturnsEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	This is the "callback" event for asynchronous Client-Server-Communication via the BSW Scheduler which is thrown after completion of the asynchronous Client-Server call. Its eventSource specifies the call point to be used for retrieving the result.			
Base	ARObject, AbstractEvent, BswEvent, BswScheduleEvent, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
eventSource	BswAsynchronousServerCallResultPoint	0..1	ref	The call point to be used for retrieving the result.

Table A.95: BswAsynchronousServerCallReturnsEvent

Enumeration	BswCallType
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswInterfaces
Note	Denotes the mechanism by which the entry into the Bsw module shall be called.
Aggregated by	BswModuleEntry.callType
Literal	Description
callback	Callback (i.e. the caller specifies the signature) Tags: atp.EnumerationLiteralIndex=0
callout	Callout - provide defined means to extend the functionality of an existing module. In this case caller specifies the signature. Tags: atp.EnumerationLiteralIndex=4
interrupt	Interrupt routine Tags: atp.EnumerationLiteralIndex=1
regular	Regular API call Tags: atp.EnumerationLiteralIndex=2
scheduled	Called by the scheduler Tags: atp.EnumerationLiteralIndex=3

Table A.96: BswCallType

Class	BswCalledEntity			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	BSW module entity which is designed to be called from another BSW module or cluster.			
Base	ARObject, BswModuleEntity, ExecutableEntity, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BswInternalBehavior.entity			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.97: BswCalledEntity

Class	BswCompositionTiming			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingExtensions			
Note	<p>A model element used to define timing descriptions and constraints for a set of BswImplementations representing a BSW composition. A constraint defined at this level holds true for all referenced Bsw Implementations. Note, that multiple implementations of the same basic software module could be involved.</p> <p>TimingDescriptions aggregated by BswCompositionTiming are restricted to event chains referring to events which are derived from the class TDEventBswInternalBehavior and TDEventBsw.</p> <p>Tags: atp.recommendedPackage=TimingExtensions</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, TimingExtension			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
implementation	BswImplementation	*	ref	This defines the scope of a BswCompositionTiming. All corresponding timing descriptions and constraints shall be defined within this scope.

Table A.98: BswCompositionTiming

Class	BswDataReceivedEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	This event is thrown on reception of the referenced data via Sender-Receiver-Communication over the BSW Scheduler.			
Base	ARObject, AbstractEvent, BswEvent, BswScheduleEvent, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
data	VariableDataPrototype	0..1	ref	The received data.

Table A.99: BswDataReceivedEvent

Class	BswDataReceptionPolicy (abstract)			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Specifies the reception policy for the referred data in sender-receiver communication over the BSW Scheduler. To be used for inter-partition and/or inter-core communication.			
Base	ARObject, BswApiOptions			
Subclasses	BswQueuedDataReceptionPolicy			
Aggregated by	BswInternalBehavior.receptionPolicy			
Attribute	Type	Mult.	Kind	Note
receivedData	VariableDataPrototype	0..1	ref	The data received over the BSW Scheduler using this policy.

Table A.100: BswDataReceptionPolicy

Class	BswDirectCallPoint			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	<p>Represents a concrete point in the code from where a BswModuleEntry is called directly, i.e. not via the BSW Scheduler.</p> <p>This information can be used to analyze call tree and resource locking scenarios. It is not needed to configure the BSW Scheduler.</p>			





Class	BswDirectCallPoint			
Base	<i>ARObject</i> , <i>BswModuleCallPoint</i> , <i>Referrable</i>			
Aggregated by	<i>BswModuleEntity.callPoint</i>			
Attribute	Type	Mult.	Kind	Note
calledEntry	<i>BswModuleEntry</i>	0..1	ref	The BswModuleEntry called at this point.
calledFrom WithinExclusive Area	ExclusiveAreaNesting Order	0..1	ref	This indicates that the call point is located at the deepest level inside one or more ExclusiveAreas that are nested in the given order.

Table A.101: BswDirectCallPoint

Class	BswDistinguishedPartition			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Each instance of this meta-class represents an abstract partition in which context the code of the enclosing BswModuleBehavior can be executed. The intended use case is to distinguish between several partitions in order to implement different behavior per partition, for example to behave either as a master or satellite in a multicore ECU with shared BSW code.			
Base	<i>ARObject</i> , <i>Referrable</i>			
Aggregated by	<i>BswInternalBehavior.distinguishedPartition</i>			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.102: BswDistinguishedPartition

Class	BswEntryRelationship			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswInterfaces			
Note	Describes a relationship between two BswModuleEntrys and the type of relationship.			
Base	<i>ARObject</i>			
Aggregated by	<i>BswEntryRelationshipSet.bswEntryRelationship</i>			
Attribute	Type	Mult.	Kind	Note
bswEntry Relationship Type	BswEntryRelationship Enum	0..1	attr	Denotes the type of the relationship. Tags: xml.sequenceOffset=5
from	<i>BswModuleEntry</i>	0..1	ref	Type of relationship that refers to the abstract BswModule Entry. Please notice that in this case the bswEntry RelationshipType shall be set to drivenFrom.
to	<i>BswModuleEntry</i>	0..1	ref	Type of relationship that refers to the concrete Bsw ModuleEntry

Table A.103: BswEntryRelationship

Class	BswEntryRelationshipSet			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswInterfaces			
Note	Describes a set of relationships between two BswModuleEntrys. Tags: atp.recommendedPackage=BswEntryRelationshipSets			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>CollectableElement</i> , <i>Identifiable</i> , <i>Multilanguage Referrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			





Class	BswEntryRelationshipSet			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
bswEntryRelationship	BswEntryRelationship	*	aggr	Relationship between two BswModuleEntrys.

Table A.104: BswEntryRelationshipSet

Class	BswEvent (abstract)			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Base class of various kinds of events which are used to trigger a BswModuleEntity of this BSW module or cluster. The event is local to the BSW module or cluster. The short name of the meta-class instance is intended as an input to configure the required API of the BSW Scheduler.			
Base	ARObject , AbstractEvent , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	BswInterruptEvent , BswOperationInvokedEvent , BswScheduleEvent			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
contextLimitation	BswDistinguishedPartition	*	ref	The existence of this reference indicates that the usage of the event is limited to the context of the referred BswDistinguishedPartitions.
disabledInMode	ModeDeclaration	*	iref	The modes, in which this event is disabled. Stereotypes: atpSplitable Tags: atp.Splitkey=disabledInMode.contextModeDeclarationGroup, disabledInMode.targetMode InstanceRef implemented by: ModeInBswModuleDescriptionInstanceRef
startsOnEvent	BswModuleEntity	0..1	ref	The entity which is started by the event.

Table A.105: BswEvent

Class	BswExclusiveAreaPolicy			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	The ExclusiveArea for which the BSW Scheduler using this policy.			
Base	ARObject , BswApiOptions			
Aggregated by	BswInternalBehavior.exclusiveAreaPolicy			
Attribute	Type	Mult.	Kind	Note
apiPrinciple	ApiPrincipleEnum	0..1	attr	Specifies for this ExclusiveArea if either one common set of Enter and Exit APIs for the whole BSW module is requested from the SchM or if the set of Enter and Exit APIs is expected per BswModuleEntity. The default value is "common".
exclusiveArea	ExclusiveArea	0..1	ref	The ExclusiveArea for which the BSW Scheduler using this policy.

Table A.106: BswExclusiveAreaPolicy

Enumeration	BswExecutionContext
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswInterfaces
Note	Specifies the execution context required or guaranteed for the call associated with this service.
Aggregated by	BswModuleEntry.executionContext
Literal	Description
hook	Context of an OS "hook" routine always Tags: atp.EnumerationLiteralIndex=0
interruptCat1	CAT1 interrupt context always Tags: atp.EnumerationLiteralIndex=1
interruptCat2	CAT2 interrupt context always Tags: atp.EnumerationLiteralIndex=2
task	Task context always Tags: atp.EnumerationLiteralIndex=3
unspecified	The execution context is not specified by the API Tags: atp.EnumerationLiteralIndex=4

Table A.107: BswExecutionContext

Class	BswExternalTriggerOccurredEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	A BswEvent resulting from a trigger released by another module or cluster.			
Base	ARObject , AbstractEvent , BswEvent , BswScheduleEvent , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
trigger	Trigger	0..1	ref	The trigger associated with this event. The trigger is external to this module.

Table A.108: BswExternalTriggerOccurredEvent

Class	BswImplementation			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswImplementation			
Note	Contains the implementation specific information in addition to the generic specification (BswModule Description and BswBehavior). It is possible to have several different BswImplementations referring to the same BswBehavior. Tags: atp.recommendedPackage=BswImplementations			
Base	ARElement , ARObject , CollectableElement , Identifiable , Implementation , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
arRelease Version	RevisionLabelString	0..1	attr	Version of the AUTOSAR Release on which this implementation is based. The numbering contains three levels (major, minor, revision) which are defined by AUTOSAR.





Class	BswImplementation			
behavior	BswInternalBehavior	0..1	ref	The behavior of this implementation. This relation is made as an association because <ul style="list-style-type: none"> it follows the pattern of the SWCT since ARElement cannot be split, but we want supply the implementation later, the BswImplementation is not aggregated in BswBehavior
preconfigured Configuration	EcucModule ConfigurationValues	*	ref	Reference to the set of preconfigured (i.e. fixed) configuration values for this BswImplementation. If the BswImplementation represents a cluster of several modules, more than one EcucModuleConfigurationValues element can be referred (at most one per module), otherwise at most one such element can be referred. Tags: xml.roleWrapperElement=true
recommended Configuration	EcucModule ConfigurationValues	*	ref	Reference to one or more sets of recommended configuration values for this module or module cluster.
vendorApiInfix	Identifier	0..1	attr	In driver modules which can be instantiated several times on a single ECU, SRS_BSW_00347 requires that the names of files, APIs, published parameters and memory allocation keywords are extended by the vendorId and a vendor specific name. This parameter is used to specify the vendor specific name. In total, the implementation specific API name is generated as follows: <Module Name>_<vendorId>_<vendorApiInfix>_<API name from SWS>. E.g. assuming that the vendorId of the implementer is 123 and the implementer chose a vendorApiInfix of "v11r456" an API name Can_Write defined in the SWS will translate to Can_123_v11r456_Write. This attribute is mandatory for all modules with upper multiplicity > 1. It shall not be used for modules with upper multiplicity =1. See also SWS_BSW_00102.
vendorSpecific ModuleDef	EcucModuleDef	*	ref	Reference to <ul style="list-style-type: none"> the vendor specific EcucModuleDef used in this Bsw Implementation if it represents a single module several EcucModuleDefs used in this Bsw Implementation if it represents a cluster of modules one or no EcucModuleDefs used in this Bsw Implementation if it represents a library Tags: xml.roleWrapperElement=true

Table A.109: BswImplementation

Class	BswInternalBehavior			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Specifies the behavior of a BSW module or a BSW cluster w.r.t. the code entities visible by the BSW Scheduler. It is possible to have several different BswInternalBehaviors referring to the same BswModule Description.			
Base	AObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , InternalBehavior , Multilanguage Referrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , BswModuleDescription.internalBehavior			
Attribute	Type	Mult.	Kind	Note





Class	BswInternalBehavior			
arTypedPerInstanceMemory	VariableDataPrototype	*	aggr	<p>Defines an AUTOSAR typed memory-block that needs to be available for each instance of the Basic Software Module. The aggregation of arTypedPerInstanceMemory is subject to variability with the purpose to support variability in the Basic Software Module's implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=arTypedPerInstanceMemory.shortName, arTypedPerInstanceMemory.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
bswPerInstanceMemoryPolicy	BswPerInstanceMemoryPolicy	*	aggr	<p>Policy for a arTypedPerInstanceMemory The policy selects the options of the Schedule Manager API generation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=bswPerInstanceMemoryPolicy, bswPerInstanceMemoryPolicy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
clientPolicy	BswClientPolicy	*	aggr	<p>Policy for a requiredClientServerEntry. The policy selects the options of the Schedule Manager API generation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=clientPolicy, clientPolicy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
distinguishedPartition	BswDistinguishedPartition	*	aggr	<p>Indicates an abstract partition context in which the enclosing BswModuleEntity can be executed.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=distinguishedPartition.shortName, distinguishedPartition.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=60</p>
entity	BswModuleEntity	*	aggr	<p>A code entity for which the behavior is described</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=entity.shortName, entity.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=5</p>
event	BswEvent	*	aggr	<p>An event required by this module behavior.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=event.shortName, event.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=10</p>





Class	BswInternalBehavior			
exclusiveArea Policy	BswExclusiveArea Policy	*	aggr	<p>Policy for an ExclusiveArea in this BswInternalBehavior. The policy selects the options of the Schedule Manager API generation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=exclusiveAreaPolicy, exclusiveArea Policy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
includedData TypeSet	IncludedDataTypeSet	*	aggr	<p>The includedDataTypeSet is used by a basic software module for its implementation.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=includedDataTypeSet</p>
includedMode Declaration GroupSet	IncludedMode DeclarationGroupSet	*	aggr	<p>This aggregation represents the included Mode DeclarationGroups</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=includedModeDeclarationGroupSet</p>
internal TriggeringPoint	BswInternalTriggering Point	*	aggr	<p>An internal triggering point.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=internalTriggeringPoint.shortName, internal TriggeringPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=2</p>
internal TriggeringPoint Policy	BswInternalTriggering PointPolicy	*	aggr	<p>Policy for an internalTriggeringPoint in this BswInternal Behavior.. The policy selects the options of the Schedule Manager API generation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=internalTriggeringPointPolicy, internal TriggeringPointPolicy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
modeReceiver Policy	BswModeReceiver Policy	*	aggr	<p>Implementation policy for the reception of mode switches.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=modeReceiverPolicy, modeReceiver Policy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=25</p>
modeSender Policy	BswModeSenderPolicy	*	aggr	<p>Implementation policy for providing a mode group.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=modeSenderPolicy, modeSender Policy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=20</p>
parameterPolicy	BswParameterPolicy	*	aggr	<p>Policy for a perInstanceParameter in this BswInternal Behavior. The policy selects the options of the Schedule Manager API generation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=parameterPolicy, parameterPolicy.variation Point.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	BswInternalBehavior			
perInstanceParameter	ParameterData Prototype	*	aggr	<p>Describes a read only memory object containing characteristic value(s) needed by this BswInternal Behavior. The role name perInstanceParameter is chosen in analogy to the similar role in the context of SwcInternal Behavior.</p> <p>In contrast to constantMemory, this object is not allocated locally by the module's code, but by the BSW Scheduler and it is accessed from the BSW module via the BSW Scheduler API. The main use case is the support of software emulation of calibration data.</p> <p>The aggregation is subject to variability with the purpose to support implementation variants.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=perInstanceParameter.shortName, perInstanceParameter.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=45</p>
receptionPolicy	BswDataReception Policy	*	aggr	<p>Data reception policy for inter-partition and/or inter-core communication.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=receptionPolicy, receptionPolicy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=55</p>
releasedTriggerPolicy	BswReleasedTrigger Policy	*	aggr	<p>Policy for a releasedTrigger. The policy selects the options of the Schedule Manager API generation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=releasedTriggerPolicy, releasedTriggerPolicy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
schedulerNamePrefix	BswSchedulerName Prefix	*	aggr	<p>Optional definition of one or more prefixes to be used for the BswScheduler.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=schedulerNamePrefix.shortName, schedulerNamePrefix.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=50</p>
sendPolicy	BswDataSendPolicy	*	aggr	<p>Policy for a providedData. The policy selects the options of the Schedule Manager API generation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=sendPolicy, sendPolicy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	BswInternalBehavior			
service Dependency	BswService Dependency	*	aggr	<p>Defines the requirements on AUTOSAR Services for a particular item.</p> <p>The aggregation is subject to variability with the purpose to support the conditional existence of ServiceNeeds.</p> <p>The aggregation is splitable in order to support that ServiceNeeds might be provided in later development steps.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=serviceDependency.ident.shortName, serviceDependency.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=40</p>
triggerDirect Implementation	BswTriggerDirect Implementation	*	aggr	<p>Specifies a trigger to be directly implemented via OS calls.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=triggerDirectImplementation, triggerDirectImplementation.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=15</p>
variationPoint Proxy	VariationPointProxy	*	aggr	<p>Proxy of a variation points in the C/C++ implementation.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=variationPointProxy.shortName</p>

Table A.110: BswInternalBehavior

Class	BswInternalTriggerOccurredEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	A BswEvent, which can happen sporadically. The event is activated by explicit calls from the module to the BSW Scheduler. The main purpose for such an event is to cause a context switch, e.g. from an ISR context into a task context. Activation and switching are handled within the same module or cluster only.			
Base	ARObject , AbstractEvent , BswEvent , BswScheduleEvent , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
eventSource	BswInternalTriggering Point	0..1	ref	The activation point is the source of this event.

Table A.111: BswInternalTriggerOccurredEvent

Class	BswInternalTriggeringPoint			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Represents the activation point for one or more BswInternalTriggerOccurredEvents.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	BswInternalBehavior.internalTriggeringPoint			
Attribute	Type	Mult.	Kind	Note
swImplPolicy	SwImplPolicyEnum	0..1	attr	This attribute, when set to value queued, specifies a queued processing of the internal trigger event.

Table A.112: BswInternalTriggeringPoint

Enumeration	BswInterruptCategory
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior
Note	Category of the interrupt service
Aggregated by	BswInterruptEntity.interruptCategory
Literal	Description
cat1	Cat1 interrupt routines are not controlled by the OS and are only allowed to make a very limited selection of OS calls to enable and disable all interrupts. The BswInterruptEntity is implemented by the interrupt service routine, which is directly called from the interrupt vector (not via the OS). Tags: atp.EnumerationLiteralIndex=0
cat2	Cat2 interrupt routines are controlled by the OS and they are allowed to make OS calls. The Bsw InterruptEntity is implemented by the interrupt handler, which is called from the OS. Tags: atp.EnumerationLiteralIndex=1

Table A.113: BswInterruptCategory

Class	BswInterruptEntity			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	BSW module entity, which is designed to be triggered by an interrupt.			
Base	ARObject , BswModuleEntity , ExecutableEntity , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	BswInternalBehavior.entity			
Attribute	Type	Mult.	Kind	Note
interruptCategory	BswInterruptCategory	0..1	attr	Category of the interrupt
interruptSource	String	0..1	attr	Allows a textual documentation of the intended interrupt source.

Table A.114: BswInterruptEntity

Class	BswInterruptEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	This meta-class represents an event triggered by an interrupt.			
Base	ARObject , AbstractEvent , BswEvent , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.115: BswInterruptEvent

Class	BswMgrNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs on the configuration of the Basic Software Manager for one "user".			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.116: BswMgrNeeds

Class	BswModeManagerErrorEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	This represents the ability to react on errors occurring during mode handling.			
Base	<i>ARObject</i> , AbstractEvent , BswEvent , BswScheduleEvent , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
modeGroup	ModeDeclarationGroup Prototype	0..1	ref	This represents the ModeDeclarationGroupPrototype for which the error behavior of the mode manager applies.

Table A.117: BswModeManagerErrorEvent

Class	BswModeReceiverPolicy			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Specifies the details for the reception of a mode switch for the referred mode group.			
Base	<i>ARObject</i>			
Aggregated by	BswInternalBehavior.modeReceiverPolicy			
Attribute	Type	Mult.	Kind	Note
enhancedMode Api	Boolean	0..1	attr	This controls the creation of the enhanced mode API that returns information about the previous mode and the next mode. If set to TRUE the enhanced mode API is supposed to be generated. For more details please refer to the SWS_RTE.
requiredMode Group	ModeDeclarationGroup Prototype	0..1	ref	The required mode group for which the policy is specified.
supports Asynchronous ModeSwitch	Boolean	0..1	attr	Specifies whether the module can handle the reception of an asynchronous mode switch (true) or not (false).

Table A.118: BswModeReceiverPolicy

Class	BswModeSenderPolicy			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Specifies the details for the sending of a mode switch for the referred mode group.			
Base	<i>ARObject</i>			
Aggregated by	BswInternalBehavior.modeSenderPolicy			
Attribute	Type	Mult.	Kind	Note
ackRequest	BswModeSwitchAck Request	0..1	aggr	Request for acknowledgement
enhancedMode Api	Boolean	0..1	attr	This controls the creation of the enhanced mode API that returns information about the previous mode and the next mode. If set to TRUE the enhanced mode API is supposed to be generated. For more details please refer to the SWS_RTE.
providedMode Group	ModeDeclarationGroup Prototype	0..1	ref	The provided mode group for which the policy is specified.
queueLength	PositiveInteger	0..1	attr	Length of call queue on the sender side. The queue is implemented by the RTE resp.BswScheduler. The value shall be greater or equal to 0. Setting the value of queue Length to 0 implies non-queued communication.

Table A.119: BswModeSenderPolicy

Class	BswModeSwitchAckRequest			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Requests acknowledgements that a mode switch has been processed successfully			
Base	ARObject			
Aggregated by	BswModeSenderPolicy.ackRequest			
Attribute	Type	Mult.	Kind	Note
timeout	TimeValue	0..1	attr	Number of seconds before an error is reported.

Table A.120: BswModeSwitchAckRequest

Class	BswModeSwitchEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	A BswEvent resulting from a mode switch.			
Base	ARObject, AbstractEvent, BswEvent, BswScheduleEvent, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
activation	ModeActivationKind	0..1	attr	Kind of activation w.r.t. to the referred mode.
mode (ordered)	ModeDeclaration	0..2	iref	Reference to one or two Modes that initiate the Mode Switch Event. InstanceRef implemented by: ModeInBswModule DescriptionInstanceRef

Table A.121: BswModeSwitchEvent

Class	BswModeSwitchedAckEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	The event is raised after a switch of the referenced mode group has been acknowledged or an error occurs. The referenced mode group shall be provided by this module.			
Base	ARObject, AbstractEvent, BswEvent, BswScheduleEvent, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
modeGroup	ModeDeclarationGroup Prototype	0..1	ref	A mode group provided by this module. The acknowledgement of a switch of this group raises this event.

Table A.122: BswModeSwitchedAckEvent

Class	BswModuleCallPoint (abstract)			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Represents a point at which a BswModuleEntity handles a procedure call into a BswModuleEntry, either directly or via the BSW Scheduler.			
Base	ARObject, Referrable			
Subclasses	BswAsynchronousServerCallPoint, BswAsynchronousServerCallResultPoint, BswDirectCallPoint, BswSynchronousServerCallPoint			
Aggregated by	BswModuleEntity.callPoint			
Attribute	Type	Mult.	Kind	Note





Class	BswModuleCallPoint (abstract)			
context Limitation	BswDistinguishedPartition	*	ref	The existence of this reference indicates that the call point is used only in the context of the referred Bsw DistinguishedPartitions.

Table A.123: BswModuleCallPoint

Class	BswModuleClientServerEntry			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswInterfaces			
Note	This meta-class represents a single API entry into the BSW module or cluster that has the ability to be called in client-server fashion via the BSW Scheduler. In this regard it is more special than BswModuleEntry and can be seen as a wrapper around the Bsw ModuleEntry to which it refers (property encapsulatedEntry). Tags: atp.recommendedPackage=BswModuleEntrys			
Base	<i>ARObject</i> , <i>Referrable</i>			
Aggregated by	BswModuleDescription.providedClientServerEntry , BswModuleDescription.requiredClientServerEntry			
Attribute	Type	Mult.	Kind	Note
encapsulated Entry	BswModuleEntry	0..1	ref	The underlying BswModuleEntry. Tags: xml.sequenceOffset=5
isReentrant	Boolean	0..1	attr	Reentrancy from the viewpoint of clients invoking the service via the BSW Scheduler: <ul style="list-style-type: none"> • true: Enables the service to be invoked again, before the service has finished. • false: It is prohibited to invoke the service again before is has finished. Tags: xml.sequenceOffset=10
isSynchronous	Boolean	0..1	attr	Synchronicity from the viewpoint of clients invoking the service via the BSW Scheduler: <ul style="list-style-type: none"> • true: This calls a synchronous service, i.e. the service is completed when the call returns. • false: The service (on semantical level) may not be complete when the call returns. Tags: xml.sequenceOffset=15

Table A.124: BswModuleClientServerEntry

Class	BswModuleDependency			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswInterfaces			
Note	This class collects the dependencies of a BSW module or cluster on a certain other BSW module.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	BswModuleDescription.bswModuleDependency			
Attribute	Type	Mult.	Kind	Note
targetModuleId	PositiveInteger	0..1	attr	AUTOSAR identifier of the target module of which the dependencies are defined. This information is optional, because the target module may also be identified by targetModuleRef. Tags: xml.sequenceOffset=5





Class	BswModuleDependency			
targetModuleRef	BswModuleDescription	0..1	ref	<p>Reference to the target module. It is an <<atpUriDef>> because the reference shall be used to identify the target module without actually needing the description of that target module.</p> <p>Stereotypes: atpSplitable; atpUriDef; atpVariation Tags: atp.Splitkey=targetModuleRef.bswModuleDescription, targetModuleRef.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=7</p>

Table A.125: BswModuleDependency

Class	BswModuleDescription			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswOverview			
Note	<p>Root element for the description of a single BSW module or BSW cluster. In case it describes a BSW module, the short name of this element equals the name of the BSW module.</p> <p>Tags: atp.recommendedPackage=BswModuleDescriptions</p>			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpFeature, AtpStructureElement, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element , AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
bswModuleDependency	BswModuleDependency	*	aggr	<p>Describes the dependency to another BSW module.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=bswModuleDependency.shortName, bswModuleDependency.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=20</p>
bswModuleDocumentation	SwComponentDocumentation	0..1	aggr	<p>This adds a documentation to the BSW module.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=bswModuleDocumentation, bswModuleDocumentation.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=6</p>
expectedEntry	BswModuleEntry	*	ref	<p>Indicates an entry which is required by this module. Replacement of outgoingCallback / requiredEntry.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=expectedEntry.bswModuleEntry, expectedEntry.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
implementedEntry	BswModuleEntry	*	ref	<p>Specifies an entry provided by this module which can be called by other modules. This includes "main" functions, interrupt routines, and callbacks. Replacement of providedEntry / expectedCallback.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=implementedEntry.bswModuleEntry, implementedEntry.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	BswModuleDescription			
internalBehavior	BswInternalBehavior	*	aggr	<p>The various BswInternalBehaviors associated with a Bsw ModuleDescription can be distributed over several physical files. Therefore the aggregation is <<atp Splitable>>.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=internalBehavior.shortName xml.sequenceOffset=65</p>
moduleId	PositiveInteger	0..1	attr	<p>Refers to the BSW Module Identifier defined by the AUTOSAR standard. For non-standardized modules, a proprietary identifier can be optionally chosen.</p> <p>Tags: xml.sequenceOffset=5</p>
providedClient ServerEntry	BswModuleClientServer Entry	*	aggr	<p>Specifies that this module provides a client server entry which can be called from another partition or core. This entry is declared locally to this context and will be connected to the requiredClientServerEntry of another or the same module via the configuration of the BSW Scheduler.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=providedClientServerEntry.shortName, providedClientServerEntry.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=45</p>
providedData	VariableDataPrototype	*	aggr	<p>Specifies a data prototype provided by this module in order to be read from another partition or core. The providedData is declared locally to this context and will be connected to the requiredData of another or the same module via the configuration of the BSW Scheduler.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=providedData.shortName, provided Data.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=55</p>
providedMode Group	ModeDeclarationGroup Prototype	*	aggr	<p>A set of modes which is owned and provided by this module or cluster. It can be connected to the required ModeGroups of other modules or clusters via the configuration of the BswScheduler. It can also be synchronized with modes provided via ports by an associated ServiceSwComponentType, EcuAbstraction SwComponentType or ComplexDeviceDriverSw ComponentType.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=providedModeGroup.shortName, provided ModeGroup.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=25</p>





Class	BswModuleDescription			
releasedTrigger	Trigger	*	aggr	<p>A Trigger released by this module or cluster. It can be connected to the requiredTriggers of other modules or clusters via the configuration of the BswScheduler. It can also be synchronized with Triggers provided via ports by an associated ServiceSwComponentType, Ecu AbstractionSwComponentType or ComplexDeviceDriver SwComponentType.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=releasedTrigger.shortName, releasedTrigger.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=35</p>
requiredClientServerEntry	BswModuleClientServerEntry	*	aggr	<p>Specifies that this module requires a client server entry which can be implemented on another partition or core.This entry is declared locally to this context and will be connected to the providedClientServerEntry of another or the same module via the configuration of the BSW Scheduler.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=requiredClientServerEntry.shortName, requiredClientServerEntry.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=50</p>
requiredData	VariableDataPrototype	*	aggr	<p>Specifies a data prototype required by this module in order to be provided from another partition or core.The required Data is declared locally to this context and will be connected to the providedData of another or the same module via the configuration of the BswScheduler.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=requiredData.shortName, requiredData.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=60</p>
requiredModeGroup	ModeDeclarationGroupPrototype	*	aggr	<p>Specifies that this module or cluster depends on a certain mode group. The requiredModeGroup is local to this context and will be connected to the providedModeGroup of another module or cluster via the configuration of the BswScheduler.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=requiredModeGroup.shortName, requiredModeGroup.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=30</p>
requiredTrigger	Trigger	*	aggr	<p>Specifies that this module or cluster reacts upon an external trigger.This requiredTrigger is declared locally to this context and will be connected to the providedTrigger of another module or cluster via the configuration of the BswScheduler.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=requiredTrigger.shortName, requiredTrigger.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=40</p>

Table A.126: BswModuleDescription

Class	BswModuleEntity (abstract)			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Specifies the smallest code fragment which can be described for a BSW module or cluster within AUTOSAR.			
Base	ARObject , ExecutableEntity , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	BswCalledEntity , BswInterruptEntity , BswSchedulableEntity			
Aggregated by	BswInternalBehavior.entity			
Attribute	Type	Mult.	Kind	Note
accessedMode Group	ModeDeclarationGroup Prototype	*	ref	A mode group which is accessed via API call by this entity. It shall be a ModeDeclarationGroupPrototype required by this module or cluster. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=accessedModeGroup.modeDeclarationGroupPrototype, accessedModeGroup.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
activationPoint	BswInternalTriggering Point	*	ref	Activation point used by the module entity to activate one or more internal triggers. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=activationPoint.bswInternalTriggeringPoint, activationPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
callPoint	BswModuleCallPoint	*	aggr	A call point used in the code of this entity. The variability of this association is especially targeted at debug scenarios: It is possible to have one variant calling into the AUTOSAR debug module and another one which doesn't. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=callPoint.shortName, callPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
dataReceive Point	BswVariableAccess	*	aggr	The data is received via the BSW Scheduler. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataReceivePoint.shortName, dataReceivePoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
dataSendPoint	BswVariableAccess	*	aggr	The data is sent via the BSW Scheduler. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataSendPoint.shortName, dataSendPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
implemented Entry	BswModuleEntry	0..1	ref	The entry which is implemented by this module entity.
issuedTrigger	Trigger	*	ref	A trigger issued by this entity via BSW Scheduler API call. It shall be a BswTrigger released (i.e. owned) by this module or cluster. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=issuedTrigger.trigger, issuedTrigger.variationPoint.shortLabel vh.latestBindingTime=preCompileTime





Class	<i>BswModuleEntity</i> (abstract)			
managedModeGroup	ModeDeclarationGroupPrototype	*	ref	A mode group which is managed by this entity. It shall be a ModeDeclarationGroupPrototype provided by this module or cluster. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=managedModeGroup.modeDeclarationGroupPrototype, managedModeGroup.variation Point.shortLabel vh.latestBindingTime=preCompileTime
schedulerNamePrefix	BswSchedulerNamePrefix	0..1	ref	A prefix to be used in generated names for the BswModuleScheduler in the context of this BswModuleEntity, for example entry point prototypes, macros for dealing with exclusive areas, header file names. Details are defined in the SWS RTE. The prefix supersedes default rules for the prefix of those names.

Table A.127: BswModuleEntity

Class	<i>BswModuleEntry</i>			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswInterfaces			
Note	This class represents a single API entry (C-function prototype) into the BSW module or cluster. The name of the C-function is equal to the short name of this element with one exception: In case of multiple instances of a module on the same CPU, special rules for "infixes" apply, see description of class BswImplementation. Tags: atp.recommendedPackage=BswModuleEntrys			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
argument (ordered)	SwServiceArg	*	aggr	An argument belonging to this BswModuleEntry. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=argument.shortName, argument.variation Point.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.sequenceOffset=45
bswEntryKind	BswEntryKindEnum	0..1	attr	This describes whether the entry is concrete or abstract. If the attribute is missing the entry is considered as concrete. Tags: xml.sequenceOffset=40
callType	BswCallType	0..1	attr	The type of call associated with this service. Tags: xml.sequenceOffset=25
executionContext	BswExecutionContext	0..1	attr	Specifies the execution context which is required (in case of entries into this module) or guaranteed (in case of entries called from this module) for this service. Tags: xml.sequenceOffset=30
functionPrototypeEmitter	NameToken	0..1	attr	This attribute is used to control the generation of function prototypes. If set to "RTE", the RTE generates the function prototypes in the Module Interlink Header File.





Class	BswModuleEntry			
isReentrant	Boolean	0..1	attr	<p>Reentrancy from the viewpoint of function callers:</p> <ul style="list-style-type: none"> • true: Enables the service to be invoked again, before the service has finished. • false: It is prohibited to invoke the service again before it has finished. <p>Tags: xml.sequenceOffset=15</p>
isSynchronous	Boolean	0..1	attr	<p>Synchronicity from the viewpoint of function callers:</p> <ul style="list-style-type: none"> • true: This calls a synchronous service, i.e. the service is completed when the call returns. • false: The service (on semantical level) may not be complete when the call returns. <p>Tags: xml.sequenceOffset=20</p>
returnType	SwServiceArg	0..1	aggr	<p>The return type belonging to this bswModuleEntry.</p> <p>Tags: xml.sequenceOffset=40</p>
role	Identifier	0..1	attr	<p>Specifies the role of the entry in the given context. It shall be equal to the standardized name of the service call, especially in cases where no ServiceIdentifier is specified, e.g. for callbacks. Note that the ShortName is not always sufficient because it maybe vendor specific (e.g. for callbacks which can have more than one instance).</p> <p>Tags: xml.sequenceOffset=10</p>
serviceId	PositiveInteger	0..1	attr	<p>Refers to the service identifier of the Standardized Interfaces of AUTOSAR basic software. For non-standardized interfaces, it can optionally be used for proprietary identification.</p> <p>Tags: xml.sequenceOffset=5</p>
swServiceImplPolicy	SwServiceImplPolicy Enum	0..1	attr	<p>Denotes the implementation policy as a standard function call, inline function or macro. This has to be specified on interface level because it determines the signature of the call.</p> <p>Tags: xml.sequenceOffset=35</p>

Table A.128: BswModuleEntry

Class	BswModuleTiming			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingExtensions			
Note	<p>A model element used to define timing descriptions and constraints for the BswInternalBehavior of one BSW Module. Thereby, for each BswInternalBehavior a separate timing can be specified.</p> <p>A constraint defined at this level holds true for all Implementations of that BswInternalBehavior.</p> <p>TimingDescriptions aggregated by BswModuleTiming are restricted to event chains referring to events which are derived from the class TDEventBswInternalBehavior.</p> <p>Tags: atp.recommendedPackage=TimingExtensions</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, TimingExtension			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
behavior	BswInternalBehavior	0..1	ref	This defines the scope of a BswModuleTiming. All corresponding timing descriptions and constraints shall be defined within this scope.

Table A.129: BswModuleTiming

Class	BswOperationInvokedEvent			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	This event is thrown on operation invocation in Client-Server-Communication via the BSW Scheduler. Its "entry" reference provides the BswClientServerEntry that is called subsequently. Note this event is not needed in case of direct function calls.			
Base	ARObject, AbstractEvent, BswEvent, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
entry	BswModuleClientServerEntry	0..1	ref	The providedClientServerEntry invoked by this event.

Table A.130: BswOperationInvokedEvent

Class	BswQueuedDataReceptionPolicy			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Reception policy attributes specific for queued receiving.			
Base	ARObject, BswApiOptions, BswDataReceptionPolicy			
Aggregated by	BswInternalBehavior.receptionPolicy			
Attribute	Type	Mult.	Kind	Note
queueLength	PositiveInteger	0..1	attr	Length of queue for received events.

Table A.131: BswQueuedDataReceptionPolicy

Class	BswSchedulableEntity			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	BSW module entity, which is designed for control by the BSW Scheduler. It may for example implement a so-called "main" function.			
Base	ARObject, BswModuleEntity, ExecutableEntity, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	BswInternalBehavior.entity			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.132: BswSchedulableEntity

Class	BswScheduleEvent (abstract)			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	BswEvent that is able to start a BswSchedulabeEntity.			
Base	ARObject, AbstractEvent, BswEvent, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	BswAsynchronousServerCallReturnsEvent, BswBackgroundEvent, BswDataReceivedEvent, BswExternalTriggerOccurredEvent, BswInternalTriggerOccurredEvent, BswModeManagerErrorEvent, BswModeSwitchEvent, BswModeSwitchedAckEvent, BswOsTaskExecutionEvent, BswTimingEvent			
Aggregated by	BswInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.133: BswScheduleEvent

Class	BswServiceDependency			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Specialization of ServiceDependency in the context of an BswInternalBehavior. It allows to associate BswModuleEntries and data defined for a BSW module or cluster to a given ServiceNeeds element.			
Base	ARObject, ServiceDependency			
Aggregated by	BswInternalBehavior.serviceDependency			
Attribute	Type	Mult.	Kind	Note
assignedData	RoleBasedDataAssignment	*	aggr	Defines the role of an associated data object (owned by this module or cluster) in the context of the ServiceNeeds element. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=assignedData, assignedData.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
assignedEntryRole	RoleBasedBswModuleEntryAssignment	*	aggr	Defines the role of an associated BswModuleEntry in the context of the ServiceNeeds element. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=assignedEntryRole, assignedEntryRole.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
ident	BswServiceDependencyIdent	0..1	aggr	This adds the ability to become referable to BswServiceDependency. Stereotypes: atpIdentityContributor Tags: xml.sequenceOffset=-100
serviceNeeds	ServiceNeeds	0..1	aggr	The associated ServiceNeeds.

Table A.134: BswServiceDependency

Class	BswServiceDependencyIdent			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This meta-class is created to add the ability to become the target of a reference to the non-Referrable BswServiceDependency.			
Base	ARObject, AtpClassifier , AtpFeature , AtpStructureElement , IdentCaption , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , BswServiceDependency.ident			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.135: BswServiceDependencyIdent

Class	BswSynchronousServerCallPoint			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	Represents a synchronous procedure call point via the BSW Scheduler.			
Base	ARObject, BswModuleCallPoint , Referrable			
Aggregated by	BswModuleEntity.callPoint			
Attribute	Type	Mult.	Kind	Note
calledEntry	BswModuleClientServerEntry	0..1	ref	The entry to be called.





Class		BswSynchronousServerCallPoint		
calledFrom WithinExclusive Area	ExclusiveAreaNesting Order	0..1	ref	This indicates that the call point is located at the deepest level inside one or more ExclusiveAreas that are nested in the given order.

Table A.136: BswSynchronousServerCallPoint

Class		BswTimingEvent		
Package		M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior		
Note		A recurring BswEvent driven by a time period.		
Base		ARObject, AbstractEvent, BswEvent, BswScheduleEvent, Identifiable, MultilanguageReferrable, Referrable		
Aggregated by		BswInternalBehavior.event		
Attribute	Type	Mult.	Kind	Note
period	TimeValue	0..1	attr	Requirement for the time period (in seconds) by which this event is triggered.

Table A.137: BswTimingEvent

Class		BswTriggerDirectImplementation		
Package		M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior		
Note		Specifies a released trigger to be directly implemented via OS calls, for example in a Complex Driver module.		
Base		ARObject		
Aggregated by		BswInternalBehavior.triggerDirectImplementation		
Attribute	Type	Mult.	Kind	Note
cat2Isr	Identifier	0..1	attr	The name of the OS category 2 ISR, which is controlled by the referred trigger. This means, that the module manages the category 2 ISR (e.g. according hardware initialization and enabling of ISR). Instead of calling an RTE / SchM API to raise the appropriate events in components or modules receiving the trigger, this ISR directly schedules the triggered ExecutableEntitys. The ISR name is required by the integrator to map the Bsw Events and RTEEvents to this ISR.
masteredTrigger	Trigger	0..1	ref	The trigger which is directly mastered by this module. There may be several different BswTriggerDirect Implementations mastering the same Trigger. This may be required e.g. due to memory partitioning.
task	Identifier	0..1	attr	The name of the OS task, which is controlled by the referred trigger. This means, that the module uses the trigger condition to directly activate an OS task instead of calling an API of the BswScheduler. The task name is required by the RTE generator resp. BswScheduler to raise the appropriate events in components or modules receiving the trigger.

Table A.138: BswTriggerDirectImplementation

Class	BswVariableAccess			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	The presence of a BswVariableAccess implies that a BswModuleEntity needs access to a VariableData Prototype via the BSW Scheduler. The kind of access is specified by the role in which the class is used.			
Base	ARObject, Referrable			
Aggregated by	BswModuleEntity.dataReceivePoint, BswModuleEntity.dataSendPoint			
Attribute	Type	Mult.	Kind	Note
accessed Variable	VariableDataPrototype	0..1	ref	The data accessed via the BSW Scheduler.
context Limitation	BswDistinguished Partition	*	ref	The existence of this reference indicates that the variable is received resp. sent only in the context of the referred BswDistinguishedPartitions.

Table A.139: BswVariableAccess

Class	BufferProperties			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	Configuration of the buffer properties the transformer needs to work.			
Base	ARObject			
Aggregated by	TransformationTechnology.bufferProperties			
Attribute	Type	Mult.	Kind	Note
headerLength	Integer	0..1	attr	Defines the length of the header (in bits) this transformer will add in front of the data.
inPlace	Boolean	0..1	attr	If set, the transformer uses the input buffer as output buffer.

Table A.140: BufferProperties

Class	BulkNvDataDescriptor			
Package	M2::AUTOSARTemplates::SWComponentTemplate::NvBlockComponent			
Note	This meta-class represents one bulk NV Data Block that is read-only for the application software. The purpose of a bulk NV Data Block is to provide access to information uploaded to the vehicle at e.g. the end of the production line.			
Base	ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, NvBlockSwComponentType.bulkNvDataDescriptor			
Attribute	Type	Mult.	Kind	Note
bulkNvBlock	VariableDataPrototype	0..1	aggr	This aggregation represents the actual bulk NVBlock.
nvBlockData Mapping	NvBlockDataMapping	*	aggr	Defines the mapping between the VariableData Prototypes in the NvBlockComponents ports and the VariableDataPrototypes of the non-volatile memory. The aggregation of NvBlockDataMapping is subject to variability with the purpose to support the conditional existence of nv data ports. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=nvBlockDataMapping, nvBlockData Mapping.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.141: BulkNvDataDescriptor

Class	BurstPatternEventTriggering			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::EventTriggeringConstraint			
Note	Describes the maximum number of occurrences of the same event in a given time interval. Typically used to model a worst case activation scenario.			
Base	ARObject, EventTriggeringConstraint , Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
maxNumberOfOccurrences	PositiveInteger	0..1	attr	The maximum number of event occurrences within the given time interval. The event may never occur, or may occur N times between 1 and maxNumberOfOccurrences . If the parameter minNumberOfOccurrences is specified then the event occurs at least the number of times specified by minNumberOfOccurrences and at maximum by maxNumberOfOccurrences .
minimumInterArrivalTime	MultidimensionalTime	0..1	aggr	Specifies the minimum distance between subsequent occurrences of the event within the given time interval.
minNumberOfOccurrences	PositiveInteger	0..1	attr	The minimum number of event occurrences within the given time interval. Tags: xml.sequenceOffset=10
patternJitter	MultidimensionalTime	0..1	aggr	The maximum deviation of the time interval's starting point from the beginning of the given period. This parameter is only applicable in conjunction with the parameter patternPeriod
patternLength	MultidimensionalTime	0..1	aggr	The duration of the time interval within which the event repeatedly occurs. The event occurs at arbitrary points in time within the given time interval.
patternPeriod	MultidimensionalTime	0..1	aggr	The time distance between the beginnings of subsequent repetitions of the given burst pattern.

Table A.142: BurstPatternEventTriggering

Class	BusMirrorCanIdRangeMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror			
Note	This element defines a rule for remapping a set of CAN IDs.			
Base	ARObject			
Aggregated by	BusMirrorChannelMappingCan.canIdRangeMapping			
Attribute	Type	Mult.	Kind	Note
destinationBaseId	PositiveInteger	0..1	attr	Base ID merged with the masked parts of the original CAN ID to form the mapped CAN ID.
sourceCanIdCode	PositiveInteger	0..1	attr	Value to match masked original CAN IDs.
sourceCanIdMask	PositiveInteger	0..1	attr	Mask applied to original CAN IDs before comparison.

Table A.143: BusMirrorCanIdRangeMapping

Class	BusMirrorCanIdToCanIdMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror			
Note	This element defines a rule for remapping a single CAN ID.			
Base	ARObject			
Aggregated by	BusMirrorChannelMappingCan.canIdToCanIdMapping			





Class		BusMirrorCanIdToCanIdMapping		
Attribute	Type	Mult.	Kind	Note
remappedCanId	PositiveInteger	0..1	attr	This attribute defines the CanId on the targetChannel.
sourceCanId	CanFrameTriggering	0..1	ref	This reference points to the sourceFrame with sourceCan Id on the sourceChannel.

Table A.144: BusMirrorCanIdToCanIdMapping

Class		BusMirrorChannel		
Package		M2::AUTOSARTemplates::SystemTemplate::BusMirror		
Note		This element assigns a busMirrorNetworkId to the referenced channel.		
Base		ARObject		
Aggregated by		BusMirrorChannelMapping.sourceChannel , BusMirrorChannelMapping.targetChannel		
Attribute	Type	Mult.	Kind	Note
busMirrorNetworkId	PositiveInteger	0..1	attr	This attribute defines the networkId of the communication channel.
channel	PhysicalChannel	0..1	ref	Reference to PhysicalChannel that is used in the bus mirroring as sourceChannel or targetChannel. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=channel.physicalChannel, channel.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime

Table A.145: BusMirrorChannel

Class		BusMirrorChannelMapping (abstract)		
Package		M2::AUTOSARTemplates::SystemTemplate::BusMirror		
Note		This element defines a bus mirroring in which the traffic from one communication bus (sourceChannel) is forwarded to another one (targetChannel).		
Base		ARObject , CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable		
Subclasses		BusMirrorChannelMappingCan , BusMirrorChannelMappingFlexray , BusMirrorChannelMappingIp , BusMirrorChannelMappingUserDefined		
Aggregated by		ARPackage.element		
Attribute	Type	Mult.	Kind	Note
ecuInstance	EcuInstance	0..1	ref	Ecu on which the BusMirroring is performed Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=ecuInstance.ecuInstance, ecuInstance.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
globalTimeDomain	GlobalTimeDomain	0..1	ref	Reference to the GlobalTimeDomain this BusMirrorChannelMapping shall be synchronized with. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=globalTimeDomain.globalTimeDomain, globalTimeDomain.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
mirroringProtocol	MirroringProtocolEnum	0..1	attr	This attribute defines the bus mirroring protocol that is used in the BusMirrorChannelMapping





Class	<i>BusMirrorChannelMapping</i> (abstract)			
sourceChannel	BusMirrorChannel	0..1	aggr	Defines the sourceChannel from which frames are received. Stereotypes: atpSplitable Tags: atp.Splitkey=sourceChannel
targetChannel	BusMirrorChannel	0..1	aggr	Defines the targetChannel to which frames are forwarded. Stereotypes: atpSplitable Tags: atp.Splitkey=targetChannel
targetPduTriggering	PduTriggering	*	ref	Reference to the PduTriggering that is used for transmission of the mirrored frames on the targetChannel. Please note that on FlexRay several targetPduTriggerings may be used. For all other communication channels only a single targetPduTriggering is supported. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=targetPduTriggering.pduTriggering, targetPduTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild
transmissionDeadline	TimeValue	0..1	attr	Time in seconds after which the collection of source frames into the destination frame is stopped and the frame is sent at the latest. If omitted, destination frames are only sent when full or when the time stamp overflows.

Table A.146: BusMirrorChannelMapping

Class	<i>BusMirrorChannelMappingCan</i>			
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror			
Note	This element defines the bus mirroring between a CAN or LIN sourceChannel and a CAN targetChannel. Tags: atp.recommendedPackage=BusMirrorChannelMappings			
Base	ARObject , BusMirrorChannelMapping , CollectableElement , FibexElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
canIdRangeMapping	BusMirrorCanIdRangeMapping	*	aggr	Rules for remapping of a set of CAN IDs.
canIdToCanIdMapping	BusMirrorCanIdToCanIdMapping	*	aggr	Rules for remapping of single CanIds.
linPidToCanIdMapping	BusMirrorLinPidToCanIdMapping	*	aggr	Rules for remapping of single LIN Frames.
mirrorSourceLinToCanRangeBaseId	PositiveInteger	0..1	attr	Base ID merged with the LIN frame ID to form the CAN ID. Only required when a BusMirrorChannel that refers to a LinPhysicalChannel in the role channel is referenced in the role sourceChannel.
mirrorStatusCanId	PositiveInteger	0..1	attr	CAN ID of the CAN status frame. If configured, a status frame will be sent on the CAN destination bus that contains the state of all active source buses.

Table A.147: BusMirrorChannelMappingCan

Class	BusMirrorChannelMappingFlexray			
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror			
Note	This element defines the bus mirroring between a CAN, LIN or FlexRay sourceChannel and a FlexRay targetChannel. Tags: atp.recommendedPackage=BusMirrorChannelMappings			
Base	ARObject , BusMirrorChannelMapping , CollectableElement , FibexElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.148: BusMirrorChannelMappingFlexray

Class	BusMirrorChannelMappingIp			
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror			
Note	This element defines the bus mirroring between a CAN, LIN or FlexRay sourceChannel and an Ethernet IP targetChannel. Tags: atp.recommendedPackage=BusMirrorChannelMappings			
Base	ARObject , BusMirrorChannelMapping , CollectableElement , FibexElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.149: BusMirrorChannelMappingIp

Class	BusMirrorChannelMappingUserDefined			
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror			
Note	This element defines the bus mirroring between a CAN, LIN or FlexRay sourceChannel and a User Defined targetChannel. Tags: atp.recommendedPackage=BusMirrorChannelMappings			
Base	ARObject , BusMirrorChannelMapping , CollectableElement , FibexElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.150: BusMirrorChannelMappingUserDefined

Class	BusMirrorLinPidToCanIdMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror			
Note	This element defines a rule for remapping a single LIN Frame.			
Base	ARObject			
Aggregated by	BusMirrorChannelMappingCan.linPidToCanIdMapping			
Attribute	Type	Mult.	Kind	Note
remappedCanId	PositiveInteger	0..1	attr	This attribute defines the CanId on the targetChannel.
sourceLinPid	LinFrameTriggering	0..1	ref	This reference points to the sourceFrame with sourceCan Id on the sourceChannel.

Table A.151: BusMirrorLinPidToCanIdMapping

Class	BusspecificNmEcu (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	Busspecific NmEcu attributes.			
Base	ARObject			
Subclasses	CanNmEcu, FlexrayNmEcu, J1939NmEcu, UdpNmEcu			
Aggregated by	NmEcu.busDependentNmEcu			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.152: BusspecificNmEcu

Enumeration	ByteOrderEnum
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes
Note	When more than one byte is stored in the memory the order of those bytes may differ depending on the architecture of the processing unit. If the least significant byte is stored at the lowest address, this architecture is called little endian and otherwise it is called big endian. ByteOrder is very important in case of communication between different PUs or ECUs.
Aggregated by	ApSomeipTransformationProps.byteOrder, BaseTypeDirectDefinition.byteOrder , DiagnosticCommonProps.defaultEndianness , ISignalToIPduMapping.packingByteOrder , MultiplexedIPdu.selectorFieldByteOrder , PduToFrameMapping.packingByteOrder , SegmentPosition.segmentByteOrder , SOMEIPTransformationDescription.byteOrder , System.containerIPduHeaderByteOrder
Literal	Description
mostSignificantByte First	Most significant byte shall come at the lowest address (also known as BigEndian or as Motorola-Format) Tags: atp.EnumerationLiteralIndex=0
mostSignificantByte Last	Most significant byte shall come highest address (also known as LittleEndian or as Intel-Format) Tags: atp.EnumerationLiteralIndex=1
opaque	For opaque data endianness conversion has to be configured to Opaque. See AUTOSAR COM Specification for more details. Tags: atp.EnumerationLiteralIndex=2

Table A.153: ByteOrderEnum

Class	CalibrationParameterValue			
Package	M2::AUTOSARTemplates::SWComponentTemplate::MeasurementAndCalibration::CalibrationParameter Values			
Note	Specifies instance specific calibration parameter values used to initialize the memory objects implementing calibration parameters in the generated RTE code. RTE generator will use the implInitValue to override the initial values specified for the DataPrototypes of a component type. The applInitValue is used to exchange init values with the component vendor not publishing the transformation algorithm between ApplicationDataTypes and ImplementationDataTypes or defining an instance specific initialization of components which are only defined with ApplicationDataTypes. Note: If both representations of init values are available these need to represent the same content. Note further that in this case an explicit mapping of ValueSpecification is not implemented because calibration parameters are delivered back after the calibration phase.			
Base	ARObject			
Aggregated by	CalibrationParameterValueSet.calibrationParameterValue			
Attribute	Type	Mult.	Kind	Note
applInitValue	ValueSpecification	0..1	aggr	This is the initial value specification structured according to the ApplicationDataType





Class	CalibrationParameterValue			
implInitValue	ValueSpecification	0..1	aggr	This is the initial value specification structured according to the ImplementationDataType
initializedParameter	FlatInstanceDescriptor	0..1	ref	This represents the parameter that is initialized by the CalibrationParameterValue.

Table A.154: CalibrationParameterValue

Enumeration	CalprmAxisCategoryEnum
Package	M2::MSR::DataDictionary::CalibrationParameter
Note	This enum specifies the possible values of the category property within SwCalprmAxis.
Aggregated by	RuleBasedAxisCont.category , SwAxisCont.category , SwCalprmAxis.category
Literal	Description
comAxis	COM_AXIS is equal to an STD_AXIS, the difference is, that a COM_AXIS is an shared axis, that means this axis can be used multiple times by different CURVEs, MAPs, CUBOIDs, CUBE_4s, and CUBE_5s. Tags: atp.EnumerationLiteralIndex=0 xml.name=COM_AXIS
fixAxis	FIX_AXIS means that the input axis is not stored. The axis is calculated using parameters and so on it is also not possible to modify the axis points. Tags: atp.EnumerationLiteralIndex=4 xml.name=FIX_AXIS
resAxis	RES_AXIS is also an shared axis like COM_AXIS, the difference is that this kind of axis can be used for rescaling. Tags: atp.EnumerationLiteralIndex=6 xml.name=RES_AXIS
stdAxis	STD_AXIS means that input and output axis definition are stored within this CURVE, MAP, CUBOID, CUBE_4, and CUBE_5. There is no shared or calculated axis. Tags: atp.EnumerationLiteralIndex=8 xml.name=STD_AXIS

Table A.155: CalprmAxisCategoryEnum

Class	«atpVariation» CanCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	CAN bus specific cluster attributes. Tags: atp.recommendedPackage=CommunicationClusters			
Base	ARElement , ARObject , AbstractCanCluster , CollectableElement , CommunicationCluster , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.156: CanCluster

Class	CanCommunicationConnector			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	CAN bus specific communication connector attributes.			
Base	<i>ARObject</i> , <i>AbstractCanCommunicationConnector</i> , <i>CommunicationConnector</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	<i>EcuInstance.connector</i> , <i>MachineDesign.communicationConnector</i>			
Attribute	Type	Mult.	Kind	Note
pncWakeupCanId	PositiveInteger	0..1	attr	CAN Identifier used to configure the CAN Transceiver for partial network wakeup.
pncWakeupCanIdExtended	Boolean	0..1	attr	Defines whether pncWakeupCanId and pncWakeupCanIdMask shall be interpreted as extended or standard CAN ID.
pncWakeupCanIdMask	PositiveInteger	0..1	attr	Bit mask for CAN Identifier used to configure the CAN Transceiver for partial network wakeup.
pncWakeupDataMask	PositiveUnlimitedInteger	0..1	attr	Bit mask for CAN Payload used to configure the CAN Transceiver for partial network wakeup.
pncWakeupDlc	PositiveInteger	0..1	attr	Data Length of the remote data frame used to configure the CAN Transceiver for partial network wakeup in Bytes.

Table A.157: CanCommunicationConnector

Class	«atpVariation» CanCommunicationController			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	CAN bus specific communication port attributes.			
Base	<i>ARObject</i> , <i>AbstractCanCommunicationController</i> , <i>CommunicationController</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	<i>EcuInstance.commController</i> , <i>MachineDesign.communicationController</i>			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.158: CanCommunicationController

Class	CanControllerConfiguration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	This element is used for the specification of the exact CAN Bit Timing configuration parameter values.			
Base	<i>ARObject</i> , <i>AbstractCanCommunicationControllerAttributes</i>			
Aggregated by	<i>AbstractCanCommunicationController.canControllerAttributes</i> , <i>CanXIProps.canConfig</i>			
Attribute	Type	Mult.	Kind	Note
propSeg	Integer	0..1	attr	Specifies propagation delay in time quantas.
syncJumpWidth	Integer	0..1	attr	The number of quanta in the Synchronization Jump Width, SJW. The (Re-)Synchronization Jump Width (SJW) defines how far a resynchronization may move the Sample Point inside the limits defined by the Phase Buffer Segments to compensate for edge phase errors.
timeSeg1	Integer	0..1	attr	Specifies phase segment 1 in time quantas. timeSeg1 = Phase_Seg1
timeSeg2	Integer	0..1	attr	Specifies phase segment 2 in time quantas. timeSeg2 = Phase_Seg2

Table A.159: CanControllerConfiguration

Class				
Class	CanControllerConfigurationRequirements			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	This element allows the specification of ranges for the CAN Bit Timing configuration parameters. These ranges are taken as requirements and have to be respected by the ECU developer.			
Base	ARObject, AbstractCanCommunicationControllerAttributes			
Aggregated by	AbstractCanCommunicationController.canControllerAttributes			
Attribute	Type	Mult.	Kind	Note
maxNumberOfTimeQuantaPerBit	Integer	0..1	attr	Maximum number of time quanta in the bit time.
maxSamplePoint	Float	0..1	attr	The max. value of the sample point as a percentage of the total bit time.
maxSyncJumpWidth	Float	0..1	attr	The max. Synchronization Jump Width value as a percentage of the total bit time. The (Re-)Synchronization Jump Width (SJW) defines how far a resynchronization may move the Sample Point inside the limits defined by the Phase Buffer Segments to compensate for edge phase errors.
minNumberOfTimeQuantaPerBit	Integer	0..1	attr	Minimum number of time quanta in the bit time.
minSamplePoint	Float	0..1	attr	The min. value of the sample point as a percentage of the total bit time.
minSyncJumpWidth	Float	0..1	attr	The min. Synchronization Jump Width value as a percentage of the total bit time. The (Re-)Synchronization Jump Width (SJW) defines how far a resynchronization may move the Sample Point inside the limits defined by the Phase Buffer Segments to compensate for edge phase errors.

Table A.160: CanControllerConfigurationRequirements

Class				
Class	CanControllerFdConfiguration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	Bit timing related configuration of a CAN controller for payload and CRC of a CAN FD frame.			
Base	ARObject			
Aggregated by	AbstractCanCommunicationControllerAttributes.canControllerFdAttributes , CanXIProps.canFdConfig			
Attribute	Type	Mult.	Kind	Note
paddingValue	PositiveInteger	0..1	attr	Specifies the value which is used to pad unused data in CAN FD frames which are bigger than 8 byte if the length of a Pdu which was requested to be sent does not match the allowed DLC values of CAN FD.
propSeg	PositiveInteger	0..1	attr	Specifies propagation delay in time quantas.
sspOffset	PositiveInteger	0..1	attr	Specifies the Transmitter Delay Compensation Offset in minimum time quanta. Transmitter Delay Compensation Offset is used to adjust the position of the Secondary Sample Point (SSP), relative to the beginning of the received bit. If this parameter is configured, the Transmitter Delay Compensation is done by measurement of the CAN controller. If not specified Transmitter Delay Compensation is disabled.
syncJumpWidth	PositiveInteger	0..1	attr	Specifies the synchronization jump width for the controller in time quantas.
timeSeg1	PositiveInteger	0..1	attr	Specifies phase segment 1 in time quantas.
timeSeg2	PositiveInteger	0..1	attr	Specifies phase segment 2 in time quantas.





Class	CanControllerFdConfiguration			
txBitRateSwitch	Boolean	0..1	attr	<p>Specifies if the bit rate switching shall be used for transmissions.</p> <p>TRUE: CAN FD frames shall be sent with bit rate switching.</p> <p>FALSE: CAN FD frames shall be sent without bit rate switching.</p>

Table A.161: CanControllerFdConfiguration

Class	CanControllerFdConfigurationRequirements			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	This element allows the specification of ranges for the CanFD bit timing configuration parameters. These ranges are taken as requirements and shall be respected by the ECU developer.			
Base	ARObject			
Aggregated by	AbstractCanCommunicationControllerAttributes.canControllerFdRequirements			
Attribute	Type	Mult.	Kind	Note
maxNumberOfTimeQuantaPerBit	Integer	0..1	attr	Maximum number of time quanta in the bit time.
maxSamplePoint	Float	0..1	attr	The max. value of the sample point as a percentage of the total bit time.
maxSyncJumpWidth	Float	0..1	attr	The max. Synchronization Jump Width value as a percentage of the total bit time. The (Re-)Synchronization Jump Width (SJW) defines how far a resynchronization may move the Sample Point inside the limits defined by the Phase Buffer Segments to compensate for edge phase errors.
maxTrcvDelayCompensationOffset	TimeValue	0..1	attr	Specifies the maximum Transceiver Delay Compensation Offset in seconds. If not specified Transceiver Delay Compensation is disabled.
minNumberOfTimeQuantaPerBit	Integer	0..1	attr	Minimum number of time quanta in the bit time.
minSamplePoint	Float	0..1	attr	The min. value of the sample point as a percentage of the total bit time.
minSyncJumpWidth	Float	0..1	attr	The min. Synchronization Jump Width value as a percentage of the total bit time. The (Re-)Synchronization Jump Width (SJW) defines how far a resynchronization may move the Sample Point inside the limits defined by the Phase Buffer Segments to compensate for edge phase errors.
minTrcvDelayCompensationOffset	TimeValue	0..1	attr	Specifies the minimum Transceiver Delay Compensation Offset in seconds. If not specified Transceiver Delay Compensation is disabled.
paddingValue	PositiveInteger	0..1	attr	Specifies the value which is used to pad unused data in CAN FD frames which are bigger than 8 byte if the length of a Pdu which was requested to be sent does not match the allowed DLC values of CAN FD.





Class	CanControllerFdConfigurationRequirements			
txBitRateSwitch	Boolean	0..1	attr	Specifies if the bit rate switching shall be used for transmissions. TRUE: CAN FD frames shall be sent with bit rate switching. FALSE: CAN FD frames shall be sent without bit rate switching.

Table A.162: CanControllerFdConfigurationRequirements

Class	CanControllerXIConfiguration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	This meta-class represents the CAN XL-specific controller attributes.			
Base	ARObject			
Aggregated by	AbstractCanCommunicationControllerAttributes.canControllerXIAttributes , CanXIProps.canXIConfig			
Attribute	Type	Mult.	Kind	Note
errorSignalingEnabled	Boolean	0..1	attr	Specifies if error signaling shall be enabled. This is not possible when the transceiver is switched to PWM mode (trcvPwmModeEnabled set to TRUE). TRUE: Error signaling shall be enabled. FALSE: Error signaling shall be disabled.
propSeg	PositiveInteger	0..1	attr	Specifies propagation delay in time quantas.
pwmL	PositiveInteger	0..1	attr	Specifies the PWM long phase length.
pwmO	PositiveInteger	0..1	attr	Specifies the PWM time offset.
pwmS	PositiveInteger	0..1	attr	Specifies the PWM short phase length.
sspOffset	PositiveInteger	0..1	attr	Specifies the Transmitter Delay Compensation Offset in minimum time quanta. Transmitter Delay Compensation Offset is used to adjust the position of the Secondary Sample Point (SSP), relative to the beginning of the received bit. If this parameter is configured, the Transmitter Delay Compensation is done by measurement of the CAN controller. If not specified Transmitter Delay Compensation is disabled.
syncJumpWidth	PositiveInteger	0..1	attr	Specifies the synchronization jump width for the controller in time quantas.
timeSeg1	PositiveInteger	0..1	attr	Specifies phase segment 1 in time quantas.
timeSeg2	PositiveInteger	0..1	attr	Specifies phase segment 2 in time quantas.
trcvPwmModeEnabled	Boolean	0..1	attr	Specifies if the transceiver shall be set to the PWM mode. TRUE: The transceiver shall be switched to PWM mode. FALSE: The transceiver shall work in classic CAN mode.

Table A.163: CanControllerXIConfiguration

Class	CanControllerXIConfigurationRequirements			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	This element allows the specification of ranges for the CAN XL configuration parameters. These ranges are taken as requirements and have to be respected by the ECU developer.			
Base	ARObject			





Class		CanControllerXIConfigurationRequirements			
Aggregated by		<i>AbstractCanCommunicationControllerAttributes.canControllerXIRequirements</i> , CanXIProps.canXIConfig Reqs			
Attribute	Type	Mult.	Kind	Note	
errorSignaling Enabled	Boolean	0..1	attr	Specifies if error signaling shall be enabled. This is not possible when the transceiver is switched to PWM mode (trcvPwmModeEnabled set to TRUE). TRUE: Error signaling shall be enabled. FALSE: Error signaling shall be disabled.	
maxNumberOfTimeQuantaPerBit	Integer	0..1	attr	Maximum number of time quanta in the bit time.	
maxPwmL	PositiveInteger	0..1	attr	Specifies the maximum PWM long phase length.	
maxPwmO	PositiveInteger	0..1	attr	Specifies the minimum PWM time offset.	
maxPwmS	PositiveInteger	0..1	attr	Specifies the maximum PWM short phase length.	
maxSamplePoint	Float	0..1	attr	The max. value of the sample point as a percentage of the total bit time.	
maxSyncJumpWidth	Float	0..1	attr	The max. Synchronization Jump Width value as a percentage of the total bit time. The (Re-)Synchronization Jump Width (SJW) defines how far a resynchronization may move the Sample Point inside the limits defined by the Phase Buffer Segments to compensate for edge phase errors.	
maxTrcvDelayCompensationOffset	TimeValue	0..1	attr	Specifies the maximum Transceiver Delay Compensation Offset in seconds. If not specified Transceiver Delay Compensation is disabled.	
minNumberOfTimeQuantaPerBit	Integer	0..1	attr	Minimum number of time quanta in the bit time.	
minPwmL	PositiveInteger	0..1	attr	Specifies the minimum PWM long phase length.	
minPwmO	PositiveInteger	0..1	attr	Specifies the maximum PWM time offset.	
minPwmS	PositiveInteger	0..1	attr	Specifies the minimum PWM short phase length.	
minSamplePoint	Float	0..1	attr	The min. value of the sample point as a percentage of the total bit time.	
minSyncJumpWidth	Float	0..1	attr	The min. Synchronization Jump Width value as a percentage of the total bit time. The (Re-)Synchronization Jump Width (SJW) defines how far a resynchronization may move the Sample Point inside the limits defined by the Phase Buffer Segments to compensate for edge phase errors.	
minTrcvDelayCompensationOffset	TimeValue	0..1	attr	Specifies the minimum Transceiver Delay Compensation Offset in seconds. If not specified Transceiver Delay Compensation is disabled.	
trcvPwmModeEnabled	Boolean	0..1	attr	Specifies if the transceiver shall be set to the PWM mode. TRUE: The transceiver shall be switched to PWM mode. FALSE: The transceiver shall work in classic CAN mode.	

Table A.164: CanControllerXIConfigurationRequirements

Class	CanFrameTriggering			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanCommunication			
Note	CAN specific attributes to the FrameTriggering			
Base	ARObject, FrameTriggering , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	PhysicalChannel.frameTriggering			
Attribute	Type	Mult.	Kind	Note
absolutely Scheduled Timing	TtcanAbsolutely ScheduledTiming	*	aggr	Each frame in TTCAN is identified by its slot id and communication cycle. A description is provided by the usage of AbsolutelyScheduledTiming.
canAddressing Mode	CanAddressingMode Type	0..1	attr	The CAN protocol supports two types of frame formats. The standard frame format uses 11-bit identifiers and is defined in the CAN specification 2.0 A. Additionally the extended frame format allows 29-bit identifiers and is defined in the CAN specification 2.0 B.
canFrameRx Behavior	CanFrameRxBehavior Enum	0..1	attr	Defines which CAN protocol shall be expected for frame reception.
canFrameTx Behavior	CanFrameTxBehavior Enum	0..1	attr	Defines which CAN protocol shall be used for frame transmission.
canXIframe TriggeringProps	CanXIframeTriggering Props	0..1	aggr	Definition of CAN XL specific attributes in case the frame is a CAN XL frame.
identifier	Integer	0..1	attr	This attribute is used to define the identifier this frame shall use on the CAN network.
j1939requestable	Boolean	0..1	attr	Frame can be triggered by the J1939 request message.
rxIdentifier Range	RxIdentifierRange	0..1	aggr	Optional definition of a CanId range.
rxMask	PositiveInteger	0..1	attr	Identifier mask which denotes the relevant bits in the CAN Identifier. Together with the identifier, this parameter defines a CAN identifier range.
txMask	PositiveInteger	0..1	attr	Identifier mask which denotes static bits in the CAN identifier. The other bits can be set dynamically.

Table A.165: CanFrameTriggering

Enumeration	CanFrameTxBehaviorEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanCommunication
Note	Defines different CAN protocols for frame transmission behavior.
Aggregated by	CanFrameTriggering.canFrameTxBehavior , IEEE1722TpAcfCanPart.canFrameTxBehavior
Literal	Description
can20	This CAN frame shall be sent as CAN 2.0 only. Tags: atp.EnumerationLiteralIndex=0
canFd	This CAN frame shall be sent as CAN FD. Tags: atp.EnumerationLiteralIndex=1

Table A.166: CanFrameTxBehaviorEnum

Class	CanNmCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	Can specific NmCluster attributes			
Base	ARObject, Identifiable , MultilanguageReferrable , NmCluster , Referrable			
Aggregated by	NmConfig.nmCluster			
Attribute	Type	Mult.	Kind	Note





Class	CanNmCluster			
nmBusloadReductionActive	Boolean	0..1	attr	It determines if bus load reduction for the respective Can Nm channel is active or not.
nmCarWakeUpBitPosition	PositiveInteger	0..1	attr	Specifies the bit position of the CarWakeUp within the Nm Pdu.
nmCarWakeUpFilterNodeId	PositiveInteger	0..1	attr	Source node identifier for CarWakeUp filtering.
nmCbvPosition	Integer	0..1	attr	Defines the position of the control bit vector within the Nm Pdu (Byte position). If this attribute is not configured, the Control Bit Vector is not used.
nmImmediateNmCycleTime	TimeValue	0..1	attr	Defines the immediate NmPdu cycle time in seconds which is used for nmImmediateNmTransmissions NmPdu transmissions. This parameter is only valid if CanNm ImmediateNmTransmissions is greater one.
nmImmediateNmTransmissions	PositiveInteger	0..1	attr	Defines the number of immediate NmPdus which shall be transmitted. If the value is zero no immediate NmPdus are transmitted. The cycle time of immediate NmPdus is defined by nmImmediateNmCycleTime.
nmMessageTimeoutTime	TimeValue	0..1	attr	Timeout of an NmPdu in seconds. It determines how long the NM shall wait with notification of transmission failure while communication errors occur on the bus.
nmMsgCycleTime	TimeValue	0..1	attr	Period of a NmPdu in seconds. It determines the periodic rate in the periodic transmission mode with bus load reduction and is the basis for transmit scheduling in the periodic transmission mode without bus load reduction.
nmNetworkTimeout	TimeValue	0..1	attr	Network Timeout for NmPdus in seconds It denotes the time how long the CanNm shall stay in the Network Mode before transition into Prepare Bus-Sleep Mode shall take place.
nmNidPosition	Integer	0..1	attr	Defines the byte position of the source node identifier within the NmPdu. If this attribute is not configured, the Node Identification is not used.
nmRemoteSleepIndicationTime	TimeValue	0..1	attr	Timeout for Remote Sleep Indication in seconds. It defines the time how long it shall take to recognize that all other nodes are ready to sleep.
nmRepeatMessageTime	TimeValue	0..1	attr	Timeout for Repeat Message State in seconds. Defines the time how long the NM shall stay in the Repeat Message State.
nmWaitBusSleepTime	TimeValue	0..1	attr	Timeout for bus calm down phase in seconds. It denotes the time how long the CanNm shall stay in the Prepare Bus-Sleep Mode before transition into Bus-Sleep Mode shall take place.

Table A.167: CanNmCluster

Class	CanNmClusterCoupling			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	CAN attributes that are valid for each of the referenced (coupled) CAN clusters.			
Base	ARObject, NmClusterCoupling			
Aggregated by	NmConfig.nmClusterCoupling			
Attribute	Type	Mult.	Kind	Note
coupledCluster	CanNmCluster	*	ref	Reference to coupled CAN Clusters.
nmBusloadReductionEnabled	Boolean	0..1	attr	Enables busload reduction support





Class	CanNmClusterCoupling			
nmImmediateRestartEnabled	Boolean	0..1	attr	Enables the asynchronous transmission of a CanNm PDU upon bus-communication request in Prepare-Bus-Sleep mode.

Table A.168: CanNmClusterCoupling

Class	CanPhysicalChannel			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology			
Note	CAN bus specific physical channel attributes.			
Base	ARObject, AbstractCanPhysicalChannel, Identifiable, MultilanguageReferrable, PhysicalChannel, Referrable			
Aggregated by	CommunicationCluster.physicalChannel			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.169: CanPhysicalChannel

Class	CanTpAddress			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	An ECUs TP address on the referenced channel. This represents the diagnostic Address.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	CanTpConfig.tpAddress			
Attribute	Type	Mult.	Kind	Note
tpAddress	Integer	0..1	attr	An ECUs TP address on the referenced channel. This represents the diagnostic Address.
tpAddressExtensionValue	Integer	0..1	attr	If the mixed addressing format is used, this parameter contains the transport protocol address extension value.

Table A.170: CanTpAddress

Class	CanTpChannel			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	Configuration parameters of the CanTp channel.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	CanTpConfig.tpChannel			
Attribute	Type	Mult.	Kind	Note
channelId	PositiveInteger	0..1	attr	The id of the channel. The value shall be unique for each channel.

Table A.171: CanTpChannel

Class	CanTpConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	This element defines exactly one CAN TP Configuration. One CanTpConfig element shall be created for each CAN Network in the System. Tags: atp.recommendedPackage=TpConfigs			
Base	ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, TpConfig			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
tpAddress	CanTpAddress	*	aggr	Collection of TP Addresses. atpVariation: Derived, because EcuInstance can vary. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=tpAddress.shortName, tpAddress.variation Point.shortLabel vh.latestBindingTime=postBuild
tpChannel	CanTpChannel	*	aggr	Configuration of CAN TP channels. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=tpChannel.shortName, tpChannel.variation Point.shortLabel vh.latestBindingTime=postBuild
tpConnection	CanTpConnection	*	aggr	Senders and receivers of CAN TP messages. atpVariation: Derived, because TpNode can vary. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=tpConnection, tpConnection.variation Point.shortLabel vh.latestBindingTime=postBuild
tpEcu	CanTpEcu	*	aggr	Collection of TP Ecus atpVariation: Derived, because EcuInstance can vary. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=tpEcu, tpEcu.variationPoint.shortLabel vh.latestBindingTime=postBuild
tpNode	CanTpNode	*	aggr	Senders and receivers of Can TP messages. atpVariation: Derived, because EcuInstance can vary. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=tpNode.shortName, tpNode.variation Point.shortLabel vh.latestBindingTime=postBuild

Table A.172: CanTpConfig

Class	CanTpConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	A connection identifies the sender and the receiver of this particular communication. The CanTp module routes a Pdu through this connection. atpVariation: Derived, because TpNode can vary.			
Base	ARObject, TpConnection			
Aggregated by	CanTpConfig.tpConnection			





Class		CanTpConnection		
Attribute	Type	Mult.	Kind	Note
addressing Format	CanTpAddressing FormatType	0..1	attr	Declares which communication addressing mode is supported.
cancellation	Boolean	0..1	attr	With this switch Tx Cancellation can be turned on or off. Please note that the Rx Cancellation is always enabled.
canTpChannel	CanTpChannel	0..1	ref	Reference to the CanTpChannel on which this CanTp Connection is realized.
dataPdu	NPdu	0..1	ref	Reference to an Data NPdu.
flowControlPdu	NPdu	0..1	ref	Reference to the Flow Control NPdu.
maxBlockSize	Integer	0..1	attr	The maximum number of N-PDUs the CanTp receiver allows the sender to send, before waiting for an authorization to continue transmission of the following N-PDUs. For further details on this parameter value see ISO 15765-2 specification. Note: For reasons of buffer length, the CAN Transport Layer can adapt the BS value within the limit of this maximum BS
multicast	CanTpAddress	0..1	ref	TP address for 1:n connections.
padding Activation	Boolean	0..1	attr	This specifies whether or not Sfs, FCs and the last CF shall be padded to 8 bytes length in case it contains less payload. true: The N-PDU received uses padding for SF, FC and the last CF. (N-PDU length is always 8 bytes) false: The N-PDU received does not use padding for SF, CF and the last CF. (N-PDU length is dynamic)
receiver	CanTpNode	*	ref	The target of the TP connection.
taType	NetworkTargetAddress Type	0..1	attr	Network Target Address type.
timeoutBr	TimeValue	0..1	attr	Value in seconds of the performance requirement for (N_Br + N_Ar). N_Br is the elapsed time between the receiving indication of a FF or CF or the transmit confirmation of a FC, until the transmit request of the next FC.
timeoutBs	TimeValue	0..1	attr	This parameter defines the timeout for waiting for an FC or AF on the sender side in an 1:1 connection. Specified in seconds.
timeoutCr	TimeValue	0..1	attr	This parameter defines the timeout value for waiting for a CF or FF-x (in case of retry) after receiving the last CF or after sending an FC or AF on the receiver side. Specified in seconds.
timeoutCs	TimeValue	0..1	attr	The attribute timeoutCs represents the time (in seconds) which elapses between the transmit request of a CF N-PDU until the transmit request of the next CF N-PDU.
tpSdu	IPdu	0..1	ref	Reference to an IPdu that is segmented by the Transport Protocol.
transmitter	CanTpNode	0..1	ref	The source of the TP connection.

Table A.173: CanTpConnection

Class	CanTpEcu			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	ECU specific TP configuration parameters. Each TpEcu element has a reference to exactly one ECUInstance in the topology.			
Base	ARObject			
Aggregated by	CanTpConfig.tpEcu			
Attribute	Type	Mult.	Kind	Note
cycleTimeMainFunction	TimeValue	0..1	attr	The period between successive calls to the Main Function of the AUTOSAR TP. Specified in seconds.
ecuInstance	EcuInstance	0..1	ref	Connection to the ECUInstance in the Topology

Table A.174: CanTpEcu

Class	CanTpNode			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	TP Node (Sender or Receiver) provides the TP Address and the connection to the Topology description.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CanTpConfig.tpNode			
Attribute	Type	Mult.	Kind	Note
connector	CommunicationConnector	0..1	ref	Association to a CommunicationConnector in the topology description. In a System Description this reference is mandatory. In an ECU Extract this reference is optional (references to ECUs that are not part of the ECU Extract shall be avoided).
maxFcWait	Integer	0..1	attr	This attribute defines the maximum number of flow control PDUs that can be consecutively be transmitted by a receiver.
stMin	TimeValue	0..1	attr	Sets the duration of the minimum time the CanTp sender shall wait between the transmissions of two CF N-PDUs.
timeoutAr	TimeValue	0..1	attr	This attribute states the timeout between the PDU transmit request of the Transport Layer to the Can Interface and the corresponding confirmation of the Can Interface on the receiver side (for FC or AF). Specified in seconds.
timeoutAs	TimeValue	0..1	attr	This attribute states the timeout between the PDU transmit request for the first PDU of the group used in the current connection of the Transport Layer to the Can Interface and the corresponding confirmation of the Can Interface (when having sent the last PDU of the group used in this connection) on the sender side (SF-x, FF-x, CF or FC (in case of Transmit Cancellation)). Specified in seconds.
tpAddress	CanTpAddress	0..1	ref	Reference to the TP Address that is used by the TpNode. This reference is optional in case that the multicast TP Address is used (reference from TpConnection).

Table A.175: CanTpNode

Class	CanXIframeTriggeringProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanCommunication			
Note	This element indicates the frame being CAN XL and contains further CAN XL specific attributes.			
Base	ARObject			
Aggregated by	CanFrameTriggering.canXIframeTriggeringProps			





Class				
CanXIframeTriggeringProps				
Attribute	Type	Mult.	Kind	Note
acceptanceField	PositiveInteger	0..1	attr	Acceptance field of a CAN XL message.
priorityId	PositiveInteger	0..1	attr	Priority ID of a CAN XL message.
sduType	PositiveInteger	0..1	attr	SDU type of a CAN XL message.
vcid	PositiveInteger	0..1	attr	Virtual CAN network ID of a CAN XL message.

Table A.176: CanXIframeTriggeringProps

Class				
Caption				
Package M2::MSR::Documentation::BlockElements				
Note This meta-class represents the ability to express a caption which is a title, and a shortName.				
Base <i>ARObject</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>				
Aggregated by MIFigure.figureCaption, MIFormula.formulaCaption, Table.tableCaption				
Attribute	Type	Mult.	Kind	Note
desc	MultiLanguageOverviewParagraph	0..1	aggr	This represents a general but brief (one paragraph) description what the object in question is about. It is only one paragraph! This property helps a human reader to identify the object in question. Tags: xml.sequenceOffset=10

Table A.177: Caption

Class				
Chapter				
Package M2::MSR::Documentation::Chapters				
Note This meta-class represents a chapter of a document. Chapters are the primary structuring element in documentation.				
Base <i>ARObject</i> , <i>DocumentViewSelectable</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Paginateable</i> , <i>Referrable</i>				
Aggregated by ChapterOrMsrQuery.chapter, MsrQueryResultChapter.chapter, SwComponentDocumentation.chapter, SwComponentDocumentation.swCalibrationNotes, SwComponentDocumentation.swCarbDoc, SwComponentDocumentation.swDiagnosticsNotes, SwComponentDocumentation.swFeatureDef, SwComponentDocumentation.swFeatureDesc, SwComponentDocumentation.swMaintenanceNotes, SwComponentDocumentation.swTestDesc, <i>System.systemDocumentation</i>				
Attribute	Type	Mult.	Kind	Note
chapterModel	ChapterModel	1	aggr	This represents the overall contents of the chapter. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.typeElement=false xml.typeWrapperElement=false
helpEntry	String	0..1	attr	This specifies an entry point in an online help system to be linked with the parent class. The syntax shall be defined by the applied help system respectively help system generator. Maybe it is a concatenated Identifier, but as of now we leave it as an arbitrary string. Tags: xml.attribute=true

Table A.178: Chapter

Class	ClassContentConditional			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	Specifies the valid content of the class. The content can optionally depend on a condition. (E.g. value of attribute 'category')			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ClassTailoring.classContent			
Attribute	Type	Mult.	Kind	Note
attribute Tailoring	AttributeTailoring	*	aggr	Tailorings of the owned and inherited attributes of this Meta Classes Tags: xml.sequenceOffset=20
condition	AbstractCondition	0..1	aggr	The rules on the content of this class are enabled if the condition validates to true. Tags: xml.sequenceOffset=10
constraint Tailoring	ConstraintTailoring	*	aggr	Specification of tailorings of Constraints of that are owned by this Meta Classes Tags: xml.sequenceOffset=30
sdgTailoring	SdgTailoring	*	aggr	Specification of the applicable Special Data Group Tags: xml.sequenceOffset=40

Table A.179: ClassContentConditional

Class	ClassTailoring (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	The ClassTailoring is an abstract class that allows the tailoring of its attributes, applicable constraints and Sdgs.			
Base	ARObject			
Subclasses	AbstractClassTailoring , ConcreteClassTailoring			
Aggregated by	AggregationTailoring.typeTailoring , DataFormatTailoring.classTailoring , ReferenceTailoring.typeTailoring			
Attribute	Type	Mult.	Kind	Note
classContent	ClassContentConditional	*	aggr	Specifies the accepted / not accepted content of the class. All rules apply that fulfill the condition of the ClassContentConditional Tags: xml.sequenceOffset=30
multiplicity Restriction	MultiplicityRestrictionWithSeverity	0..1	aggr	Specifies the multiplicity of the class in the current context. Tags: xml.sequenceOffset=10
variation Restriction	VariationRestrictionWithSeverity	0..1	aggr	Specifies restrictions on the usage of variant handling. Tags: xml.sequenceOffset=20

Table A.180: ClassTailoring

Class	ClientComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Client-specific communication attributes (RPortPrototype typed by ClientServerInterface).			
Base	ARObject, RPortComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec , PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note





Class	ClientComSpec			
endToEndCallResponseTimeout	TimeValue	0..1	attr	This attribute defines the maximum time interval in which the application shall expect the servers's response (time between the sending of the call invocation until the arrival of the server's response).
operation	ClientServerOperation	0..1	ref	This represents the corresponding ClientServerOperation.
transformationComSpecProps	TransformationComSpecProps	*	aggr	This references the TransformationComSpecProps which define port-specific configuration for data transformation.

Table A.181: ClientComSpec

Class	ClientIdDefinition			
Package	M2::AUTOSARTemplates::SystemTemplate			
Note	Several clients in one client-ECU can communicate via inter-ECU client-server communication with a server on a different ECU, if a client identifier is used to distinguish the different clients. The Client Identifier of the transaction handle that is used by the RTE can be defined by this element.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ClientIdDefinitionSet.clientIdDefinition			
Attribute	Type	Mult.	Kind	Note
clientId	Numerical	0..1	attr	The Client Identifier of the transaction handle used for an inter-ECU client server communication is defined by this attribute. If defined the RTE generator shall use this client Id.
clientServerOperation	ClientServerOperation	0..1	iref	Reference to the ClientServerOperation that is called by the client. InstanceRef implemented by: OperationInSystemInstanceRef

Table A.182: ClientIdDefinition

Class	ClientIdRange			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	With this element it is possible to restrict the Client Identifier of the transaction handle that is generated by the client RTE for inter-Ecu Client/Server communication to an allowed range of numerical values.			
Base	ARObject			
Aggregated by	EcuInstance.clientIdRange			
Attribute	Type	Mult.	Kind	Note
lowerLimit	Limit	0..1	attr	This specifies the lower limit of the ClientIdRange. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
upperLimit	Limit	0..1	attr	This specifies the upper limit of the ClientIdRange. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.183: ClientIdRange

Class	ClientServerAnnotation			
Package	M2::AUTOSARTemplates::SWComponentTemplate::ApplicationAttributes			
Note	Annotation to a port regarding a certain Operation.			
Base	ARObject, GeneralAnnotation			
Aggregated by	PortPrototype.clientServerAnnotation			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	0..1	ref	This represents the ClientServerOperation that the Client ServerAnnotation corresponds to.

Table A.184: ClientServerAnnotation

Class	ClientServerApplicationErrorMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This meta-class represents the ability to map ApplicationErrors onto each other.			
Base	ARObject			
Aggregated by	ClientServerInterfaceMapping.errorMapping			
Attribute	Type	Mult.	Kind	Note
firstApplication Error	ApplicationError	0..1	ref	This represents the first ApplicationError in the context of the ClientServerApplicationErrorMapping.
second ApplicationError	ApplicationError	0..1	ref	This represents the second ApplicationError in the context of the ClientServerApplicationErrorMapping.

Table A.185: ClientServerApplicationErrorMapping

Class	ClientServerInterface			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	A client/server interface declares a number of operations that can be invoked on a server by a client. Tags: atp.recommendedPackage=PortInterfaces			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	*	aggr	ClientServerOperation(s) of this ClientServerInterface. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=operation.shortName, operation.variation Point.shortLabel vh.latestBindingTime=blueprintDerivationTime
possibleError	ApplicationError	*	aggr	Application errors that are defined as part of this interface.

Table A.186: ClientServerInterface

Class	ClientServerInterfaceMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Defines the mapping of ClientServerOperations in context of two different ClientServerInterfaces.			
Base	ARObject , AtpBlueprint , AtpBlueprintable , Identifiable , MultilanguageReferrable , PortInterfaceMapping , Referrable			
Aggregated by	PortInterfaceMappingSet.portInterfaceMapping			
Attribute	Type	Mult.	Kind	Note





Class	ClientServerInterfaceMapping			
errorMapping	ClientServerApplicationErrorMapping	*	aggr	Map two different ApplicationErrors defined in the context of two different ClientServerInterfaces.
operation Mapping	ClientServerOperationMapping	*	aggr	Mapping of two ClientServerOperations in two different ClientServerInterfaces Stereotypes: atpSplittable Tags: atp.Splitkey=operationMapping

Table A.187: ClientServerInterfaceMapping

Class	ClientServerInterfaceToBswModuleEntryBlueprintMapping			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::ClientServerInterfaceToBswModuleEntryMapping			
Note	This represents a mapping between one ClientServerInterface blueprint and BswModuleEntry blueprint in order to express the intended implementation of ClientServerOperations by specific BswModuleEntries under consideration of PortDefinedArguments. Such a mapping enables the formal check whether the number of arguments and the data types of arguments of the operation + additional PortDefined Arguments matches the signature of the BswModuleEntry. Tags: atp.recommendedPackage=BlueprintMappingSets			
Base	ARElement , ARObject , AtpBlueprint , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
clientServer Interface	ClientServerInterface	1	ref	The referenced ClientServerInterface represents the client server interface the mapping is dedicated to.
operation Mapping	ClientServerOperationBlueprintMapping	1..*	aggr	This specifies the operations used in the mapping between the ClientServerInterface and the BswModuleEntry. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=operationMapping, operationMapping.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
portDefined Argument Blueprint (ordered)	PortDefinedArgument Blueprint	*	aggr	This specifies the PortDefinedArguments used in the mapping between the ClientServerInterface and the BswModuleEntry. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=portDefinedArgumentBlueprint, portDefinedArgumentBlueprint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.188: ClientServerInterfaceToBswModuleEntryBlueprintMapping

Class	ClientServerOperation
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface
Note	An operation declared within the scope of a client/server interface.
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable
Aggregated by	ApplicationInterface.command, AtpClassifier.atpFeature , ClientServerInterface.operation , DiagnosticDataElementInterface.read, DiagnosticDataIdentifierInterface.read, DiagnosticDataIdentifierInterface.write, DiagnosticRoutineInterface.requestResult, DiagnosticRoutineInterface.start, DiagnosticRoutineInterface.stop, PhmRecoveryActionInterface.recovery, ServiceInterface.method





Class		ClientServerOperation		
Attribute	Type	Mult.	Kind	Note
argument (ordered)	ArgumentDataPrototype	*	aggr	An argument of this ClientServerOperation Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=argument.shortName, argument.variation Point.shortLabel vh.latestBindingTime=blueprintDerivationTime
diagArgIntegrity	Boolean	0..1	attr	This attribute shall only be used in the implementation of diagnostic routines to support the case where input and output arguments are allocated in a shared buffer and might unintentionally overwrite input arguments by tentative write operations to output arguments. This situation can happen during sliced execution or while output parameters are arrays (call by reference). The value true means that the ClientServerOperation is aware of the usage of a shared buffer and takes precautions to avoid unintentional overwrite of input arguments. If the attribute does not exist or is set to false the Client ServerOperation does not have to consider the usage of a shared buffer.
possibleError	ApplicationError	*	ref	Possible errors that may be raised by the referring operation.

Table A.189: ClientServerOperation

Class		ClientServerOperationBlueprintMapping		
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::ClientServerInterfaceToBswModuleEntryMapping			
Note	This class describes a specific mapping between a ClientServerOperation in a ClientServerInterface blueprint and a BswModuleEntry blueprint.			
Base	<i>ARObject</i>			
Aggregated by	ClientServerInterfaceToBswModuleEntryBlueprintMapping.operationMapping			
Attribute	Type	Mult.	Kind	Note
blueprint MappingGuide	DocumentationBlock	0..1	aggr	This attribute offers the possibility to provide additional information with respect to the mapping.
bswModule Entry	BswModuleEntry	1	ref	The referenced BswModuleEntry represents the Bsw ModuleEntry the mapping is dedicated to.
clientServer Operation	ClientServerOperation	1	ref	The referenced ClientServerOperation represents the client server operation the mapping is dedicated to.

Table A.190: ClientServerOperationBlueprintMapping

Class		ClientServerOperationMapping		
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Defines the mapping of two particular ClientServerOperations in context of two different ClientServer Interfaces.			
Base	<i>ARObject</i>			
Aggregated by	ClientServerInterfaceMapping.operationMapping			
Attribute	Type	Mult.	Kind	Note





Class	ClientServerOperationMapping			
argument Mapping	DataPrototypeMapping	*	aggr	Defines the mapping of two particular ArgumentData Prototypes with unequal names or unequal semantic (resolution or range) in context of Operations. Stereotypes: atpSplitable Tags: atp.Splitkey=argumentMapping
firstOperation	ClientServerOperation	0..1	ref	First to-be-mapped ClientServerOperation of a Client ServerInterface.
firstToSecond Data Transformation	DataTransformation	0..1	ref	This reference indicates that a DataTransformation is intended in the context of the ClientServerOperation Mapping.
second Operation	ClientServerOperation	0..1	ref	Second to-be-mapped ClientServerOperation of a Client ServerInterface.

Table A.191: ClientServerOperationMapping

Class	ClientServerToSignalMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	This element maps the ClientServerOperation to call- and return-SystemSignals.			
Base	ARObject , DataMapping			
Aggregated by	SystemMapping.dataMapping			
Attribute	Type	Mult.	Kind	Note
callSignal	SystemSignal	0..1	ref	Reference to the callSignal to which the IN and INOUT ArgumentDataPrototypes are mapped.
clientServer Operation	ClientServerOperation	0..1	iref	Reference to a ClientServerOperation, which is mapped to a call SystemSignal and a return SystemSignal. InstanceRef implemented by: OperationInSystem InstanceRef
returnSignal	SystemSignal	0..1	ref	Reference to the returnSignal to which the OUT and INOUT ArgumentDataPrototypes are mapped.

Table A.192: ClientServerToSignalMapping

Class	Code			
Package	M2::AUTOSARTemplates::CommonStructure::Implementation			
Note	A generic code descriptor. The type of the code (source or object) is defined via the category attribute of the associated engineering object.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	Implementation.codeDescriptor			
Attribute	Type	Mult.	Kind	Note
artifact Descriptor	AutosarEngineering Object	*	aggr	Refers to the artifact belonging to this code descriptor.
callbackHeader	ServiceNeeds	*	ref	The association callbackHeader describes in which header files the function declarations of callback functions are provided to a service module. With this information the service module can include the appropriate header files in its configuration files.

Table A.193: Code

Class	Collection			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::ElementCollection			
Note	<p>This meta-class specifies a collection of elements. A collection can be utilized to express additional aspects for a set of elements.</p> <p>Note that Collection is an ARElement. Therefore it is applicable e.g. for EvaluatedVariant, even if this is not obvious.</p> <p>Usually the category of a Collection is "SET". On the other hand, a Collection can also express an arbitrary relationship between elements. This is denoted by the category "RELATION" (see also [TPS_GST_00347]).</p> <p>In this case the collection represents an association from "sourceElement" to "targetElement" in the role "role".</p> <p>Tags: atp.recommendedPackage=Collections</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
autoCollect	AutoCollectEnum	0..1	attr	<p>This attribute reflects how far the referenced objects are part of the collection.</p> <p>Tags: xml.sequenceOffset=20</p>
collected Instance	AtpFeature	*	iref	<p>This instance ref supports the use case that a particular instance is part of the collection.</p> <p>Tags: xml.sequenceOffset=60 InstanceRef implemented by: AnyInstanceRef</p>
collection Semantics	NameToken	0..1	attr	<p>Provides the ability to express the semantics of a Collection depending on the intended use case. The collectionSemantics is specified as a NameToken which must be agreed by all stakeholders.</p> <p>Tags: xml.sequenceOffset=25</p>
element	Identifiable	*	ref	<p>This is an element in the collection. Note that Collection itself is collectable. Therefore collections can be nested.</p> <p>In case of category="RELATION" this represents the target end of the relation.</p> <p>Tags: xml.sequenceOffset=40</p>
elementRole	Identifier	0..1	attr	<p>This attribute allows to denote a particular role of the collection. Note that the applicable semantics shall be mutually agreed between the two parties.</p> <p>In particular it denotes the role of element in the context of sourceElement.</p> <p>Tags: xml.sequenceOffset=30</p>
sourceElement	Identifiable	*	ref	<p>Only if Category = "RELATION". This represents the source of a relation.</p> <p>Tags: xml.sequenceOffset=50</p>
sourceInstance	AtpFeature	*	iref	<p>Only if Category = "RELATION". This represents the source instance of a relation.</p> <p>Tags: xml.sequenceOffset=70 InstanceRef implemented by: AnyInstanceRef</p>

Table A.194: Collection

Class	CommConnectorPort (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	<p>The Ecu communication relationship defines which signals, Pdus and frames are actually received and transmitted by this ECU.</p> <p>For each signal, Pdu or Frame that is transmitted or received and used by the Ecu an association between an ISignalPort, IPduPort or FramePort with the corresponding Triggering shall be created. An ISignalPort shall be created only if the corresponding signal is handled by COM (RTE or Signal Gateway). If a Pdu Gateway ECU only routes the Pdu without being interested in the content only a FramePort and an IPduPort needs to be created.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	FramePort , IPduPort , ISignalPort			
Aggregated by	CommunicationConnector.ecuCommPortInstance			
Attribute	Type	Mult.	Kind	Note
communication Direction	CommunicationDirectionType	0..1	attr	Communication Direction of the Connector Port (input or output Port).

Table A.195: CommConnectorPort

Class	CommunicationBufferLocking			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::PortAPIOptions			
Note	The aggregation of this meta-class specifies that a RunnableEntity supports locked communication buffers supplied by the RTE. It is able to cope with the error RTE_E_COM_BUSY.			
Base	ARObject, SwcSupportedFeature			
Aggregated by	PortAPIOption.supportedFeature			
Attribute	Type	Mult.	Kind	Note
supportBuffer Locking	SupportBufferLockingEnum	0..1	attr	This attribute is used to indicate the intended buffer locking behavior.

Table A.196: CommunicationBufferLocking

Class	«atpVariation» CommunicationCluster (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	<p>The CommunicationCluster is the main element to describe the topological connection of communicating ECUs.</p> <p>A cluster describes the ensemble of ECUs, which are linked by a communication medium of arbitrary topology (bus, star, ring, ...). The nodes within the cluster share the same communication protocol, which may be event-triggered, time-triggered or a combination of both.</p> <p>A CommunicationCluster aggregates one or more physical channels.</p> <p>Tags: vh.latestBindingTime=postBuild</p>			
Base	ARElement, ARObject, CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Subclasses	AbstractCanCluster , EthernetCluster , FlexrayCluster , LinCluster , UserDefinedCluster			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
baudrate	PositiveUnlimitedInteger	0..1	attr	Channels speed in bits/s.





Class	«atpVariation» CommunicationCluster (abstract)			
physical Channel	PhysicalChannel	*	aggr	This relationship defines which channel element belongs to which cluster. A channel shall be assigned to exactly one cluster, whereas a cluster may have one or more channels. Note: This atpSplitable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplitable; atpVariation Tags: vh.latestBindingTime=systemDesignTime
protocolName	String	0..1	attr	The name of the protocol used.
protocolVersion	String	0..1	attr	The version of the protocol used.

Table A.197: CommunicationCluster

Class	CommunicationConnector (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	The connection between the referencing ECU and the referenced channel via the referenced controller. Connectors are used to describe the bus interfaces of the ECUs and to specify the sending/receiving behavior. Each CommunicationConnector has a reference to exactly one communicationController. Note: Several CommunicationConnectors can be assigned to one PhysicalChannel in the scope of one ECU Instance.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>AbstractCanCommunicationConnector</i> , <i>EthernetCommunicationConnector</i> , <i>FlexrayCommunicationConnector</i> , <i>LinCommunicationConnector</i> , <i>UserDefinedCommunicationConnector</i>			
Aggregated by	<i>EcuInstance.connector</i> , <i>MachineDesign.communicationConnector</i>			
Attribute	Type	Mult.	Kind	Note
commController	CommunicationController	0..1	ref	Reference to the communication controller. The CommunicationConnector and referenced CommunicationController shall be aggregated by the same ECUInstance. The communicationController can be referenced by several CommunicationConnector elements. This is important for the FlexRay Bus. FlexRay communicates via two physical channels. But only one controller in an ECU is responsible for both channels. Thus, two connectors (for channel A and for channel B) shall reference to the same controller.
createEcuWakeupSource	Boolean	0..1	attr	If this parameter is available and set to true then a channel wakeup source shall be created for the Physical Channel referencing this CommunicationConnector.
dynamicPncToChannelMappingEnabled	Boolean	0..1	attr	Defines if this EcuInstance shall implement the dynamic PNC-to-channel-mapping functionality on this CommunicationConnector and its respective Physical Channel. Tags: atp.Status=draft
ecuCommPortInstance	CommConnectorPort	*	aggr	An ECUs reception or send ports. atpVariation: If signals/PDUs/frames are variable, the corresponding ports shall be variable, too. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=ecuCommPortInstance.shortName, ecuCommPortInstance.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	CommunicationConnector (abstract)			
pncFilterArray Mask (ordered)	PositiveInteger	*	attr	Bit mask for NM-Pdu Payload used to configure the NM filter mask for the Network Management.
pncGateway Type	PncGatewayTypeEnum	0..1	attr	Defines if this EcuInstance shall implement the Pnc Gateway functionality on this CommunicationConnector and its respective PhysicalChannel. Several Ecu Instances on the same PhysicalChannel can have the PncGateway functionality enabled, but only one of them shall have the pncGatewayType "active".

Table A.198: CommunicationConnector

Class	«atpVariation» CommunicationController (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	The communication controller is a dedicated hardware device by means of which hosts are sending frames to and receiving frames from the communication medium. Tags: vh.latestBindingTime=postBuild			
Base	<i>ARObject</i> , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	<i>AbstractCanCommunicationController</i> , EthernetCommunicationController , <i>FlexrayCommunicationController</i> , LinCommunicationController , <i>UserDefinedCommunicationController</i>			
Aggregated by	EcuInstance.commController , <i>MachineDesign.communicationController</i>			
Attribute	Type	Mult.	Kind	Note
wakeUpBy Controller Supported	Boolean	0..1	attr	Defines whether the ECU shall be woken up by this CommunicationController. TRUE: wake up is possible FALSE: wake up is not supported Note: If wakeUpByControllerSupported is set to TRUE the feature shall be supported by both hardware and basic software.

Table A.199: CommunicationController

Class	CommunicationControllerMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::ECUResourceMapping			
Note	CommunicationControllerMapping specifies the CommunicationPeripheral hardware (defined in the ECU Resource Template) to realize the specified CommunicationController in a physical topology.			
Base	<i>ARObject</i>			
Aggregated by	ECUMapping.commControllerMapping			
Attribute	Type	Mult.	Kind	Note
communication Controller	CommunicationController	0..1	ref	Reference to the CommunicationController in the System Template
hw Communication Controller	HwElement	0..1	ref	Reference to a HwElement of category Communication Controller in the ECU Resource Template.

Table A.200: CommunicationControllerMapping

Class	CommunicationCycle (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	The communication cycle where the frame is sent.			
Base	ARObject			
Subclasses	CycleCounter , CycleRepetition			
Aggregated by	FlexrayAbsolutelyScheduledTiming.communicationCycle , TtcanAbsolutelyScheduledTiming.communicationCycle			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.201: CommunicationCycle

Enumeration	CommunicationDirectionType
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	Describes the communication direction.
Aggregated by	CommConnectorPort.communicationDirection , IEEE1722TpConnection.communicationDirection , IPSecRule.direction , ISignalIPduGroup.communicationDirection
Literal	Description
in	Reception (Input) Tags: atp.EnumerationLiteralIndex=0
out	Transmission (Output) Tags: atp.EnumerationLiteralIndex=1

Table A.202: CommunicationDirectionType

Class	ComplexDeviceDriverSwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	The ComplexDeviceDriverSwComponentType is a special AtomicSwComponentType that has direct access to hardware on an ECU and which is therefore linked to a specific ECU or specific hardware. The ComplexDeviceDriverSwComponentType introduces the possibility to link from the software representation to its hardware description provided by the ECU Resource Template. Tags: atp.recommendedPackage=SwComponentTypes			
Base	ARElement , ARObject , AtomicSwComponentType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
hardware Element	HwDescriptionEntity	*	ref	Reference from the ComplexDeviceDriverSwComponent Type to the description of the used HwElements.

Table A.203: ComplexDeviceDriverSwComponentType

Class	ComponentClustering
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping
Note	Constraint that forces the mapping of all referenced SW component instances to the same ECU, Core, Partition depending on the defined mappingScope attribute. If mappingScope is not specified then mappingScopeEcu shall be assumed.
Base	ARObject , MappingConstraint
Aggregated by	SystemMapping.mappingConstraint





Class		ComponentClustering		
Attribute	Type	Mult.	Kind	Note
clustered Component	SwComponent Prototype	*	iref	Reference to the components that have to be mapped together. InstanceRef implemented by: ComponentInSystem InstanceRef
mappingScope	MappingScopeEnum	0..1	attr	This attribute indicates whether the ComponentClustering mapping constraint applies to different ECUs, partitions or cores. If this attribute is not specified then mappingScope Ecu shall be assumed.

Table A.204: ComponentClustering

Class		ComponentSeparation		
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	Constraint that forces the two referenced SW components (called A and B in the following) not to be mapped to the same ECU, Core, Partition depending on the defined mappingScope attribute. If mapping Scope is not specified then mappingScopeEcu shall be assumed. If a SW component (e.g. A) is a composition, none of the atomic SW components making up the A composition shall be mapped together with any of the atomic SW components making up the B composition. Furthermore, A and B shall be disjoint.			
Base	<i>ARObject</i> , <i>MappingConstraint</i>			
Aggregated by	SystemMapping.mappingConstraint			
Attribute	Type	Mult.	Kind	Note
mappingScope	MappingScopeEnum	0..1	attr	This attribute indicates whether the Component Separation mapping constraint applies to different ECUs, partitions or cores. If this attribute is not specified then mappingScopeEcu shall be assumed.
separated Component	SwComponent Prototype	0..2	iref	The two components that have to be mapped to different ECUs InstanceRef implemented by: ComponentInSystem InstanceRef

Table A.205: ComponentSeparation

Class		CompositeNetworkRepresentation		
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	This meta-class is used to define the network representation of leaf elements of composite application data types.			
Base	<i>ARObject</i>			
Aggregated by	ReceiverComSpec.compositeNetworkRepresentation , SenderComSpec.compositeNetworkRepresentation			
Attribute	Type	Mult.	Kind	Note
leafElement	ApplicationComposite ElementDataPrototype	0..1	iref	This represents that leaf element of an application composite data type. InstanceRef implemented by: ApplicationComposite ElementInPortInterfaceInstanceRef





Class	CompositeNetworkRepresentation			
network Representation	SwDataDefProps	0..1	aggr	<p>The SwDataDefProps owned by the CompositeNetworkRepresentation are used to define the network representation of the leaf element of an Application CompositeDataType.</p> <p>Stereotypes: atpSplittable Tags: atp.Splitkey=networkRepresentation</p>

Table A.206: CompositeNetworkRepresentation

Class	CompositeRuleBasedValueSpecification				
Package	M2::AUTOSARTemplates::CommonStructure::Constants				
Note	This meta-class represents rule-based values for DataPrototypes typed by composite AutosarDataTypes.				
Base	<i>ARObject</i> , AbstractRuleBasedValueSpecification , ValueSpecification				
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue				
Attribute	Type	Mult.	Kind	Note	
argument (ordered)	CompositeValueSpecification	*	aggr	<p>This represents the collection of aggregated Value Specifications. The last ValueSpecification in the collection shall be taken to execute the filling rule.</p> <p>Tags: xml.sequenceOffset=30</p>	
compound Primitive Argument (ordered)	CompositeRuleBasedValueArgument	*	aggr	<p>This represents the collection of aggregated Value Specifications for compound primitive data type. The last ValueSpecification in the collection shall be taken to execute the filling rule.</p> <p>Tags: xml.sequenceOffset=35</p>	
maxSizeToFill	PositiveInteger	0..1	attr	<p>If a rule is chosen which does not fill until the end, this determines until which size the rule shall fill the values.</p> <p>Tags: xml.sequenceOffset=40</p>	
rule	Identifier	0..1	attr	<p>This denotes the name of the rule of the RuleBasedValue Specification. The rule determines the calculation specification according which the arguments are used to calculated the values.</p> <p>Tags: xml.sequenceOffset=20</p>	

Table A.207: CompositeRuleBasedValueSpecification

Class	<i>CompositeValueSpecification</i> (abstract)
Package	M2::AUTOSARTemplates::CommonStructure::Constants
Note	This abstract meta-class acts a base class for ValueSpecifications that have a composite form.
Base	<i>ARObject</i> , ValueSpecification





Class	CompositeValueSpecification (abstract)			
Subclasses	ArrayValueSpecification, RecordValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, CompositeRuleBasedValueSpecification.argument, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeipEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.208: CompositeValueSpecification

Class	CompositionSwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	A <code>CompositionSwComponentType</code> aggregates <code>SwComponentPrototypes</code> (that in turn are typed by <code>SwComponentTypes</code>) as well as <code>SwConnectors</code> for primarily connecting <code>SwComponentPrototypes</code> among each others and towards the surface of the <code>CompositionSwComponentType</code> . By this means, a hierarchical structures of software-components can be created. Tags: atp.recommendedPackage=SwComponentTypes			
Base	<code>ARElement</code> , <code>ARObject</code> , <code>AtpBlueprint</code> , <code>AtpBlueprintable</code> , <code>AtpClassifier</code> , <code>AtpType</code> , <code>CollectableElement</code> , <code>Identifiable</code> , <code>MultilanguageReferrable</code> , <code>PackageableElement</code> , <code>Referrable</code> , <code>SwComponentType</code>			
Aggregated by	<code>ARPackage.element</code>			
Attribute	Type	Mult.	Kind	Note
component	<code>SwComponentPrototype</code>	*	aggr	The instantiated components that are part of this composition. The aggregation of <code>SwComponentPrototype</code> is subject to variability with the purpose to support the conditional existence of a <code>SwComponentPrototype</code> . Please be aware: if the conditional existence of <code>SwComponentPrototypes</code> is resolved post-build, the deselected <code>SwComponentPrototypes</code> are still contained in the ECUs build but the instances are inactive in that they are not scheduled by the RTE. The aggregation is marked as <code>atpSplitable</code> in order to allow the addition of service components to the ECU extract during the ECU integration. The use case for having 0 components owned by the <code>CompositionSwComponentType</code> could be to deliver an empty <code>CompositionSwComponentType</code> to e.g. a supplier for filling the internal structure. Stereotypes: <code>atpSplitable</code> ; <code>atpVariation</code> Tags: <code>atp.Splitkey=component.shortName, component.variationPoint.shortLabel</code> <code>vh.latestBindingTime=postBuild</code>





Class	CompositionSwComponentType			
connector	SwConnector	*	aggr	<p>SwConnectors have the principal ability to establish a connection among PortPrototypes. They can have many roles in the context of a CompositionSwComponentType. Details are refined by subclasses.</p> <p>The aggregation of SwConnectors is subject to variability with the purpose to support variant data flow.</p> <p>The aggregation is marked as atpSplitable in order to allow the extension of the ECU extract with AssemblySwConnectors between ApplicationSwComponentTypes and ServiceSwComponentTypes during the ECU integration.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=connector.shortName, connector.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
constantValue Mapping	ConstantSpecificationMappingSet	*	ref	<p>Reference to the ConstantSpecificationMapping to be applied for initValues of PPortComSpecs and RPortComSpec.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=constantValueMapping</p>
dataType Mapping	DataTypeMappingSet	*	ref	<p>Reference to the DataTypeMappingSet to be applied for the used ApplicationDataTypes in PortInterfaces.</p> <p>Background: when developing subsystems it may happen that ApplicationDataTypes are used on the surface of CompositionSwComponentTypes. In this case it would be reasonable to be able to also provide the intended mapping to the ImplementationDataTypes. However, this mapping shall be informal and not technically binding for the implementors mainly because the RTE generator is not concerned about the CompositionSwComponentTypes.</p> <p>Rationale: if the mapping of ApplicationDataTypes on the delegated and inner PortPrototype matches then the mapping to ImplementationDataTypes is not impacting compatibility.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=dataTypeMapping</p>
instantiation RTEEventProps	InstantiationRTEEventProps	*	aggr	<p>This allows to define instantiation specific properties for RTE Events, in particular for instance specific scheduling.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=instantiationRTEEventProps.shortLabel, instantiationRTEEventProps.variationPoint.shortLabel vh.latestBindingTime=codeGenerationTime</p>





Class	CompositionSwComponentType			
physical Dimension Mapping	PhysicalDimension MappingSet	0..1	ref	This reference identifies the <code>PhysicalDimensionMappingSet</code> that is applicable in the context of the enclosing <code>CompositionSwComponentType</code> . The <code>PhysicalDimensionMappings</code> contained in the <code>PhysicalDimensionMappingSet</code> shall be taken into account for the assessment of the compatibility of <code>PhysicalDimensions</code> in the context of creation of a <code>PortInterfaceMapping</code> in the scope of the <code>CompositionSwComponentType</code> .

Table A.209: CompositionSwComponentType

Class	Compu			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the ability to express one particular computation.			
Base	<i>ARObject</i>			
Aggregated by	CompuMethod.compuInternalToPhys , CompuMethod.compuPhysToInternal			
Attribute	Type	Mult.	Kind	Note
compuContent	CompuContent	0..1	aggr	This specifies the details of the computation. Stereotypes: atpSplitable Tags: atp.Splitkey=compuContent xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false
compuDefault Value	CompuConst	0..1	aggr	This property can be used to specify an output value for a conversion formula, if the value to be converted lies outside the plausibility limit. Although this is possible for all conversion formulae, it is especially valid for variables with tabular conversion formulae. Tags: xml.sequenceOffset=70

Table A.210: Compu

Class	CompuConst			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the fact that the value of a computation method scale is constant.			
Base	<i>ARObject</i>			
Aggregated by	Compu.compuDefaultValue , CompuScale.compuInverseValue , CompuScaleConstantContents.compu Const			
Attribute	Type	Mult.	Kind	Note
compuConst Content Type	CompuConstContent	0..1	aggr	This is the actual content of the constant compu method scale. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=10 xml.typeElement=false xml.typeWrapperElement=false

Table A.211: CompuConst

Class	CompuConstFormulaContent			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the fact that the constant value of the computation method is represented by a variation point. This difference is due to compatibility with ASAM HDO.			
Base	<i>ARObject</i> , <i>CompuConstContent</i>			
Aggregated by	CompuConst.compuConstContentType			
Attribute	Type	Mult.	Kind	Note
vf	Numerical	1	attr	Value calculated via a system constant. This element is included in every case where parameters should be generated from numerical values during compile time (not runtime!). Thus for example, the influence of the cylinder number on conversion formulae can be introduced in a repeatable manner. Stereotypes: atpVariation Tags: vh.latestBindingTime=codeGenerationTime xml.sequenceOffset=30

Table A.212: CompuConstFormulaContent

Class	CompuConstTextContent			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the textual content of a scale.			
Base	<i>ARObject</i> , <i>CompuConstContent</i>			
Aggregated by	CompuConst.compuConstContentType			
Attribute	Type	Mult.	Kind	Note
vt	VerbatimString	0..1	attr	This represents a textual constant in the computation method.

Table A.213: CompuConstTextContent

Class	CompuMethod			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the ability to express the relationship between a physical value and the mathematical representation. Note that this is still independent of the technical implementation in data types. It only specifies the formula how the internal value corresponds to its physical pendant. Tags: atp.recommendedPackage=CompuMethods			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>CollectableElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
compuInternalToPhys	Compu	0..1	aggr	This specifies the computation from internal values to physical values. Stereotypes: atpSplitable Tags: atp.Splitkey=compuInternalToPhys xml.sequenceOffset=80





Class	CompuMethod			
compuPhysToInternal	Compu	0..1	aggr	This represents the computation from physical values to the internal values. Stereotypes: atpSplitable Tags: atp.Splitkey=compuPhysToInternal xml.sequenceOffset=90
displayFormat	DisplayFormatString	0..1	attr	This property specifies, how the physical value shall be displayed e.g. in documents or measurement and calibration tools. Tags: xml.sequenceOffset=20
unit	Unit	0..1	ref	This is the physical unit of the Physical values for which the CompuMethod applies. Tags: xml.sequenceOffset=30

Table A.214: CompuMethod

Class	CompuNominatorDenominator			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This class represents the ability to express a polynomial either as Nominator or as Denominator.			
Base	ARObject			
Aggregated by	CompuRationalCoeffs.compuDenominator , CompuRationalCoeffs.compuNumerator			
Attribute	Type	Mult.	Kind	Note
v (ordered)	Numerical	*	attr	this is the list of polynomial factors. Note that the first vf represents the power=0. The polynomial is v[0] * x^0 + v[1] * x^1 ... Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.roleElement=true xml.roleWrapperElement=false xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false

Table A.215: CompuNominatorDenominator

Class	CompuRationalCoeffs			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the ability to express a rational function by specifying the coefficients of nominator and denominator.			
Base	ARObject			
Aggregated by	CompuScaleRationalFormula.compuRationalCoeffs			
Attribute	Type	Mult.	Kind	Note
compuDenominator	CompuNominatorDenominator	0..1	aggr	This is the denominator of the expression. Tags: xml.sequenceOffset=30
compuNumerator	CompuNominatorDenominator	0..1	aggr	This is the numerator of the rational expression. Tags: xml.sequenceOffset=20

Table A.216: CompuRationalCoeffs

Class	CompuScale			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the ability to specify one segment of a segmented computation method.			
Base	ARObject			
Aggregated by	CompuScales.compuScale			
Attribute	Type	Mult.	Kind	Note
a2lDisplayText	String	0..1	attr	The value of this attribute shall be taken for generating one display text (specifically the OutVal) within the equivalent of the enclosing <code>CompuMethod</code> in A2L.
compuInverse Value	CompuConst	0..1	aggr	This is the inverse value of the constraint. This supports the case that the scale is not reversible per se. Tags: xml.sequenceOffset=60
compuScale Contents	CompuScaleContents	0..1	aggr	This represents the computation details of the scale. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=70 xml.typeElement=false xml.typeWrapperElement=false
desc	MultiLanguageOverview Paragraph	0..1	aggr	<desc> represents a general but brief description of the object in question. Tags: xml.sequenceOffset=30
lowerLimit	Limit	0..1	attr	This specifies the lower limit of the scale. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=40
mask	PositiveUnlimitedInteger	0..1	attr	In difference to all the other computational methods every COMPU-SCALE will be applied including the bit MASK. Therefore it is allowed for this type of COMPU-METHOD, that COMPU-SCALES overlap. To calculate the string reverse to a value, the string has to be split and the according value for each substring has to be summed up. The sum is finally transmitted. The processing has to be done in order of the COMPU-SCALE elements. Tags: xml.sequenceOffset=35
shortLabel	Identifier	0..1	attr	This element specifies a short name for the particular scale. The name can for example be used to derive a programming language identifier. Tags: xml.sequenceOffset=20
symbol	CIdentifier	0..1	attr	The symbol, if provided, is used by code generators to get a C identifier for the CompuScale. The name will be used as is for the code generation, therefore it needs to be unique within the generation context. Tags: xml.sequenceOffset=25
upperLimit	Limit	0..1	attr	This specifies the upper limit of a of the scale. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=50

Table A.217: CompuScale

Class	CompuScaleConstantContents			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the fact that a particular scale of the computation method is constant.			
Base	ARObject, CompuScaleContents			
Aggregated by	CompuScale.compuScaleContents			
Attribute	Type	Mult.	Kind	Note
compuConst	CompuConst	0..1	aggr	This represents the fact that the scale is a constant. The use case is mainly a non interpolated scale. It is a simplification of the fact that a constant scale can also be expressed as rational function of order 0. Tags: xml.sequenceOffset=90

Table A.218: CompuScaleConstantContents

Class	CompuScales			
Package	M2::MSR::AsamHdo::ComputationMethod			
Note	This meta-class represents the ability to stepwise express a computation method.			
Base	ARObject, CompuContent			
Aggregated by	Compu.compuContent			
Attribute	Type	Mult.	Kind	Note
compuScale (ordered)	CompuScale	*	aggr	This represents one scale within the compu method. Note that it contains a Variationpoint in order to support blueprints of enumerations. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=compuScale, compuScale.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=40 xml.typeElement=false xml.typeWrapperElement=false

Table A.219: CompuScales

Class	ConcreteClassTailoring			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	Tailoring of concrete meta classes.			
Base	ARObject, ClassTailoring, DataFormatElementReference, DataFormatElementScope, Identifiable, MultilanguageReferrable, Referrable, SpecElementReference, SpecElementScope			
Aggregated by	AggregationTailoring.typeTailoring, DataFormatTailoring.classTailoring, ReferenceTailoring.typeTailoring			
Attribute	Type	Mult.	Kind	Note
validationRoot	Boolean	0..1	attr	Specification if this concrete Meta-Class is a root element for validation. I.e.: The validation starts at an object of this concrete Meta-Class and continues by following all aggregations and references that are in scope of this Data Exchange Point. Tags: xml.sequenceOffset=10

Table A.220: ConcreteClassTailoring

Class	ConcretePatternEventTriggering			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::EventTriggeringConstraint			
Note	Describes the behavior of an event that occurs according to a precisely known pattern.			
Base	ARObject, EventTriggeringConstraint , Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
offset	MultidimensionalTime	*	aggr	The offset for each occurrence of the event in the specified time interval. A list of point-in-times in the time interval given by the parameter <code>patternLength</code> at which the event occurs. Tags: xml.name=TIME-VALUE xml.roleElement=true xml.sequenceOffset=10 xml.typeElement=false
patternJitter	MultidimensionalTime	0..1	aggr	The maximum deviation of the time interval's starting point from the beginning of the given period. This parameter is only applicable in conjunction with the parameter <code>patternPeriod</code> .
patternLength	MultidimensionalTime	0..1	aggr	The duration of the time interval within which the event repeatedly occurs. The event occurs at concrete points in time within the given time interval. Tags: xml.sequenceOffset=20
patternPeriod	MultidimensionalTime	0..1	aggr	The time distance between the beginnings of subsequent repetitions of the given concrete pattern.

Table A.221: ConcretePatternEventTriggering

Class	«atpMixedString» ConditionByFormula			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling			
Note	This class represents a condition which is computed based on system constants according to the specified expression. The expected result is considered as boolean value. The result of the expression is interpreted as a condition. <ul style="list-style-type: none"> • "0" represents "false"; • a value other than zero is considered "true" 			
Base	ARObject, FormulaExpression , SwSystemconstDependentFormula			
Aggregated by	VariationPoint.swSyscond , VariationPointProxy.conditionAccess			
Attribute	Type	Mult.	Kind	Note
bindingTime	BindingTimeEnum	1	attr	This attribute specifies the point in time when condition may be evaluated at earliest. At this point in time all referenced system constants shall have a value. Tags: xml.attribute=true

Table A.222: ConditionByFormula

Class	ConditionalChangeNad			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Generates an conditional change NAD request. See ISO 17987 protocol specification for more information.			
Base	ARObject, LinConfigurationEntry , ScheduleTableEntry			
Aggregated by	LinScheduleTable.tableEntry			





Class		ConditionalChangeNad		
Attribute	Type	Mult.	Kind	Note
byte	Integer	0..1	attr	Byte Position of Data Byte that should be used for the bitwise XOR with Invert and the bitwise AND with Mask.
id	PositiveInteger	0..1	attr	Byte Position of Id.
invert	Integer	0..1	attr	Byte Position of Invert.
mask	Integer	0..1	attr	Byte Position of Mask.
newNad	Integer	0..1	attr	The newly assigned NAD value (Byte Position).

Table A.223: ConditionalChangeNad

Class		ConfidenceInterval		
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::EventTriggeringConstraint			
Note	Additionally to the list of measured distances of event occurrences, a confidence interval can be specified for the expected distance of two consecutive event occurrences with a given probability.			
Base	ARObject			
Aggregated by	ArbitraryEventTriggering.confidenceInterval			
Attribute	Type	Mult.	Kind	Note
lowerBound	MultidimensionalTime	0..1	aggr	The lower bound of the expected distance of two consecutive event occurrences.
propability	Float	0..1	attr	The probability for the measured lower and upper bound of the confidence interval.
upperBound	MultidimensionalTime	0..1	aggr	The upper bound of the expected distance of two consecutive event occurrences.

Table A.224: ConfidenceInterval

Class		ConsistencyNeeds		
Package	M2::AUTOSARTemplates::SWComponentTemplate::ImplicitCommunicationBehavior			
Note	This meta-class represents the ability to define requirements on the implicit communication behavior.			
Base	ARObject, AtpBlueprint, AtpBlueprintable, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ConsistencyNeedsBlueprintSet.consistencyNeeds, SwComponentType.consistencyNeeds			
Attribute	Type	Mult.	Kind	Note
dpgDoesNotRequireCoherency	DataPrototypeGroup	*	aggr	<p>This group of VariableDataPrototypes does not require coherency with respect to the implicit communication behavior.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=dpgDoesNotRequireCoherency.shortName, dpgDoesNotRequireCoherency.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	ConsistencyNeeds			
dpgRequiresCoherency	DataPrototypeGroup	*	aggr	<p>This group of VariableDataPrototypes requires coherency with respect to the implicit communication behavior, i.e. all read and write access to VariableDataPrototypes in the DataPrototypeGroup by the RunnableEntities of the RunnableEntityGroup need to be handled in a coherent manner.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dpgRequiresCoherency.shortName, dpgRequiresCoherency.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
regDoesNotRequireStability	RunnableEntityGroup	*	aggr	<p>This group of RunnableEntities does not require stability with respect to the implicit communication behavior.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=regDoesNotRequireStability.shortName, regDoesNotRequireStability.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
regRequiresStability	RunnableEntityGroup	*	aggr	<p>This group of RunnableEntities requires stability with respect to the implicit communication behavior, i.e. all read and write access to VariableDataPrototypes in the DataPrototypeGroup by the RunnableEntities of the RunnableEntityGroup need to be handled in a stable manner.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=regRequiresStability.shortName, regRequiresStability.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>

Table A.225: ConsistencyNeeds

Class	ConstantReference			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	Instead of defining this value inline, a constant is referenced.			
Base	<i>ARObject</i> , <i>ValueSpecification</i>			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
constant	ConstantSpecification	0..1	ref	The referenced constant.

Table A.226: ConstantReference

Class	ConstantSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	Specification of a constant that can be part of a package, i.e. it can be defined stand-alone. Tags: atp.recommendedPackage=ConstantSpecifications			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
valueSpec	ValueSpecification	0..1	aggr	Specification of an expression leading to a value for this constant. Stereotypes: atp.Splitable Tags: atp.Splitkey=valueSpec

Table A.227: ConstantSpecification

Class	ConstantSpecificationMapping			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This meta-class is used to create an association of two ConstantSpecifications. One Constant Specification is supposed to be defined in the application domain while the other should be defined in the implementation domain. Hence the ConstantSpecificationMapping needs to be used where a ConstantSpecification defined in one domain needs to be associated to a ConstantSpecification in the other domain. This information is crucial for the RTE generator.			
Base	ARObject			
Aggregated by	ConstantSpecificationMappingSet.mapping			
Attribute	Type	Mult.	Kind	Note
applConstant	ConstantSpecification	0..1	ref	A ConstantSpecification defined in the application domain.
implConstant	ConstantSpecification	0..1	ref	A ConstantSpecification defined in the implementation domain.

Table A.228: ConstantSpecificationMapping

Class	ConstantSpecificationMappingSet			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This meta-class represents the ability to map two ConstantSpecifications to each others. One Constant Specification is supposed to be described in the application domain and the other should be described in the implementation domain. Tags: atp.recommendedPackage=ConstantSpecificationMappingSets			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
mapping	ConstantSpecification Mapping	*	aggr	ConstantSpecificationMappings owned by the Constant SpecificationMappingSet.

Table A.229: ConstantSpecificationMappingSet

Class	ConsumedEventGroup			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	This element represents an event-group to which the service consumer wants to subscribe.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ConsumedServiceInstance.consumedEventGroup			
Attribute	Type	Mult.	Kind	Note
application Endpoint	ApplicationEndpoint	0..1	ref	Defines the application endpoint where the events of the event group are received in case of multicast reception. Tags: atp.Status=obsolete
autoRequire	Boolean	0..1	attr	Defines that this ConsumedEventGroup shall be requested (subscribed) as soon as the corresponding ConsumedServiceInstance is requested. This could be at ECU start, if ConsumedServiceInstance.autoRequire is set to TRUE or as soon as the ConsumedServiceInstance is requested by the application, if ConsumedServiceInstance.autoRequire is set to FALSE.
eventGroup Identifier	PositiveInteger	0..1	attr	EventGroup ID. Shall be unique within one system to allow service discovery.
eventMulticast Address	ApplicationEndpoint	*	ref	This reference defines the multicast address or a multicast address resource where the events of the event group are received. If the multicast address is determined via configuration and not at runtime via service discovery this reference points to the multicast address over which the events will be received. If the multicast address is determined at runtime via service discovery this reference shall be used to define the necessary local multicast address resources, i.e. RAM space in the Tcplp module in which the multicast address is stored at runtime. Please note that in this case the referenced address may be defined as ANY UDP port and ANY IP address since the multicast address will be received at runtime. If several multicast addresses are considered to be used the ConsumedEventGroup shall point to different ApplicationEndpoint objects to reserve the necessary resources in the configuration. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=eventMulticastAddress.applicationEndpoint, eventMulticastAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
pduActivation RoutingGroup	PduActivationRouting Group	*	aggr	The ServiceDiscovery module is able to activate and deactivate the PDU routing for receiving events.
priority	PositiveInteger	0..1	attr	Defines the frame priority where values from 0 (best effort) to 7 (highest) are allowed.
routingGroup	SoAdRoutingGroup	*	ref	The ServiceDiscovery module is able to activate and deactivate the PDU routing for receiving events. Tags: atp.Status=obsolete
sdClientConfig	SdClientConfig	0..1	aggr	The readiness to receive events is defined by the Service Discovery of the ConsumedEventGroup. The Event Handler shall know about this announcement to decide about the submission of events. Therefore the Event Handler may be configured with Service-Discovery Client attributes. Tags: atp.Status=obsolete





Class	ConsumedEventGroup			
sdClientTimer Config	SomeipSdClientEventGroupTimingConfig	0..1	ref	Client Timing configuration settings that are EventGroup specific. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=sdClientTimerConfig.someipSdClientEventGroupTimingConfig, sdClientTimerConfig.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.230: ConsumedEventGroup

Class	ConsumedServiceInstance			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Service instances that are consumed by the ECU that is connected via the ApplicationEndpoint to a CommunicationConnector.			
Base	ARObject , AbstractServiceInstance , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ApplicationEndpoint.consumedServiceInstance , ServiceInstanceCollectionSet.serviceInstance			
Attribute	Type	Mult.	Kind	Note
allowedServiceProvider	NetworkEndpoint	*	ref	NetworkEndpoint on which the ProvidedServiceInstance that is communicating with this ConsumedServiceInstance is allowed to be located so that the ACL check in the ServiceDiscovery is successful and the connection is allowed to be established. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=allowedServiceProvider.networkEndpoint, allowedServiceProvider.variationPoint.shortLabel atp.Status=draft vh.latestBindingTime=postBuild
autoRequire	Boolean	0..1	attr	Defines that this ConsumedServiceInstance shall be required (searched for) by the service discovery at ECU start.
blocklistedVersion	SomeipServiceVersion	*	aggr	Collection of blocklisted versions Tags: atp.Status=draft
consumedEventGroup	ConsumedEventGroup	*	aggr	Selection of event-groups the consumer wants to subscribe for. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=consumedEventGroup.shortName, consumedEventGroup.variationPoint.shortLabel vh.latestBindingTime=postBuild
eventMulticastSubscriptionAddress	ApplicationEndpoint	0..1	ref	Multicast Address that is used by the client to subscribe to the server: This enables the multicast subscription feature. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=eventMulticastSubscriptionAddress.applicationEndpoint, eventMulticastSubscriptionAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
instanceIdentifier	AnyServiceInstanceId	0..1	attr	This attribute represents the ability to describe the required service instance ID.





Class	ConsumedServiceInstance			
localUnicastAddress	ApplicationEndpoint	0..2	ref	The local address over which the CSI is consumed (udp, tcp or both). Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=localUnicastAddress.applicationEndpoint, localUnicastAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
minorVersion	AnyVersionString	0..1	attr	Minor Version of the ServiceInterface. Value can be set to a number that represents the Minor Version of the searched service or to ANY.
providedServiceInstance	ProvidedServiceInstance	0..1	ref	Reference to a providedServiceInstance to get the instanceIdentifier information from the ProvidedServiceInstance. Tags: atp.Status=obsolete
remoteUnicastAddress	ApplicationEndpoint	0..2	ref	This reference defines the remote address where the service provider is located. This reference shall ONLY be used if the remote address is determined from the configuration and not at runtime from the Service Discovery. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=remoteUnicastAddress.applicationEndpoint, remoteUnicastAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
sdClientConfig	SdClientConfig	0..1	aggr	Service Discovery Client configuration. Tags: atp.Status=obsolete
sdClientTimerConfig	SomeipSdClientServiceInstanceConfig	0..1	ref	Client specific configuration settings relevant for the SOME/IP service discovery. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=sdClientTimerConfig.someipSdClientServiceInstanceConfig, sdClientTimerConfig.variationPoint.shortLabel vh.latestBindingTime=postBuild
serviceIdentifier	PositiveInteger	0..1	attr	This attribute represents the ability to describe the SOME/IP service ID that is searched.
versionDrivenFindBehavior	ServiceVersionAcceptanceKindEnum	0..1	attr	Defines the service discovery find behavior. Tags: atp.Status=draft

Table A.231: ConsumedServiceInstance

Enumeration	ContainedIPduCollectionSemanticsEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	Defines the collection semantics for ContainedIPdus.
Aggregated by	ContainedIPduProps.collectionSemantics
Literal	Description
lastIsBest	The ContainedIPdu data will be fetched via TriggerTransmit just before the transmission executes. Tags: atp.EnumerationLiteralIndex=0
queued	The ContainedIPdu data will instantly be stored to the ContainerIPdu in the context of the Transmit API. Tags: atp.EnumerationLiteralIndex=1

Table A.232: ContainedIPduCollectionSemanticsEnum

Class	ContainedIPduProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Defines the aspects of an IPdu which can be collected inside a ContainerIPdu.			
Base	ARObject			
Aggregated by	ContainerIPdu.containedIPduTriggeringProps, IPdu.containedIPduProps			
Attribute	Type	Mult.	Kind	Note
collection Semantics	ContainedIPdu CollectionSemantics Enum	0..1	attr	Defines whether this ContainedIPdu shall be collected using a last-is-best or queued semantics.
containedPdu Triggering	PduTriggering	0..1	ref	Reference to Pdu for which the ContainedIPduProps are valid.
headerIdLong Header	PositiveInteger	0..1	attr	Defines the header id this IPdu shall have in case this IPdu is put inside a ContainerIPdu with headerType = longHeader.
headerIdShort Header	PositiveInteger	0..1	attr	Defines the header id this IPdu shall have in case this IPdu is put inside a ContainerIPdu with headerType = shortHeader.
offset	PositiveInteger	0..1	attr	Byte offset that describes the location of the Contained Pdu in the ContainerPdu if no header is used.
priority	PositiveInteger	0..1	attr	Defines a priority of a ContainedTxPdu. 255 represents the lowest priority and 0 represent the highest priority.
timeout	TimeValue	0..1	attr	Defines a IPdu specific sender timeout which can reduce the ContainerIPdu timer when this containedIPdu is put inside the ContainerIPdu. This attribute is ignored on receiver side.
trigger	PduCollectionTrigger Enum	0..1	attr	Defines whether this IPdu does trigger the sending of the ContainerIPdu. This attribute is ignored on receiver side.
update IndicationBit Position	PositiveInteger	0..1	attr	The updateIndicationBit specifies the bit location of ContainedIPdu Update-Bit in the Container PDU. It indicates to the receivers that the ContainedIPdu in the ContainerIPdu was updated.

Table A.233: ContainedIPduProps

Class	ContainerIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Allows to collect several IPdus in one ContainerIPdu based on the headerType. Tags: atp.recommendedPackage=Pdus			
Base	ARElement, ARObject, CollectableElement, FibexElement, IPdu, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
containedIPdu TriggeringProps	ContainedIPduProps	*	aggr	Defines properties for an IPdu that is part of the ContainerIPdu.
containedPdu Triggering	PduTriggering	*	ref	This PduTriggering shall be collected inside the Container IPdu.
container Timeout	TimeValue	0..1	attr	When this timeout expires the ContainerIPdu is sent out. The respective timer is started when the first Ipdu is put into the ContainerIPdu. This attribute is ignored on receiver side.
containerTrigger	ContainerIPduTrigger Enum	0..1	attr	Defines if the transmission of the ContainerIPdu shall be requested right after the first ContainedIPdu was put into it. This attribute shall be ignored on receiver side.
headerType	ContainerIPduHeader TypeEnum	0..1	attr	Defines whether and which header type is used (header id and length).





Class	ContainerIPdu			
minimumRxContainerQueueSize	PositiveInteger	0..1	attr	This attribute defines the minimum queue size for received containers.
minimumTxContainerQueueSize	PositiveInteger	0..1	attr	This attribute defines the minimum queue size for transmitted containers.
rxAcceptContainedIPdu	RxAcceptContainedIPduEnum	0..1	attr	Defines whether this ContainerIPdu has a fixed set of containedIPdus assigned for reception.
thresholdSize	PositiveInteger	0..1	attr	Defines the size threshold which, when exceeded, triggers the sending of the ContainerIPdu although the maximum Pdu size has not been reached yet. Unit: byte.
unusedBitPattern	PositiveInteger	0..1	attr	IPduM fills not updated areas of the ContainerPdu with this byte-pattern.

Table A.234: ContainerIPdu

Enumeration	ContainerIPduHeaderTypeEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	Is used to define the header type and size of ContainerIPdus. The header size includes the header id and the length information.
Aggregated by	ContainerIPdu.headerType
Literal	Description
longHeader	Header size is 64 bit: <ul style="list-style-type: none"> • Header Id 32 bit • Dlc 32 bit Tags: atp.EnumerationLiteralIndex=0
noHeader	No Header is used and the location of each containedPdu in the ContainerPdu is statically configured. Tags: atp.EnumerationLiteralIndex=2
shortHeader	Header size is 32 bit: <ul style="list-style-type: none"> • Header Id 24 bit • Dlc 8 bit. Tags: atp.EnumerationLiteralIndex=1

Table A.235: ContainerIPduHeaderTypeEnum

Class	CouplingElement			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	A CouplingElement is used to connect EcuInstances to the VLAN of an EthernetCluster. Coupling Elements can reach from a simple hub to a complex managed switch or even devices with functionalities in higher layers. A CouplingElement that is not related to an EcuInstance occurs as a dedicated single device. Tags: atp.recommendedPackage=CouplingElements			
Base	ARObject , CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
communicationCluster	EthernetCluster	0..1	ref	This relationship defines to which cluster the Coupling Element belongs.





Class	CouplingElement			
couplingElementDetails	CouplingElementAbstractDetails	0..1	aggr	Definition of details for this specific CouplingElement. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=couplingElementDetails.shortName, couplingElementDetails.variationPoint.shortLabel atp.Status=candidate vh.latestBindingTime=postBuild xml.namePlural=COUPLING-ELEMENT-DETAILS
couplingPort	CouplingPort	*	aggr	Hardware Port of the CouplingElement that is used to connect this CouplingPort to EcuInstances or other CouplingElements. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=couplingPort.shortName, couplingPort.variationPoint.shortLabel vh.latestBindingTime=postBuild
couplingType	CouplingElementEnum	0..1	attr	Describes the coupling type of this CouplingElement.
ecuInstance	EcuInstance	0..1	ref	Optional reference to the ECU where the CouplingElement is located.
firewallRule	StateDependentFirewall	*	ref	Firewall rules defined in the context of a CouplingElement. Tags: atp.Status=candidate
switchMacAddressLearningMode	SwitchMacAddressLearningEnum	0..1	attr	Defines the MAC address learning mode of the Ethernet switch.

Table A.236: CouplingElement

Enumeration	CouplingElementEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Identifies the Coupling type.
Aggregated by	CouplingElement.couplingType
Literal	Description
hub	A device that is used to connect segments of a LAN. In Hubs frames are "broadcasted" to every one of its ports. Tags: atp.EnumerationLiteralIndex=0
router	A device that routes frames between different networks. Tags: atp.EnumerationLiteralIndex=1
switch	A device that filters and forwards frames between different LAN segments. Tags: atp.EnumerationLiteralIndex=2

Table A.237: CouplingElementEnum

Class	CouplingElementSwitchDetails
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Collection of specific details for the CouplingElement of couplingType switch. Tags: atp.Status=candidate atp.recommendedPackage=SwitchStreamIdentificationTables
Base	<i>ARObject</i> , <i>CouplingElementAbstractDetails</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>





Class	CouplingElementSwitchDetails			
Aggregated by	CouplingElement.couplingElementDetails			
Attribute	Type	Mult.	Kind	Note
flowMetering	SwitchFlowMeteringEntry	*	aggr	Collection of Flow Metering Entries. Tags: atp.Status=candidate
streamFilter (ordered)	SwitchStreamFilterEntry	*	aggr	Collection of Stream Filter Entries. Tags: atp.Status=candidate
streamGate	SwitchStreamGateEntry	*	aggr	Collection of Stream Gate Entries. Tags: atp.Status=candidate
switchStream Identification (ordered)	SwitchStreamIdentification	*	aggr	Collection of switch stream identification entries. Tags: atp.Status=candidate
trafficShaper Group	SwitchAsynchronousTrafficShaperGroupEntry	*	aggr	Collection of Traffic Shaper Groups. Tags: atp.Status=candidate

Table A.238: CouplingElementSwitchDetails

Class	CouplingPort			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	A CouplingPort is used to connect a CouplingElement with an EcuInstance or two CouplingElements with each other via a CouplingPortConnection. Optionally, the CouplingPort may also have a reference to a macMulticastGroup and a defaultVLAN.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CouplingElement.couplingPort, EthernetCommunicationController.couplingPort			
Attribute	Type	Mult.	Kind	Note
connection Negotiation Behavior	EthernetConnectionNegotiationEnum	0..1	attr	Specifies the connection negotiation of the CouplingPort.
couplingPort Details	CouplingPortDetails	0..1	aggr	Defines more details of a CouplingPort in case a more specific configuration is required.
couplingPort Role	CouplingPortRoleEnum	0..1	attr	Defines the role this CouplingPort takes in the context of the CouplingElement.
defaultVlan	EthernetPhysicalChannel	0..1	ref	The vLanIdentifier of the referenced VLAN is the Default-PVID (port VLAN ID). A Port VLAN ID is a default VLAN ID that is assigned to an access CouplingPort to designate the VLAN segment to which this port is connected. Also, if a CouplingPort has not been configured with any VLAN memberships, the virtual switch's Port VLAN ID (pvid) becomes the default VLAN ID for the ports connection. This identifier/tag is added for incoming untagged messages at the port (ingress tagging). For outgoing messages with this identifier, the tag is removed at the port (egress untagging, depending on the Vlan Membership.sendActivity).





Class	CouplingPort			
macAddressVlanAssignment	MacAddressVlanMembership	*	aggr	Statically defines the assignment of MAC-Multicast-Addresses, optionally together with VLANs, to this CouplingPort. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=macAddressVlanAssignment.shortName, macAddressVlanAssignment.variationPoint.shortLabel vh.latestBindingTime=postBuild
macLayerType	EthernetMacLayerTypeEnum	0..1	attr	Specifies the mac layer type of the CouplingPort.
macMulticastAddress	MacMulticastGroup	*	ref	Assigns a set of MAC-Multicast-Addresses which are addressable via this CouplingPort. This is a static pre-configuration and further addresses may be learned during runtime. Tags: atp.Status=obsolete
macSecProps	MacSecProps	*	aggr	Properties to configure MACsec (Media access control security) and the MKA (MACsec Key Agreement) for the CouplingPort (PHY). Tags: atp.Status=candidate
physicalLayerType	EthernetPhysicalLayerTypeEnum	0..1	attr	Specifies the physical layer type of the CouplingPort.
plcaProps	PlcaProps	0..1	aggr	Optional properties for configuration of PLCA (Physical Layer Collision Avoidance) in case 10-BASE-T1S Ethernet is used and PLCA is enabled on the Coupling Port (PHY).
pncMapping	PncMappingIdent	*	ref	Reference to the partial networks this CouplingPort participates in. Stereotypes: atpSplittable Tags: atp.Splitkey=pncMapping
receiveActivity	EthernetSwitchVlanIngressTagEnum	0..1	attr	Defines the handling of frames at the ingress port.
vlanMembership	VlanMembership	*	aggr	Messages of VLANs that are defined here can be communicated via the CouplingPort.
wakeupSleepOnDatalineConfig	EthernetWakeupSleepOnDatalineConfig	0..1	ref	Optional reference to EthernetWakeupSleepOnDataline Config.

Table A.239: CouplingPort

Class	CouplingPortConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Connection between two CouplingPorts (firstPort and secondPort) or between a collection of Ports that are all referenced by the portCollection reference.			
Base	ARObject			
Aggregated by	EthernetCluster.couplingPortConnection			
Attribute	Type	Mult.	Kind	Note
firstPort	CouplingPort	0..1	ref	Reference to the first CouplingPort that is connected via the CouplingPortConnection.





Class	CouplingPortConnection			
nodePort	CouplingPort	*	ref	Reference to a number of CouplingPorts that are connected via the CouplingPortConnection. This reference shall be used to describe a 10BASE-T1S topology architecture where several CouplingPorts of EthernetCommunicationControllers are connected via one CouplingPortConnection. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=nodePort.couplingPort, nodePort.variationPoint.shortLabel vh.latestBindingTime=postBuild
plcaLocalNodeCount	PositiveInteger	0..1	attr	Defines the number of communication participants in case 10BASE-T1S and the nodePort reference is used.
plcaTransmitOpportunityTimer	PositiveInteger	0..1	attr	Timer for the transmission in bit time to evaluate if a Transmission Opportunity is yield or not.
secondPort	CouplingPort	0..1	ref	Reference to the second CouplingPort that is connected via the CouplingPortConnection.

Table A.240: CouplingPortConnection

Class	CouplingPortDetails			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines details of a CouplingPort. May be used to configure the structures of a switch.			
Base	ARObject			
Aggregated by	CouplingPort.couplingPortDetails			
Attribute	Type	Mult.	Kind	Note
couplingPortStructuralElement	CouplingPortStructuralElement	*	aggr	Collects all the structural parts at which a CouplingPort may be configurable.
defaultTrafficClass	PositiveInteger	0..1	attr	Defines the default traffic class for this CouplingPort.
ethernetPriorityRegeneration	EthernetPriorityRegeneration	0..8	aggr	Defines a priority regeneration where the ingress priority is replaced by regenerated priority.
ethernetTrafficClassAssignment	CouplingPortTrafficClassAssignment	*	aggr	Defines the priority to traffic class assignment.
framePreemptionSupport	Boolean	0..1	attr	Defines whether frames handled by this CouplingPort may be preempted.
globalTimeProps	GlobalTimeCouplingPortProps	0..1	aggr	Specifies properties for the usage of the CouplingPort in the scope of Global Time Sync.
lastEgressScheduler	CouplingPortScheduler	0..1	ref	Defines which CouplingPortScheduler is the last in the egress port structure.
ratePolicy	CouplingPortRatePolicy	*	aggr	Rate policies to be applied for this CouplingPort.
vlanTranslationTable	EthernetVlanTranslationTable	*	aggr	Definition of entries that define the ingress Vlan translation between IngressVlanID and TranslatedVlanID.

Table A.241: CouplingPortDetails

Class	CouplingPortEnhancedTrafficShaper			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines a scheduler used for enhanced traffic shaping (e.g. weighted round robin). Tags: atp.Status=candidate			
Base	ARObject, CouplingPortAbstractShaper, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	CouplingPortFifo.shaper			
Attribute	Type	Mult.	Kind	Note
etsAvailableBandwidthInPercent	PositiveInteger	0..1	attr	Defines the available bandwidth in percent of an enhanced transmission selection algorithm (ETS). Tags: atp.Status=candidate
etsAvailableBandwidthInWeightValue	PositiveInteger	0..1	attr	Defines the available bandwidth as weight value of an enhanced transmission selection algorithm (ETS). Tags: atp.Status=candidate

Table A.242: CouplingPortEnhancedTrafficShaper

Class	CouplingPortFifo			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines a FIFO for the CouplingPort egress structure.			
Base	ARObject, CouplingPortStructuralElement, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	CouplingPortDetails.couplingPortStructuralElement			
Attribute	Type	Mult.	Kind	Note
assignedTrafficClass	PositiveInteger	*	attr	Defines a set of Traffic Classes which shall be handled by this FIFO.
minimumFifoLength	PositiveInteger	0..1	attr	FIFO minimum length in Byte. An actual configuration/hardware may use a bigger value.
shaper	CouplingPortAbstractShaper	0..1	aggr	Definition of the shaper to be used for the processing of this FIFO. Tags: atp.Status=candidate
trafficClassPreemptionSupport	EthernetCouplingPortPreemptionEnum	0..1	attr	Defines whether frames assigned to the traffic class associated with this CouplingPortFifo may be preempted or not.

Table A.243: CouplingPortFifo

Class	CouplingPortRatePolicy			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines a rate policy on a CouplingPort.			
Base	ARObject			
Aggregated by	CouplingPortDetails.ratePolicy			
Attribute	Type	Mult.	Kind	Note
dataLength	PositiveInteger	0..1	attr	Amount of data in bytes (excluding header information) that can be received to define the rate policy.
policyAction	CouplingPortRatePolicyActionEnum	0..1	attr	Defines the action to be performed when this rate policy is violated.
priority	PositiveInteger	0..1	attr	Defines the priority which this rate policy shall be limited on. If no priority is given this rate policy is not considering priority.
timeInterval	TimeValue	0..1	attr	Time interval used to define the base of the rate policy.





Class	CouplingPortRatePolicy			
vLan	EthernetPhysicalChannel	*	ref	Defines the VLANs this rate policy shall be limited on. If no VLAN is given this rate policy is not considering VLAN tags.

Table A.244: CouplingPortRatePolicy

Enumeration	CouplingPortRoleEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Defines the role a CouplingPort takes in the context of a CouplingElement.
Aggregated by	CouplingPort.couplingPortRole
Literal	Description
hostPort	The hostPort is connected to an ECU (host ecu). The host ECU controls the connected Coupling Element (e.g. Ethernet switch). Tags: atp.EnumerationLiteralIndex=0
standardPort	A CouplingPort can be a standardPort that is used to connect the CouplingElement with Coupling Ports outside the ECU. Tags: atp.EnumerationLiteralIndex=2
upLinkPort	A CouplingPort can be connected to another CouplingPort of a CouplingElement located on the same ECU (CouplingElement.ecuInstance) using the CouplingPortConnection. This is used to model a cascaded switch. Tags: atp.EnumerationLiteralIndex=1

Table A.245: CouplingPortRoleEnum

Class	CouplingPortScheduler			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines a scheduler for the CouplingPort egress structure.			
Base	ARObject , CouplingPortStructuralElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CouplingPortDetails.couplingPortStructuralElement			
Attribute	Type	Mult.	Kind	Note
portScheduler	EthernetCouplingPortSchedulerEnum	0..1	attr	Defines the schedule algorithm to be used.
predecessor (ordered)	CouplingPortStructuralElement	*	ref	Ordered List of predecessor inputs. The first element has the highest priority. The following elements have decreasing priorities.

Table A.246: CouplingPortScheduler

Class	CouplingPortTrafficClassAssignment			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines the assignment of Traffic Class to a frame.			
Base	ARObject , Referrable			
Aggregated by	CouplingPortDetails.ethernetTrafficClassAssignment			
Attribute	Type	Mult.	Kind	Note
priority	PositiveInteger	*	attr	Defines a priority which is mapped onto a Traffic Class.
trafficClass	PositiveInteger	0..1	attr	Defines the Traffic Class which is assigned.

Table A.247: CouplingPortTrafficClassAssignment

Class	CpSoftwareCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	<p>This meta class provides the ability to define a CP Software Cluster. Each CP Software Cluster can be integrated and build individually. It defines the sub-set of hierarchical tree(s) of Software Components belonging to this CP Software Cluster. Resources required or provided by this CP Software Cluster are given in the according mappings.</p> <p>Tags: atp.recommendedPackage=CpSoftwareClusters</p>			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
softwareCluster Id	PositiveInteger	0..1	attr	This attribute represents the value of the id of the corresponding CP software cluster.
swComponent Assignment	SwComponent PrototypeAssignment	*	aggr	<p>This is the collection of SwComponentPrototype Assignments</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=swComponentAssignment, swComponent Assignment.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
swComposition	CompositionSw ComponentType	*	ref	<p>Software Components in the context of a CompositionSw ComponentType belonging to this CP Software Cluster. This reference can be used to describe the belonging SWCs when the CP Software Cluster is described out of the context of a System, e.g. reusable CP Software Cluster.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=swComposition.compositionSwComponent Type, swComposition.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime</p>

Table A.248: CpSoftwareCluster

Class	CpSoftwareClusterBinaryManifestDescriptor			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster::BinaryManifest			
Note	<p>This meta-class has the ability to act as a hub for all information related to the binary manifest of a given CP software cluster. The manifest is subject to integrator work and therefore not a part of the definition of the CP software cluster itself.</p> <p>Tags: atp.recommendedPackage=CpSoftwareClusterBinaryManifestDescriptors</p>			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
cpSoftware Cluster	CpSoftwareCluster	0..1	ref	<p>This reference identifies the CpSoftwareCluster to which the enclosing CpSoftwareClusterBinaryManifest Descriptor belongs,</p> <p>The CpSoftwareClusterBinaryManifestDescriptor is defined in an integration phase while the referenced Cp SoftwareCluster represents a design element. Therefore, it makes sense to use a reference rather than an aggregation in the relation of the two meta-classes.</p>
metaDataField	BinaryManifestMeta DataField	*	aggr	This aggregation identifies the collection of meta-data contained in the enclosing binary manifest.
provide Resource	BinaryManifestProvide Resource	*	aggr	This aggregation represents the collection of provided resources in the enclosing binary manifest.





Class		CpSoftwareClusterBinaryManifestDescriptor		
require Resource	BinaryManifestRequireResource	*	aggr	This aggregation represents the collection of required resources in the enclosing binary manifest.
resource Definition	BinaryManifestResourceDefinition	*	aggr	This aggregation represents the collection of binary manifest resource definitions that belong to the enclosing CpSoftwareClusterBinaryManifestDescriptor.
softwareCluster Id	PositiveInteger	0..1	attr	This attribute represents the value of the id of the corresponding CP software cluster. This id is assigned by an integrator, but may also be copied from CpSoftwareCluster.softwareClusterId if available.

Table A.249: CpSoftwareClusterBinaryManifestDescriptor

Class		CpSoftwareClusterCommunicationResource		
Package		M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster		
Note		Represents a single resource required or provided by a CP Software Cluster which relates to the port based communication on VFB level.		
Base		ARObject , CpSoftwareClusterResource , Identifiable , MultilanguageReferrable , Referrable		
Aggregated by		CpSoftwareClusterResourcePool.resource		
Attribute	Type	Mult.	Kind	Note
communication ResourceProps	CpSoftwareClusterCommunicationResourceProps	0..1	aggr	This aggregation supports the further qualification of the enclosing CpSoftwareClusterCommunicationResource by means of additional attributes depending on the nature of the CpSoftwareClusterCommunicationResource.

Table A.250: CpSoftwareClusterCommunicationResource

Class		CpSoftwareClusterResource (abstract)		
Package		M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster		
Note		Represents a single resource required or provided by a CP Software Cluster. Tags: atp.recommendedPackage=Resources		
Base		ARObject , Identifiable , MultilanguageReferrable , Referrable		
Subclasses		CpSoftwareClusterCommunicationResource , CpSoftwareClusterServiceResource		
Aggregated by		CpSoftwareClusterResourcePool.resource		
Attribute	Type	Mult.	Kind	Note
dependent Resource	RoleBasedResourceDependency	*	aggr	Link to a resource which depends on this resource to implement them.
globalResource Id	PositiveInteger	0..1	attr	A unique identifiers per resource used for the connection process. The identifier is required to be unique in the scope of a single machine. If software clusters are designed to be reused on multiple machines the uniqueness requirements applies for all the intended machines.
isMandatory	Boolean	0..1	attr	This attribute indicates, that the resource is mandatory to operate the Software Cluster. If the resource is not provided on the machine the connection process of any Software Cluster requiring this resource gets aborted.

Table A.251: CpSoftwareClusterResource

Class	CpSoftwareClusterResourceToApplicationPartitionMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	This meta class maps a Software Cluster resource to an Application Partition to restrict the usage.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	CpSoftwareClusterMappingSet.resourceToApplicationPartitionMapping, SystemMapping.resourceToApplicationPartitionMapping			
Attribute	Type	Mult.	Kind	Note
application Partition	ApplicationPartition	0..1	ref	ApplicationPartition for which the mapping applies.
resource	CpSoftwareClusterResource	0..1	ref	Software Cluster Resource for which the mapping applies.

Table A.252: CpSoftwareClusterResourceToApplicationPartitionMapping

Class	CpSoftwareClusterServiceResource			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	Represents a single resource required or provided by a CP Software Cluster which relates to the BSW.			
Base	<i>ARObject</i> , <i>CpSoftwareClusterResource</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	CpSoftwareClusterResourcePool.resource			
Attribute	Type	Mult.	Kind	Note
resourceNeeds	EcucContainerValue	*	ref	Reference(s) to one or multiple EcucContainerValue(s) qualifying the characteristics of the resource.

Table A.253: CpSoftwareClusterServiceResource

Class	CpSoftwareClusterToApplicationPartitionMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	This meta class defines ApplicationPartitions that are applicable for the CpSoftwareCluster.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	CpSoftwareClusterMappingSet.softwareClusterToApplicationPartitionMapping, SystemMapping.softwareClusterToApplicationPartitionMapping			
Attribute	Type	Mult.	Kind	Note
application Partition	ApplicationPartition	*	ref	Collection of ApplicationPartitions available in the Cp SoftwareCluster
softwareCluster	CpSoftwareCluster	0..1	ref	Software Cluster Resource for which the mapping applies

Table A.254: CpSoftwareClusterToApplicationPartitionMapping

Class	CpSoftwareClusterToEcucInstanceMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	This meta class maps a CpSoftwareCluster to a EcucInstance.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	SystemMapping.swClusterMapping			
Attribute	Type	Mult.	Kind	Note
ecucInstance	EcucInstance	0..1	ref	Reference to a specific ECU Instance description.
machineId	PositiveInteger	0..1	attr	Unique number of the (virtual or physical) machine to which the Software Cluster is mapped.





Class		CpSoftwareClusterToEculInstanceMapping		
swCluster	CpSoftwareCluster	*	ref	The mapped CP Software Cluster Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swCluster.cpSoftwareCluster, swCluster.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime

Table A.255: CpSoftwareClusterToEculInstanceMapping

Class		CpSoftwareClusterToResourceMapping		
Package		M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster		
Note		This meta class maps a service resource to CP Software Clusters. By this mapping it's specified whether the Software Cluster has to provide or to require the resource.		
Base		ARObject , Identifiable , MultilanguageReferrable , Referrable		
Aggregated by		CpSoftwareClusterMappingSet.softwareClusterToResourceMapping, SystemMapping.softwareClusterToResourceMapping		
Attribute	Type	Mult.	Kind	Note
provider	CpSoftwareCluster	0..1	ref	CP Software Cluster providing the resource
requester	CpSoftwareCluster	*	ref	CP Software Cluster requesting the resource
service Resource	CpSoftwareClusterServiceResource	0..1	ref	Service resource for which the mapping applies.

Table A.256: CpSoftwareClusterToResourceMapping

Class		CryptoServiceCertificate		
Package		M2::AUTOSARTemplates::SystemTemplate::SecureCommunication		
Note		This meta-class represents the ability to model a cryptographic certificate. Tags: atp.recommendedPackage=CryptoServiceCertificates		
Base		ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement		
Aggregated by		ARPackage.element		
Attribute	Type	Mult.	Kind	Note
algorithmFamily	CryptoCertificateAlgorithmFamilyEnum	0..1	attr	This attribute represents a description of the family of crypto algorithm used to generate public key and signature of the cryptographic certificate.
format	CryptoCertificateFormatEnum	0..1	attr	This attribute can be used to provide information about the format used to create the certificate
maximum Length	PositiveInteger	0..1	attr	This attribute represents the ability to define the maximum length of the certificate in bytes.
nextHigher Certificate	CryptoServiceCertificate	0..1	ref	The reference identifies the next higher certificate in the certificate chain.
serverName Identification	String	0..1	attr	Server Name Indication (SNI) is needed if the IP address hosts multiple servers (on the same port), each of them using a different certificate. If the client sends the SNI to the Server in the client hello, the server looks the SNI up in its certificate list and uses the certificate identified by the SNI.

Table A.257: CryptoServiceCertificate

Class	CryptoServiceKey			
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This meta-class has the ability to represent a crypto key. Tags: atp.recommendedPackage=CryptoDevelopmentKeys			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
algorithmFamily	String	0..1	attr	This attribute represent the description of the family of the applicable crypto algorithm.
development Value	ValueSpecification	0..1	aggr	This aggregation represents the ability to assign a specific value to the crypto key as part of the system description. This value can then be taken for the development of the respective ECU.
keyGeneration	CryptoServiceKey GenerationEnum	0..1	attr	This attribute describes how a the specific cryptographic key is created.
keyStorageType	String	0..1	attr	This attribute describes where the enclosing cryptographic key shall be stored. AUTOSAR reserves specific values for this attributes but it is possible to insert custom values as well.
length	PositiveInteger	0..1	attr	This attribute describes the length of the cryptographic key in bits.

Table A.258: CryptoServiceKey

Class	CryptoServicePrimitive			
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This meta-class has the ability to represent a crypto primitive. Tags: atp.recommendedPackage=CryptoPrimitives			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement, Referrable , UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
algorithmFamily	String	0..1	attr	This attribute represents a description of the family (e.g. AES) of crypto algorithm implemented by the crypto primitive.
algorithmMode	String	0..1	attr	This attribute represents a description of the mode of the crypto algorithm implemented by the crypto primitive.
algorithm Secondary Family	String	0..1	attr	This attribute represents a further description of the secondary family of crypto algorithm implemented by the crypto primitive. The secondary family is needed for the specification of the hash algorithm for a signature check, e.g. using RSA.

Table A.259: CryptoServicePrimitive

Class	CryptoServiceQueue			
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This meta-class has the ability to represent a crypto queue. Tags: atp.recommendedPackage=CryptoServiceQueues			





Class	CryptoServiceQueue			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
queueSize	PositiveInteger	0..1	attr	Defines the queue size of the CryptoServiceQueue.

Table A.260: CryptoServiceQueue

Class	CycleCounter			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	The communication cycle where the frame is send is described by the attribute "cycleCounter".			
Base	ARObject, CommunicationCycle			
Aggregated by	FlexrayAbsolutelyScheduledTiming.communicationCycle, TtcanAbsolutelyScheduledTiming.communicationCycle			
Attribute	Type	Mult.	Kind	Note
CycleCounter	Integer	0..1	attr	The communication cycle where the frame described by this timing is sent. If a timing is given in this way the referencing FlexrayCluster shall specify the cycleCount Max as upper bound and point of total repetition. This value is incremented at the beginning of each new cycle, ranging from 0 to cycleCountMax, and is reset to 0 after a sequence of cycleCountMax+1 cycles.

Table A.261: CycleCounter

Class	CycleRepetition			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	The communication cycle where the frame is send is described by the attributes baseCycle and cycleRepetition.			
Base	ARObject, CommunicationCycle			
Aggregated by	FlexrayAbsolutelyScheduledTiming.communicationCycle, TtcanAbsolutelyScheduledTiming.communicationCycle			
Attribute	Type	Mult.	Kind	Note
BaseCycle	Integer	0..1	attr	The first communication cycle where the frame is sent. This value is incremented at the beginning of each new cycle, ranging from 0 to 63, and is reset to 0 after a sequence of 64 cycles.
CycleRepetition	CycleRepetitionType	0..1	attr	The number of communication cycles (after the first cycle) whenever the frame described by this timing is sent again.

Table A.262: CycleRepetition

Class	CyclicTiming			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	Specification of a cyclic sending behavior.			
Base	ARObject, Describable			
Aggregated by	TransmissionModeTiming.cyclicTiming			
Attribute	Type	Mult.	Kind	Note





Class	CyclicTiming			
timeOffset	TimeRangeType	0..1	aggr	This attribute specifies the time until first transmission of this I-PDU. This attribute defines the time between Com_IpduGroupStart and the first transmission of the cyclic part of this transmission request for this I-PDU.
timePeriod	TimeRangeType	0..1	aggr	Period of the repetition of cyclic transmissions.

Table A.263: CyclicTiming

Class	DataConstr			
Package	M2::MSR::AsamHdo::Constraints::GlobalConstraints			
Note	This meta-class represents the ability to specify constraints on data. Tags: atp.recommendedPackage=DataConstrs			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataConstrRule	DataConstrRule	*	aggr	This is one particular rule within the data constraints. Tags: xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=30 xml.typeElement=false xml.typeWrapperElement=false

Table A.264: DataConstr

Class	DataConstrRule			
Package	M2::MSR::AsamHdo::Constraints::GlobalConstraints			
Note	This meta-class represents the ability to express one specific data constraint rule.			
Base	ARObject			
Aggregated by	DataConstr.dataConstrRule			
Attribute	Type	Mult.	Kind	Note
constrLevel	Integer	0..1	attr	This attribute describes the category of a constraint. One of its functions is in the area of constraint violation, where it can be used from a certain level, to produce error messages. The lower the level, the more stringent the check. Used to distinguish hard or soft limits. Tags: xml.sequenceOffset=20
internalConstrs	InternalConstrs	0..1	aggr	Describes the limitations applicable on the internal domain (as opposed to the physical domain). Tags: xml.sequenceOffset=40
physConstrs	PhysConstrs	0..1	aggr	Describes the limitations applicable on the physical domain (as opposed to the internal domain). Tags: xml.sequenceOffset=30

Table A.265: DataConstrRule

Class	DataDumpEntry			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	This service is reserved for initial configuration of a slave node by the slave node supplier and the format of this message is supplier specific.			
Base	ARObject, LinConfigurationEntry, ScheduleTableEntry			
Aggregated by	LinScheduleTable.tableEntry			
Attribute	Type	Mult.	Kind	Note
byteValue (ordered)	Integer	*	attr	Supplier specific format.

Table A.266: DataDumpEntry

Class	DataFilter			
Package	M2::AUTOSARTemplates::CommonStructure::Filter			
Note	Base class for data filters. The type of the filter is specified in attribute dataFilterType. Some of the filter types require additional arguments which are specified as attributes of this class.			
Base	ARObject			
Aggregated by	ISignalPort.dataFilter , NonqueuedReceiverComSpec.filter , NonqueuedSenderComSpec.dataFilter , SignalBasedEventElementToSignalTriggeringMapping.filter , SignalBasedFieldToSignalTriggeringMapping.filter , SignalServiceTranslationElementProps.filter , TransmissionModeCondition.dataFilter			
Attribute	Type	Mult.	Kind	Note
dataFilterType	DataFilterTypeEnum	0..1	attr	This attribute specifies the type of the filter.
mask	UnlimitedInteger	0..1	attr	Mask for old and new value.
max	UnlimitedInteger	0..1	attr	Value to specify the upper boundary
min	UnlimitedInteger	0..1	attr	Value to specify the lower boundary
offset	PositiveInteger	0..1	attr	Specifies the initial number of messages to occur before the first message is passed
period	PositiveInteger	0..1	attr	Specifies number of messages to occur before the message is passed again
x	UnlimitedInteger	0..1	attr	Value to compare with

Table A.267: DataFilter

Enumeration	DataFilterTypeEnum
Package	M2::AUTOSARTemplates::CommonStructure::Filter
Note	This enum specifies the supported DataFilterTypes.
Aggregated by	DataFilter.dataFilterType
Literal	Description
always	No filtering is performed so that the message always passes. Tags: atp.EnumerationLiteralIndex=0
maskedNewDiffers MaskedOld	Pass messages where the masked value has changed. (new_value&mask) !=(old_value&mask) new_value: current value of the message old_value: last value of the message (initialized with the initial value of the message, updated with new_value if the new message value is not filtered out) Tags: atp.EnumerationLiteralIndex=1





Enumeration	DataFilterTypeEnum
maskedNewDiffers X	Pass messages whose masked value is not equal to a specific value x $(new_value \& mask) \neq x$ new_value: current value of the message Tags: atp.EnumerationLiteralIndex=2
maskedNewEquals X	Pass messages whose masked value is equal to a specific value x $(new_value \& mask) == x$ new_value: current value of the message Tags: atp.EnumerationLiteralIndex=3
never	The filter removes all messages. Tags: atp.EnumerationLiteralIndex=4
newIsOutside	Pass a message if its value is outside a predefined boundary. $(min > new_value) \text{ OR } (new_value > max)$ Tags: atp.EnumerationLiteralIndex=5
newIsWithin	Pass a message if its value is within a predefined boundary. $min \leq new_value \leq max$ Tags: atp.EnumerationLiteralIndex=6
oneEveryN	Pass a message once every N message occurrences. Algorithm: $occurrence \% period == offset$ Start: $occurrence = 0$. Each time the message is received or transmitted, occurrence is incremented by 1 after filtering. Length of occurrence is 8 bit (minimum). Tags: atp.EnumerationLiteralIndex=7

Table A.268: DataFilterTypeEnum

Enumeration	DataIdModeEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer
Note	Supported inclusion modes to include the implicit two-byte Data ID in the one-byte CRC.
Aggregated by	E2EProfileConfiguration.dataIdMode, EndToEndTransformationDescription.dataIdMode
Literal	Description
all16Bit	Two bytes are included in the CRC (double ID configuration). Tags: atp.EnumerationLiteralIndex=0
alternating8Bit	One of the two bytes byte is included, alternating high and low byte, depending on parity of the counter (alternating ID configuration). For even counter low byte is included; For odd counters the high byte is included. Tags: atp.EnumerationLiteralIndex=1
lower12Bit	The low byte is included in the implicit CRC calculation, the low nibble of the high byte is transmitted along with the data (i.e. it is explicitly included), the high nibble of the high byte is not used. This is applicable for the IDs up to 12 bits. Tags: atp.EnumerationLiteralIndex=2
lower8Bit	Only low byte is included, high byte is never used. This is applicable if the IDs in a particular system are 8 bits. Tags: atp.EnumerationLiteralIndex=3

Table A.269: DataIdModeEnum

Class	DataInterface (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	The purpose of this meta-class is to act as an abstract base class for subclasses that share the semantics of being concerned about data (as opposed to e.g. operations).			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable			
Subclasses	NvDataInterface, ParameterInterface, SenderReceiverInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.270: DataInterface

Class	DataMapping (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	Mapping of port elements (data elements and parameters) to frames and signals.			
Base	ARObject			
Subclasses	ClientServerToSignalMapping, SenderReceiverCompositeElementToSignalMapping, SenderReceiverToSignalGroupMapping, SenderReceiverToSignalMapping, TriggerToSignalMapping			
Aggregated by	SystemMapping.dataMapping			
Attribute	Type	Mult.	Kind	Note
introduction	DocumentationBlock	0..1	aggr	This represents introductory documentation about the data mapping.

Table A.271: DataMapping

Class	DataPrototype (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::DataPrototypes			
Note	Base class for prototypical roles of any data type.			
Base	ARObject, AtpFeature, AtpPrototype, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	ApplicationCompositeElementDataPrototype, AutosarDataPrototype			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
swDataDef Props	SwDataDefProps	0..1	aggr	This property allows to specify data definition properties which apply on data prototype level. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.272: DataPrototype

Class	DataPrototypeInClientServerInterfaceInstanceRef			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer::InstanceRef			
Note				
Base	ARObject, AtpInstanceRef, DataPrototypeInPortInterfaceInstanceRef			
Aggregated by	DataPrototypeInPortInterfaceRef.dataPrototypeInClientServerInterface, DiagnosticServiceSwMapping.accessedDataPrototype			
Attribute	Type	Mult.	Kind	Note
base	ClientServerInterface	0..1	ref	Stereotypes: atpDerived





Class	DataPrototypeInClientServerInterfaceInstanceRef			
contextDataPrototypeInCs (ordered)	ApplicationCompositeElementDataPrototype	*	ref	Tags: xml.sequenceOffset=20
rootDataPrototypeInCs	AutosarDataPrototype	0..1	ref	Tags: xml.sequenceOffset=10
targetDataPrototypeInCs	DataPrototype	0..1	ref	Tags: xml.sequenceOffset=30

Table A.273: DataPrototypeInClientServerInterfaceInstanceRef

Class	DataPrototypeInPortInterfaceRef			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	This class represents a RootDataPrototype that is typed by an ApplicationDataType or ImplementationDataType or a DataTypeElement that is aggregated within a composite application data type (record or array).			
Base	<i>ARObject</i> , DataPrototypeReference			
Aggregated by	DataPrototypeTransformationProps.dataPrototypeInPortInterfaceRef , SignalServiceTranslationElementProps.element , TransmissionComSpecProps.onChangeDataPrototype			
Attribute	Type	Mult.	Kind	Note
dataPrototypeInClientServerInterface	DataPrototype	0..1	iref	This element defines a reference to a DataPrototype in the context of a ClientServerInterface. InstanceRef implemented by: DataPrototypeInClientServerInterfaceInstanceRef
dataPrototypeInSenderReceiverInterface	DataPrototype	0..1	iref	This element defines a reference to a DataPrototype in the context of a SenderReceiverInterface. InstanceRef implemented by: DataPrototypeInSenderReceiverInterfaceInstanceRef

Table A.274: DataPrototypeInPortInterfaceRef

Class	DataPrototypeInSenderReceiverInterfaceInstanceRef			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer::InstanceRef			
Note				
Base	<i>ARObject</i> , AtpInstanceRef , DataPrototypeInPortInterfaceInstanceRef			
Aggregated by	DataPrototypeInPortInterfaceRef.dataPrototypeInSenderReceiverInterface			
Attribute	Type	Mult.	Kind	Note
base	SenderReceiverInterface	0..1	ref	Stereotypes: atpDerived
contextDataPrototypeInSr (ordered)	ApplicationCompositeElementDataPrototype	*	ref	Tags: xml.sequenceOffset=20
rootDataPrototypeInSr	AutosarDataPrototype	0..1	ref	Tags: xml.sequenceOffset=10
targetDataPrototypeInSr	DataPrototype	0..1	ref	Tags: xml.sequenceOffset=30

Table A.275: DataPrototypeInSenderReceiverInterfaceInstanceRef

Class	DataPrototypeMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	<p>Defines the mapping of two particular VariableDataPrototypes, ParameterDataPrototypes or Argument DataPrototypes with non-equal shortNames, non-equal structure (specific condition is described by [constr_1187]), and/or non-equal semantic (resolution or range) in context of two different Sender ReceiverInterface, NvDataInterface or ParameterInterface or Operations.</p> <p>If the semantic is unequal, the following rules apply: The textTableMapping is only applicable if the referred DataPrototypes are typed by AutosarDataType referring to CompuMethods of category TEXTTABLE, SCALE_LINEAR_AND_TEXTTABLE or BITFIELD_TEXTTABLE.</p> <p>In the case that the DataPrototypes are typed by AutosarDataType either referring to CompuMethods of category LINEAR, IDENTICAL or referring to no CompuMethod (which is similar as IDENTICAL) the linear conversion factor is calculated out of the factorSiToUnit and offsetSiToUnit attributes of the referred Units and the CompuRationalCoeffs of a compuInternalToPhys of the referred CompuMethods.</p>			
Base	ARObject			
Aggregated by	ClientServerOperationMapping.argumentMapping, VariableAndParameterInterfaceMapping.dataMapping			
Attribute	Type	Mult.	Kind	Note
firstData Prototype	AutosarDataType	0..1	ref	First to be mapped DataPrototype in context of a Sender ReceiverInterface, NvDataInterface, ParameterInterface or Operation.
firstToSecond Data Transformation	DataTransformation	0..1	ref	<p>This reference defines the need to execute the Data Transformation <Mip>_<transformerId> functions of the transformation chain when communicating from the Data PrototypeMapping.firstDataPrototype to the Data PrototypeMapping.secondDataPrototype.</p> <p>This reference also specifies the reverse Data Transformation <Mip>_Inv_<transformerId> functions of the transformation chain (i.e. from the DataPrototype Mapping.secondDataPrototype to the DataPrototype Mapping.firstDataPrototype) if the referenced Data Transformation is symmetric, i.e. attribute Data Transformation.dataTransformationKind is set to symmetric.</p>
secondData Prototype	AutosarDataType	0..1	ref	Second to be mapped DataPrototype in context of a SenderReceiverInterface, NvDataInterface, Parameter Interface or Operation.
secondToFirst Data Transformation	DataTransformation	0..1	ref	This defines the need to execute the reverse Data Transformation <Mip>_Inv_<transformerId> functions of the transformation chain when communicating from the DataPrototypeMapping.secondDataPrototype to the Data PrototypeMapping.firstDataPrototype.
subElement Mapping	SubElementMapping	*	aggr	<p>This represents the owned SubelementMapping.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=subElementMapping</p>
textTable Mapping	TextTableMapping	0..2	aggr	Applied TextTableMapping(s)

Table A.276: DataPrototypeMapping

Class	DataPrototypeReference (abstract)
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer
Note	This meta-class provides the ability to reference a DataPrototype.
Base	ARObject
Subclasses	DataPrototypeInPortInterfaceRef, ImplementationDataTypeElementInPortInterfaceRef
Aggregated by	DataPrototypeTransformationProps.dataPrototypeInPortInterfaceRef, SignalServiceTranslationElement Props.element, TransmissionComSpecProps.onChangeDataPrototype





Class	DataPrototypeReference (abstract)			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.277: DataPrototypeReference

Class	DataPrototypeTransformationProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	DataPrototypeTransformationProps allows to set the attributes for the different Transformation Technologies that are DataPrototype specific.			
Base	ARObject			
Aggregated by	TransformationISignalProps.dataPrototypeTransformationProps			
Attribute	Type	Mult.	Kind	Note
dataPrototypeInPortInterfaceRef	DataPrototypeReference	0..1	aggr	Reference to a DataPrototype that is transported in the serialized ISignal.
ident	DataPrototypeTransformationPropsIdent	0..1	aggr	This adds the ability to add a shortName to DataPrototypeTransformationProps. Please note that the short-name needs to be provided if the splittable mechanism is used.
networkRepresentationProps	SwDataDefProps	0..1	aggr	Specification of the actual network representation for the referenced primitive DataPrototype. If a network representation is provided then the baseType shall be used by the Transformer as input for the serialization/deserialization. Stereotypes: atpSplittable Tags: atp.Splitkey=networkRepresentationProps
transformationProps	TransformationProps	0..1	ref	Collection of AutosarDataPrototype related configuration settings for a transformer.

Table A.278: DataPrototypeTransformationProps

Class	DataReceiveErrorEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the Com layer detects and notifies an error concerning the reception of the referenced VariableDataPrototype.			
Base	ARObject, AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
data	VariableDataPrototype	0..1	iref	The referenced VariableDataPrototype raises this DataReceiveErrorEvent when there was an error during the reception. InstanceRef implemented by: RVariableInAtomicSwcInstanceRef

Table A.279: DataReceiveErrorEvent

Class	DataReceivedEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the referenced data element is received.			
Base	ARObject, AbstractEvent, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, RTEEvent, Referrable			
Aggregated by	AtpClassifier.atpFeature, SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
data	VariableDataPrototype	0..1	iref	The referenced VariableDataPrototype raises this DataReceivedEvent when the data has been received. InstanceRef implemented by: RVariableInAtomicSwc InstanceRef

Table A.280: DataReceivedEvent

Class	DataSendCompletedEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the referenced explicit data element has been sent or an error occurred.			
Base	ARObject, AbstractEvent, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, RTEEvent, Referrable			
Aggregated by	AtpClassifier.atpFeature, SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
eventSource	VariableAccess	0..1	ref	The referenced VariableAccess raises this DataSendCompletedEvent when the explicit write access was successful or an error occurred.

Table A.281: DataSendCompletedEvent

Class	DataTransformation			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	A DataTransformation represents a transformer chain. It is an ordered list of transformers.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	DataTransformationSet.dataTransformation			
Attribute	Type	Mult.	Kind	Note
dataTransformationKind	DataTransformationKindEnum	0..1	attr	This attribute controls the kind of DataTransformation to be applied.
executeDespiteDataUnavailability	Boolean	0..1	attr	Specifies whether the transformer chain is executed even if no input data are available.
transformerChain (ordered)	TransformationTechnology	*	ref	This attribute represents the definition of a chain of transformers that are supposed to be executed according to the order of being referenced from DataTransformation.

Table A.282: DataTransformation

Enumeration	DataTransformationKindEnum			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	This enumeration contributes to the definition of the scope of the DataTransformation.			
Aggregated by	DataTransformation.dataTransformationKind			
Literal	Description			





Enumeration	DataTransformationKindEnum
asymmetricFromByteArray	The DataTransformation shall only be applied to the receiving end only, i.e. transform from byte array to data type. Tags: atp.EnumerationLiteralIndex=0
asymmetricToByteArray	The DataTransformation shall be applied to the sending end only, i.e. from data type to byte array. Tags: atp.EnumerationLiteralIndex=1
symmetric	The DataTransformation shall be applied at both the sending and the receiving end of the communication. Tags: atp.EnumerationLiteralIndex=2

Table A.283: DataTransformationKindEnum

Class	DataTypeMap			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes			
Note	This class represents the relationship between ApplicationDataType and its implementing AbstractImplementationDataType.			
Base	ARObject			
Aggregated by	DataTypeMappingSet.dataTypeMap			
Attribute	Type	Mult.	Kind	Note
applicationDataType	ApplicationDataType	0..1	ref	This is the corresponding ApplicationDataType
implementationDataType	AbstractImplementationDataType	0..1	ref	This is the corresponding AbstractImplementationDataType.

Table A.284: DataTypeMap

Class	DataTypeMappingSet			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::Datatypes			
Note	This class represents a list of mappings between ApplicationDataTypes and ImplementationDataTypes. In addition, it can contain mappings between ImplementationDataTypes and ModeDeclarationGroups. Tags: atp.recommendedPackage=DataTypeMappingSets			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataTypeMap	DataTypeMap	*	aggr	This is one particular association between an ApplicationDataType and its AbstractImplementationDataType.
modeRequestTypeMap	ModeRequestTypeMap	*	aggr	This is one particular association between an ModeDeclarationGroup and its AbstractImplementationDataType.

Table A.285: DataTypeMappingSet

Enumeration	DataTypePolicyEnum
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping
Note	This class lists the supported DataTypePolicies.
Aggregated by	ISignal.dataTypePolicy
Literal	Description





Enumeration	DataPolicyEnum
ddsService	This literal indicates that this ISignal is used to transport a message as part of a service for Dds. Tags: atp.EnumerationLiteralIndex=6 atp.Status=candidate
ddsSignal	This literal indicates that this ISignal is used to transport a signal based signal for Dds. Tags: atp.EnumerationLiteralIndex=5 atp.Status=candidate
legacy	In case the System Description doesn't use a complete Software Component Description (VFB View) this value can be chosen. This supports the inclusion of legacy signals. The aggregation of SwDataDefProps shall be used to configure the "ComSignalDataInvalidValue" and the Data Semantics. Tags: atp.EnumerationLiteralIndex=0
networkRepresentationFromComSpec	Ignore any networkRepresentationProps of this ISignal and use the networkRepresentation from the ComSpec. Please note that the usage does not imply the existence of the SwDataDefProps in the role networkRepresentation aggregated by the SenderComSpec or ReceiverComSpec if an ImplementationDataType is defined. Tags: atp.EnumerationLiteralIndex=1
override	If this value is chosen the requirements specified in the ComSpec (networkRepresentationFromComSpec) are not fulfilled by the aggregated SwDataDefProps. In this case the networkRepresentation is specified by the aggregated swDataDefProps. Tags: atp.EnumerationLiteralIndex=2
transformingISignal	This literal indicates that a transformer chain shall be used to communicate the ISignal as UINT8_N over the bus. Tags: atp.EnumerationLiteralIndex=4

Table A.286: DataPolicyEnum

Class	DataWriteCompletedEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when an implicit write access was successful or an error occurred.			
Base	ARObject, AbstractEvent, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, RTEEvent, Referrable			
Aggregated by	AtpClassifier.atpFeature, SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
eventSource	VariableAccess	0..1	ref	The referenced VariableAccess raises this DataWriteCompletedEvent when the implicit write access was successful or an error occurred.

Table A.287: DataWriteCompletedEvent

Class	DcmIPdu
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	Represents the IPdus handled by Dcm. Tags: atp.recommendedPackage=Pdus
Base	ARElement, ARObject, CollectableElement, FibexElement, IPdu, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement
Aggregated by	ARPackage.element





Class				
DcmIPdu				
Attribute	Type	Mult.	Kind	Note
diagPduType	DiagPduType	0..1	attr	Attribute is used to distinguish a request from a response.

Table A.288: DcmIPdu

Class				
DdsCplSignalToDdsTopicMapping				
Package				
M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::Dds				
Note				
Mapping of an ISignal to a DdsTopic. Tags: atp.Status=candidate				
Base				
ARObject				
Aggregated by				
SystemMapping.ddsISignalToTopicMapping				
Attribute	Type	Mult.	Kind	Note
ddsTopic	DdsCpTopic	0..1	ref	Reference to the DdsTopic. Tags: atp.Status=candidate
iSignal	ISignal	0..1	ref	Reference to the ISignal. Tags: atp.Status=candidate

Table A.289: DdsCplSignalToDdsTopicMapping

Class				
DdsCpServiceInstance (abstract)				
Package				
M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::Dds				
Note				
Provided and Consumed Dds Service Instances that are available at the ApplicationEndpoint. Tags: atp.Status=candidate				
Base				
ARObject, AbstractServiceInstance , Identifiable , MultilanguageReferrable , Referrable				
Subclasses				
DdsCpConsumedServiceInstance, DdsCpProvidedServiceInstance				
Aggregated by				
ServiceInstanceCollectionSet.serviceInstance				
Attribute	Type	Mult.	Kind	Note
ddsFieldReplyTopic	DdsCpTopic	0..1	ref	Reference to the DdsTopic used as fragment for the topic name of field setters. Tags: atp.Status=candidate
ddsFieldRequestTopic	DdsCpTopic	0..1	ref	Reference to the DdsTopic used as fragment for the topic name of field getters. Tags: atp.Status=candidate
ddsMethodReplyTopic	DdsCpTopic	0..1	ref	Reference to the DdsTopic used as fragment for the topic name of method replies. Tags: atp.Status=candidate
ddsMethodRequestTopic	DdsCpTopic	0..1	ref	Reference to the DdsTopic used as fragment for the topic name of method requests. Tags: atp.Status=candidate
ddsServiceQosProfile	DdsCpQosProfile	0..1	ref	Reference to the QOS Profile used for the service. Tags: atp.Status=candidate
serviceInstanceId	PositiveInteger	0..1	attr	Identification number that is used by DDS to identify DomainParticipants associated with an instance of the service. Tags: atp.Status=candidate





Class		DdsCpServiceInstance (abstract)		
serviceInterfaceId	String	0..1	attr	Unique Identifier that identifies the ServiceInterface in DDS. This Identifier is encoded in the USER_DATA QoS of the DomainParticipant associated with the Service Instance and its value is propagated by DDS Discovery messages. Tags: atp.Status=candidate

Table A.290: DdsCpServiceInstance

Class		DdsCpServiceInstanceEvent		
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::Dds			
Note	This element represents an event as part of the Provided Service Instance. Tags: atp.Status=candidate			
Base	ARObject			
Aggregated by	DdsCpConsumedServiceInstance.consumedDdsServiceEvent, DdsCpProvidedServiceInstance.providedDdsServiceInstanceEvent			
Attribute	Type	Mult.	Kind	Note
ddsEvent	PduTriggering	0..1	ref	Reference to the PduTriggerung used for the upper layer transport of this DdsEvent message. Tags: atp.Status=candidate
ddsEventQosProfile	DdsCpQosProfile	0..1	ref	Reference to the QOS Profile used for this Event. Tags: atp.Status=candidate
ddsEventTopic	DdsCpTopic	0..1	ref	Reference to the DDS Topic used for this Event. Tags: atp.Status=candidate

Table A.291: DdsCpServiceInstanceEvent

Class		DdsCpServiceInstanceOperation		
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::Dds			
Note	This element represents an operation as part of the Provided Service Instance. Tags: atp.Status=candidate			
Base	ARObject			
Aggregated by	DdsCpConsumedServiceInstance.consumedDdsOperation, DdsCpProvidedServiceInstance.providedDdsOperation			
Attribute	Type	Mult.	Kind	Note
ddsOperationRequestTriggering	PduTriggering	0..1	ref	Reference to the PduTriggering used for the upper layer transport of this DdsOperation request message. Tags: atp.Status=candidate
ddsOperationResponseTriggering	PduTriggering	0..1	ref	Reference to the PduTriggering used for the upper layer transport of this DdsOperation response message. Tags: atp.Status=candidate

Table A.292: DdsCpServiceInstanceOperation

Class	DefaultValueElement			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Multiplatform			
Note	The default value consists of a number of elements. Each element is one byte long and the number of elements is specified by SduLength.			
Base	ARObject			
Aggregated by	PduMappingDefaultValue.defaultValueElement			
Attribute	Type	Mult.	Kind	Note
elementByte Value	Integer	0..1	attr	The integer value of a freely defined data byte.
elementPosition	Integer	0..1	attr	This attribute specifies the byte position of the element within the default value

Table A.293: DefaultValueElement

Class	DelegatedPortAnnotation			
Package	M2::AUTOSARTemplates::SWComponentTemplate::ApplicationAttributes			
Note	Annotation to a "delegated port" to specify the Signal Fan In or Signal Fan Out inside the CompositionSw ComponentType.			
Base	ARObject, GeneralAnnotation			
Aggregated by	PortPrototype.delegatedPortAnnotation			
Attribute	Type	Mult.	Kind	Note
signalFan	SignalFanEnum	0..1	attr	Specifies the Signal Fan In or Signal Fan Out inside the Composition Type.

Table A.294: DelegatedPortAnnotation

Class	DelegationSwConnector			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	A delegation connector delegates one inner PortPrototype (a port of a component that is used inside the composition) to a outer PortPrototype of compatible type that belongs directly to the composition (a port that is owned by the composition).			
Base	ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, Referrable, SwConnector			
Aggregated by	AtpClassifier.atpFeature , CompositionSwComponentType.connector			
Attribute	Type	Mult.	Kind	Note
innerPort	PortPrototype	0..1	iref	The port that belongs to the ComponentPrototype in the composition Tags: xml.typeElement=true InstanceRef implemented by: PortInCompositionType InstanceRef
outerPort	PortPrototype	0..1	ref	The port that is located on the outside of the Composition Type

Table A.295: DelegationSwConnector

Class	DependencyOnArtifact			
Package	M2::AUTOSARTemplates::CommonStructure::Implementation			
Note	Dependency on the existence of another artifact, e.g. a library.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	Implementation.generatedArtifact , Implementation.requiredArtifact , Implementation.requiredGenerator Tool			





Class		DependencyOnArtifact		
Attribute	Type	Mult.	Kind	Note
artifact Descriptor	AutosarEngineering Object	0..1	aggr	The specified artifact needs to exist.
usage	DependencyUsage Enum	*	attr	Specification for which process step(s) this dependency is required.

Table A.296: DependencyOnArtifact

Class		Dhcpv6Props		
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This meta-class specifies the configuration options for DHCPv6.			
Base	ARObject			
Aggregated by	Ipv6Props.dhcpProps			
Attribute	Type	Mult.	Kind	Note
tcplpDhcp V6CnfDelayMax	TimeValue	0..1	attr	Maximum delay in seconds before sending the first Confirm message. If this value is bigger than the previous minimum delay value a random delay will be chosen from the interval.
tcplpDhcp V6CnfDelayMin	TimeValue	0..1	attr	Minimum delay in seconds before the first Confirm message will be sent.
tcplpDhcpV6Inf DelayMax	TimeValue	0..1	attr	Maximum delay in seconds before sending the first Information Request message. If this value is bigger than the previous minimum delay value a random delay will be chosen from the interval.
tcplpDhcpV6Inf DelayMin	TimeValue	0..1	attr	Minimum delay (s) before the first Information Request message will be sent.
tcplpDhcpV6Sol DelayMax	TimeValue	0..1	attr	Maximum delay in seconds before sending the first Solicit message. If this value is bigger than the previous minimum delay value a random delay will be chosen from the interval.
tcplpDhcpV6Sol DelayMin	TimeValue	0..1	attr	Minimum delay (s) before the first Solicit message will be sent.

Table A.297: Dhcpv6Props

Class		DiagEventDebounceCounterBased		
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	This meta-class represents the ability to indicate that the counter-based debounce algorithm shall be used by the DEM for this diagnostic monitor. This is related to set the ECUC choice container DemDebounceAlgorithmClass to DemDebounce CounterBased.			
Base	ARObject, DiagEventDebounceAlgorithm , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DiagnosticDebounceAlgorithmProps.debounceAlgorithm , DiagnosticEventNeeds.diagEventDebounce Algorithm			
Attribute	Type	Mult.	Kind	Note
counterBased FdcThreshold StorageValue	Integer	0..1	attr	Threshold to allocate an event memory entry and to capture the Freeze Frame.





Class	DiagEventDebounceCounterBased			
counterDecrementStepSize	Integer	0..1	attr	This value shall be taken to decrement the internal debounce counter. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
counterFailedThreshold	Integer	0..1	attr	This value defines the event-specific limit that indicates the "failed" counter status. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
counterIncrementStepSize	Integer	0..1	attr	This value shall be taken to increment the internal debounce counter. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
counterJumpDown	Boolean	0..1	attr	This value activates or deactivates the counter jump-down behavior. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
counterJumpDownValue	Integer	0..1	attr	This value represents the initial value of the internal debounce counter if the counting direction changes from incrementing to decrementing. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
counterJumpUp	Boolean	0..1	attr	This value activates or deactivates the counter jump-up behavior. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
counterJumpUpValue	Integer	0..1	attr	This value represents the initial value of the internal debounce counter if the counting direction changes from decrementing to incrementing. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
counterPassedThreshold	Integer	0..1	attr	This value defines the event-specific limit that indicates the "passed" counter status. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.298: DiagEventDebounceCounterBased

Class	DiagEventDebounceMonitorInternal			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	This meta-class represents the ability to indicate that no Dem pre-debounce algorithm shall be used for this diagnostic monitor. The SWC might implement an internal debouncing algorithm and report qualified (debounced) results to the Dem/DM.			
Base	ARObject, DiagEventDebounceAlgorithm , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DiagnosticDebounceAlgorithmProps.debounceAlgorithm , DiagnosticEventNeeds.diagEventDebounceAlgorithm			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.299: DiagEventDebounceMonitorInternal

Class	DiagEventDebounceTimeBased			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	This meta-class represents the ability to indicate that the time-based pre-debounce algorithm shall be used by the Dem for this diagnostic monitor. This is related to set the EcuC choice container DemDebounceAlgorithmClass to DemDebounceTimeBase.			
Base	ARObject, DiagEventDebounceAlgorithm , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DiagnosticDebounceAlgorithmProps.debounceAlgorithm , DiagnosticEventNeeds.diagEventDebounceAlgorithm			
Attribute	Type	Mult.	Kind	Note
timeBasedFdcThresholdStorageValue	TimeValue	0..1	attr	Threshold to allocate an event memory entry and to capture the Freeze Frame. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
timeFailedThreshold	TimeValue	0..1	attr	This value represents the event-specific delay indicating the "failed" status. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
timePassedThreshold	TimeValue	0..1	attr	This value represents the event-specific delay indicating the "passed" status. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.300: DiagEventDebounceTimeBased

Class	DiagnosticAbstractDataIdentifier (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents an abstract base class for the modeling of a diagnostic data identifier (DID).			
Base	ARElement, ARObject, CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	DiagnosticDataIdentifier , DiagnosticDynamicDataIdentifier			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
id	PositiveInteger	0..1	attr	This is the numerical identifier used to identify the DiagnosticAbstractDataIdentifier in the scope of diagnostic workflow Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.301: DiagnosticAbstractDataIdentifier

Class	DiagnosticAbstractParameter (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents an abstract base class for modeling a diagnostic parameter.			
Base	ARObject			
Subclasses	DiagnosticParameter , DiagnosticParameterElement			
Attribute	Type	Mult.	Kind	Note





Class	<i>DiagnosticAbstractParameter</i> (abstract)			
bitOffset	PositiveInteger	0..1	attr	This represents the bitOffset of the DiagnosticParameter. The value of the bitOffset shall always be interpreted as relative to the start of the enclosing DiagnosticData Identifier, DiagnosticParameterIdentifier, or Diagnostic RoutineSubfunction. Stereotypes: atpIdentityContributor Tags: atp.Status=candidate
dataElement	DiagnosticDataElement	0..1	aggr	This represents the related dataElement of the Diagnostic Parameter Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataElement.shortName, data Element.variationPoint.shortLabel vh.latestBindingTime=postBuild
parameterSize	PositiveInteger	0..1	attr	This attribute allows for the specification of the parameter size. This information is relevant if there is a gap between one diagnostic parameter and the following diagnostic parameter (or the tail of the telegram). The unit is bit and the values shall be multiples of 8. Tags: atp.Status=candidate

Table A.302: DiagnosticAbstractParameter

Class	<i>DiagnosticAccessPermission</i>			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm			
Note	This represents the specification of whether a given service can be accessed according to the existence of meta-classes referenced by a particular DiagnosticAccessPermission. In other words, this meta-class acts as a mapping element between several (otherwise unrelated) pieces of information that are put into context for the purpose of checking for access rights. Tags: atp.recommendedPackage=DiagnosticAccessPermissions			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , Multilanguage Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
authentication Enabled	DiagnosticAuthRole Proxy	0..1	aggr	The existence of this aggregation indicates that an authentication is foreseen. The details are clarified by the aggregated class. Stereotypes: atpSplitable Tags: atp.Splitkey=authenticationEnabled
diagnostic Session	DiagnosticSession	*	ref	This represents the associated DiagnosticSessions Stereotypes: atpSplitable Tags: atp.Splitkey=diagnosticSession
environmental Condition	Diagnostic EnvironmentalCondition	0..1	ref	This represents the environmental conditions associated with the access permission. Stereotypes: atpSplitable Tags: atp.Splitkey=environmentalCondition
securityLevel	DiagnosticSecurityLevel	*	ref	This represents the associated DiagnosticSecurityLevels Stereotypes: atpSplitable Tags: atp.Splitkey=securityLevel

Table A.303: DiagnosticAccessPermission

Class	DiagnosticAging			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticAging			
Note	Defines the aging algorithm. Tags: atp.recommendedPackage=DiagnosticAging			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
agingCycle	DiagnosticOperationCycle	0..1	ref	This represents the applicable aging cycle. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=agingCycle.diagnosticOperationCycle, agingCycle.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
threshold	PositiveInteger	0..1	attr	Number of aging cycles needed to unlearn/delete the event. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.304: DiagnosticAging

Class	DiagnosticAuthentication (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::Authentication			
Note	This meta-class represents the ability to configure the usage of the UDS service Authentication in the Diagnostic extract.			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	DiagnosticAuthTransmitCertificate , DiagnosticAuthenticationConfiguration , DiagnosticDeAuthentication , DiagnosticProofOfOwnership , DiagnosticVerifyCertificateBidirectional , DiagnosticVerifyCertificateUnidirectional			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
authenticationClass	DiagnosticAuthenticationClass	0..1	ref	This represents the corresponding "class", i.e. this meta-class provides properties that are shared among all instances of applicable sub-classes of DiagnosticServiceInstance. The subclasses that affected by this pattern implement references to the applicable "class"-role that substantiate this abstract reference.

Table A.305: DiagnosticAuthentication

Class	DiagnosticAuthenticationConfiguration			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::Authentication			
Note	This meta-class represents the subfunction to configure the authentication. Tags: atp.recommendedPackage=DiagnosticAuthentications			
Base	ARElement , ARObject , CollectableElement , DiagnosticAuthentication , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.306: DiagnosticAuthenticationConfiguration

Class	DiagnosticClearResetEmissionRelatedInfo			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x04_ClearResetEmissionRelatedInfo			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x04 service. Tags: atp.recommendedPackage=DiagnosticClearResetEmissionRelatedInfos			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
clearResetEmissionRelatedDiagnosticInfoClass	DiagnosticClearResetEmissionRelatedInfoClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticClearResetEmissionRelatedInfo in the given context.

Table A.307: DiagnosticClearResetEmissionRelatedInfo

Class	DiagnosticComControl			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::CommunicationControl			
Note	This represents an instance of the "Communication Control" diagnostic service. Tags: atp.recommendedPackage=DiagnosticCommunicationControls			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
comControlClass	DiagnosticComControlClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticComControl in the given context.
customSubFunctionNumber	PositiveInteger	0..1	attr	This attribute shall be used to define a custom sub-function number if none of the standardized values of category shall be used.

Table A.308: DiagnosticComControl

Class	DiagnosticComControlSpecificChannel			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::CommunicationControl			
Note	This represents the ability to add further attributes to the definition of a specific channel that is subject to the diagnostic service "communication control".			
Base	<i>ARObject</i>			
Aggregated by	DiagnosticComControlClass.specificChannel			
Attribute	Type	Mult.	Kind	Note
specificChannel	CommunicationCluster	0..1	ref	This represents the affected CommunicationCluster in the role specificChannel
specificPhysicalChannel	EthernetPhysicalChannel	0..1	ref	This represents the affected specific EthernetPhysicalChannel.
subnetNumber	PositiveInteger	0..1	attr	This represents the applicable subnet number (which is an arbitrary number ranging from 1..14)

Table A.309: DiagnosticComControlSpecificChannel

Class	DiagnosticComControlSubNodeChannel			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::CommunicationControl			
Note	This represents the ability to add further attributes to the definition of a specific sub-node channel that is subject to the diagnostic service "communication control".			
Base	<i>ARObject</i>			
Aggregated by	DiagnosticComControlClass.subNodeChannel			
Attribute	Type	Mult.	Kind	Note
subNode Channel	CommunicationCluster	0..1	ref	This represents the affected CommunicationCluster in the role subNodeChannel
subNode Number	PositiveInteger	0..1	attr	This represents the applicable subNode number. The value corresponds to the request message parameter nodeIdentificationNumber of diagnostic service CommunicationControl (0x28).
subNode Physical Channel	EthernetPhysicalChannel	0..1	ref	This represents the affected sub-node EthernetPhysicalChannel.

Table A.310: DiagnosticComControlSubNodeChannel

Class	DiagnosticCommonElement (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents a common base class for all diagnostic elements. It does not contribute any specific functionality other than the ability to become the target of a reference.			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Subclasses	<i>DiagnosticAbstractAliasEvent, DiagnosticAbstractDataIdentifier, DiagnosticAccessPermission, DiagnosticAging, DiagnosticAuthRole, DiagnosticCondition, DiagnosticConditionGroup, DiagnosticCustomServiceClass, DiagnosticDataIdentifierSet, DiagnosticEcuInstanceProps, DiagnosticEnvironmentalCondition, DiagnosticEvent, DiagnosticExtendedDataRecord, DiagnosticFimEventGroup, DiagnosticFreezeFrame, DiagnosticFunctionIdentifier, DiagnosticFunctionIdentifierInhibit, DiagnosticIndicator, DiagnosticInfoType, DiagnosticLumpr, DiagnosticLumprDenominatorGroup, DiagnosticLumprGroup, DiagnosticJ1939ExpandedFreezeFrame, DiagnosticJ1939FreezeFrame, DiagnosticJ1939Node, DiagnosticJ1939Spn, DiagnosticMapping, DiagnosticMeasurementIdentifier, DiagnosticMemoryDestination, DiagnosticMemoryIdentifier, DiagnosticOperationCycle, DiagnosticParameterIdentifier, DiagnosticPowertrainFreezeFrame, DiagnosticProtocol, DiagnosticRoutine, DiagnosticSecurityLevel, DiagnosticServiceClass, DiagnosticServiceInstance, DiagnosticServiceTable, DiagnosticSession, DiagnosticTestResult, DiagnosticTestRoutineIdentifier, DiagnosticTroubleCode, DiagnosticTroubleCodeGroup, DiagnosticTroubleCodeProps</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.311: DiagnosticCommonElement

Class	«atpVariation» DiagnosticCommonProps			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticCommonProps			
Note	This meta-class aggregates a number of common properties that are shared among a diagnostic extract. Tags: vh.latestBindingTime=codeGenerationTime			
Base	<i>ARObject</i>			
Aggregated by	DiagnosticContributionSet.commonProperties			
Attribute	Type	Mult.	Kind	Note





Class	«atpVariation» DiagnosticCommonProps			
authentication Timeout	TimeValue	0..1	attr	This attribute defines the time (in seconds) that the authentication state is maintained in default-session if there is no communication from the authenticated client.
debounce AlgorithmProps	DiagnosticDebounce AlgorithmProps	*	aggr	Defines the used debounce algorithms relevant in the context of the enclosing DiagnosticCommonProps. Usually, there is a variety of debouncing algorithms to take into account and therefore the multiplicity of this aggregation is set to 0..*. Note: This atpSplittable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplittable; atpVariation Tags: vh.latestBindingTime=postBuild
default Endianness	ByteOrderEnum	0..1	attr	Defines the default endianness of the data belonging to a DID or RID which is applicable if the DiagnosticData Element does not define the endianness via the swData DefProps.baseType attribute.
event Combination Reporting Behavior	DiagnosticEvent CombinationReporting BehaviorEnum	0..1	attr	In case of EventCombination on Retrieval, this attribute specifies if a specific order of reporting is to be maintained.
maxNumberOf Request Correctly Received Response Pending	PositiveInteger	0..1	attr	Maximum number of negative responses with response code 0x78 (requestCorrectlyReceived-ResponsePending) allowed per request. DCM will send a negative response with response code 0x10 (generalReject), in case the limit value gets reached. Value 0xFF means that no limit number of NRC 0x78 response apply.
occurrence Counter Processing	DiagnosticOccurrence CounterProcessing Enum	0..1	attr	This attribute defines the consideration of the fault confirmation process for the occurrence counter.
resetConfirmed BitOnOverflow	Boolean	0..1	attr	This attribute defines, whether the confirmed bit is reset or not while an event memory entry will be displaced.
resetPendingBit OnOverflow	Boolean	0..1	attr	This attribute defines, whether the pending bit is reset or not while an event memory entry will be displaced. In order to be compliant to ISO 14229-1 [1], this parameter needs to be set to "false".
responseOnAll RequestSids	Boolean	0..1	attr	If set to FALSE the DCM will not respond to diagnostic request that contains a service ID which is in the range from 0x40 to 0x7F or in the range from 0xC0 to 0xFF (Response IDs).
responseOn Second Declined Request	Boolean	0..1	attr	Defines the reaction upon a second request (ClientB) that can not be processed (e.g. due to priority assessment). TRUE: when the second request (Client B) can not be processed, it shall be answered with NRC21 BusyRepeat Request. FALSE: when the second request (Client B) can not be processed, it shall not be responded.
typeOfEvent Combination Supported	DiagnosticEvent CombinationBehavior Enum	0..1	attr	Select type of Event Combination support.

Table A.312: DiagnosticCommonProps

Enumeration	DiagnosticCompareTypeEnum
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition
Note	Enumeration for the type of a comparison of values usually expressed by the following operators: ==, !=, <, <=, >, >=
Aggregated by	DiagnosticEnvCompareCondition.compareType
Literal	Description
isEqual	equal Tags: atp.EnumerationLiteralIndex=0
isGreaterOrEqual	greater than or equal Tags: atp.EnumerationLiteralIndex=5
isGreaterThan	greater than Tags: atp.EnumerationLiteralIndex=4
isLessOrEqual	less than or equal Tags: atp.EnumerationLiteralIndex=3
isLessThan	less than Tags: atp.EnumerationLiteralIndex=2
isNotEqual	not equal Tags: atp.EnumerationLiteralIndex=1

Table A.313: DiagnosticCompareTypeEnum

Class	DiagnosticCondition (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticCondition			
Note	Abstract element for StorageConditions and EnableConditions.			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	DiagnosticEnableCondition , DiagnosticStorageCondition			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
initValue	Boolean	0..1	attr	Defines the initial status for enable or disable of acceptance/storage of event reports of a diagnostic event. The value is the initialization after power up (before this condition is reported the first time). true: acceptance/storage of a diagnostic event enabled false: acceptance/storage of a diagnostic event disabled

Table A.314: DiagnosticCondition

Class	DiagnosticConnectedIndicator			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticEvent			
Note	Description of indicators that are defined per DiagnosticEvent.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DiagnosticEvent.connectedIndicator			
Attribute	Type	Mult.	Kind	Note
behavior	DiagnosticConnectedIndicatorBehaviorEnum	0..1	attr	Behavior of the linked indicator.





Class	DiagnosticConnectedIndicator			
healingCycle	DiagnosticOperation Cycle	0..1	ref	The deactivation of indicators per event is defined as healing of a diagnostic event. The operation cycle in which the warning indicator will be switched off is defined here.
healingCycle Counter Threshold	PositiveInteger	0..1	attr	This attribute defines the number of healing cycles for the WarningIndicatorOffCriteria Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
indicator	DiagnosticIndicator	0..1	ref	Reference to the used indicator.
indicatorFailure CycleCounter Threshold	PositiveInteger	0..1	attr	This attribute defines the number of failure cycles for the WarningIndicatorOnCriteria. Please note that this attribute is not relevant for the Adaptive Platform.

Table A.315: DiagnosticConnectedIndicator

Class	DiagnosticConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::DiagnosticConnection			
Note	DiagnosticConncection that is used to describe the relationship between several TP connections. Tags: atp.recommendedPackage=DiagnosticConnections			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
functional Request	TpConnectionIdent	*	ref	Reference to functional request messages.
periodic ResponseUudt	PduTriggering	*	ref	Reference to UUDT responses.
physical Request	TpConnectionIdent	0..1	ref	Reference to a physical request message.
response	TpConnectionIdent	0..1	ref	In the vast majority of cases a response is required. However, there are also cases where providing the response is not possible and/or not allowed.
responseOn Event	TpConnectionIdent	0..1	ref	Reference to a ROE message. Tags: atp.Status=obsolete

Table A.316: DiagnosticConnection

Class	DiagnosticContributionSet			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticContribution			
Note	This meta-class represents a root node of a diagnostic extract. It bundles a given set of diagnostic model elements. The granularity of the DiagonsticContributionSet is arbitrary in order to support the aspect of decentralized configuration, i.e. different contributors can come up with an own DiagnosticContribution Set. Tags: atp.recommendedPackage=DiagnosticContributionSets			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticContributionSet			
common Properties	DiagnosticCommon Props	0..1	aggr	This attribute represents a collection of diagnostic properties that are shared among the entire DiagnosticContributionSet. Stereotypes: atpSplittable Tags: atp.Splitkey=commonProperties
element	DiagnosticCommon Element	*	ref	This represents a DiagnosticCommonElement considered in the context of the DiagnosticContributionSet Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=element.diagnosticCommonElement, element.variationPoint.shortLabel, vh.latestBindingTime=postBuild
serviceTable	DiagnosticService Table	*	ref	This represents the collection of DiagnosticServiceTables to be considered in the scope of this DiagnosticContributionSet. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=service Table.diagnosticService Table, service Table.variationPoint.shortLabel, vh.latestBindingTime=postBuild

Table A.317: DiagnosticContributionSet

Class	DiagnosticControlEnableMaskBit			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::IOControl			
Note	This meta-class has the ability to represent one bit in the control enable mask record.			
Base	ARObject			
Aggregated by	DiagnosticIOControl.controlEnableMaskBit			
Attribute	Type	Mult.	Kind	Note
bitNumber	PositiveInteger	0..1	attr	This attribute represents the bit number of the bit in the control mask record. Bit number 0 is the most significant bit (MSB) in the first byte of the CEMR in the network presentation.
controlledData Element	DiagnosticDataElement	*	ref	This reference represents the collection of DiagnosticDataElements that are controlled by this bit of the control mask record.

Table A.318: DiagnosticControlEnableMaskBit

Class	DiagnosticCustomServiceClass			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::CommonService			
Note	This represents the ability to define a custom diagnostic service class and assign an ID to it. Further configuration is not foreseen from the point of view of the diagnostic extract and consequently needs to be done on the level of ECUC. Tags: atp.recommendedPackage=DiagnosticCustomServiceClasses			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticServiceClass , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class		DiagnosticCustomServiceClass		
customServiceId	PositiveInteger	0..1	attr	This attribute may only be used for the definition of custom services. The values shall not overlap with existing standardized service IDs.

Table A.319: DiagnosticCustomServiceClass

Class		DiagnosticDataByIdentifier (abstract)		
Package		M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::DataByIdentifier		
Note		This represents an abstract base class for all diagnostic services that access data by identifier.		
Base		ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable, MultilanguageReferrable, PackageableElement, Referrable		
Subclasses		DiagnosticReadDataByIdentifier, DiagnosticReadScalingDataByIdentifier, DiagnosticWriteDataByIdentifier		
Aggregated by		ARPackage.element		
Attribute	Type	Mult.	Kind	Note
dataIdentifier	DiagnosticAbstractDataIdentifier	0..1	ref	This represents the linked DiagnosticDataIdentifier.

Table A.320: DiagnosticDataByIdentifier

Class		DiagnosticDataElement		
Package		M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics		
Note		This meta-class represents the ability to describe a concrete piece of data to be taken into account for diagnostic purposes.		
Base		ARObject, DiagnosticServiceMappingDiagTarget, Identifiable, MultilanguageReferrable, Referrable		
Aggregated by		DiagnosticAbstractParameter.dataElement		
Attribute	Type	Mult.	Kind	Note
arraySizeSemantics	ArraySizeSemanticsEnum	0..1	attr	This attribute controls the meaning of the value of the array size.
maxNumberOfElements	PositiveInteger	0..1	attr	The existence of this attribute turns the data instance into an array of data. The attribute determines the size of the array in terms of how many elements the array can take.
scalingInfoSize	PositiveInteger	0..1	attr	Size in bytes of scaling information for the DiagnosticDataElement if used with DiagnosticReadScalingDataByIdentifier
swDataDefProps	SwDataDefProps	0..1	aggr	This property allows to specify data definition properties in order to support the definition of e.g. computation formulae and data constraints. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.321: DiagnosticDataElement

Class		DiagnosticDataIdentifier		
Package		M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics		
Note		This meta-class represents the ability to model a diagnostic data identifier (DID) that is fully specified regarding the payload at configuration-time. Tags: atp.recommendedPackage=DiagnosticDataIdentifiers		





Class	DiagnosticDataIdentifier			
Base	ARElement , ARObject , CollectableElement , DiagnosticAbstractDataIdentifier , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataElement	DiagnosticParameter	*	aggr	This is the dataElement associated with the Diagnostic DataIdentifier. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataElement.bitOffset, dataElement.ident.shortName, dataElement.variationPoint.shortLabel vh.latestBindingTime=postBuild
didSize	PositiveInteger	0..1	attr	This attribute indicates the size in bytes of the Diagnostic DataIdentifier.
representsVin	Boolean	0..1	attr	This attributes indicates whether the specific Diagnostic DataIdentifier represents the vehicle identification.
supportInfoByte	DiagnosticSupportInfoByte	0..1	aggr	This attribute represents the supported information associated with the DiagnosticDataIdentifier.

Table A.322: DiagnosticDataIdentifier

Class	DiagnosticDataIdentifierSet			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTroubleCode			
Note	This represents the ability to define a list of DiagnosticDataIdentifiers that can be reused in different contexts. Tags: atp.recommendedPackage=DiagnosticDataIdentifierSets			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataIdentifier (ordered)	DiagnosticDataIdentifier	*	ref	Reference to an ordered list of Data Identifiers.

Table A.323: DiagnosticDataIdentifierSet

Class	DiagnosticDeAuthentication			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::Authentication			
Note	This meta-class represents the subfunction to remove the authentication Tags: atp.recommendedPackage=DiagnosticAuthentications			
Base	ARElement , ARObject , CollectableElement , DiagnosticAuthentication , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.324: DiagnosticDeAuthentication

Class	DiagnosticDebounceAlgorithmProps			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticDebouncingAlgorithm			
Note	Defines properties for the debounce algorithm class.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	DiagnosticCommonProps.debounceAlgorithmProps			
Attribute	Type	Mult.	Kind	Note
debounce Algorithm	DiagEventDebounce Algorithm	0..1	aggr	This represents the actual debounce algorithm.
debounce Behavior	DiagnosticDebounce BehaviorEnum	0..1	attr	This attribute defines how the event debounce algorithm will behave, if a related enable condition is not fulfilled or ControlDTCSetting of the related event is disabled. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
debounce CounterStorage	Boolean	0..1	attr	Switch to store the debounce counter value non-volatile or not. true: debounce counter value shall be stored non-volatile false: debounce counter value is volatile Please note that this attribute is not relevant for the adaptive platform.

Table A.325: DiagnosticDebounceAlgorithmProps

Class	DiagnosticDemProvidedDataMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This represents the ability to define the nature of a data access for a DiagnosticDataElement in the Dem. Tags: atp.recommendedPackage=DiagnosticServiceMappings			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>DiagnosticCommonElement</i> , <i>DiagnosticMapping</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataElement	DiagnosticDataElement	0..1	ref	This represents the DiagnosticDataElement for which the access is further qualified by the DiagnosticDemProvided DataMapping.
dataProvider	NameToken	0..1	attr	This represents the ability to further specify the access within the Dem.

Table A.326: DiagnosticDemProvidedDataMapping

Class	DiagnosticDynamicDataIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents the ability to define a diagnostic data identifier (DID) at run-time. Tags: atp.recommendedPackage=DiagnosticDataIdentifiers			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>DiagnosticAbstractDataIdentifier</i> , <i>DiagnosticCommon Element</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.327: DiagnosticDynamicDataIdentifier

Class	DiagnosticDynamicallyDefineDataIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::DynamicallyDefineDataIdentifier			
Note	This represents an instance of the "Dynamically Define Data Identifier" diagnostic service. Tags: atp.recommendedPackage=DiagnosticDynamicallyDefineDataIdentifiers			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataIdentifier	DiagnosticDynamicDataIdentifier	0..1	ref	This represents the applicable DiagnosticDynamicDataIdentifier.
dynamicallyDefineDataIdentifierClass	DiagnosticDynamicallyDefineDataIdentifierClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticDynamicallyDefineDataIdentifier in the given context.
maxSourceElement	PositiveInteger	0..1	attr	This represents the maximum number of source elements of the dynamically created DID.

Table A.328: DiagnosticDynamicallyDefineDataIdentifier

Class	DiagnosticDynamicallyDefineDataIdentifierClass			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::DynamicallyDefineDataIdentifier			
Note	This meta-class contains attributes shared by all instances of the "Dynamically Define Data Identifier" diagnostic service. Tags: atp.recommendedPackage=DiagnosticDynamicallyDefineDataIdentifiers			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceClass , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
checkPerSourceId	Boolean	0..1	attr	If set to TRUE, the Dcm module shall check the session, security and mode dependencies per source DIDs with a ReadDataByIdentifier (0x22) with DID in the range 0x F200 to 0xF3FF. If set to FALSE. the Dcm module shall not check the session, security and mode dependencies per source DIDs with a ReadDataByIdentifier (0x22) with DID in the range 0xF200 to 0xF3FF.
configurationHandling	DiagnosticHandleDDDIConfigurationEnum	0..1	attr	This configuration switch defines whether DDDID definition is handled as non-volatile information or not.
subfunction	DiagnosticDynamicallyDefineDataIdentifierSubfunctionEnum	*	attr	This attribute contains a list of applicable subfunctions for all DiagnosticDynamicallyDefineDataIdentifier that reference the DiagnosticDynamicallyDefineDataIdentifierClass.

Table A.329: DiagnosticDynamicallyDefineDataIdentifierClass

Enumeration	DiagnosticDynamicallyDefineDataIdentifierSubfunctionEnum
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::DynamicallyDefineDataIdentifier
Note	This meta-class contains a list of possible subfunctions for the UDS service 0x2C.
Aggregated by	DiagnosticDynamicallyDefineDataIdentifierClass.subfunction
Literal	Description





Enumeration	DiagnosticDynamicallyDefineDataIdentifierSubfunctionEnum
clearDynamicallyDefineDataIdentifier	Clear the specified dynamic data identifier. Tags: atp.EnumerationLiteralIndex=0
defineByIdentifier	The definition of dynamic data identifier shall be done via a reference to a diagnostic data identifier. Tags: atp.EnumerationLiteralIndex=1
defineByMemoryAddress	The definition of dynamic data identifier shall be done via a reference to a memory address. Tags: atp.EnumerationLiteralIndex=2

Table A.330: DiagnosticDynamicallyDefineDataIdentifierSubfunctionEnum

Class	DiagnosticEcuInstanceProps			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticContribution			
Note	<p>This meta-class represents the ability to model properties that are specific for a given EcuInstance but on the other hand represent purely diagnostic-related information.</p> <p>In the spirit of decentralized configuration it is therefore possible to specify the diagnostic-related information related to a given EcuInstance even if the EcuInstance does not yet exist.</p> <p>Tags: atp.recommendedPackage=DiagnosticEcuInstanceProps</p>			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
ecuInstance	EcuInstance	*	ref	<p>This represents the actual EcuInstance to which the information contained in the DiagnosticEcuInstance contribute.</p> <p>Stereotypes: atp.Splitable Tags: atp.Splitkey=ecuInstance</p>
obdSupport	DiagnosticObdSupportEnum	0..1	attr	This attribute is used to specify the role (if applicable) in which the DiagnosticEcuInstance supports OBD.

Table A.331: DiagnosticEcuInstanceProps

Class	DiagnosticEcuReset			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::EcuReset			
Note	<p>This represents an instance of the "ECU Reset" diagnostic service.</p> <p>Tags: atp.recommendedPackage=DiagnosticEcuResets</p>			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
customSubFunctionNumber	PositiveInteger	0..1	attr	This attribute shall be used to define a custom sub-function number if none of the standardized values of category shall be used.
ecuResetClass	DiagnosticEcuResetClass	0..1	ref	<p>This reference substantiates that abstract reference in the role serviceClass for this specific concrete class.</p> <p>Thereby, the reference represents the ability to access shared attributes among all DiagnosticEcuReset in the given context.</p>

Table A.332: DiagnosticEcuReset

Class	DiagnosticEnableCondition			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticCondition			
Note	Specification of an enable condition. Tags: atp.recommendedPackage=DiagnosticConditions			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticCondition , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.333: DiagnosticEnableCondition

Class	DiagnosticEnableConditionGroup			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticConditionGroup			
Note	Enable condition group which includes one or several enable conditions. Tags: atp.recommendedPackage=DiagnosticConditions			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticConditionGroup , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
enableCondition	DiagnosticEnableCondition	*	ref	Reference to enableConditions that are part of the EnableConditionGroup. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=enableCondition.diagnosticEnableCondition, enableCondition.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.334: DiagnosticEnableConditionGroup

Class	DiagnosticEnableConditionPortMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines to which SWC service ports the DiagnosticEnableCondition is mapped. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
enableCondition	DiagnosticEnableCondition	0..1	ref	Reference to the EnableCondition which is mapped to a SWC service port.
swcFlatServiceDependency	SwcServiceDependency	0..1	ref	Reference to a SwcServiceDependencyType that links ServiceNeeds to SWC service ports. This reference can be used in early stages of the development in order to identify the SwcServiceDependency without a full System Context.
swcServiceDependencyInSystem	SwcServiceDependency	0..1	iref	Instance reference to a SwcServiceDependency that links ServiceNeeds to SWC service ports. InstanceRef implemented by: SwcServiceDependencyInSystemInstanceRef

Table A.335: DiagnosticEnableConditionPortMapping

Class	DiagnosticEnvBswModeElement			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	This meta-class represents the ability to refer to a specific ModeDeclaration in the scope of a BswModule Description.			
Base	ARObject, DiagnosticEnvModeElement , Referrable			
Aggregated by	DiagnosticEnvironmentalCondition.modeElement			
Attribute	Type	Mult.	Kind	Note
mode	ModeDeclaration	0..1	iref	This reference identifies both the ModeDeclarationGroup Prototype and the ModeDeclaration for the specific mode comparison. InstanceRef implemented by: ModeInBswModule DescriptionInstanceRef

Table A.336: DiagnosticEnvBswModeElement

Class	DiagnosticEnvCompareCondition (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	DiagnosticCompareConditions are atomic conditions. They are based on the idea of a comparison at runtime of some variable data with something constant. The type of the comparison (==, !=, <, <=, ...) is specified in DiagnosticCompareCondition.compareType.			
Base	ARObject, DiagnosticEnvConditionFormulaPart			
Subclasses	DiagnosticEnvDataCondition , DiagnosticEnvDataElementCondition , DiagnosticEnvModeCondition			
Aggregated by	DiagnosticEnvConditionFormula.part			
Attribute	Type	Mult.	Kind	Note
compareType	DiagnosticCompareTypeEnum	0..1	attr	This attributes represents the concrete type of the comparison.

Table A.337: DiagnosticEnvCompareCondition

Class	DiagnosticEnvConditionFormula			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	<p>A DiagnosticEnvConditionFormula embodies the computation instruction that is to be evaluated at runtime to determine if the DiagnosticEnvironmentalCondition is currently present (i.e. the formula is evaluated to true) or not (otherwise). The formula itself consists of parts which are combined by the logical operations specified by DiagnosticEnvConditionFormula.op.</p> <p>If a diagnostic functionality cannot be executed because an environmental condition fails then the diagnostic stack shall send a negative response code (NRC) back to the client. The value of the NRC is directly related to the specific formula and is therefore formalized in the attribute DiagnosticEnvConditionFormula.nrcValue.</p>			
Base	ARObject, DiagnosticEnvConditionFormulaPart			
Aggregated by	DiagnosticEnvConditionFormula.part , DiagnosticEnvironmentalCondition.formula			
Attribute	Type	Mult.	Kind	Note
nrcValue	PositiveInteger	0..1	attr	This attribute represents the concrete NRC value that shall be returned if the condition fails.
op	DiagnosticLogicalOperatorEnum	0..1	attr	This attribute represents the concrete operator (supported operators: and, or) of the condition formula.
part (ordered)	DiagnosticEnvConditionFormulaPart	*	aggr	This aggregation represents the collection of formula parts that can be combined by logical operators.

Table A.338: DiagnosticEnvConditionFormula

Class	DiagnosticEnvDataCondition			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	A DiagnosticEnvDataCondition is an atomic condition that compares the current value of the referenced DiagnosticDataElement with a constant value defined by the ValueSpecification. All compareTypes are supported.			
Base	ARObject, DiagnosticEnvCompareCondition , DiagnosticEnvConditionFormulaPart			
Aggregated by	DiagnosticEnvConditionFormula.part			
Attribute	Type	Mult.	Kind	Note
compareValue	ValueSpecification	0..1	aggr	This attribute represents a fixed compare value taken to evaluate the compare condition.
dataElement	DiagnosticDataElement	0..1	ref	This reference represents the related diagnostic data element.

Table A.339: DiagnosticEnvDataCondition

Class	DiagnosticEnvDataElementCondition			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	This meta-class represents the ability to formulate a diagnostic environment condition based on the value of a data element owned by the application software.			
Base	ARObject, DiagnosticEnvCompareCondition , DiagnosticEnvConditionFormulaPart			
Aggregated by	DiagnosticEnvConditionFormula.part			
Attribute	Type	Mult.	Kind	Note
compareValue	ValueSpecification	0..1	aggr	This aggregation represents the definition of the compare value against which the value taken from the application software shall be compared.
dataPrototype	DataPrototype	0..1	iref	This instanceRef represent the ability to access a data element owned by the application software on the AUTOSAR classic platform. InstanceRef implemented by: DataPrototypeInSystem InstanceRef
swDataDef Props	SwDataDefProps	0..1	aggr	Via this aggregation it is possible to describe the properties of the data that is obtained from the application for the environmental condition. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.340: DiagnosticEnvDataElementCondition

Class	DiagnosticEnvModeCondition			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	DiagnosticEnvModeCondition are atomic condition based on the comparison of the active Mode Declaration in a ModeDeclarationGroupPrototype with the constant value of a ModeDeclaration. The formulation of this condition uses only one DiagnosticEnvElement, which contains enough information to deduce the variable part (i.e. the part that changes at runtime) as well as the constant part of the comparison. Only DiagnosticCompareTypeEnum.isEqual or DiagnosticCompareTypeEnum.isNotEqual are eligible values for DiagnosticAtomicCondition.compareType.			
Base	ARObject, DiagnosticEnvCompareCondition , DiagnosticEnvConditionFormulaPart			
Aggregated by	DiagnosticEnvConditionFormula.part			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticEnvModeCondition			
modeElement	DiagnosticEnvModeElement	0..1	ref	This reference represents both the ModeDeclaration GroupPrototype and the ModeDeclaration relevant for the mode comparison.

Table A.341: DiagnosticEnvModeCondition

Class	DiagnosticEnvModeElement (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	<p>All ModeDeclarations that are referenced in a DiagnosticEnvModeCondition shall be defined as a DiagnosticEnvModeElement of this DiagnosticEnvironmentalCondition.</p> <p>This concept keeps the ARXML clean: It avoids that the DiagnosticEnvConditionFormula is cluttered by lengthy InstanceRef definitions.</p> <p>Furthermore, it allows that an InstanceRef only needs to be defined once and can be used multiple times in the different DiagnosticEnvModeConditions.</p>			
Base	<i>ARObject</i> , <i>Referrable</i>			
Subclasses	DiagnosticEnvBswModeElement , DiagnosticEnvSwcModeElement			
Aggregated by	DiagnosticEnvironmentalCondition.modeElement			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.342: DiagnosticEnvModeElement

Class	DiagnosticEnvSwcModeElement			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	This meta-class represents the ability to refer to a ModeDeclaration in a concrete System context.			
Base	<i>ARObject</i> , <i>DiagnosticEnvModeElement</i> , <i>Referrable</i>			
Aggregated by	DiagnosticEnvironmentalCondition.modeElement			
Attribute	Type	Mult.	Kind	Note
mode	ModeDeclaration	0..1	iref	<p>This reference identifies both the ModeDeclarationGroup Prototype and the ModeDeclaration for the specific mode comparison.</p> <p>InstanceRef implemented by: PModeInSystemInstanceRef</p>

Table A.343: DiagnosticEnvSwcModeElement

Class	DiagnosticEnvironmentalCondition			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::EnvironmentalCondition			
Note	<p>The meta-class DiagnosticEnvironmentalCondition formalizes the idea of a condition which is evaluated during runtime of the ECU by looking at "environmental" states (e.g. one such condition is that the vehicle is not driving, i.e. vehicle speed == 0).</p> <p>Tags: atp.recommendedPackage=DiagnosticEnvironmentalConditions</p>			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>DiagnosticCommonElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–





Class		DiagnosticEnvironmentalCondition		
formula	DiagnosticEnvCondition Formula	0..1	aggr	This attribute represents the formula part of the DiagnosticEnvironmentalCondition.
modeElement	DiagnosticEnvMode Element	*	aggr	This aggregation contains a representation of Mode Declarations in the context of a DiagnosticEnvironmentalCondition.

Table A.344: DiagnosticEnvironmentalCondition

Class		DiagnosticEvent		
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticEvent			
Note	This element is used to configure DiagnosticEvents. Tags: atp.recommendedPackage=DiagnosticEvents			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , Multilanguage Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
associated Event Identification	PositiveInteger	0..1	attr	This attribute represents the identification number that is associated with the enclosing DiagnosticEvent and allows to identify it when placed into a snapshot record or extended data record storage. This value can be reported as internal data element in snapshot records or extended data records.
clearEvent Allowed Behavior	DiagnosticClearEvent AllowedBehaviorEnum	0..1	attr	This attribute defines the resulting UDS status byte for the related event, which shall not be cleared according to the ClearEventAllowed callback
confirmation Threshold	PositiveInteger	0..1	attr	This attribute defines the number of operation cycles with a failed result before a confirmed DTC is set to 1. The semantic of this attribute is a by "1" increased value compared to the confirmation threshold of the "trip counter" mentioned in ISO 14229-1 in figure D.4. A value of "1" defines the immediate confirmation of the DTC along with the first reported failed. This is also sometimes called "zero trip DTC". A value of "2" defines a DTC confirmation in the operation cycle after the first occurred failed. A value of "2" is typically used in the US for OBD DTC confirmation. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
connected Indicator	DiagnosticConnected Indicator	*	aggr	Event specific description of Indicators. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=connectedIndicator.shortName, connectedIndicator.variationPoint.shortLabel vh.latestBindingTime=postBuild
eventClear Allowed	DiagnosticEventClear AllowedEnum	0..1	attr	This attribute defines whether the Dem has access to a "ClearEventAllowed" callback.
eventKind	DiagnosticEventKind Enum	0..1	attr	This attribute is used to distinguish between SWC and BSW events.
prestorage FreezeFrame	Boolean	0..1	attr	This attribute describes whether the Prestorage of Freeze Frames is supported by the assigned event or not. true: Prestorage of FreezeFrames is supported false: Prestorage of FreezeFrames is not supported





Class	DiagnosticEvent			
prestoredFreezeFrameStoredInNvm	Boolean	0..1	attr	If the Event uses a prestored freeze-frame (using the operations PrestoreFreezeFrame and ClearPrestoredFreezeFrame of the service interface DiagnosticMonitor) this attribute indicates if the Event requires the data to be stored in non-volatile memory. TRUE = Dem shall store the prestored data in non-volatile memory, FALSE = Data can be lost at shutdown (not stored in Nvm)
recoverableInSameOperationCycle	Boolean	0..1	attr	If the attribute is set to true then reporting PASSED will reset the indication of a failed test in the current operation cycle. If the attribute is set to false then reporting PASSED will be ignored and not lead to a reset of the indication of a failed test.

Table A.345: DiagnosticEvent

Enumeration	DiagnosticEventCombinationBehaviorEnum
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticCommonProps
Note	Select type of Event Combination support
Aggregated by	DiagnosticCommonProps.typeOfEventCombinationSupported
Literal	Description
eventCombinationOnRetrieval	Event combination on retrieval is used to combine events. For each event an individual event memory entry is created, while reporting the data via UDS, the data is combined. Tags: atp.EnumerationLiteralIndex=1
eventCombinationOnStorage	Event combination on storage is used to combine events. Only one memory entry exists for each DTC which is also reported via UDS. Tags: atp.EnumerationLiteralIndex=0

Table A.346: DiagnosticEventCombinationBehaviorEnum

Enumeration	DiagnosticEventCombinationReportingBehaviorEnum
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticCommonProps
Note	Select reporting format of events. Applicable only for Event Combination on Retrieval.
Aggregated by	DiagnosticCommonProps.eventCombinationReportingBehavior
Literal	Description
reportingInChronologicalOrderOldestFirst	The reporting order for event combination on retrieval is the chronological storage order of the events Tags: atp.EnumerationLiteralIndex=0

Table A.347: DiagnosticEventCombinationReportingBehaviorEnum

Class	DiagnosticEventNeeds
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds
Note	Specifies the abstract needs on the configuration of the Diagnostic Event Manager for one diagnostic event. Its shortName can be regarded as a symbol identifying the diagnostic event from the viewpoint of the component or module which owns this element. In case the diagnostic event specifies a production error, the shortName shall be the name of the production error.
Base	<i>ARObject</i> , <i>DiagnosticCapabilityElement</i> , Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds





Class		DiagnosticEventNeeds		
Attribute	Type	Mult.	Kind	Note
deferringFid	FunctionInhibitionNeeds	*	ref	This reference contains the link to a function identifier within the FiM which is used by the monitor before delivering a result.
diagEventDebounceAlgorithm	DiagEventDebounceAlgorithm	0..1	aggr	Specifies the abstract need on the Debounce Algorithm applied by the Diagnostic Event Manager.
inhibitingFid	FunctionInhibitionNeeds	0..1	ref	This represents the primary Function Inhibition Identifier used for inhibition of the diagnostic monitor. The FID might either inhibit the monitoring of a symptom or the reporting of detected faults.
inhibitingSecondaryFid	FunctionInhibitionNeeds	*	ref	This represents the secondary Function Inhibition Identifier used for inhibition of the diagnostic monitor. Any of the FID inhibitions leads to an inhibition of the monitoring of a symptom or the reporting of detected faults.
prestoredFreezeFrameStoredInNvm	Boolean	0..1	attr	If the Event uses a prestored freeze-frame (using the operations <code>PrestoreFreezeFrame</code> and <code>ClearPrestoredFreezeFrame</code> of the service interface <code>DiagnosticMonitor</code>) this attribute indicates if the Event requires the data to be stored in non-volatile memory. TRUE = Dem shall store the prestored data in non-volatile memory, FALSE = Data can be lost at shutdown (not stored in Nvm).
usesMonitorData	Boolean	0..1	attr	This attribute defines whether additional monitor data shall be added to the reporting of events.

Table A.348: DiagnosticEventNeeds

Class		DiagnosticEventPortMapping		
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines to which SWC service ports the DiagnosticEvent is mapped. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
bswServiceDependency	BswServiceDependencyIdent	0..1	ref	Reference to a BswServiceDependency that links ServiceNeeds to BswModuleEntries.
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to the DiagnosticEvent that is assigned to SWC service ports.
swcFlatServiceDependency	SwcServiceDependency	0..1	ref	Reference to a SwcServiceDependencyType that links ServiceNeeds to SWC service ports.
swcServiceDependencyInSystem	SwcServiceDependency	0..1	iref	Instance reference to a SwcServiceDependency that links ServiceNeeds to SWC service ports. InstanceRef implemented by: SwcServiceDependencyInSystemInstanceRef

Table A.349: DiagnosticEventPortMapping

Class	DiagnosticEventToDebounceAlgorithmMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines which Debounce Algorithm is applicable for a DiagnosticEvent. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
debounce Algorithm	DiagnosticDebounceAlgorithmProps	0..1	ref	Reference to a DebounceAlgorithm assigned to a DiagnosticEvent.
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to a DiagnosticEvent to which a Debounce Algorithm is assigned.

Table A.350: DiagnosticEventToDebounceAlgorithmMapping

Class	DiagnosticEventToEnableConditionGroupMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines which EnableConditionGroup is applicable for a DiagnosticEvent. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to a DiagnosticEvent to which an Enable ConditionGroup is assigned.
enableCondition Group	DiagnosticEnableConditionGroup	0..1	ref	Reference to an EnableConditionGroup assigned to a DiagnosticEvent.

Table A.351: DiagnosticEventToEnableConditionGroupMapping

Class	DiagnosticEventToSecurityEventMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	This meta-class represents the ability to map a security event that is defined in the context of the Security Extract to a diagnostic event defined on the context of the DiagnosticExtract. Tags: atp.Status=candidate atp.recommendedPackage=DiagnosticMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	This reference identifies the applicable diagnostic event. Tags: atp.Status=candidate
securityEvent Props	SecurityEventContextProps	0..1	ref	This reference identifies the qualification of the applicable security event Tags: atp.Status=candidate

Table A.352: DiagnosticEventToSecurityEventMapping

Class	DiagnosticEventToStorageConditionGroupMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines which StorageConditionGroup is applicable for a DiagnosticEvent. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to a DiagnosticEvent to which a Storage ConditionGroup is assigned.
storage ConditionGroup	DiagnosticStorage ConditionGroup	0..1	ref	Reference to a StorageConditionGroup assigned to a DiagnosticEvent.

Table A.353: DiagnosticEventToStorageConditionGroupMapping

Class	DiagnosticEventToTroubleCodeJ1939Mapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::DiagnosticJ1939Mapping			
Note	By means of this meta-class it is possible to associate a DiagnosticEvent to a DiagnosticTroubleCode J1939. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to a DiagnosticEvent to which a J1939 Diagnostic Trouble Code is assigned.
troubleCode J1939	DiagnosticTroubleCode J1939	0..1	ref	Reference to a J1939 Diagnostic Trouble Code to which a DiagnosticEvent is assigned.

Table A.354: DiagnosticEventToTroubleCodeJ1939Mapping

Class	DiagnosticEventToTroubleCodeUdsMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines which UDS Diagnostic Trouble Code is applicable for a DiagnosticEvent. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	Reference to a DiagnosticEvent to which a UDS Diagnostic Trouble Code is assigned.
troubleCodeUds	DiagnosticTroubleCode Uds	0..1	ref	Reference to an UDS Diagnostic Trouble Code assigned to a DiagnosticEvent.

Table A.355: DiagnosticEventToTroubleCodeUdsMapping

Class	DiagnosticExtendedDataRecord			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticExtendedDataRecord			
Note	Description of an extended data record. Tags: atp.recommendedPackage=DiagnosticExtendedDataRecords			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
customTrigger	String	0..1	attr	This attribute shall be taken to verbally describe the nature of the custom trigger.
recordElement	DiagnosticParameter	*	aggr	Defined DataElements in the extended record element. Stereotypes: atp.Splittable Tags: atp.Splitkey=recordElement.bitOffset, recordElement.ident.shortName
recordNumber	PositiveInteger	0..1	attr	This attribute specifies an unique identifier for an extended data record.
trigger	DiagnosticRecordTriggerEnum	0..1	attr	This attribute specifies the primary trigger to allocate an event memory entry.
update	Boolean	0..1	attr	This attribute defines when an extended data record is captured. true: This extended data record is captured every time. false: This extended data record is only captured for new event memory entries.

Table A.356: DiagnosticExtendedDataRecord

Class	DiagnosticFimAliasEventGroupMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::FimMapping			
Note	This meta-class represents the ability to map a DiagnosticFimEventGroup to a DiagnosticFimAliasEvent Group. By this means the "preliminary" modeling by way of a DiagnosticFimAliasEventGroup is further substantiated. Tags: atp.recommendedPackage=DiagnosticFimAliasEventGroupMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
actualEvent	DiagnosticFimEvent Group	0..1	ref	This represents the reference to the actual summary event.
aliasEvent	DiagnosticFimAlias EventGroup	0..1	ref	This represents the reference to the alias summary event.

Table A.357: DiagnosticFimAliasEventGroupMapping

Class	DiagnosticFimAliasEventMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticEvent			
Note	This meta-class represents the ability to model the mapping of a DiagnosticEvent to a DiagnosticAlias Event. By this means the "preliminary" modeling by way of a DiagnosticAliasEvent is further substantiated. Tags: atp.recommendedPackage=DiagnosticFimEventMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			





Class	DiagnosticFimAliasEventMapping			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
actualEvent	DiagnosticEvent	0..1	ref	This represents the reference to the actual diagnostic event.
aliasEvent	DiagnosticFimAlias Event	0..1	ref	This represents the reference to the alias event.

Table A.358: DiagnosticFimAliasEventMapping

Class	DiagnosticFimFunctionMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This meta-class represents the ability to define a mapping between a function identifier (FID) and the corresponding SwcServiceDependency in the application software resp. basic software. Tags: atp.recommendedPackage=DiagnosticFimFunctionMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticMapping, DiagnosticSwMapping, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
mappedBsw Service Dependency	BswService DependencyIdent	0..1	ref	This is supposed to represent a reference to a Bsw ServiceDependency. the latter is not derived from Referrable and therefore this detour needs to be implemented to still let BswServiceDependency become the target of a reference.
mappedFlatSwc Service Dependency	SwcService Dependency	0..1	ref	This represents the ability to refer to an AtomicSw ComponentType that is available without the definition of how it will be embedded into the component hierarchy.
mapped Function	DiagnosticFunction Identifier	0..1	ref	This represents the mapped FID.
mappedSwc Service Dependency	SwcService Dependency	0..1	iref	This represents the ability to point into the component hierarchy (under possible consideration of the root SoftwareComposition). InstanceRef implemented by: SwcServiceDependency InSystemInstanceRef

Table A.359: DiagnosticFimFunctionMapping

Class	DiagnosticFreezeFrame			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticFreezeFrame			
Note	This element describes combinations of DIDs for a non OBD relevant freeze frame. Tags: atp.recommendedPackage=DiagnosticFreezeFrames			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, Identifiable, Multilanguage Referrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
customTrigger	String	0..1	attr	This attribute shall be taken to verbally describe the nature of the custom trigger.





Class		DiagnosticFreezeFrame		
recordNumber	PositiveInteger	0..1	attr	This attribute defines a record number for a freeze frame record. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
trigger	DiagnosticRecordTriggerEnum	0..1	attr	This attribute defines the primary trigger to allocate an event memory entry.
update	Boolean	0..1	attr	This attribute defines the approach when the freeze frame record is stored/updated. true: FreezeFrame record is captured every time. false: FreezeFrame record is only captured for new event memory entries.

Table A.360: DiagnosticFreezeFrame

Class		DiagnosticFunctionIdentifierInhibit		
Package	M2::AUTOSARTemplates::DiagnosticExtract::Fim			
Note	This meta-class represents the ability to define the inhibition of a specific function identifier within the Fim configuration. Tags: atp.recommendedPackage=DiagnosticFunctionIdentifierInhibits			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
functionIdentifier	DiagnosticFunctionIdentifier	0..1	ref	This represents the corresponding function identifier.
inhibitionMask	DiagnosticInhibitionMaskEnum	0..1	attr	This represents the value of the inhibition mask behavior.
inhibitSource	DiagnosticFunctionInhibitSource	*	aggr	This represents a collection of DiagnosticFunctionInhibitSource that contribute to the configuration of the enclosing DiagnosticFunctionIdentifierInhibit.

Table A.361: DiagnosticFunctionIdentifierInhibit

Class		DiagnosticFunctionInhibitSource		
Package	M2::AUTOSARTemplates::DiagnosticExtract::Fim			
Note	This meta-class represents the ability to define an inhibition source in the context of the Fim configuration.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DiagnosticFunctionIdentifierInhibit.inhibitSource			
Attribute	Type	Mult.	Kind	Note
event	DiagnosticFimAliasEvent	0..1	ref	This represents the alias event applicable for the referencing inhibition source.
eventGroup	DiagnosticFimAliasEventGroup	0..1	ref	This represents the event group applicable for the referencing inhibition source.

Table A.362: DiagnosticFunctionInhibitSource

Class	DiagnosticIOControl			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::IOControl			
Note	This represents an instance of the "I/O Control" diagnostic service. Tags: atp.recommendedPackage=DiagnosticIoControls			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
controlEnableMaskBit	DiagnosticControlEnableMaskBit	*	aggr	This aggregation represents the control mask record consisting of single bits.
dataIdentifier	DiagnosticDataIdentifier	0..1	ref	This represents the corresponding DiagnosticData Identifier
freezeCurrentState	Boolean	0..1	attr	Setting this attribute to true represents the ability of the Dcm to execute a freezeCurrentState.
ioControlClass	DiagnosticIoControl Class	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticIOControl in the given context.
resetToDefault	Boolean	0..1	attr	Setting this attribute to true represents the ability of the Dcm to execute a resetToDefault.
shortTermAdjustment	Boolean	0..1	attr	Setting this attribute to true represents the ability of the Dcm to execute a shortTermAdjustment.

Table A.363: DiagnosticIOControl

Class	DiagnosticIndicator			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticIndicator			
Note	Definition of an indicator. Tags: atp.recommendedPackage=DiagnosticIndicators			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
type	DiagnosticIndicatorType Enum	0..1	attr	Defines the type of the indicator. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.364: DiagnosticIndicator

Class	DiagnosticInfoType			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents the ability to model an OBD info type. Tags: atp.recommendedPackage=DiagnosticInfoTypes			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticInfoType			
dataElement	DiagnosticParameter	*	aggr	This represents the data associated with the enclosing DiagnosticInfoType. Stereotypes: atpSplitable Tags: atp.Splitkey=dataElement.bitOffset, dataElement.ident.shortName
id	PositiveInteger	0..1	attr	This attribute represents the value of InfoType (see SAE J1979-DA).

Table A.365: DiagnosticInfoType

Class	DiagnosticIoControlNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the general needs on the configuration of the Diagnostic Communication Manager (DCM) which are not related to a particular item (e.g. a PID). The main use case is the mapping of service ports to the Dcm which are not related to a particular item.			
Base	ARObject , DiagnosticCapabilityElement , Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
currentValue	DiagnosticValueNeeds	0..1	ref	Reference to the DiagnosticValueNeeds indicating the access to the current value via signalBasedDiagnostics.
freezeCurrentStateSupported	Boolean	0..1	attr	This attribute determines, if the referenced port supports temporary freezing of I/O value.
resetToDefaultSupported	Boolean	0..1	attr	This represents a flag for the existence of the ResetToDefault operation in the service interface.
shortTermAdjustmentSupported	Boolean	0..1	attr	This attribute determines, if the referenced port supports temporarily setting of I/O value to a specific value provided by the diagnostic tester.

Table A.366: DiagnosticIoControlNeeds

Class	DiagnosticIumprGroup			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticEvent			
Note	This meta-class represents the ability to model a IUMPR groups. Tags: atp.recommendedPackage=DiagnosticIumprGroups			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
iumpr	DiagnosticIumpr	*	ref	This reference collects DiagnosticIumpr to a DiagnosticIumprGroup. Stereotypes: atpSplitable Tags: atp.Splitkey=iumpr
iumprGroupIdentifier	DiagnosticIumprGroupIdentifier	0..1	aggr	This aggregation allows for the variant modeling of the groupIdentifier. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=iumprGroupIdentifier.groupId, iumprGroupIdentifier.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.367: DiagnosticIumprGroup

Class	DiagnosticlumprGroupIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticEvent			
Note	This meta-class provides the ability to the define the group identifier for an lumprGroup.			
Base	ARObject			
Aggregated by	DiagnosticlumprGroup.iumprGroupIdentifier			
Attribute	Type	Mult.	Kind	Note
groupId	NameToken	0..1	attr	This attribute shall be taken to define an identifier for the IUMPR group. Please note that the value of this identifier is driven by regulations outside the scope of AUTOSAR and can therefore not be limited to the set of characters suitable for a shortName. Stereotypes: atpIdentityContributor

Table A.368: DiagnosticlumprGroupIdentifier

Class	DiagnosticlumprToFunctionIdentifierMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	This meta-class represents the ability to associate a DiagnosticFunctionIdentifier with a Diagnosticlumpr. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
functionIdentifier	DiagnosticFunctionIdentifier	0..1	ref	This reference identifies the applicable DiagnosticFunctionIdentifier.
lumpr	Diagnosticlumpr	0..1	ref	This reference identifies the applicable Diagnosticlumpr.

Table A.369: DiagnosticlumprToFunctionIdentifierMapping

Class	DiagnosticJ1939Node			
Package	M2::AUTOSARTemplates::DiagnosticExtract::J1939			
Note	This meta-class represents the diagnostic configuration of a J1939 Nm node, which in turn represents a "virtual Ecu" on the J1939 communication bus. Tags: atp.recommendedPackage=DiagnosticJ1939Nodes			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
nmNode	J1939NmNode	0..1	ref	This represents the reference to the "virtual Ecu" to which the enclosing DiagnosticJ1939Node is associated.

Table A.370: DiagnosticJ1939Node

Class	DiagnosticJ1939Spn			
Package	M2::AUTOSARTemplates::DiagnosticExtract::J1939			
Note	This meta-class represents the ability to model a J1939 Suspect Parameter Number (SPN). Tags: atp.recommendedPackage=DiagnosticJ1939Spns			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			





Class	DiagnosticJ1939Spn			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
spn	PositiveInteger	0..1	attr	This attribute represents the concrete numerical identification for the enclosing SPN.

Table A.371: DiagnosticJ1939Spn

Class	DiagnosticMasterToSlaveEventMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	This meta-class provides the ability to map a master diagnostic event with a slave diagnostic event such that reporting of the master event with a given value also reports the slave event with the same value Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
masterEvent	DiagnosticEvent	0..1	ref	This represents the master diagnostic event.
slaveEvent	DiagnosticEvent	0..1	ref	This represents the slave diagnostic event.

Table A.372: DiagnosticMasterToSlaveEventMapping

Class	DiagnosticMeasurementIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTestResult			
Note	This meta-class represents the ability to describe a measurement identifier. Tags: atp.recommendedPackage=DiagnosticMeasurementIdentifiers			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
obdMid	PositiveInteger	0..1	attr	This represents the numerical measurement Id Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.373: DiagnosticMeasurementIdentifier

Class	DiagnosticMemoryAddressableRangeAccess (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::MemoryByAddress			
Note	This abstract base class			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMemoryByAddress , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	DiagnosticReadMemoryByAddress, DiagnosticRequestDownload , DiagnosticRequestUpload , DiagnosticWriteMemoryByAddress			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticMemoryAddressableRangeAccess (abstract)			
memoryRange	DiagnosticMemoryIdentifier	*	ref	This represents the formal description of the memory segment to which the DiagnosticMemoryByAddress applies.

Table A.374: DiagnosticMemoryAddressableRangeAccess

Class	DiagnosticMemoryDestination (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticMemoryDestination			
Note	This abstract meta-class represents a possible memory destination for a diagnostic event.			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	DiagnosticMemoryDestinationPrimary , DiagnosticMemoryDestinationUserDefined			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
agingRequiresTestedCycle	Boolean	0..1	attr	Defines whether the aging cycle counter is processed every aging cycles or else only tested aging cycle are considered. If the attribute is set to TRUE: only tested aging cycle are considered for aging cycle counter. If the attribute is set to FALSE: aging cycle counter is processed every aging cycle. On the classic platform, the value of this attribute has to be identical for each DiagnosticMemoryDestination.
clearDtcLimitation	DiagnosticClearDtcLimitationEnum	0..1	attr	Defines the scope of the DEM_ClearDTC Api. On the classic platform, the value of this attribute has to be identical for each DiagnosticMemoryDestination.
dtcStatusAvailabilityMask	PositiveInteger	0..1	attr	Mask for the supported DTC status bits by the Dem.
eventDisplacementStrategy	DiagnosticEventDisplacementStrategyEnum	0..1	attr	This attribute defines, whether support for event displacement is enabled or not, and which displacement strategy is followed.
maxNumberOfEventEntries	PositiveInteger	0..1	attr	This attribute fixes the maximum number of event entries in the fault memory.
memoryEntryStorageTrigger	DiagnosticMemoryEntryStorageTriggerEnum	0..1	attr	Describes the trigger to allocate an event memory entry.
statusBitHandlingTestFailedSinceLastClear	DiagnosticStatusBitHandlingTestFailedSinceLastClearEnum	0..1	attr	This attribute defines, whether the aging and displacement mechanism shall be applied to the "TestFailedSinceLastClear" status bits. On the classic platform, the value of this attribute has to be identical for each DiagnosticMemoryDestination.
statusBitStorageTestFailed	Boolean	0..1	attr	This parameter is used to activate/deactivate the permanent storage of the "TestFailed" status bits. true: storage activated false: storage deactivated
typeOfFreezeFrameRecordNumeration	DiagnosticTypeOfFreezeFrameRecordNumerationEnum	0..1	attr	This attribute defines the type of assigning freeze frame record numbers for event-specific freeze frame records.

Table A.375: DiagnosticMemoryDestination

Class	DiagnosticMemoryDestinationPrimary			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticMemoryDestination			
Note	This represents a primary memory for a diagnostic event. Tags: atp.recommendedPackage=DiagnosticMemoryDestinations			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMemoryDestination , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
typeOfDtcSupported	DiagnosticTypeOfDtcSupportedEnum	0..1	attr	This attribute defines the format returned by Dem_DcmGetTranslationType and does not relate to/influence the supported Dem functionality.

Table A.376: DiagnosticMemoryDestinationPrimary

Class	DiagnosticMemoryDestinationUserDefined			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticMemoryDestination			
Note	This represents a user-defined memory for a diagnostic event. Tags: atp.recommendedPackage=DiagnosticMemoryDestinations			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMemoryDestination , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
affectedByControlDTCSetting	Boolean	0..1	attr	This attribute configures how the content of the memory is affected by an active ControlDTCSetting or not: <ul style="list-style-type: none"> • If the attribute is set to true, the user-defined fault memory is not updated if ControlDTCSetting is off. • If the attribute is set to false, the user defined fault memory is updated even if ControlDTCSetting is off.
authenticationEnabled	DiagnosticAuthRoleProxy	0..1	aggr	The existence of this aggregation indicates that an authentication is foreseen. The details are clarified by the aggregated class. Stereotypes: atp.Splittable Tags: atp.Splitkey=authenticationEnabled
memoryId	PositiveInteger	0..1	attr	This represents the identifier of the user-defined memory.

Table A.377: DiagnosticMemoryDestinationUserDefined

Class	DiagnosticMemoryIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::MemoryByAddress			
Note	This meta-class represents the ability to define memory properties from the diagnostics point of view. Tags: atp.recommendedPackage=DiagnosticMemoryByAdresss			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
accessPermission	DiagnosticAccessPermission	0..1	ref	This represents that access permission defined for the specific DiagnosticMemoryIdentifier. Stereotypes: atp.Splittable Tags: atp.Splitkey=accessPermission
id	PositiveInteger	0..1	attr	This represents the identification of the memory segment.





Class		DiagnosticMemoryIdentifier		
memoryHigh Address	PositiveInteger	0..1	attr	This represents the upper bound for addresses of the memory segment.
memoryHigh AddressLabel	String	0..1	attr	This represents a symbolic label for the upper bound for addresses of the memory segment.
memoryLow Address	PositiveInteger	0..1	attr	This represents the lower bound for addresses of the memory segment.
memoryLow AddressLabel	String	0..1	attr	This represents a symbolic label for the lower bound for addresses of the memory segment.

Table A.378: DiagnosticMemoryIdentifier

Class		DiagnosticOperationCycle		
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticOperationCycle			
Note	Definition of an operation cycle that is the base of the event qualifying and for Dem scheduling. Tags: atp.recommendedPackage=DiagnosticOperationCycles			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
type	DiagnosticOperation CycleTypeEnum	0..1	attr	Operation cycles types for the Dem.

Table A.379: DiagnosticOperationCycle

Class		DiagnosticOperationCyclePortMapping		
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines to which SWC service ports the DiagnosticOperationCycle is mapped. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
operationCycle	DiagnosticOperation Cycle	0..1	ref	Reference to the DiagnosticOperationCycle that is assigned to SWC service ports.
swcFlatService Dependency	SwcService Dependency	0..1	ref	Reference to a SwcServiceDependencyType that links ServiceNeeds to SWC service ports.
swcService DependencyIn System	SwcService Dependency	0..1	iref	Instance reference to a SwcServiceDependency that links ServiceNeeds to SWC service ports. InstanceRef implemented by: SwcServiceDependency InSystemInstanceRef

Table A.380: DiagnosticOperationCyclePortMapping

Class		DiagnosticParameter		
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents the ability to describe information relevant for the execution of a specific diagnostic service, i.e. it can be taken to parameterize the service.			





Class	DiagnosticParameter			
Base	<i>ARObject</i> , <i>DiagnosticAbstractParameter</i>			
Aggregated by	DiagnosticDataIdentifier.dataElement, DiagnosticExtendedDataRecord.recordElement, DiagnosticInfoType.dataElement, DiagnosticParameterIdentifier.dataElement, DiagnosticRequestRoutineResults.request, DiagnosticRequestRoutineResults.response, DiagnosticStartRoutine.request, DiagnosticStartRoutine.response, DiagnosticStopRoutine.request, DiagnosticStopRoutine.response			
Attribute	Type	Mult.	Kind	Note
ident	DiagnosticParameterIdent	0..1	aggr	The aggregation in the role ident provides the ability to make the DiagnosticAbstractParameter identifiable. From the semantical point of view, the AbstractDiagnosticParameter is considered a first-class Identifiable and therefore the aggregation in the role ident shall always exist (until it may be possible to let AbstractDiagnosticParameter directly inherit from Identifiable). Stereotypes: atpIdentityContributor
supportInfo	DiagnosticParameterSupportInfo	0..1	aggr	This attribute represents the ability to define which bit of the support info byte is representing this part of the PID.

Table A.381: DiagnosticParameter

Class	DiagnosticParameterElement			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents an element of a DiagnosticParameter if the DiagnosticParameter represents a structure.			
Base	<i>ARObject</i> , <i>DiagnosticAbstractParameter</i> , <i>DiagnosticServiceMappingDiagTarget</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	DiagnosticParameterElement.subElement , DiagnosticParameterIdent.subElement			
Attribute	Type	Mult.	Kind	Note
arraySize	PositiveInteger	0..1	attr	This attribute indicates that the enclosing DiagnosticParameterElement represents an array and configures the array size in terms of the number of elements of the array.
subElement	DiagnosticParameterElement	*	aggr	This collection represents the sub-elements on the next lower level.

Table A.382: DiagnosticParameterElement

Class	DiagnosticParameterElementAccess			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This meta-class acts as a single point for defining structured references to a specific DiagnosticParameterElement.			
Base	<i>ARObject</i>			
Aggregated by	DiagnosticServiceDataMapping.parameterElementAccess , DiagnosticServiceSwMapping.parameterElementAccess			
Attribute	Type	Mult.	Kind	Note
contextElement (ordered)	DiagnosticParameterElement	*	ref	This represents the context of an applicable payload that corresponds to the referenced DataPrototype in the role mappedDataElement. Tags: xml.sequenceOffset=10





Class		DiagnosticParameterElementAccess		
targetElement	DiagnosticParameterElement	0..1	ref	This represents the target reference of an applicable payload that corresponds to the referenced Data Prototype in the role mappedDataElement. Tags: xml.sequenceOffset=20

Table A.383: DiagnosticParameterElementAccess

Class		DiagnosticParameterIdent		
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class has been created to introduce the ability to become referenced into the meta-class AbstractDiagnosticParameter without breaking backwards compatibility.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , DiagnosticServiceMappingDiagTarget , IdentCaption , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , DiagnosticParameter.ident			
Attribute	Type	Mult.	Kind	Note
subElement	DiagnosticParameterElement	*	aggr	This collection represents the subElements on the top level.

Table A.384: DiagnosticParameterIdent

Class		DiagnosticParameterIdentifier		
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents the ability to model a diagnostic parameter identifier (PID) for the purpose of executing on-board diagnostics (OBD). Tags: atp.recommendedPackage=DiagnosticParameterIdentifiers			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataElement	DiagnosticParameter	*	aggr	This represents the data carried by the Diagnostic ParameterIdentifier. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=dataElement.bitOffset, dataElement.ident.shortName, dataElement.variationPoint.shortLabel vh.latestBindingTime=postBuild
id	PositiveInteger	0..1	attr	This is the numerical identifier used to identify the DiagnosticParameterIdentifier in the scope of diagnostic workflow (see SAE J1979-DA).
pidSize	PositiveInteger	0..1	attr	The size of the entire PID can be greater than the sum of the data elements because padding might be applied. Unit: byte.
supportInfoByte	DiagnosticSupportInfoByte	0..1	aggr	This represents the supported information associated with the DiagnosticParameterIdentifier.

Table A.385: DiagnosticParameterIdentifier

Class	DiagnosticPeriodicRate			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::ReadDataByPeriodicID			
Note	This represents the ability to define a periodic rate for the specification of the "read data by periodic ID" diagnostic service.			
Base	ARObject			
Aggregated by	DiagnosticReadDataByPeriodicIDClass.periodicRate			
Attribute	Type	Mult.	Kind	Note
period	TimeValue	0..1	attr	This represents the period of the DiagnosticPeriodicRate in seconds.
periodicRate Category	DiagnosticPeriodicRate CategoryEnum	0..1	attr	This attribute represents the category of the periodic rate.

Table A.386: DiagnosticPeriodicRate

Class	DiagnosticProofOfOwnership			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::Authentication			
Note	This meta-class represents the subfunction to provide proof of ownership. Tags: atp.recommendedPackage=DiagnosticAuthentications			
Base	ARElement , ARObject , CollectableElement , DiagnosticAuthentication , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.387: DiagnosticProofOfOwnership

Class	DiagnosticProtocol			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticContribution			
Note	This meta-class represents the ability to define a diagnostic protocol. Tags: atp.recommendedPackage=DiagnosticProtocols			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic Connection	DiagnosticConnection	*	ref	This represents the collection of applicable Diagnostic Connections for this DiagnosticProtocol. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=diagnosticConnection.diagnosticConnection, diagnosticConnection.variationPoint.shortLabel vh.latestBindingTime=postBuild
priority	PositiveInteger	0..1	attr	This represents the priority of the diagnostic protocol in comparison to other diagnostic protocols. Lower numeric values represent higher protocol priority: <ul style="list-style-type: none">• 0 - Highest protocol priority• 255 - Lowest protocol priority Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
protocolKind	NameToken	0..1	attr	This identifies the applicable protocol.





Class	DiagnosticProtocol			
sendRespPend OnTransToBoot	Boolean	0..1	attr	The purpose of this attribute is to define whether or not the ECU should send a NRC 0x78 (response pending) before transitioning to the bootloader (in this case the attribute shall be set to "true") or if the transition shall be initiated without sending NRC 0x78 (in this case the attribute shall be set to "false"). Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
serviceTable	DiagnosticServiceTable	0..1	ref	This represents the service table applicable for the given diagnostic protocol. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=serviceTable.diagnosticServiceTable, serviceTable.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.388: DiagnosticProtocol

Class	DiagnosticReadDataByIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::DataByIdentifier			
Note	This represents an instance of the "Read Data by Identifier" diagnostic service. Tags: atp.recommendedPackage=DiagnosticDataByIdentifiers			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticDataByIdentifier , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
readClass	DiagnosticReadDataByIdentifierClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticReadDataByIdentifier in the given context.

Table A.389: DiagnosticReadDataByIdentifier

Class	DiagnosticReadDataByPeriodicIDClass			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::ReadDataByPeriodicID			
Note	This meta-class contains attributes shared by all instances of the "Read Data by periodic Identifier" diagnostic service. Tags: atp.recommendedPackage=DiagnosticReadDataByPeriodicIds			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceClass , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
maxPeriodicDidToRead	PositiveInteger	0..1	attr	This represents the maximum number of data identifiers that can be included in one request.
periodicRate	DiagnosticPeriodicRate	*	aggr	This represents the description of a collection of periodic rates in which the service can be executed.
schedulerMaxNumber	PositiveInteger	0..1	attr	This represents the maximum number of periodic data identifiers that can be scheduled in parallel.

Table A.390: DiagnosticReadDataByPeriodicIDClass

Class	DiagnosticReadScalingDataByIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::DataByIdentifier			
Note	This represents an instance of the "Read Scaling Data by Identifier" diagnostic service. Tags: atp.recommendedPackage=DiagnosticDataByIdentifiers			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticDataByIdentifier , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
readScalingDataClass	DiagnosticReadScalingDataByIdentifierClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticReadScalingDataByIdentifier in the given context.

Table A.391: DiagnosticReadScalingDataByIdentifier

Enumeration	DiagnosticRecordTriggerEnum			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticFreezeFrame			
Note	Triggers to allocate an event memory entry.			
Aggregated by	DiagnosticExtendedDataRecord.trigger , DiagnosticFreezeFrame.trigger			
Literal	Description			
confirmed	capture on "Confirmed" Tags: atp.EnumerationLiteralIndex=0			
custom	implement custom capture Tags: atp.EnumerationLiteralIndex=4			
fdcThreshold	capture on "FDC Threshold" Tags: atp.EnumerationLiteralIndex=1			
pending	capture on "Pending" Tags: atp.EnumerationLiteralIndex=2			
testFailed	capture on "Test Failed" Tags: atp.EnumerationLiteralIndex=3			
testFailedThisOperationCycle	Test Failed This Operation Cycle. Tags: atp.EnumerationLiteralIndex=5			
testPassed	Capture on testFailed bit transition 1 --> 0. Tags: atp.EnumerationLiteralIndex=6			

Table A.392: DiagnosticRecordTriggerEnum

Class	DiagnosticRequestControlOfOnBoardDevice			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x08_RequestControlOfOnBoardDevice			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x08 service. Tags: atp.recommendedPackage=DiagnosticRequestControlOfOnBoardDevices			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class		DiagnosticRequestControlOfOnBoardDevice		
requestControlOfOnBoardDeviceClass	DiagnosticRequestControlOfOnBoardDeviceClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestControlOfOnBoardDevice in the given context.
testId	DiagnosticTestRoutineIdentifier	0..1	ref	This represents the test Id for the mode 0x08.

Table A.393: DiagnosticRequestControlOfOnBoardDevice

Class		DiagnosticRequestCurrentPowertrainData		
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x01_RequestCurrentPowertrainDiagnosticData			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x01 service. Tags: atp.recommendedPackage=DiagnosticRequestCurrentPowertrainDatas			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pid	DiagnosticParameterIdentifier	0..1	ref	This represents the PID associated with this instance of the OBD mode 0x01 service.
requestCurrentPowertrainDiagnosticDataClass	DiagnosticRequestCurrentPowertrainDataClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestCurrentPowertrainData in the given context.

Table A.394: DiagnosticRequestCurrentPowertrainData

Class		DiagnosticRequestDownload		
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::MemoryByAddress			
Note	This represents an instance of the "Request Download" diagnostic service. Tags: atp.recommendedPackage=DiagnosticMemoryByAdresss			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMemoryAddressableRangeAccess , DiagnosticMemoryByAddress , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
requestDownloadClass	DiagnosticRequestDownloadClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestDownload in the given context.

Table A.395: DiagnosticRequestDownload

Class	DiagnosticRequestEmissionRelatedDTC			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x03_0x07_RequestEmissionRelatedDTC			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x03/0x07 service. Tags: atp.recommendedPackage=DiagnosticRequestEmissionRelatedDTCs			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
requestEmissionRelatedDtcClass	DiagnosticRequestEmissionRelatedDTCClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestEmissionRelatedDTC in the given context.

Table A.396: DiagnosticRequestEmissionRelatedDTC

Class	DiagnosticRequestEmissionRelatedDTCPermanentStatus			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x0A_RequestEmissionRelatedDTCPermanentStatus			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x0A service. Tags: atp.recommendedPackage=DiagnosticRequestEmissionRelatedDTCPermanentStatuss			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
requestEmissionRelatedDtcClassPermanentStatus	DiagnosticRequestEmissionRelatedDTCPermanentStatusClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestEmissionRelatedDTCPermanentStatus in the given context.

Table A.397: DiagnosticRequestEmissionRelatedDTCPermanentStatus

Class	DiagnosticRequestOnBoardMonitoringTestResults			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x06_RequestOnBoardMonitoringTestResults			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x06 service. Tags: atp.recommendedPackage=DiagnosticRequestOnBoardMonitoringTestResultss			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticTestResult	DiagnosticTestResult	*	ref	This reference identifies the applicable collection of test identifiers for setting up a request message for mode 0x06.
requestOnBoardMonitoringTestResultsClass	DiagnosticRequestOnBoardMonitoringTestResultsClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestOnBoardMonitoringTestResults in the given context.

Table A.398: DiagnosticRequestOnBoardMonitoringTestResults

Class	DiagnosticRequestPowertrainFreezeFrameData			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x02_RequestPowertrainFreezeFrameData			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x02 service. Tags: atp.recommendedPackage=DiagnosticPowertrainFreezeFrames			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
freezeFrame	DiagnosticPowertrainFreezeFrame	0..1	ref	This represents the associated freeze-frame.
requestPowertrainFreezeFrameData	DiagnosticRequestPowertrainFreezeFrameDataClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestPowertrainFreezeFrameData in the given context.

Table A.399: DiagnosticRequestPowertrainFreezeFrameData

Class	DiagnosticRequestRoutineResults			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents the ability to define the result of a diagnostic routine execution.			
Base	ARObject , DiagnosticRoutineSubfunction , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DiagnosticRoutine.requestResult			
Attribute	Type	Mult.	Kind	Note
request	DiagnosticParameter	*	aggr	This represents the request parameters.
response	DiagnosticParameter	*	aggr	This represents the response parameters.

Table A.400: DiagnosticRequestRoutineResults

Class	DiagnosticRequestUpload			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::MemoryByAddress			
Note	This represents an instance of the "Request Upload" diagnostic service. Tags: atp.recommendedPackage=DiagnosticMemoryByAdresss			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMemoryAddressableRangeAccess , DiagnosticMemoryByAddress , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
requestUploadClass	DiagnosticRequestUploadClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestUpload in the given context.

Table A.401: DiagnosticRequestUpload

Class	DiagnosticRequestVehicleInfo			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x09_RequestVehicleInformation			
Note	This meta-class represents the ability to model an instance of the OBD mode 0x09 service. Tags: atp.recommendedPackage=DiagnosticRequestVehicleInfos			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
infoType	DiagnosticInfoType	0..1	ref	This represents the info type associated with the mode 0x09 service.
requestVehicleInformationClass	DiagnosticRequestVehicleInfoClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRequestVehicleInfo in the given context.

Table A.402: DiagnosticRequestVehicleInfo

Class	DiagnosticResponseOnEventClass			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::ResponseOnEvent			
Note	This represents the ability to define common properties for all instances of the "Response on Event" diagnostic service. Tags: atp.recommendedPackage=DiagnosticResponseOnEvents			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceClass , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
maxNumberOfStoredDTCStatusChangedEvents	PositiveInteger	0..1	attr	The maximum number of DTCs that can be stored as DTCs with change status within one ResponseOnEvent SchedulerRate interval.
maxNumChangeOfDataIdentifierEvents	PositiveInteger	0..1	attr	The maximum number of events that can be simultaneously configured with sub function onChangeOfDataIdentifier.
maxNumComparisonOfValueEvents	PositiveInteger	0..1	attr	The maximum number of events that can be simultaneously configured with sub function onComparisonOfValues.
maxSupportedDIDLength	PositiveInteger	0..1	attr	The maximum number of measurable data bytes allowed for each DID that is used for comparison or data change.
responseOnEventSchedulerRate	TimeValue	0..1	attr	The call rate of the periodic scheduler to compare the values of the DataIdentifier (DID) or to detect DTC status changes.
storeEventEnabled	Boolean	0..1	attr	Specifies if the storeEvent functionality of the ResponseOnEvent diagnostic service shall be supported or not. If set to true, the storeEvent functionality is available. If set to false the storeEvent functionality is not available.

Table A.403: DiagnosticResponseOnEventClass

Class	DiagnosticRoutine			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This meta-class represents the ability to define a diagnostic routine. Tags: atp.recommendedPackage=DiagnosticRoutines			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
id	PositiveInteger	0..1	attr	This is the numerical identifier used to identify the DiagnosticRoutine in the scope of diagnostic workflow Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
requestResult	DiagnosticRequestRoutineResults	0..1	aggr	This represents the ability to request the result of a running routine.
routineInfo	PositiveInteger	0..1	attr	This represents the routine info byte. The info byte contains a manufacturer-specific value (for the identification of record identifiers) that is reported to the tester. Other use cases for this attribute are mentioned in ISO 27145 and ISO 26021.
start	DiagnosticStartRoutine	0..1	aggr	This represents the ability to start a routine
stop	DiagnosticStopRoutine	0..1	aggr	This represents the ability to stop a running routine.

Table A.404: DiagnosticRoutine

Class	DiagnosticRoutineControl			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::RoutineControl			
Note	This represents an instance of the "Routine Control" diagnostic service. Tags: atp.recommendedPackage=DiagnosticRoutineControls			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
routine	DiagnosticRoutine	0..1	ref	This refers to the applicable DiagnosticRoutine.
routineControl Class	DiagnosticRoutineControlClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticRoutineControl in the given context.

Table A.405: DiagnosticRoutineControl

Class	DiagnosticRoutineNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the general needs on the configuration of the Diagnostic Communication Manager (Dcm) which are not related to a particular item (e.g. a PID). The main use case is the mapping of service ports to the Dcm which are not related to a particular item.			
Base	ARObject, DiagnosticCapabilityElement, Identifiable, MultilanguageReferrable, Referrable, ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds, SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
diagRoutineType	DiagnosticRoutineTypeEnum	0..1	attr	This denotes the type of diagnostic routine which is implemented by the referenced server port.

Table A.406: DiagnosticRoutineNeeds

Enumeration	DiagnosticRoutineTypeEnum			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	This enumerator specifies the different types of diagnostic routines.			
Aggregated by	DiagnosticRoutineNeeds.diagRoutineType			
Literal	Description			
asynchronous	This indicates that the diagnostic server is not blocked while the diagnostic routine is running. Tags: atp.EnumerationLiteralIndex=0			
synchronous	This indicates that the diagnostic routine blocks the diagnostic server in the ECU while the routine is running. Tags: atp.EnumerationLiteralIndex=1			

Table A.407: DiagnosticRoutineTypeEnum

Class	DiagnosticSecurityAccess			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::SecurityAccess			
Note	This represents an instance of the "Security Access" diagnostic service. Tags: atp.recommendedPackage=DiagnosticSecurityAccesss			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
requestSeedId	PositiveInteger	0..1	attr	This would be 0x01, 0x03, 0x05, ... The sendKey id can be computed by adding 1 to the requestSeedId
securityAccessClass	DiagnosticSecurityAccessClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticSecurityAccess in the given context.
securityDelayTimeOnBoot	TimeValue	0..1	attr	Start delay timer on power on in seconds. This delay indicates the time after ECU boot power-on where no security access request is accepted.
securityLevel	DiagnosticSecurityLevel	0..1	ref	This reference identifies the applicable security level for the security access. Stereotypes: atp.Splittable Tags: atp.Splitkey=securityLevel

Table A.408: DiagnosticSecurityAccess

Class	DiagnosticSecurityAccessClass			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::SecurityAccess			
Note	This meta-class contains attributes shared by all instances of the "Security Access" diagnostic service. Tags: atp.recommendedPackage=DiagnosticSecurityAccess			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticServiceClass , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.409: DiagnosticSecurityAccessClass

Class	DiagnosticSecurityEventReportingModeMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This meta-class represents the ability to associate a location in a DID with a security event. The purpose of this mapping is that the location in the DID contains the setting of the reporting mode for the specific security event. This means that the reporting mode of the security event can be set via the diagnostic service WriteDataByIdentifier. Tags: atp.Status=candidate atp.recommendedPackage=DiagnosticMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataElement	DiagnosticDataElement	0..1	ref	This reference identifies the data element that carries the information about the reporting mode. Tags: atp.Status=candidate
securityEvent	SecurityEventContext Props	0..1	ref	This reference identifies the mapped security event. Tags: atp.Status=candidate

Table A.410: DiagnosticSecurityEventReportingModeMapping

Class	DiagnosticSecurityLevel			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm			
Note	This meta-class represents the ability to define a security level considered for diagnostic purposes. Tags: atp.recommendedPackage=DiagnosticSecurityLevels			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
accessData RecordSize	PositiveInteger	0..1	attr	This represents the size of the AccessDataRecord used in GetSeed. Unit:byte.
keySize	PositiveInteger	0..1	attr	This represents the size of the security key. Unit: byte.
numFailed SecurityAccess	PositiveInteger	0..1	attr	This represents the number of failed security accesses after which the delay time is activated.
securityDelay Time	TimeValue	0..1	attr	This represents the delay time after a failed security access. Unit: second.
seedSize	PositiveInteger	0..1	attr	This represents the size of the security seed. Unit: byte.

Table A.411: DiagnosticSecurityLevel

Class	DiagnosticServiceClass (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::CommonService			
Note	This meta-class provides the ability to define common properties that are shared among all instances of sub-classes of DiagnosticServiceInstance.			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	DiagnosticAuthenticationClass, DiagnosticClearDiagnosticInformationClass, DiagnosticClearResetEmissionRelatedInfoClass, DiagnosticComControlClass, DiagnosticControlDTCSettingClass, DiagnosticCustomServiceClass , DiagnosticDataTransferClass, DiagnosticDynamicallyDefineDataIdentifierClass , DiagnosticEcuResetClass, DiagnosticIoControlClass, DiagnosticReadDTCInformationClass, DiagnosticReadDataByIdentifierClass, DiagnosticReadDataByPeriodicIDClass , DiagnosticReadMemoryByAddressClass, DiagnosticReadScalingDataByIdentifierClass, DiagnosticRequestControlOfOnBoardDeviceClass, DiagnosticRequestCurrentPowertrainDataClass, DiagnosticRequestDownloadClass, DiagnosticRequestEmissionRelatedDTCClass, DiagnosticRequestEmissionRelatedDTCPermanentStatusClass, DiagnosticRequestFileTransferClass, DiagnosticRequestOnBoardMonitoringTestResultsClass, DiagnosticRequestPowertrainFreezeFrameDataClass, DiagnosticRequestUploadClass, DiagnosticRequestVehicleInfoClass, DiagnosticResponseOnEventClass , DiagnosticRoutineControlClass, DiagnosticSecurityAccessClass , DiagnosticSessionControlClass , DiagnosticTransferExitClass, DiagnosticWriteDataByIdentifierClass, DiagnosticWriteMemoryByAddressClass			
Aggregated by	ARPackageElement			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.412: DiagnosticServiceClass

Class	DiagnosticServiceDataMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This represents the ability to define a mapping of a diagnostic service to a software-component. This kind of service mapping is applicable for the usage of SenderReceiverInterfaces or event/notifier semantics in ServiceInterfaces on the adaptive platform. Tags: atp.recommendedPackage=DiagnosticServiceMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackageElement			
Attribute	Type	Mult.	Kind	Note
diagnosticDataElement	DiagnosticDataElement	0..1	ref	This represents the applicable payload that corresponds to the referenced DataPrototype in the role mappedDataElement or (in case of a usage on the adaptive platform) mappedApDataElement.
diagnosticParameter	DiagnosticParameterIdent	0..1	ref	This represents the applicable payload that corresponds to the referenced DataPrototype in the role mappedDataElement. Tags: xml.sequenceOffset=20
mappedDataElement	DataPrototype	0..1	iref	This represents the dataElement in the application software that is accessed for diagnostic purpose. This role is applicable on the classic platform. InstanceRef implemented by: DataPrototypeInSystemInstanceRef
parameterElementAccess	DiagnosticParameterElementAccess	0..1	aggr	This aggregation represents the single point of access to the reference to one specific DiagnosticParameterElement.

Table A.413: DiagnosticServiceDataMapping

Class	<i>DiagnosticServiceInstance</i> (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::CommonService			
Note	This represents a concrete instance of a diagnostic service.			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>DiagnosticCommonElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Subclasses	<i>DiagnosticAuthentication</i> , <i>DiagnosticClearDiagnosticInformation</i> , <i>DiagnosticClearResetEmissionRelatedInfo</i> , <i>DiagnosticComControl</i> , <i>DiagnosticControlDTCSetting</i> , <i>DiagnosticCustomServiceInstance</i> , <i>DiagnosticDataByIdentifier</i> , <i>DiagnosticDynamicallyDefineDataIdentifier</i> , <i>DiagnosticEcuReset</i> , <i>DiagnosticIOControl</i> , <i>DiagnosticMemoryByAddress</i> , <i>DiagnosticReadDTCInformation</i> , <i>DiagnosticReadDataByPeriodicID</i> , <i>DiagnosticRequestControlOfOnBoardDevice</i> , <i>DiagnosticRequestCurrentPowertrainData</i> , <i>DiagnosticRequestEmissionRelatedDTC</i> , <i>DiagnosticRequestEmissionRelatedDTCPermanentStatus</i> , <i>DiagnosticRequestFileTransfer</i> , <i>DiagnosticRequestOnBoardMonitoringTestResults</i> , <i>DiagnosticRequestPowertrainFreezeFrameData</i> , <i>DiagnosticRequestVehicleInfo</i> , <i>DiagnosticResponseOnEvent</i> , <i>DiagnosticRoutineControl</i> , <i>DiagnosticSecurityAccess</i> , <i>DiagnosticSessionControl</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
access Permission	DiagnosticAccessPermission	0..1	ref	This represents the collection of DiagnosticAccessPermissions that allow for the execution of the referencing DiagnosticServiceInstance.. Stereotypes: atpSplitable Tags: atp.Splitkey=accessPermission
serviceClass	DiagnosticServiceClass	0..1	ref	This represents the corresponding "class", i.e. this meta-class provides properties that are shared among all instances of applicable sub-classes of DiagnosticServiceInstance. The subclasses that affected by this pattern implement references to the applicable "class"-role that substantiate this abstract reference. Stereotypes: atpAbstract

Table A.414: DiagnosticServiceInstance

Class	<i>DiagnosticServiceMappingDiagTarget</i> (abstract)			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This meta-class serves as a base class for diagnostics-related targets of subclasses of DiagnosticSwMapping			
Base	<i>ARObject</i>			
Subclasses	DiagnosticDataElement , DiagnosticParameterElement , DiagnosticParameterIdent			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.415: DiagnosticServiceMappingDiagTarget

Class	<i>DiagnosticServiceSwMapping</i>			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping::ServiceMapping			
Note	This represents the ability to define a mapping of a diagnostic service to a software-component or a basic-software module. If the former is used then this kind of service mapping is applicable for the usage of ClientServerInterfaces. Tags: atp.recommendedPackage=DiagnosticServiceMappings			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>DiagnosticCommonElement</i> , <i>DiagnosticMapping</i> , <i>DiagnosticSwMapping</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticServiceSwMapping			
accessedData Prototype	DataPrototype	0..1	iref	This instanceRef identifies the DataPrototype that is supposed to be accessed in the context of the operation argument. InstanceRef implemented by: DataPrototypeInClientServerInterfaceInstanceRef
diagnosticData Element	DiagnosticDataElement	0..1	ref	This represents a DiagnosticDataElement required to execute the respective diagnostic service in the context of the diagnostic service mapping,
diagnostic Parameter	DiagnosticParameterIdent	0..1	ref	This represents the applicable payload that corresponds to the referenced DataPrototype in the role mappedData Element.
mappedBsw Service Dependency	BswServiceDependencyIdent	0..1	ref	This is supposed to represent a reference to a BswServiceDependency. the latter is not derived from Referrable and therefore this detour needs to be implemented to still let BswServiceDependency become the target of a reference.
mappedFlatSwc Service Dependency	SwcServiceDependency	0..1	ref	This represents the ability to refer to an AtomicSwComponentType that is available without the definition of how it will be embedded into the component hierarchy.
mappedSwc Service DependencyIn System	SwcServiceDependency	0..1	iref	This represents the ability to point into the component hierarchy (under possible consideration of the root SoftwareComposition) InstanceRef implemented by: SwcServiceDependencyInSystemInstanceRef
parameter ElementAccess	DiagnosticParameterElementAccess	0..1	aggr	This aggregation represents the single point of access to the reference to one specific DiagnosticParameterElement.
serviceInstance	DiagnosticServiceInstance	0..1	ref	This represents the service instance that needs to be considered in this diagnostics service mapping.

Table A.416: DiagnosticServiceSwMapping

Class	DiagnosticServiceTable			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticContribution			
Note	This meta-class represents a model of a diagnostic service table, i.e. the UDS services applicable for a given ECU. Tags: atp.recommendedPackage=DiagnosticServiceTables			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic Connection	DiagnosticConnection	*	ref	This represents the DiagnosticConnection that is taken for handling the data transmission for the enclosing DiagnosticServiceTable. It is possible to refer to more than one diagnostic Connections in order to support more than one diagnostic tester. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=diagnosticConnection.diagnosticConnection, diagnosticConnection.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	DiagnosticServiceTable			
diagnosticServiceInstance	DiagnosticServiceInstance	*	ref	This represents the collection of DiagnosticServiceInstances to be considered in the scope of this DiagnosticServiceTable. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=diagnosticServiceInstance.diagnosticServiceInstance, diagnosticServiceInstance.variationPoint.shortLabel vh.latestBindingTime=postBuild
ecuInstance	EcuInstance	0..1	ref	This represents the applicable EcuInstance for this DiagnosticServiceTable. Stereotypes: atpSplittable Tags: atp.Splitkey=ecuInstance
protocolKind	NameToken	0..1	attr	This identifies the applicable protocol.

Table A.417: DiagnosticServiceTable

Class	DiagnosticSession			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm			
Note	This meta-class represents the ability to define a diagnostic session. Tags: atp.recommendedPackage=DiagnosticSessions			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
id	PositiveInteger	0..1	attr	This is the numerical identifier used to identify the DiagnosticSession in the scope of diagnostic workflow
jumpToBootLoader	DiagnosticJumpToBootLoaderEnum	0..1	attr	This attribute represents the ability to define whether this diagnostic session allows to jump to Bootloader (OEM Bootloader or System Supplier Bootloader). If this diagnostic session doesn't allow to jump to Bootloader the value JumpToBootLoaderEnum.noBoot shall be chosen.
p2ServerMax	TimeValue	0..1	attr	This is the session value for P2ServerMax in seconds (per Session Control). The AUTOSAR configuration standard is to use SI units, so this parameter is defined as a float value in seconds.
p2StarServerMax	TimeValue	0..1	attr	This is the session value for P2*ServerMax in seconds (per Session Control). The AUTOSAR configuration standard is to use SI units, so this parameter is defined as a float value in seconds.

Table A.418: DiagnosticSession

Class	DiagnosticSessionControl			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::SessionControl			
Note	This represents an instance of the "Session Control" diagnostic service. Tags: atp.recommendedPackage=DiagnosticSessionControls			





Class	DiagnosticSessionControl			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceInstance, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic Session	DiagnosticSession	0..1	ref	This represents the applicable DiagnosticSessions
sessionControl Class	DiagnosticSession ControlClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticSessionControl in the given context.

Table A.419: DiagnosticSessionControl

Class	DiagnosticSessionControlClass			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::SessionControl			
Note	This meta-class contains attributes shared by all instances of the "Session Control" diagnostic service. Tags: atp.recommendedPackage=DiagnosticSessionControls			
Base	<i>ARElement, ARObject, CollectableElement, DiagnosticCommonElement, DiagnosticServiceClass, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
s3Server Timeout	TimeValue	0..1	attr	Time for the server to keep a diagnostic session other than the default session active while not receiving any diagnostic request message.

Table A.420: DiagnosticSessionControlClass

Class	DiagnosticStartRoutine			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This represents the ability to start a diagnostic routine.			
Base	<i>ARObject, DiagnosticRoutineSubfunction, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	DiagnosticRoutine.start			
Attribute	Type	Mult.	Kind	Note
request	DiagnosticParameter	*	aggr	This represents the request parameters.
response	DiagnosticParameter	*	aggr	This represents the response parameters.

Table A.421: DiagnosticStartRoutine

Class	DiagnosticStopRoutine			
Package	M2::AUTOSARTemplates::DiagnosticExtract::CommonDiagnostics			
Note	This represents the ability to stop a diagnostic routine.			
Base	<i>ARObject, DiagnosticRoutineSubfunction, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	DiagnosticRoutine.stop			
Attribute	Type	Mult.	Kind	Note
request	DiagnosticParameter	*	aggr	This represents the request parameters.
response	DiagnosticParameter	*	aggr	This represents the response parameters.

Table A.422: DiagnosticStopRoutine

Class	DiagnosticStorageCondition			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticCondition			
Note	Specification of a storage condition. Tags: atp.recommendedPackage=DiagnosticConditions			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticCondition , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.423: DiagnosticStorageCondition

Class	DiagnosticStorageConditionGroup			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticConditionGroup			
Note	Storage condition group which includes one or several storage conditions. Tags: atp.recommendedPackage=DiagnosticConditions			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticConditionGroup , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
storage Condition	DiagnosticStorageCondition	*	ref	Reference to storageConditions that are part of the StorageConditionGroup. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=storageCondition.diagnosticStorageCondition, storageCondition.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.424: DiagnosticStorageConditionGroup

Class	DiagnosticStorageConditionPortMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	Defines to which SWC service ports with DiagnosticStorageConditionNeeds the DiagnosticStorageCondition is mapped. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , DiagnosticMapping , DiagnosticSwMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic Storage Condition	DiagnosticStorageCondition	0..1	ref	Reference to the StorageCondition which is mapped to a SWC service port with DiagnosticStorageConditionNeeds.
swcFlatService Dependency	SwcServiceDependency	0..1	ref	Reference to a SwcServiceDependencyType that links ServiceNeeds to SWC service ports.
swcService DependencyIn System	SwcServiceDependency	0..1	iref	Instance reference to a SwcServiceDependency that links ServiceNeeds to SWC service ports. InstanceRef implemented by: SwcServiceDependencyInSystemInstanceRef

Table A.425: DiagnosticStorageConditionPortMapping

Class	DiagnosticTestIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTestResult			
Note	This meta-class represents the ability to create a diagnostic test identifier.			
Base	ARObject			
Aggregated by	DiagnosticTestResult.testIdentifier			
Attribute	Type	Mult.	Kind	Note
id	PositiveInteger	0..1	attr	This represents the numerical id associated with the diagnostic test identifier. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
uasld	PositiveInteger	0..1	attr	This represents the unit and scaling Id of the diagnostic test result. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.426: DiagnosticTestIdentifier

Class	DiagnosticTestResult			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTestResult			
Note	This meta-class represents the ability to define diagnostic test results. Tags: atp.recommendedPackage=DiagnosticTestResults			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnosticEvent	DiagnosticEvent	0..1	ref	This attribute represents the diagnostic event that is related to the diagnostic test result. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=diagnosticEvent.diagnosticEvent, diagnosticEvent.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
monitored Identifier	DiagnosticMeasurementIdentifier	0..1	ref	This attribute represents the related diagnostic monitored identifier.
testIdentifier	DiagnosticTestIdentifier	0..1	aggr	This attribute represents the applicable test identifier.
updateKind	DiagnosticTestResult UpdateEnum	0..1	attr	This attribute controls the update behavior of the enclosing DiagnosticTestResult. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.427: DiagnosticTestResult

Class	DiagnosticTestRoutineIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::ObdService::Mode_0x08_RequestControlOfOnBoard Device			
Note	This represents the test id of the DiagnosticTestIdentifier. Tags: atp.recommendedPackage=DiagnosticTestRoutineIdentifier			
Base	ARElement, ARObject, CollectableElement, DiagnosticCommonElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticTestRoutineIdentifier			
id	PositiveInteger	0..1	attr	This represents the numerical id of the DiagnosticTest Identifier (see SAE J1979-DA).
requestDataSize	PositiveInteger	0..1	attr	This represents the specified data size for the request message. Unit: byte.
responseDataSize	PositiveInteger	0..1	attr	This represents the specified data size for the response message. Unit:byte.

Table A.428: DiagnosticTestRoutineIdentifier

Class	DiagnosticTroubleCodeGroup			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTroubleCode			
Note	The diagnostic trouble code group defines the DTCs belonging together and thereby forming a group. Tags: atp.recommendedPackage=DiagnosticTroubleCodes			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dtc	DiagnosticTroubleCode	*	ref	This represents the collection of DiagnosticTroubleCodes defined by this DiagnosticTroubleCodeGroup. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dtc.diagnosticTroubleCode, dtc.variationPoint.shortLabel vh.latestBindingTime=postBuild
groupNumber	PositiveInteger	0..1	attr	This represents the base number of the DTC group. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.429: DiagnosticTroubleCodeGroup

Class	DiagnosticTroubleCodeJ1939			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTroubleCode			
Note	This meta-class represents the ability to model specific trouble-code related properties for J1939. Tags: atp.recommendedPackage=DiagnosticTroubleCodes			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticTroubleCode , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dtcProps	DiagnosticTroubleCodeProps	0..1	ref	Defined properties associated with the J1939 DTC.
fmi	PositiveInteger	0..1	attr	This attribute represents the behavior of the Failure Mode Indicator.
kind	DiagnosticTroubleCodeJ1939DtcKindEnum	0..1	attr	This attribute further specifies the DTC in terms of its semantics.
node	DiagnosticJ1939Node	0..1	ref	This represents the related DiagnosticJ1939Node.
spn	DiagnosticJ1939Spn	0..1	ref	This represents the related SPN.

Table A.430: DiagnosticTroubleCodeJ1939

Enumeration	DiagnosticTroubleCodeJ1939DtcKindEnum
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTroubleCode
Note	This meta-class represents the ability to further specify a J1939 DTC in terms of its semantics.
Aggregated by	DiagnosticTroubleCodeJ1939.kind
Literal	Description
serviceOnly	this represents a DTC that is only relevant for service in a garage, reported by e.g. DM53. Tags: atp.EnumerationLiteralIndex=0
standard	This represents a non-specific DTC reported by e.g. DM1. Tags: atp.EnumerationLiteralIndex=1

Table A.431: DiagnosticTroubleCodeJ1939DtcKindEnum

Class	DiagnosticTroubleCodeObd			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTroubleCode			
Note	This element is used to define OBD-relevant DTCs. Tags: atp.recommendedPackage=DiagnosticTroubleCodes			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticTroubleCode , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
considerPtoStatus	Boolean	0..1	attr	This attribute describes the affection of the event by the Dem PTO handling. true: the event is affected by the Dem PTO handling. false: the event is not affected by the Dem PTO handling. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
eventReadinessGroup	EventObdReadinessGroup	0..1	aggr	This aggregation allows for the variant definition of the attribute eventObdReadinessGroup. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=eventReadinessGroup.eventObdReadinessGroup, eventReadinessGroup.variationPoint.shortLabel, vh.latestBindingTime=postBuild
obdDTCValue	PositiveInteger	0..1	attr	Unique Diagnostic Trouble Code value for OBD. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.432: DiagnosticTroubleCodeObd

Class	DiagnosticTroubleCodeProps			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTroubleCode			
Note	This element defines common Dtc properties that can be reused by different DTCs. Tags: atp.recommendedPackage=DiagnosticTroubleCodeProps			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	DiagnosticTroubleCodeProps			
aging	DiagnosticAging	0..1	ref	Reference to an aging algorithm in case that an aging/unlearning of the event is allowed. Stereotypes: atpSplitable Tags: atp.Splitkey=aging
diagnosticMemory	DiagnosticMemoryDestination	0..1	ref	Reference to the applicable DiagnosticMemory Destination. Stereotypes: atpSplitable Tags: atp.Splitkey=diagnosticMemory
extendedDataRecord	DiagnosticExtendedDataRecord	*	ref	Defines the links to an extended data class sampler. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=extendedDataRecord.diagnosticExtendedDataRecord, extendedDataRecord.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
freezeFrame	DiagnosticFreezeFrame	*	ref	Define the links to a freeze frame class sampler. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=freezeFrame.diagnosticFreezeFrame, freezeFrame.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
immediateNvDataStorage	Boolean	0..1	attr	Change description for Class immediateNvDataStorage in table "Table A.111: DiagnosticTroubleCodeProps": Switch to enable immediate storage triggering of an according event memory entry persistently to NVRAM. true: immediate non-volatile storage triggering on first occurrence and shutdown. false: immediate non-volatile storage triggering on shutdown.
legislatedFreezeFrameContentUdsObd	DiagnosticDataIdentifierSet	0..1	ref	This reference identifies the layout of legislated freeze frames used for emission related diagnostics over the UDS protocol such as OBD on UDS or WWH-OBD. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=legislatedFreezeFrameContentUdsObd.diagnosticDataIdentifierSet, legislatedFreezeFrameContentUdsObd.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
maxNumberFreezeFrameRecords	PositiveInteger	0..1	attr	This attribute defines the number of according freeze frame records, which can maximal be stored for this event. Therefore all these freeze frame records have the same freeze frame class.
obdProps	DiagnosticTroubleCodeObdProps	0..1	aggr	This aggregation is used to define OBD-relevant properties for a Diagnostic Trouble Code Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=obdProps, obdProps.variationPoint.shortLabel vh.latestBindingTime=postBuild
priority	PositiveInteger	0..1	attr	Priority of the event, in view of full event buffer. A lower value means higher priority. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime





Class	DiagnosticTroubleCodeProps			
significance	DiagnosticSignificance Enum	0..1	attr	Significance of the event, which indicates additional information concerning fault classification and resolution.
snapshot RecordContent	DiagnosticDataIdentifier Set	0..1	ref	This represents the freeze frame layout as a set of DIDs. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=snapshotRecordContent.diagnosticDataIdentifierSet, snapshotRecordContent.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.433: DiagnosticTroubleCodeProps

Class	DiagnosticTroubleCodeUds			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dem::DiagnosticTroubleCode			
Note	This element is used to describe diagnostic trouble codes (DTCs). Tags: atp.recommendedPackage=DiagnosticTroubleCodes			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticTroubleCode , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
considerPto Status	Boolean	0..1	attr	This attribute describes the affection of the event by the Dem PTO handling. true: the event is affected by the Dem PTO handling. false: the event is not affected by the Dem PTO handling. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
eventReadiness Group	EventObdReadiness Group	0..1	aggr	This attribute specifies the Event OBD Readiness group for PID \$01 and PID \$41 computation. This attribute is only applicable for emission-related ECUs. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=eventReadinessGroup.eventObdReadinessGroup, eventReadinessGroup.variationPoint.shortLabel vh.latestBindingTime=postBuild
functionalUnit	PositiveInteger	0..1	attr	This attribute specifies a 1-byte value which identifies the corresponding basic vehicle / system function which reports the DTC. This parameter is necessary for the report of severity information. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
obdDtc Value3Byte	PositiveInteger	0..1	attr	3 Byte OBD DTC value based on the definition from SAE J2012. The existence of this attribute is only required if separated UDS and OBD DTC values are used for SAE J1979-2. If this attribute does not exist, then UDS DTC values are used with J1979-2. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
severity	DiagnosticUdsSeverity Enum	0..1	attr	DTC severity according to ISO 14229-1. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime





Class	DiagnosticTroubleCodeUds			
troubleCode Props	DiagnosticTroubleCode Props	0..1	ref	Defined properties associated with the DemDTC. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=troubleCodeProps.diagnosticTroubleCode Props, troubleCodeProps.variationPoint.shortLabel vh.latestBindingTime=postBuild
udsDtcValue	PositiveInteger	0..1	attr	Unique Diagnostic Trouble Code value for UDS. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
wwhObdDtc Class	DiagnosticWwhObdDtc ClassEnum	0..1	attr	This attribute is used to identify (if applicable) the corresponding severity class of an WWH-OB DTC. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.434: DiagnosticTroubleCodeUds

Class	DiagnosticTroubleCodeUdsToTroubleCodeObdMapping			
Package	M2::AUTOSARTemplates::DiagnosticExtract::DiagnosticMapping			
Note	This meta-class represents the ability to associate a UDS trouble code to an OBD trouble code. Tags: atp.recommendedPackage=DiagnosticMappings			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticMapping , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
troubleCode Obd	DiagnosticTroubleCode Obd	0..1	ref	This represents the OBD DTC referenced in the mapping between UDS and OBD DTCs.
troubleCodeUds	DiagnosticTroubleCode Uds	0..1	ref	This represents the UDS DTC referenced in the mapping between UDS and OBD DTCs.

Table A.435: DiagnosticTroubleCodeUdsToTroubleCodeObdMapping

Class	DiagnosticValueNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the general needs on the configuration of the Diagnostic Communication Manager (DCM) which are not related to a particular item (e.g. a PID). The main use case is the mapping of service ports to the DCM which are not related to a particular item. In the case of using a sender receiver communicated value, the related value shall be taken via assigned Data in the role "signalBasedDiagnostics". In case of using a client/server communicated value, the related value shall be communicated via the port referenced by assignedPort. The details of this communication (e.g. appropriate naming conventions) are specified in the related software specifications (SWS).			
Base	ARObject , DiagnosticCapabilityElement , Identifiable , MultilanguageReferrable , Referrable , Service Needs			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
dataLength	PositiveInteger	0..1	attr	This attribute is applicable only if the DiagnosticValue Needs is aggregated within a BswModuleDependency. This attribute represents the length of data (in bytes) provided for this particular PID signal.





Class	DiagnosticValueNeeds			
diagnosticValueAccess	DiagnosticValueAccessEnum	0..1	attr	This attribute is applicable only if the DiagnosticValueNeeds is aggregated within a BswModuleDependency. This attribute controls whether the data can be read and written or whether it is to be handled read-only.
fixedLength	Boolean	0..1	attr	This attribute is applicable only if the DiagnosticValueNeeds is aggregated within a BswModuleDependency. This attribute controls whether the data length of the data is fixed.
processingStyle	DiagnosticProcessingStyleEnum	0..1	attr	This attribute controls whether interaction requires the software-component to react synchronously on a request or whether it processes the request in background but still the DCM has to issue the call again to eventually obtain the result of the request.

Table A.436: DiagnosticValueNeeds

Class	DiagnosticVerifyCertificateBidirectional			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::Authentication			
Note	This meta-class represents the subfunction to do a bidirectional verification of the certificate. Tags: atp.recommendedPackage=DiagnosticAuthentications			
Base	ARElement , ARObject , CollectableElement , DiagnosticAuthentication , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.437: DiagnosticVerifyCertificateBidirectional

Class	DiagnosticVerifyCertificateUnidirectional			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::Authentication			
Note	This meta-class represents the subfunction to do a unidirectional verification of the certificate. Tags: atp.recommendedPackage=DiagnosticAuthentications			
Base	ARElement , ARObject , CollectableElement , DiagnosticAuthentication , DiagnosticCommonElement , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.438: DiagnosticVerifyCertificateUnidirectional

Class	DiagnosticWriteDataByIdentifier			
Package	M2::AUTOSARTemplates::DiagnosticExtract::Dcm::DiagnosticService::DataByIdentifier			
Note	This represents an instance of the "Write Data by Identifier" diagnostic service. Tags: atp.recommendedPackage=DiagnosticDataByIdentifiers			
Base	ARElement , ARObject , CollectableElement , DiagnosticCommonElement , DiagnosticDataByIdentifier , DiagnosticServiceInstance , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			





Class		DiagnosticWriteDataByIdentifier		
Attribute	Type	Mult.	Kind	Note
writeClass	DiagnosticWriteDataByIdentifierClass	0..1	ref	This reference substantiates that abstract reference in the role serviceClass for this specific concrete class. Thereby, the reference represents the ability to access shared attributes among all DiagnosticWriteDataByIdentifier in the given context.

Table A.439: DiagnosticWriteDataByIdentifier

Class		DltConfig		
Package	M2::AUTOSARTemplates::SystemTemplate::Dlt			
Note	This element defines a Dlt configuration for a specific Ecu.			
Base	ARObject			
Aggregated by	EcuInstance.dltConfig			
Attribute	Type	Mult.	Kind	Note
dltEcu	DltEcu	0..1	ref	Reference to the Ecu representation in the Log And Trace Extract.
dltLogChannel	DltLogChannel	*	aggr	Describes the DltLogChannels that are configured for the log/trace message output
globalTimeDomain	GlobalTimeDomain	0..1	ref	Reference to the GlobalTimeDomain this DltConfig shall be synchronized with Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=globalTimeDomain.globalTimeDomain, globalTimeDomain.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
sessionIdSupport	Boolean	0..1	attr	This attribute defines whether the sessionId is used or not.
timestampSupport	Boolean	0..1	attr	This attribute defines whether a timestamp shall be added to the Dlt messages or not.

Table A.440: DltConfig

Class		DltLogChannel		
Package	M2::AUTOSARTemplates::SystemTemplate::Dlt			
Note	This element contains the settings for the log/trace message output for a tuple of ApplicationId and ContextId (verbose mode) or a SessionId (non-verbose mode).			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	DltConfig.dltLogChannel			
Attribute	Type	Mult.	Kind	Note
applicationContext	DltContext	*	ref	Reference to the Swc that produces the log or trace message. Please note that this reference shall not be set in case that the Bsw module produces the associated log or trace messages.
defaultTraceState	DltDefaultTraceStateEnum	0..1	attr	This attributes defines the default trace status.
dltMessage	DltMessage	*	ref	Reference to DltMessages that can be transported over the DltLogChannel in the DltPdu.
logChannelId	String	0..1	attr	This attribute identifies the Channel for usage within the Log And Trace protocol.





Class	DltLogChannel			
logTraceDefaultLogThreshold	LogTraceDefaultLogLevelEnum	0..1	attr	This attribute allows to set a log level Threshold for Log Level filtering.
nonVerboseMode	Boolean	0..1	attr	This attribute defines whether this channel supports non-Verbose Dlt messages. If disabled only verbose mode messages shall be used.
rxPduTriggering	PduTriggering	0..1	ref	Reference to DltPdu that is received by the DltLog Channel
segmentationSupported	Boolean	0..1	attr	If enabled, segmentation will be used if a DLT message is larger than Pdu.length referenced via DltLogChannel.txPduTriggering.
txPduTriggering	PduTriggering	0..1	ref	Reference to DltPdu that is transmitted by the DltLog Channel.

Table A.441: DltLogChannel

Class	DolpActivationLineNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	A DolP entity needs to be informed when an external tester is attached or activated. The DolpActivationServiceNeeds specifies the trigger for such an event. Examples would be a Pdu via a regular communication bus, a PWM signal, or an I/O. For details please refer to the ISO 13400.			
Base	ARObject , DolpServiceNeeds , Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.442: DolpActivationLineNeeds

Class	DolpGidNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	The DolpGidNeeds indicates that the software-component owning this ServiceNeeds is providing the GID number either after a GID Synchronisation or by other means like e.g. flashed EEPROM parameter. This need can be used independent from DolpGidSynchronizationNeeds and is necessary if the GID can not be provided out of the DolP configuration options.			
Base	ARObject , DolpServiceNeeds , Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.443: DolpGidNeeds

Class	DolpGidSynchronizationNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	The DolpGidSynchronizationNeeds indicates that the software-component owning this ServiceNeeds is triggered by the DolP entity to start a synchronization of the GID (Group Identification) on the DolP service 0x0001, 0x0002, 0x0003 or before announcement via service 0x0004 according to ISO 13400-2:2012 if necessary. Note that this need is only relevant for DolP synchronization masters.			
Base	ARObject , DolpServiceNeeds , Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.444: DolpGidSynchronizationNeeds

Class	DolpLogicAddress			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	The logical DoIP address.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	DolpConfig.logicAddress, DolpTpConfig.dolpLogicAddress			
Attribute	Type	Mult.	Kind	Note
address	Integer	0..1	attr	The logical DoIP address.
dolpLogicAddressProps	AbstractDolpLogicAddressProps	0..1	aggr	Collection of additional LogicAddress properties.

Table A.445: DolpLogicAddress

Class	DolpPowerModeStatusNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	The DolpPowerModeStatusNeeds indicates that the software-component owning this ServiceNeeds is providing the PowerModeStatus for the DoIP service 0x4003 according to ISO 13400-2:2012.			
Base	<i>ARObject</i> , <i>DolpServiceNeeds</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>ServiceNeeds</i>			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.446: DolpPowerModeStatusNeeds

Class	DolpServiceNeeds (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	This represents an abstract base class for ServiceNeeds related to DoIP.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>ServiceNeeds</i>			
Subclasses	DolpActivationLineNeeds , DolpGidNeeds , DolpGidSynchronizationNeeds , DolpPowerModeStatusNeeds , DolpRoutingActivationAuthenticationNeeds , DolpRoutingActivationConfirmationNeeds , FurtherActionByteNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.447: DolpServiceNeeds

Class	DolpTpConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	This element defines exactly one DolpTp Configuration that is used to configure all DolpChannels available in a DolpInterface. Each DoIPChannel describes a connection between a dolpSourceAddress and a dolpTargetAddress and the exchange of DcmIPdus between the PduR and DoIP. Tags: atp.recommendedPackage=TpConfigs			
Base	<i>ARObject</i> , <i>CollectableElement</i> , <i>FibexElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i> , <i>TpConfig</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dolpLogicAddress	DolpLogicAddress	*	aggr	Collection of logical DoIP Addresses.
tpConnection	DolpTpConnection	*	aggr	Collection of unidirectional connections between a source address and a target address.

Table A.448: DolpTpConfig

Class	DolpTpConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::DiagnosticConnection			
Note	A connection identifies the sender and the receiver of this particular communication. The Dolp module routes a tpSdu through this connection.			
Base	<i>ARObject</i> , <i>TpConnection</i>			
Aggregated by	DolpTpConfig.tpConnection			
Attribute	Type	Mult.	Kind	Note
dolpSource Address	DolpLogicAddress	0..1	ref	Reference to the address of the sender of the tpSdu.
dolpTarget Address	DolpLogicAddress	0..1	ref	Reference to the address of the receiver of the tpSdu.
tpSdu	PduTriggering	0..1	ref	This reference is used to describe the data exchange between Dolp and the PduR.

Table A.449: DolpTpConnection

Class	Documentation			
Package	M2::AUTOSARTemplates::GenericStructure::DocumentationOnM1			
Note	This meta-class represents the ability to handle a so called standalone documentation. Standalone means, that such a documentation is not embedded in another ARElement or identifiable object. The standalone documentation is an entity of its own which denotes its context by reference to other objects and instances. Tags: atp.recommendedPackage=Documentations			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , MultilanguageReferrable , <i>PackageableElement</i> , Referrable , <i>UploadableDesignElement</i> , <i>UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
context	DocumentationContext	*	aggr	This is the context of the particular documentation.
documentation Content	PredefinedChapter	0..1	aggr	This is the content of the documentation related to the specified contexts. Tags: xml.sequenceOffset=200

Table A.450: Documentation

Class	«atpMixed» DocumentationBlock			
Package	M2::MSR::Documentation::BlockElements			
Note	This class represents a documentation block. It is made of basic text structure elements which can be displayed in a table cell.			
Base	<i>ARObject</i>			
Aggregated by	ApplicabilityInfo.remark, AUTOSAR.introduction , <i>BlueprintGenerator.introduction</i> , <i>BlueprintPolicyModifiable.blueprintDerivationGuide</i> , ClientServerOperationBlueprintMapping.blueprintMappingGuide , DataMapping.introduction , <i>DefItem.def</i> , <i>Describable.introduction</i> , EcucAddInfoParamValue.value , EcuResourceEstimation.introduction, <i>Entry.entryContents</i>, FrameMapping.introduction, <i>GeneralAnnotation.annotationText</i>, Identifiable.introduction, IPduMapping.introduction, ISignalMapping.introduction, <i>Item.itemContents</i>, <i>LabeledItem.itemContents</i>, LifeCycleInfo.remark, MappingConstraint.introduction, <i>MsrQueryP2.msrQueryResultP2</i>, <i>Note.noteText</i>, <i>PortDefinedArgumentBlueprint.blueprintMappingGuide</i>, <i>PrmChar.cond</i>, <i>PrmChar.remark</i>, ScheduleTableEntry.introduction, SignalPathConstraint.introduction, StructuredReq.conflicts, StructuredReq.dependencies, StructuredReq.description, StructuredReq.rationale, StructuredReq.remark, StructuredReq.supportingMaterial, StructuredReq.useCase, <i>SwAxisType.swGenericAxisDesc</i>, <i>TopicContent.blockLevelContent</i>, TraceableText.text, VariationPoint.blueprintCondition 			
Attribute	Type	Mult.	Kind	Note





Class	«atpMixed» DocumentationBlock			
defList	DefList	0..1	aggr	This represents a definition list in the documentation block. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=40
figure	MIFigure	0..1	aggr	This represents a figure in the documentation block. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=70
formula	MIFormula	0..1	aggr	This is a formula in the definition block. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=60
labeledList	LabeledList	0..1	aggr	This represents a labeled list. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=50
list	List	0..1	aggr	This represents numbered or unnumbered list. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=30
msrQueryP2	MsrQueryP2	0..1	aggr	This represents automatically contributed contents provided by an msrquery in the context of Documentation Block.
note	Note	0..1	aggr	This represents a note in the text flow. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=80
p	MultiLanguage Paragraph	0..1	aggr	This is one particular paragraph. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=10
structuredReq	StructuredReq	0..1	aggr	This aggregation supports structured requirements embedded in a documentation block. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=100
trace	TraceableText	0..1	aggr	This represents traceable text in the documentation block. This allows to specify requirements/constraints in any documentation block. The kind of the trace is specified in the category. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=90





Class	«atpMixed» DocumentationBlock			
verbatim	MultiLanguageVerbatim	0..1	aggr	This represents one particular verbatim text. Stereotypes: atpVariation Tags: vh.latestBindingTime=postBuild xml.sequenceOffset=20

Table A.451: DocumentationBlock

Class	DocumentationContext			
Package	M2::AUTOSARTemplates::GenericStructure::DocumentationOnM1			
Note	This class represents the ability to denote a context of a so called standalone documentation. Note that this is an <<atpMixed>>. The contents needs to be considered as ordered.			
Base	ARObject, MultilanguageReferrable , Referrable			
Aggregated by	Documentation.context			
Attribute	Type	Mult.	Kind	Note
feature	AtpFeature	0..1	iref	This refers to a particular feature (instance in the M0 model) to which is the context of the documentation. InstanceRef implemented by: AnyInstanceRef
identifiable	Identifiable	0..1	ref	This is an identifiable object which is part of the context of the documentation.

Table A.452: DocumentationContext

Class	DtcStatusChangeNotificationNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	This meta-class represents the needs of a software-component interested to get information regarding any DTC status change.			
Base	ARObject, DiagnosticCapabilityElement , Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
notificationTime	DiagnosticClearDtc NotificationEnum	0..1	attr	This attribute determines the time when the notification about the DTC operation shall be executed. This attribute is only relevant for the configuration of the ClearDtc Notification.

Table A.453: DtcStatusChangeNotificationNeeds

Class	DynamicPart			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Dynamic part of a multiplexed I-Pdu. Reserved space which is used to transport varying SignallPdus at the same position, controlled by the corresponding selectorFieldCode.			
Base	ARObject, MultiplexedPart			
Aggregated by	MultiplexedIPdu.dynamicPart			
Attribute	Type	Mult.	Kind	Note
dynamicPart Alternative	DynamicPartAlternative	*	aggr	Com IPdu alternatives that are transmitted in the Dynamic Part of the MultiplexedIPdu.

Table A.454: DynamicPart

Class	DynamicPartAlternative			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	One of the Com IPdu alternatives that are transmitted in the Dynamic Part of the MultiplexedIPdu. The selectorFieldCode specifies which Com IPdu is contained in the DynamicPart within a certain transmission of a multiplexed PDU.			
Base	ARObject			
Aggregated by	DynamicPart.dynamicPartAlternative			
Attribute	Type	Mult.	Kind	Note
initialDynamicPart	Boolean	0..1	attr	Dynamic part that shall be used to initialize this multiplexed IPdu. Constraint: Only one "DynamicPartAlternative" in a "DynamicPart" shall be the initialDynamicPart.
iPdu	ISignalIPdu	0..1	ref	Reference to a Com IPdu which is routed to the IPduM module and is combined to a multiplexedPdu.
selectorFieldCode	Integer	0..1	attr	The selector field is part of a multiplexed IPdu. It consists of contiguous bits. The value of the selector field selects the layout of the multiplexed part of the IPdu.

Table A.455: DynamicPartAlternative

Class	E2EProfileCompatibilityProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	This meta-class collects settings for configuration of the E2E state machine. Tags: atp.recommendedPackage=E2EProfileCompatibilityPropsCollection			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
combinedNoDataInitCount	Boolean	0..1	attr	E2E State machine behavior concerning counting of detected counter errors and missing messages in states NODATA and INIT <ul style="list-style-type: none"> value = 0 (false) or not defined: counting of detected counter errors and missing messages in states NODATA and INIT are counted per state separated (Autosar R23-11 or former behavior) value = 1 (true): counting of detected counter errors and missing messages in states NODATA and INIT are counted in total
transitToInvalidExtended	Boolean	0..1	attr	E2E State machine behavior concerning transition from NODATA/INIT to INVALID value=0 (false): no direct transition from NODATA to INVALID, no transition from INIT to INVALID due to counter-related faults (Autosar R19-11 or former behavior) value=1 (true): direct transition from NODATA to INVALID covered, transition from INIT to INVALID due to counter-related faults covered (state machine extended)

Table A.456: E2EProfileCompatibilityProps

Class	ECUMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::ECUResourceMapping			
Note	ECUMapping allows to assign an ECU hardware type (defined in the ECU Resource Template) to an ECUInstance used in a physical topology.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SystemMapping.ecuResourceMapping			
Attribute	Type	Mult.	Kind	Note
commControllerMapping	CommunicationControllerMapping	*	aggr	The ECUMapping contains the mapping of all CommunicationControllers of the ECU.
ecu	HwElement	0..1	ref	Reference to a HwElement of category ECU in the ECU Resource Template.
ecuInstance	EcuInstance	0..1	ref	Reference to the EcuInstance in the System Template
hwPortMapping	HwPortMapping	1..*	aggr	The ECUMapping contains the mapping of all HW Communication Ports of the ECU.

Table A.457: ECUMapping

Class	EOCEventRef			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::ExecutionOrderConstraint			
Note	This is used to define a reference to an RTE or BSW Event.			
Base	ARObject, EOCExecutableEntityRefAbstract , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ExecutionOrderConstraint.orderedElement			
Attribute	Type	Mult.	Kind	Note
bswModuleInstance	BswImplementation	0..1	ref	Specifies the BSW module instance the BSW event is related to.
component	SwComponentPrototype	0..1	iref	This association references the specific instance of the SW-C prototype. InstanceRef implemented by: ComponentInCompositionInstanceRef
event	AbstractEvent	0..1	ref	The AbstractEvent (event) whose execution order is restricted by the constraint.
successor	EOCExecutableEntityRefAbstract	*	ref	The logical successor of an executable entity or a group of executable entities.

Table A.458: EOCEventRef

Class	EOCExecutableEntityRef			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::ExecutionOrderConstraint			
Note	This is used to define a reference to an ExecutableEntity If the ExecutionOrderConstraint is defined on VFB, System or ECU level, a reference to the Sw ComponentPrototype, via the ComponentInCompositionInstanceRef, the referenced ExecutableEntity belongs to, shall be provided as context information.			
Base	ARObject, EOCExecutableEntityRefAbstract , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ExecutionOrderConstraint.orderedElement			
Attribute	Type	Mult.	Kind	Note
bswModuleInstance	BswImplementation	0..1	ref	Specifies the BSW module instance the BSW module entity belongs to.





Class	EOCExecutableEntityRef			
component	SwComponentPrototype	0..1	iref	This association references the specific instance of the SW-C prototype. InstanceRef implemented by: ComponentInCompositionInstanceRef
executable	ExecutableEntity	0..1	ref	The ExecutableEntity whose execution order is restricted by the constraint.
successor	EOCExecutableEntityRefAbstract	*	ref	The logical successor of an executable entity or a group of executable entities.

Table A.459: EOCExecutableEntityRef

Class	EOCExecutableEntityRefAbstract (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::ExecutionOrderConstraint			
Note	This is the abstractions for Execution Order Constraint Executable Entity References (leaves) and Execution Order Constraint Executable Entity Reference Groups (composites).			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	EOCEventRef , EOCExecutableEntityRef , EOCExecutableEntityRefGroup			
Aggregated by	ExecutionOrderConstraint.orderedElement			
Attribute	Type	Mult.	Kind	Note
directSuccessor	EOCExecutableEntityRefAbstract	*	ref	The direct successor of an executable entity or a group of executable entities.

Table A.460: EOCExecutableEntityRefAbstract

Class	EOCExecutableEntityRefGroup			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::ExecutionOrderConstraint			
Note	This is used to specify a group (composite) consisting of Execution Order Constraint Executable Entity References (leaves) and/or further Execution Order Constraint Executable Entity Reference Groups (composite).			
Base	<i>ARObject</i> , EOCExecutableEntityRefAbstract , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	ExecutionOrderConstraint.orderedElement			
Attribute	Type	Mult.	Kind	Note
letDataExchangeParadigm	LetDataExchangeParadigmEnum	0..1	attr	Specifies the data exchange paradigm between ExecutableEntity s within a LET interval. Tags: atp.Status=draft
letInterval	TimingDescriptionEventChain	*	ref	This association references the TimingDescriptionEventChain that plays the role of a LET interval the executable entities in the group are assigned to. [constr_4554] applies.
maxCycleRepetitions	PositiveInteger	0..1	attr	Repetitive Execution Order Constraint only: The number of repetitions (cycles) of the event in the Repetitive Execution Order Constraint. Tags: atp.Status=draft
maxCycles	Integer	0..1	attr	In case of a Repetitive Execution Order Constraint this attribute specifies the number of cycles the Execution Order Constraint is considering. Tags: atp.Status=obsolete





Class	EOCExecutableEntityRefGroup			
maxSlots	Integer	0..1	attr	In case of a Repetitive Execution Order Constraint this attribute specifies the number of slots every cycle of the Execution Order Constraint is consisting of. Tags: atp.Status=obsolete
maxSlotsPer Cycle	PositiveInteger	0..1	attr	Repetitive Execution Order Constraint only: The number of ExecutableEntities (slots) that are executed in a given order within a cycle, for the Repetitive Execution Order Constraint. Tags: atp.Status=draft
nestedElement (ordered)	EOCExecutableEntityRefAbstract	*	ref	This association is used to establish hierarchies of EOCEER Groups and References.
successor	EOCExecutableEntityRefAbstract	*	ref	The logical successor of an executable entity or a group of executable entities.
triggeringEvent	TimingDescriptionEvent	0..1	ref	In case of a Repetitive Execution Order Constraint this association references the timing description event triggering every cycle.

Table A.461: EOCExecutableEntityRefGroup

Class	EcuAbstractionSwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	The ECUAbstraction is a special AtomicSwComponentType that resides between a software-component that wants to access ECU periphery and the Microcontroller Abstraction. The EcuAbstractionSwComponentType introduces the possibility to link from the software representation to its hardware description provided by the ECU Resource Template. Tags: atp.recommendedPackage=SwComponentTypes			
Base	ARElement , ARObject , AtomicSwComponentType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
hardware Element	HwDescriptionEntity	*	ref	Reference from the EcuAbstractionComponentType to the description of the used HwElements.

Table A.462: EcuAbstractionSwComponentType

Class	EcuInstance			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	ECUInstances are used to define the ECUs used in the topology. The type of the ECU is defined by a reference to an ECU specified with the ECU resource description. Tags: atp.recommendedPackage=EcuInstances			
Base	ARObject , CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	EcuInstance			
associatedComIPduGroup	ISignalPduGroup	*	ref	<p>With this reference it is possible to identify which ISignalIPduGroups are applicable for which Communication Connector/ ECU.</p> <p>Only top level ISignalPduGroups shall be referenced by an EcuInstance. If an ISignalPduGroup contains other ISignalIPduGroups than these contained ISignalPdu Groups shall not be referenced by the EcuInstance. Contained ISignalIPduGroups are associated to an Ecu Instance via the top level ISignalPduGroup.</p>
associatedConsumedProvidedServiceInstanceGroup	ConsumedProvidedServiceInstanceGroup	*	ref	<p>With this reference it is possible to identify which ConsumedProvidedServiceInstanceGroups are applicable for which ECUInstance.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=associatedConsumedProvidedServiceInstanceGroup.consumedProvidedServiceInstanceGroup, associatedConsumedProvidedServiceInstanceGroup.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
associatedPdurIPduGroup	PdurIPduGroup	*	ref	<p>With this reference it is possible to identify which PduRIPdu Groups are applicable for which Communication Connector/ ECU.</p>
channelSynchronousWakeup	Boolean	0..1	attr	<p>If this parameter is available and set to true, then all available channels will be woken up as soon as at least one channel wakeup occurs. If PNCs are configured, then all PNCs will be requested upon a channel wakeup.</p>
clientIdRange	ClientIdRange	0..1	aggr	<p>Restriction of the Client Identifier for this Ecu to an allowed range of numerical values. The Client Identifier of the transaction handle is generated by the client RTE for inter-Ecu Client/Server communication.</p>
comConfigurationGwTimeBase	TimeValue	0..1	attr	<p>The period between successive calls to Com_MainFunctionRouteSignals of the AUTOSAR COM module in seconds.</p>
comConfigurationRxTimeBase	TimeValue	0..1	attr	<p>The period between successive calls to Com_MainFunctionRx of the AUTOSAR COM module in seconds.</p>
comConfigurationTxTimeBase	TimeValue	0..1	attr	<p>The period between successive calls to Com_MainFunctionTx of the AUTOSAR COM module in seconds.</p>
comEnableMDTForCyclicTransmission	Boolean	0..1	attr	<p>Enables for the Com module of this EcuInstance the minimum delay time monitoring for cyclic and repeated transmissions (TransmissionModeTiming has cyclic Timing assigned or eventControlledTiming with numberOfRepetitions > 0).</p>
commController	CommunicationController	*	aggr	<p>CommunicationControllers of the ECU.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=commController.shortName, commController.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
connector	CommunicationConnector	*	aggr	<p>All channels controlled by a single controller.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=connector.shortName, connector.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
dltConfig	DltConfig	0..1	aggr	<p>Describes the Dlt configuration on this EcuInstance.</p>





Class	EcuInstance			
dolpConfig	DolpConfig	0..1	aggr	Dolp configuration on this EcuInstance. Tags: atp.Status=draft
ecuTaskProxy	OsTaskProxy	*	ref	Reference to OsTaskProxies assigned to the Ecu Instance. Stereotypes: atpSplitable Tags: atp.Splitkey=ecuTaskProxy
ethSwitchPort Group Derivation	Boolean	0..1	attr	Defines whether the derivation of SwitchPortGroups based on VLAN and/or CouplingPort.pncMapping shall be performed for this EcuInstance. If not defined the derivation shall not be done.
firewallRule	StateDependentFirewall	*	ref	Firewall rules defined in the context of an EcuInstance. Tags: atp.Status=candidate
partition	EcuPartition	*	aggr	Optional definition of Partitions within an Ecu.
pncNmRequest	Boolean	0..1	attr	Defines if this EcuInstance shall request Nm on all its PhysicalChannels which have Nm variant set to FULL each time a PNC is requested.
pncPrepare SleepTimer	TimeValue	0..1	attr	Time in seconds the PNC state machine shall wait in PNC_PREPARE_SLEEP.
pnc Synchronous Wakeup	Boolean	0..1	attr	If this parameter is available and set to true then all available PNCs will be woken up as soon as a channel wakeup occurs. This is ensured by adding all PNCs to all channel wakeup sources during upstream mapping.
pnResetTime	TimeValue	0..1	attr	Specifies the runtime of the reset timer in seconds. This reset time is valid for the reset of PN requests in the EIRA and in the ERA.
sleepMode Supported	Boolean	0..1	attr	Specifies whether the ECU instance may be put to a "low power mode" <ul style="list-style-type: none"> • true: sleep mode is supported • false: sleep mode is not supported Note: This flag may only be set to "true" if the feature is supported by both hardware and basic software.
tcplplcmpProps	EthTcplplcmpProps	0..1	ref	EcuInstance specific ICMP (Internet Control Message Protocol) attributes
tcplpProps	EthTcplpProps	0..1	ref	EcuInstance specific Tcplp Stack attributes.
v2xSupported	V2xSupportEnum	0..1	attr	This attribute is used to control the existence of the V2X stack on the given EcuInstance.
wakeUpOver BusSupported	Boolean	0..1	attr	Driver support for wakeup over Bus.

Table A.463: EcuInstance

Class	EcuPartition			
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	Partitions are used as error containment regions. They permit the grouping of SWCs and resources and allow to describe recovery policies individually for each partition. Partitions can be terminated or restarted during run-time as a result of a detected error.			
Base	AObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EcuInstance.partition			
Attribute	Type	Mult.	Kind	Note





Class	EcuPartition			
execInUser Mode	Boolean	0..1	attr	A partition can execute either in CPU user mode (execInUserMode = TRUE) or supervisor mode (execInUserMode = FALSE). In user mode, the partition has a limited access to memory, to memory mapped hardware and to CPU. In user mode, the partition is mapped to a non-trusted OS-Application.

Table A.464: EcuPartition

Class	EcuResourceEstimation			
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	Resource estimations for RTE and BSW of a single ECU instance.			
Base	ARObject			
Aggregated by	SystemMapping.resourceEstimation			
Attribute	Type	Mult.	Kind	Note
bswResource Estimation	ResourceConsumption	0..1	aggr	Estimation for the resource consumption of the basic software.
ecuInstance	EcuInstance	0..1	ref	Reference to the ECU this estimation is done for.
introduction	DocumentationBlock	0..1	aggr	This represents introductory documentation about the ecu resource estimation Tags: xml.sequenceOffset=-10
rteResource Estimation	ResourceConsumption	0..1	aggr	Estimation for the resource consumption of the run time environment.
swCompToEcu Mapping	SwcToEcuMapping	*	ref	References to SwcToEcuMappings that have been taken into account for the resource estimations. This way it is possible to define different EcuResourceEstimations with different mappings, e.g. before and after mapping an additional SW component.

Table A.465: EcuResourceEstimation

Class	EcuTiming			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingExtensions			
Note	A model element used to define timing descriptions and constraints within the scope of one ECU configuration. TimingDescriptions aggregated by EcuTiming are allowed to use all events derived from the class TimingDescriptionEvent. Tags: atp.recommendedPackage=TimingExtensions			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable , TimingExtension			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
ecu Configuration	EcucValueCollection	0..1	ref	This defines the scope of an EcuTiming. All corresponding timing descriptions and constraints shall be defined within this scope.

Table A.466: EcuTiming

Class	EcucAbstractConfigurationClass (abstract)			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Specifies the ValueConfigurationClass of a parameter/reference or the MultiplicityConfigurationClass of a parameter/reference or a container for each ConfigurationVariant of the EcucModuleDef.			
Base	ARObject			
Subclasses	EcucMultiplicityConfigurationClass, EcucValueConfigurationClass			
Attribute	Type	Mult.	Kind	Note
configClass	EcucConfigurationClass Enum	0..1	attr	Specifies the ConfigurationClass for the given ConfigurationVariant.
configVariant	EcucConfiguration VariantEnum	0..1	attr	Specifies the ConfigurationVariant the ConfigurationClass is specified for.

Table A.467: EcucAbstractConfigurationClass

Class	EcucAbstractInternalReferenceDef (abstract)			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Common abstract class to gather attributes for internal references (where the destination is located in the Ecu Configuration Description).			
Base	ARObject, AtpDefinition, EcucAbstractReferenceDef, EcucCommonAttributes, EcucDefinitionElement, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	EcucChoiceReferenceDef, EcucReferenceDef, EcucUriReferenceDef			
Aggregated by	EcucDestinationUriPolicy.reference, EcucParamConfContainerDef.reference			
Attribute	Type	Mult.	Kind	Note
requires SymbolicName Value	Boolean	0..1	attr	If this attribute is set to true the implementation of the reference is done using a Symbolic Name defined by the referenced container according to TPS_ECUC_02108.

Table A.468: EcucAbstractInternalReferenceDef

Class	EcucAbstractReferenceDef (abstract)			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Common class to gather the attributes for the definition of references.			
Base	ARObject, AtpDefinition, EcucCommonAttributes, EcucDefinitionElement, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	EcucAbstractExternalReferenceDef, EcucAbstractInternalReferenceDef			
Aggregated by	EcucDestinationUriPolicy.reference, EcucParamConfContainerDef.reference			
Attribute	Type	Mult.	Kind	Note
withAuto	Boolean	0..1	attr	<p>Specifies whether it shall be allowed on the value side to specify this reference value as "AUTO".</p> <p>If withAuto is "true" it shall be possible to set the "isAuto Value" attribute of the respective reference to "true". This means that the actual value will not be considered during ECU Configuration but will be (re-)calculated by the code generator and stored in the value attribute afterwards. These implicit updated values might require a re-generation of other modules which reference these values.</p> <p>If withAuto is "false" it shall not be possible to set the "isAuto Value" attribute of the respective reference to "true".</p> <p>If withAuto is not present the default is "false".</p>

Table A.469: EcucAbstractReferenceDef

Class	EcucAbstractReferenceValue (abstract)			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	Abstract class to be used as common parent for all reference values in the ECU Configuration Description.			
Base	ARObject, EcucIndexableValue			
Subclasses	EcucInstanceReferenceValue, EcucReferenceValue			
Aggregated by	EcucContainerValue.referenceValue			
Attribute	Type	Mult.	Kind	Note
annotation	Annotation	*	aggr	Possibility to provide additional notes while defining a model element (e.g. the ECU Configuration Parameter Values). These are not intended as documentation but are mere design notes.
definition	EcucAbstractReferenceDef	0..1	ref	Reference to the definition of this EcucAbstractReferenceValue subclasses in the ECU Configuration Parameter Definition. Tags: xml.sequenceOffset=-10
isAutoValue	Boolean	0..1	attr	If withAuto is set to "true" for this parameter definition the isAutoValue can be set to "true". If isAutoValue is set to "true" the actual value will not be considered during ECU Configuration but will be (re-)calculated by the code generator and stored in the value attribute afterwards. These implicit updated values might require a re-generation of other modules which reference these values. If isAutoValue is not present the default is "false".

Table A.470: EcucAbstractReferenceValue

Class	EcucAddInfoParamValue			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	This parameter corresponds to EcucAddInfoParamDef.			
Base	ARObject, EcucIndexableValue, EcucParameterValue			
Aggregated by	EcucContainerValue.parameterValue			
Attribute	Type	Mult.	Kind	Note
value	DocumentationBlock	0..1	aggr	Holds the content of the formatted text.

Table A.471: EcucAddInfoParamValue

Class	EcucChoiceContainerDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Used to define configuration containers that provide a choice between several EcucParamConfContainerDef. But in the actual ECU Configuration Values only one instance from the choice list will be present.			
Base	ARObject, AtpDefinition, EcucContainerDef , EcucDefinitionElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EcucDestinationUriPolicy.container , EcucModuleDef.container , EcucParamConfContainerDef.subContainer			
Attribute	Type	Mult.	Kind	Note
choice	EcucParamConfContainerDef	*	aggr	The choices available in a EcucChoiceContainerDef. Stereotypes: atpSplitable Tags: atp.Splitkey=choice.shortName

Table A.472: EcucChoiceContainerDef

Class	EcucChoiceReferenceDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Specify alternative references where in the ECU Configuration description only one of the specified references will actually be used.			
Base	<i>ARObject, AtpDefinition, EcucAbstractInternalReferenceDef, EcucAbstractReferenceDef, EcucCommonAttributes, EcucDefinitionElement, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	EcucDestinationUriPolicy.reference , EcucParamConfContainerDef.reference			
Attribute	Type	Mult.	Kind	Note
destination	EcucContainerDef	*	ref	All the possible parameter containers for the reference are specified. Stereotypes: atpUriDef

Table A.473: EcucChoiceReferenceDef

Class	EcucCommonAttributes (abstract)			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Attributes used by Configuration Parameters as well as References.			
Base	<i>ARObject, AtpDefinition, EcucDefinitionElement, Identifiable, MultilanguageReferrable, Referrable</i>			
Subclasses	EcucAbstractReferenceDef , EcucParameterDef			
Attribute	Type	Mult.	Kind	Note
multiplicity ConfigClass	EcucMultiplicityConfigurationClass	*	aggr	Specifies in which MultiplicityConfigurationClass this parameter or reference is available in a particular ConfigurationVariant. This aggregation is optional if the surrounding EcucModuleDef has the Category STANDARDIZED_MODULE_DEFINITION. If the category attribute of the EcucModuleDef is set to VENDOR_SPECIFIC_MODULE_DEFINITION, then this aggregation is mandatory. Tags: xml.name Plural=MULTIPLICITY-CONFIG-CLASSES
origin	String	0..1	attr	String specifying if this configuration parameter is an AUTOSAR standardized configuration parameter or if the parameter is hardware- or vendor-specific.
postBuildVariant Multiplicity	Boolean	0..1	attr	Indicates if a parameter or a reference may have different number of instances in different post-build variants (previously known as post-build selectable configuration sets). TRUE means yes, FALSE means no.
postBuildVariant Value	Boolean	0..1	attr	Indicates if a parameter or a reference may have different value in different post-build variants (previously known as post-build selectable configuration sets). TRUE means yes, FALSE means no.
requiresIndex	Boolean	0..1	attr	Used to define whether the value element for this definition shall be provided with an index.
valueConfig Class	EcucValueConfigurationClass	*	aggr	Specifies in which ValueConfigurationClass this parameter or reference is available in a particular ConfigurationVariant. This aggregation is optional if the surrounding EcucModuleDef has the Category STANDARDIZED_MODULE_DEFINITION. If the category attribute of the EcucModuleDef is set to VENDOR_SPECIFIC_MODULE_DEFINITION, then this aggregation is mandatory. Tags: xml.namePlural=VALUE-CONFIG-CLASSES

Table A.474: EcucCommonAttributes

Class	«atpMixedString» EcucConditionFormula			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	This formula shall yield a boolean expression depending on ecuc queries. Note that the EcucCondition Formula is a mixed string. Therefore, the properties have the upper multiplicity 1.			
Base	ARObject, FormulaExpression			
Aggregated by	EcucConditionSpecification.conditionFormula, EcucValidationCondition.validationFormula			
Attribute	Type	Mult.	Kind	Note
ecucQuery	EcucQuery	0..1	ref	The EcucQuery serves as a argument for the formula.
ecucQuery String	EcucQuery	0..1	ref	This indicates that the referenced query shall return a string.

Table A.475: EcucConditionFormula

Enumeration	EcucConfigurationClassEnum
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate
Note	Possible configuration classes for the AUTOSAR configuration parameters.
Aggregated by	EcucAbstractConfigurationClass.configClass
Literal	Description
Link	Link Time: parts of configuration are delivered from another object code file Tags: atp.EnumerationLiteralIndex=0
PostBuild	PostBuildTime: after compilation a configuration parameter can be changed. Tags: atp.EnumerationLiteralIndex=1
PreCompile	PreCompile Time: after compilation a configuration parameter can not be changed any more. Tags: atp.EnumerationLiteralIndex=2
Published Information	PublishedInformation is used to specify the fact that certain information is fixed even before the pre-compile stage. Tags: atp.EnumerationLiteralIndex=3

Table A.476: EcucConfigurationClassEnum

Enumeration	EcucConfigurationVariantEnum
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate
Note	Specifies the possible Configuration Variants used for AUTOSAR BSW Modules.
Aggregated by	EcucAbstractConfigurationClass.configVariant , EcucModuleConfigurationValues.implementationConfigVariant , EcucModuleDef.supportedConfigVariant
Literal	Description
Preconfigured Configuration	Preconfigured (i.e. fixed) configuration which cannot be changed. Tags: atp.EnumerationLiteralIndex=0
Recommended Configuration	Recommended configuration for a module. Tags: atp.EnumerationLiteralIndex=1
VariantLinkTime	Specifies that the BSW Module implementation may use PreCompileTime and LinkTime configuration parameters. Tags: atp.EnumerationLiteralIndex=2
VariantPostBuild	Specifies that the BSW Module implementation may use PreCompileTime, LinkTime and PostBuild configuration parameters. Tags: atp.EnumerationLiteralIndex=3
VariantPreCompile	Specifies that the BSW Module implementation uses only PreCompileTime configuration parameters. Tags: atp.EnumerationLiteralIndex=6

Table A.477: EcucConfigurationVariantEnum

Class	EcucContainerDef (abstract)			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Base class used to gather common attributes of configuration container definitions.			
Base	ARObject, AtpDefinition, EcucDefinitionElement, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	EcucChoiceContainerDef, EcucParamConfContainerDef			
Aggregated by	EcucDestinationUriPolicy.container, EcucModuleDef.container, EcucParamConfContainerDef.sub Container			
Attribute	Type	Mult.	Kind	Note
destinationUri	EcucDestinationUriDef	*	ref	Several destinationUris can be defined for an Ecuc ContainerDef. With such destinationUris an Ecuc ContainerDef is applicable for several EcucUriReference Defs. Stereotypes: atpUriDef
multiplicity ConfigClass	EcucMultiplicity ConfigurationClass	*	aggr	Specifies which MultiplicityConfigurationClass this container is available for which ConfigurationVariant. This aggregation is optional if the surrounding EcucModuleDef has the Category STANDARDIZED_MODULE_DEFINITION. If the category attribute of the EcucModule Def is set to VENDOR_SPECIFIC_MODULE_DEFINITION and if the upperMultiplicity is greater than the lowerMultiplicity then this aggregation is mandatory. Tags: xml.name Plural=MULTIPLICITY-CONFIG-CLASSES
origin	String	0..1	attr	This attribute specifies whether this configuration container is an AUTOSAR standardized container or whether it is vendor-specific.
postBuildVariant Multiplicity	Boolean	0..1	attr	Indicates if a container may have different number of instances in different post-build variants (previously known as post-build selectable configuration sets). TRUE means yes, FALSE means no.
requiresIndex	Boolean	0..1	attr	Used to define whether the value element for this definition shall be provided with an index.

Table A.478: EcucContainerDef

Class	EcucContainerValue			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	Represents a Container definition in the ECU Configuration Description.			
Base	ARObject, EcucIndexableValue, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	EcucContainerValue.subContainer, EcucModuleConfigurationValues.container			
Attribute	Type	Mult.	Kind	Note
definition	EcucContainerDef	0..1	ref	Reference to the definition of this Container in the ECU Configuration Parameter Definition. Tags: xml.sequenceOffset=-10
parameterValue	EcucParameterValue	*	aggr	Aggregates all ECU Configuration Values within this Container. atpVariation: [RS_ECUC_00079] Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=parameterValue, parameterValue.variation Point.shortLabel vh.latestBindingTime=postBuild





Class	EcucContainerValue			
referenceValue	EcucAbstractReferenceValue	*	aggr	Aggregates all References with this container. atpVariation: [RS_ECUC_00079] Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=referenceValue, referenceValue.variationPoint.shortLabel vh.latestBindingTime=postBuild
subContainer	EcucContainerValue	*	aggr	Aggregates all sub-containers within this container. atpVariation: [RS_ECUC_00078] Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=subContainer.shortName, subContainer.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.479: EcucContainerValue

Class	EcucDefinitionElement (abstract)			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Common class used to express the commonalities of configuration parameters, references and containers. If not stated otherwise the default multiplicity is exactly one mandatory occurrence of the specified element.			
Base	ARObject , AtpDefinition , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	EcucCommonAttributes , EcucContainerDef , EcucModuleDef			
Attribute	Type	Mult.	Kind	Note
ecucCond	EcucConditionSpecification	0..1	aggr	If it evaluates to true the Ecu Parameter definition shall be processed as specified. Otherwise the parameter definition shall be ignored. Tags: xml.sequenceOffset=100
ecucValidationCond	EcucValidationCondition	*	aggr	Collection of validation conditions which all need to evaluate to true in order to indicate a valid validation condition of the EcucDefinitionElement.
lowerMultiplicity	PositiveInteger	0..1	attr	The lower multiplicity of the specified element. 0: optional 1: at least one occurrence n: at least n occurrences atpVariation: [RS_ECUC_00082] Stereotypes: atpVariation Tags: vh.latestBindingTime=codeGenerationTime xml.sequenceOffset=110
relatedTraceItem	Traceable	0..1	ref	This contains a sloppy reference to the Autosar compatible identifier of the element (EcuId). Stereotypes: atpUriDef Tags: xml.sequenceOffset=-10
scope	EcucScopeEnum	0..1	attr	Specifies the scope of this configuration element. Tags: xml.sequenceOffset=150





Class	EcucDefinitionElement (abstract)			
upperMultiplicity	PositiveInteger	0..1	attr	The upper multiplicity of the specified element. 0: no occurrence (used for VSMD) 1: at most one occurrence m: at most m occurrences If upperMultiplicity is set than upperMultiplicityInfinite shall not be used. atpVariation: [RS_ECUC_00082] Stereotypes: atpVariation Tags: vh.latestBindingTime=codeGenerationTime xml.sequenceOffset=120
upperMultiplicityInfinite	Boolean	0..1	attr	To express an infinite number of occurrences of this element this attribute has to be set to true. If upperMultiplicityInfinite is set than upperMultiplicity shall not be used. atpVariation: [RS_ECUC_00082] Stereotypes: atpVariation Tags: vh.latestBindingTime=codeGenerationTime xml.sequenceOffset=130

Table A.480: EcucDefinitionElement

Class	EcucDestinationUriDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Description of an EcucDestinationUriDef that is used as target of EcucUriReferenceDefs.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	EcucDestinationUriDefSet.destinationUriDef			
Attribute	Type	Mult.	Kind	Note
destinationUriPolicy	EcucDestinationUriPolicy	0..1	aggr	Description of the targeted EcucContainerDef.

Table A.481: EcucDestinationUriDef

Class	EcucDestinationUriDefSet			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	This class represents a list of EcucDestinationUriDefs. Tags: atp.recommendedPackage=EcucDestinationUriDefSets			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
destinationUriDef	EcucDestinationUriDef	*	aggr	This is one particular EcucDestinationUriDef.

Table A.482: EcucDestinationUriDefSet

Enumeration	EcucDestinationUriNestingContractEnum
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate
Note	EcucDestinationUriNestingContractEnum is used to determine what is qualified by the EcucDestinationUriPolicy.
Aggregated by	EcucDestinationUriPolicy.destinationUriNestingContract
Literal	Description
leafOfTargetContainer	EcucDestinationUriPolicy describes elements (subContainers, Parameters, References) that are directly owned by the target container. Tags: atp.EnumerationLiteralIndex=0
targetContainer	EcucDestinationUriPolicy describes the target container of EcucUriReferenceDef. Tags: atp.EnumerationLiteralIndex=1
vertexOfTargetContainer	EcucDestinationUriPolicy describes elements (subContainers, Parameters, References) of the target container which can be defined in arbitrary nested subContainer structure. Tags: atp.EnumerationLiteralIndex=2

Table A.483: EcucDestinationUriNestingContractEnum

Class	EcucDestinationUriPolicy			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	The EcucDestinationUriPolicy describes the EcucContainerDef that will be targeted by EcucUriReference Defs. The type of the description is dependent of the destinationUriNestingContract attribute.			
Base	<i>ARObject</i>			
Aggregated by	EcucDestinationUriDef.destinationUriPolicy			
Attribute	Type	Mult.	Kind	Note
container	EcucContainerDef	*	aggr	Description of the targetContainer in case that the destinationUriNestingPolicy is set to targetContainer. In all other cases the subContainers of the target container are defined here.
destinationUriNestingContract	EcucDestinationUriNestingContractEnum	0..1	attr	This attribute defines how the referenced target EcucContainerDef is described.
parameter	EcucParameterDef	*	aggr	Description of parameters that are contained in the target container.
reference	EcucAbstractReferenceDef	*	aggr	Description of references that are contained in the target container.

Table A.484: EcucDestinationUriPolicy

Class	EcucEnumerationLiteralDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Configuration parameter type for enumeration literals definition.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	EcucEnumerationParamDef.literal			
Attribute	Type	Mult.	Kind	Note
ecucCond	EcucConditionSpecification	0..1	aggr	If it evaluates to true the literal definition shall be processed as specified. Otherwise the literal definition shall be ignored.
origin	String	0..1	attr	String specifying if this literal is an AUTOSAR standardized literal or if the literal is vendor-specific.

Table A.485: EcucEnumerationLiteralDef

Class	EcucForeignReferenceDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Specify a reference to an XML description of an entity described in another AUTOSAR template.			
Base	<i>ARObject, AtpDefinition, EcucAbstractExternalReferenceDef, EcucAbstractReferenceDef, EcucCommonAttributes, EcucDefinitionElement, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	EcucDestinationUriPolicy.reference , EcucParamConfContainerDef.reference			
Attribute	Type	Mult.	Kind	Note
destinationType	String	0..1	attr	The type in the AUTOSAR Metamodel to which instance this reference is allowed to point to.

Table A.486: EcucForeignReferenceDef

Class	«atpVariation» EcucFunctionNameDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Configuration parameter type for Function Names like those used to specify callback functions.			
Base	<i>ARObject, AtpDefinition, EcucAbstractStringParamDef, EcucCommonAttributes, EcucDefinitionElement, EcucParameterDef, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	EcucDestinationUriPolicy.parameter , EcucParamConfContainerDef.parameter			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.487: EcucFunctionNameDef

Class	EcucInstanceReferenceDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Specify a reference to an XML description of an entity described in another AUTOSAR template using the INSTANCE REFERENCE semantics.			
Base	<i>ARObject, AtpDefinition, EcucAbstractExternalReferenceDef, EcucAbstractReferenceDef, EcucCommonAttributes, EcucDefinitionElement, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	EcucDestinationUriPolicy.reference , EcucParamConfContainerDef.reference			
Attribute	Type	Mult.	Kind	Note
destinationContext	String	0..1	attr	The context in the AUTOSAR Metamodel to which' this reference is allowed to point to.
destinationType	String	0..1	attr	The type in the AUTOSAR Metamodel to which' instance this reference is allowed to point to.

Table A.488: EcucInstanceReferenceDef

Class	EcucInstanceReferenceValue			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	InstanceReference representation in the ECU Configuration.			
Base	<i>ARObject, EcucAbstractReferenceValue, EcucIndexableValue</i>			
Aggregated by	EcucContainerValue.referenceValue			
Attribute	Type	Mult.	Kind	Note
value	AtpFeature	0..1	iref	InstanceReference representation in the ECU Configuration. InstanceRef implemented by: AnyInstanceRef

Table A.489: EcucInstanceReferenceValue

Class	EcucModuleConfigurationValues			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	<p>Head of the configuration of one Module. A Module can be a BSW module as well as the RTE and ECU Infrastructure.</p> <p>As part of the BSW module description, the EcucModuleConfigurationValues element has two different roles:</p> <p>The recommendedConfiguration contains parameter values recommended by the BSW module vendor.</p> <p>The preconfiguredConfiguration contains values for those parameters which are fixed by the implementation and cannot be changed.</p> <p>These two EcucModuleConfigurationValues are used when the base EcucModuleConfigurationValues (as part of the base ECU configuration) is created to fill parameters with initial values.</p> <p>Tags: atp.recommendedPackage=EcucModuleConfigurationValues</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
container	EcucContainerValue	*	aggr	<p>Aggregates all containers that belong to this module configuration.</p> <p>atpVariation: [RS_ECUC_00078]</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=container.shortName, container.variation Point.shortLabel vh.latestBindingTime=postBuild xml.sequenceOffset=10</p>
definition	EcucModuleDef	0..1	ref	<p>Reference to the definition of this EcucModule ConfigurationValues element. Typically, this is a vendor specific module configuration.</p> <p>Tags: xml.sequenceOffset=-10</p>
ecucDefEdition	RevisionLabelString	0..1	attr	<p>This is the version info of the ModuleDef ECUC Parameter definition to which this values conform to / are based on.</p> <p>For the Definition of ModuleDef ECUC Parameters the AdminData shall be used to express the semantic changes. The compatibility rules between the definition and value revision labels is up to the module's vendor.</p>
implementation ConfigVariant	EcucConfiguration VariantEnum	0..1	attr	<p>Specifies the kind of deliverable this EcucModule ConfigurationValues element provides. If this element is not used in a particular role (e.g. preconfigured Configuration or recommendedConfiguration) then the value shall be one of VariantPreCompile, VariantLink Time, VariantPostBuild.</p>
module Description	BswImplementation	0..1	ref	<p>Referencing the BSW module description, which this EcucModuleConfigurationValues element is configuring. This is optional because the EcucModuleConfiguration Values element is also used to configure the ECU infrastructure (memory map) or Application SW-Cs. However in case the EcucModuleConfigurationValues are used to configure the module, the reference is mandatory in order to fetch module specific "common" published information.</p>
postBuildVariant Used	Boolean	0..1	attr	<p>Indicates whether a module implementation has or plans to have (i.e., introduced at link or post-build time) new post-build variation points. TRUE means yes, FALSE means no. If the attribute is not defined, FALSE semantics shall be assumed.</p>

Table A.490: EcucModuleConfigurationValues

Class	EcucModuleDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Used as the top-level element for configuration definition for Software Modules, including BSW and RTE as well as ECU Infrastructure. Tags: atp.recommendedPackage=EcucModuleDefs			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpDefinition , CollectableElement , EcucDefinitionElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
apiServicePrefix	CIdentifier	0..1	attr	For modules where several instances of the VSMD can be defined the apiServicePrefix defines the API namespace of the derived instances, e.g. Cdd, Xfrm (ComXf, SomelpXf, E2EXf).
container	EcucContainerDef	*	aggr	Aggregates the top-level container definitions of this specific module definition. Stereotypes: atpSplitable Tags: atp.Splitkey=container.shortName xml.sequenceOffset=11
postBuildVariant Support	Boolean	0..1	attr	Indicates if a module supports different post-build variants (previously known as post-build selectable configuration sets). TRUE means yes, FALSE means no.
refinedModule Def	EcucModuleDef	0..1	ref	Optional reference from the Vendor Specific Module Definition to the Standardized Module Definition it refines. In case this EcucModuleDef has the category STANDARDIZED_MODULE_DEFINITION this reference shall not be provided. In case this EcucModuleDef has the category VENDOR_SPECIFIC_MODULE_DEFINITION this reference is mandatory. Stereotypes: atpUriDef
supported ConfigVariant	EcucConfigurationVariantEnum	*	attr	Specifies which ConfigurationVariants are supported by this software module. This attribute is optional if the EcucModuleDef has the category STANDARDIZED_MODULE_DEFINITION. If the category attribute of the EcucModuleDef is set to VENDOR_SPECIFIC_MODULE_DEFINITION then this attribute is mandatory.

Table A.491: EcucModuleDef

Class	EcucMultiplicityConfigurationClass			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Specifies the MultiplicityConfigurationClass of a parameter/reference or a container for each ConfigurationVariant of the EcucModuleDef.			
Base	ARObject , EcucAbstractConfigurationClass			
Aggregated by	EcucCommonAttributes.multiplicityConfigClass , EcucContainerDef.multiplicityConfigClass			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.492: EcucMultiplicityConfigurationClass

Class	EcucNumericalParamValue			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	Holding the value which is subject to variant handling.			
Base	<i>ARObject</i> , <i>EcucIndexableValue</i> , <i>EcucParameterValue</i>			
Aggregated by	<i>EcucContainerValue.parameterValue</i>			
Attribute	Type	Mult.	Kind	Note
value	Numerical	0..1	attr	Value which is subject to variant handling. atpVariation: [RS_ECUC_00080] Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.493: EcucNumericalParamValue

Class	EcucParamConfContainerDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Used to define configuration containers that can hierarchically contain other containers and/or parameter definitions.			
Base	<i>ARObject</i> , <i>AtpDefinition</i> , <i>EcucContainerDef</i> , <i>EcucDefinitionElement</i> , <i>Identifiable</i> , <i>Multilanguage Referrable</i> , <i>Referrable</i>			
Aggregated by	<i>EcucChoiceContainerDef.choice</i> , <i>EcucDestinationUriPolicy.container</i> , <i>EcucModuleDef.container</i> , <i>EcucParamConfContainerDef.subContainer</i>			
Attribute	Type	Mult.	Kind	Note
parameter	<i>EcucParameterDef</i>	*	aggr	The parameters defined within the EcucParamConf ContainerDef. Stereotypes: atpSplittable Tags: atp.Splitkey=parameter.shortName
reference	<i>EcucAbstractReference Def</i>	*	aggr	The references defined within the EcucParamConf ContainerDef. Stereotypes: atpSplittable Tags: atp.Splitkey=reference.shortName
subContainer	<i>EcucContainerDef</i>	*	aggr	The containers defined within the EcucParamConf ContainerDef. Stereotypes: atpSplittable Tags: atp.Splitkey=subContainer.shortName

Table A.494: EcucParamConfContainerDef

Class	EcucParameterDef (abstract)			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Abstract class used to define the similarities of all ECU Configuration Parameter types defined as subclasses.			
Base	<i>ARObject</i> , <i>AtpDefinition</i> , <i>EcucCommonAttributes</i> , <i>EcucDefinitionElement</i> , <i>Identifiable</i> , <i>Multilanguage Referrable</i> , <i>Referrable</i>			
Subclasses	<i>EcucAbstractStringParamDef</i> , <i>EcucAddInfoParamDef</i> , <i>EcucBooleanParamDef</i> , <i>EcucEnumerationParam Def</i> , <i>EcucFloatParamDef</i> , <i>EcucIntegerParamDef</i>			
Aggregated by	<i>EcucDestinationUriPolicy.parameter</i> , <i>EcucParamConfContainerDef.parameter</i>			
Attribute	Type	Mult.	Kind	Note
derivation	EcucDerivation Specification	0..1	aggr	A derivation of a Configuration Parameter value can be specified by an informal Calculation Formula or by a formal language that can be used to specify the computational rules.





Class		<i>EcucParameterDef</i> (abstract)		
symbolicName Value	Boolean	0..1	attr	Specifies that this parameter's value is used, together with the aggregating container, to derive a symbolic name definition. See chapter "Representation of Symbolic Names" in Ecuc specification for more details.
withAuto	Boolean	0..1	attr	<p>Specifies whether it shall be allowed on the value side to specify this parameter value as "AUTO".</p> <p>If withAuto is "true" it shall be possible to set the "isAuto Value" attribute of the respective parameter to "true". This means that the actual value will not be considered during ECU Configuration but will be (re-)calculated by the code generator and stored in the value attribute afterwards. These implicit updated values might require a re-generation of other modules which reference these values.</p> <p>If withAuto is "false" it shall not be possible to set the "is AutoValue" attribute of the respective parameter to "true".</p> <p>If withAuto is not present the default is "false".</p>

Table A.495: EcucParameterDef

Class		<i>EcucParameterValue</i> (abstract)		
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	Common class to all types of configuration values.			
Base	<i>ARObject</i> , <i>EcucIndexableValue</i>			
Subclasses	EcucAddInfoParamValue , EcucNumericalParamValue , EcucTextualParamValue			
Aggregated by	EcucContainerValue .parameterValue			
Attribute	Type	Mult.	Kind	Note
annotation	Annotation	*	aggr	<p>Possibility to provide additional notes while defining the ECU Configuration Parameter Values. These are not intended as documentation but are mere design notes.</p> <p>Tags: xml.sequenceOffset=10</p>
definition	EcucParameterDef	0..1	ref	<p>Reference to the definition of this EcucParameterValue subclasses in the ECU Configuration Parameter Definition.</p> <p>Tags: xml.sequenceOffset=-10</p>
isAutoValue	Boolean	0..1	attr	<p>If withAuto is set to "true" for this parameter definition the isAutoValue can be set to "true". If isAutoValue is set to "true" the actual value will not be considered during ECU Configuration but will be (re-)calculated by the code generator and stored in the value attribute afterwards. These implicit updated values might require a re-generation of other modules which reference these values.</p> <p>If isAutoValue is not present the default is "false".</p> <p>Tags: xml.sequenceOffset=20</p>

Table A.496: EcucParameterValue

Class	EcucQuery			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Defines a query to the ECUC Description.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	EcucConditionSpecification.ecucQuery, EcucDerivationSpecification.ecucQuery, EcucValidationCondition.ecucQuery			
Attribute	Type	Mult.	Kind	Note
ecucQuery Expression	EcucQueryExpression	0..1	aggr	This is the EcucQuery used in the calculation formula or the condition formula.

Table A.497: EcucQuery

Class	«atpMixedString» EcucQueryExpression			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Defines a query expression to the ECUC Description and output the result as an numerical value. Due to the "mixedString" nature of the formula there can be several EcucQueryExpressions used.			
Base	<i>ARObject</i>			
Aggregated by	EcucQuery.ecucQueryExpression			
Attribute	Type	Mult.	Kind	Note
configElement DefGlobal	EcucDefinitionElement	0..1	ref	The EcucQueryExpression points to an EcucDefinition Element that is used to find an element in the Ecuc Description. In order to find the right element in the Ecuc Description a search is necessary. If the complete Ecuc Description needs to be searched this global reference shall be used. Due to the "mixedString" nature of the EcucQueryExpression several references to Ecuc DefinitionElements can be used in one EcucQuery Expression. Stereotypes: atpUriDef
configElement DefLocal	EcucDefinitionElement	0..1	ref	The EcucQueryExpression points to an EcucDefinition Element that is used to find an element in the Ecuc Description. In order to find the right element in the Ecuc Description a search is necessary. If the search is executed inside of the same module that contains the EcucQuery this local reference shall be used. Due to the "mixedString" nature of the EcucQueryExpression several references to EcucDefintionElements can be used in one EcucQueryExpression. Stereotypes: atpUriDef

Table A.498: EcucQueryExpression

Class	EcucReferenceDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Specify references within the ECU Configuration Description between parameter containers.			
Base	<i>ARObject</i> , <i>AtpDefinition</i> , EcucAbstractInternalReferenceDef , EcucAbstractReferenceDef , EcucCommonAttributes , EcucDefinitionElement , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	EcucDestinationUriPolicy.reference , EcucParamConfContainerDef.reference			
Attribute	Type	Mult.	Kind	Note
destination	EcucContainerDef	0..1	ref	Exactly one reference to a parameter container is allowed as destination. Stereotypes: atpUriDef

Table A.499: EcucReferenceDef

Class	EcucReferenceValue			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	Used to represent a configuration value that has a parameter definition of type EcucAbstractReferenceDef (used for all of its specializations excluding EcucInstanceReferenceDef).			
Base	ARObject, EcucAbstractReferenceValue , EcucIndexableValue			
Aggregated by	EcucContainerValue.referenceValue			
Attribute	Type	Mult.	Kind	Note
value	Referrable	0..1	ref	Specifies the destination of the reference.

Table A.500: EcucReferenceValue

Class	EcucTextualParamValue			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	Holding a value which is not subject to variation.			
Base	ARObject, EcucIndexableValue , EcucParameterValue			
Aggregated by	EcucContainerValue.parameterValue			
Attribute	Type	Mult.	Kind	Note
value	VerbatimString	0..1	attr	Value of the parameter, not subject to variant handling.

Table A.501: EcucTextualParamValue

Class	EcucUriReferenceDef			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Definition of reference with a destination that is specified via a destinationUri. With such a reference it is possible to define a reference to a EcucContainerDef in a different module independent from the concrete definition of the target container.			
Base	ARObject, AtpDefinition , EcucAbstractInternalReferenceDef , EcucAbstractReferenceDef , EcucCommonAttributes , EcucDefinitionElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EcucDestinationUriPolicy.reference , EcucParamConfContainerDef.reference			
Attribute	Type	Mult.	Kind	Note
destinationUri	EcucDestinationUriDef	0..1	ref	Any EcucContainerDef with a destinationUri that is identical to the destinationUri that is referenced here defines a valid target. Stereotypes: atpUriDef

Table A.502: EcucUriReferenceDef

Class	EcucValidationCondition			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Validation condition to perform a formula calculation based on EcucQueries.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EcucDefinitionElement.ecucValidationCond			
Attribute	Type	Mult.	Kind	Note
ecucQuery	EcucQuery	*	aggr	Query to the ECU Configuration Description.
validation Formula	EcucConditionFormula	0..1	aggr	Definition of the formula used to define validation condition.

Table A.503: EcucValidationCondition

Class	EcucValueCollection			
Package	M2::AUTOSARTemplates::ECUCDescriptionTemplate			
Note	This represents the anchor point of the ECU configuration description. Tags: atp.recommendedPackage=EcucValueCollections			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
ecucValue	EcucModuleConfigurationValues	*	ref	References to the configuration of individual software modules that are present on this ECU. atpVariation: [RS_ECUC_00079] Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=ecucValue.ecucModuleConfigurationValues, ecucValue.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
ecuExtract	System	0..1	ref	Represents the extract of the System Configuration that is relevant for the ECU configured with that ECU Configuration Description.

Table A.504: EcucValueCollection

Class	EcucValueConfigurationClass			
Package	M2::AUTOSARTemplates::ECUCParameterDefTemplate			
Note	Specifies the ValueConfigurationClass of a parameter/reference for each ConfigurationVariant of the EcucModuleDef.			
Base	ARObject, EcucAbstractConfigurationClass			
Aggregated by	EcucCommonAttributes.valueConfigClass			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.505: EcucValueConfigurationClass

Class	EndToEndDescription			
Package	M2::AUTOSARTemplates::SWComponentTemplate::EndToEndProtection			
Note	This meta-class contains information about end-to-end protection. The set of applicable attributes depends on the actual value of the category attribute of EndToEndProtection. Tags: atp.Status=obsolete			
Base	ARObject			
Aggregated by	EndToEndProtection.endToEndProfile			
Attribute	Type	Mult.	Kind	Note
category	NameToken	0..1	attr	The category represents the identification of the concrete E2E profile. The applicable values are specified in a semantic constraint and determine the applicable attributes of EndToEndDescription. Tags: atp.Status=obsolete xml.sequenceOffset=-100





Class	EndToEndDescription			
counterOffset	PositiveInteger	0..1	attr	<p>Bit offset of Counter from the beginning of the Array representation of the Signal Group/VariableDataPrototype (MSB order, bit numbering: bit 0 is the least important). The offset shall be a multiplicity of 4 and it should be 8 whenever possible. For example, offset 8 means that the counter will take the low nibble of the byte 1, i.e. bits 8 .. 11. If counterOffset is not present the value is defined by the selected profile.</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-50</p>
crcOffset	PositiveInteger	0..1	attr	<p>Bit offset of CRC from the beginning of the Array representation of the Signal Group/VariableDataPrototype (MSB order, bit numbering: bit 0 is the least important). The offset shall be a multiplicity of 8 and it should be 0 whenever possible. For example, offset 8 means that the CRC will take the byte 1, i.e. bits 8..15. If crcOffset is not present the value is defined by the selected profile.</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-60</p>
dataId (ordered)	PositiveInteger	*	attr	<p>This represents a unique numerical identifier.</p> <p>Note: ID is used for protection against masquerading. The details concerning the maximum number of values (this information is specific for each E2E profile) applicable for this attribute are controlled by a semantic constraint that depends on the category of the EndToEnd Protection.</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-90</p>
dataIdMode	PositiveInteger	0..1	attr	<p>There are three inclusion modes how the implicit two-byte Data ID is included in the one-byte CRC:</p> <ul style="list-style-type: none"> • dataIdMode = 0: Two bytes are included in the CRC (double ID configuration) This is used in variant 1A. • dataIdMode = 1: One of the two bytes byte is included, alternating high and low byte, depending on parity of the counter (alternating ID configuration). For even counter low byte is included; For odd counters the high byte is included. This is used in variant 1B. • dataIdMode = 2: Only low byte is included, high byte is never used. This is applicable if the IDs in a particular system are 8 bits. • dataIdMode = 3: The low byte is included in the implicit CRC calculation, the low nibble of the high byte is transmitted along with the data (i.e. it is explicitly included), the high nibble of the high byte is not used. This is applicable for the IDs up to 12 bits. <p>Tags: atp.Status=obsolete xml.sequenceOffset=-85</p>
dataIdNibble Offset	PositiveInteger	0..1	attr	<p>Bit offset of the low nibble of the high byte of Data ID. The applicability of this attribute is controlled by [constr_1261].</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-25</p>





Class	EndToEndDescription			
dataLength	PositiveInteger	0..1	attr	<p>This attribute represents the length of the Array representation of the Signal Group/VariableDataPrototype including CRC and Counter in bits.</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-80</p>
maxDeltaCounterInit	PositiveInteger	0..1	attr	<p>Initial maximum allowed gap between two counter values of two consecutively received valid Data, i.e. how many subsequent lost data is accepted. For example, if the receiver gets Data with counter 1 and MaxDeltaCounter Init is 1, then at the next reception the receiver can accept Counters with values 2 and 3, but not 4.</p> <p>Note that if the receiver does not receive new Data at a consecutive read, then the receiver increments the tolerance by 1.</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-70</p>
maxNoNewOrRepeatedData	PositiveInteger	0..1	attr	<p>The maximum amount of missing or repeated Data which the receiver does not expect to exceed under normal communication conditions.</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-40</p>
syncCounterInit	PositiveInteger	0..1	attr	<p>Number of Data required for validating the consistency of the counter that shall be received with a valid counter (i.e. counter within the allowed lock-in range) after the detection of an unexpected behavior of a received counter.</p> <p>Tags: atp.Status=obsolete xml.sequenceOffset=-30</p>

Table A.506: EndToEndDescription

Enumeration	EndToEndProfileBehaviorEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer
Note	Behavior of the check functionality
Aggregated by	EndToEndTransformationDescription.profileBehavior
Literal	Description
PRE_R4_2	<p>Check has the legacy behavior, before AUTOSAR Release 4.2.</p> <p>Tags: atp.EnumerationLiteralIndex=0 xml.name=PRE--R-4--2</p>
R4_2	<p>Check behaves like new P4/P5/P6 profiles introduced in AUTOSAR Release 4.2.</p> <p>Tags: atp.EnumerationLiteralIndex=1 xml.name=R-4--2</p>

Table A.507: EndToEndProfileBehaviorEnum

Class	EndToEndProtection			
Package	M2::AUTOSARTemplates::SWComponentTemplate::EndToEndProtection			
Note	This meta-class represents the ability to describe a particular end to end protection. Tags: atp.Status=obsolete			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EndToEndProtectionSet.endToEndProtection			
Attribute	Type	Mult.	Kind	Note
endToEndProfile	EndToEndDescription	0..1	aggr	This represents the particular EndToEndDescription. Stereotypes: atpSplitable Tags: atp.Splitkey=endToEndProfile atp.Status=obsolete
endToEndProtectionISignalPdu	EndToEndProtectionISignalPdu	*	aggr	Defines to which ISignalPdu - ISignalGroup pair this EndToEndProtection shall apply. In case several ISignalGroups are used to transport the data (e.g. fan-out in the RTE) there may exist several EndToEndProtectionISignalPdu definitions. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=endToEndProtectionISignalPdu, endToEndProtectionISignalPdu.variationPoint.shortLabel atp.Status=obsolete vh.latestBindingTime=preCompileTime
endToEndProtectionVariablePrototype	EndToEndProtectionVariablePrototype	*	aggr	Defines to which VariableDataPrototypes in the roles of one sender and one or more receivers this EndToEndProtection applies. It shall be possible to aggregate several EndToEndProtectionVariablePrototype in case additional hierarchical decompositions are introduced subsequently. In this case one particular PortPrototype is split into multiple PortPrototypes and connectors, all representing the same data entity. Caveat: The E2E wrapper approach involves technologies that are not subjected to the AUTOSAR standard and is superseded by the superior E2E transformer approach (which is fully standardized by AUTOSAR). Hence, new projects (without legacy constraints due to carry-over parts) shall use the fully standardized E2E transformer approach. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=endToEndProtectionVariablePrototype.shortLabel, endToEndProtectionVariablePrototype.variationPoint.shortLabel atp.Status=obsolete vh.latestBindingTime=preCompileTime

Table A.508: EndToEndProtection

Class	EndToEndProtectionISignalIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::EndToEndProtection			
Note	<p>It is possible to protect the inter-ECU data exchange of safety-related ISignalGroups at the level of COM IPdus using protection mechanisms provided by E2E Library. For each ISignalGroup to be protected, a separate EndToEndProtectionISignalIPdu element shall be created within the EndToEndProtectionSet.</p> <p>The EndToEndProtectionISignalIPdu element refers to the ISignalGroup that is to be protected and to the ISignalIPdu that transmits the protected ISignalGroup. The information how the referenced ISignalGroup shall be protected (through which E2E Profile and with which E2E settings) is defined in the EndToEndDescription element.</p> <p>Tags: atp.Status=obsolete</p>			
Base	ARObject			
Aggregated by	EndToEndProtection.endToEndProtectionISignalIPdu			
Attribute	Type	Mult.	Kind	Note
dataOffset	Integer	0..1	attr	<p>This attribute defines the beginning offset (in bits) of the Array representation of the Signal Group (including CRC, counter and application signal group) in the IPdu. This attribute is mandatory and the dataOffset shall always be defined.</p> <p>Tags: atp.Status=obsolete</p>
iSignalGroup	ISignalGroup	0..1	ref	<p>Reference to the ISignalGroup that is to be protected.</p> <p>Tags: atp.Status=obsolete</p>
iSignalIPdu	ISignalIPdu	0..1	ref	<p>Reference to the ISignalIPdu that transmits the protected ISignalGroup.</p> <p>Tags: atp.Status=obsolete</p>

Table A.509: EndToEndProtectionISignalIPdu

Class	EndToEndProtectionVariablePrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::EndToEndProtection			
Note	<p>It is possible to protect the data exchanged between software components. For this purpose, for each communication to be protected, the user defines a separate EndToEndProtection (specifying a set of protection settings) and refers to a variableDataPrototype in the role of sender and to one or many variableDataPrototypes in the role of receiver. For details, see EndToEnd Library.</p> <p>Caveat: The E2E wrapper approach involves technologies that are not subjected to the AUTOSAR standard and is superseded by the superior E2E transformer approach (which is fully standardized by AUTOSAR). Hence, new projects (without legacy constraints due to carry-over parts) shall use the fully standardized E2E transformer approach.</p> <p>Tags: atp.Status=obsolete</p>			
Base	ARObject			
Aggregated by	EndToEndProtection.endToEndProtectionVariablePrototype			
Attribute	Type	Mult.	Kind	Note
receiver	VariableDataPrototype	*	iref	<p>This represents the receiver. Note that 1:n communication is supported for this use case.</p> <p>Tags: atp.Status=obsolete InstanceRef implemented by: VariableDataPrototypeInSystemInstanceRef</p>
sender	VariableDataPrototype	0..1	iref	<p>This represents the sender.</p> <p>Can be optional if an ecu extract is provided and the sender is part of the extract.</p> <p>Tags: atp.Status=obsolete InstanceRef implemented by: VariableDataPrototypeInSystemInstanceRef</p>





Class	EndToEndProtectionVariablePrototype			
shortLabel	Identifier	0..1	attr	This serves as part of the split key in case of more than one EndToEndProtectionVariablePrototype is aggregated in the bound model. Stereotypes: atpIdentityContributor Tags: atp.Status=obsolete

Table A.510: EndToEndProtectionVariablePrototype

Class	EndToEndTransformationComSpecProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	The class EndToEndTransformationComSpecProps specifies port specific configuration properties for EndToEnd transformer attributes.			
Base	<i>ARObject, Describable, TransformationComSpecProps</i>			
Aggregated by	ClientComSpec.transformationComSpecProps , ReceiverComSpec.transformationComSpecProps , ServerComSpec.transformationComSpecProps			
Attribute	Type	Mult.	Kind	Note
clearFromValidToInvalid	Boolean	0..1	attr	Clear monitoring window on transition from state Valid to state Invalid.
disableEndToEndCheck	Boolean	0..1	attr	Disables/Enables the E2E check. The E2Eheader is removed from the payload independent from the setting of this attribute.
disableEndToEndStateMachine	Boolean	0..1	attr	Disables the E2EStateMachine (only E2E check functionality is performed)
e2eProfileCompatibilityProps	E2EProfileCompatibilityProps	0..1	ref	Reference to additional settings for the E2E state machine.
maxDeltaCounter	PositiveInteger	0..1	attr	Maximum allowed difference between two counter values of two consecutively received valid messages. For example, if the receiver gets data with counter 1 and MaxDeltaCounter is 3, then at the next reception the receiver can accept Counters with values 2, 3 or 4.
maxErrorStateInit	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_INIT. The minimum value is 0.
maxErrorStateInvalid	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_INVALID. The minimum value is 0.
maxErrorStateValid	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_VALID. The minimum value is 0.
maxNoNewOrRepeatedData	PositiveInteger	0..1	attr	EndToEndTransformationDescription holds these attributes which are profile specific and have the same value for all E2E transformers.
minOkStateInit	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_INIT. The minimum value is 1.





Class	EndToEndTransformationComSpecProps			
minOkState Invalid	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_INVALID. The minimum value is 1.
minOkState Valid	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_VALID. The minimum value is 1.
syncCounterInit	PositiveInteger	0..1	attr	EndToEndTransformationDescription holds these attributes which are profile specific and have the same value for all E2E transformers.
windowSizeInit	PositiveInteger	0..1	attr	Size of the monitoring window of state Init for the E2E state machine.
windowSize Invalid	PositiveInteger	0..1	attr	Size of the monitoring window of state Invalid for the E2E state machine.
windowSize Valid	PositiveInteger	0..1	attr	Size of the monitoring window of state Valid for the E2E state machine.

Table A.511: EndToEndTransformationComSpecProps

Class	EndToEndTransformationDescription			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	EndToEndTransformationDescription holds these attributes which are profile specific and have the same value for all E2E transformers.			
Base	<i>ARObject</i> , <i>Describable</i> , TransformationDescription			
Aggregated by	TransformationTechnology.transformationDescription			
Attribute	Type	Mult.	Kind	Note
clearFromValid ToInvalid	Boolean	0..1	attr	Clear monitoring window on transition from state Valid to state Invalid.
counterOffset	PositiveInteger	0..1	attr	Offset of the counter in the Data[] array in bits.
crcOffset	PositiveInteger	0..1	attr	Offset of the CRC in the Data[] array in bits.
dataIdMode	DataIdModeEnum	0..1	attr	This attribute describes the inclusion mode that is used to include the implicit two-byte Data ID in the one-byte CRC.
dataIdNibble Offset	PositiveInteger	0..1	attr	Offset of the Data ID nibble in the Data[] array in bits.
e2eProfile Compatibility Props	E2EProfileCompatibility Props	0..1	ref	Reference to additional settings for the E2E state machine.
maxDelta Counter	PositiveInteger	0..1	attr	Maximum allowed difference between two counter values of two consecutively received valid messages. For example, if the receiver gets data with counter 1 and Max DeltaCounter is 3, then at the next reception the receiver can accept Counters with values 2, 3 or 4.
maxErrorState Init	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_INIT.
maxErrorState Invalid	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_INVALID.
maxErrorState Valid	PositiveInteger	0..1	attr	Maximal number of checks in which ProfileStatus equal to E2E_P_ERROR was determined, within the last Window Size checks, for the state E2E_SM_VALID.





Class	EndToEndTransformationDescription			
maxNoNewOrRepeatedData	PositiveInteger	0..1	attr	The maximum allowed amount of consecutive failed counter checks.
minOkStateInit	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_INIT.
minOkStateInvalid	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_INVALID.
minOkStateValid	PositiveInteger	0..1	attr	Minimal number of checks in which ProfileStatus equal to E2E_P_OK was determined, within the last WindowSize checks, for the state E2E_SM_VALID.
offset	PositiveInteger	0..1	attr	Offset of the E2E header in the Data[] array in bits.
profileBehavior	EndToEndProfileBehaviorEnum	0..1	attr	Behavior of the check functionality
profileName	NameToken	0..1	attr	Definition of the E2E profile.
syncCounterInit	PositiveInteger	0..1	attr	Number of checks required for validating the consistency of the counter that shall be received with a valid counter (i.e. counter within the allowed lock-in range) after the detection of an unexpected behavior of a received counter.
upperHeaderBitsToShift	PositiveInteger	0..1	attr	<p>This attribute describes the number of upper-header bits to be shifted.</p> <p>value = 0 or not present: shift of upper header is NOT performed.</p> <p>value > 0: the E2E Transformer on the protect-side, takes the first upperHeaderBitsToShift bits from the upper buffer (e.g. SOME/IP header part generated by SOME/IP transformer) and shifts them towards the lower bytes and bits within the Data[] for the length of the E2E header (e.g. 12 bytes in case of E2E Profile 4). This means the shift distance is fixed - it depends on the E2E header size - what is configured here is the number of bits that are to be shifted. This option is defined because the Some/IP header generated by SOME/IP transformer shall be, due to compatibility between non-protected and E2E-protected communication, at the same position, which is before E2E header.</p>
windowSizeInit	PositiveInteger	0..1	attr	Size of the monitoring window of state Init for the E2E state machine.
windowSizeInvalid	PositiveInteger	0..1	attr	Size of the monitoring window of state Invalid for the E2E state machine.
windowSizeValid	PositiveInteger	0..1	attr	Size of the monitoring window of state Valid for the E2E state machine.

Table A.512: EndToEndTransformationDescription

Class	«atpVariation» EndToEndTransformationSignalProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	Holds all the ISignal specific attributes for the EndToEndTransformer.			
Base	<i>ARObject</i> , <i>Describable</i> , TransformationSignalProps			
Aggregated by	ISignal.transformationSignalProps , ISignalGroup.transformationSignalProps			
Attribute	Type	Mult.	Kind	Note





Class				
«atpVariation» EndToEndTransformationSignalProps				
dataId (ordered)	PositiveInteger	*	attr	This represents a unique numerical identifier. Note: ID is used for protection against masquerading. The details concerning the maximum number of values (this information is specific for each E2E profile) applicable for this attribute are controlled by a semantic constraint that depends on the category of the EndToEnd Protection.
dataLength	PositiveInteger	0..1	attr	Length of payload and E2E header in bits.
maxDataLength	PositiveInteger	0..1	attr	Maximum length of payload and E2E header in bits.
minDataLength	PositiveInteger	0..1	attr	Minimum length of payload and E2E header in bits.
sourceId	PositiveInteger	0..1	attr	This attribute represents a unique numerical identifier identifying the source of a certain transmission. In case of C/S communication, this ID uniquely identifies the client. Note: ID is used for protection against masquerading. The details concerning the maximum number of values (this information is specific for each E2E profile) applicable for this attribute are controlled by a semantic constraint that depends on the category of the EndToEnd Protection.

Table A.513: EndToEndTransformationSignalProps

Class	EngineeringObject (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::EngineeringObject			
Note	This class specifies an engineering object. Usually such an object is represented by a file artifact. The properties of engineering object are such that the artifact can be found by querying an ASAM catalog file. The engineering object is uniquely identified by domain+category+shortLabel+revisionLabel.			
Base	ARObject			
Subclasses	AutosarEngineeringObject, BuildEngineeringObject, Graphic			
Attribute	Type	Mult.	Kind	Note
category	NameToken	1	attr	This denotes the role of the engineering object in the development cycle. Categories are such as <ul style="list-style-type: none"> • SWSRC for source code • SWOBJ for object code • SWHDR for a C-header file Further roles need to be defined via Methodology. Tags: xml.sequenceOffset=20
domain	NameToken	0..1	attr	This denotes the domain in which the engineering object is stored. This allows to indicate various segments in the repository keeping the engineering objects. The domain may segregate companies, as well as automotive domains. Details need to be defined by the Methodology. Attribute is optional to support a default domain. Tags: xml.sequenceOffset=40
revisionLabel	RevisionLabelString	*	attr	This is a revision label denoting a particular version of the engineering object. Tags: xml.sequenceOffset=30





Class	EngineeringObject (abstract)			
shortLabel	NameToken	1	attr	This is the short name of the engineering object. Note that it is modeled as NameToken and not as Identifier since in ASAM-CC it is also a NameToken. Tags: xml.sequenceOffset=10

Table A.514: EngineeringObject

Class	EnumerationMappingTable			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling::AttributeValueVariationPoints			
Note	This class represents an attribute value variation point for Enumeration attributes. Note that this class might be used in the extended meta-model only. Tags: atp.recommendedPackage=EnumerationMappingTables			
Base	ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
entry	EnumerationMappingEntry	*	aggr	Key-value pair mapping enumeration values to unique integers. Tags: xml.roleElement=true xml.roleWrapperElement=true xml.typeElement=false xml.typeWrapperElement=false

Table A.515: EnumerationMappingTable

Class	ErrorTracerNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the need to report failures to the error tracer.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds, SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
tracedFailure	TracedFailure	*	aggr	list of traced failures Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=tracedFailure.shortName, tracedFailure.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.516: ErrorTracerNeeds

Class	EthGlobalTimeDomainProps			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::ETH			
Note	Enables the definition of Ethernet Global Time specific properties.			
Base	ARObject, AbstractGlobalTimeDomainProps			
Aggregated by	GlobalTimeDomain.globalTimeDomainProperty			
Attribute	Type	Mult.	Kind	Note
crcFlags	EthTSynCrcFlags	0..1	aggr	Defines the fields of the message which shall be taken into account for CRC calculation and verification.





Class	EthGlobalTimeDomainProps			
destination Physical Address	MacAddressString	0..1	attr	Defines the MAC multicast address the Ethernet time sync messages are communicated on.
fupDataDList (ordered)	PositiveInteger	0..16	attr	The DataIDList for FUP messages to calculate CRC.
managed CouplingPort	EthGlobalTimeManagedCouplingPort	*	aggr	Collection of CouplingPorts which are managed in the scope of this Ethernet GlobalTimeDomain.
message Compliance	EthGlobalTimeMessageFormatEnum	0..1	attr	Defines the compliance of the Ethernet time sync messages to specific standards.
vlanPriority	PositiveInteger	0..1	attr	Defines which VLAN priority shall be assigned to a time sync message in case the message is sent using a VLAN tag.

Table A.517: EthGlobalTimeDomainProps

Class	EthGlobalTimeManagedCouplingPort			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::ETH			
Note	Specifies a CouplingPort which is managed by an Ethernet Global Time Domain.			
Base	ARObject			
Aggregated by	EthGlobalTimeDomainProps.managedCouplingPort			
Attribute	Type	Mult.	Kind	Note
couplingPort	CouplingPort	0..1	ref	Defines which CouplingPort is managed by this EthGlobalTimeManagedCouplingPort.
globalTimePort Role	GlobalTimePortRoleEnum	0..1	attr	This attribute defines the port behavior.
globalTimeTx Period	TimeValue	0..1	attr	This attribute defines the TX period in seconds
pdelayLatency Threshold	TimeValue	0..1	attr	Threshold for calculated Pdelay. If a measured Pdelay exceeds pdelayLatencyThreshold, the measured Pdelay value is discarded.
pdelayRequest Period	TimeValue	0..1	attr	Defines the period for the pdelay request messages.
pdelayRespAnd RespFollowUp Timeout	TimeValue	0..1	attr	Timeout value for Pdelay_Resp and Pdelay_Resp_Follow_Up after a Pdelay_Req has been transmitted resp. a Pdelay_Resp has been received. A value of 0 or not defining this attribute deactivates this timeout observation.
pdelay Response Enabled	Boolean	0..1	attr	Defines whether PDELAY RESPONSE and PDELAY RESPONSE FOLLOW UP shall be sent on this Coupling Port.

Table A.518: EthGlobalTimeManagedCouplingPort

Class	«atpVariation» EthernetCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Ethernet-specific cluster attributes. Tags: atp.recommendedPackage=CommunicationClusters			
Base	ARElement, ARObject, CollectableElement, CommunicationCluster , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	«atpVariation» EthernetCluster			
couplingPort Connection	CouplingPort Connection	*	aggr	Specification of connections between CouplingElements and EcuInstances. Note: This atpSplittable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplittable; atpVariation Tags: vh.latestBindingTime=postBuild
couplingPort StartupActive Time	TimeValue	0..1	attr	The attribute specifies the time in second a coupling port is switched on to enable the host ECU (ECU that maintains an Ethernet switch) to listen to the network for potential network management requests.
couplingPort SwitchoffDelay	TimeValue	0..1	attr	Switch off delay for CouplingPorts in seconds. It denotes the delay of switching off couplingPorts after the request to switch off a couplingPort was issued. (e.g. switch off of Ethernet switch ports).
macMulticast Group	MacMulticastGroup	*	aggr	MacMulticastGroup that is defined for the Subnet (EthernetCluster).

Table A.519: EthernetCluster

Class	EthernetCommunicationConnector				
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology				
Note	Ethernet specific attributes to the CommunicationConnector.				
Base	<i>ARObject</i> , <i>CommunicationConnector</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>				
Aggregated by	EcuInstance.connector , MachineDesign.communicationConnector				
Attribute	Type	Mult.	Kind	Note	
ethIpProps	EthIpProps	0..1	ref	EcuInstance specific IP attributes.	
maximum Transmission Unit	PositiveInteger	0..1	attr	This attribute specifies the maximum transmission unit in bytes.	
neighborCache Size	PositiveInteger	0..1	attr	This attribute specifies the size of neighbor cache or ARP table in units of entries.	
pathMtu Enabled	Boolean	0..1	attr	If enabled the IPv4/IPv6 processes incoming ICMP "Packet Too Big" messages and stores a MTU value for each destination address.	
pathMtuTimeout	TimeValue	0..1	attr	If this value is >0 the IPv4/IPv6 will reset the MTU value stored for each destination after n seconds.	

Table A.520: EthernetCommunicationConnector

Class	«atpVariation» EthernetCommunicationController				
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology				
Note	Ethernet specific communication port attributes.				
Base	<i>ARObject</i> , <i>CommunicationController</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>				
Aggregated by	EcuInstance.commController , MachineDesign.communicationController				
Attribute	Type	Mult.	Kind	Note	





Class	«atpVariation» EthernetCommunicationController			
canXIConfig	AbstractCanCommunicationController	0..1	ref	If the Ethernet frames handled by this EthernetCommunicationController are to be tunneled through CAN XL, then this reference shall refer to the AbstractCanCommunicationController that aggregates the CanControllerXIConfiguration of the physical CAN XL channel to be used for tunneling.
couplingPort	CouplingPort	*	aggr	Optional CouplingPort that can be used to connect the ECU to a CouplingElement (e.g. a switch).
macLayerType	EthernetMacLayerTypeEnum	0..1	attr	Specifies the mac layer type of the ethernet controller.
macUnicastAddress	MacAddressString	0..1	attr	Media Access Control address (MAC address) that uniquely identifies each EthernetCommunicationController in the network.
maximumReceiveBufferLength	Integer	0..1	attr	Determines the maximum receive buffer length (frame length) in bytes.
maximumTransmitBufferLength	Integer	0..1	attr	Determines the maximum transmit buffer length (frame length) in bytes.
slaveActAsPassiveCommunicationSlave	Boolean	0..1	attr	This attribute specifies if the EcuInstance is acting as a passive communication slave on the connected Physical Channel. This is used for EthernetCommunicationControllers that use Ethernet hardware which supports wake-up and sleep on the network (e.g. Open Alliance TC10 compliant Ethernet hardware).
slaveQualifiedUnexpectedLinkDownTime	TimeValue	0..1	attr	This attribute specifies time when an unexpected link down is evaluated as link down and indicated to the AUTOSAR communication stack.

Table A.521: EthernetCommunicationController

Enumeration	EthernetConnectionNegotiationEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Specifies connection negotiation types of Ethernet transceiver links.
Aggregated by	CouplingPort.connectionNegotiationBehavior
Literal	Description
auto	Automatic Negotiation Tags: atp.EnumerationLiteralIndex=0
master	Master Tags: atp.EnumerationLiteralIndex=1
slave	Slave Tags: atp.EnumerationLiteralIndex=2

Table A.522: EthernetConnectionNegotiationEnum

Enumeration	EthernetCouplingPortSchedulerEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Defines the schedule algorithm to be used.
Aggregated by	CouplingPortScheduler.portScheduler
Literal	Description





Enumeration	EthernetCouplingPortSchedulerEnum
deficitRoundRobin	Schedule algorithm "deficit round robin" Tags: atp.EnumerationLiteralIndex=0 atp.Status=obsolete
enhancedTrafficShaper	Scheduler used for enhanced traffic shaping (e.g. weighted round robin) Tags: atp.EnumerationLiteralIndex=3
strictPriority	Schedule algorithm "strict priority" Tags: atp.EnumerationLiteralIndex=1
weightedRoundRobin	Schedule algorithm "weighted round robin" Tags: atp.EnumerationLiteralIndex=2 atp.Status=obsolete

Table A.523: EthernetCouplingPortSchedulerEnum

Enumeration	EthernetMacLayerTypeEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Specifies MAC (Media Access Control) Layer types.
Aggregated by	CouplingPort.macLayerType , EthernetCommunicationController.macLayerType
Literal	Description
xGMII	Mac layer interface (data) bandwidth class 1Gbit/s (e.g. GMII, RGMII, SGMII, RvGMII, USGMII) Tags: atp.EnumerationLiteralIndex=1 xml.name=XG-MII
xMII	Mac layer interface (data) bandwidth class 100Mbit/s and 10Mbit/s (e.g. RMII, RvMII, SMII, RvMII) Tags: atp.EnumerationLiteralIndex=0 xml.name=X-MII
xXGMII	Mac layer interface (data) bandwidth class 10Gbit/s Tags: atp.EnumerationLiteralIndex=2 xml.name=XXG-MII

Table A.524: EthernetMacLayerTypeEnum

Class	EthernetPhysicalChannel			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	The EthernetPhysicalChannel represents a VLAN or an untagged channel. An untagged channel is modeled as an EthernetPhysicalChannel without an aggregated VLAN.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PhysicalChannel</i> , <i>Referrable</i>			
Aggregated by	CommunicationCluster.physicalChannel			
Attribute	Type	Mult.	Kind	Note
networkEndpoint	NetworkEndpoint	*	aggr	Collection of NetworkEndpoints that are used in the VLAN. Stereotypes: atp.Splittable Tags: atp.Splitkey=networkEndpoint.shortName





Class	EthernetPhysicalChannel			
soAdConfig	SoAdConfig	0..1	aggr	SoAd Configuration for one specific Physical Channel. Stereotypes: atp.Splitable Tags: atp.Splitkey=soAdConfig
vlan	VlanConfig	0..1	aggr	VLAN Configuration.

Table A.525: EthernetPhysicalChannel

Enumeration	EthernetPhysicalLayerTypeEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Specifies physical layer types of Ethernet transceiver links.
Aggregated by	CouplingPort.physicalLayerType
Literal	Description
_10000BASE_T1	Ethernet Standard (IEEE 802.3ch) to support 10Gbit/s over a single twisted pair cable. Tags: atp.EnumerationLiteralIndex=13 xml.name=10000BASE-T1
_1000BASE_T	Ethernet Standard (IEEE 802.3ab) to support 1Gbit/s over 4 twisted pairs. Tags: atp.EnumerationLiteralIndex=6 xml.name=1000BASE-T
_1000BASE_T1	Ethernet Standard (IEEE 802.3bp) to support 1Gbit/s over a single twisted pair cable. Tags: atp.EnumerationLiteralIndex=8 xml.name=1000BASE-T1
_100BASE_T1	Ethernet Standard (IEEE 802.3bw) to support 100Mbit/s over a single twisted pair cable. 100BASE-T1 is the IEEE Standardized version of BroadRReach. Tags: atp.EnumerationLiteralIndex=7 xml.name=100BASE-T1
_100BASE_TX	Ethernet Standard (IEEE 802.3u) to support 100Mbit/s over two twisted pairs. Tags: atp.EnumerationLiteralIndex=5 xml.name=100BASE-TX
_10BASE_T1S	Physical layer interface 10BASE-T1S (10Mbit/s, 2 pairs). Used for automotive. Tags: atp.EnumerationLiteralIndex=10 atp.Status=draft xml.name=10BASE-T1S
_2500BASE_T1	Ethernet Standard (IEEE 802.3ch) to support 2.5Gbit/s over a single twisted pair cable. Tags: atp.EnumerationLiteralIndex=11 xml.name=2500BASE-T1
_5000BASE_T1	Ethernet Standard (IEEE 802.3ch) to support 5Gbit/s over a single twisted pair cable. Tags: atp.EnumerationLiteralIndex=12 xml.name=5000BASE-T1
iEEE802_11P	Ethernet Standard (IEEE 802.11p) to support wireless communication in vehicular environments. Tags: atp.EnumerationLiteralIndex=9 xml.name=IEEE802-11P

Table A.526: EthernetPhysicalLayerTypeEnum

Class	EthernetPriorityRegeneration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines a priority regeneration where the ingressPriority is replaced by regeneratedPriority. The ethernetPriorityRegeneration is optional in case no priority regeneration shall be performed. In case a ethernetPriorityRegeneration is defined it shall have 8 mappings, one for each priority.			
Base	ARObject, Referrable			
Aggregated by	CouplingPortDetails.ethernetPriorityRegeneration			
Attribute	Type	Mult.	Kind	Note
ingressPriority	PositiveInteger	0..1	attr	Message priority of the incoming message. range: 0-7
regeneratedPriority	PositiveInteger	0..1	attr	Regenerated message priority. range: 0-7

Table A.527: EthernetPriorityRegeneration

Class	EthernetVlanTranslationTable			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This element defines one ingress Vlan translation entry in which the IngressVlanID from the incoming frame is replaced by the TranslatedVlanID.			
Base	ARObject			
Aggregated by	CouplingPortDetails.vlanTranslationTable			
Attribute	Type	Mult.	Kind	Note
ingressVlanId	PositiveInteger	0..1	attr	Incoming VlanID from received frame
translatedVlanId	PositiveInteger	0..1	attr	Mapped VlanID after ingress Vlan translation

Table A.528: EthernetVlanTranslationTable

Class	EthernetWakeupSleepOnDatalineConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	EthernetWakeupSleepOnDatalineConfigSet is the main element that aggregates different config set regarding the wakeup and sleep on data line. An EthernetWakeupSleepOnDatalineConfigSet could aggregate multiple different configurations regarding the wakeup and sleep on dataline (EthernetWakeupSleepOnDatalineConfig).			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EthernetWakeupSleepOnDatalineConfigSet.ethernetWakeupSleepOnDatalineConfig			
Attribute	Type	Mult.	Kind	Note
sleepModeExecutionDelay	TimeValue	0..1	attr	Delay in seconds to perform a sleep request if the Ethernet hardware (PHY) detect a pending wake-up. This is used to avoid the race condition, if a sleep was requested while a wake-up of a neighboring PHY was received via a local wake-up connection (e.g. I/O pin).
sleepRepetitionDelayOfSleepRequest	TimeValue	0..1	attr	Delay in seconds for a repetition of a sleep request. This is used to retry a synchronized shutdown of the connected Ethernet hardware (PHY) of the link partner.
sleepRepetitionsOfSleepRequest	PositiveInteger	0..1	attr	Count of repetitions for a sleep on dataline. If a sleep is rejected by the linked communication partner, the sleep is repeated until the count of repetitions exceed. If count of repetitions exceed, the Ethernet hardware (PHY) transit to sleep without acknowledgement of the connected link partner.





Class	EthernetWakeupSleepOnDatalineConfig			
wakeupForwardLocalEnabled	Boolean	0..1	attr	If enabled, then a remote wake-up received on the physical dataline (e.g. 100BASE-T1) is forwarded as local wake-up (e.g. via an I/O pin). If disabled, then a remote wake-up is not forwarded as local wake-up.
wakeupForwardRemoteEnabled	Boolean	0..1	attr	If enabled, then a local wake-up is forwarded to the physical dataline (e.g. 100BASE-T1). If disabled, then a local wake-up is not forwarded to the physical dataline.
wakeupLocalDetectionTime	TimeValue	0..1	attr	Specify the detection time if a local wake-up in seconds is present on the local wake-up connection (e.g. I/O pin). A local wake-up has to be present at least for wakeupLocalDetectionTime to be detected a valid local wake-up.
wakeupLocalDurationTime	TimeValue	0..1	attr	Specify the duration of a local wake-up in seconds to be present on the local wake-up connection (e.g. I/O pin).
wakeupLocalEnabled	Boolean	0..1	attr	If enabled, then a local wake-up received via a local connection (e.g. I/O pin) shall be detected by the Ethernet hardware (PHY). If disabled, Ethernet hardware is not reacting on a local wake-up.
wakeupRemoteEnabled	Boolean	0..1	attr	If enabled, then a remote wake-up received via the physical dataline (e.g. 100BASE-T1) shall be detected by the Ethernet hardware (PHY). If disabled, Ethernet hardware is not reaction on a remote wake-up.
wakeupRepetitionDelayOfWakeupRequest	TimeValue	0..1	attr	Delay in seconds for a repetition of a wake-up. This is used to increase the reliability in the network, such that an ECU which initiates the wake-up does repeat the wake-up and increase the probability that affected ECUs receive the wake-up.
wakeupRepetitionsOfWakeupRequest	PositiveInteger	0..1	attr	Count of repetitions for a wake-up. This is used to increase the reliability in the network, such that an ECU which initiates the wake-up does repeat the wake-up and increase the probability that affected ECUs receive the wake-up.

Table A.529: EthernetWakeupSleepOnDatalineConfig

Class	EvaluatedVariantSet			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling			
Note	<p>This meta class represents the ability to express if a set of ARElements is able to support one or more particular variants.</p> <p>In other words, for a given set of evaluatedElements this meta class represents a table of evaluated variants, where each PredefinedVariant represents one column. In this column each descendant swSystemconstantValue resp. postbuildVariantCriterionValue represents one entry.</p> <p>In a graphical representation each swSystemconstantValueSet / postBuildVariantCriterionValueSet could be used as an intermediate headline in the table column.</p> <p>If the approvalStatus is "APPROVED" it expresses that the collection of CollectableElements is known be valid for the given evaluatedVariants.</p> <p>Note that the EvaluatedVariantSet is a CollectableElement. This allows to establish a hierarchy of EvaluatedVariantSets.</p> <p>Tags: atp.recommendedPackage=EvaluatedVariantSets</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	EvaluatedVariantSet			
approvalStatus	NameToken	1	attr	<p>Defines the approval status of a predefined variant. Two values are predefined: "APPROVED" and "REJECTED":</p> <ul style="list-style-type: none"> • Approved variants are known to work. • Rejected variants are known NOT to work. <p>Further values can be approved on a per-company basis; within AUTOSAR only "APPROVED" and "REJECTED" should be recognized.</p>
evaluated Element	CollectableElement	*	ref	<p>This represents a particular element which is evaluated in context of the EvaluatedVariants. The approvalStatus applies to this element (and all of its descendants). In other words, the referenced elements are those that were considered when the predefined variant was evaluated.</p>
evaluated Variant	PredefinedVariant	*	ref	<p>This metaclass represents one particular variant which was evaluated. LowerMultiplicity is set to 0 to support a stepwise approach.</p>

Table A.530: EvaluatedVariantSet

Class	EventControlledTiming			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	Specification of a event driven sending behavior. The PDU is sent n (numberOfRepeat + 1) times separated by the repetitionPeriod. If numberOfRepeats = 0, then the Pdu is sent just once.			
Base	ARObject , Describable			
Aggregated by	TransmissionModeTiming.eventControlledTiming			
Attribute	Type	Mult.	Kind	Note
numberOfRepetitions	Integer	0..1	attr	Defines the number of repetitions for the Direct/N-Times transmission mode and the event driven part of Mixed transmission mode.
repetitionPeriod	TimeRangeType	0..1	aggr	The repetitionPeriod specifies the time in seconds that elapses before the pdu can be sent the next time (Minimum repeat gap between two pdus). The repetition Period is optional in case that no repetitions are configured.

Table A.531: EventControlledTiming

Enumeration	EventGroupControlTypeEnum			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Types of a RoutingGroups for the event communication.			
Aggregated by	PduActivationRoutingGroup.eventGroupControlType , SoAdRoutingGroup.eventGroupControlType			
Literal	Description			
activationAndTriggerUnicast	<p>Activate the data path for unicast events and triggered unicast events that are sent out after a client got subscribed.</p> <p>Tags: atp.EnumerationLiteralIndex=0</p>			
activationMulticast	<p>Activate the data path for multicast events of an EventGroup.</p> <p>Tags: atp.EnumerationLiteralIndex=1</p>			
activationUnicast	<p>Activate the data path for unicast events of an EventGroup.</p> <p>Tags: atp.EnumerationLiteralIndex=2</p>			
triggerUnicast	<p>Activate the data path for triggered unicast events that are sent out after a client got subscribed.</p> <p>Tags: atp.EnumerationLiteralIndex=3</p>			

Table A.532: EventGroupControlTypeEnum

Class	EventHandler			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	This element represents an event group as part of the Provided Service Instance.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ProvidedServiceInstance.eventHandler			
Attribute	Type	Mult.	Kind	Note
consumedEventGroup	ConsumedEventGroup	*	ref	All consumers of the event are referenced here. Tags: atp.Status=obsolete
eventGroupIdentifier	PositiveInteger	0..1	attr	Unique Identifier that identifies the EventGroup in SOME/IP. This Identifier is sent as Eventgroup ID in SOME/IP Service Discovery messages.
eventMulticastAddress	ApplicationEndpoint	0..1	ref	Multicast Address that is used for event communication in the IP-Multicast case. It is the destination address to which the server sends the multicast event messages if the mulicastThreshold is exceeded. This address is transmitted in the SD-SubscribeEvent GroupAck Message to client (answer to SD-Subscribe EventGroup). Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=eventMulticastAddress.applicationLabelEndpoint, eventMulticastAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
multicastThreshold	PositiveInteger	0..1	attr	Specifies the number of subscribed clients that trigger the server to change the transmission of events to multicast. If configured to 0 only unicast will be used. If configured to 1 the first client will be already served by multicast. If configured to 2 the first client will be served with unicast and as soon as the second client arrives both will be served by multicast. This does not influence the handling of initial events, which are served using unicast only.
pduActivationRoutingGroup	PduActivationRoutingGroup	*	aggr	The ServiceDiscovery module is able to activate and deactivate the PDU routing for events.
routingGroup	SoAdRoutingGroup	*	ref	The ServiceDiscovery module is able to activate and deactivate the PDU routing for events. Tags: atp.Status=obsolete
sdServerConfig	SdServerConfig	0..1	aggr	Server configuration parameter for Service-Discovery. Tags: atp.Status=obsolete
sdServerEgTimingConfig	SomeipSdServerEventGroupTimingConfig	0..1	ref	Server Timing configuration settings that are EventGroup specific. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=sdServerEgTimingConfig.someipSdServerEventGroupTimingConfig, sdServerEgTimingConfig.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.533: EventHandler

Class	EventTriggeringConstraint (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::EventTriggeringConstraint			
Note	Describes the occurrence behavior of the referenced timing event. The occurrence behavior can only be determined when a mapping from the timing events to the implementation can be obtained. However, such an occurrence behavior can also be described by the modeler as an assumption or as a requirement about the occurrence of the event.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Subclasses	ArbitraryEventTriggering , BurstPatternEventTriggering , ConcretePatternEventTriggering , PeriodicEventTriggering , SporadicEventTriggering			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
event	TimingDescriptionEvent	0..1	ref	The referenced timing event

Table A.534: EventTriggeringConstraint

Class	ExclusiveArea			
Package	M2::AUTOSARTemplates::CommonStructure::InternalBehavior			
Note	Prevents an executable entity running in the area from being preempted.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	InternalBehavior.exclusiveArea			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.535: ExclusiveArea

Class	ExecutableEntity (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::InternalBehavior			
Note	Abstraction of executable code.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	BswModuleEntity , RunnableEntity			
Attribute	Type	Mult.	Kind	Note
activation Reason	ExecutableEntity ActivationReason	*	aggr	If the ExecutableEntity provides at least one activation Reason element the RTE resp. BSW Scheduler shall provide means to read the activation vector of this executable entity execution. If no activationReason element is provided the feature of being able to determine the activating RTEEvent is disabled for this ExecutableEntity.
canEnter	ExclusiveArea	*	ref	This means that the executable entity can enter/leave the referenced exclusive area through explicit API calls. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=canEnter.exclusiveArea, canEnter.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
exclusiveArea NestingOrder	ExclusiveAreaNestingOrder	*	ref	This represents the set of ExclusiveAreaNestingOrders recognized by this ExecutableEntity.
minimumStart Interval	TimeValue	0..1	attr	Specifies the time in seconds by which two consecutive starts of an ExecutableEntity are guaranteed to be separated.





Class	ExecutableEntity (abstract)			
reentrancyLevel	ReentrancyLevelEnum	0..1	attr	<p>The reentrancy level of this ExecutableEntity. See the documentation of the enumeration type ReentrancyLevelEnum for details.</p> <p>Please note that nonReentrant interfaces can have also reentrant or multicoreReentrant implementations, and reentrant interfaces can also have multicoreReentrant implementations.</p>
runsInside	ExclusiveArea	*	ref	<p>The executable entity runs completely inside the referenced exclusive area.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=runsInside.exclusiveArea, runsInside.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
swAddrMethod	SwAddrMethod	0..1	ref	<p>Addressing method related to this code entity. Via an association to the same SwAddrMethod, it can be specified that several code entities (even of different modules or components) shall be located in the same memory without already specifying the memory section itself.</p>

Table A.536: ExecutableEntity

Class	ExecutableEntityActivationReason			
Package	M2::AUTOSARTemplates::CommonStructure::InternalBehavior			
Note	This meta-class represents the ability to define the reason for the activation of the enclosing ExecutableEntity.			
Base	ARObject , ImplementationProps , Referrable			
Aggregated by	ExecutableEntity.activationReason			
Attribute	Type	Mult.	Kind	Note
bitPosition	PositiveInteger	0..1	attr	This attribute allows for defining the position of the enclosing ExecutableEntityActivationReason in the activation vector.

Table A.537: ExecutableEntityActivationReason

Class	ExecutionOrderConstraint			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::ExecutionOrderConstraint			
Note	<p>This constraint is used to restrict the order of execution for a set of ExecutableEntities. The ExecutionOrderConstraint can be used in any timing view.</p> <p>The various scopes for ExecutionOrderConstraint are described below. Generally, each ExecutionOrderConstraint has a scope of software components and can reference all ExecutableEntities available in the corresponding internal behavior (RunnableEntity and BswModuleEntity) either directly or by the events activating respectively starting them (RteEvent and BswEvent).</p> <p>On VFB level an ExecutionOrderConstraint can be specified for RunnableEntities part of the composition hierarchy referenced by the VfbTiming.</p> <p>On SW-C level an ExecutionOrderConstraint can be specified for RunnableEntities part of the Internal Behavior referenced by the SwcTiming.</p> <p>On System level an ExecutionOrderConstraint can be specified for RunnableEntities part of the composition hierarchy of the system referenced by the SystemTiming.</p> <p>On BSW Module level, an ExecutionOrderConstraint can be specified for BswModuleEntities part of an BswInternalBehavior referenced by the BswModuleTiming.</p> <p>On ECU level an ExecutionOrderConstraint can be specified for all ExecutableEntities and Events available via the EcucValueCollection, covering ECU Extract and BSW Module Configuration, referenced by the EcuTiming.</p>			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
base Composition	CompositionSwComponentType	0..1	ref	Specifies the composition SW-C type playing the role of a SW-C containing further SW-Cs and represents the scope of the Execution Order Constraint.
executionOrderConstraintType	ExecutionOrderConstraintTypeEnum	0..1	attr	Specifies the specific type of ExecutionOrderConstraint.
ignoreOrderAllowed	Boolean	0..1	attr	Controls whether the order of execution specified by this constraint can be intentionally ignored (TRUE), or shall be respected (FALSE). Tags: atp.Status=obsolete
isEvent	Boolean	0..1	attr	Indicates whether the ExecutionOrderConstraint is only referring to Executable Entities (FALSE) or only to RTE and/or BSW Events (TRUE).
orderedElement	EOCExecutableEntityRefAbstract	*	aggr	This aggregation represents an unordered collection of references to RunnableEntities which shall be considered in the ExecutionOrderConstraint. The role does not imply that the collection of references itself shall be ordered.
permitMultipleReferencesToEE	Boolean	0..1	attr	Indicates that the ExecutionOrderConstraints permits that an Executable Entity is referenced multiple times (TRUE) or only once (FALSE) in the constraint.

Table A.538: ExecutionOrderConstraint

Enumeration	ExecutionOrderConstraintTypeEnum
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::ExecutionOrderConstraint
Note	Specifies the type of the executionOrderConstraintType for a ExecutionOrderConstraint .
Aggregated by	ExecutionOrderConstraint.executionOrderConstraintType
Literal	Description
hierarchicalEOC	Specifies that the Execution Order Constraint specifies a hierarchical execution order constraint. Tags: atp.EnumerationLiteralIndex=0





Enumeration	ExecutionOrderConstraintTypeEnum
ordinaryEOC	Specifies that the Execution Order Constraint specifies an ordinary execution order constraint. Tags: atp.EnumerationLiteralIndex=1
repetitiveEOC	Specifies that the Execution Order Constraint specifies a repetitive execution order constraint. Tags: atp.EnumerationLiteralIndex=2

Table A.539: ExecutionOrderConstraintTypeEnum

Class	ExecutionTime (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::ExecutionTime			
Note	Base class for several means how to describe the ExecutionTime of software. The required context information is provided through this class.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	AnalyzedExecutionTime , MeasuredExecutionTime , RoughEstimateOfExecutionTime , SimulatedExecutionTime			
Aggregated by	ResourceConsumption.executionTime			
Attribute	Type	Mult.	Kind	Note
exclusiveArea	ExclusiveArea	0..1	ref	Reference to the ExclusiveArea this execution time is provided for.
executableEntity	ExecutableEntity	0..1	ref	The executable entity for which this execution time is described.
hardware Configuration	HardwareConfiguration	0..1	aggr	Provides information on the HardwareConfiguration used to specify this ExecutionTime.
hwElement	HwElement	0..1	ref	The hardware element (e.g. type of ECU) for which the execution time is specified.
includedLibrary	DependencyOnArtifact	*	ref	If this dependency is specified, the execution time of the library code is included in the execution time data for the runnable.
memorySection Location	MemorySectionLocation	*	aggr	Provides information on the MemorySectionLocation which is involved in the ExecutionTime description.
softwareContext	SoftwareContext	0..1	aggr	Provides information on the detailed SoftwareContext used to provide the ExecutionTime description.

Table A.540: ExecutionTime

Class	ExecutionTimeConstraint			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::ExecutionTimeConstraint			
Note	<p>Constrains the execution time of the referenced executable in component between a minimum and maximum interval.</p> <p>The time to execute the executable including interruptions by other entities and including external calls is commonly called "response time". The TimingExtensions provide the concept of event chains and latency constraints for that purpose. An event chain from the start of the entity to the termination of the entity with according latency constraint represents a response time constraint for that executable entity.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee, TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note





Class	ExecutionTimeConstraint			
component	SwComponent Prototype	0..1	iref	The component that contains the referenced Executable Entity for the ExecutionTimeConstraint. If the entity is in a basic software module no component shall be provided. InstanceRef implemented by: ComponentInCompositionInstanceRef
executable	ExecutableEntity	0..1	ref	The referenced ExecutableEntity for the ExecutionTimeConstraint.
executionTime Type	ExecutionTimeType Enum	0..1	attr	Specifies the type of the execution time constrained by ExecutionTimeConstraint,
maximum	MultidimensionalTime	0..1	aggr	The maximum execution time.
minimum	MultidimensionalTime	0..1	aggr	The minimum execution time.

Table A.541: ExecutionTimeConstraint

Class	ExternalTriggerOccurredEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the referenced Trigger has occurred.			
Base	ARObject , AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , Multilanguage Referrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
trigger	Trigger	0..1	iref	The referenced Trigger raises this ExternalTrigger OccurredEvent. InstanceRef implemented by: RTriggerInAtomicSwc InstanceRef

Table A.542: ExternalTriggerOccurredEvent

Class	ExternalTriggeringPoint			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::Trigger			
Note	If a RunnableEntity owns an ExternalTriggeringPoint it is entitled to raise an ExternalTriggerOccurred Event.			
Base	ARObject			
Aggregated by	RunnableEntity.externalTriggeringPoint			
Attribute	Type	Mult.	Kind	Note
ident	ExternalTriggeringPoint Ident	0..1	aggr	The aggregation in the role ident provides the ability to make the ExternalTriggeringPoint identifiable. From the semantical point of view, the ExternalTriggering Point is considered a first-class Identifiable and therefore the aggregation in the role ident shall always exist (until it may be possible to let ModeAccessPoint directly inherit from Identifiable). Stereotypes: atpIdentityContributor Tags: xml.sequenceOffset=-100





Class	ExternalTriggeringPoint			
trigger	Trigger	0..1	iref	<p>The trigger taken for the ExternalTriggeringPoint.</p> <p>Tags: xml.namePlural=TRIGGER-IREF xml.roleElement=false xml.roleWrapperElement=true xml.typeElement=true xml.typeWrapperElement=false InstanceRef implemented by: PTriggerInAtomicSwc TypeInstanceRef</p>

Table A.543: ExternalTriggeringPoint

Class	FibexElement (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore			
Note	ASAM FIBEX elements specifying Communication and Topology.			
Base	ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Subclasses	BusMirrorChannelMapping , CommunicationCluster , ConsumedProvidedServiceInstanceGroup, CouplingElement , EcuInstance , EthernetWakeupSleepOnDataLineConfigSet , Frame , Gateway , GlobalTimeDomain , ISignal , ISignalGroup , ISignalPduGroup , NmConfig , Pdu , PdurlPduGroup , SecureCommunicationPropsSet , ServiceInstanceCollectionSet , SoAdRoutingGroup , SocketConnectionIpduIdentifierSet , TpConfig			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.544: FibexElement

Class	FlatInstanceDescriptor			
Package	M2::AUTOSARTemplates::CommonStructure::FlatMap			
Note	<p>Represents exactly one node (e.g. a component instance or data element) of the instance tree of a software system. The purpose of this element is to map the various nested representations of this instance to a flat representation and assign a unique name (shortName) to it.</p> <p>Use cases:</p> <ul style="list-style-type: none"> • Specify unique names of measurable data to be used by MCD tools • Specify unique names of calibration data to be used by MCD tool • Specify a unique name for an instance of a component prototype in the ECU extract of the system description <p>Note that in addition it is possible to assign alias names via AliasNameAssignment.</p>			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	FlatMap.instance			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–





Class	FlatInstanceDescriptor			
ecuExtract Reference	AtpFeature	0..1	iref	<p>Refers to the instance in the ECU extract. This is valid only, if the FlatMap is used in the context of an ECU extract.</p> <p>The reference shall be such that it uniquely defines the object instance. For example, if a data prototype is declared as a role within an SwcInternalBehavior, it is not enough to state the SwcInternalBehavior as context and the aggregated data prototype as target. In addition, the reference shall also include the complete path identifying instance of the component prototype and the Atomic SoftwareComponentType, which is referred by the particular SwcInternalBehavior.</p> <p>Tags: xml.sequenceOffset=40 InstanceRef implemented by: AnyInstanceRef</p>
role	Identifier	0..1	attr	<p>The role denotes the particular role of the downstream memory location described by this FlatInstanceDescriptor.</p> <p>It applies to use case where one upstream object results in multiple downstream objects, e.g. ModeDeclaration GroupPrototypes which are measurable. In this case the RTE will provide locations for current mode, previous mode and next mode.</p>
rtePluginProps	RtePluginProps	0..1	aggr	<p>The properties of a communication graph with respect to the utilization of RTE Implementation Plug-in.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=rtePluginProps</p>
swDataDef Props	SwDataDefProps	0..1	aggr	<p>The properties of this FlatInstanceDescriptor.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps</p>
upstream Reference	AtpFeature	0..1	iref	<p>Refers to the instance in the context of an "upstream" description, which could be: the SYSTEM_DESCRIPTION, or SYSTEM_EXTRACT, or ECU_SYSTEM_DESCRIPTION, or SW_CLUSTER_SYSTEM_DESCRIPTION, or the basic software module description (in this case only the target reference of the AnyInstance Ref is needed), or (if a flat map is used in preliminary context) a description of an atomic component or composition.</p> <p>This reference is optional in case the flat map is used in ECU context. The reference shall be such that it uniquely defines the object instance in the given context. For example, if a data prototype is declared as a role within an SwcInternal Behavior, it is not enough to state the Swc Internal Behavior as context and the aggregated data prototype as target. In addition, the reference shall also include the complete path identifying the instance of the component prototype that contains the particular instance of Swc InternalBehavior.</p> <p>Tags: xml.sequenceOffset=20 InstanceRef implemented by: AnyInstanceRef</p>

Table A.545: FlatInstanceDescriptor

Class	FlatMap			
Package	M2::AUTOSARTemplates::CommonStructure::FlatMap			
Note	<p>Contains a flat list of references to software objects. This list is used to identify instances and to resolve name conflicts. The scope is given by the RootSwCompositionPrototype for which it is used, i.e. it can be applied to a system, system extract or ECU-extract.</p> <p>An instance of FlatMap may also be used in a preliminary context, e.g. in the scope of a software component before integration into a system. In this case it is not referred by a RootSwComposition Prototype.</p> <p>Tags: atp.recommendedPackage=FlatMaps</p>			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
instance	FlatInstanceDescriptor	*	aggr	<p>A descriptor instance aggregated in the flat map.</p> <p>The variation point accounts for the fact, that the system in scope can be subject to variability, and thus the existence of some instances is variable.</p> <p>The aggregation has been made splittable because the content might be contributed by different stakeholders at different times in the workflow. Plus, the overall size might be so big that eventually it becomes more manageable if it is distributed over several files.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=instance.shortName, instance.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>

Table A.546: FlatMap

Class	FlexrayAbsolutelyScheduledTiming			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayCommunication			
Note	<p>Each frame in FlexRay is identified by its slot id and communication cycle. A description is provided by the usage of AbsolutelyScheduledTiming.</p> <p>In the static segment a frame can be sent multiple times within one communication cycle. For describing this case multiple AbsolutelyScheduledTimings have to be used. The main use case would be that a frame is sent twice within one communication cycle.</p>			
Base	ARObject			
Aggregated by	FlexrayFrameTriggering.absolutelyScheduledTiming			
Attribute	Type	Mult.	Kind	Note
communication Cycle	CommunicationCycle	0..1	aggr	The communication cycle where the frame is sent.
slotID	PositiveInteger	0..1	attr	<p>In the static part the SlotID defines the slot in which the frame is transmitted. The SlotID also determines, in combination with FlexrayCluster::numberOfStaticSlots, whether the frame is sent in static or dynamic segment. In the dynamic part, the slot id is equivalent to a priority. Lower dynamic slot ids are all sent until the end of the dynamic segment. Higher numbers, which were ignored that time, have to wait one cycle and then shall try again.</p> <p>minValue: 1 maxValue: 2047</p>

Table A.547: FlexrayAbsolutelyScheduledTiming

Class	FlexrayArTpChannel			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	<p>A channel is a group of connections sharing several properties.</p> <p>The FlexRay AutosarTransport Layer supports several channels. These channels can work concurrently, thus each of them requires its own state machine and management data structures and its own PDU-IDs.</p>			
Base	ARObject			
Aggregated by	FlexrayArTpConfig.tpChannel			
Attribute	Type	Mult.	Kind	Note
ackType	FrArTpAckType	0..1	attr	Type of Acknowledgement.
cancellation	Boolean	0..1	attr	With this switch Tx and Rx Cancellation can be turned on or off.
extended Addressing	Boolean	0..1	attr	Adressing Type of this connection: true: Two Bytes false: One Byte
maxAr	Integer	0..1	attr	This attribute defines the maximum number of trying to send a frame when a TIMEOUT AR occurs (depending on whether retry is configured).
maxAs	Integer	0..1	attr	This attribute defines the maximum number of trying to send a frame when a TIMEOUT AS occurs (depending on whether retry is configured).
maxBs	Integer	0..1	attr	This attribute defines the number of consecutive CFs between two FCs (block size). Valid values are 1 .. 16 when retry is activated, and 0 .. 255 otherwise.
maxFcWait	PositiveInteger	0..1	attr	This attribute defines the maximal number of wait frames to be sent for a pending connection. Range is 0..255.
maximum MessageLength	MaximumMessageLengthType	0..1	attr	This specifies the maximum message length for the particular channel.
maxRetries	Integer	0..1	attr	This attribute defines the maximum number of retries (if retry is configured for the particular channel).
minimum Multicast SeperationTime	TimeValue	0..1	attr	<p>This attribute defines the minimum amount of time between two succeeding CFs of a 1:n segmented transmission in seconds. Valid values are 0, 100µs, 200µs ... 900µs, 1ms, 2ms .. 127ms. The value can be changed at runtime using the FrArTp_ChangeParameter interface.</p> <p>minimumMulticastSeparationTime shall be an integer multiple of the cycle length multiplied with the multiplexing factor, i.e. $\text{minimumMulticastSeparationTime} = n * \text{cycle} * m$, where n is an integer ≥ 0, cycle is Flexray Cluster.cycle, and m is the cycle multiplexor of those cycles where PDUs of the PDU pool are scheduled. Please note: Due to the scheduling strategies of FrTp, minimumMulticastSeparationTime can only be kept to a degree defined by the maximum temporal distance of the PDUs of a PDU pool within one FlexRay cycle.</p> <p>Range: 0 .. 0.127</p>





Class	FlexrayArTpChannel			
minimumSeparationTime	TimeValue	0..1	attr	<p>This attribute defines the minimum amount of time between two succeeding CFs of a 1:1 segmented transmission in seconds. Valid values are 0, 100µs, 200µs .. 900µs, 1ms, 2ms .. 127ms. The value can be changed at runtime using the FrArTp_ChangeParameter interface.</p> <p>The minimumSeparationTime shall be an integer multiple of the cycle length multiplied with the multiplexing factor, i.e. $\text{minimumSeparationTime} = n * \text{cycle} * m$, where n is an integer ≥ 0, cycle is FlexrayCluster.cycle, and m is the cycle multiplexor of those cycles where PDUs of the PDU pool are scheduled.</p> <p>Please note: Due to the scheduling strategies of FrTp, minimumSeparationTime can only be kept to a degree defined by the maximum temporal distance of the PDUs of a PDU pool within one FlexRay cycle.</p> <p>Range: 0 .. 0.127</p>
multicastSegmentation	Boolean	0..1	attr	This attribute defines whether segmentation within a 1:n connection is allowed or not.
nPdu	NPdu	*	ref	A FlexRayTpChannel references a set of NPdus. These NPdus are logically assembled into a pool of Rx NPdus and another pool of Tx NPdus. It shall be ensured that a second channel either references all NPdus of such a pool, or none.
timeBr	TimeValue	0..1	attr	This attribute defines the time in seconds between receiving the last CF of a block or an FF-x (or SF-x) and sending out an FC or AF.
timeCs	TimeValue	0..1	attr	This attribute defines the time in seconds between the sending of two consecutive frames or between a consecutive frame and a flow control (for Transmit Cancellation) or between reception of an flow control or Acknowledgement Frame and sending of the next consecutive frame or a flow control (for Transmit Cancellation).
timeoutAr	TimeValue	0..1	attr	This attribute states the timeout in seconds between the PDU transmit request of the Transport Layer to the Flex Ray Interface and the corresponding confirmation of the FlexRay Interface on the receiver side (for FC or AF).
timeoutAs	TimeValue	0..1	attr	This attribute states the timeout in seconds between the PDU transmit request for the first PDU of the group used in the current connection of the Transport Layer to the FlexRay Interface and the corresponding confirmation of the FlexRay Interface (when having sent the last PDU of the group used in this connection) on the sender side (SF-x, FF-x, CF).
timeoutBs	TimeValue	0..1	attr	This attribute defines the timeout in seconds for waiting for an FC or AF on the sender side in a 1:1 connection.
timeoutCr	TimeValue	0..1	attr	This attribute defines the timeout value in seconds for waiting for a CF or FF-x (in case of retry) after receiving the last CF or after sending an FC or AF on the receiver side.
tpConnection	FlexrayArTpConnection	*	aggr	Group of connections that can be used in this channel.

Table A.548: FlexrayArTpChannel

Class	FlexrayArTpConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	<p>This element defines exactly one FlexRay Autosar TP Configuration.</p> <p>One FlexrayArTpConfig element shall be created for each FlexRay Network in the System that uses Flex Ray Autosar TP.</p> <p>Tags: atp.recommendedPackage=TpConfigs</p>			
Base	<i>ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, TpConfig</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
tpAddress	TPAddress	*	aggr	<p>Collection of TpAddresses.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpAddress.shortName, tpAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
tpChannel	FlexrayArTpChannel	*	aggr	<p>Configuration of FlexRay Autosar Transport Protocol channels.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpChannel, tpChannel.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
tpNode	FlexrayArTpNode	*	aggr	<p>Senders and receivers of TP messages.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpNode.shortName, tpNode.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>

Table A.549: FlexrayArTpConfig

Class	FlexrayArTpConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	<p>A connection within a channel identifies the sender and the receiver of this particular communication.</p> <p>The FlexRay Autosar Tp module routes a Pdu through this connection.</p>			
Base	<i>ARObject, TpConnection</i>			
Aggregated by	FlexrayArTpChannel.tpConnection			
Attribute	Type	Mult.	Kind	Note
connectionPrioPdus	Integer	0..1	attr	<p>This parameter defines the number of PDUs that shall be reserved for this connection when it is active. The range is 1-255.</p>
directTpSdu	IPdu	0..1	ref	<p>Reference to the IPdu that is segmented by the Transport Protocol.</p> <p>The source address of the transmitted NPdu is determined by the configured source Communication Connector. The target address of the transmitted NPdu is determined by the configured target Communication Connector.</p>
multicast	TPAddress	0..1	ref	<p>TP address for 1:n connections.</p>





Class	FlexrayArTpConnection			
reversedTpSdu	IPdu	0..1	ref	Reference to the IPdu that is segmented by the Transport Protocol. If support of both sending and receiving is used, this association references the IPdu used for the additional second direction. The source address of the transmitted NPdu is determined by the configured target Communication Connector. The target address of the transmitted NPdu is determined by the configured source Communication Connector.
source	FlexrayArTpNode	0..1	ref	The source of the TP connection.
target	FlexrayArTpNode	*	ref	The target of the TP connection.

Table A.550: FlexrayArTpConnection

Class	FlexrayArTpNode			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	TP Node (Sender or Receiver) provides the TP Address and the connection to the Topology description.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	FlexrayArTpConfig.tpNode			
Attribute	Type	Mult.	Kind	Note
connector	FlexrayCommunicationConnector	*	ref	Association to one or more physical connectors (max number of connectors for FlexRay: 2). In a System Description this reference is mandatory. In an ECU Extract this reference is optional (references to ECUs that are not part of the ECU Extract shall be avoided).
tpAddress	TpAddress	0..1	ref	Reference to the TP Address that is used by the TpNode. This reference is optional in case that the multicast TP Address is used (reference from TpConnection).

Table A.551: FlexrayArTpNode

Enumeration	FlexrayChannelName	
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayTopology	
Note	Name of the channel.	
Aggregated by	FlexrayPhysicalChannel.channelName	
Literal	Description	
channelA	Channel A Tags: atp.EnumerationLiteralIndex=0	
channelB	Channel B Tags: atp.EnumerationLiteralIndex=1	

Table A.552: FlexrayChannelName

Class	«atpVariation» FlexrayCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayTopology			
Note	FlexRay specific attributes to the physicalCluster Tags: atp.recommendedPackage=CommunicationClusters			
Base	ARElement, ARObject, CollectableElement, CommunicationCluster, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
actionPointOffset	Integer	0..1	attr	The offset of the action point in networks
bit	TimeValue	0..1	attr	Nominal bit time (= 1 / fx:SPEED). gdBit = cSamplesPerBit * gdSampleClockPeriod. Unit: seconds (gdBit)
casRxLowMax	Integer	0..1	attr	Upper limit of the Collision Avoidance Symbol (CAS) acceptance window. Unit: bitDuration
coldStartAttempts	Integer	0..1	attr	The maximum number of times that a node in this cluster is permitted to attempt to start the cluster by initiating schedule synchronization
cycle	TimeValue	0..1	attr	Length of the cycle. Unit: seconds
cycleCountMax	Integer	0..1	attr	Maximum cycle counter value in a given cluster. Remark: Set to 63 for FlexRay Protocol 2.1 Rev. A compliance.
detectNitError	Boolean	0..1	attr	Indicates whether NIT error status of each cluster shall be detected or not.
dynamicSlotIdlePhase	Integer	0..1	attr	The duration of the dynamic slot idle phase in minislots.
ignoreAfterTx	Integer	0..1	attr	Duration for which the bitstrobing is paused after transmission [gdBit].
listenNoise	Integer	0..1	attr	Upper limit for the start up and wake up listen timeout in the presence of noise. Expressed as a multiple of the cluster constant pdListenTimeout. Unit: microticks
macroPerCycle	Integer	0..1	attr	The number of macroticks in a communication cycle
macrotickDuration	TimeValue	0..1	attr	Duration of the cluster wide nominal macrotick, expressed in s.
maxWithoutClockCorrectionFatal	Integer	0..1	attr	Threshold concerning vClockCorrectionFailedCounter. Defines the number of consecutive even/odd Cycle pairs with missing clock correction terms that will cause the protocol to transition from the POC:normal active or POC:normal passive state into the POC:halt state.
maxWithoutClockCorrectionPassive	Integer	0..1	attr	Threshold concerning vClockCorrectionFailedCounter. Defines the number of consecutive even/odd Cycle pairs with missing clock correction terms that will cause the protocol to transition from the POC:normal active state to the POC:normal passive state.
minislotActionPointOffset	Integer	0..1	attr	The Offset of the action point within a minislot. Unit: macroticks
minislotDuration	Integer	0..1	attr	The duration of a minislot (dynamic segment). Unit: macroticks.
networkIdleTime	Integer	0..1	attr	The duration of the network idle time in macroticks
networkManagementVectorLength	Integer	0..1	attr	Length of the Network Management vector in a cluster [bytes]
numberOfMinislots	Integer	0..1	attr	Number of Minislots in the dynamic segment.
numberOfStaticSlots	Integer	0..1	attr	The number of static slots in the static segment.





Class	«atpVariation» FlexrayCluster			
offsetCorrectionStart	Integer	0..1	attr	Start of the offset correction phase within the Network Idle Time (NIT), expressed as the number of macroticks from the start of cycle. Unit: macroticks
payloadLengthStatic	Integer	0..1	attr	Globally configured payload length of a static frame. Unit: 16-bit WORDS.
safetyMargin	Integer	0..1	attr	Additional timespan in macroticks which takes jitter into account to be able to set the JobListPointer to the next possible job which can be executed in case the FlexRay Job List Execution Function has been resynchronized.
sampleClockPeriod	TimeValue	0..1	attr	Sample clock period. Unit: seconds
staticSlotDuration	Integer	0..1	attr	The duration of a slot in the static segment. Unit: macroticks
symbolWindow	Integer	0..1	attr	The duration of the symbol window. Unit: macroticks
symbolWindowActionPointOffset	Integer	0..1	attr	Number of macroticks the action point offset is from the beginning of the symbol window [Macroticks].
syncFrameIdCountMax	Integer	0..1	attr	Maximum number of distinct syncframe identifiers present in a given cluster. This parameter maps to FlexRay Protocol 2.1 Rev. A parameter gSyncNodeMax.
tranceiverStandbyDelay	Float	0..1	attr	The duration of timer t_TrvcStdbbyDelay in seconds. The granularity of this parameter shall be restricted to full FlexRay cycles (cycle). The tranceiver status setting to STANDBY shall be delayed by this value. Not specifying a value or a value of 0 shall imply that the timer is not used.
transmissionStartSequenceDuration	Integer	0..1	attr	Number of bits in the Transmission Start Sequence [gd Bits].
wakeupRxIdle	Integer	0..1	attr	Number of bits used by the node to test the duration of the 'idle' or HIGH phase of a received wakeup. Unit: bitDuration Remarks: This parameter maps to FlexRay Protocol 2.1 Rev. A parameter gdWakeupSymbolRxIdle.
wakeupRxLow	Integer	0..1	attr	Number of bits used by the node to test the duration of the LOW phase of a received wakeup. Unit: bitDuration Remarks: This parameter maps to FlexRay Protocol 2.1 Rev. A parameter gdWakeupSymbolRxLow.
wakeupRxWindow	Integer	0..1	attr	The size of the window used to detect wakeups [gdBit]. Remarks: This parameter maps to FlexRay Protocol 2.1 Rev. A parameter gdWakeupSymbolRxWindow.
wakeupTxActive	Integer	0..1	attr	Number of bits used by the node to transmit the LOW phase of a wakeup symbol and the HIGH and LOW phases of a WUDOP. Unit: bitDuration
wakeupTxIdle	Integer	0..1	attr	Number of bits used by the node to transmit the 'idle' part of a wakeup symbol. Unit: gDbit

Table A.553: FlexrayCluster

Class	FlexrayCommunicationConnector
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayTopology
Note	FlexRay specific attributes to the CommunicationConnector
Base	<i>ARObject</i> , <i>CommunicationConnector</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>





Class	FlexrayCommunicationConnector			
Aggregated by	EcuInstance.connector , MachineDesign.communicationConnector			
Attribute	Type	Mult.	Kind	Note
nmReadySleepTime	Float	0..1	attr	The value of this attribute influences the shutdown behavior of the FlexRay NM. FrNm switches to bus sleep mode nmReadySleepTime seconds after the completion of the last repetition cycle containing a NM vote.
wakeUpChannel	Boolean	0..1	attr	Referenced channel used by the node to send a wakeup pattern. (pWakeupChannel)

Table A.554: FlexrayCommunicationConnector

Class	FlexrayFifoConfiguration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayTopology			
Note	One First In First Out (FIFO) queued receive structure, defining the admittance criteria to the FIFO, and mandating the ability to admit messages into the FIFO based on Message Id filtering criteria.			
Base	ARObject			
Aggregated by	FlexrayCommunicationController.flexrayFifo			
Attribute	Type	Mult.	Kind	Note
admitWithoutMessageld	Boolean	0..1	attr	Boolean configuration which determines whether or not frames received in the dynamic segment that don't contain a message ID will be admitted into the FIFO.
baseCycle	Integer	0..1	attr	FIFO cycle counter acceptance criteria.
channel	FlexrayPhysicalChannel	0..1	ref	Fifo channel admittance criteria.
cycleRepetition	Integer	0..1	attr	FIFO cycle counter acceptance criteria.
fifoDepth	Integer	0..1	attr	FrFifoDepth configures the maximum number of rx-frames which can be contained in the FIFO.
fifoRange	FlexrayFifoRange	*	aggr	FIFO Frame Id range acceptance criteria.
msgIdMask	Integer	0..1	attr	FIFO message identifier acceptance criteria (Mask filter).
msgIdMatch	Integer	0..1	attr	FIFO message identifier acceptance criteria (Match filter).

Table A.555: FlexrayFifoConfiguration

Class	FlexrayFifoRange			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayTopology			
Note	FIFO Frame Id range acceptance criteria.			
Base	ARObject			
Aggregated by	FlexrayFifoConfiguration.fifoRange			
Attribute	Type	Mult.	Kind	Note
rangeMax	Integer	0..1	attr	Max Range.
rangeMin	Integer	0..1	attr	Min Range.

Table A.556: FlexrayFifoRange

Class	FlexrayFrame			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayCommunication			
Note	FlexRay specific Frame element. Tags: atp.recommendedPackage=Frames			
Base	ARObject, CollectableElement, FibexElement, Frame, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.557: FlexrayFrame

Class	FlexrayFrameTriggering			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayCommunication			
Note	FlexRay specific attributes to the FrameTriggering			
Base	ARObject, FrameTriggering, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	PhysicalChannel.frameTriggering			
Attribute	Type	Mult.	Kind	Note
absolutely Scheduled Timing	FlexrayAbsolutely ScheduledTiming	*	aggr	Specification of a sending behaviour where the exact time for the frames transmission is guaranteed.
allowDynamic LSduLength	Boolean	0..1	attr	Allows L-PDU length reduction and indicates that the related CC buffer has to be reconfigured for the actual length and Header-CRC before transmission of the L-PDU. If this attribute is set to true than the referenced Frame length attribute defines the max. length.
messageld	PositiveInteger	0..1	attr	The first two bytes of the payload segment of the FlexRay frame format for frames transmitted in the dynamic segment can be used as receiver filterable data called the message ID.
payload Preamble Indicator	Boolean	0..1	attr	Switching the Payload Preamble bit.

Table A.558: FlexrayFrameTriggering

Class	FlexrayNmCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	FlexRay specific NM cluster attributes.			
Base	ARObject, Identifiable, MultilanguageReferrable, NmCluster, Referrable			
Aggregated by	NmConfig.nmCluster			
Attribute	Type	Mult.	Kind	Note
nmCarWakeUp BitPosition	PositiveInteger	0..1	attr	Specifies the bit position of the CarWakeUp within the Nm Pdu.
nmCarWakeUp FilterEnabled	Boolean	0..1	attr	If this attribute is set to true the CareWakeUp filtering is supported. In this case only the CarWakeUp bit within the NmPdu with source node identifier nmCarWakeUpFilter NodeId is considered as CarWakeUp request.





Class	FlexrayNmCluster			
nmCarWakeUpFilterNodeId	PositiveInteger	0..1	attr	Source node identifier for CarWakeUp filtering. If CarWakeUp filtering is supported (nmCarWakeUpFilterEnabled), only the CarWakeUp bit within the NmPdu with source node identifier nmCarWakeUpFilterNodeId is considered as CarWakeUp request.
nmCarWakeUpRxEnabled	Boolean	0..1	attr	If set to true this attribute enables the support of CarWakeUp bit evaluation in received NmPdus.
nmDataCycle	Integer	0..1	attr	Number of FlexRay Communication Cycles needed to transmit the Nm Data PDUs of all FlexRay Nm Ecus of this FlexRayNmCluster.
nmMainFunctionPeriod	TimeValue	0..1	attr	Defines the processing cycle of the main function of FrNm module.
nmRemoteSleepIndicationTime	TimeValue	0..1	attr	Timeout for Remote Sleep Indication in seconds. It defines the time how long it shall take to recognize that all other nodes are ready to sleep.
nmRepeatMessageTime	TimeValue	0..1	attr	Timeout for Repeat Message State in seconds. Defines the time how long the NM shall stay in the Repeat Message State.
nmRepetitionCycle	Integer	0..1	attr	Number of FlexRay Communication Cycles used to repeat the transmission of the Nm vote Pdus of all FlexRay NmEcus of this FlexRayNmCluster. This value shall be an integral multiple of nmVotingCycle.
nmVotingCycle	Integer	0..1	attr	Number of FlexRay CommunicationCycles needed to transmit the Nm vote of Pdus of all FlexRay NmEcus of this FlexRayNmCluster.

Table A.559: FlexrayNmCluster

Class	FlexrayNmClusterCoupling			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	FlexRay attributes that are valid for each of the referenced (coupled) FlexRay clusters.			
Base	ARObject, NmClusterCoupling			
Aggregated by	NmConfig.nmClusterCoupling			
Attribute	Type	Mult.	Kind	Note
coupledCluster	FlexrayNmCluster	*	ref	Reference to coupled FlexRay Clusters.
nmScheduleVariant	FlexrayNmScheduleVariant	0..1	attr	FrNm schedule variant according to FrNm SWS.

Table A.560: FlexrayNmClusterCoupling

Class	FlexrayPhysicalChannel			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Flexray::FlexrayTopology			
Note	FlexRay specific attributes to the physicalChannel			
Base	ARObject, Identifiable, MultilanguageReferrable, PhysicalChannel, Referrable			
Aggregated by	CommunicationCluster.physicalChannel			
Attribute	Type	Mult.	Kind	Note
channelName	FlexrayChannelName	0..1	attr	Name of the channel (Channel A or Channel B).

Table A.561: FlexrayPhysicalChannel

Class	FlexrayTpConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	<p>This element defines exactly one FlexRay ISO TP Configuration.</p> <p>One FlexRayTpConfig element shall be created for each FlexRay Network in the System that uses Flex Ray Iso Tp.</p> <p>Tags: atp.recommendedPackage=TpConfigs</p>			
Base	<i>ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable, TpConfig</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pduPool	FlexrayTpPduPool	*	aggr	<p>Configuration of FlexRay TP Pdu Pools.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=pduPool.shortName, pduPool.variation Point.shortLabel vh.latestBindingTime=postBuild</p>
tpAddress	TpAddress	*	aggr	<p>Collection of TpAddresses.</p> <p>atpVariation: Derived, because EcuInstance can vary.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpAddress.shortName, tpAddress.variation Point.shortLabel vh.latestBindingTime=postBuild</p>
tpConnection	FlexrayTpConnection	*	aggr	<p>Configuration of FlexRay TP Connections.</p> <p>atpVariation: Derived, because TpNode can vary.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpConnection, tpConnection.variation Point.shortLabel vh.latestBindingTime=postBuild</p>
tpConnection Control	FlexrayTpConnection Control	*	aggr	<p>Configuration of FlexRay TP Connection Controls.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpConnectionControl.shortName, tp ConnectionControl.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
tpEcu	FlexrayTpEcu	*	aggr	<p>Collection of TP Ecus</p> <p>atpVariation: Derived, because EcuInstance can vary.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpEcu, tpEcu.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
tpNode	FlexrayTpNode	*	aggr	<p>Senders and receivers of FlexRay TP messages.</p> <p>atpVariation: Derived, because EcuInstance can vary.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=tpNode.shortName, tpNode.variation Point.shortLabel vh.latestBindingTime=postBuild</p>

Table A.562: FlexrayTpConfig

Class	FlexrayTpConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	<p>A connection identifies the sender and the receiver of this particular communication. The FlexRayTp module routes a Pdu through this connection.</p> <p>In a System Description the references to the PduPools are mandatory. In an ECU Extract these references can be optional: On unicast connections these references are always mandatory. On multicast the txPduPool is mandatory on the sender side. The rxPduPool is mandatory on the receiver side. On Gateway ECUs both references are mandatory.</p>			
Base	ARObject, TpConnection			
Aggregated by	FlexrayTpConfig.tpConnection			
Attribute	Type	Mult.	Kind	Note
bandwidthLimitation	Boolean	0..1	attr	Specifies whether the connection requires a bandwidth limitation or not.
directTpSdu	IPdu	0..1	ref	Reference to the IPdu that is segmented by the Transport Protocol.
multicast	TpAddress	0..1	ref	TP address for 1:n connections.
receiver	FlexrayTpNode	*	ref	The target of the TP connection.
reversedTpSdu	IPdu	0..1	ref	Reference to the IPdu that is segmented by the Transport Protocol. If support of both sending and receiving is used, this association references the IPdu used for the additional second direction.
rxPduPool	FlexrayTpPduPool	0..1	ref	<p>A connection has a reference to a set of NPdus (FrTpRx PduPool) which are defined for receiving data via this particular connection.</p> <p>The following constraint is valid only for the System Extract/ECU Extract: In case this connection is applied to the transmitter the rxPduPool holds the actually received NPdus. In case this connection is applied to the receiver the rxPduPool holds the actually sent NPdus.</p>
tpConnectionControl	FlexrayTpConnectionControl	0..1	ref	Reference to the connection control.
transmitter	FlexrayTpNode	0..1	ref	The source of the TP connection.
txPduPool	FlexrayTpPduPool	0..1	ref	<p>A connection has a reference to a set of NPdus (FrTpTx PduPool) which are defined for sending data via this particular connection.</p> <p>The following constraint is valid only for the System Extract/ECU Extract: In case this connection is applied to the transmitter the txPduPool holds the actually sent NPdus. In case this connection is applied to the receiver the txPduPool holds the actually received NPdus.</p>

Table A.563: FlexrayTpConnection

Class	FlexrayTpConnectionControl			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	Configuration parameters to control a FlexRay TP connection.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	FlexrayTpConfig.tpConnectionControl			
Attribute	Type	Mult.	Kind	Note
ackType	TpAckType	0..1	attr	This parameter defines the type of acknowledgement which is used for the specific channel.
maxFcWait	Integer	0..1	attr	This attribute defines the maximum number of Flow Control N-PDUs with FlowState "WAIT".





Class	FlexrayTpConnectionControl			
maxNumberOfNpduPerCycle	Integer	0..1	attr	This parameter limits the number of N-Pdus the sender is allowed to transmit within a FlexRay cycle.
maxRetries	Integer	0..1	attr	This parameter defines the maximum number of retries (if retry is configured for the particular channel).
separationCycleExponent	Integer	0..1	attr	Exponent to calculate the minimum number of "Separation Cycles" the sender has to wait for the next transmission of an FrTp N-Pdu.
timeBr	TimeValue	0..1	attr	Time (in seconds) until transmission of the next Flow Control N-PDU.
timeBuffer	TimeValue	0..1	attr	This parameter defines the time of waiting for the next try to get a Tx or Rx buffer. This parameter is equivalent to the temporal distance between two FC.WT N-Pdus in case the buffer request returns busy. Specified in seconds.
timeCs	TimeValue	0..1	attr	Time (in seconds) until transmission of the next ConsecutiveFrame NPdu / LastFrame NPdu.
timeoutAr	TimeValue	0..1	attr	This parameter states the timeout between the PDU transmit request of the Transport Layer to the FlexRay Interface and the corresponding confirmation of the Flex Ray Interface on the receiver side (for FC or AF). Specified in seconds.
timeoutAs	TimeValue	0..1	attr	This attribute states the timeout between the PDU transmit request for the first PDU of the group used in the current connection of the Transport Layer to the FlexRay Interface and the corresponding confirmation of the Flex Ray Interface (when having sent the last PDU of the group used in this connection) on the sender side (SF-x, FF-x, CF or FC (in case of Transmit Cancellation)). Specified in seconds.
timeoutBs	TimeValue	0..1	attr	This parameter defines the timeout in seconds for waiting for an FC or AF on the sender side in a 1:1 connection.
timeoutCr	TimeValue	0..1	attr	This parameter defines the timeout value in seconds for waiting for a CF or FF-x (in case of retry) after receiving the last CF or after sending an FC or AF on the receiver side. Specified in seconds.

Table A.564: FlexrayTpConnectionControl

Class	FlexrayTpEcu			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	ECU specific TP configuration parameters. Each TpEcu element has a reference to exactly one ECUInstance in the topology.			
Base	ARObject			
Aggregated by	FlexrayTpConfig.tpEcu			
Attribute	Type	Mult.	Kind	Note
cancellation	Boolean	0..1	attr	With this switch Tx and Rx Cancellation can be turned on or off.
cycleTimeMainFunction	TimeValue	0..1	attr	The period between successive calls to the Main Function of the AUTOSAR TP. Specified in seconds.
ecuInstance	EcuInstance	0..1	ref	Connection to the ECUInstance in the Topology
fullDuplexEnabled	Boolean	0..1	attr	The full duplex mechanisms is enabled if this attribute is set to true. Otherwise half duplex is enabled.

Table A.565: FlexrayTpEcu

Class	FlexrayTpNode			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	TP Node (Sender or Receiver) provides the TP Address and the connection to the Topology description.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	FlexrayTpConfig.tpNode			
Attribute	Type	Mult.	Kind	Note
connector	Communication Connector	*	ref	Association to one or more physical connectors (max number of connectors for FlexRay: 2). In a System Description this reference is mandatory. In an ECU Extract this reference is optional (references to ECUs that are not part of the ECU Extract shall be avoided).
tpAddress	TpAddress	0..1	ref	Reference to the TP Address that is used by the TpNode. This reference is optional in case that the multicast TP Address is used (reference from TpConnection).

Table A.566: FlexrayTpNode

Class	FlexrayTpPduPool			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	FlexrayTpPduPool is a set of N-PDUs which are defined for FrTp sending or receiving purpose.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	FlexrayTpConfig.pduPool			
Attribute	Type	Mult.	Kind	Note
nPdu	NPdu	*	ref	Reference to NPdus that are part of the PduPool.

Table A.567: FlexrayTpPduPool

Class	ForbiddenSignalPath			
Package	M2::AUTOSARTemplates::SystemTemplate::SignalPaths			
Note	The ForbiddenSignalPath describes the physical channels which an element shall not take in the topology. Such a signal path can be a constraint for the communication matrix, because such a path has an effect on the frame generation and the frame path.			
Base	ARObject, SignalPathConstraint			
Aggregated by	SystemMapping.signalPathConstraint			
Attribute	Type	Mult.	Kind	Note
operation	SwcToSwcOperation Arguments	*	aggr	Reference to the operation arguments of one operation which shall not take the predefined way in the topology.
physical Channel	PhysicalChannel	*	ref	The SwcToSwcSignal shall not be transmitted on one of these physical channels.
signal	SwcToSwcSignal	*	aggr	The data element which shall not take the predefined way in the topology.

Table A.568: ForbiddenSignalPath

Class	Frame (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Data frame which is sent over a communication medium. This element describes the pure Layout of a frame sent on a channel.			





Class	Frame (abstract)			
Base	ARObject , CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	AbstractEthernetFrame , CanFrame , FlexrayFrame , LinFrame			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
frameLength	Integer	0..1	attr	The used length (in bytes) of the referencing frame. Should not be confused with a static byte length reserved for each frame by some platforms (e.g. FlexRay). The frameLength of zero bytes is allowed. Please consider also TPS_SYST_02255.
pduToFrame Mapping	PduToFrameMapping	*	aggr	A frames layout as a sequence of Pdus. atpVariation: The content of a frame can be variable. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=pduToFrameMapping.shortName, pduToFrameMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.569: Frame

Class	FrameMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Multiplatform			
Note	Maps the source frame to the target frame.			
Base	ARObject			
Aggregated by	Gateway.frameMapping			
Attribute	Type	Mult.	Kind	Note
introduction	DocumentationBlock	0..1	aggr	This represents introductory documentation about the frame mapping.
sourceFrame	FrameTriggering	0..1	ref	Source destination of the referencing mapping.
targetFrame	FrameTriggering	0..1	ref	Target destination of the referencing mapping.

Table A.570: FrameMapping

Class	FramePid			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Frame_PIDs that are included in the request. The "pid" attribute describes the value and the "index" attribute the position of the frame_PID in the request.			
Base	ARObject			
Aggregated by	AssignFrameIdRange.framePid			
Attribute	Type	Mult.	Kind	Note
index	Integer	0..1	attr	This attribute is used to order the frame_PIDs. The values of index shall be unique within one AssignFrameIdRange.
pid	PositiveInteger	0..1	attr	Frame_PID value.

Table A.571: FramePid

Class	FramePort			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Connectors reception or send port on the referenced channel referenced by a FrameTriggering.			
Base	ARObject, CommConnectorPort , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CommunicationConnector.ecuCommPortInstance			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.572: FramePort

Class	FrameTriggering (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>The FrameTriggering describes the instance of a frame sent on a channel and defines the manner of triggering (timing information) and identification of a frame on the channel, on which it is sent.</p> <p>For the same frame, if FrameTriggerings exist on more than one channel of the same cluster the fan-out/in is handled by the Bus interface.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	CanFrameTriggering , EthernetFrameTriggering , FlexrayFrameTriggering , LinFrameTriggering			
Aggregated by	PhysicalChannel.frameTriggering			
Attribute	Type	Mult.	Kind	Note
frame	Frame	0..1	ref	One frame can be triggered several times, e.g. on different channels. If a frame has no frame triggering, it won't be sent at all. A frame triggering has assigned exactly one frame, which it triggers.
framePort	FramePort	*	ref	References to the FramePort on every ECU of the system which sends and/or receives the frame. References for both the sender and the receiver side shall be included when the system is completely defined.
pduTriggering	PduTriggering	*	ref	<p>This reference provides the relationship to the Pdu Triggerings that are implemented by the FrameTriggering. The reference is optional since no PduTriggering can be defined for NmPdus and XCP Pdus.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=pduTriggering.pduTriggering, pduTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>

Table A.573: FrameTriggering

Class	FreeFormat			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Representing freely defined data.			
Base	ARObject, FreeFormatEntry , ScheduleTableEntry			
Aggregated by	LinScheduleTable.tableEntry			
Attribute	Type	Mult.	Kind	Note
byteValue (ordered)	Integer	*	attr	The integer Value of a freely defined data byte.

Table A.574: FreeFormat

Class	FunctionInhibitionNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs on the configuration of the Function Inhibition Manager for one Function Identifier (FID). This class currently contains no attributes. Its name can be regarded as a symbol identifying the FID from the viewpoint of the component or module which owns this class.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.575: FunctionInhibitionNeeds

Class	Gateway			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Multiplatform			
Note	A gateway is an ECU that is connected to two or more clusters (channels, but not redundant), and performs a frame, Pdu or signal mapping between them. Tags: atp.recommendedPackage=Gateways			
Base	ARObject, CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
ecu	EcuInstance	0..1	ref	Reference to one ECU instance that implements the gateway.
frameMapping	FrameMapping	*	aggr	Frame Gateway: The entire source frame is mapped as it is onto the target frame (what in general is only possible inside of a common platform). In this case source and target frame should be the identical object. atpVariation: If frames are variable in clusters, the gateway frame mapping needs to be variable, too. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=frameMapping, frameMapping.variation Point.shortLabel vh.latestBindingTime=postBuild
iPduMapping	IPduMapping	*	aggr	IPdu Gateway: Arranges those IPdus that are transferred by the gateway from one channel to the other in pairs and defines the mapping between them. atpVariation: If PDUs are variable in clusters, the gateway PDU mapping needs to be variable, too. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=iPduMapping, iPduMapping.variation Point.shortLabel vh.latestBindingTime=postBuild
signalMapping	ISignalMapping	*	aggr	Signal Gateway: Arranges those signals that are transferred by the gateway from one channel to the other in pairs and defines the mapping between them. atpVariation: If signals are variable in clusters, the gateway signal mapping needs to be variable, too. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=signalMapping, signalMapping.variation Point.shortLabel vh.latestBindingTime=postBuild

Table A.576: Gateway

Class	GeneralPurposeConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::GeneralPurposeConnection			
Note	This meta-class allows to describe the relationship between several PduTriggerings that are defined on the same PhysicalChannel, e.g. to create a link between Rx and Tx Pdu that are used for request/response. Tags: atp.recommendedPackage=GeneralPurposeConnections			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
pduTriggering	PduTriggering	*	ref	Reference to PduTriggerings that are connected to each other by a GeneralPurposeConnection.

Table A.577: GeneralPurposeConnection

Class	GeneralPurposeIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	This element is used for AUTOSAR Pdus without attributes that are routed by the PduR. Please note that the category name of such Pdus is standardized in the AUTOSAR System Template. Tags: atp.recommendedPackage=Pdus			
Base	ARElement, ARObject, CollectableElement, FibexElement , IPdu , Identifiable , MultilanguageReferrable , PackageableElement , Pdu , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.578: GeneralPurposeIPdu

Class	GeneralPurposePdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	This element is used for AUTOSAR Pdus without additional attributes that are routed by a bus interface. Please note that the category name of such Pdus is standardized in the AUTOSAR System Template. Tags: atp.recommendedPackage=Pdus			
Base	ARElement, ARObject, CollectableElement, FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Pdu , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.579: GeneralPurposePdu

Class	GenericTp			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Content Model for a generic transport protocol. Tags: atp.Status=obsolete			
Base	ARObject, TransportProtocolConfiguration			
Aggregated by	ApplicationEndpoint.tpConfiguration			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–





Class	GenericTp			
tpAddress	String	0..1	attr	Transport Protocol dependent Address. Tags: atp.Status=obsolete
tpTechnology	String	0..1	attr	Name of the used Transport Protocol. Tags: atp.Status=obsolete

Table A.580: GenericTp

Class	GlobalTimeCanMaster			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::CAN			
Note	This represents the specialization of the GlobalTimeMaster for the CAN communication.			
Base	ARObject, GlobalTimeMaster , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalTimeDomain.globalTimeMaster			
Attribute	Type	Mult.	Kind	Note
crcSecured	GlobalTimeCrcSupportEnum	0..1	attr	Definition of whether or not CRC is supported. This is only relevant for selected bus systems.
syncConfirmationTimeout	TimeValue	0..1	attr	This represents the value for the confirmation timeout. Unit: seconds.

Table A.581: GlobalTimeCanMaster

Class	GlobalTimeCanSlave			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::CAN			
Note	This represents the specialization of the GlobalTimeSlave for the CAN communication.			
Base	ARObject, GlobalTimeSlave , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalTimeDomain.slave			
Attribute	Type	Mult.	Kind	Note
crcValidated	GlobalTimeCrcValidationEnum	0..1	attr	Definition of whether or not validation of the CRC is supported.
sequenceCounterJumpWidth	PositiveInteger	0..1	attr	Specifies the maximum allowed gap of the sequence counter between two SYNC resp. two OFS messages.

Table A.582: GlobalTimeCanSlave

Class	GlobalTimeCouplingPortProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines properties for the usage of the CouplingPort in the scope of Global Time Sync.			
Base	ARObject			
Aggregated by	CouplingPortDetails.globalTimeProps			
Attribute	Type	Mult.	Kind	Note
propagationDelay	TimeValue	0..1	attr	If cyclic propagation delay measurement is enabled, this parameter represents the default value of the propagation delay until the first actually measured propagation delay is available. If cyclic propagation delay measurement is disabled, this parameter defines a fixed value for the propagation delay.

Table A.583: GlobalTimeCouplingPortProps

Class	GlobalTimeDomain			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime			
Note	This represents the ability to define a global time domain. Tags: atp.recommendedPackage=GlobalTimeDomains			
Base	ARElement, ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
debounceTime	TimeValue	0..1	attr	Defines the minimum amount of time between two time sync messages are transmitted.
domainId	PositiveInteger	0..1	attr	This represents the ID of the GlobalTimeDomain used in the network messages sent on behalf of global time management.
gateway	GlobalTimeGateway	*	aggr	A GlobalTimeGateway may exist in the context of a GlobalTimeDomain to actively update the global time information as it is routed from one GlobalTimeDomain to another. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=gateway.shortName, gateway.variationPoint.shortLabel vh.latestBindingTime=postBuild
globalTimeCorrectionProps	GlobalTimeCorrectionProps	0..1	aggr	Defintion of attributes for rate and offset correction.
globalTimeDomainProperty	AbstractGlobalTimeDomainProps	0..1	aggr	Additional properties of the GlobalTimeDomain. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=globalTimeDomainProperty, globalTimeDomainProperty.variationPoint.shortLabel vh.latestBindingTime=postBuild
globalTimeMaster	GlobalTimeMaster	0..1	aggr	This represents the single master of a GlobalTimeDomain. A GlobalTimeDomain may have no GlobalTimeDomain.master, e.g. when it gets its time from a GPS receiver. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=globalTimeMaster.shortName, globalTimeMaster.variationPoint.shortLabel vh.latestBindingTime=postBuild
globalTimeSubDomain	GlobalTimeDomain	*	ref	By this means it is possible to create a hierarchy of sub Domains where one global time domain can declare one or more other global time domains as its subDomains. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=globalTimeSubDomain.globalTimeDomain, globalTimeSubDomain.variationPoint.shortLabel vh.latestBindingTime=postBuild
icvFreshnessValueId	PositiveInteger	0..1	attr	This attribute defines the Id of the Freshness Value for the Integrity Check Value (ICV) calculation and verification.
icvSecureComProps	SecOcSecureComProps	0..1	ref	Reference to a SecureComProps definition to be used for the Integrity Check Value (ICV) calculation and verification. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=icvSecureComProps.secOcSecureComProps, icvSecureComProps.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	GlobalTimeDomain			
maxProgressionMismatchThreshold	TimeValue	0..1	attr	This attribute defines the maximum allowed difference between local time and fallback time of the time base in seconds.
networkSegmentId	NetworkSegmentIdentification	0..1	aggr	Defines the numerical identification of a GlobalTime sub domain.
pduTriggering	PduTriggering	0..1	ref	This PduTriggering will be taken to transmit the global time information from a GlobalTimeMaster to a the associated GlobalTimeSlaves. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=pduTriggering.pduTriggering, pduTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild
slave	GlobalTimeSlave	*	aggr	This represents the collections of slaves of the Global TimeDomain. A GlobalTimeDomain may have no Global TimeDomain.slaves, e.g. when it propagates its time directly to sub domains. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=slave.shortName, slave.variationPoint.shortLabel vh.latestBindingTime=postBuild
syncLossTimeout	TimeValue	0..1	attr	This attribute describes the timeout for the situation that the time synchronization gets lost in the scope of the time domain.

Table A.584: GlobalTimeDomain

Class	GlobalTimeEthMaster			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::ETH			
Note	This represents the specialization of the GlobalTimeMaster for Ethernet communication.			
Base	<i>ARObject</i> , GlobalTimeMaster , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalTimeDomain.globalTimeMaster			
Attribute	Type	Mult.	Kind	Note
crcSecured	GlobalTimeCrcSupportEnum	0..1	attr	Definition of whether or not CRC is supported. This is only relevant for selected bus systems.
holdOverTime	TimeValue	0..1	attr	This attribute defines the timeout for transmission of Sync and Follow_Up messages on Master ports in absence of reception of Sync and Follow_Up messages on Slave port.
subTlvConfig	EthTSynSubTlvConfig	0..1	aggr	Defines the subTLV fields which shall be included in the time sync message.

Table A.585: GlobalTimeEthMaster

Class	GlobalTimeFrMaster			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::FR			
Note	This represents the specialization of the GlobalTimeMaster for Flexray communication.			
Base	<i>ARObject</i> , GlobalTimeMaster , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalTimeDomain.globalTimeMaster			
Attribute	Type	Mult.	Kind	Note
crcSecured	GlobalTimeCrcSupportEnum	0..1	attr	Definition of whether or not CRC is supported. This is only relevant for selected bus systems.

Table A.586: GlobalTimeFrMaster

Class	GlobalTimeFrSlave			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::FR			
Note	This represents the specialization of the GlobalTimeSlave for Flexray communication.			
Base	ARObject, GlobalTimeSlave , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalTimeDomain.slave			
Attribute	Type	Mult.	Kind	Note
crcValidated	GlobalTimeCrc ValidationEnum	0..1	attr	Definition of whether or not validation of the CRC is supported.
sequence CounterJump Width	PositiveInteger	0..1	attr	Specifies the maximum allowed gap of the sequence counter between two SYNC resp. two OFS messages.

Table A.587: GlobalTimeFrSlave

Class	GlobalTimeGateway			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime			
Note	This represents the ability to define a time gateway for establishing a global time domain over several communication clusters.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	GlobalTimeDomain.gateway			
Attribute	Type	Mult.	Kind	Note
host	EcuInstance	0..1	ref	The GlobalTimeGateway is hosted by the referenced Ecu Instance.
master	GlobalTimeMaster	0..1	ref	This represents the master of the global time gateway.
slave	GlobalTimeSlave	0..1	ref	This represents the slave of the GlobalTimeGateway.

Table A.588: GlobalTimeGateway

Class	GlobalTimeMaster (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime			
Note	This represents the generic concept of a global time master.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	GlobalTimeCanMaster , GlobalTimeEthMaster , GlobalTimeFrMaster , UserDefinedGlobalTimeMaster			
Aggregated by	GlobalTimeDomain.globalTimeMaster			
Attribute	Type	Mult.	Kind	Note
communication Connector	Communication Connector	0..1	ref	The GlobalTimeMaster is bound to the Communication Connector.
icvSecured	GlobalTimeIcvSupport Enum	0..1	attr	Defines whether an Integrity Check Value (ICV) shall be added to the sent time sync messages. Tags: atp.Status=candidate
immediate ResumeTime	TimeValue	0..1	attr	Defines the minimum time between an "immediate" message and the next periodic message.
isSystemWide GlobalTime Master	Boolean	0..1	attr	If set to TRUE, the GlobalTimeMaster is supposed to act as the root of global time information.
syncPeriod	TimeValue	0..1	attr	This represents the period. Unit: seconds

Table A.589: GlobalTimeMaster

Enumeration	GlobalTimePortRoleEnum
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime::ETH
Note	Selection of port behavior to Time Slave, Time Master or Dynamic (Time Slave or Time Master at runtime).
Aggregated by	EthGlobalTimeManagedCouplingPort.globalTimePortRole
Literal	Description
dynamic	Time Slave or Time Master port behavior at runtime. Tags: atp.EnumerationLiteralIndex=2
timeMaster	timeMaster port behavior Tags: atp.EnumerationLiteralIndex=1
timeSlave	TimeSlave port behavior Tags: atp.EnumerationLiteralIndex=0

Table A.590: GlobalTimePortRoleEnum

Class	GlobalTimeSlave (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime			
Note	This represents the generic concept of a global time slave.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	GlobalTimeCanSlave , GlobalTimeEthSlave , GlobalTimeFrSlave , UserDefinedGlobalTimeSlave			
Aggregated by	GlobalTimeDomain.slave			
Attribute	Type	Mult.	Kind	Note
communicationConnector	CommunicationConnector	0..1	ref	The GlobalTimeSlave is bound to the Communication Connector.
followUpTimeoutValue	TimeValue	0..1	attr	Rx timeout for the follow-up message.
icvVerification	GlobalTimeIcvVerificationEnum	0..1	attr	Defines how an Integrity Check Value (ICV) shall be handled at the receiver. Tags: atp.Status=candidate
timeLeapFutureThreshold	TimeValue	0..1	attr	Defines the maximum allowed positive difference between the current Local Time Base value and a newly received Global Time Base value.
timeLeapHealingCounter	PositiveInteger	0..1	attr	Defines the required number of updates to the Time Base where the time difference to the previous received value has to remain within the bounds of timeLeapFutureThreshold and timeLeapPastThreshold until that Time Base is considered healed.
timeLeapPastThreshold	TimeValue	0..1	attr	Defines the maximum allowed negative difference between the current Local Time Base value and a newly received Global Time Base value.

Table A.591: GlobalTimeSlave

Enumeration	HandleInvalidEnum
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication
Note	Strategies of handling the reception of invalidValue.
Aggregated by	InvalidationPolicy.handleInvalid , ISignalPort.handleInvalid
Literal	Description
dontInvalidate	Invalidation is switched off. Tags: atp.EnumerationLiteralIndex=0





Enumeration	HandleInvalidEnum
external Replacement	Replace a received invalidValue. The replacement value is sourced from the aggregation in the role replaceWith. Tags: atp.EnumerationLiteralIndex=1
keep	The application software is supposed to handle signal invalidation on RTE API level either by Data ReceiveErrorEvent or check of error code on read access. Tags: atp.EnumerationLiteralIndex=2
replace	Replace a received invalidValue. The replacement value is specified by the initValue. Tags: atp.EnumerationLiteralIndex=3

Table A.592: HandleInvalidEnum

Enumeration	HandleOutOfRangeEnum
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication
Note	A value of this type is taken for controlling the range checking behavior of the AUTOSAR RTE.
Aggregated by	ISignalProps.handleOutOfRange, ReceiverComSpec.handleOutOfRange , SenderComSpec.handleOutOfRange
Literal	Description
default	The RTE will use the initValue if the actual value is out of the specified bounds. Tags: atp.EnumerationLiteralIndex=0
external Replacement	This indicates that the value replacement is sourced from the attribute replaceWith. Tags: atp.EnumerationLiteralIndex=1
ignore	The RTE will ignore any attempt to send or receive the corresponding dataElement if the value is out of the specified range. Tags: atp.EnumerationLiteralIndex=2
invalid	The RTE will use the invalidValue if the value is out of the specified bounds. Tags: atp.EnumerationLiteralIndex=3
none	A range check is not required. Tags: atp.EnumerationLiteralIndex=4
saturate	The RTE will saturate the value of the dataElement such that it is limited to the applicable upper bound if it is greater than the upper bound. Consequently, it is limited to the applicable lower bound if the value is less than the lower bound. Tags: atp.EnumerationLiteralIndex=5

Table A.593: HandleOutOfRangeEnum

Class	HardwareConfiguration			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption			
Note	Describes in which mode the hardware is operating while needing this resource consumption.			
Base	ARObject			
Aggregated by	ExecutionTime.hardwareConfiguration , HeapUsage.hardwareConfiguration , StackUsage.hardwareConfiguration			
Attribute	Type	Mult.	Kind	Note
additional Information	String	0..1	attr	Specifies additional information on the Hardware Configuration.
processorMode	String	0..1	attr	Specifies in which mode the processor is operating.
processor Speed	String	0..1	attr	Specifies the speed the processor is operating.

Table A.594: HardwareConfiguration

Class	HttpTp			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Http over TCP as transport protocol. Tags: atp.Status=obsolete			
Base	ARObject, TransportProtocolConfiguration			
Aggregated by	ApplicationEndpoint.tpConfiguration			
Attribute	Type	Mult.	Kind	Note
contentType	String	0..1	attr	Descriptor for the transported content. Tags: atp.Status=obsolete
protocolVersion	String	0..1	attr	HTTP Protocol version (e.g. 1.1) Tags: atp.Status=obsolete
requestMethod	RequestMethodEnum	0..1	attr	HTTP request method to be used. Tags: atp.Status=obsolete
tcpTpConfig	TcpTp	0..1	aggr	TcpTp Configuration. Tags: atp.Status=obsolete
uri	UriString	0..1	attr	URI to be called. Tags: atp.Status=obsolete

Table A.595: HttpTp

Class	HwAttributeDef			
Package	M2::AUTOSARTemplates::EcuResourceTemplate::HwElementCategory			
Note	This metaclass represents the ability to define a particular hardware attribute. The category of this element defines the type of the attributeValue. If the category is Enumeration the hw AttributeEnumerationLiterals specify the available literals.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	HwCategory.hwAttributeDef			
Attribute	Type	Mult.	Kind	Note
hwAttributeLiteral	HwAttributeLiteralDef	*	aggr	The available EnumerationLiterals of the Enumeration definition. Only applicable if the category of the Hw AttributeDef equals Enumeration.
isRequired	Boolean	0..1	attr	This attribute specifies if the defined attribute value is required to be provided.
unit	Unit	0..1	ref	This association specifies the physical unit of the defined hardware attribute. This is optional due to the fact that there are textual attributes.

Table A.596: HwAttributeDef

Class	HwAttributeValue			
Package	M2::AUTOSARTemplates::EcuResourceTemplate::HwElementCategory			
Note	This metaclass represents the ability to assign a hardware attribute value. Note that v and vt are mutually exclusive.			
Base	ARObject			
Aggregated by	HwDescriptionEntity.hwAttributeValue			
Attribute	Type	Mult.	Kind	Note
annotation	Annotation	0..1	aggr	Optional annotation that can be added to each Hw AttributeValue.





Class	HwAttributeValue			
hwAttributeDef	HwAttributeDef	0..1	ref	This association represents the definition of the particular hardware attribute value.
v	Numerical	0..1	attr	This represents a numerical hardware attribute value. Stereotypes: atpVariation Tags: vh.latestBindingTime=systemDesignTime
vt	VerbatimString	0..1	attr	This represents a textual hardware attribute value.

Table A.597: HwAttributeValue

Class	HwDescriptionEntity (abstract)			
Package	M2::AUTOSARTemplates::EcuResourceTemplate			
Note	This meta-class represents the ability to describe a hardware entity.			
Base	ARObject , Referrable			
Subclasses	HwElement , HwPin , HwPinGroup , HwType			
Attribute	Type	Mult.	Kind	Note
hwAttribute Value	HwAttributeValue	*	aggr	This aggregation represents a particular hardware attribute value. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=hwAttribute Value, hwAttribute Value.variation Point.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=50
hwCategory	HwCategory	*	ref	One of the associations representing one particular category of the hardware entity. Tags: xml.sequenceOffset=30
hwType	HwType	0..1	ref	This association is used to assign an optional HwType which contains the common attribute values for all occurrences of this HwDescriptionEntity. Note that HwTypes can not be redefined and therefore shall not have a hwType reference.

Table A.598: HwDescriptionEntity

Class	HwElement			
Package	M2::AUTOSARTemplates::EcuResourceTemplate			
Note	This represents the ability to describe Hardware Elements on an instance level. The particular types of hardware are distinguished by the category. This category determines the applicable attributes. The possible categories and attributes are defined in HwCategory. Tags: atp.recommendedPackage=HwElements			
Base	ARElement , ARObject , CollectableElement , HwDescriptionEntity , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	HwElement			
hwElement Connection	HwElementConnector	*	aggr	<p>This represents one particular connection between two hardware elements.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=hwElementConnection, hwElement Connection.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=110</p>
hwPinGroup	HwPinGroup	*	aggr	<p>This aggregation is used to describe the connection facilities of a hardware element. Note that hardware element has no pins but only pingroups.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=hwPinGroup.shortName, hwPin Group.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=90</p>
nestedElement	HwElement	*	ref	<p>This association is used to establish hierarchies of hw elements. Note that one particular HwElement can be target of this association only once. I.e. multiple instantiation of the same HwElement is not supported (at any hierarchy level).</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=nestedElement.hwElement, nested Element.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=70</p>

Table A.599: HwElement

Class	HwElementConnector			
Package	M2::AUTOSARTemplates::EcuResourceTemplate			
Note	This meta-class represents the ability to connect two hardware elements. The details of the connection can be refined by hwPinGroupConnection.			
Base	<i>ARObject, Describable</i>			
Aggregated by	HwElement.hwElementConnection			
Attribute	Type	Mult.	Kind	Note
hwElement	HwElement	*	ref	This association connects two hardware elements.
hwPin Connection	HwPinConnector	*	aggr	<p>This represents one particular connection between two hardware pins. This connection shall be used if pin-to-pin-connection is to be described but no description of the connection between the hierarchical composition of HwPinGroups (using HwPinGroupConnector) is required.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=hwPinConnection, hwPin Connection.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=60</p>





Class	HwElementConnector			
hwPinGroup Connection	HwPinGroupConnector	*	aggr	<p>This represents one particular connection between two hardware pin groups.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=hwPinGroupConnection, hwPinGroupConnection.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=50</p>

Table A.600: HwElementConnector

Class	HwPinConnector			
Package	M2::AUTOSARTemplates::EcuResourceTemplate			
Note	This meta-class represents the ability to connect two pins.			
Base	<i>ARObject, Describable</i>			
Aggregated by	HwElementConnector.hwPinConnection , HwPinGroupConnector.hwPinConnection			
Attribute	Type	Mult.	Kind	Note
hwPin	HwPin	*	ref	This association connects two hardware pins.

Table A.601: HwPinConnector

Class	HwPinGroup			
Package	M2::AUTOSARTemplates::EcuResourceTemplate			
Note	This meta-class represents the ability to describe groups of pins which are used to connect hardware elements. This group acts as a bundle of pins. Thereby they allow to describe high level connections. Pin groups can even be nested.			
Base	<i>ARObject, HwDescriptionEntity, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	HwElement.hwPinGroup , HwPinGroupContent.hwPinGroup			
Attribute	Type	Mult.	Kind	Note
hwPinGroup Content	HwPinGroupContent	0..1	aggr	This aggregation describes the contained pins/pin groups.

Table A.602: HwPinGroup

Class	HwPinGroupConnector			
Package	M2::AUTOSARTemplates::EcuResourceTemplate			
Note	This meta-class represents the ability to connect two pin groups.			
Base	<i>ARObject, Describable</i>			
Aggregated by	HwElementConnector.hwPinGroupConnection			
Attribute	Type	Mult.	Kind	Note
hwPin Connection	HwPinConnector	*	aggr	<p>This represents one particular connection between two hardware pins. The connected pins shall match the connection provided by the parent hwPinGroup Connection.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=hwPinConnection, hwPinConnection.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime</p>
hwPinGroup	HwPinGroup	*	ref	This association connects two hardware pin groups.

Table A.603: HwPinGroupConnector

Class	HwPortMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::ECUResourceMapping			
Note	HwPortMapping specifies the hwCommunicationPort (defined in the ECU Resource Template) to realize the specified CommunicationConnector in a physical topology.			
Base	ARObject			
Aggregated by	ECUMapping.hwPortMapping			
Attribute	Type	Mult.	Kind	Note
communication Connector	Communication Connector	0..1	ref	Reference to the CommunicationConnector in the System Template
hw Communication Port	HwPinGroup	0..1	ref	Reference to the HwPinPortGroup of category CommunicationPort. The connection to the Hw CommunicationController is described in the Ecu Resource Description.

Table A.604: HwPortMapping

Class	HwType			
Package	M2::AUTOSARTemplates::EcuResourceTemplate::HwElementCategory			
Note	This represents the ability to describe Hardware types on an abstract level. The particular types of hardware are distinguished by the category. This category determines the applicable attributes. The possible categories and attributes are defined in HwCategory. Tags: atp.recommendedPackage=HwTypes			
Base	ARElement, ARObject, CollectableElement, HwDescriptionEntity, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.605: HwType

Class	IEEE1722TpAcfBus (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp::IEEE1722TpAcf			
Note	Abstract class to define various busses to be transported over a IEEE1722TP ACF connection. Tags: atp.Status=candidate			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	IEEE1722TpAcfCan, IEEE1722TpAcfLin			
Aggregated by	IEEE1722TpAcfConnection.acfTransportedBus			
Attribute	Type	Mult.	Kind	Note
acfPart	IEEE1722TpAcfBusPart	*	aggr	One part transported over IEEE1722Tp channel. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=acfPart.shortName, acfPart.variationPoint.shortLabel atp.Status=candidate vh.latestBindingTime=postBuild
busId	PositiveInteger	0..1	attr	Id of the transported bus over the ACF connection.

Table A.606: IEEE1722TpAcfBus

Class	IEEE1722TpAcfCan			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp::IEEE1722TpAcf			
Note	ACF IEEE1722Tp bus used for CAN transport. Tags: atp.Status=candidate atp.recommendedPackage=IEEE1722TpConnections			
Base	ARObject, IEEE1722TpAcfBus , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	IEEE1722TpAcfConnection.acfTransportedBus			
Attribute	Type	Mult.	Kind	Note
messageType	IEEE1722TpAcfCan MessageTypeEnum	0..1	attr	Definition of the ACF CAN stream message type.

Table A.607: IEEE1722TpAcfCan

Class	IEEE1722TpAcfCanPart			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp::IEEE1722TpAcf			
Note	Definition of one CAN part (frame or frame range) transported over the IEEE1722Tp channel. Tags: atp.Status=candidate			
Base	ARObject, IEEE1722TpAcfBusPart , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	IEEE1722TpAcfBus.acfPart			
Attribute	Type	Mult.	Kind	Note
canAddressingMode	CanAddressingMode Type	0..1	attr	Defines whether standard or extended address format shall be used.
canBitRateSwitch	Boolean	0..1	attr	Defines whether the bit rate switch bit shall be set.
canFrameTxBehavior	CanFrameTxBehaviorEnum	0..1	attr	Defines which CAN protocol shall be used for frame transmission.
canIdentifier	PositiveInteger	0..1	attr	Optional Can Id defined in case the Can Id can not be determined during runtime.
canIdentifierMask	PositiveInteger	0..1	attr	CAN identifier mask which denotes relevant bits in the CAN Identifier. This attribute defines a CAN Identifier range in an alternative way to canIdentifierRange. It identifies the bits of the configured CAN Identifier that must match the received CAN Identifier.
canIdentifierRange	RxIdentifierRange	0..1	aggr	Definition of the identifier range for IEEE1722Tp ACF Can messages. Tags: atp.Status=candidate
sdu	PduTriggering	0..1	ref	Reference to the Pdu transported in the IEEE1722Tp channel. Tags: atp.Status=candidate

Table A.608: IEEE1722TpAcfCanPart

Class	IEEE1722TpAcfConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp			
Note	ACF IEEE1722Tp connection. Tags: atp.Status=candidate atp.recommendedPackage=IEEE1722TpConnections			
Base	ARElement, ARObject, CollectableElement , IEEE1722TpConnection , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			





Class	IEEE1722TpAcfConnection			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
acfMaxTransitTime	TimeValue	0..1	attr	Defines the time offset that is added to the current time at the producer in order to get the "presentation time" (in seconds) when content shall be presented at the consumers.
acfTransportedBus	IEEE1722TpAcfBus	*	aggr	Definition of the transported busses over this ACF connection. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=acfTransportedBus.shortName, acfTransportedBus.variationPoint.shortLabel atp.Status=candidate vh.latestBindingTime=postBuild
collectionThreshold	PositiveInteger	0..1	attr	Defines the size threshold in bytes which, when exceeded, triggers the sending of the IEEE1722Tp ACF message, even when the maximum IEEE1722Tp ACF message size has not been reached yet.
collectionTimeout	TimeValue	0..1	attr	When this timeout expires the IEEE1722Tp ACF message is triggered for sending. The respective timer is started when the first Pdu is put into the IEEE1722Tp ACF message. Defined in seconds.
mixedBusTypeCollection	Boolean	0..1	attr	Defines if this ACF-stream is allowed to collect ACF-messages of different bus kinds (i.e. whether it is allowed to collect CAN and LIN ACF-messages in one ACF-stream message).

Table A.609: IEEE1722TpAcfConnection

Class	IEEE1722TpAcfLin			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp::IEEE1722TpAcf			
Note	ACF IEEE1722Tp bus used for LIN transport. Tags: atp.Status=candidate atp.recommendedPackage=IEEE1722TpConnections			
Base	ARObject , IEEE1722TpAcfBus , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	IEEE1722TpAcfConnection.acfTransportedBus			
Attribute	Type	Mult.	Kind	Note
baseFrequency	PositiveInteger	0..1	attr	CRF base frequency in Hz.
frameSyncEnabled	Boolean	0..1	attr	Defines whether the "fs" (frame sync) shall be enabled.
timestampInterval	PositiveInteger	0..1	attr	CRF timestamp interval as multiple of the baseFrequency.

Table A.610: IEEE1722TpAcfLin

Class	IEEE1722TpAcfLinPart			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp::IEEE1722TpAcf			
Note	Definition of one LIN part transported over the IEEE1722Tp channel. Tags: atp.Status=candidate			





Class	IEEE1722TpAcfLinPart			
Base	<i>ARObject, IEEE1722TpAcfBusPart, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	<i>IEEE1722TpAcfBus.acfPart</i>			
Attribute	Type	Mult.	Kind	Note
linIdentifier	PositiveInteger	0..1	attr	Optional Lin Id defined in case the Lin Id can not be determined during runtime. Tags: atp.Status=candidate
sdu	PduTriggering	0..1	ref	Reference to the Pdu transported in the IEEE1722Tp channel. Tags: atp.Status=candidate

Table A.611: IEEE1722TpAcfLinPart

Class	IEEE1722TpAvConnection (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp			
Note	AV IEEE1722Tp connection. Tags: atp.Status=candidate			
Base	<i>ARElement, ARObject, CollectableElement, IEEE1722TpConnection, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Subclasses	<i>IEEE1722TpAafConnection, IEEE1722TpCrfConnection, IEEE1722TplidcConnection, IEEE1722TpRvfConnection</i>			
Aggregated by	<i>ARPackage.element</i>			
Attribute	Type	Mult.	Kind	Note
maxTransitTime	TimeValue	0..1	attr	Defines the time offset that is added to the current time at the producer in order to get the "presentation time" (in seconds) when content shall be presented at the consumers.
sdu	PduTriggering	*	ref	Reference to the upper layer Sdu used for the transport of the payload of the IEEE1722Tp. Tags: atp.Status=candidate

Table A.612: IEEE1722TpAvConnection

Class	IEEE1722TpConnection (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols::IEEE1722Tp			
Note	Definition of the IEEE1722Tp protocol. Tags: atp.Status=candidate			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Subclasses	<i>IEEE1722TpAcfConnection, IEEE1722TpAvConnection</i>			
Aggregated by	<i>ARPackage.element</i>			
Attribute	Type	Mult.	Kind	Note
destinationMacAddress	MacAddressString	0..1	attr	Optional definition of the destination MAC address for this stream. If no given then macAddressStreamId is used as destination MAC address. Tags: atp.Status=candidate





Class		IEEE1722TpConnection (abstract)		
globalTimeDomain	GlobalTimeDomain	0..1	ref	Reference to the GlobalTimeDomain this IEEE1722TpConnection shall be synchronized with. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=globalTimeDomain.globalTimeDomain, globalTimeDomain.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
macAddressStreamId	MacAddressString	0..1	attr	MAC Address part of the Stream Id. Tags: atp.Status=candidate
pdu	PduTriggering	0..1	ref	Reference to the lower layer Pdu used for the IEEE1722Tp protocol transport. Tags: atp.Status=candidate
uniqueStreamId	PositiveInteger	0..1	attr	Unique Id part of the Stream Id. Tags: atp.Status=candidate
version	PositiveInteger	0..1	attr	Version of the IEEE1722TP stream. Tags: atp.Status=candidate
vlanPriority	PositiveInteger	0..1	attr	Optional definition of the VLAN priority for this stream.

Table A.613: IEEE1722TpConnection

Class		IPSecRule		
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This element defines an IPsec rule that describes communication traffic that is monitored, protected and filtered.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	IPSecConfig.ipSecRule			
Attribute	Type	Mult.	Kind	Note
direction	CommunicationDirectionType	0..1	attr	This attribute defines the direction in which the traffic is monitored. If this attribute is not set a bidirectional traffic monitoring is assumed.
headerType	IPsecHeaderTypeEnum	0..1	attr	Header type specifying the IPsec security mechanism.
ipProtocol	IPsecIpProtocolEnum	0..1	attr	This attribute defines the relevant IP protocol used in the Security Policy Database (SPD) entry.
localCertificate	CryptoServiceCertificate	*	ref	This reference identifies the applicable certificate used for a local authentication.
localId	String	0..1	attr	This attribute defines how the local participant should be identified for authentication.
localPortRangeEnd	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines an end value for the local port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.





Class	IPSecRule			
localPortRangeStart	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines a start value for the local port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.
mode	IPsecModeEnum	0..1	attr	This attribute defines the type of the connection.
policy	IPsecPolicyEnum	0..1	attr	An IPsec policy defines the rules that determine which type of IP traffic needs to be secured using IPsec and how that traffic is secured.
preSharedKey	CryptoServiceKey	0..1	ref	This reference identifies the applicable cryptographic key used for authentication.
priority	PositiveInteger	0..1	attr	This attribute defines the priority of the IPSecRule (SPD entry). The processing of entries is based on priority, starting with the highest priority "0".
remoteCertificate	CryptoServiceCertificate	*	ref	This reference identifies the applicable certificate used for a remote authentication.
remoteld	String	0..1	attr	This attribute defines how the remote participant should be identified for authentication.
remotelpAddress	NetworkEndpoint	*	ref	Definition of the remote NetworkEndpoint. With this reference the connection between the local NetworkEndpoint and the remote NetworkEndpoint is described on which the traffic is monitored.
remotePortRangeEnd	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines an end value for the remote port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.
remotePortRangeStart	PositiveInteger	0..1	attr	This attribute restricts the traffic monitoring and defines a start value for the remote port range. If this attribute is not set then this rule shall be effective for all local ports. Please note that port ranges are currently not supported in the AUTOSAR AP's operating system backend. If AP systems are involved, each IPsec rule may only contain a single port.

Table A.614: IPSecRule

Class	<i>IPdu</i> (abstract)
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	The IPdu (Interaction Layer Protocol Data Unit) element is used to sum up all Pdus that are routed by the PduR.
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , <i>FibexElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Pdu</i> , <i>Referrable</i> , <i>UploadableDesignElement</i> , <i>UploadablePackageElement</i>
Subclasses	ContainerIPdu , DcmIPdu , GeneralPurposeIPdu , ISignalIPdu , J1939DcmIPdu , J1939ProtectedIPdu , MultiplexedIPdu , NPdu , SecuredIPdu , UserDefinedIPdu
Aggregated by	ARPackageElement





Class	IPdu (abstract)			
Attribute	Type	Mult.	Kind	Note
containedIPdu Props	ContainedIPduProps	0..1	aggr	Defines whether this IPdu may be collected inside a ContainerIPdu.

Table A.615: IPdu

Class	IPduMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Multiplatform			
Note	Arranges those IPdus that are transferred by the gateway from one channel to the other in pairs and defines the mapping between them.			
Base	<i>ARObject</i>			
Aggregated by	Gateway.iPduMapping			
Attribute	Type	Mult.	Kind	Note
introduction	DocumentationBlock	0..1	aggr	This represents introductory documentation about the IPdu mapping.
pduMaxLength	PositiveInteger	0..1	attr	Define the maximum length in bytes which limits the length of the Pdu during gateway operation if the runtime length of the received Pdu exceeds this limit.
pduTpChunk Size	PositiveInteger	0..1	attr	Optionally defines the to be configured Pdu Router Tp ChunkSize for this routing relation.
sourceIPdu	PduTriggering	0..1	ref	Source destination of the referencing mapping.
targetIPdu	TargetIPduRef	0..1	aggr	Target destination of the referencing mapping.

Table A.616: IPduMapping

Class	IPduPort			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Connectors reception or send port on the referenced channel referenced by a PduTriggering.			
Base	<i>ARObject</i> , CommConnectorPort , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CommunicationConnector.ecuCommPortInstance			
Attribute	Type	Mult.	Kind	Note
iPduSignal Processing	IPduSignalProcessing Enum	0..1	attr	Definition of the two signal processing modes Immediate and Deferred for both Tx and Rx IPdus.
rxSecurity Verification	Boolean	0..1	attr	This attribute defines the bypassing of signature authentication or MAC verification in the receiving ECU. If not defined or set to true the signature authentication or MAC verification shall be performed for the SecuredIPdu. If set to false the signature authentication or MAC verification shall not be performed for the SecuredIPdu.
timestampRx Acceptance Window	TimeValue	0..1	attr	This attribute is used to define the maximum allowed deviation in seconds from the expected timestamp for which a SecuredIPdu is still deemed authentic. Please note that this attribute is for documentation only to allow the configuration of required freshness value manager and no upstream mapping is defined for it.
useAuthData Freshness	Boolean	0..1	attr	This attribute describes whether a part of AuthenticPdu contained in a SecuredIPdu shall be passed on to the SWC that verifies and generates the Freshness. The part of the Authentic-PDU is defined by the authData FreshnessStartPosition and authDataFreshnessLength.

Table A.617: IPduPort

Class	IPv6ExtHeaderFilterList			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::IPv6HeaderFilterList			
Note	Permitted list for the filtering of IPv6 extension headers.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	IPv6ExtHeaderFilterSet.extHeaderFilterList			
Attribute	Type	Mult.	Kind	Note
allowedIPv6ExtHeader	PositiveInteger	*	attr	IPv6 Extension Header type allowed by this filter.

Table A.618: IPv6ExtHeaderFilterList

Class	ISignal			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>Signal of the Interaction Layer. The RTE supports a "signal fan-out" where the same System Signal is sent in different SignalIPdus to multiple receivers.</p> <p>To support the RTE "signal fan-out" each SignalIPdu contains ISignals. If the same System Signal is to be mapped into several SignalIPdus there is one ISignal needed for each ISignalToIPduMapping.</p> <p>ISignals describe the Interface between the Precompile configured RTE and the potentially Postbuild configured Com Stack (see ECUC Parameter Mapping).</p> <p>In case of the SystemSignalGroup an ISignal shall be created for each SystemSignal contained in the SystemSignalGroup.</p> <p>Tags: atp.recommendedPackage=ISignals</p>			
Base	ARElement, ARObject, CollectableElement, FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dataTransformation	DataTransformation	0..1	ref	<p>Optional reference to a DataTransformation which represents the transformer chain that is used to transform the data that shall be placed inside this ISignal.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=dataTransformation.dataTransformation, dataTransformation.variationPoint.shortLabel vh.latestBindingTime=codeGenerationTime</p>
dataTypePolicy	DataTypePolicyEnum	0..1	attr	<p>With the aggregation of SwDataDefProps an ISignal specifies how it is represented on the network. This representation follows a particular policy. Note that this causes some redundancy which is intended and can be used to support flexible development methodology as well as subsequent integrity checks.</p> <p>If the policy "networkRepresentationFromComSpec" is chosen the network representation from the ComSpec that is aggregated by the PortPrototype shall be used. If the "override" policy is chosen the requirements specified in the PortInterface and in the ComSpec are not fulfilled by the networkRepresentationProps. In case the System Description doesn't use a complete Software Component Description (VFB View) the "legacy" policy can be chosen.</p>





Class	ISignal			
initValue	ValueSpecification	0..1	aggr	<p>Optional definition of a ISignal's initValue in case the System Description doesn't use a complete Software Component Description (VFB View). This supports the inclusion of legacy system signals.</p> <p>This value can be used to configure the Signal's "Init Value".</p> <p>If a full DataMapping exist for the SystemSignal this information may be available from a configured Sender ComSpec and ReceiverComSpec. In this case the initvalues in SenderComSpec and/or ReceiverComSpec override this optional value specification. Further restrictions apply from the RTE specification.</p>
iSignalProps	ISignalProps	0..1	aggr	<p>Additional optional ISignal properties that may be stored in different files.</p> <p>Stereotypes: atpSplittable Tags: atp.Splitkey=iSignalProps</p>
iSignalType	ISignalTypeEnum	0..1	attr	<p>This attribute defines whether this iSignal is an array that results in a UINT8_N / UINT8_DYN ComSignalType in the COM configuration or a primitive type.</p>
length	UnlimitedInteger	0..1	attr	<p>Size of the signal in bits. The size needs to be derived from the mapped VariableDataPrototype according to the mapping of primitive DataTypes to BaseTypes as used in the RTE. Indicates maximum size for dynamic length signals.</p> <p>The ISignal length of zero bits is allowed.</p>
network Representation Props	SwDataDefProps	0..1	aggr	<p>Specification of the actual network representation. The usage of SwDataDefProps for this purpose is restricted to the attributes compuMethod and baseType. The optional baseType attributes "memAllignment" and "byteOrder" shall not be used.</p> <p>The attribute "dataTypePolicy" in the SystemTemplate element defines whether this network representation shall be ignored and the information shall be taken over from the network representation of the ComSpec.</p> <p>If "override" is chosen by the system integrator the network representation can violate against the requirements defined in the PortInterface and in the network representation of the ComSpec.</p> <p>In case that the System Description doesn't use a complete Software Component Description (VFB View) this element is used to configure "ComSignalDataInvalid Value" and the Data Semantics.</p> <p>Stereotypes: atpSplittable Tags: atp.Splitkey=networkRepresentationProps</p>
reception DefaultValue (ordered)	ValueSpecification	*	aggr	<p>Value used to fill data on the receiver side, if less then expected data is received.</p> <p>The value is expected to cover the entire expected ISignal network payload.</p>
systemSignal	SystemSignal	0..1	ref	<p>Reference to the System Signal that is supposed to be transmitted in the ISignal.</p>
timeout Substitution Value	ValueSpecification	0..1	aggr	<p>Defines and enables the ComTimeoutSubstitution for this ISignal.</p>





Class	ISignal			
transformation ISignalProps	TransformationSignal Props	*	aggr	<p>A transformer chain consists of an ordered list of transformers. The ISignal specific configuration properties for each transformer are defined in the TransformationSignalProps class. The transformer configuration properties that are common for all ISignals are described in the TransformationTechnology class.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=transformationISignalProps</p>

Table A.619: ISignal

Class	ISignalGroup			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>SignalGroup of the Interaction Layer. The RTE supports a "signal fan-out" where the same System Signal Group is sent in different SignalPBus to multiple receivers.</p> <p>An ISignalGroup refers to a set of ISignals that shall always be kept together. A ISignalGroup represents a COM Signal Group.</p> <p>Therefore it is recommended to put the ISignalGroup in the same Package as ISignals (see atp.recommendedPackage)</p> <p>Tags: atp.recommendedPackage=ISignalGroup</p>			
Base	<i>ARElement, ARObjct, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
comBased SignalGroup Transformation	DataTransformation	0..1	ref	<p>Optional reference to a DataTransformation which represents the transformer chain that is used to transform the data that shall be placed inside this ISignalGroup based on the COMBasedTransformer approach.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=comBasedSignalGroupTransformation.dataTransformation, comBasedSignalGroupTransformation.variationPoint.shortLabel vh.latestBindingTime=codeGenerationTime</p>
iSignal	ISignal	*	ref	Reference to a set of ISignals that shall always be kept together.
systemSignal Group	SystemSignalGroup	0..1	ref	Reference to the SystemSignalGroup that is defined on VFB level and that is supposed to be transmitted in the ISignalGroup.
transformation ISignalProps	TransformationSignal Props	*	aggr	<p>A transformer chain consists of an ordered list of transformers. The ISignalGroup specific configuration properties for each transformer are defined in the TransformationSignalProps class. The transformer configuration properties that are common for all ISignal Groups are described in the TransformationTechnology class.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=transformationISignalProps</p>

Table A.620: ISignalGroup

Class	ISignalIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>Represents the IPdus handled by Com. The ISignalIPdu assembled and disassembled in AUTOSAR COM consists of one or more signals. In case no multiplexing is performed this IPdu is routed to/from the Interface Layer.</p> <p>A maximum of one dynamic length signal per IPdu is allowed.</p> <p>Tags: atp.recommendedPackage=Pdus</p>			
Base	ARElement , ARObject , CollectableElement , FibexElement , IPdu , Identifiable , MultilanguageReferrable , PackageableElement , Pdu , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
iPduTiming Specification	IPduTiming	0..1	aggr	<p>Timing specification for Com IPdus (Transmission Modes). This information is mandatory for the sender in a System Extract. This information may be omitted on receivers in a System Extract.</p> <p>atpVariation: The timing of a Pdu can vary.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=iPduTimingSpecification, iPduTimingSpecification.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
iSignalToPdu Mapping	ISignalToIPduMapping	*	aggr	<p>Definition of SignalToIPduMappings included in the Signal IPdu.</p> <p>atpVariation: The content of a PDU can be variable.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=iSignalToPduMapping.shortName, iSignalToPduMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
unusedBit Pattern	Integer	0..1	attr	<p>AUTOSAR COM and AUTOSAR IPDUM are filling not used areas of an IPDU with this bit-pattern. This attribute is mandatory to avoid undefined behavior. This byte-pattern will be repeated throughout the IPdu.</p>

Table A.621: ISignalIPdu

Class	ISignalIPduGroup			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>The AUTOSAR COM Layer is able to start and to stop sending and receiving configurable groups of I-Pdus during runtime. An ISignalIPduGroup contains either ISignalIPdus or ISignalIPduGroups.</p> <p>Tags: atp.recommendedPackage=ISignalIPduGroup</p>			
Base	ARObject , CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
communication Direction	CommunicationDirectionType	0..1	attr	<p>This attribute determines in which direction IPdus that are contained in this IPduGroup will be transmitted (communication direction can be either In or Out).</p>
communication Mode	String	0..1	attr	<p>This attribute defines the use-case for this ISignalIPdu Group (e.g. diagnostic, debugging etc.). For example, in a diagnostic mode all IPdus - which are not involved in diagnostic - are disabled. The use cases are not limited to a fixed enumeration and can be specified as a string.</p>





Class	ISignalPduGroup			
contained ISignalPdu Group	ISignalPduGroup	*	ref	An I-Pdu group can be included in other I-Pdu groups. Contained I-Pdu groups shall not be referenced by the EcuInstance.
iSignalPdu	ISignalPdu	*	ref	Reference to a set of Signal I-Pdus, which are contained in the ISignal I-Pdu Group. atpVariation: The content of a ISignal I-Pdu group can vary (->vehicle modes). Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=iSignalPdu.iSignalPdu, iSignal IPdu.variationPoint.shortLabel vh.latestBindingTime=postBuild
nmPdu	NmPdu	*	ref	Reference to a set of NmPdus with NmUserData, which are contained in the ISignalPduGroup. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=nmPdu.nmPdu, nmPdu.variationPoint.short Label vh.latestBindingTime=postBuild

Table A.622: ISignalPduGroup

Class	ISignalMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Multiplatform			
Note	Arranges those signals (or SignalGroups) that are transferred by the gateway from one channel to the other in pairs and defines the mapping between them. Each pair consists in a source and a target referencing to a ISignalTriggering.			
Base	ARObject			
Aggregated by	Gateway.signalMapping			
Attribute	Type	Mult.	Kind	Note
introduction	DocumentationBlock	0..1	aggr	This represents introductory documentation about the ISignal mapping.
sourceSignal	ISignalTriggering	0..1	ref	Source destination of the referencing mapping.
targetSignal	ISignalTriggering	0..1	ref	Target destination of the referencing mapping.

Table A.623: ISignalMapping

Class	ISignalPort			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Connectors reception or send port on the referenced channel referenced by an ISignalTriggering. If different timeouts or DataFilters for ISignals need to be specified several ISignalPorts may be created.			
Base	ARObject, CommConnectorPort , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CommunicationConnector.ecuCommPortInstance			
Attribute	Type	Mult.	Kind	Note





Class	ISignalPort			
dataFilter	DataFilter	0..1	aggr	Optional specification of a signal COM filter at the receiver side in case that the System Description doesn't use a complete Software Component Description (VFB View). This supports the inclusion of legacy system signals. If a full DataMapping exist for the SystemSignal this information may be available from a configured ReceiverComSpec. In this case the ReceiverComSpec overrides this optional specification.
ddsQosProfile	DdsCpQosProfile	0..1	ref	Reference to the DDS Qos profile used for this ISignal. Tags: atp.Status=candidate
firstTimeout	TimeValue	0..1	attr	<ul style="list-style-type: none"> ISignalPort with communicationDirection = in: Optional first timeout value in seconds for the reception of the ISignal. ISignalPort with communicationDirection = out: Optional first timeout value in seconds for transmission deadline monitoring.
handleInvalid	HandleInvalidEnum	0..1	attr	This attribute defines how invalidation is applied to the ISignals received in the context of this ISignalPort.
timeout	TimeValue	0..1	attr	<ul style="list-style-type: none"> ISignalPort with communicationDirection = in: Optional timeout value in seconds for the reception of the ISignal. The attribute value is used to configure the Com Timeout in the COM module. The RTE ignores this attribute. The timeout can also be specified with the NonqueuedReceiverComSpec.aliveTimeout attribute. If a full DataMapping exists for the SystemSignal and the value is available in the configured ReceiverComSpec, then the timeout value in the ReceiverComSpec overrides this optional timeout specification during the creation of the Base Ecu Configuration of the COM module. ISignalPort with communicationDirection = out: Optional timeout value in seconds for the transmission of the ISignal. The attribute value is used to configure the ComTimeout in the COM module. The RTE ignores this attribute. The timeout can also be specified with the ender ComSpec.transmissionAcknowledge.timeout attribute. If a full DataMapping exists for the SystemSignal and the value is available in the configured SenderComSpec, then the timeout value in the SenderComSpec overrides this optional timeout specification during the creation of the Base Ecu Configuration of the COM module. <p>This attribute can be used in the following cases:</p> <ul style="list-style-type: none"> legacy signal where the System Description doesn't use a complete Software Component Description (VFB View) and where the DataMapping is missing. bus monitoring use cases in which the DataMapping is ignored.

Table A.624: ISignalPort

Class	ISignalToIPduMapping
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	An ISignalToIPduMapping describes the mapping of ISignals to ISignalIPdus and defines the position of the ISignal within an ISignalIPdu.





Class		ISignalToIPduMapping		
Base		<i>ARObject, Identifiable, MultilanguageReferrable, Referrable</i>		
Aggregated by		<i>ISignalIPdu.ISignalToPduMapping, NmPdu.ISignalToIPduMapping</i>		
Attribute	Type	Mult.	Kind	Note
iSignal	ISignal	0..1	ref	Reference to a ISignal that is mapped into the ISignal IPdu. Each ISignal contained in the ISignalGroup shall be mapped into an IPdu by an own ISignalToIPduMapping. The references to the ISignal and to the ISignalGroup in an ISignalToIPduMapping are mutually exclusive.
iSignalGroup	ISignalGroup	0..1	ref	Reference to an ISignalGroup that is mapped into the SignalIPdu. If an ISignalToIPduMapping for an ISignal Group is defined, only the UpdateIndicationBitPosition and the transferProperty is relevant. The startPosition and the packingByteOrder shall be ignored. Each ISignal contained in the ISignalGroup shall be mapped into an IPdu by an own ISignalToIPduMapping. The references to the ISignal and to the ISignalGroup in an ISignalToIPduMapping are mutually exclusive.
packingByte Order	ByteOrderEnum	0..1	attr	This parameter defines the order of the bytes of the signal and the packing into the SignalIPdu. The byte ordering "Little Endian" (MostSignificantByteLast), "Big Endian" (MostSignificantByteFirst) and "Opaque" can be selected. For opaque data endianness conversion shall be configured to Opaque. The value of this attribute impacts the absolute position of the signal into the SignalIPdu (see the startPosition attribute description). For an ISignalGroup the packingByteOrder is irrelevant and shall be ignored.
startPosition	UnlimitedInteger	0..1	attr	This parameter is necessary to describe the bitposition of a signal within an SignalIPdu. It denotes the least significant bit for "Little Endian" and the most significant bit for "Big Endian" packed signals within the IPdu (see the description of the packingByteOrder attribute). In AUTOSAR the bit counting is always set to "sawtooth" and the bit order is set to "Decreasing". The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7. Please note that the way the bytes will be actually sent on the bus does not impact this representation: they will always be seen by the software as a byte array. If a mapping for the ISignalGroup is defined, this attribute is irrelevant and shall be ignored.
transferProperty	TransferPropertyEnum	0..1	attr	Defines how the referenced ISignal contributes to the send triggering of the ISignalIPdu.





Class	ISignalToIPduMapping			
updateIndicationBitPosition	UnlimitedInteger	0..1	attr	<p>The UpdateIndicationBit indicates to the receivers that the signal (or the signal group) was updated by the sender. Length is always one bit. The UpdateIndicationBitPosition attribute describes the position of the update bit within the SignalIPdu. For Signals of a ISignalGroup this attribute is irrelevant and shall be ignored.</p> <p>Note that the exact bit position of the updateIndicationBitPosition is linked to the value of the attribute packingByteOrder because the method of finding the bit position is different for the values mostSignificantByteFirst and mostSignificantByteLast. This means that if the value of packingByteOrder is changed while the value of updateIndicationBitPosition remains unchanged the exact bit position of updateIndicationBitPosition within the enclosing ISignalIPdu still undergoes a change.</p> <p>This attribute denotes the least significant bit for "Little Endian" and the most significant bit for "Big Endian" packed signals within the IPdu (see the description of the packingByteOrder attribute). In AUTOSAR the bit counting is always set to "sawtooth" and the bit order is set to "Decreasing". The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7.</p>

Table A.625: ISignalToIPduMapping

Class	ISignalTriggering			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	A ISignalTriggering allows an assignment of ISignals to physical channels.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	PhysicalChannel.ISignalTriggering			
Attribute	Type	Mult.	Kind	Note
iSignal	ISignal	0..1	ref	This reference shall be used if an ISignal is transported on the PhysicalChannel. This reference forms an XOR relationship with the ISignalTriggering-ISignalGroup reference.
iSignalGroup	ISignalGroup	0..1	ref	This reference shall be used if an ISignalGroup is transported on the PhysicalChannel. This reference forms an XOR relationship with the ISignalTriggering-ISignal reference.
iSignalPort	ISignalPort	*	ref	<p>References to the ISignalPort on every ECU of the system which sends and/or receives the ISignal.</p> <p>References for both the sender and the receiver side shall be included when the system is completely defined.</p>

Table A.626: ISignalTriggering

Enumeration	ISignalTypeEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	This enumeration defines ISignal types that are used for derivation of the ComSignalType in the COM configuration.
Aggregated by	ISignal.ISignalType
Literal	Description





Enumeration	ISignalTypeEnum
array	ISignal shall be interpreted as an array (UINT8_N, UINT8_DYN) Tags: atp.EnumerationLiteralIndex=0
primitive	ISignal shall be interpreted as a primitive type (e.g. UINT_8, SINT_32) Tags: atp.EnumerationLiteralIndex=1

Table A.627: ISignalTypeEnum

Class	Identifiable (abstract)
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::Identifiable
Note	Instances of this class can be referred to by their identifier (within the namespace borders). In addition to this, Identifiables are objects which contribute significantly to the overall structure of an AUTOSAR description. In particular, Identifiables might contain Identifiables.
Base	<i>ARObject</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>
Subclasses	<i>ARPackage</i> , <i>AbstractDolpLogicAddressProps</i> , <i>AbstractEvent</i> , <i>AbstractImplementationDataTypeElement</i> , <i>AbstractSecurityEventFilter</i> , <i>AbstractSecurityIdsmInstanceFilter</i> , <i>AbstractServiceInstance</i> , <i>AppOsTaskProxyToEcuTaskProxyMapping</i> , <i>ApplicationEndpoint</i> , <i>ApplicationError</i> , <i>ApplicationPartitionToEcuPartitionMapping</i> , <i>AppliedStandard</i> , <i>AsynchronousServerCallResultPoint</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>AutosarOperationArgumentInstance</i> , <i>AutosarVariableInstance</i> , <i>BinaryManifestAddressableObject</i> , <i>BinaryManifestItemDefinition</i> , <i>BinaryManifestResource</i> , <i>BinaryManifestResourceDefinition</i> , <i>BlockState</i> , <i>BswInternalTriggeringPoint</i> , <i>BswModuleDependency</i> , <i>BuildActionEntity</i> , <i>BuildActionEnvironment</i> , <i>CanTpAddress</i> , <i>CanTpChannel</i> , <i>CanTpNode</i> , <i>Chapter</i> , <i>ClassContentConditional</i> , <i>ClientIdDefinition</i> , <i>ClientServerOperation</i> , <i>Code</i> , <i>CollectableElement</i> , <i>ComManagementMapping</i> , <i>CommConnectorPort</i> , <i>CommunicationConnector</i> , <i>CommunicationController</i> , <i>Compiler</i> , <i>ConsistencyNeeds</i> , <i>ConsumedEventGroup</i> , <i>CouplingElementAbstractDetails</i> , <i>CouplingPort</i> , <i>CouplingPortAbstractShaper</i> , <i>CouplingPortStructuralElement</i> , <i>CpSoftwareClusterResource</i> , <i>CpSoftwareClusterResourceToApplicationPartitionMapping</i> , <i>CpSoftwareClusterToApplicationPartitionMapping</i> , <i>CpSoftwareClusterToEcuInstanceMapping</i> , <i>CpSoftwareClusterToResourceMapping</i> , <i>CryptoServiceMapping</i> , <i>DataPrototypeGroup</i> , <i>DataPrototypeTransformationPropsIdent</i> , <i>DataTransformation</i> , <i>DdsCpDomain</i> , <i>DdsCpPartition</i> , <i>DdsCpQosProfile</i> , <i>DdsCpTopic</i> , <i>DependencyOnArtifact</i> , <i>DiagEventDebounceAlgorithm</i> , <i>DiagnosticAuthTransmitCertificateEvaluation</i> , <i>DiagnosticConnectedIndicator</i> , <i>DiagnosticDataElement</i> , <i>DiagnosticDebounceAlgorithmProps</i> , <i>DiagnosticFunctionInhibitSource</i> , <i>DiagnosticParameterElement</i> , <i>DiagnosticRoutineSubfunction</i> , <i>DltApplication</i> , <i>DltArgument</i> , <i>DltLogChannel</i> , <i>DltMessage</i> , <i>DolpInterface</i> , <i>DolpLogicAddress</i> , <i>DolpRoutingActivation</i> , <i>ECUMapping</i> , <i>EOCExecutableEntityRefAbstract</i> , <i>EcuPartition</i> , <i>EcucContainerValue</i> , <i>EcucDefinitionElement</i> , <i>EcucDestinationUriDef</i> , <i>EcucEnumerationLiteralDef</i> , <i>EcucQuery</i> , <i>EcucValidationCondition</i> , <i>EndToEndProtection</i> , <i>EthernetWakeupSleepOnDataLineConfig</i> , <i>EventHandler</i> , <i>ExclusiveArea</i> , <i>ExecutableEntity</i> , <i>ExecutionTime</i> , <i>FMAttributeDef</i> , <i>FMFeatureMapAssertion</i> , <i>FMFeatureMapCondition</i> , <i>FMFeatureMapElement</i> , <i>FMFeatureRelation</i> , <i>FMFeatureRestriction</i> , <i>FMFeatureSelection</i> , <i>FlatInstanceDescriptor</i> , <i>FlexrayArTpNode</i> , <i>FlexrayTpConnectionControl</i> , <i>FlexrayTpNode</i> , <i>FlexrayTpPduPool</i> , <i>FrameTriggering</i> , <i>GeneralParameter</i> , <i>GlobalTimeGateway</i> , <i>GlobalTimeMaster</i> , <i>GlobalTimeSlave</i> , <i>HeapUsage</i> , <i>HwAttributeDef</i> , <i>HwAttributeLiteralDef</i> , <i>HwPin</i> , <i>HwPinGroup</i> , <i>IEEE1722TpAcfBus</i> , <i>IEEE1722TpAcfBusPart</i> , <i>IPSecRule</i> , <i>IPv6ExtHeaderFilterList</i> , <i>ISignalToIPduMapping</i> , <i>ISignalTriggering</i> , <i>IdentCaption</i> , <i>ImpositionTime</i> , <i>InternalTriggeringPoint</i> , <i>J1939SharedAddressCluster</i> , <i>J1939TpNode</i> , <i>Keyword</i> , <i>LifeCycleState</i> , <i>LinScheduleTable</i> , <i>LinTpNode</i> , <i>Linker</i> , <i>MacAddressVlanMembership</i> , <i>MacMulticastGroup</i> , <i>MacSecKayParticipant</i> , <i>McDataInstance</i> , <i>MemorySection</i> , <i>ModeDeclaration</i> , <i>ModeDeclarationMapping</i> , <i>ModeSwitchPoint</i> , <i>NetworkEndpoint</i> , <i>NmCluster</i> , <i>NmEcu</i> , <i>NmNode</i> , <i>NvBlockDescriptor</i> , <i>PackageableElement</i> , <i>ParameterAccess</i> , <i>PduActivationRoutingGroup</i> , <i>PduToFrameMapping</i> , <i>PduTriggering</i> , <i>PerInstanceMemory</i> , <i>PhysicalChannel</i> , <i>PortElementToCommunicationResourceMapping</i> , <i>PortGroup</i> , <i>PortInterfaceMapping</i> , <i>ResourceConsumption</i> , <i>RootSwCompositionPrototype</i> , <i>RptComponent</i> , <i>RptContainer</i> , <i>RptExecutableEntity</i> , <i>RptExecutableEntityEvent</i> , <i>RptExecutionContext</i> , <i>RptProfile</i> , <i>RptServicePoint</i> , <i>RteEventInCompositionSeparation</i> , <i>RteEventInCompositionToOsTaskProxyMapping</i> , <i>RteEventInSystemSeparation</i> , <i>RteEventInSystemToOsTaskProxyMapping</i> , <i>RunnableEntityGroup</i> , <i>SdgAttribute</i> , <i>SdgClass</i> , <i>SecOcJobRequirement</i> , <i>SecureCommunicationAuthenticationProps</i> , <i>SecureCommunicationFreshnessProps</i> , <i>SecurityEventContextDataElement</i> , <i>SecurityEventContextProps</i> , <i>ServerCallPoint</i> , <i>ServiceNeeds</i> , <i>SignalServiceTranslationElementProps</i> , <i>SignalServiceTranslationEventProps</i> , <i>SignalServiceTranslationProps</i> , <i>SocketAddress</i> , <i>SomeipTpChannel</i> , <i>SpecElementReference</i> , <i>StackUsage</i> , <i>StaticSocketConnection</i> , <i>StructuredReq</i> , <i>SwGenericAxisParamType</i> , <i>SwServiceArg</i> , <i>SwcServiceDependency</i> , <i>SwcToApplicationPartitionMapping</i> , <i>SwcToEcuMapping</i> , <i>SwcToImpMapping</i> , <i>SwitchAsynchronousTrafficShaperGroupEntry</i> , <i>SwitchFlowMeteringEntry</i> , <i>SwitchStreamFilterActionDest</i>





Class	Identifiable (abstract)			
	PortModification, SwitchStreamFilterEntry, SwitchStreamFilterRule, SwitchStreamGateEntry, SwitchStreamIdentification, SystemMapping , SystemSignalGroupToCommunicationResourceMapping , SystemSignalToCommunicationResourceMapping , TDCpSoftwareClusterMapping , TDCpSoftwareClusterResourceMapping , TcpOptionFilterList , TimingClock , TimingClockSyncAccuracy, TimingCondition, TimingConstraint , TimingDescription , TimingExtensionResource, TimingModelInstance, TlsCryptoCipherSuite , TlsCryptoCipherSuiteProps , Topic1 , TpAddress , TraceableTable, TraceableText , TracedFailure , TransformationISignalPropsIdent, TransformationProps , TransformationTechnology , Trigger , VariableAccess , VariationPointProxy , ViewMap, VlanConfig , WaitPoint			
Attribute	Type	Mult.	Kind	Note
adminData	AdminData	0..1	aggr	This represents the administrative data for the identifiable object. Stereotypes: atpSplittable Tags: atp.Splitkey=adminData xml.sequenceOffset=-40
annotation	Annotation	*	aggr	Possibility to provide additional notes while defining a model element (e.g. the ECU Configuration Parameter Values). These are not intended as documentation but are mere design notes. Tags: xml.sequenceOffset=-25
category	CategoryString	0..1	attr	The category is a keyword that specializes the semantics of the Identifiable. It affects the expected existence of attributes and the applicability of constraints. Tags: xml.sequenceOffset=-50
desc	MultiLanguageOverviewParagraph	0..1	aggr	This represents a general but brief (one paragraph) description what the object in question is about. It is only one paragraph! Desc is intended to be collected into overview tables. This property helps a human reader to identify the object in question. More elaborate documentation, (in particular how the object is built or used) should go to "introduction". Tags: xml.sequenceOffset=-60
introduction	DocumentationBlock	0..1	aggr	This represents more information about how the object in question is built or is used. Therefore it is a DocumentationBlock. Tags: xml.sequenceOffset=-30
uuid	String	0..1	attr	The purpose of this attribute is to provide a globally unique identifier for an instance of a meta-class. The values of this attribute should be globally unique strings prefixed by the type of identifier. For example, to include a DCE UUID as defined by The Open Group, the UUID would be preceded by "DCE:". The values of this attribute may be used to support merging of different AUTOSAR models. The form of the UUID (Universally Unique Identifier) is taken from a standard defined by the Open Group (was Open Software Foundation). This standard is widely used, including by Microsoft for COM (GUIDs) and by many companies for DCE, which is based on CORBA. The method for generating these 128-bit IDs is published in the standard and the effectiveness and uniqueness of the IDs is not in practice disputed. If the id namespace is omitted, DCE is assumed. An example is "DCE:2fac1234-31f8-11b4-a222-08002b34c003". The uuid attribute has no semantic meaning for an AUTOSAR model and there is no requirement for AUTOSAR tools to manage the timestamp. Tags: xml.attribute=true

Table A.628: Identifiable

Primitive	Identifier			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes			
Note	<p>An Identifier is a string with a number of constraints on its appearance, satisfying the requirements typical programming languages define for their Identifiers.</p> <p>This datatype represents a string, that can be used as a c-Identifier.</p> <p>It shall start with a letter, may consist of letters, digits and underscores.</p> <p>Tags: xml.xsd.customType=IDENTIFIER xml.xsd.maxLength=128 xml.xsd.pattern=[a-zA-Z][a-zA-Z0-9_]* xml.xsd.type=string</p>			
Attribute	Type	Mult.	Kind	Note
blueprintValue	String	0..1	attr	<p>This represents a description that documents how the value shall be defined when deriving objects from the blueprint.</p> <p>Tags: atp.Status=draft xml.attribute=true</p>
namePattern	String	0..1	attr	<p>This attribute represents a pattern which shall be used to define the value of the identifier if the identifier in question is part of a blueprint.</p> <p>For more details refer to TPS_StandardizationTemplate.</p> <p>Tags: xml.attribute=true</p>

Table A.629: Identifier

Class	ieee1722Tp			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	<p>Content Model for IEEE 1722 configuration.</p> <p>Tags: atp.Status=obsolete</p>			
Base	<i>ARObject, TransportProtocolConfiguration</i>			
Aggregated by	ApplicationEndpoint.tpConfiguration			
Attribute	Type	Mult.	Kind	Note
relativeRepresentationTime	TimeValue	0..1	attr	<p>Defines the time when content shall be presented (in seconds). The actual absolute time is creation time plus relative presentation time.</p> <p>Tags: atp.Status=obsolete</p>
streamIdentifier	PositiveInteger	0..1	attr	<p>IEEE 1722 stream identifier</p> <p>Tags: atp.Status=obsolete</p>
subType	PositiveInteger	0..1	attr	<p>Protocol type.</p> <p>Tags: atp.Status=obsolete</p>
version	PositiveInteger	0..1	attr	<p>Revision of ieee1722 standard</p> <p>Tags: atp.Status=obsolete</p>

Table A.630: ieee1722Tp

Class	Implementation (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Implementation			
Note	Description of an implementation a single software component or module.			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	BswImplementation , SwcImplementation			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
buildActionManifest	BuildActionManifest	0..1	ref	A manifest specifying the intended build actions for the software delivered with this implementation. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=buildActionManifest.buildActionManifest, buildActionManifest.variationPoint.shortLabel vh.latestBindingTime=codeGenerationTime
codeDescriptor	Code	*	aggr	Specifies the provided implementation code.
compiler	Compiler	*	aggr	Specifies the compiler for which this implementation has been released
generatedArtifact	DependencyOnArtifact	*	aggr	Relates to an artifact that will be generated during the integration of this Implementation by an associated generator tool. Note that this is an optional information since it might not always be in the scope of a single module or component to provide this information. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=generatedArtifact.shortName, generatedArtifact.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
hwElement	HwElement	*	ref	The hardware elements (e.g. the processor) required for this implementation.
linker	Linker	*	aggr	Specifies the linker for which this implementation has been released.
mcSupport	McSupportData	0..1	aggr	The measurement & calibration support data belonging to this implementation. The measurement & calibration support data belonging to this implementation. The aggregation is <<atpSplitable>> because in case of an already existing BSW Implementation model, this description will be added later in the process, namely at code generation time. Stereotypes: atpSplitable Tags: atp.Splitkey=mcSupport
programmingLanguage	ProgramminglanguageEnum	0..1	attr	Programming language the implementation was created in.
requiredArtifact	DependencyOnArtifact	*	aggr	Specifies that this Implementation depends on the existence of another artifact (e.g. a library). This aggregation of DependencyOnArtifact is subject to variability with the purpose to support variability in the implementations. Different algorithms in the implementation might cause different dependencies, e.g. the number of used libraries. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=requiredArtifact.shortName, requiredArtifact.variationPoint.shortLabel vh.latestBindingTime=preCompileTime





Class	Implementation (abstract)			
requiredGeneratorTool	DependencyOnArtifact	*	aggr	Relates this Implementation to a generator tool in order to generate additional artifacts during integration. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=requiredGeneratorTool.shortName, requiredGeneratorTool.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
resourceConsumption	ResourceConsumption	0..1	aggr	All static and dynamic resources for each implementation are described within the ResourceConsumption class. Stereotypes: atpSplittable Tags: atp.Splitkey=resourceConsumption.shortName
swcBswMapping	SwcBswMapping	0..1	ref	This allows a mapping between an SWC and a BSW behavior to be attached to an implementation description (for AUTOSAR Service, ECU Abstraction and Complex Driver Components). It is up to the methodology to define whether this reference has to be set for the Swc- or Bsw Implementation or for both.
swVersion	RevisionLabelString	0..1	attr	Software version of this implementation. The numbering contains three levels (like major, minor, patch), its values are vendor specific.
usedCodeGenerator	String	0..1	attr	Optional: code generator used.
vendorId	PositiveInteger	0..1	attr	Vendor ID of this Implementation according to the AUTOSAR vendor list

Table A.631: Implementation

Class	ImplementationDataType			
Package	M2::AUTOSARTemplates::CommonStructure::ImplementationDataTypes			
Note	Describes a reusable data type on the implementation level. This will typically correspond to a typedef in C-code. Tags: atp.recommendedPackage=ImplementationDataTypes			
Base	ARElement , ARObject , AbstractImplementationDataType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , AutosarDataType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dynamicArraySizeProfile	String	0..1	attr	Specifies the profile which the array will follow in case this data type is a variable size array.
isStructWithOptionalElement	Boolean	0..1	attr	This attribute is only valid if the attribute category is set to STRUCTURE. If set to true, this attribute indicates that the ImplementationDataType has been created with the intention to define at least one element of the structure as optional.





Class	ImplementationDataType			
subElement (ordered)	ImplementationDataTypeElement	*	aggr	<p>Specifies an element of an array, struct, or union data type.</p> <p>The aggregation of ImplementationDataTypeElement is subject to variability with the purpose to support the conditional existence of elements inside a ImplementationDataType representing a structure.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=subElement.shortName, subElement.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
symbolProps	SymbolProps	0..1	aggr	<p>This represents the SymbolProps for the ImplementationDataType.</p> <p>Stereotypes: atpSplittable Tags: atp.Splitkey=symbolProps.shortName</p>
typeEmitter	NameToken	0..1	attr	<p>This attribute is used to control which part of the AUTOSAR toolchain is supposed to trigger data type definitions.</p>

Table A.632: ImplementationDataType

Class	ImplementationDataTypeElement			
Package	M2::AUTOSARTemplates::CommonStructure::ImplementationDataTypes			
Note	<p>Declares a data object which is locally aggregated. Such an element can only be used within the scope where it is aggregated.</p> <p>This element either consists of further subElements or it is further defined via its swDataDefProps.</p> <p>There are several use cases within the system of ImplementationDataTypes for such a local declaration:</p> <ul style="list-style-type: none"> • It can represent the elements of an array, defining the element type and array size • It can represent an element of a struct, defining its type • It can be the local declaration of a debug element. 			
Base	ARObject , AbstractImplementationDataTypeElement , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , ImplementationDataType.subElement , ImplementationDataTypeElement.subElement			
Attribute	Type	Mult.	Kind	Note
arrayImplPolicy	ArrayImplPolicyEnum	0..1	attr	<p>This attribute controls the implementation of the payload of an array. It shall only be used if the enclosing ImplementationDataType constitutes an array.</p>
arraySize	PositiveInteger	0..1	attr	<p>The existence of this attributes (if bigger than 0) defines the size of an array and declares that this ImplementationDataTypeElement represents the type of each single array element.</p> <p>Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime</p>
arraySizeHandling	ArraySizeHandlingEnum	0..1	attr	<p>The way how the size of the array is handled in case of a variable size array.</p>
arraySizeSemantics	ArraySizeSemanticsEnum	0..1	attr	<p>This attribute controls the meaning of the value of the array size.</p>





Class	ImplementationDataTypeElement			
isOptional	Boolean	0..1	attr	<p>This attribute represents the ability to declare the enclosing ImplementationDataTypeElement as optional. This means that, at runtime, the ImplementationDataTypeElement may or may not have a valid value and shall therefore be ignored.</p> <p>The underlying runtime software provides means to set the CppImplementationDataTypeElement as not valid at the sending end of a communication and determine its validity at the receiving end.</p>
subElement (ordered)	ImplementationDataTypeElement	*	aggr	<p>Element of an array, struct, or union in case of a nested declaration (i.e. without using "typedefs").</p> <p>The aggregation of ImplementationDataTypeElement is subject to variability with the purpose to support the conditional existence of elements inside a ImplementationDataTypeElement representing a structure.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=subElement.shortName, subElement.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
swDataDef Props	SwDataDefProps	0..1	aggr	The properties of this ImplementationDataTypeElement.

Table A.633: ImplementationDataTypeElement

Class	ImplementationDataTypeElementInPortInterfaceRef			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer::InstanceRef			
Note	<p>This meta-class represents the ability to refer to the internal structure of an AutosarDataPrototype which is typed by an ImplementationDatatype in the context of a PortInterface.</p> <p>In other words, this meta-class shall not be used to model a reference to the AutosarDataPrototype as a target itself, even if the AutosarDataPrototype is typed by an ImplementationDataType and even if that ImplementationDataType represents a composite data type.</p>			
Base	ARObject , DataPrototypeReference			
Aggregated by	DataPrototypeTransformationProps.dataPrototypeInPortInterfaceRef , SignalServiceTranslationElementProps.element , TransmissionComSpecProps.onChangeDataPrototype			
Attribute	Type	Mult.	Kind	Note
context Implementation DataElement (ordered)	AbstractImplementationDataTypeElement	*	ref	<p>This is a context in case there are subelements with explicit types. The reference has to be ordered to properly reflect the nested structure.</p> <p>Tags: xml.sequenceOffset=20</p>
rootData Prototype	AutosarDataPrototype	0..1	ref	<p>This refers to the AutosarDataPrototype which is typed by the ImplementationDatatype. The targetDataPrototype and all defined contextDataPrototypes can be found within this rootDataPrototype.</p> <p>Tags: xml.sequenceOffset=10</p>
target Implementation DataType Element	AbstractImplementationDataTypeElement	0..1	ref	<p>This is a target ImplementationDataTypeElement in case that the rootDataPrototype is composite and the target is a subElement of the rootDataPrototype.</p> <p>Tags: xml.sequenceOffset=30</p>

Table A.634: ImplementationDataTypeElementInPortInterfaceRef

Class	ImplementationDataTypeSubElementRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This meta-class represents the specialization of SubElementMapping with respect to ImplementationDataTypes.			
Base	ARObject, SubElementRef			
Aggregated by	SubElementMapping.firstElement, SubElementMapping.secondElement			
Attribute	Type	Mult.	Kind	Note
implementationDataTypeElement	ArVariableInImplementationDataInstanceRef	0..1	aggr	This represents the referenced implementationDataTypeElement.
parameterImplementationDataTypeElement	ArParameterInImplementationDataInstanceRef	0..1	aggr	This represents the referenced ImplementationDataTypeElement.

Table A.635: ImplementationDataTypeSubElementRef

Class	ImplementationElementInParameterInstanceRef			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport			
Note	<p>Describes a reference to a particular ImplementationDataTypeElement instance in the context of a given ParameterDataPrototype. Thus it refers to a particular element in the implementation description of a software data structure.</p> <p>Use Case: The RTE generator publishes its generated structure of calibration parameters in its BSW module description using the "constantMemory" role of ParameterDataPrototypes. Each ParameterDataPrototype describes a group of single calibration parameters. In order to point to these single parameters, this "instance ref" is needed.</p> <p>Note that this class follows the pattern of an InstanceRef but is not implemented based on the abstract classes because the ImplementationDataType isn't either, especially because ImplementationDataTypeElement isn't derived from AtpPrototype.</p>			
Base	ARObject			
Aggregated by	McDataInstance.instanceInMemory			
Attribute	Type	Mult.	Kind	Note
context	ParameterDataPrototype	0..1	ref	The context for the referred element. Tags: xml.sequenceOffset=20
target	AbstractImplementationDataTypeElement	0..1	ref	The referred data element. Tags: xml.sequenceOffset=30

Table A.636: ImplementationElementInParameterInstanceRef

Class	ImplementationProps (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Implementation			
Note	Defines a symbol to be used as (depending on the concrete case) either a complete replacement or a prefix when generating code artifacts.			
Base	ARObject, Referrable			
Subclasses	BswSchedulerNamePrefix, ExecutableEntityActivationReason , SectionNamePrefix , SymbolProps , SymbolicNameProps			
Attribute	Type	Mult.	Kind	Note
symbol	CIdentifier	0..1	attr	The symbol to be used as (depending on the concrete case) either a complete replacement or a prefix.

Table A.637: ImplementationProps

Class	IndexedArrayElement			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	This element represents exactly one indexed element in the array. Either the applicationArrayElement or implementationArrayElement reference shall be used.			
Base	ARObject			
Aggregated by	SenderRecArrayElementMapping.indexedArrayElement			
Attribute	Type	Mult.	Kind	Note
applicationArrayElement	ApplicationArrayElement	0..1	ref	Reference to an ApplicationArrayElement in an array.
implementationArrayElement	ImplementationDataTypeElement	0..1	ref	Reference to an ImplementationDataTypeElement in an array.
index	Integer	0..1	attr	Position of an element in an array. Starting position is 0.

Table A.638: IndexedArrayElement

Class	InitEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This RTEEvent is supposed to be used for initialization purposes, i.e. for starting and restarting a partition. It is not guaranteed that all RunnableEntities referenced by this InitEvent are executed before the 'regular' RunnableEntities are executed for the first time. The execution order depends on the task mapping.			
Base	ARObject, AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.639: InitEvent

Class	InitialSdDelayConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	This element is used to configure the offer behavior of the server and the find behavior on the client.			
Base	ARObject			
Aggregated by	SdClientConfig.initialFindBehavior , SdServerConfig.initialOfferBehavior , SomeipSdClientServiceInstanceConfig.initialFindBehavior , SomeipSdServerServiceInstanceConfig.initialOfferBehavior			
Attribute	Type	Mult.	Kind	Note
initialDelayMaxValue	TimeValue	0..1	attr	Max Value in seconds to delay randomly the first offer (if aggregated by SdServerConfig) or the transmission of a find message (if aggregated by SdClientConfig).
initialDelayMinValue	TimeValue	0..1	attr	Min Value in seconds to delay randomly the first offer or the transmission of a find message (if aggregated by SdClientConfig).
initialRepetitionsBaseDelay	TimeValue	0..1	attr	The base delay for offer repetitions (if aggregated by SdServerConfig) or find repetitions (if aggregated by SdClientConfig). Successive find messages have an exponential back off delay.
initialRepetitionsMax	PositiveInteger	0..1	attr	Describes the maximum amount of offer repetitions (if aggregated by SdServerConfig) or the maximum amount of find repetitions (if aggregated by SdClientConfig).

Table A.640: InitialSdDelayConfig

Class	InstantiationDataDefProps			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::InstantiationDataDefProps			
Note	<p>This is a general class allowing to apply additional SwDataDefProps to particular instantiations of a Data Prototype.</p> <p>Typically the accessibility and further information like alias names for a particular data is modeled on the level of DataPrototypes (especially VariableDataPrototypes, ParameterDataPrototypes). But due to the recursive structure of the meta-model concerning data types (a composite (data) type consists out of data prototypes) a part of the MCD information is described in the data type (in case of Application CompositeDataType).</p> <p>This is a strong restriction in the reuse of data typed because the data type should be re-used for different VariableDataPrototypes and ParameterDataPrototypes to guarantee type compatibility on C-implementation level (e.g. data of a Port is stored in PIM or a ParameterDataPrototype used as ROM Block and shall be typed by the same data type as NVRAM Block).</p> <p>This class overcomes such a restriction if applied properly.</p>			
Base	ARObject			
Aggregated by	NvBlockDescriptor.instantiationDataDefProps, ParameterSwComponentType.instantiationDataDefProps, SwcInternalBehavior.instantiationDataDefProps			
Attribute	Type	Mult.	Kind	Note
parameter Instance	AutosarParameterRef	0..1	aggr	This reference identifies the particular DataPrototype (defined in the context of a composite ParameterData Prototype) on which the swDataDefProps shall be applied.
swDataDef Props	SwDataDefProps	0..1	aggr	These are the particular data definition properties which shall be applied Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps
variableInstance	AutosarVariableRef	0..1	aggr	This reference identifies the particular DataPrototype (defined in the context of a composite VariableData Prototype) on which the swDataDefProps shall be applied.

Table A.641: InstantiationDataDefProps

Class	InstantiationRTEEventProps (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	This meta-class represents the ability to refine the properties of RTEEvents for particular instances of a software component.			
Base	ARObject			
Subclasses	InstantiationTimingEventProps			
Aggregated by	CompositionSwComponentType.instantiationRTEEventProps			
Attribute	Type	Mult.	Kind	Note
refinedEvent	RTEEvent	0..1	iref	This instance ref denotes the Timing Event for which the period shall be refined on an instance level. InstanceRef implemented by: InstanceEventIn CompositionInstanceRef
shortLabel	Identifier	0..1	attr	The main purpose of the shortLabel is to contribute to the splitkey of aggregations that are <<atpSplitable>>. Stereotypes: atpIdentityContributor

Table A.642: InstantiationRTEEventProps

Class	InstantiationTimingEventProps			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	This meta-class represents the ability to refine a timing event for particular instances of a software component. This approach supports an instance specific timing.			
Base	ARObject, InstantiationRTEEventProps			
Aggregated by	CompositionSwComponentType.instantiationRTEEventProps			
Attribute	Type	Mult.	Kind	Note
period	TimeValue	0..1	attr	This attribute represents the value of the refined activation period.

Table A.643: InstantiationTimingEventProps

Class	InternalBehavior (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::InternalBehavior			
Note	Common base class (abstract) for the internal behavior of both software components and basic software modules/clusters.			
Base	ARObject, AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	BswInternalBehavior , SwcInternalBehavior			
Aggregated by	AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
constantMemory	ParameterDataPrototype	*	aggr	<p>Describes a read only memory object containing characteristic value(s) implemented by this Internal Behavior.</p> <p>The shortName of ParameterDataPrototype has to be equal to the "C" identifier of the described constant.</p> <p>The characteristic value(s) might be shared between Sw ComponentPrototypes of the same SwComponentType.</p> <p>The aggregation of constantMemory is subject to variability with the purpose to support variability in the software component or module implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=constantMemory.shortName, constantMemory.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
constantValueMapping	ConstantSpecificationMappingSet	*	ref	<p>Reference to the ConstantSpecificationMapping to be applied for the particular InternalBehavior</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=constantValueMapping</p>
dataTypeMapping	DataTypeMappingSet	*	ref	<p>Reference to the DataTypeMapping to be applied for the particular InternalBehavior</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=dataTypeMapping</p>





Class	InternalBehavior (abstract)			
exclusiveArea	ExclusiveArea	*	aggr	<p>This specifies an ExclusiveArea for this InternalBehavior. The exclusiveArea is local to the component resp. module. The aggregation of ExclusiveAreas is subject to variability. Note: the number of ExclusiveAreas might vary due to the conditional existence of RunnableEntities or BswModuleEntities.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=exclusiveArea.shortName, exclusiveArea.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
exclusiveAreaNestingOrder	ExclusiveAreaNestingOrder	*	aggr	<p>This represents the set of ExclusiveAreaNestingOrder owned by the InternalBehavior.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=exclusiveAreaNestingOrder.shortName, exclusiveAreaNestingOrder.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
staticMemory	VariableDataPrototype	*	aggr	<p>Describes a read and writeable static memory object representing measurement variables implemented by this software component. The term "static" is used in the meaning of "non-temporary" and does not necessarily specify a linker encapsulation. This kind of memory is only supported if supportsMultipleInstantiation is FALSE.</p> <p>The shortName of the VariableDataPrototype has to be equal with the "C" identifier of the described variable.</p> <p>The aggregation of staticMemory is subject to variability with the purpose to support variability in the software component's implementations.</p> <p>Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=staticMemory.shortName, staticMemory.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>

Table A.644: InternalBehavior

Class	InternalTriggerOccurredEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the referenced InternalTriggeringPoint has occurred.			
Base	ARObject , AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
eventSource	InternalTriggeringPoint	0..1	ref	The referenced InternalTriggeringPoint raises this InternalTriggerOccurredEvent.

Table A.645: InternalTriggerOccurredEvent

Class	InternalTriggeringPoint			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::Trigger			
Note	If a RunnableEntity owns an InternalTriggeringPoint it is entitled to trigger the execution of Runnable Entities of the corresponding software-component.			
Base	ARObject, AbstractAccessPoint, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, RunnableEntity.internalTriggeringPoint			
Attribute	Type	Mult.	Kind	Note
swImplPolicy	SwImplPolicyEnum	0..1	attr	This attribute, when set to value queued, allows for a queued processing of Triggers.

Table A.646: InternalTriggeringPoint

Class	InterpolationRoutine			
Package	M2::AUTOSARTemplates::SWComponentTemplate::MeasurementAndCalibration::InterpolationRoutine MappingSet			
Note	This represents an interpolation routine taken to evaluate the contents of a curve or map against a specific input value.			
Base	ARObject			
Aggregated by	InterpolationRoutineMapping.interpolationRoutine			
Attribute	Type	Mult.	Kind	Note
interpolation Routine	BswModuleEntry	0..1	ref	This specifies a BswModuleEntry which implements the current interpolation method for the given record layout. Tags: xml.sequenceOffset=30
isDefault	Boolean	0..1	attr	This attribute specifies whether the enclosing InterpolationRoutine is considered the default in the context (defined by the System Template) of a given collection InterpolationRoutineMapping that owns the enclosing InterpolationRoutine. Tags: xml.sequenceOffset=20
shortLabel	Identifier	0..1	attr	This is the name of the interpolation method which is implemented by the referenced bswModuleEntry. It corresponds to swInterpolationMethod in SwDataDef Props. Tags: xml.sequenceOffset=10

Table A.647: InterpolationRoutine

Class	InterpolationRoutineMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::MeasurementAndCalibration::InterpolationRoutine MappingSet			
Note	This meta-class provides a mapping between one record layout and its matching interpolation routines. This allows to formally specify the semantics of the interpolation routines. The use case is such that the curves/Maps define an interpolation method. This mapping table specifies which interpolation routine implements methods for a particular record layout. Using this information, the implementer of a software-component can select the appropriate interpolation routine.			
Base	ARObject			
Aggregated by	InterpolationRoutineMappingSet.interpolationRoutineMapping			
Attribute	Type	Mult.	Kind	Note
interpolation Routine	InterpolationRoutine	*	aggr	This is one particular interpolation routine which is mapped to the record layout.
swRecord Layout	SwRecordLayout	0..1	ref	This refers to the record layout which is mapped to interpolation routines.

Table A.648: InterpolationRoutineMapping

Class	InterpolationRoutineMappingSet			
Package	M2::AUTOSARTemplates::SWComponentTemplate::MeasurementAndCalibration::InterpolationRoutineMappingSet			
Note	This meta-class specifies a set of interpolation routine mappings. Tags: atp.recommendedPackage=InterpolationRoutineMappingSets			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
interpolation Routine Mapping	InterpolationRoutineMapping	*	aggr	This specifies one particular mapping of recordlayout and its matching interpolationRoutines.

Table A.649: InterpolationRoutineMappingSet

Class	InvalidationPolicy			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Specifies whether the component can actively invalidate a particular dataElement. If no invalidationPolicy points to a dataElement this is considered to yield the identical result as if the handleInvalid attribute was set to dontInvalidate.			
Base	ARObject			
Aggregated by	SenderReceiverInterface.invalidationPolicy			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	0..1	ref	Reference to the dataElement for which the Invalidation Policy applies.
handleInvalid	HandleInvalidEnum	0..1	attr	This attribute controls how invalidation is applied to the dataElement.

Table A.650: InvalidationPolicy

Class	Ipv4ArpProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Specifies the configuration options for the ARP (Address Resolution Protocol).			
Base	ARObject			
Aggregated by	Ipv4Props.arpProps			
Attribute	Type	Mult.	Kind	Note
tcplpArpNum GratuitousArp OnStartup	PositiveInteger	0..1	attr	This attribute specifies the number of gratuitous ARP replies which shall be sent on assignment of a new IP address.
tcplpArpPacket QueueEnabled	Boolean	0..1	attr	This attribute enables (TRUE) or disables (FALSE) support of the ARP Packet Queue according to IETF RFC 1122, section 2.3.2.2.
tcplpArp Request Timeout	TimeValue	0..1	attr	This attribute specifies a timeout in seconds for the validity of ARP requests. After the transmission of an ARP request the Tcplp shall skip the transmission of any further ARP requests to the same destination within a duration of tcplpArpRequestTimeout seconds. (IETF RFC 1122, section 2.3.2.1).
tcplpArpTable EntryTimeout	TimeValue	0..1	attr	This attribute specifies the timeout in seconds after which an unused ARP entry is removed.

Table A.651: Ipv4ArpProps

Class	Ipv4Configuration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Internet Protocol version 4 (IPv4) configuration.			
Base	ARObject, NetworkEndpointAddress			
Aggregated by	NetworkEndpoint.networkEndpointAddress			
Attribute	Type	Mult.	Kind	Note
assignmentPriority	PositiveInteger	0..1	attr	Priority of assignment (1 is highest). If a new address from an assignment method with a higher priority is available, it overwrites the IP address previously assigned by an assignment method with a lower priority.
defaultGateway	Ip4AddressString	0..1	attr	IP address of the default gateway.
dnsServerAddress	Ip4AddressString	*	attr	IP addresses of preconfigured DNS servers. Tags: xml.namePlural=DNS-SERVER-ADDRESSES
ipAddressKeepBehavior	IpAddressKeepEnum	0..1	attr	Defines the lifetime of a dynamically fetched IP address.
ipv4Address	Ip4AddressString	0..1	attr	IPv4 Address. Notation: 255.255.255.255. The IP Address shall be declared in case the ipv4AddressSource is FIXED and thus no auto-configuration mechanism is used.
ipv4AddressSource	Ip4AddressSourceEnum	0..1	attr	Defines how the node obtains its IP address.
networkMask	Ip4AddressString	0..1	attr	Network mask. Notation 255.255.255.255
tTl	PositiveInteger	0..1	attr	Lifespan of data (0..255). The purpose of the TimeToLive field is to avoid a situation in which an undeliverable datagram keeps circulating on a system.

Table A.652: Ipv4Configuration

Class	Ipv4FragmentationProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Specifies the configuration options for IPv4 packet fragmentation/reassembly.			
Base	ARObject			
Aggregated by	Ipv4Props.fragmentationProps			
Attribute	Type	Mult.	Kind	Note
tcpIplpFragmentationRxEnabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) support for reassembling of incoming datagrams that are fragmented according to IETF RFC 815 (IP Datagram Reassembly Algorithms).
tcpIplpNumFragments	PositiveInteger	0..1	attr	Specifies the maximum number of IP fragments per datagram.
tcpIplpNumReassDgrams	PositiveInteger	0..1	attr	Specifies the maximum number of fragmented IP datagrams that can be reassembled in parallel.
tcpIplpReassTimeout	TimeValue	0..1	attr	Specifies the timeout in [s] after which an incomplete datagram gets discarded.

Table A.653: Ipv4FragmentationProps

Class	Ipv6Configuration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Internet Protocol version 6 (IPv6) configuration.			
Base	ARObject, NetworkEndpointAddress			





Class		Ipv6Configuration		
Aggregated by		NetworkEndpoint.networkEndpointAddress		
Attribute	Type	Mult.	Kind	Note
assignment Priority	PositiveInteger	0..1	attr	Priority of assignment (1 is highest). If a new address from an assignment method with a higher priority is available, it overwrites the IP address previously assigned by an assignment method with a lower priority.
defaultRouter	Ip6AddressString	0..1	attr	IP address of the default router.
dnsServer Address	Ip6AddressString	*	attr	IP addresses of pre configured DNS servers. Tags: xml.namePlural=DNS-SERVER-ADDRESSES
enableAnycast	Boolean	0..1	attr	This attribute is used to enable anycast addressing (i.e. to one of multiple receivers).
hopCount	PositiveInteger	0..1	attr	The distance between two hosts. The hop count n means that n gateways separate the source host from the destination host (Range 0..255)
ipAddressKeep Behavior	IpAddressKeepEnum	0..1	attr	Defines the lifetime of a dynamically fetched IP address.
ipAddressPrefix Length	PositiveInteger	0..1	attr	IPv6 prefix length defines the part of the IPv6 address that is the network prefix.
ipv6Address	Ip6AddressString	0..1	attr	IPv6 Address. Notation: FFFF::...:FFFF. The IP Address shall be declared in case the ipv6AddressSource is FIXED and thus no auto-configuration mechanism is used.
ipv6Address Source	Ipv6AddressSource Enum	0..1	attr	Defines how the node obtains its IP address.

Table A.654: Ipv6Configuration

Class		Ipv6FragmentationProps		
Package		M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology		
Note		This meta-class specifies the configuration options for IPv6 packet fragmentation/reassembly.		
Base		ARObject		
Aggregated by		Ipv6Props.fragmentationProps		
Attribute	Type	Mult.	Kind	Note
tcpIplp Reassembly BufferCount	PositiveInteger	0..1	attr	Number of buffers that can be used for fragment reassembly. In case of a reassembly error or if not all fragments are received in time this buffer will be blocked until the specified "Fragment Reassembly Timeout" has been exceeded. A value of 0 disables fragment reassembly.
tcpIplp Reassembly BufferSize	PositiveInteger	0..1	attr	Size of each fragment tx buffer in bytes.
tcpIplp Reassembly SegmentCount	PositiveInteger	0..1	attr	Specifies the maximum number of consecutive data segments that can be managed in each reassembly buffer. If all fragments are received in order, only one segment will be needed. To deal with fragments received out of order this value should be configured bigger than 1.
tcpIplp Reassembly Timeout	TimeValue	0..1	attr	Specifies the timeout in seconds after which an incomplete datagram gets discarded.





Class	Ipv6FragmentationProps			
tcpIplpTx FragmentBuffer Count	PositiveInteger	0..1	attr	These buffers will be used if the IpV6 receives packets from the upper layer that do not fit into the MTU and thus must be fragmented. A value of 0 disables tx fragmentation.
tcpIplpTx FragmentBuffer Size	PositiveInteger	0..1	attr	Size of each fragment tx buffer in bytes.

Table A.655: Ipv6FragmentationProps

Class	Ipv6NdpProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This meta-class specifies the configuration options for the Neighbor Discovery Protocol for IPv6.			
Base	ARObject			
Aggregated by	Ipv6Props.ndpProps			
Attribute	Type	Mult.	Kind	Note
tcpIplpNdpDefault ReachableTime	TimeValue	0..1	attr	Configuration of the ReachableTime (s) specified in [RFC4861 6.3.2. Host Variables].
tcpIplpNdpDefault RetransTimer	TimeValue	0..1	attr	Configures the default value (s) for the RetransTimer variable specified in [RFC4861 6.3.2. Host Variables].
tcpIplpNdpDefault RouterListSize	PositiveInteger	0..1	attr	Maximum number of default router entries.
tcpIplpNdp Defensive Processing	Boolean	0..1	attr	If enabled the NDP shall only process Neighbor Advertisements which are received in reaction to a previously transmitted Neighbor Solicitation as well as skipping updates to the Neighbor Cache based on received Neighbor Solicitations. If disabled all Neighbor Advertisements and Solicitations shall be processed as specified in RFC4861.
tcpIplpNdpDelay FirstProbeTime Value	TimeValue	0..1	attr	Delay before sending the first NUD probe in (s).
tcpIplpNdp Destination CacheSize	PositiveInteger	0..1	attr	Maximum number of entries in the destination cache.
tcpIplpNdp DynamicHop LimitEnabled	Boolean	0..1	attr	If enabled the default hop limit may be reconfigured based on received Router Advertisements.
tcpIplpNdp DynamicMtu Enabled	Boolean	0..1	attr	Allow dynamic reconfiguration of link MTU via Router Advertisements.
tcpIplpNdp Dynamic ReachableTime Enabled	Boolean	0..1	attr	If enabled the default Reachable Time value may be reconfigured based on received Router Advertisements.
tcpIplpNdp Dynamic RetransTime Enabled	Boolean	0..1	attr	If enabled the default Retransmit Timer value may be reconfigured based on received Router Advertisements.
tcpIplpNdpMax RandomFactor	PositiveInteger	0..1	attr	Maximum random factor used for randomization
tcpIplpNdpMaxRtr Solicitation Delay	TimeValue	0..1	attr	Maximum delay before the first Router Solicitation will be sent after interface initialization in (s).





Class	Ipv6NdpProps			
tcpIpNdpMaxRtrSolicitations	PositiveInteger	0..1	attr	Maximum number of Router Solicitations that will be sent before the first Router Advertisement has been received.
tcpIpNdpMinRandomFactor	PositiveInteger	0..1	attr	Minimum random factor used for randomization
tcpIpNdpNeighborUnreachabilityDetectionEnabled	Boolean	0..1	attr	Neighbor Unreachability Detection is used to remove unused entries from the neighbor cache. This feature is a basic feature of NDP and should be turned on.
tcpIpNdpNumMulticastSolicitations	PositiveInteger	0..1	attr	Maximum number of multicast solicitations that will be sent when performing address resolution.
tcpIpNdpNumUnicastSolicitations	PositiveInteger	0..1	attr	Maximum number of unicast solicitations that will be sent when performing Neighbor Unreachability Detection.
tcpIpNdpPacketQueueEnabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) support of a NDP Packet Queue according to IETF RFC 4861, section 7.2.2.
tcpIpNdpPrefixListSize	PositiveInteger	0..1	attr	Maximum number of entries in the on-link prefix list.
tcpIpNdpRandomReachableTimeEnabled	Boolean	0..1	attr	If enabled the value of ReachableTime will be multiplied with a random value between MIN_RANDOM_FACTOR and MAX_RANDOM_FACTOR in order to prevent multiple nodes from transmitting at exactly the same time.
tcpIpNdpRndRtrSolicitationDelayEnabled	Boolean	0..1	attr	If enabled the first router solicitation will be delayed randomly from [0...MAX_RTR_SOLICITATION_DELAY]. Otherwise the first router solicitation will be sent after exactly MAX_RTR_SOLICITATION_DELAY milliseconds.
tcpIpNdpRtrSolicitationInterval	TimeValue	0..1	attr	Interval between consecutive Router Solicitations in (s).
tcpIpNdpSlaacDadNumberOfTransmissions	PositiveInteger	0..1	attr	Number of Neighbor Solicitations that have to be unanswered in order to set an autoconfigured address to PREFERRED (usable) state.
tcpIpNdpSlaacDadRetransmissionDelay	TimeValue	0..1	attr	Sets the maximum value for the address configuration delay (s).
tcpIpNdpSlaacDelayEnabled	Boolean	0..1	attr	If enabled transmission of the first DAD Neighbor Solicitation will be delayed by a random value from [0...MAX_DAD_DELAY].
tcpIpNdpSlaacOptimisticDadEnabled	Boolean	0..1	attr	Enable Optimistic Duplicate Address Detection (DAD) according to RFC4429.

Table A.656: Ipv6NdpProps

Class	«atpVariation» J1939Cluster
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanTopology
Note	J1939 specific cluster attributes. Tags: atp.recommendedPackage=CommunicationClusters
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AbstractCanCluster</i> , <i>CollectableElement</i> , <i>CommunicationCluster</i> , <i>FibexElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i> , <i>UploadableDesignElement</i> , <i>UploadablePackageElement</i>
Aggregated by	ARPackage.element





Class «atpVariation» J1939Cluster				
Attribute	Type	Mult.	Kind	Note
networkId	PositiveInteger	0..1	attr	This represents the network ID for the J1939 cluster.
re-quest2Support	Boolean	0..1	attr	Enables support for the Request2 PGN (RQST2).
usesAddress Arbitration	Boolean	0..1	attr	Defines whether the nodes attached to this channel use an initial address claim, and whether they react to contending address claims of other nodes. True: The initial address claim is sent, and the node reacts to address claims of other nodes. False: The node only sends an address claim upon request, and does not care for contending address claims.

Table A.657: J1939Cluster

Class	J1939ControllerApplication			
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	This element represents a J1939 controller application. Tags: atp.recommendedPackage=J1939ControllerApplications			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, Packageable Element, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
functionId	PositiveInteger	0..1	attr	This attribute represents the numerical function id of the J1939 controller application.
swComponent Prototype	SwComponent Prototype	0..1	iref	This represents the SwComponentPrototype (which is typically typed by a CompositionSwComponentType) that corresponds to the J1939ControllerApplication. InstanceRef implemented by: ComponentInSystem InstanceRef

Table A.658: J1939ControllerApplication

Class	J1939ControllerApplicationToJ1939NmNodeMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	This meta-class represents the ability to map a J1939ControllerApplication to a J1939NmNode. Note that this is similar but not identical to the mapping of SwComponentPrototypes to EcuInstances; for J1939 the semantics of an EcuInstance itself is basically replaced by a J1939NmNode.			
Base	<i>ARObject</i>			
Aggregated by	SystemMapping.j1939ControllerApplicationToJ1939NmNodeMapping			
Attribute	Type	Mult.	Kind	Note
j1939Controller Application	J1939Controller Application	0..1	ref	Reference to the J1939 Controller Application that is mapped to the referenced J1939NmNode.
j1939NmNode	J1939NmNode	0..1	ref	J1939NmNode that is the target of the J1939Controller ApplicationTo1939NmNodeMapping.

Table A.659: J1939ControllerApplicationToJ1939NmNodeMapping

Class	J1939DcmIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Represents the IPdus handled by J1939Dcm. Tags: atp.recommendedPackage=Pdus			
Base	<i>ARElement, ARObject, CollectableElement, FibexElement, IPdu, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
diagnostic MessageType	PositiveInteger	0..1	attr	This attribute is used to identify the actual DMx message, e.g 1 means DM01, etc.

Table A.660: J1939DcmIPdu

Class	J1939NmCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	J1939 specific NmCluster attributes			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, NmCluster, Referrable</i>			
Aggregated by	NmConfig.nmCluster			
Attribute	Type	Mult.	Kind	Note
addressClaim Enabled	Boolean	0..1	attr	This attribute specifies whether the J1939Nm Bsw module is used or not. If this attribute is set to false then the J1939Nm configuration shall not be derived from the system description. But even in this case the nmNodeId might still be necessary for the J1939Rm and J1939Tp.
usesDynamic Addressing	Boolean	0..1	attr	Defines whether fully dynamic address resolution according to SAE J1939-81 shall be supported on this J1939NmCluster. <ul style="list-style-type: none"> • True: The dynamically allocated addresses on the bus are matched at runtime to the configured addresses. • False: The addresses on the bus resemble the configured addresses.

Table A.661: J1939NmCluster

Class	J1939NmNode			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	J1939 specific NM Node attributes.			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, NmNode, Referrable</i>			
Aggregated by	NmCluster.nmNode			
Attribute	Type	Mult.	Kind	Note
address Configuration Capability	J1939NmAddress ConfigurationCapability Enum	0..1	attr	Defines the Address Configuration Capability of the J1939NmNode (corresponding to an SAE J1939 Controller Application, CA).
nodeName	J1939NodeName	0..1	aggr	nodeName configuration

Table A.662: J1939NmNode

Class	J1939NodeName			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	This element contains attributes to configure the J1939NmNode NAME.			
Base	ARObject			
Aggregated by	J1939NmNode.nodeName			
Attribute	Type	Mult.	Kind	Note
arbitrary Address Capable	Boolean	0..1	attr	Arbitrary Address Capable field of the NAME of this node.
eculInstance	Integer	0..1	attr	ECU Instance field of the NAME of this node.
function	Integer	0..1	attr	Function field of the NAME of this node.
function Instance	Integer	0..1	attr	Function Instance field of the NAME of this node.
identityNumber	Integer	0..1	attr	Identity Number field of the NAME of this node.
industryGroup	Integer	0..1	attr	Industry Group field of the NAME of this node.
manufacturer Code	Integer	0..1	attr	Manufacturer Code field of the NAME of this node.
vehicleSystem	Integer	0..1	attr	Vehicle System field of the NAME of this node.
vehicleSystem Instance	Integer	0..1	attr	Vehicle System Instance field of the NAME of this node.

Table A.663: J1939NodeName

Class	J1939ProtectedIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Represents the SDM (Safety Data Message) that contains the actual payload (signals) of the E2E protected J1939 message. Tags: atp.Status=draft atp.recommendedPackage=Pdus			
Base	ARElement, ARObject, CollectableElement, FibexElement, IPdu, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
payload	PduTriggering	0..1	ref	References the ISignalIPdu that represents the SDG (Safety Data Group) that contains both the payload (signals) and the E2E protection data of the protected J1939 message. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=payload.pduTriggering, payload.variation Point.shortLabel atp.Status=draft vh.latestBindingTime=postBuild
srvt	TimeValue	0..1	attr	Maximum time between SHM (Safety Header Message) and SDM (Safety Data Message) of one SDG (Safety Data Group) Tags: atp.Status=draft

Table A.664: J1939ProtectedIPdu

Class	J1939TpConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	This element defines exactly one J1939 TP Configuration. One J1939TpConfig element shall be created for each J1939 Network in the System. Tags: atp.recommendedPackage=TpConfigs			
Base	ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, TpConfig			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
tpAddress	TpAddress	*	aggr	Collection of TP Adresses. atpVariation: Derived, because EcuInstance can vary. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=tpAddress.shortName, tpAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
tpConnection	J1939TpConnection	*	aggr	Configuration of J1939 TP connections. atpVariation: Derived, because TpNode can vary. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=tpConnection, tpConnection.variationPoint.shortLabel vh.latestBindingTime=postBuild
tpNode	J1939TpNode	*	aggr	Senders and receivers of J1939 TP messages. atpVariation: Derived, because EcuInstance can vary. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=tpNode.shortName, tpNode.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.665: J1939TpConfig

Class	J1939TpConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	A J1939TpConnection represents an internal path for the transmission or reception of a Pdu via J1939Tp and describes the sender and the receiver of this particular communication. The J1939Tp module routes a Pdu (J1939 PGN) through the connection.			
Base	ARObject, TpConnection			
Aggregated by	J1939TpConfig.tpConnection			
Attribute	Type	Mult.	Kind	Note
acceptVariable DA	Boolean	0..1	attr	The TP message is accepted independently of the actually used destination address (DA). Otherwise, only the destination address configured as receiver.tpAddress is accepted. Only derived for the receiving ECU.
acceptVariable SA	Boolean	0..1	attr	The TP message is accepted independently of the actually used source address (SA). Otherwise, only the source address configured as transmitter.tpAddress is accepted. Only derived for the receiving ECU.





Class	J1939TpConnection			
broadcast	Boolean	0..1	attr	BAM (Broadcast Announce Message) is a broadcast protocol. If this attribute is set to true broadcast is used. Since address FF is the only broadcast address, there's no reason to configure it. Tags: atp.Status=obsolete
bufferRatio	PositiveInteger	0..1	attr	Defines usage of available data for dynamic block size calculation when protocol retry is enabled. This attribute describes in percent of available buffer that shall be used for retry.
cancellation	Boolean	0..1	attr	Enable support for Tx/Rx cancellation.
dataPdu	NPdu	0..1	ref	Data Message (TP.DT) used by CMDT and BAM. The DataNPdu has a fixed length of 8 bytes.
dynamicBs	Boolean	0..1	attr	Enable support for dynamic block size calculation.
flowControlPdu	NPdu	0..2	ref	Reference to the Command NPdus (TP.CM) that are used in the CMDT (Connection Mode Data Transfer) in both directions. BAM uses one TP.CM (Transport Protocol Command). The flowControlNPdu has a fixed length of 8 bytes. Please note that the role name "flowControlIPdu" is misleading and is kept for backward compatibility reasons.
maxBs	PositiveInteger	0..1	attr	Set maximum block size (number of packets in TP.CM_CTS).
maxExpBs	PositiveInteger	0..1	attr	Set maximum for expected block size (maximum number of packets in TP.CM_RTS).
receiver	J1939TpNode	*	ref	The target of the TP connection.
retry	Boolean	0..1	attr	Enable support for protocol retry.
tpPg	J1939TpPg	*	aggr	J1939 messages (parameter groups, PGs) that can be transferred via this connection.
tpProtocolType	J1939TpProtocolType Enum	0..1	attr	Protocol type used by the J1939TpConnection
transmitter	J1939TpNode	0..1	ref	The source of the TP connection.
useVariableDA	Boolean	0..1	attr	The TP message is sent with variable destination address (DA). Otherwise, the destination address configured as receiver.tpAddress is always used. Only derived for the transmitting ECU.
useVariableSA	Boolean	0..1	attr	The TP message is sent with variable source address (SA). Otherwise, the source address configured as transmitter.tpAddress is always used. Only derived for the transmitting ECU.

Table A.666: J1939TpConnection

Class	J1939TpNode			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	TP Node (Sender or Receiver) provides the TP Address and the connection to the Topology description.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	J1939TpConfig.tpNode			
Attribute	Type	Mult.	Kind	Note





Class		J1939TpNode		
connector	CommunicationConnector	0..1	ref	Association to a CommunicationConnector in the topology description. In a System Description this reference is mandatory. In an ECU Extract this reference is optional (references to ECUs that are not part of the ECU Extract shall be avoided).
tpAddress	TpAddress	0..1	ref	Reference to the TP Address that is used by the TpNode. This reference is optional only when no TP is sent and only BAM is received.

Table A.667: J1939TpNode

Class		J1939TpPg		
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	A J1939TpPg represents one J1939 message (parameter group, PG) identified by the PGN (parameter group number) that can be received or transmitted via J1939Tp.			
Base	<i>ARObject</i>			
Aggregated by	J1939TpConnection.tpPg			
Attribute	Type	Mult.	Kind	Note
directPdu	NPdu	0..1	ref	In case of variable length IPdus (with system signals of variable length), an additional NPdu (with the PGN in the CAN ID) is used for messages with up to 8 bytes.
pgn	Integer	0..1	attr	Parameter group number (PGN) of a J1939 message (parameter group, PG) that can be received or transmitted via J1939Tp. The PGN may be omitted when the a directPdu is referenced and is mapped into a Can FrameTriggering with an identifier.
requestable	Boolean	0..1	attr	Parameter Group can be triggered by the J1939 request message.
sdu	IPdu	*	ref	Reference to IPdus that are segmented by the Transport Protocol. If more than one IPdu is referenced, the IPdus are used when the same PGN is received in parallel via different transport protocols (BAM, CMDT, direct) on the same J1939TpConnection.

Table A.668: J1939TpPg

Class		«atpMixedString» LParagraph		
Package	M2::MSR::Documentation::TextModel::LanguageDataModel			
Note	This is the text for a paragraph in one particular language. The language is denoted in the attribute l.			
Base	<i>ARObject</i> , <i>LanguageSpecific</i> , MixedContentForParagraph			
Aggregated by	MultiLanguageParagraph.l1			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.669: LParagraph

Enumeration	LatencyConstraintTypeEnum
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::LatencyTimingConstraint
Note	Specifies the latencyConstraintType for a LatencyTimingConstraint .
Aggregated by	LatencyTimingConstraint.latencyConstraintType
Literal	Description
age	The LatencyTimingConstraint is seen from the perspective of the response event of the scope . Given a certain response event, the age interval of the latest stimulus is constrained. Tags: atp.EnumerationLiteralIndex=0
reaction	The LatencyTimingConstraint is seen from the perspective of the stimulus event of the scope . Given a certain stimulus event, the reaction interval of the first response is constrained. Tags: atp.EnumerationLiteralIndex=1

Table A.670: LatencyConstraintTypeEnum

Class	LatencyTimingConstraint			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::LatencyTimingConstraint			
Note	Constrains the time duration between the occurrence of the stimulus and the occurrence of the corresponding response of that scope . In contrast to scope , a causal dependency between the stimulus and the corresponding response of the scope is required.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
latencyConstraintType	LatencyConstraintTypeEnum	0..1	attr	The specific type of this latency constraint.
maximum	MultidimensionalTime	0..1	aggr	The maximum latency between the occurrence of the stimulus and the occurrence of the corresponding response of the associated event chain. Tags: xml.sequenceOffset=20
minimum	MultidimensionalTime	0..1	aggr	The minimum latency between the occurrence of the stimulus and the occurrence of the corresponding response of the associated event chain. Tags: xml.sequenceOffset=10
nominal	MultidimensionalTime	0..1	aggr	The nominal latency between the occurrence of the stimulus and the occurrence of the corresponding response of the associated event chain. Tags: xml.sequenceOffset=30
scope	TimingDescriptionEventChain	0..1	ref	The event chain that defines the scope of the constraint.

Table A.671: LatencyTimingConstraint

Class	LifeCycleInfo			
Package	M2::AUTOSARTemplates::GenericStructure::LifeCycles			
Note	LifeCycleInfo describes the life cycle state of an element together with additional information like what to use instead			
Base	ARObject			
Aggregated by	LifeCycleInfoSet.lifeCycleInfo			
Attribute	Type	Mult.	Kind	Note
lcObject	Referrable	1	ref	Element(s) have the life cycle as described in lcState.





Class	LifeCycleInfo			
lcState	LifeCycleState	0..1	ref	This denotes the particular state assigned to the object. If no lcState is given then the default life cycle state of LifeCycleInfoSet is assumed.
periodBegin	LifeCyclePeriod	0..1	aggr	Starting point of period in which the element has the denoted life cycle state lcState. If no periodBegin is given then the default period begin of LifeCycleInfoSet is assumed.
periodEnd	LifeCyclePeriod	0..1	aggr	Expiry date, i.e. end point of period the element does not have the denoted life cycle state lcState any more. If no periodEnd is given then the default period begin of LifeCycleInfoSet is assumed.
remark	DocumentationBlock	0..1	aggr	Remark describing for example <ul style="list-style-type: none"> • why the element was given the specified life cycle • the semantics of useInstead
useInstead	Referrable	*	ref	Element(s) that should be used instead of the one denoted in referrable. Only relevant in case of life cycle states lcState unlike "valid". In case there are multiple references the exact semantics shall be individually described in the remark.

Table A.672: LifeCycleInfo

Class	LifeCycleInfoSet			
Package	M2::AUTOSARTemplates::GenericStructure::LifeCycles			
Note	This meta class represents the ability to attach a life cycle information to a particular set of elements. The information can be defined for a particular period. This supports the definition of transition plans. If no period is specified, the life cycle state applies forever. Tags: atp.recommendedPackage=LifeCycleInfoSets			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
defaultLcState	LifeCycleState	1	ref	This denotes the default life cycle state. To be used in all LifeCycleInfo elements within the LifeCycleInfoSet if no life cycle state is stated there explicitly. I.e. the defaultLcState can be overwritten in LifeCycleInfo elements.
defaultPeriodBegin	LifeCyclePeriod	0..1	aggr	Default starting point of period in which all the specified lifeCycleInfo apply. Note that the default period can be overridden for each lifeCycleInfo individually.
defaultPeriodEnd	LifeCyclePeriod	0..1	aggr	Default expiry date, i.e. default end point of period for which all specified lifeCycleInfo apply. Note that the default period can be overridden for each lifeCycleInfo individually.
lifeCycleInfo	LifeCycleInfo	*	aggr	This represents one particular life cycle information.
usedLifeCycleStateDefinitionGroup	LifeCycleStateDefinitionGroup	1	ref	This denotes the life cycle states applicable to the current life cycle info set.

Table A.673: LifeCycleInfoSet

Class	LifeCyclePeriod			
Package	M2::AUTOSARTemplates::GenericStructure::LifeCycles			
Note	This meta class represents the ability to specify a point of time within a specified period, e.g. the starting or end point, in which a specific life cycle state is valid/applies to.			
Base	<i>ARObject</i>			
Aggregated by	LifeCycleInfo.periodBegin , LifeCycleInfo.periodEnd , LifeCycleInfoSet.defaultPeriodBegin , LifeCycleInfoSet.defaultPeriodEnd			
Attribute	Type	Mult.	Kind	Note
arReleaseVersion	RevisionLabelString	0..1	attr	Version of the AUTOSAR Release the element referred to is part of. The numbering contains three levels (major, minor, revision) which are defined by AUTOSAR. Tags: xml.sequenceOffset=20
date	DateTime	0..1	attr	Date within period. Tags: xml.sequenceOffset=10
productRelease	RevisionLabelString	0..1	attr	Version of the product within the period. Tags: xml.sequenceOffset=30

Table A.674: LifeCyclePeriod

Class	LifeCycleState			
Package	M2::AUTOSARTemplates::GenericStructure::LifeCycles			
Note	This meta class represents one particular state in the LifeCycle.			
Base	<i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	LifeCycleStateDefinitionGroup.IcState			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.675: LifeCycleState

Class	LifeCycleStateDefinitionGroup			
Package	M2::AUTOSARTemplates::GenericStructure::LifeCycles			
Note	This meta class represents the ability to define the states and properties of one particular life cycle. Tags: atp.recommendedPackage=LifeCycleStateDefintionGroups			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>CollectableElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
IcState	LifeCycleState	*	aggr	Describes a single life cycle state of this life cycle state definition group.

Table A.676: LifeCycleStateDefinitionGroup

Primitive	Limit			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes			
Note	<p>This class represents the ability to express a numerical limit. Note that this is in fact a NumericalVariation Point but has the additional attribute intervalType.</p> <p>Tags: xml.xsd.customType=LIMIT-VALUE xml.xsd.pattern=(0[xX][0-9a-fA-F+) (0[0-7+) (0[bB][0-1+) (([\-\+]?[1-9][0-9]+\.[0-9+)? [\-\+]?[0-9]\.[0-9+)?)([eE]([\-\+]?[0-9+)?)\.0 INF INF NaN xml.xsd.type=string</p>			
Attribute	Type	Mult.	Kind	Note
intervalType	IntervalTypeEnum	0..1	attr	<p>This specifies the type of the interval. If the attribute is missing the interval shall be considered as "CLOSED".</p> <p>Tags: xml.attribute=true</p>

Table A.677: Limit

Class	«atpVariation» LinCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	<p>LIN specific attributes</p> <p>Tags: atp.recommendedPackage=CommunicationClusters</p>			
Base	ARElement , ARObject , CollectableElement , CommunicationCluster , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.678: LinCluster

Class	LinCommunicationConnector			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	LIN bus specific communication connector attributes.			
Base	ARObject , CommunicationConnector , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EcuInstance.connector , MachineDesign.communicationConnector			
Attribute	Type	Mult.	Kind	Note
initialNad	Integer	0..1	attr	Initial NAD of the LIN slave.
linConfigurableFrame	LinConfigurableFrame	*	aggr	LinConfigurableFrames shall list all frames (unconditional frames, event-triggered frames and sporadic frames) processed by the slave node. This element is necessary for the LIN 2.0 Assign-Frame command.
linOrderedConfigurableFrame	LinOrderedConfigurableFrame	*	aggr	LinOrderedConfigurableFrames shall list all frames (unconditional frames, event-triggered frames and sporadic frames) processed by the slave node. This element is necessary for the LIN 2.1 Assign-Frame-PID-Range command.
scheduleChangeNextTimeBase	Boolean	0..1	attr	This attribute defines the point in time where a schedule table switch is performed. If this attribute is set to false or not present, the schedule table shall be switched after the current entry of the active schedule table is ended. If this attribute is enabled, the schedule table shall be switched when message transmission or reception within an entry has been completed, ensured by status checks for transmission and reception.

Table A.679: LinCommunicationConnector

Class	«atpVariation» LinCommunicationController (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	LIN bus specific communication controller attributes.			
Base	ARObject , CommunicationController , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	LinMaster , LinSlave			
Aggregated by	EcuInstance.commController , MachineDesign.communicationController			
Attribute	Type	Mult.	Kind	Note
protocolVersion	String	0..1	attr	Version specifier for a communication protocol.

Table A.680: LinCommunicationController

Class	LinConfigurableFrame			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	Assignment of messageIds to Frames. This element shall be used for the LIN 2.0 Assign-Frame command.			
Base	ARObject			
Aggregated by	LinCommunicationConnector.linConfigurableFrame , LinSlaveConfig.linConfigurableFrame			
Attribute	Type	Mult.	Kind	Note
frame	LinFrame	0..1	ref	Reference to a Frame that is processed by the slave node.
messageId	PositiveInteger	0..1	attr	MessageId for the referenced frame

Table A.681: LinConfigurableFrame

Class	LinErrorResponse			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Each slave node shall publish a one bit signal, named response_error, to the master node in one of its transmitted unconditional frames. The response_error signal shall be set whenever a frame (except for event triggered frame responses) that is transmitted or received by the slave node contains an error in the frame response. The response_error signal shall be cleared when the unconditional frame containing the response_error signal is successfully transmitted.			
Base	ARObject			
Aggregated by	LinSlave.linErrorResponse , LinSlaveConfig.linErrorResponse			
Attribute	Type	Mult.	Kind	Note
responseError	ISignalTriggering	0..1	ref	This ISignal shall be taken to transport the responseError bit.

Table A.682: LinErrorResponse

Class	LinEventTriggeredFrame			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	<p>An event triggered frame is used as a placeholder to allow multiple slave nodes to provide its response.</p> <p>The header of an event triggered frame is transmitted when a frame slot allocated to the event triggered frame is processed. The publisher of an associated unconditional frame shall only transmit the response if at least one of the signals carried in its unconditional frame is updated. The LIN Master discovers and purges collisions with the collisionResolvingScheduleTable.</p> <p>The event controlled frame shall not contain any Pdus.</p> <p>Tags: atp.recommendedPackage=Frames</p>			





Class	LinEventTriggeredFrame			
Base	<i>ARObject, CollectableElement, FibexElement, Frame, Identifiable, LinFrame, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
collision Resolving Schedule	LinScheduleTable	0..1	ref	Reference to the schedule table, which resolves a collision.
linUnconditional Frame	LinUnconditionalFrame	*	ref	<p>A list of slaves can respond to the master request if at least one of the signals carried in its unconditional frame is updated. For each response a LinFrameTriggering and a LinUnconditionalFrame shall be defined. Within a channel a LIN Frame shall be referenced by only one FrameTriggering. This allows a derivation of the identifier of a substituted Frame. The identifier is specified in FrameTriggering element. The Unconditional frames associated with an event triggered frame shall:</p> <ul style="list-style-type: none"> • have equal length. • use the same checksum model (i.e. mixing LIN 1.x and LIN 2.x frames is not allowed). • reserve the first data field to its protected identifier (even if the associated unconditional frame is scheduled as a unconditional frame in the same or another schedule table). • be published by different slave nodes. • shall not be included directly in the same schedule table as the event triggered frame is scheduled.

Table A.683: LinEventTriggeredFrame

Class	LinFrame (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Lin specific Frame element.			
Base	<i>ARObject, CollectableElement, FibexElement, Frame, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Subclasses	LinEventTriggeredFrame , LinSporadicFrame , LinUnconditionalFrame			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.684: LinFrame

Class	LinFrameTriggering			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	LIN specific attributes to the FrameTriggering			
Base	<i>ARObject, FrameTriggering, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	PhysicalChannel.frameTriggering			
Attribute	Type	Mult.	Kind	Note





Class	LinFrameTriggering			
identifier	Integer	0..1	attr	To describe a frames identifier on the communication system, usually with a fixed identifierValue. For LinSporadicFrames the attribute shall be ignored.
linChecksum	LinChecksumType	0..1	attr	Type of checksum that the frame is using. This attribute is optional because in case of sporadic frames it should not be set.

Table A.685: LinFrameTriggering

Class	«atpVariation» LinMaster			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	Describing the properties of the referring ecu as a LIN master.			
Base	ARObject, CommunicationController, Identifiable, LinCommunicationController, MultilanguageReferrable, Referrable			
Aggregated by	EcuInstance.commController, MachineDesign.communicationController			
Attribute	Type	Mult.	Kind	Note
linSlave	LinSlaveConfig	*	aggr	LinSlaves that are handled by the LinMaster.
timeBase	TimeValue	0..1	attr	Time base is mandatory for the master. It is not used for slaves. LIN 2.0 Spec states: "The time_base value specifies the used time base in the master node to generate the maximum allowed frame transfer time." The time base shall be specified AUTOSAR conform in seconds.
timeBaseJitter	TimeValue	0..1	attr	The attribute timeBaseJitter is a mandatory attribute for the master and not used for slaves. LIN 2.0 Spec states: "The jitter value specifies the differences between the maximum and minimum delay from time base start point to the frame header sending start point (falling edge of BREAK signal)." The jitter shall be specified AUTOSAR conform in seconds.

Table A.686: LinMaster

Class	LinOrderedConfigurableFrame			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	With the assignment of the index to a frame a mapping of Pids to Frames is possible. This element shall be used for the LIN 2.1 Assign-Frame-PID-Range command.			
Base	ARObject			
Aggregated by	LinCommunicationConnector.linOrderedConfigurableFrame, LinSlaveConfig.linOrderedConfigurableFrame			
Attribute	Type	Mult.	Kind	Note
frame	LinFrame	0..1	ref	Reference to a Frame that is processed by the slave node.
index	Integer	0..1	attr	This attribute is used to order the elements and allows an assignment of Pids to ConfigurableFrames that are defined in the slave.

Table A.687: LinOrderedConfigurableFrame

Class	LinPhysicalChannel			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	LIN specific attributes to the physicalChannel			
Base	ARObject, Identifiable , MultilanguageReferrable , PhysicalChannel , Referrable			
Aggregated by	CommunicationCluster .physicalChannel			
Attribute	Type	Mult.	Kind	Note
busIdleTimeoutPeriod	TimeValue	0..1	attr	This attribute shall be used to set an idle timeout period for the enclosing LinPhysicalChannel.
scheduleTable	LinScheduleTable	*	aggr	Schedule tables organize the timings of the frames for LIN. atpVariation: If the transmitted frames are variable, the corresponding ScheduleTables shall be variable, too. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=scheduleTable.shortName, scheduleTable.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.688: LinPhysicalChannel

Class	LinScheduleTable			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	The master task (in the master node) transmits frame headers based on a schedule table. The schedule table specifies the identifiers for each header and the interval between the start of a frame and the start of the following frame.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	LinPhysicalChannel .scheduleTable			
Attribute	Type	Mult.	Kind	Note
resumePosition	ResumePosition	0..1	attr	Defines, where a schedule table shall be proceeded in case if it has been interrupted by a run-once table or MRF/SRF.
runMode	RunMode	0..1	attr	The schedule table can be executed in two different modes.
tableEntry	ScheduleTableEntry	*	aggr	The scheduling table consists of table entries, which contain Frame slots.

Table A.689: LinScheduleTable

Class	«atpVariation» LinSlave			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	Describing the properties of the referring ecu as a LIN slave.			
Base	ARObject, CommunicationController , Identifiable , LinCommunicationController , MultilanguageReferrable , Referrable			
Aggregated by	EcuInstance .commController, MachineDesign.communicationController			
Attribute	Type	Mult.	Kind	Note
assignNad	Boolean	0..1	attr	This attribute has the ability to control whether the node configuration command 'Assign NAD' is supported.
configuredNad	Integer	0..1	attr	To distinguish LIN slaves that are used twice or more within the same cluster.
functionId	PositiveInteger	0..1	attr	LIN function ID
initialNad	Integer	0..1	attr	This attribute represents the initial NAD.





Class	«atpVariation» LinSlave			
linErrorResponse	LinErrorResponse	0..1	aggr	Each slave node shall publish one response error in one of its transmitted unconditional frames.
nasTimeout	TimeValue	0..1	attr	Value of the N_AS timeout. Unit: seconds.
supplierId	PositiveInteger	0..1	attr	LIN Supplier ID
variantId	PositiveInteger	0..1	attr	Specifies the Variant ID

Table A.690: LinSlave

Class	LinSlaveConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinTopology			
Note	Node attributes of LIN slaves that are handled by the LinMaster. In the System Description LIN slaves may be described in the context of the Lin Master. In an ECU Extract of the LinMaster the LinSlave Ecus shall not be available. The information that is described here is necessary in the ECU Extract for the configuration of the Lin Master. The values of attributes of LinSlaveConfig and the corresponding LinSlave shall be identical (if both are defined in a System Description).			
Base	ARObject			
Aggregated by	LinMaster.linSlave			
Attribute	Type	Mult.	Kind	Note
configuredNad	Integer	0..1	attr	To distinguish LIN slaves that are used twice or more within the same cluster.
functionId	PositiveInteger	0..1	attr	LIN function ID.
ident	LinSlaveConfigIdent	0..1	aggr	This adds the ability to become referable to LinSlave Config.
initialNad	Integer	0..1	attr	Initial NAD of the LIN slave.
linConfigurableFrame	LinConfigurableFrame	*	aggr	List of all frames that are processed by the slave node
linErrorResponse	LinErrorResponse	0..1	aggr	Each slave node shall publish one response error in one of its transmitted unconditional frames.
linOrderedConfigurableFrame	LinOrderedConfigurableFrame	*	aggr	List of all frames (unconditional frames, event-triggered frames and sporadic frames) processed by the slave node. This element is necessary for the LIN 2.1 Assign-Frame-PID-Range command.
protocolVersion	String	0..1	attr	Version specifier for a communication protocol. Protocol version of the LinMaster and the LinSlaves may be different.
supplierId	PositiveInteger	0..1	attr	LIN Supplier ID.
variantId	PositiveInteger	0..1	attr	Specifies the Variant ID.

Table A.691: LinSlaveConfig

Class	LinSporadicFrame
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication
Note	A sporadic frame is a group of unconditional frames that share the same frame slot. The sporadic frame shall not contain any Pcus. Tags: atp.recommendedPackage=Frames





Class	LinSporadicFrame			
Base	<i>ARObject, CollectableElement, FibexElement, Frame, Identifiable, LinFrame, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
substituted Frame (ordered)	LinUnconditionalFrame	*	ref	<p>Reference to a group of unconditional frames that share the same frame slot. In case that more than one of the declared frames needs to be transferred, the one first listed shall be chosen.</p> <p>Within a channel a LIN Frame shall be referenced by only one FrameTriggering. This allows a derivation of the identifier of a substituted Frame. The identifier is specified in FrameTriggering element.</p> <p>A LinUnconditionalFrame associated with a LinSporadicFrame may not be allocated in the same LinSchedule Table as the sporadic frame.</p>

Table A.692: LinSporadicFrame

Class	LinTpConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	<p>This element defines exactly one Lin TP Configuration.</p> <p>One LinTpConfig element shall be created for each Lin Network in the System.</p> <p>Tags: atp.recommendedPackage=TpConfigs</p>			
Base	<i>ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, TpConfig</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
tpAddress	TpAddress	*	aggr	<p>Collection of TpAddresses.</p> <p>atpVariation: Derived, because EcuInstance can vary.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=tpAddress.shortName, tpAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
tpConnection	LinTpConnection	*	aggr	<p>Configuration of LIN TP channels.</p> <p>atpVariation: Derived, because TpNode can vary.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=tpConnection, tpConnection.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
tpNode	LinTpNode	*	aggr	<p>Senders and receivers of LIN TP messages.</p> <p>atpVariation: Derived, because EcuInstance can vary.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=tpNode.shortName, tpNode.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>

Table A.693: LinTpConfig

Class	LinTpConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	<p>A LinTP channel represents an internal path for the transmission or reception of a Pdu via LinTp and describes the sender and the receiver of this particular communication.</p> <p>LinTp supports (per Lin Cluster) the configuration of one Rx Tp-SDU and one Tx Tp-SDU per NAD the LinMaster uses to address one or more of its Lin Slaves. To support this an arbitrary number of LinTp Connections shall be described.</p>			
Base	<i>ARObject</i> , <i>TpConnection</i>			
Aggregated by	LinTpConfig.tpConnection			
Attribute	Type	Mult.	Kind	Note
dataPdu	NPdu	0..1	ref	<p>Reference to an NPdu (Single Frame, First Frame or Consecutive Frame).</p> <p>The Single Frame network protocol data unit (SF N_PDU) shall be sent out by the sending network entity and can be received by one or multiple receiving network entities. The Single Frame (SF N_PDU) shall be sent out to transfer a service data unit that can be transferred via a single service request to the data link layer. This network protocol data unit shall be sent to transfer unsegmented messages.</p> <p>The First Frame network protocol data unit (FF N_PDU) identifies the first network protocol data unit (N_PDU) of a segmented message transmitted by a network sending entity and received by a receiving network entity.</p> <p>The Consecutive Frame network protocol data unit (CF N_PDU) transfers segments (N_Data) of the service data unit message data (<MessageData>). All network protocol data units (N_PDUs) transmitted by the sending entity after the First Frame network protocol data unit (FF N_PDU) shall be encoded as Consecutive Frames network protocol data units (CF N_PDUs).</p>
flowControl	NPdu	0..1	ref	<p>Reference to the Flow Control NPdu.</p> <p>The Flow Control network protocol data unit (FC N_PDU) is identified by the Flow Control protocol control information (FC N_PCI). The Flow Control network protocol data unit (FC N_PDU) instructs a sending network entity to start, stop or resume transmission of CF N_PDUs. The Flow Control network protocol data unit shall be sent by the receiving network layer entity to the sending network layer entity, when ready to receive more data, after correct reception of:</p> <ul style="list-style-type: none"> a) First Frame network protocol data unit (FF N_PDU) b) the last Consecutive Frame network protocol data unit (CF N_PDU) of a block of Consecutive Frames (CF N_PDU) if further Consecutive Frame network protocol data unit (CF N_PDU) need(s) to be sent.
linTpNSdu	IPdu	0..1	ref	Reference to the IPdu that is segmented by the Transport Protocol.
multicast	TpAddress	0..1	ref	TP address for 1:n connections.
receiver	LinTpNode	*	ref	The target of the TP connection.
timeoutAs	TimeValue	0..1	attr	Time for transmission of the LIN frame (any N-PDU) on the sender side. Specified in seconds.
timeoutCr	TimeValue	0..1	attr	This attribute defines the timeout value for waiting for a CF or FF-x (in case of retry) after receiving the last CF or after sending an FC or AF on the receiver side. Specified in seconds.





Class	LinTpConnection			
timeoutCs	TimeValue	0..1	attr	The attribute timeoutCs represents the time (in seconds) which elapses between the transmit request of a CF N-PDU until the transmit request of the next CF N-PDU.
transmitter	LinTpNode	0..1	ref	The source of the TP connection.

Table A.694: LinTpConnection

Class	LinTpNode			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	TP Node (Sender or Receiver) provides the TP Address and the connection to the Topology description.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	LinTpConfig.tpNode			
Attribute	Type	Mult.	Kind	Note
connector	CommunicationConnector	0..1	ref	Association to a CommunicationConnector in the topology description. In a System Description this reference is mandatory. In an ECU Extract this reference is optional (references to ECUs that are not part of the ECU Extract shall be avoided).
dropNotRequestedNad	Boolean	0..1	attr	Configures if TP Frames of not requested LIN-Slaves are dropped or not.
maxNumberOfRespPendingFrames	Integer	0..1	attr	Configures the maximum number of allowed response pending frames.
p2Max	TimeValue	0..1	attr	After reception of a response pending frame the P2 timeout counter is reloaded with the timeout time P2max.
p2Timing	TimeValue	0..1	attr	P2 timeout observation parameter.
tpAddress	TpAddress	0..1	ref	Reference to the TP Address that is used by the TpNode. This reference is optional in case that the multicast TP Address is used (reference from TpConnection).

Table A.695: LinTpNode

Class	LinUnconditionalFrame			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Unconditional frames carry signals. The master sends a frame header in a scheduled frame slot and the designated slave node fills the frame with data. Tags: atp.recommendedPackage=Frames			
Base	<i>ARObject</i> , <i>CollectableElement</i> , <i>FibexElement</i> , <i>Frame</i> , <i>Identifiable</i> , <i>LinFrame</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.696: LinUnconditionalFrame

Class	MacAddressVlanMembership			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Assigns a set of MAC-Multicast-Addresses which are addressable via the CouplingPort aggregating this MacAddressVlanMembership. Optionally also assigns a set of VLANs to this relation. This is a static pre-configuration and further addresses may be learned during runtime.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CouplingPort.macAddressVlanAssignment			
Attribute	Type	Mult.	Kind	Note
macMulticast Address	MacMulticastGroup	*	ref	Defines a set of macMulticastAddresses to be mapped to the CouplingPort.
vlan	EthernetPhysical Channel	*	ref	Defines a set of VLANs the set of macMulticastAddress apply to.

Table A.697: MacAddressVlanMembership

Class	MacMulticastConfiguration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	References a per cluster globally defined MAC-Multicast-Group.			
Base	ARObject, NetworkEndpointAddress			
Aggregated by	NetworkEndpoint.networkEndpointAddress			
Attribute	Type	Mult.	Kind	Note
macMulticast Group	MacMulticastGroup	0..1	ref	Reference to a macMulticastGroup.

Table A.698: MacMulticastConfiguration

Class	MacMulticastGroup			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Per EthernetCluster globally defined MacMulticastGroup. One sender can handle many receivers simultaneously if the receivers have all the same macMulticastAddress. The addresses need to be unique for the particular EthernetCluster.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EthernetCluster.macMulticastGroup			
Attribute	Type	Mult.	Kind	Note
macMulticast Address	MacAddressString	0..1	attr	A multicast MAC address (Media Access Control address) is a identifier for a group of hosts in a network.

Table A.699: MacMulticastGroup

Class	MacSecProps			
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This meta-class allows to configure MACsec (Media access control security) and the MKA (MACsec Key Agreement) for the CouplingPort (PHY). Tags: atp.Status=candidate			
Base	ARObject			
Aggregated by	CouplingPort.macSecProps			
Attribute	Type	Mult.	Kind	Note





Class	MacSecProps			
autoStart	Boolean	0..1	attr	This attribute defines how the Port Access Entity (PAE) is started: <ul style="list-style-type: none"> • true := Autostart • false := Manual Start Tags: atp.Status=candidate
macSecKey Config	MacSecLocalKayProps	0..1	aggr	Properties to configure the MKA instance (KaY) for a controlled CouplingPort (PaE). Tags: atp.Status=candidate
onFail Permissive Mode	MacSecFailPermissive ModeEnum	0..1	attr	This attribute sets the behavior of the Port Access Entity in case MACsec does not succeed. Tags: atp.Status=candidate
onFail Permissive ModeTimeout	TimeValue	0..1	attr	Timeout in seconds to enable the controlled port in case onFailPermissiveMode is set to Timeout. Tags: atp.Status=candidate
sakRekeyTime Span	TimeValue	0..1	attr	Time in seconds to trigger the rekey of an in use SAK (Static Secure Association key). If set to 0, the rekey will not be triggered after a time span. Tags: atp.Status=candidate

Table A.700: MacSecProps

Class	McDataAccessDetails			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport			
Note	<p>This meta-class allows to attach detailed information about the usage of a data buffer by the RTE to a corresponding McDataInstance.</p> <p>Use Case: Direct memory access to RTE internal buffers for rapid prototyping. In case of implicit communication, the various task local buffers need to be identified in relation to RTE events and variable access points.</p> <p>Note that the SwComponentPrototype, the RunnableEntity and the VariableDataPrototype are implicitly given be the referred instances of RTEEvent and VariableAccess.</p>			
Base	ARObject			
Aggregated by	McDataInstance.mcDataAccessDetails			
Attribute	Type	Mult.	Kind	Note
rteEvent	RTEEvent	*	iref	The RTE event used to receive the data via this buffer. InstanceRef implemented by: RteEventInEcuInstanceRef
variableAccess	VariableAccess	*	iref	The VariableAccess for which the data buffer is used. InstanceRef implemented by: VariableAccessInEcuInstanceRef

Table A.701: McDataAccessDetails

Class	McDataInstance			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport			
Note	<p>Describes the specific properties of one data instance in order to support measurement and/or calibration of this data instance.</p> <p>The most important attributes are:</p> <ul style="list-style-type: none"> • Its shortName is copied from the ECU Flat map (if applicable) and will be used as identifier and for display by the MC system. • The category is copied from the corresponding data type (ApplicationDataType if defined, otherwise ImplementationDataType) as far as applicable. • The symbol is the one used in the programming language. It will be used to find out the actual memory address by the final generation tool with the help of linker generated information. <p>It is assumed that in the M1 model this part and all the aggregated and referred elements (with the exception of the Flat Map and the references from ImplementationElementInParameterInstanceRef and McAccessDetails) are completely generated from "upstream" information. This means, that even if an element like e.g. a CompuMethod is only used via reference here, it will be copied into the M1 artifact which holds the complete McSupportData for a given Implementation.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	McDataInstance.subElement , McSupportData.mcParameterInstance , McSupportData.mcVariableInstance			
Attribute	Type	Mult.	Kind	Note
arraySize	PositiveInteger	0..1	attr	The existence of this attribute turns the data instance into an array of data. The attribute determines the size of the array in terms of number of elements.
displayIdentifier	McIdentifier	0..1	attr	An optional attribute to be used to set the ASAM ASAP2 DISPLAY_IDENTIFIER attribute.
flatMapEntry	FlatInstanceDescriptor	0..1	ref	<p>Reference to the corresponding entry in the ECU Flat Map. This allows to trace back to the original specification of the generated data instance. This link shall be added by the RTE generator mainly for documentation purposes.</p> <p>The reference is optional because</p> <ul style="list-style-type: none"> • The McDataInstance may represent an array or struct in which only the subElements correspond to FlatMap entries. • The McDataInstance may represent a task local buffer for rapid prototyping access which is different from the "main instance" used for measurement access.
instanceInMemory	ImplementationElementInParameterInstanceRef	0..1	aggr	Reference to the corresponding data instance in the description of calibration data structures published by the RTE generator. This is used to support emulation methods inside the ECU, it is not required for A2L generation.
mcDataAccessDetails	McDataAccessDetails	0..1	aggr	Refers to "upstream" information on how the RTE uses this data instance. Use Case: Rapid Prototyping
mcDataAssignment	RoleBasedMcDataAssignment	*	aggr	An assignment between McDataInstances. This supports the indication of related McDataElement implementing the of "RP global buffer", "RP global measurement buffer", "RP enabler flag".
resultingProperties	SwDataDefProps	0..1	aggr	These are the generated properties resulting from decisions taken by the RTE generator for the actually implemented data instance. Only those properties are relevant here, which are needed for the measurement and calibration system.
resultingRptSwPrototypingAccess	RptSwPrototypingAccess	0..1	aggr	Describes the implemented accessibility of data and modes by the rapid prototyping tooling.





Class	McDataInstance			
role	Identifier	0..1	attr	An optional attribute to be used for additional information on the role of this data instance, for example in the context of rapid prototyping.
rptImplPolicy	RptImplPolicy	0..1	aggr	Describes the implemented code preparation for rapid prototyping at data accesses for a hook based bypassing.
subElement (ordered)	McDataInstance	*	aggr	This relation indicates, that the target element is part of a "struct" which is given by the source element. This information will be used by the final generator to set up the correct addressing scheme. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
symbol	SymbolString	0..1	attr	This String is used to determine the memory address during final generation of the MC configuration data (e.g. "A2L" file) . It shall be the name of the element in the programming language such that it can be identified in linker generated information. In case the McDataInstance is part of composite data in the programming language, the symbol String may include parts denoting the element context, unless the context is given by the symbol attribute of an enclosing McDataInstance. This means in particular for the C language that the "." character shall be used as a separator between the name of a "struct" variable the name of one of its elements. The symbol can differ from the shortName in case of generated C data declarations. It is an optional attribute since it may be missing in case the instance represents an element (e.g. a single array element) which has no name in the linker map. Tags: atp.Splitkey=symbol

Table A.702: McDataInstance

Class	McFunction			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport			
Note	Represents a functional element to be used as input to support measurement and calibration. It is used to <ul style="list-style-type: none"> • assign calibration parameters to a logical function • assign measurement variables to a logical function • structure functions hierarchically Tags: atp.recommendedPackage=McFunctions			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
defCalprmSet	McFunctionDataRefSet	0..1	aggr	Refers to the set of adjustable data (= calibration parameters) defined in this function. Stereotypes: atpSplitable Tags: atp.Splitkey=defCalprmSet xml.sequenceOffset=10





Class	McFunction			
inMeasurementSet	McFunctionDataRefSet	0..1	aggr	Refers to the set of measurable input data for this function. Stereotypes: atpSplitable Tags: atp.Splitkey=inMeasurementSet xml.sequenceOffset=30
locMeasurementSet	McFunctionDataRefSet	0..1	aggr	Refers to the set of measurable local data in this function. Stereotypes: atpSplitable Tags: atp.Splitkey=locMeasurementSet xml.sequenceOffset=50
outMeasurementSet	McFunctionDataRefSet	0..1	aggr	Refers to the set of measurable output data from this function. Stereotypes: atpSplitable Tags: atp.Splitkey=outMeasurementSet xml.sequenceOffset=60
refCalprmSet	McFunctionDataRefSet	0..1	aggr	Refers to the set of adjustable data (= calibration parameters) referred by this function. Stereotypes: atpSplitable Tags: atp.Splitkey=refCalprmSet xml.sequenceOffset=20
subFunction	McFunction	*	ref	A sub-function that is seen as part of the enclosing function. Stereotypes: atpSplitable Tags: atp.Splitkey=subFunction xml.sequenceOffset=70

Table A.703: McFunction

Class	«atpVariation» McFunctionDataRefSet			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport::RptSupport			
Note	Refers to a set of data assigned to an McFunction in a particular role. The data are given <ul style="list-style-type: none"> • either by entries in a FlatMap • or by data instances that are part of MC support data. These two possibilities are exclusive within a given McFunctionDataRefSet. Which one to use depends on the process and tool environment. The set is subject to variability because the same functional model may be used with various representation of the data. Tags: vh.latestBindingTime=preCompileTime			
Base	<i>AObject</i>			
Aggregated by	McFunction.defCalprmSet , McFunction.inMeasurementSet , McFunction.locMeasurementSet , McFunction.outMeasurementSet , McFunction.refCalprmSet			
Attribute	Type	Mult.	Kind	Note





Class	«atpVariation» McFunctionDataRefSet			
flatMapEntry	FlatInstanceDescriptor	*	ref	Refers to an entry in a FlatMap that is part of the set, for example a calibration parameter or measured variable. Note: This atpSplittable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplittable Tags: xml.sequenceOffset=10
mcDataInstance	McDataInstance	*	ref	Refers to a data instance within MC support data that is part of the set, i.e. a calibration parameter or measured variable. Note: This atpSplittable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplittable Tags: xml.sequenceOffset=20

Table A.704: McFunctionDataRefSet

Class	McGroup			
Package	M2::AUTOSARTemplates::CommonStructure::McGroups			
Note	Represents a group element to be used as input to support measurement and calibration. It is used to provide selection lists (groups) of calibration parameters, measurement variables, and functions in a hierarchical manner (subGroups). Tags: atp.recommendedPackage=McFunctions			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
mcFunction	McFunction	*	ref	A McFunction that is seen as part of the enclosing group. Stereotypes: atpSplittable Tags: atp.Splitkey=mcFunction xml.sequenceOffset=40
refCalprmSet	McGroupDataRefSet	0..1	aggr	Refers to the set of adjustable data (= calibration parameters) referred by this McGroup. Stereotypes: atpSplittable Tags: atp.Splitkey=refCalprmSet xml.sequenceOffset=20
ref Measurement Set	McGroupDataRefSet	0..1	aggr	Refers to the set of measurable belonging to this Mc Group. Stereotypes: atpSplittable Tags: atp.Splitkey=refMeasurementSet xml.sequenceOffset=30
subGroup	McGroup	*	ref	A sub-group that is seen as part of the enclosing group. Stereotypes: atpSplittable Tags: atp.Splitkey=subGroup xml.sequenceOffset=10

Table A.705: McGroup

Class	«atpVariation» McGroupDataRefSet			
Package	M2::AUTOSARTemplates::CommonStructure::McGroups			
Note	<p>Refers to a set of data assigned to an McGroup in a particular role. The data are given</p> <ul style="list-style-type: none"> • either by entries in a FlatMap • or by data instances that are part of MC support data. <p>These two possibilities can be mixed within a given McGroupDataRefSet. Which one to use depends on the process and tool environment.</p> <p>The set is subject to variability because the same functional model may be used with various representation of the data.</p> <p>Tags: vh.latestBindingTime=preCompileTime</p>			
Base	ARObject			
Aggregated by	McGroup.refCalprmSet, McGroup.refMeasurementSet			
Attribute	Type	Mult.	Kind	Note
flatMapEntry	FlatInstanceDescriptor	*	ref	<p>Refers to an entry in a FlatMap that is part of the set, for example a calibration parameter or measured variable.</p> <p>Note: This atpSplitable property has no atp.Splitkey due to atpVariation (PropertySetPattern).</p> <p>Stereotypes: atpSplitable Tags: xml.sequenceOffset=50</p>
mcDataInstance	McDataInstance	*	ref	<p>Refers to a data instance within MC support data that is part of the set, i.e. a calibration parameter or measured variable.</p> <p>Note: This atpSplitable property has no atp.Splitkey due to atpVariation (PropertySetPattern).</p> <p>Stereotypes: atpSplitable Tags: xml.sequenceOffset=60</p>

Table A.706: McGroupDataRefSet

Class	McParameterElementGroup			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport			
Note	Denotes a group of calibration parameters which are handled by the RTE as one data structure.			
Base	ARObject			
Aggregated by	McSwEmulationMethodSupport.elementGroup			
Attribute	Type	Mult.	Kind	Note
ramLocation	VariableDataPrototype	0..1	ref	Refers to the RAM location of this parameter group. To be used for the init-RAM method.
romLocation	ParameterData Prototype	0..1	ref	Refers to the ROM location of this parameter group. To be used for the init-RAM method.
shortLabel	Identifier	0..1	attr	<p>Assigns a name to this element.</p> <p>Tags: xml.sequenceOffset=-100</p>

Table A.707: McParameterElementGroup

Class	McSupportData			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport			
Note	Root element for all measurement and calibration support data related to one Implementation artifact on an ECU. There shall be one such element related to the RTE implementation (if it owns MC data) and a separate one for each module or component, which owns private MC data.			
Base	ARObject			





Class		McSupportData			
Aggregated by		Implementation.mcSupport			
Attribute	Type	Mult.	Kind	Note	
emulation Support	McSwEmulationMethodSupport	*	aggr	Describes the calibration method used by the RTE. This information is not needed for A2L generation, but to setup software emulation in the ECU. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=emulationSupport, emulationSupport.variationPoint.shortLabel vh.latestBindingTime=preCompileTime	
mcParameter Instance	McDataInstance	*	aggr	A data instance to be used for calibration. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=mcParameterInstance.shortName, mcParameterInstance.variationPoint.shortLabel vh.latestBindingTime=postBuild	
mcVariable Instance	McDataInstance	*	aggr	A data instance to be used for measurement. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=mcVariableInstance.shortName, mcVariableInstance.variationPoint.shortLabel vh.latestBindingTime=postBuild	
measurable System ConstantValues	SwSystemconstant ValueSet	*	ref	Sets of system constant values to be transferred to the MCD system, because the system constants have been specified with "swCalibrationAccess" = readonly.	
rptSupportData	RptSupportData	0..1	aggr	The rapid prototyping support data belonging to this implementation. The aggregation is <<atpSplitable>> because in case of an already existing BSW Implementation model, this description will be added later in the process, namely at code generation time. Stereotypes: atpSplitable Tags: atp.Splitkey=rptSupportData	

Table A.708: McSupportData

Class		McSwEmulationMethodSupport			
Package		M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport			
Note		This denotes the method used by the RTE to handle the calibration data. It is published by the RTE generator and can be used e.g. to generate the corresponding emulation method in a Complex Driver. According to the actual method given by the category attribute, not all attributes are always needed: <ul style="list-style-type: none"> • double pointered method: only baseReference is mandatory • single pointered method: only referenceTable is mandatory • initRam method: only elementGroup(s) are mandatory Note: For single/double pointered method the group locations are implicitly accessed via the reference table and their location can be found from the initial values in the M1 model of the respective pointers. Therefore, the description of elementGroups is not needed in these cases. Likewise, for double pointered method the reference table description can be accessed via the M1 model under baseReference.			
Base		ARObject			
Aggregated by		McSupportData.emulationSupport			
Attribute	Type	Mult.	Kind	Note	





Class	McSwEmulationMethodSupport			
baseReference	VariableDataPrototype	0..1	ref	Refers to the base pointer in case of the double-pointered method.
category	Identifier	0..1	attr	Identifies the actual method. The possible names shall correspond to the symbols of the ECU configuration parameter for the calibration method of the RTE, and can include vendor specific methods. Tags: xml.sequenceOffset=-90
elementGroup	McParameterElement Group	*	aggr	Denotes the grouping of calibration parameters in the actual RTE code. Depending on the category, this information maybe required to set up the emulation code.
referenceTable	VariableDataPrototype	0..1	ref	Refers to the pointer table in case of the single-pointered method.
shortLabel	Identifier	0..1	attr	Assigns a name to this element. Tags: xml.sequenceOffset=-100

Table A.709: McSwEmulationMethodSupport

Class	MeasuredExecutionTime			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::ExecutionTime			
Note	Specifies the ExecutionTime which has been gathered using measurement means.			
Base	ARObject , ExecutionTime , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ResourceConsumption.executionTime			
Attribute	Type	Mult.	Kind	Note
maximum ExecutionTime	MultidimensionalTime	0..1	aggr	The maximum measured execution time.
minimum ExecutionTime	MultidimensionalTime	0..1	aggr	The minimum measured execution time.
nominal ExecutionTime	MultidimensionalTime	0..1	aggr	The nominal measured execution time.

Table A.710: MeasuredExecutionTime

Class	MeasuredHeapUsage			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::HeapUsage			
Note	The heap usage has been measured.			
Base	ARObject , HeapUsage , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ResourceConsumption.heapUsage			
Attribute	Type	Mult.	Kind	Note
averageMemory Consumption	PositiveInteger	0..1	attr	The average heap usage measured. Unit: byte.
maximum Memory Consumption	PositiveInteger	0..1	attr	The maximum heap usage measured. Unit: byte.
minimum Memory Consumption	PositiveInteger	0..1	attr	The minimum heap usage measured. Unit: byte.
testPattern	String	0..1	attr	Description of the test pattern used to acquire the measured values.

Table A.711: MeasuredHeapUsage

Class	MeasuredStackUsage			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::StackUsage			
Note	The stack usage has been measured.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , StackUsage			
Aggregated by	ResourceConsumption.stackUsage			
Attribute	Type	Mult.	Kind	Note
averageMemoryConsumption	PositiveInteger	0..1	attr	The average stack usage measured. Unit: byte.
maximumMemoryConsumption	PositiveInteger	0..1	attr	The maximum stack usage measured. Unit: byte.
minimumMemoryConsumption	PositiveInteger	0..1	attr	The minimum stack usage measured. Unit: byte.
testPattern	String	0..1	attr	Description of the test pattern used to acquire the measured values.

Table A.712: MeasuredStackUsage

Enumeration	MemoryAllocationKeywordPolicyType
Package	M2::MSR::DataDictionary::AuxiliaryObjects
Note	Enumeration to specify the name pattern of the Memory Allocation Keyword.
Aggregated by	SwAddrMethod.memoryAllocationKeywordPolicy
Literal	Description
addrMethodShortName	The MemorySection shortNames of referring MemorySections and therefore the belonging Memory Allocation Keywords in the code are build with the shortName of the SwAddrMethod. This is the default value if the attribute does not exist. Tags: atp.EnumerationLiteralIndex=0
addrMethodShortNameAndAlignment	The MemorySection shortNames of referring MemorySections and therefore the belonging Memory Allocation Keywords in the code are build with the shortName of the SwAddrMethod and a variable alignment postfix. Thereby the alignment postfix needs to be consistent with the alignment attribute of the related MemorySection. Tags: atp.EnumerationLiteralIndex=1

Table A.713: MemoryAllocationKeywordPolicyType

Class	MemorySection			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::MemorySectionUsage			
Note	<p>Provides a description of an abstract memory section used in the Implementation for code or data. It shall be declared by the Implementation Description of the module or component, which actually allocates the memory in its code. This means in case of data prototypes which are allocated by the RTE, that the generated Implementation Description of the RTE shall contain the corresponding MemorySections.</p> <p>The attribute "symbol" (if symbol is missing: "shortName") defines the module or component specific section name used in the code. For details see the document "Specification of Memory Mapping". Typically the section name is build according the pattern:</p> <pre><SwAddrMethod shortName>[_<further specialization nominator>][_<alignment>]</pre> <p>where</p> <ul style="list-style-type: none"> • [<SwAddrMethod shortName>] is the shortName of the referenced SwAddrMethod • [_<further specialization nominator>] is an optional infix to indicate the specialization in the case that several MemorySections for different purpose of the same Implementation Description referring to the same or equally named SwAddrMethods. • [_<alignment>] is the alignment attributes value and is only applicable in the case that the memory AllocationKeywordPolicy value of the referenced SwAddrMethod is set to addrMethodShortNameAnd Alignment <p>MemorySection used to Implement the code of RunnableEntitys and BswSchedulableEntitys shall have a symbol (if missing: shortName) identical to the referred SwAddrMethod to conform to the generated RTE header files.</p> <p>In addition to the section name described above, a prefix is used in the corresponding macro code in order to define a name space. This prefix is by default given by the shortName of the BswModule Description resp. the SwComponentType. It can be superseded by the prefix attribute.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ResourceConsumption.memorySection			
Attribute	Type	Mult.	Kind	Note
alignment	AlignmentType	0..1	attr	The attribute describes the typical alignment of objects within this memory section.
executableEntity	ExecutableEntity	*	ref	Reference to the ExecutableEntitites located in this section. This allows to locate different Executable Entities in different sections even if the associated Sw Addrmethod is the same. This is applicable to code sections only.
option	Identifier	*	attr	The service (in AUTOSAR: BswModuleEntry) is implemented in a way that it either resolves to aninline function or to a standard function depending on conditions set at a later point in time. The following two values are standardized (to be used for code sections only and exclusively to each other): <ul style="list-style-type: none"> • INLINE - The code section is declared with the keyword "inline". • LOCAL_INLINE - The code section is declared with the keyword "static inline". In both cases (INLINE and LOCAL_INLINE) the inline expansion depends on the compiler. Depending on this, the code section either corresponds to an actual section in memory or is put into the section of the caller.
prefix	SectionNamePrefix	0..1	ref	The prefix used to set the memory section's namespace in the code. The existence of a prefix element supersedes rules for a default prefix (such as the Bsw ModuleDescription's shortName). This allows the user to define several name spaces for memory sections within the scope of one module, cluster or SWC.
size	PositiveInteger	0..1	attr	The size in bytes of the section.





Class	MemorySection			
swAddrmethod	SwAddrMethod	0..1	ref	<p>This association indicates that this module specific (abstract) memory section is part of an overall SwAddr Method, referred by the upstream declarations (e.g. calibration parameters, data element prototypes, code entities) which share a common addressing strategy. This can be evaluated for the ECU configuration of the build support.</p> <p>This association shall always be declared by the Implementation description of the module or component, which allocates the memory in its code. This means in case of data prototypes which are allocated by the RTE, that the software components only declare the grouping of its data prototypes to SwAddrMethods, and the generated Implementation Description of the RTE actually sets up this association.</p>
symbol	Identifier	0..1	attr	<p>Defines the section name as explained in the main description. By using this attribute for code generation (instead of the shortName) it is possible to define several different MemorySections having the same name - e.g. symbol = CODE - but using different sectionName Prefixes.</p>

Table A.714: MemorySection

Class	MemorySectionLocation			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::ExecutionTime			
Note	Specifies in which hardware ProvidedMemorySegment the softwareMemorySection is located.			
Base	<i>ARObject</i>			
Aggregated by	ExecutionTime.memorySectionLocation			
Attribute	Type	Mult.	Kind	Note
provided Memory	HwElement	0..1	ref	Reference to the hardware ProvidedMemorySegment.
software MemorySection	MemorySection	0..1	ref	Reference to the MemorySection which is mapped on a certain hardware memory segment.

Table A.715: MemorySectionLocation

Class	MetaDatumItem			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This meta-class represents a single meta-data item.			
Base	<i>ARObject</i>			
Aggregated by	MetaDatumItemSet.metaDatumItem			
Attribute	Type	Mult.	Kind	Note
length	PositiveInteger	0..1	attr	This attribute determines the length of the MetaDatumItem at run-time.
metaDatumItem Type	TextValueSpecification	0..1	aggr	This aggregation contributes the specification of the concrete meta-data item type.

Table A.716: MetaDatumItem

Class	MetaDataItemSet			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This meta-class represents the ability to define a set of meta-data items to be used in SenderReceiver Interfaces.			
Base	ARObject			
Aggregated by	SenderReceiverInterface.metaDataItemSet			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	*	ref	This reference identifies the dataElement for which the ordered list of meta-data items is defined.
metaDataItem (ordered)	MetaDataItem	*	aggr	This aggregation represents the ordered definition of meta-data items.

Table A.717: MetaDataItemSet

Enumeration	MirroringProtocolEnum
Package	M2::AUTOSARTemplates::SystemTemplate::BusMirror
Note	Eenumeration that defines the supported bus mirroring protocol options) with two literals.
Aggregated by	BusMirrorChannelMapping.mirroringProtocol
Literal	Description
none	mirroringProtocol is not used Tags: atp.EnumerationLiteralIndex=1
version1	version1 of the mirroringProtocol is used Tags: atp.EnumerationLiteralIndex=0

Table A.718: MirroringProtocolEnum

Class	«atpMixedString» MixedContentForParagraph (abstract)			
Package	M2::MSR::Documentation::TextModel::InlineTextModel			
Note	This mainly represents the text model of a full blown paragraph within a documentation.			
Base	ARObject			
Subclasses	LParagraph , SIParagraph			
Attribute	Type	Mult.	Kind	Note
br	Br	1	aggr	This element is the same as function here as in a HTML document i.e. it forces a line break. Tags: xml.sequenceOffset=40
e	EmphasisText	1	aggr	This is emphasized text. Tags: xml.sequenceOffset=70
ft	SIParagraph	1	aggr	This is a foot note within a paragraph.
ie	IndexEntry	1	aggr	This is an index entry. Tags: xml.sequenceOffset=110
std	Std	1	aggr	This is a referrence to a standard. Tags: xml.sequenceOffset=120
sub	Superscript	1	attr	This is subscript text. Tags: xml.sequenceOffset=100
sup	Superscript	1	attr	This is superscript text. Tags: xml.sequenceOffset=90





Class	«atpMixedString» <i>MixedContentForParagraph</i> (abstract)			
trace	Traceable	1	ref	This allows to place an arbitrary reference to a traceable object in documentation.
tt	Tt	1	aggr	This is a technical term. Tags: xml.sequenceOffset=30
xdoc	Xdoc	1	aggr	This is a reference to a printable external document. Tags: xml.sequenceOffset=130
xfile	Xfile	1	aggr	This represents a reference to an external file which usually cannot be printed. Tags: xml.sequenceOffset=140
xref	Xref	1	aggr	This is a cross reference. Tags: xml.sequenceOffset=50
xrefTarget	XrefTarget	1	aggr	This element specifies a reference target which can be scattered throughout the text. Tags: xml.sequenceOffset=60

Table A.719: MixedContentForParagraph

Class	ModeAccessPoint			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ModeDeclarationGroup			
Note	A ModeAccessPoint is required by a RunnableEntity owned by a Mode Manager or Mode User. Its semantics implies the ability to access the current mode (provided by the RTE) of a ModeDeclaration GroupPrototype's ModeDeclarationGroup.			
Base	<i>ARObject</i>			
Aggregated by	RunnableEntity.modeAccessPoint			
Attribute	Type	Mult.	Kind	Note
ident	ModeAccessPointIdent	0..1	aggr	The aggregation in the role ident provides the ability to make the ModeAccessPoint identifiable. From the semantical point of view, the ModeAccessPoint is considered a first-class Identifiable and therefore the aggregation in the role ident shall always exist (until it may be possible to let ModeAccessPoint directly inherit from Identifiable). Stereotypes: atpIdentityContributor Tags: xml.sequenceOffset=-100
modeGroup	ModeDeclarationGroup Prototype	0..1	iref	The mode declaration group that is accessed by this runnable. Tags: xml.typeElement=true InstanceRef implemented by: ModeGroupInAtomicSwc InstanceRef

Table A.720: ModeAccessPoint

Enumeration	ModeActivationKind
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration
Note	Kind of mode switch condition used for activation of an event, as further described for each enumeration field.
Aggregated by	BswModeSwitchEvent.activation , SwcModeSwitchEvent.activation
Literal	Description





Enumeration	ModeActivationKind
onEntry	On entering the referred mode. Tags: atp.EnumerationLiteralIndex=0
onExit	On exiting the referred mode. Tags: atp.EnumerationLiteralIndex=1
onTransition	On transition of the 1st referred mode to the 2nd referred mode. Tags: atp.EnumerationLiteralIndex=2

Table A.721: ModeActivationKind

Class	ModeDeclaration			
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration			
Note	Declaration of one Mode. The name and semantics of a specific mode is not defined in the meta-model.			
Base	ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, ModeDeclarationGroup.modeDeclaration			
Attribute	Type	Mult.	Kind	Note
value	PositiveInteger	0..1	attr	The RTE shall take the value of this attribute for generating the source code representation of this Mode Declaration.

Table A.722: ModeDeclaration

Class	ModeDeclarationGroup			
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration			
Note	A collection of Mode Declarations. Also, the initial mode is explicitly identified. Tags: atp.recommendedPackage=ModeDeclarationGroups			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
initialMode	ModeDeclaration	0..1	ref	The initial mode of the ModeDeclarationGroup. This mode is active before any mode switches occurred.
mode Declaration	ModeDeclaration	*	aggr	The ModeDeclarations collected in this ModeDeclaration Group. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=modeDeclaration.shortName, mode Declaration.variationPoint.shortLabel vh.latestBindingTime=blueprintDerivationTime
modeManager ErrorBehavior	ModeErrorBehavior	0..1	aggr	This represents the ability to define the error behavior expected by the mode manager in case of errors on the mode user side (e.g. terminated mode user).
modeTransition	ModeTransition	*	aggr	This represents the available ModeTransitions of the ModeDeclarationGroup
modeUserError Behavior	ModeErrorBehavior	0..1	aggr	This represents the definition of the error behavior expected by the mode user in case of errors on the mode manager side (e.g. terminated mode manager).





Class	ModeDeclarationGroup			
onTransition Value	PositiveInteger	0..1	attr	The value of this attribute shall be taken into account by the RTE generator for programmatically representing a value used for the transition between two statuses.

Table A.723: ModeDeclarationGroup

Class	ModeDeclarationGroupPrototype			
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration			
Note	The ModeDeclarationGroupPrototype specifies a set of Modes (ModeDeclarationGroup) which is provided or required in the given context.			
Base	<i>ARObject</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>BswModuleDescription.providedModeGroup</i> , <i>BswModuleDescription.requiredModeGroup</i> , <i>FirewallStateSwitchInterface.firewallStateMachine</i> , <i>FunctionGroupSet.functionGroup</i> , <i>ModeSwitchInterface.modeGroup</i> , <i>Process.processStateMachine</i> , <i>StateManagementStateNotification.stateMachine</i>			
Attribute	Type	Mult.	Kind	Note
swCalibration Access	SwCalibrationAccess Enum	0..1	attr	This allows for specifying whether or not the enclosing ModeDeclarationGroupPrototype can be measured at run-time.
type	ModeDeclarationGroup	0..1	tref	The "collection of ModeDeclarations" (= ModeDeclaration Group) supported by a component Stereotypes: isOfType

Table A.724: ModeDeclarationGroupPrototype

Class	ModeDeclarationGroupPrototypeMapping			
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration			
Note	Defines the mapping of two particular ModeDeclarationGroupPrototypes (in the given context) that are unequally named and/or require a reference to a ModeDeclarationMappingSet in order to become compatible by definition of ModeDeclarationMappings.			
Base	<i>ARObject</i>			
Aggregated by	ModeInterfaceMapping.modeMapping			
Attribute	Type	Mult.	Kind	Note
firstModeGroup	ModeDeclarationGroup Prototype	0..1	ref	ModeDeclarationGroupPrototype to be mapped.
mode Declaration MappingSet	ModeDeclaration MappingSet	0..1	ref	This represents the available mappings of Mode Declarations in the context of this ModeDeclarationGroup Prototype.
secondMode Group	ModeDeclarationGroup Prototype	0..1	ref	ModeDeclarationGroupPrototype to be mapped.

Table A.725: ModeDeclarationGroupPrototypeMapping

Class	ModeDeclarationMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This meta-class implements a concrete mapping of two ModeDeclarations.			
Base	<i>ARObject</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>AtpStructureElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>ModeDeclarationMappingSet.modeDeclarationMapping</i>			





Class		ModeDeclarationMapping			
Attribute	Type	Mult.	Kind	Note	
firstMode	ModeDeclaration	*	ref	This represents the first ModeDeclaration of the Mode DeclarationMapping. This reference has the multiplicity 0 ..* to support use cases where e.g. one mode of the mode user is mapped to several modes of the mode manager.	
secondMode	ModeDeclaration	0..1	ref	This represents the second ModeDeclaration of the Mode DeclarationMapping.	

Table A.726: ModeDeclarationMapping

Class		ModeDeclarationMappingSet			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface				
Note	This meta-class implements a container for ModeDeclarationGroupMappings Tags: atp.recommendedPackage=PortInterfaceMappingSets				
Base	ARElement , ARObject , AtpClassifier , AtpType , CollectableElement , Identifiable , Multilanguage , Referrable , PackageableElement , Referrable				
Aggregated by	ARPackage.element				
Attribute	Type	Mult.	Kind	Note	
mode Declaration Mapping	ModeDeclaration Mapping	*	aggr	This represents the collection of ModeDeclaration Mappings owned by the enclosing ModeDeclaration MappingSet.	

Table A.727: ModeDeclarationMappingSet

Class		ModeDrivenTransmissionModeCondition			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing				
Note	The condition defined by this class evaluates to true if one of the referenced modeDeclarations (OR associated) is active. All referenced modeDeclarations shall be from the same ModeDeclarationGroup. The condition is used to define which TransmissionMode shall be activated using Com_SwitchIpduTx Mode.				
Base	ARObject				
Aggregated by	TransmissionModeDeclaration.modeDrivenFalseCondition, TransmissionModeDeclaration.modeDriven TrueCondition				
Attribute	Type	Mult.	Kind	Note	
mode Declaration	ModeDeclaration	*	ref	Reference to one modeDeclaration which is OR associated in the context of the ModeDrivenTransmission ModeCondition.	

Table A.728: ModeDrivenTransmissionModeCondition

Class		ModeErrorBehavior			
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration				
Note	This represents the ability to define the error behavior in the context of mode handling.				
Base	ARObject				
Aggregated by	ModeDeclarationGroup.modeManagerErrorBehavior , ModeDeclarationGroup.modeUserErrorBehavior				
Attribute	Type	Mult.	Kind	Note	





Class	ModeErrorBehavior			
defaultMode	ModeDeclaration	0..1	ref	This represents the ModeDeclaration that is considered the error mode in the context of the enclosing Mode DeclarationGroup.
errorReaction Policy	ModeErrorReaction PolicyEnum	0..1	attr	This represents the ability to define the policy in terms of which default model shall apply in case an error occurs.

Table A.729: ModeErrorBehavior

Enumeration	ModeErrorReactionPolicyEnum
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration
Note	This represents the ability to specify the reaction on a mode error.
Aggregated by	ModeErrorBehavior.errorReactionPolicy
Literal	Description
defaultMode	This represents the ability to switch to the defaultMode in case of a mode error. Tags: atp.EnumerationLiteralIndex=0
lastMode	This represents the ability to keep the last mode in case of a mode error. Tags: atp.EnumerationLiteralIndex=1

Table A.730: ModeErrorReactionPolicyEnum

Class	ModelnBswInstanceRef			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingCondition			
Note	Instance reference to be capable of referencing a specific ModeDeclaration of a ModeDeclarationGroup Prototype utilized in a BSW module.			
Base	<i>ARObject, ModelnSwcBswInstanceRef</i>			
Aggregated by	TimingModelInstance.modelInstance			
Attribute	Type	Mult.	Kind	Note
contextBsw Implementation	BswImplementation	0..1	ref	Specifies the BSW implementation that manifests the context. Tags: xml.sequenceOffset=10
contextMode Declaration GroupPrototype	ModeDeclarationGroup Prototype	0..1	ref	Specifies the mode declaration group prototype that manifests the context. Tags: xml.sequenceOffset=20
targetMode Declaration	ModeDeclaration	0..1	ref	Specifies the specific mode declaration in the given context. Tags: xml.sequenceOffset=30

Table A.731: ModelnBswInstanceRef

Class	ModelnSwcInstanceRef			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingCondition			
Note	Instance reference to be capable of referencing a ModeDeclaration at a specific Mode Switch Port of a SW-C.			
Base	<i>ARObject, AtpInstanceRef, ModelnSwcBswInstanceRef</i>			
Aggregated by	TimingModelInstance.modelInstance			
Attribute	Type	Mult.	Kind	Note





Class	ModelInSwcInstanceRef			
base	SwComponentType	0..1	ref	Specifies the SW component representing the base of the context. Stereotypes: atpDerived Tags: xml.sequenceOffset=10
context Component	SwComponent Prototype	*	ref	Specifies the SW component prototype representing the context. Tags: xml.sequenceOffset=20
contextMode Declaration GroupPrototype	ModeDeclarationGroup Prototype	0..1	ref	Specifies the mode declaration group prototype that manifests the context. Tags: xml.sequenceOffset=40
contextPort	PortPrototype	0..1	ref	Specifies the port prototype representing the context. Tags: xml.sequenceOffset=30
targetMode Declaration	ModeDeclaration	0..1	ref	Specifies the specific mode declaration in the given context. Tags: xml.sequenceOffset=50

Table A.732: ModelInSwcInstanceRef

Class	ModelInterfaceMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Defines the mapping of ModeDeclarationGroupPrototypes in context of two different ModelInterfaces.			
Base	ARObject , AtpBlueprint , AtpBlueprintable , Identifiable , MultilanguageReferrable , PortInterfaceMapping , Referrable			
Aggregated by	PortInterfaceMappingSet.portInterfaceMapping			
Attribute	Type	Mult.	Kind	Note
modeMapping	ModeDeclarationGroup PrototypeMapping	0..1	aggr	Mapping of two ModeDeclarationGroupPrototypes in two different ModelInterfaces

Table A.733: ModelInterfaceMapping

Class	ModePortAnnotation			
Package	M2::AUTOSARTemplates::SWComponentTemplate::ApplicationAttributes			
Note	Annotation to a port used for calibration regarding a certain ModeDeclarationGroupPrototype.			
Base	ARObject , GeneralAnnotation			
Aggregated by	PortPrototype.modePortAnnotation			
Attribute	Type	Mult.	Kind	Note
modeGroup	ModeDeclarationGroup Prototype	0..1	ref	The instance of annotated ModeDeclarationGroup Prototype.

Table A.734: ModePortAnnotation

Class	ModeRequestTypeMap			
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration			
Note	Specifies a mapping between a ModeDeclarationGroup and an ImplementationDataType. This ImplementationDataType shall be used to implement the ModeDeclarationGroup.			
Base	ARObject			
Aggregated by	DataTypeMappingSet.modeRequestTypeMap			





Class		ModeRequestTypeMap		
Attribute	Type	Mult.	Kind	Note
implementation DataType	AbstractImplementation DataType	0..1	ref	This is the corresponding AbstractImplementationData Type. It shall be modeled along the idea of an "unsigned integer-like" data type.
modeGroup	ModeDeclarationGroup	0..1	ref	This is the corresponding ModeDeclarationGroup.

Table A.735: ModeRequestTypeMap

Class		ModeSwitchEventTriggeredActivity		
Package	M2::AUTOSARTemplates::SWComponentTemplate::NvBlockComponent			
Note	This meta-class defines an activity of the NvBlockSwComponentType for a specific NvBlock which is triggered by a ModeSwitchEvent.			
Base	ARObject			
Aggregated by	NvBlockDescriptor.modeSwitchEventTriggeredActivity			
Attribute	Type	Mult.	Kind	Note
role	Identifier	0..1	attr	This attribute indicates which service of the NvM for the NvBlock shall be requested.
swcModeSwitch Event	SwcModeSwitchEvent	0..1	ref	This reference identifies the SwcModeSwitchEvent that triggers the activity.

Table A.736: ModeSwitchEventTriggeredActivity

Class		ModeSwitchInterface		
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	A mode switch interface declares a ModeDeclarationGroupPrototype to be sent and received. Tags: atp.recommendedPackage=PortInterfaces			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
modeGroup	ModeDeclarationGroup Prototype	0..1	aggr	The ModeDeclarationGroupPrototype of this mode interface.

Table A.737: ModeSwitchInterface

Class		ModeSwitchPoint		
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ModeDeclarationGroup			
Note	A ModeSwitchPoint is required by a RunnableEntity owned a Mode Manager. Its semantics implies the ability to initiate a mode switch.			
Base	ARObject , AbstractAccessPoint , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , RunnableEntity.modeSwitchPoint			
Attribute	Type	Mult.	Kind	Note
modeGroup	ModeDeclarationGroup Prototype	0..1	iref	The mode declaration group that is switched by this runnable. InstanceRef implemented by: PModeGroupInAtomic SwcInstanceRef

Table A.738: ModeSwitchPoint

Class	ModeSwitchReceiverComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes of RPortPrototypes with respect to mode communication			
Base	ARObject, RPortComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec, PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
enhancedMode Api	Boolean	0..1	attr	This controls the creation of the enhanced mode API that returns information about the previous mode and the next mode. If set to "true" the enhanced mode API is supposed to be generated. For more details please refer to the SWS_RTE.
modeGroup	ModeDeclarationGroup Prototype	0..1	ref	ModeDeclarationGroupPrototype (of the same Port Interface) to which these communication attributes apply.
supports Asynchronous ModeSwitch	Boolean	0..1	attr	This attribute controls the behavior of the corresponding RPortPrototype with respect to the question whether it can deal with asynchronous mode switch requests, i.e. if set to true, the RPortPrototype is able to deal with an asynchronous mode switch request.

Table A.739: ModeSwitchReceiverComSpec

Class	ModeSwitchSenderComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes of PPortPrototypes with respect to mode communication			
Base	ARObject, PPortComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec, PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
enhancedMode Api	Boolean	0..1	attr	This controls the creation of the enhanced mode API that returns information about the previous mode and the next mode. If set to "true" the enhanced mode API is supposed to be generated. For more details please refer to the SWS_RTE.
modeGroup	ModeDeclarationGroup Prototype	0..1	ref	ModeDeclarationGroupPrototype (of the same Port Interface) to which these communication attributes apply.
modeSwitched Ack	ModeSwitchedAck Request	0..1	aggr	If this aggregation exists an acknowledgement for the successful processing of the mode switch request is required.
queueLength	PositiveInteger	0..1	attr	Length of call queue on the mode user side. The queue is implemented by the RTE. The value shall be greater or equal to 1. Setting the value of queueLength to 1 implies that incoming requests are rejected while another request that arrived earlier is being processed.

Table A.740: ModeSwitchSenderComSpec

Class	ModeSwitchedAckEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the referenced ModeSwitchPoint has been processed or an error occurred.			
Base	ARObject, AbstractEvent, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, Multilanguage Referrable, RTEEvent, Referrable			
Aggregated by	AtpClassifier.atpFeature, SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note





Class	ModeSwitchedAckEvent			
eventSource	ModeSwitchPoint	0..1	ref	The referenced ModeSwitchPoint raises this Mode SwitchedAckEvent when the ModeSwitchPoint has been processed.

Table A.741: ModeSwitchedAckEvent

Class	ModeSwitchedAckRequest			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Requests acknowledgements that a mode switch has been proceeded successfully			
Base	<i>ARObject</i>			
Aggregated by	ModeSwitchSenderComSpec.modeSwitchedAck			
Attribute	Type	Mult.	Kind	Note
timeout	TimeValue	0..1	attr	Number of seconds before an error is reported or in case of allowed redundancy, the value is sent again.

Table A.742: ModeSwitchedAckRequest

Class	ModeTransition			
Package	M2::AUTOSARTemplates::CommonStructure::ModeDeclaration			
Note	This meta-class represents the ability to describe possible ModeTransitions in the context of a Mode DeclarationGroup.			
Base	<i>ARObject</i> , AtpClassifier , <i>AtpFeature</i> , AtpStructureElement , <i>Identifiable</i> , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , ModeDeclarationGroup.modeTransition			
Attribute	Type	Mult.	Kind	Note
enteredMode	ModeDeclaration	0..1	ref	This represents the entered model of the ModeTransition.
exitedMode	ModeDeclaration	0..1	ref	This represents the exited mode of the ModeTransition

Table A.743: ModeTransition

Class	MultidimensionalTime			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::MultidimensionalTime			
Note	Specifies a time value based on [13] see [TPS_GST_00354].			
Base	<i>ARObject</i>			





Class	MultidimensionalTime			
Aggregated by	AgeConstraint.maximum , AgeConstraint.minimum , AnalyzedExecutionTime.bestCaseExecutionTime , AnalyzedExecutionTime.worstCaseExecutionTime , ArbitraryEventTriggering.maximumDistance , ArbitraryEventTriggering.minimumDistance , BurstPatternEventTriggering.minimumInterArrivalTime , BurstPatternEventTriggering.patternJitter , BurstPatternEventTriggering.patternLength , BurstPatternEventTriggering.patternPeriod , ConcretePatternEventTriggering.offset , ConcretePatternEventTriggering.patternJitter , ConcretePatternEventTriggering.patternLength , ConcretePatternEventTriggering.patternPeriod , ConfidenceInterval.lowerBound , ConfidenceInterval.upperBound , ExecutionTimeConstraint.maximum , ExecutionTimeConstraint.minimum , IoHwAbstractionServerAnnotation.age , LatencyTimingConstraint.maximum , LatencyTimingConstraint.minimum , LatencyTimingConstraint.nominal , MeasuredExecutionTime.maximumExecutionTime , MeasuredExecutionTime.minimumExecutionTime , MeasuredExecutionTime.nominalExecutionTime , OffsetTimingConstraint.maximum , OffsetTimingConstraint.minimum , PeriodicEventTriggering.jitter , PeriodicEventTriggering.minimumInterArrivalTime , PeriodicEventTriggering.period , ReceiverAnnotation.signalAge , RoughEstimateOfExecutionTime.estimatedExecutionTime , SimulatedExecutionTime.maximumExecutionTime , SimulatedExecutionTime.minimumExecutionTime , SimulatedExecutionTime.nominalExecutionTime , SporadicEventTriggering.jitter , SporadicEventTriggering.maximumInterArrivalTime , SporadicEventTriggering.minimumInterArrivalTime , SporadicEventTriggering.period , SwDataDefProps.swRefreshTiming , SynchronizationTimingConstraint.tolerance , TDLE TZoneClock.accuracyExt , TDLE TZoneClock.accuracyInt , TimingClockSyncAccuracy.accuracy , Trigger.triggerPeriod			
Attribute	Type	Mult.	Kind	Note
cseCode	CseCodeType	0..1	attr	Specifies the time base by means of CSE codes.
cseCodeFactor	Integer	0..1	attr	The scaling factor for the time value based on the specified CSE code.

Table A.744: MultidimensionalTime

Class	MultilanguageReferrable (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::Identifiable			
Note	Instances of this class can be referred to by their identifier (while adhering to namespace borders). They also may have a longName. But they are not considered to contribute substantially to the overall structure of an AUTOSAR description. In particular it does not contain other Referrables.			
Base	ARObject , Referrable			
Subclasses	Caption , DefItem , DocumentationContext , Identifiable , SdgCaption , TraceReferrable , Traceable			
Attribute	Type	Mult.	Kind	Note
longName	MultilanguageLong Name	0..1	aggr	This specifies the long name of the object. Long name is targeted to human readers and acts like a headline.

Table A.745: MultilanguageReferrable

Class	MultiplexedIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>A MultiplexedPdu (i.e. NOT a COM I-PDU) contains a DynamicPart, an optional StaticPart and a selector Field. In case of multiplexing this IPdu is routed between the Pdu Multiplexer and the Interface Layer.</p> <p>A multiplexer is used to define variable parts within an IPdu that may carry different signals. The receivers of such a IPdu can determine which signalPdus are transmitted by evaluating the selector field, which carries a unique selector code for each sub-part.</p> <p>Tags: atp.recommendedPackage=Pdus</p>			
Base	ARElement , ARObject , CollectableElement , FibexElement , IPdu , Identifiable , MultilanguageReferrable , PackageableElement , Pdu , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	MultiplexedIPdu			
dynamicPart	DynamicPart	0..1	aggr	<p>According to the value of the selector field some parts of the IPdu have a different layout. In a complete System Description a MultiplexedIPdu shall contain a Dynamic Part. The following use cases support the multiplicity to be 0..1:</p> <ul style="list-style-type: none"> • If a MultiplexedIPdu is received by a Pdu Gateway and is not delivered to the IPduM but routed directly to a bus interface then the content of the MultiplexedIPdu doesn't need to be described in the System Extract/Ecu Extract. • If a MultiplexedIPdu is received by an ECU which is only interested in the static part of the MultiplexedIPdu then the dynamicPart does not need to be described in the System Extract/Ecu Extract. <p>atpVariation: Content of a multiplexed PDU can vary.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=dynamicPart, dynamicPart.variation Point.shortLabel vh.latestBindingTime=postBuild</p>
selectorField ByteOrder	ByteOrderEnum	0..1	attr	<p>This attribute defines the order of the bytes of the selector Field and the packing into the MultiplexedIPdu. Please consider that [constr_3247] and [constr_3223] are restricting the usage of this attribute.</p> <p>In a complete System Description this attribute is mandatory. If a MultiplexedPdu is received by a Pdu Gateway and is not delivered to the IPduM but routed directly to a bus interface then the content of the MultiplexedPdu doesn't need to be described in the System Extract/Ecu Extract. To support this use case the multiplicity is set to 0..1.</p>
selectorField Length	Integer	0..1	attr	<p>The size in bits of the selector field shall be configurable in a range of 1-16 bits. In a complete System Description this attribute is mandatory. If a MultiplexedPdu is received by a Pdu Gateway and is not delivered to the IPduM but routed directly to a bus interface then the content of the MultiplexedPdu doesn't need to be described in the System Extract/Ecu Extract. To support this use case the multiplicity is set to 0..1.</p>
selectorField StartPosition	Integer	0..1	attr	<p>This parameter is necessary to describe the position of the selector field within the IPdu.</p> <p>Note that the absolute position of the selectorField in the MultiplexedIPdu is determined by the definition of the selectorFieldByteOrder attribute of the Multiplexed Pdu. If Big Endian is specified, the start position indicates the bit position of the most significant bit in the IPdu. If Little Endian is specified, the start position indicates the bit position of the least significant bit in the IPdu. In AUTOSAR the bit counting is always set to "sawtooth" and the bit order is set to "Decreasing". The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7.</p> <p>In a complete System Description this attribute is mandatory. If a MultiplexedPdu is received by a Pdu Gateway and is not delivered to the IPduM but routed directly to a bus interface then the content of the MultiplexedPdu doesn't need to be described in the System Extract/Ecu Extract. To support this use case the multiplicity is set to 0..1.</p>





Class	MultiplexedIPdu			
staticPart	StaticPart	0..1	aggr	<p>The static part of the multiplexed IPdu is the same regardless of the selector field. The static part is optional.</p> <p>atpVariation: Content of a multiplexed PDU can vary.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=staticPart, staticPart.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
triggerMode	TriggerMode	0..1	attr	<p>IPduM can be configured to send a transmission request for the new multiplexed IPdu to the PDU-Router because of the trigger conditions/ modes that are described in the TriggerMode enumeration.</p> <p>In a complete System Description this attribute is mandatory. If a MultiplexedPdu is received by a Pdu Gateway and is not delivered to the IPduM but routed directly to a bus interface then the content of the MultiplexedPdu doesn't need to be described in the System Extract/Ecu Extract. To support this use case the multiplicity is set to 0..1.</p>
unusedBit Pattern	Integer	0..1	attr	<p>AUTOSAR COM and AUTOSAR IPDUM are filling not used areas of an IPdu with this bit-pattern. This attribute is mandatory to avoid undefined behavior. This byte-pattern will be repeated throughout the IPdu.</p> <p>In a complete System Description this attribute is mandatory. If a MultiplexedPdu is received by a Pdu Gateway and is not delivered to the IPduM but routed directly to a bus interface then the content of the MultiplexedPdu doesn't need to be described in the System Extract/Ecu Extract. To support this use case the multiplicity is set to 0..1.</p>

Table A.746: MultiplexedIPdu

Class	MultiplexedPart (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	The StaticPart and the DynamicPart have common properties. Both can be separated in multiple segments within the multiplexed PDU.			
Base	ARObject			
Subclasses	DynamicPart, StaticPart			
Attribute	Type	Mult.	Kind	Note
segment Position	SegmentPosition	*	aggr	The StaticPart and the DynamicPart can be separated in multiple segments within the multiplexed PDU. Therefore the StaticPart and the DynamicPart can contain multiple SegmentPositions.

Table A.747: MultiplexedPart

Class	NPdu
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	This is a Pdu of the Transport Layer. The main purpose of the TP Layer is to segment and reassemble IPdus. Tags: atp.recommendedPackage=Pdus





Class	NPdu			
Base	<i>ARElement, ARObject, CollectableElement, FibexElement, IPdu, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.748: NPdu

Class	NetworkEndpoint			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	The network endpoint defines the network addressing (e.g. IP-Address or MAC multicast address).			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	EthernetPhysicalChannel.networkEndpoint			
Attribute	Type	Mult.	Kind	Note
fullyQualifiedDomainName	String	0..1	attr	Defines the fully qualified domain name (FQDN) e.g. some.example.host.
infrastructureServices	InfrastructureServices	0..1	aggr	Defines the network infrastructure services provided or consumed.
ipSecConfig	IPSecConfig	0..1	aggr	Optional IPSec configuration that provides security services for IP packets.
networkEndpointAddress	NetworkEndpointAddress	*	aggr	Definition of a Network Address. Tags: xml.name Plural=NETWORK-ENDPOINT-ADDRESSES
priority	PositiveInteger	0..1	attr	Defines the frame priority where values from 0 (best effort) to 7 (highest) are allowed.

Table A.749: NetworkEndpoint

Class	NetworkEndpointAddress (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	To build a valid network endpoint address there has to be either one MAC multicast group reference or an ipv4 configuration or an ipv6 configuration.			
Base	<i>ARObject</i>			
Subclasses	Ipv4Configuration , Ipv6Configuration , MacMulticastConfiguration			
Aggregated by	NetworkEndpoint.networkEndpointAddress			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.750: NetworkEndpointAddress

Class	NetworkSegmentIdentification			
Package	M2::AUTOSARTemplates::SystemTemplate::GlobalTime			
Note	This meta-class represents the ability to identify the PhysicalChannel on a system scope in a numerical way. One possible application of this approach is the Time Validation.			
Base	AObject			
Aggregated by	GlobalTimeDomain.networkSegmentId			
Attribute	Type	Mult.	Kind	Note
networkSegmentId	PositiveInteger	0..1	attr	This attribute represents the numerical identifier of a PhysicalChannel on system level scope.

Table A.751: NetworkSegmentIdentification

Class	NmCluster (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	Set of NM nodes coordinated with use of the NM algorithm.			
Base	AObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	CanNmCluster , FlexrayNmCluster , J1939NmCluster , UdpNmCluster			
Aggregated by	NmConfig.nmCluster			
Attribute	Type	Mult.	Kind	Note
communicationCluster	CommunicationCluster	0..1	ref	Association to a CommunicationCluster in the topology description.
nmChannelSleepMaster	Boolean	0..1	attr	This parameter shall be set to indicate if the sleep of this network can be absolutely decided by the local node only and that no other nodes can oppose that decision.
nmLightTimeout	TimeValue	0..1	attr	Defines the timeout (in seconds) after COMM_FULL_COMMUNICATION sub-state COMM_FULL_COM_READY_SLEEP is left.
nmNode	NmNode	*	aggr	Collection of NmNodes of the NmCluster. atpVariation: Derived, because NmNode can be variable. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=nmNode.shortName, nmNode.variation Point.shortLabel vh.latestBindingTime=postBuild
nmNodeDetectionEnabled	Boolean	0..1	attr	Enables the Request Repeat Message Request support. Only valid if nmNodeIdEnabled is set to true.
nmNodeIdEnabled	Boolean	0..1	attr	Enables the source node identifier.
nmPncParticipation	Boolean	0..1	attr	Defines whether this NmCluster contributes to the partial network mechanism.
nmRepeatMsgIndEnabled	Boolean	0..1	attr	Switch for enabling the Repeat Message Bit Indication.
nmSynchronizingNetwork	Boolean	0..1	attr	If this parameter is true, then this network is a synchronizing network for the NM coordination cluster which it belongs to. The network is expected to call Nm_SynchronizationPoint() at regular intervals.
pncClusterVectorLength	PositiveInteger	0..1	attr	Optionally defines the length of the PNC Vector per CommunicationCluster (and VLAN in case of UdpNm). If not defined then System.pncVectorLength applies. Should only make the PNC Vector shorter (or same length as defined in System.pncVectorLength).

Table A.752: NmCluster

Class	NmConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	Contains the all configuration elements for AUTOSAR Nm. Tags: atp.recommendedPackage=NmConfigs			
Base	ARElement, ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
nmCluster	NmCluster	*	aggr	Collection of NM Clusters atpVariation: Derived, because cluster can be variable. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=nmCluster.shortName, nmCluster.variationPoint.shortLabel vh.latestBindingTime=postBuild
nmCluster Coupling	NmClusterCoupling	*	aggr	Collection of NmClusterCouplings atpVariation: Derived, because NmCluster can vary. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=nmClusterCoupling, nmClusterCoupling.variationPoint.shortLabel vh.latestBindingTime=postBuild
nmlfEcu	NmEcu	*	aggr	Collection of NM ECUs atpVariation: Derived, because EcuInstance can be variable. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=nmlfEcu.shortName, nmlfEcu.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.753: NmConfig

Class	NmEcu			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	ECU on which NM is running.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	NmConfig.nmlfEcu			
Attribute	Type	Mult.	Kind	Note
busDependent NmEcu	BusspecificNmEcu	*	aggr	Cluster specific NmEcu attributes
ecuInstance	EcuInstance	0..1	ref	Association to an ECUInstance in the topology description.
nmBus Synchronization Enabled	Boolean	0..1	attr	Enables bus synchronization support.
nmComControl Enabled	Boolean	0..1	attr	Enables the Communication Control support.
nmCoordinator	NmCoordinator	0..1	aggr	Nm ECU may coordinate different clusters.
nmCycletime MainFunction	TimeValue	0..1	attr	The period between successive calls to the Main Function of the NM Interface in seconds.





Class	NmEcu			
nmPduRxIndicationEnabled	Boolean	0..1	attr	Switch for enabling the PDU Rx Indication.
nmRemoteSleepIndEnabled	Boolean	0..1	attr	Switch for enabling remote sleep indication support.
nmStateChangeIndEnabled	Boolean	0..1	attr	Enables the CAN Network Management state change notification.
nmUserDataEnabled	Boolean	0..1	attr	Switch for enabling user data support.

Table A.754: NmEcu

Class	NmNode (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	The linking of NmEcus to NmClusters is realized via the NmNodes.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	CanNmNode, FlexrayNmNode, J1939NmNode, UdpNmNode			
Aggregated by	NmCluster.nmNode			
Attribute	Type	Mult.	Kind	Note
controller	CommunicationController	0..1	ref	Association to an CommunicationController in the topology description.
nmCoordCluster	PositiveInteger	0..1	attr	NmCoordinationCluster identification number.
nmCoordinatorRole	NmCoordinatorRoleEnum	0..1	attr	This attribute indicates the role the NM Coordinator will have on this channel.
nmIfEcu	NmEcu	0..1	ref	Reference to the NmEcu that contains this NmNode. (CommunicationController that is referenced by the NmNode shall be contained in the EcuInstance that is referenced by the NmEcu).
nmNodeid	Integer	0..1	attr	Node identifier of local NmNode. Shall be unique in the NmCluster.
nmPassiveModeEnabled	Boolean	0..1	attr	Enables support of the Passive Mode. The passive mode is configurable per channel.
nmVariant	NmVariantEnum	0..1	attr	Defines the functionality of Network Management.
rxNmPdu	NmPdu	*	ref	receive NM Pdu.
txNmPdu	NmPdu	*	ref	transmit NM Pdu

Table A.755: NmNode

Class	NmPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Network Management Pdu Tags: atp.recommendedPackage=Pdus			
Base	ARElement, ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	NmPdu			
iSignalToIPdu Mapping	ISignalToIPduMapping	*	aggr	This optional aggregation is used to describe NmUserData that is transmitted in the NmPdu. The counting of the startPosition starts at the beginning of the NmPdu regardless whether Cbv or Nid are used.
nmData Information	Boolean	0..1	attr	Defines if the Pdu contains NM Data. If the NmPdu does not aggregate any ISignalToIPduMappings it still may contain UserData that is set via Nm_SetUserData(). If the ISignalToIPduMapping exists then the nmDataInformation attribute shall be ignored.
nmVote Information	Boolean	0..1	attr	Defines if the Pdu contains NM Vote information.
unusedBit Pattern	Integer	0..1	attr	AUTOSAR COM is filling not used areas of an Pdu with this bit-pattern. This attribute can only be used if the nmDataInformation attribute is set to true.

Table A.756: NmPdu

Enumeration	NmVariantEnum
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement
Note	Supported NmCoordinator roles.
Aggregated by	NmNode.nmVariant
Literal	Description
full	AUTOSAR NM is available Tags: atp.EnumerationLiteralIndex=3
light	No AUTOSAR NM is available, but functionality to shut down a channel Tags: atp.EnumerationLiteralIndex=1
none	No NM available Tags: atp.EnumerationLiteralIndex=0
passive	AUTOSAR NM running in passive mode available Tags: atp.EnumerationLiteralIndex=2
slaveActive	No NM is available. This is used for e.g. LIN slaves Tags: atp.EnumerationLiteralIndex=4
slavePassive	No NM is available. This used for e.g. Ethernet communication channels with OA TC10 compliant hardware Tags: atp.EnumerationLiteralIndex=5

Table A.757: NmVariantEnum

Class	NonqueuedReceiverComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes specific to non-queued receiving.			
Base	ARObject , RPortComSpec , ReceiverComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec , PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note





Class		NonqueuedReceiverComSpec		
aliveTimeout	TimeValue	0..1	attr	Specify the amount of time (in seconds) after which the software component (via the RTE) needs to be notified if the corresponding data item have not been received according to the specified timing description. If the aliveTimeout attribute is 0 no timeout monitoring shall be performed.
enableUpdate	Boolean	0..1	attr	This attribute controls whether application code is entitled to check whether the value of the corresponding VariableDataPrototype has been updated.
filter	DataFilter	0..1	aggr	The applicable filter algorithm for filtering the value of the corresponding dataElement.
handleData Status	Boolean	0..1	attr	If this attribute is set to true, then the Rte_IStatus API shall exist. If the attribute does not exist or is set to false, then the Rte_IStatus API may still exist in response to the existence of further conditions.
handleNever Received	Boolean	0..1	attr	This attribute specifies whether for the corresponding VariableDataPrototype the "never received" flag is available. If yes, the RTE is supposed to assume that initially the VariableDataPrototype has not been received before. After the first reception of the corresponding VariableDataPrototype the flag is cleared. <ul style="list-style-type: none"> • If the value of this attribute is set to "true" the flag is required. • If set to "false", the RTE shall not support the "never received" functionality for the corresponding VariableDataPrototype.
handleTimeout Type	HandleTimeoutEnum	0..1	attr	This attribute controls the behavior with respect to the handling of timeouts.
initValue	ValueSpecification	0..1	aggr	Initial value to be used in case the sending component is not yet initialized. If the sender also specifies an initial value, then the receiver's value will be used.
timeout Substitution Value	ValueSpecification	0..1	aggr	This attribute represents the substitution value applicable in the case of a timeout.

Table A.758: NonqueuedReceiverComSpec

Class		NonqueuedSenderComSpec		
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes for non-queued sender/receiver communication (sender side)			
Base	ARObject , PPortComSpec , SenderComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec , PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
dataFilter	DataFilter	0..1	aggr	The applicable filter algorithm for filtering the value of the corresponding dataElement.
initValue	ValueSpecification	0..1	aggr	Initial value to be sent if sender component is not yet fully initialized, but receiver needs data already.

Table A.759: NonqueuedSenderComSpec

Class	NotAvailableValueSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This meta-class provides the ability to specify a ValueSpecification to state that the respective element is not available. This ability is needed to support the existence of ApplicationRecordElements where attribute isOptional ist set to the value true.			
Base	<i>ARObject</i> , <i>ValueSpecification</i>			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
defaultPattern	PositiveInteger	0..1	attr	The content of this attribute shall be used to initialize gaps in the memory occupied by a structured data type in the case that an NotAvailableValueSpecification is used. Note that this pattern is only applied during initialization!

Table A.760: NotAvailableValueSpecification

Primitive	Numerical
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes
Note	<p>This primitive specifies a numerical value. It can be denoted in different formats such as Decimal, Octal, Hexadecimal, Float. See the xsd pattern for details.</p> <p>The value can be expressed in octal, hexadecimal, binary representation. Negative numbers can only be expressed in decimal or float notation.</p> <p>Tags: xml.xsd.customType=NUMERICAL-VALUE xml.xsd.pattern=(0[xX][0-9a-fA-F]+) (0[0-7]+) (0[bB][0-1]+) (([\+-]?[1-9][0-9]+ \.[0-9]+)?[\+-]?[0-9](\.[0-9]+)?)([eE]([\+-]?[0-9]+)? \.[0]INF -INF NaN xml.xsd.type=string</p>

Table A.761: Numerical

Class	NumericalOrText			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This meta-class represents the ability to yield either a numerical or a string. A typical use case is that two or more instances of this meta-class are aggregated with a VariationPoint where some instances yield strings while other instances yield numerical depending on the resolution of the binding expression.			
Base	<i>ARObject</i>			
Aggregated by	RuleArguments.vtf , SwValues.vtf			
Attribute	Type	Mult.	Kind	Note





Class	NumericalOrText			
vf	Numerical	0..1	attr	This attribute represents the ability to provide a numerical value. The latest binding time of the VariationPoint shall be preCompileTime. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=10
vt	String	0..1	attr	This attribute represents the ability to provide a textual value. Tags: xml.sequenceOffset=20

Table A.762: NumericalOrText

Class	NumericalRuleBasedValueSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This meta-class is used to support a rule-based initialization approach for data types with an array-nature (ImplementationDataType of category ARRAY).			
Base	ARObject, AbstractRuleBasedValueSpecification , ValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element , CalibrationParameterValue.applInitValue , CalibrationParameterValue.implInitValue , ConstantSpecification.valueSpec , CryptoServiceKey.developmentValue , DiagnosticEnvDataCondition.compareValue , DiagnosticEnvDataElementCondition.compareValue , FieldSenderComSpec.initValue , ISignal.initValue , ISignal.receptionDefaultValue , ISignal.timeoutSubstitutionValue , NonqueuedReceiverComSpec.initValue , NonqueuedReceiverComSpec.timeoutSubstitutionValue , NonqueuedSenderComSpec.initValue , NvProvideComSpec.ramBlockInitValue , NvProvideComSpec.romBlockInitValue , NvRequireComSpec.initValue , ParameterDataPrototype.initValue , ParameterProvideComSpec.initValue , ParameterRequireComSpec.initValue , PersistencyDataRequiredComSpec.initValue , PersistencyKeyValuePair.initValue , PortDefinedArgumentValue.value , PortPrototypeBlueprintInitValue.value , RecordValueSpecification.field , SomeipEventDeployment.eventReceptionDefaultValue , StateManagementCompareCondition.compareValue , SwDataDefProps.invalidValue , UserDefinedEventDeployment.eventReceptionDefaultValue , VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
ruleBasedValues	RuleBasedValueSpecification	0..1	aggr	This represents the rule based value specification for the array. Tags: xml.roleElement=true xml.roleWrapperElement=false xml.typeWrapperElement=false

Table A.763: NumericalRuleBasedValueSpecification

Class	NumericalValueSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	A numerical ValueSpecification which is intended to be assigned to a Primitive data element. Note that the numerical value is a variant, it can be computed by a formula.			
Base	ARObject, ValueSpecification			





Class	NumericalValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.ramBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeipEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
value	Numerical	0..1	attr	This is the value itself. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.764: NumericalValueSpecification

Class	NvBlockDataMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::NvBlockComponent			
Note	Defines the mapping between the VariableDataPrototypes in the NvBlockComponents ports and the VariableDataPrototypes of the RAM Block. The data types of the referenced VariableDataPrototypes in the ports and the referenced sub-element (inside a CompositeDataType) of the VariableDataPrototype representing the RAM Block shall be compatible.			
Base	ARObject			
Aggregated by	BulkNvDataDescriptor.nvBlockDataMapping, NvBlockDescriptor.nvBlockDataMapping			
Attribute	Type	Mult.	Kind	Note
bitfieldTextTableMaskNvBlockDescriptor	PositiveInteger	0..1	attr	This attribute identifies the applicable bit mask on the side of the Nv Block.
bitfieldTextTableMaskPortPrototype	PositiveInteger	0..1	attr	This attribute identifies the applicable bit mask on the side of the PortPrototype.
nvRamBlockElement	AutosarVariableRef	0..1	aggr	Reference to a VariableDataPrototype of a RAM Block.
readNvData	AutosarVariableRef	0..1	aggr	Reference to a VariableDataPrototype of a pPort of the NvBlockComponent providing read access to the RAM Block.If there is no PortPrototype providing read access (write-only) the reference can be omitted.
writtenNvData	AutosarVariableRef	0..1	aggr	Reference to a VariableDataPrototype of a rPort of the NvBlockComponent providing write access to the RAM Block. If there is no port providing write access (read-only) the reference can be omitted.
writtenReadNvData	AutosarVariableRef	0..1	aggr	Reference to a VariableDataPrototype of a PRPort Prototype of the NvBlockSwComponentType providing write and read access to the RAM Block.

Table A.765: NvBlockDataMapping

Class	NvBlockDescriptor			
Package	M2::AUTOSARTemplates::SWComponentTemplate::NvBlockComponent			
Note	Specifies the properties of exactly one NVRAM Block.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , NvBlockSwComponentType.nvBlockDescriptor			
Attribute	Type	Mult.	Kind	Note
clientServerPort	RoleBasedPortAssignment	*	aggr	<p>The RoleBasedPortAssignment defines which client server port of the NvBlockSwComponentType serves for which kind of service or notification. In case of notifications one common callback function is provided by the RTE for each individual kind of notification defined by the "role".</p> <p>The aggregation of RoleBasedPortAssignment is subject to variability with the purpose to support the conditional existence of ports.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=clientServerPort, clientServerPort.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
constantValueMapping	ConstantSpecificationMappingSet	*	ref	<p>Reference to the ConstantSpecificationMapping to be applied for the particular NVRAM Block</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=constantValueMapping</p>
dataTypeMapping	DataTypeMappingSet	*	ref	<p>Reference to the DataTypeMapping to be applied for the particular NVRAM Block.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=dataTypeMapping</p>
instantiationDataDefProps	InstantiationDataDefProps	*	aggr	<p>The purpose of InstantiationDataDefProps are the refinement of some data def properties of individual instantiations within the context of a NvBlockSwComponentType.</p> <p>The aggregation of InstantiationDataDefProps is subject to variability with the purpose to support the conditional existence of ports, component internal memory objects and those attributes.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=instantiationDataDefProps, instantiationDataDefProps.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
modeSwitchEventTriggeredActivity	ModeSwitchEventTriggeredActivity	*	aggr	<p>This represents the collection of ModeSwitchEventTriggeredActivities related to the enclosing NvBlockDescriptor.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=modeSwitchEventTriggeredActivity, modeSwitchEventTriggeredActivity.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	NvBlockDescriptor			
nvBlockData Mapping	NvBlockDataMapping	*	aggr	<p>Defines the mapping between the VariableData Prototypes in the NvBlockComponents ports and the VariableDataPrototypes of the RAM Block.</p> <p>The aggregation of NvBlockDataMapping is subject to variability with the purpose to support the conditional existence of nv data ports.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=nvBlockDataMapping, nvBlockData Mapping.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
nvBlockNeeds	NvBlockNeeds	0..1	aggr	<p>Specifies the abstract needs on the configuration of the NVRAM Manager for the single NVRAM Block described by this NvBlockDescriptor.</p> <p>In addition, it may define requirements for writing strategies in an implementation of an NvBlockSw ComponentType by the RTE.</p> <p>Please note that the attributes nDataSets and nRom Blocks are not relevant for this aggregation because the RTE will allocate just one block anyway. In a different context, however, they do make sense.</p>
ramBlock	VariableDataPrototype	0..1	aggr	Defines the RAM Block of the NVRAM Block provided by NvBlockSwComponentType.
romBlock	ParameterData Prototype	0..1	aggr	Defines the ROM Block of the NVRAM Block provided by NvBlockSwComponentType.
supportDirty Flag	Boolean	0..1	attr	Specifies whether calling of NvM functions for writing and/ or status control of potentially modified RAM Blocks to NV memory shall be controlled by the RTE.
timingEvent	TimingEvent	0..1	ref	this reference can be taken to identify the TimingEvent to be used by the RTE for implementing a cyclic writing strategy for this block
writingStrategy	RoleBasedData Assignment	*	aggr	This attribute allows for assigning a specific writing strategy for an incoming AutosarDataPrototype.

Table A.766: NvBlockDescriptor

Class	NvBlockNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs on the configuration of a single NVRAM Block.			
Base	<i>AObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>ServiceNeeds</i>			
Aggregated by	BswServiceDependency.serviceNeeds , NvBlockDescriptor.nvBlockNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
calcRamBlock Crc	Boolean	0..1	attr	Defines if CRC (re)calculation for the permanent RAM Block is required.
checkStatic BlockId	Boolean	0..1	attr	Defines if the Static Block Id check shall be enabled.
cyclicWriting Period	TimeValue	0..1	attr	This represents the period for cyclic writing of NvData to store the associated RAM Block.
nDataSets	PositiveInteger	0..1	attr	Number of data sets to be provided by the NVRAM manager for this block. This is the total number of ROM Blocks and RAM Blocks.





Class	NvBlockNeeds			
nRomBlocks	PositiveInteger	0..1	attr	Number of ROM Blocks to be provided by the NVRAM manager for this block. Please note that these multiple ROM Blocks are given in a contiguous area.
ramBlockStatusControl	RamBlockStatusControlEnum	0..1	attr	This attribute defines how the management of the RAM Block status is controlled.
readonly	Boolean	0..1	attr	true: data of this NVRAM Block are write protected for normal operation (but protection can be disabled) false: no restriction
reliability	NvBlockNeedsReliabilityEnum	0..1	attr	Reliability against data loss on the non-volatile medium.
resistantToChangedSw	Boolean	0..1	attr	Defines whether an NVRAM Block shall be treated resistant to configuration changes (true) or not (false). For details how to handle initialization in the latter case, please refer to the NVRAM specification.
restoreAtStart	Boolean	0..1	attr	Defines whether the associated RAM Block shall be implicitly restored during startup by the basic software.
selectBlockForFirstInitAll	Boolean	0..1	attr	If this attribute is set to true the NvM shall process this block in the NvM_FirstInitAll() function.
storeAtShutdown	Boolean	0..1	attr	Defines whether or not the associated RAM Block shall be implicitly stored during shutdown by the basic software.
storeCyclic	Boolean	0..1	attr	Defines whether or not the associated RAM Block shall be implicitly stored periodically by the basic software.
storeEmergency	Boolean	0..1	attr	Defines whether or not the associated RAM Block shall be implicitly stored in case of ECU failure (e.g. loss of power) by the basic software. If the attribute storeEmergency is set to true the associated RAM Block shall be configured to have immediate priority.
storeImmediate	Boolean	0..1	attr	Defines whether or not the associated RAM Block shall be implicitly stored immediately during or after execution of the according SW-C RunnableEntity by the basic software.
storeOnChange	Boolean	0..1	attr	This attribute defines whether the associated RAM Block shall be stored immediately if the written value is different to the value stored in the associated RAM Block(s) during or after execution of the according SW-C RunnableEntity.
useAutoValidationAtShutdown	Boolean	0..1	attr	If set to true the RAM Block shall be auto validated during shutdown phase.
useCRCCompMechanism	Boolean	0..1	attr	If set to true the CRC of the RAM Block shall be compared during a write job with the CRC which was calculated during the last successful read or write job in order to skip unnecessary NVRAM writings.
writeOnlyOnce	Boolean	0..1	attr	Defines write protection after first write: true: This block is prevented from being changed/erased or being replaced with the default ROM data after first initialization by the software-component. false: No such restriction.
writeVerification	Boolean	0..1	attr	Defines if Write Verification shall be enabled for this NVRAM Block.
writingFrequency	PositiveInteger	0..1	attr	Provides the amount of updates to this block from the application point of view. It has to be provided in "number of write access per year".
writingPriority	NvBlockNeedsWritingPriorityEnum	0..1	attr	Requires the priority of writing this block in case of concurrent requests to write other blocks.

Table A.767: NvBlockNeeds

Enumeration	NvBlockNeedsReliabilityEnum
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds
Note	Reliability against data loss on the non-volatile medium. These requirements give only a relative indication, for example on the required degree of redundancy for storage. They do, however, not specify by which means (e.g. software or hardware) the reliability is actually achieved.
Aggregated by	NvBlockNeeds.reliability
Literal	Description
errorCorrection	Errors shall be corrected Tags: atp.EnumerationLiteralIndex=0
errorDetection	Errors shall be detected Tags: atp.EnumerationLiteralIndex=1
noProtection	Data need not to be handled with protection Tags: atp.EnumerationLiteralIndex=2

Table A.768: NvBlockNeedsReliabilityEnum

Class	NvBlockSwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	The NvBlockSwComponentType defines non volatile data which data can be shared between Sw ComponentPrototypes. The non volatile data of the NvBlockSwComponentType are accessible via provided and required ports. Tags: atp.recommendedPackage=SwComponentTypes			
Base	ARElement , ARObject , AtomicSwComponentType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
bulkNvData Descriptor	BulkNvDataDescriptor	*	aggr	This aggregation formally defines the bulk Nv Blocks that are provided to the application software by the enclosing NvBlockSwComponentType. Stereotypes: atp.Splittable; atp.Variation Tags: atp.Splitkey=bulkNvDataDescriptor.shortName, bulkNvDataDescriptor.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
nvBlock Descriptor	NvBlockDescriptor	*	aggr	Specification of the properties of exactly one NVRAM Block. Stereotypes: atp.Splittable; atp.Variation Tags: atp.Splitkey=nvBlockDescriptor.shortName, nvBlockDescriptor.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.769: NvBlockSwComponentType

Class	NvDataInterface
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface
Note	A non volatile data interface declares a number of VariableDataPrototypes to be exchanged between non volatile block components and atomic software components. Tags: atp.recommendedPackage=PortInterfaces





Class	NvDataInterface			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DataInterface, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
nvData	VariableDataPrototype	*	aggr	The VariableDataPrototype of this nv data interface.

Table A.770: NvDataInterface

Class	NvDataPortAnnotation			
Package	M2::AUTOSARTemplates::SWComponentTemplate::ApplicationAttributes			
Note	Annotation to a port regarding a certain VariableDataPrototype.			
Base	<i>ARObject, GeneralAnnotation</i>			
Aggregated by	PortPrototype.nvDataPortAnnotation			
Attribute	Type	Mult.	Kind	Note
variable	VariableDataPrototype	0..1	ref	The instance of nv data annotated.

Table A.771: NvDataPortAnnotation

Class	NvProvideComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes of PPortPrototypes with respect to Nv data communication on the provided side.			
Base	<i>ARObject, PPortComSpec</i>			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec , PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
ramBlockInit Value	ValueSpecification	0..1	aggr	This represents the initial value of the RAM Block that corresponds to the referenced variable.
romBlockInit Value	ValueSpecification	0..1	aggr	This represents the initial value of the ROM block that corresponds to the referenced variable.
variable	VariableDataPrototype	0..1	ref	This represents the variable for which the ComSpec is specified.

Table A.772: NvProvideComSpec

Class	NvRequireComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes of RPortPrototypes with respect to Nv data communication on the required side.			
Base	<i>ARObject, RPortComSpec</i>			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec , PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	The initial value owned by the NvComSpec
variable	VariableDataPrototype	0..1	ref	The VariableDataPrototype the ComSpec applies for.

Table A.773: NvRequireComSpec

Class	ObdControlServiceNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs of a component or module on the configuration of OBD Service 08 (request control of on-board system) in relation to a particular test-Identifier (TID) supported by this component or module.			
Base	<i>ARObject</i> , <i>DiagnosticCapabilityElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>Service Needs</i>			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.774: ObdControlServiceNeeds

Class	ObdInfoServiceNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs of a component or module on the configuration of OBD Services in relation to a given InfoType (OBD Service 09) which is supported by this component or module.			
Base	<i>ARObject</i> , <i>DiagnosticCapabilityElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>Service Needs</i>			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.775: ObdInfoServiceNeeds

Class	ObdPidServiceNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs of a component or module on the configuration of OBD Services in relation to a particular PID (parameter identifier) which is supported by this component or module. In case of using a client/server communicated value, the related value shall be communicated via the port referenced by assignedPort. The details of this communication (e.g. appropriate naming conventions) are specified in the related software specifications (SWS).			
Base	<i>ARObject</i> , <i>DiagnosticCapabilityElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>Service Needs</i>			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.776: ObdPidServiceNeeds

Enumeration	ObdRatioConnectionKindEnum			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Defines the way how the IUMPR service connection between the Dem and the client component or module is handled (for details see the DEM Specification).			
Aggregated by	ObdRatioServiceNeeds.connectionType			
Literal	Description			
apiUse	The IUMPR service (of the DEM) uses an explicit API to connect to the component or module. Tags: atp.EnumerationLiteralIndex=0			
observer	The IUMPR service (of the Dem) uses no API but "observes" the associated diagnostic event. Tags: atp.EnumerationLiteralIndex=1			

Table A.777: ObdRatioConnectionKindEnum

Class	ObdRatioServiceNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs of a component or module on the configuration of OBD Services in relation to a particular "ratio monitoring" which is supported by this component or module.			
Base	<i>ARObject</i> , <i>DiagnosticCapabilityElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>ServiceNeeds</i>			
Aggregated by	<i>BswServiceDependency.serviceNeeds</i> , <i>SwcServiceDependency.serviceNeeds</i>			
Attribute	Type	Mult.	Kind	Note
connectionType	ObdRatioConnectionKindEnum	0..1	attr	Defines how the DEM is connected to the component or module to perform the IUMPR (In use monitor performance ratio) service.
rateBasedMonitoredEvent	DiagnosticEventNeeds	0..1	ref	The rate based monitored Diagnostic Event.
usedFid	FunctionInhibitionNeeds	0..1	ref	This represents the primary Function Inhibition Identifier used for the rate based monitor. This is an optional attribute.

Table A.778: ObdRatioServiceNeeds

Class	OffsetTimingConstraint			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::OffsetConstraint			
Note	<p>Bounds the time offset between the occurrence of two timing events, without requiring a direct functional dependency between the <i>source</i> and the <i>target</i>.</p> <p>If the <i>target</i> event occurs, it is expected to occur earliest with the <i>minimum</i>, and latest with the <i>maximum</i> offset relatively after the occurrence of the <i>source</i> event.</p> <p>Note: not every <i>source</i> event occurrence shall be followed by a <i>target</i> event occurrence.</p> <p>In contrast to <i>LatencyTimingConstraint</i>, there shall not necessarily be a causal dependency between the <i>source</i> and <i>target</i> event.</p>			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>TimingConstraint</i> , <i>Traceable</i>			
Aggregated by	<i>TimingExtension.timingGuarantee</i> , <i>TimingExtension.timingRequirement</i>			
Attribute	Type	Mult.	Kind	Note
maximum	MultidimensionalTime	0..1	aggr	The maximum offset the target event occurs relatively after the occurrence of the source event. Tags: xml.sequenceOffset=20
minimum	MultidimensionalTime	0..1	aggr	The minimum offset the target event occurs relatively after the occurrence of the source event. Tags: xml.sequenceOffset=10
source	TimingDescriptionEvent	0..1	ref	The timing event that the target event is to be synchronized with.
target	TimingDescriptionEvent	0..1	ref	The timing event which is expected to occur timely after the source event.

Table A.779: OffsetTimingConstraint

Class	OperationInSystemInstanceRef			
Package	M2::AUTOSARTemplates::SystemTemplate::InstanceRefs			
Note				
Base	<i>ARObject</i> , <i>AtpInstanceRef</i>			
Aggregated by	<i>ClientIdDefinition.clientServerOperation</i> , <i>ClientServerToSignalMapping.clientServerOperation</i> , <i>PortElementToCommunicationResourceMapping.clientServerOperation</i> , <i>SwcToSwcOperationArguments.operation</i>			
Attribute	Type	Mult.	Kind	Note





Class	OperationInSystemInstanceRef			
base	System	0..1	ref	Stereotypes: atpDerived Tags: xml.sequenceOffset=10
context Component (ordered)	SwComponent Prototype	*	ref	Tags: xml.sequenceOffset=30
context Composition	RootSwComposition Prototype	0..1	ref	Tags: xml.sequenceOffset=20
contextPort	PortPrototype	1	ref	Tags: xml.sequenceOffset=40
targetOperation	ClientServerOperation	0..1	ref	Tags: xml.sequenceOffset=50

Table A.780: OperationInSystemInstanceRef

Class	OperationInvokedEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the ClientServerOperation referenced in OperationInvokedEvent.operation shall be invoked.			
Base	ARObject , AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , Multilanguage Referrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	0..1	iref	This represents the ClientServerOperation which shall be invoked. InstanceRef implemented by: POperationInAtomicSwc InstanceRef

Table A.781: OperationInvokedEvent

Class	OsTaskExecutionEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This RTEEvent is supposed to execute RunnableEntities which have to react on the execution of specific OsTasks. Therefore, this event is unconditionally raised whenever the OsTask on which it is mapped is executed. The main use case for this event is scheduling of Runnables of Complex Drivers which have to react on task executions.			
Base	ARObject , AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , Multilanguage Referrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.782: OsTaskExecutionEvent

Class	PPortComSpec (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes of a provided PortPrototype. This class will contain attributes that are valid for all kinds of provide ports, independent of client-server or sender-receiver communication patterns.			
Base	ARObject			
Subclasses	ModeSwitchSenderComSpec , NvProvideComSpec , ParameterProvideComSpec , SenderComSpec , ServerComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec , PortPrototypeBlueprint.providedComSpec			





Class	<i>PPortComSpec</i> (abstract)			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.783: PPortComSpec

Class	PPortPrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	Component port providing a certain port interface.			
Base	<i>ARObject</i> , <i>AbstractProvidedPortPrototype</i> , <i>AtpBlueprintable</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PortPrototype</i> , <i>Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>SwComponentType.port</i>			
Attribute	Type	Mult.	Kind	Note
provided Interface	PortInterface	0..1	tref	The interface that this port provides. Stereotypes: isOfType

Table A.784: PPortPrototype

Class	PRPortPrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	This kind of PortPrototype can take the role of both a required and a provided PortPrototype.			
Base	<i>ARObject</i> , <i>AbstractProvidedPortPrototype</i> , <i>AbstractRequiredPortPrototype</i> , <i>AtpBlueprintable</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PortPrototype</i> , <i>Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>SwComponentType.port</i>			
Attribute	Type	Mult.	Kind	Note
provided Required Interface	PortInterface	0..1	tref	This represents the PortInterface used to type the PRPort Prototype Stereotypes: isOfType

Table A.785: PRPortPrototype

Class	ParameterAccess			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements			
Note	The presence of a ParameterAccess implies that a RunnableEntity needs access to a ParameterData Prototype.			
Base	<i>ARObject</i> , <i>AbstractAccessPoint</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>AtpStructureElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>RunnableEntity.parameterAccess</i>			
Attribute	Type	Mult.	Kind	Note
accessed Parameter	AutosarParameterRef	0..1	aggr	Reference to the accessed calibration parameter.
swDataDef Props	SwDataDefProps	0..1	aggr	This allows denote instance and access specific properties, mainly input values and common axis. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps

Table A.786: ParameterAccess

Class	ParameterDataPrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::DataPrototypes			
Note	A ParameterDataPrototype represents a formalized generic piece of information that is typically immutable by the application software layer, but mutable by measurement and calibration tools. ParameterDataPrototype is used in various contexts and the specific context gives the otherwise generic ParameterDataPrototype a dedicated semantics.			
Base	<i>ARObject, AtpFeature, AtpPrototype, AutosarDataPrototype, DataPrototype, Identifiable, Multilanguage Referrable, Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature, BswInternalBehavior.perInstanceParameter, InternalBehavior.constantMemory, NvBlockDescriptor.romBlock, ParameterInterface.parameter, SwcInternalBehavior.perInstanceParameter, SwcInternalBehavior.sharedParameter</i>			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	Specifies initial value(s) of the ParameterDataPrototype

Table A.787: ParameterDataPrototype

Class	ParameterInAtomicSWCTypeInstanceRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements::InstanceRefs Usage			
Note	This class implements an instance reference which can be applied for variables as well as for parameters.			
Base	<i>ARObject, AtpInstanceRef</i>			
Aggregated by	<i>AutosarParameterRef.autosarParameter</i>			
Attribute	Type	Mult.	Kind	Note
base	AtomicSwComponentType	0..1	ref	Stereotypes: atpDerived Tags: xml.sequenceOffset=10
contextData Prototype (ordered)	ApplicationCompositeElementDataPrototype	*	ref	This is the context in a compositeDataType. Tags: xml.sequenceOffset=40
portPrototype	PortPrototype	0..1	ref	This is the port providing the variable or the entry point to the variable structure. Tags: xml.sequenceOffset=20
rootParameter DataPrototype	DataPrototype	0..1	ref	This represents the entry point for references into a CompositeDataType. Tags: xml.sequenceOffset=30
targetData Prototype	DataPrototype	0..1	ref	This is the target parameter element. Note that this must be nested in ParameterDataPrototype. The target must be one of ParameterDataPrototype, ApplicationCompositeElementDataPrototype. Tags: xml.sequenceOffset=50

Table A.788: ParameterInAtomicSWCTypeInstanceRef

Class	ParameterInterface			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	A parameter interface declares a number of parameter and characteristic values to be exchanged between parameter components and software components. Tags: atp.recommendedPackage=PortInterfaces			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, DataInterface, Identifiable, MultilanguageReferrable, PackageableElement, PortInterface, Referrable</i>			
Aggregated by	<i>ARPackage.element</i>			
Attribute	Type	Mult.	Kind	Note
parameter	ParameterDataPrototype	*	aggr	The ParameterDataPrototype of this ParameterInterface.

Table A.789: ParameterInterface

Class	ParameterPortAnnotation			
Package	M2::AUTOSARTemplates::SWComponentTemplate::ApplicationAttributes			
Note	Annotation to a port used for calibration regarding a certain ParameterDataPrototype.			
Base	ARObject, GeneralAnnotation			
Aggregated by	PortPrototype.parameterPortAnnotation			
Attribute	Type	Mult.	Kind	Note
parameter	ParameterDataPrototype	0..1	ref	The instance of annotated ParameterDataPrototype.

Table A.790: ParameterPortAnnotation

Class	ParameterProvideComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	"Communication" specification that applies to parameters on the provided side of a connection.			
Base	ARObject, PPortComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec, PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	The initial value applicable for the corresponding ParameterDataPrototype.
parameter	ParameterDataPrototype	0..1	ref	The ParameterDataPrototype to which the Parameter ComSpec applies.

Table A.791: ParameterProvideComSpec

Class	ParameterRequireComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	"Communication" specification that applies to parameters on the required side of a connection.			
Base	ARObject, RPortComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec, PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	The initial value applicable for the corresponding ParameterDataPrototype.
parameter	ParameterDataPrototype	0..1	ref	The ParameterDataPrototype to which the Parameter RequireComSpec applies.

Table A.792: ParameterRequireComSpec

Class	ParameterSwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	The ParameterSwComponentType defines parameters and characteristic values accessible via provided Ports. The provided values are the same for all connected SwComponentPrototypes Tags: atp.recommendedPackage=SwComponentTypes			
Base	ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	ParameterSwComponentType			
constant Mapping	ConstantSpecificationMappingSet	*	ref	Reference to the ConstantSpecificationMapping to be applied for the particular ParameterSwComponentType Stereotypes: atpSplitable Tags: atp.Splitkey=constantMapping
data Type Mapping	DataTypeMappingSet	*	ref	Reference to the DataTypeMapping to be applied for the particular ParameterSwComponentType Stereotypes: atpSplitable Tags: atp.Splitkey=dataTypeMapping
instantiation DataDefProps	InstantiationDataDefProps	*	aggr	The purpose of this is that within the context of a given SwComponentType some data def properties of individual instantiations can be modified. The aggregation of InstantiationDataDefProps is subject to variability with the purpose to support the conditional existence of PortPrototypes Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=instantiationDataDefProps, instantiationDataDefProps.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.793: ParameterSwComponentType

Class	PassThroughSwConnector			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	This kind of SwConnector can be used inside a CompositionSwComponentType to connect two delegation PortPrototypes.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable , SwConnector			
Aggregated by	AtpClassifier.atpFeature , CompositionSwComponentType.connector			
Attribute	Type	Mult.	Kind	Note
providedOuter Port	AbstractProvidedPortPrototype	0..1	ref	This represents the provided outer delegation Port Prototype of the PassThroughSwConnector.
requiredOuter Port	AbstractRequiredPortPrototype	0..1	ref	This represents the required outer delegation Port Prototype of the PassThroughSwConnector.

Table A.794: PassThroughSwConnector

Class	Pdu (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Collection of all Pdus that can be routed through a bus interface.			
Base	ARElement , ARObject , CollectableElement , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Subclasses	GeneralPurposePdu , IPdu , NmPdu , UserDefinedPdu			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
hasDynamic Length	Boolean	0..1	attr	This attribute defines whether the Pdu has dynamic length (true) or not (false). Please note that the usage of this attribute is restricted by [constr_3448].





Class	Pdu (abstract)			
length	UnlimitedInteger	0..1	attr	Pdu length in bytes. In case of dynamic length IPdus (containing a dynamical length signal), this value indicates the maximum data length. It should be noted that in former AUTOSAR releases (Rel 2.1, Rel 3.0, Rel 3.1, Rel 4.0 Rev. 1) this parameter was defined in bits. The Pdu length of zero bytes is allowed.

Table A.795: Pdu

Class	PduActivationRoutingGroup			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Group of Pdus that can be activated or deactivated for transmission over a socket connection.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	AbstractServiceInstance.methodActivationRoutingGroup , ConsumedEventGroup.pduActivationRoutingGroup , EventHandler.pduActivationRoutingGroup			
Attribute	Type	Mult.	Kind	Note
eventGroup ControlType	EventGroupControlType Enum	0..1	attr	This attribute defines the type of a RoutingGroup. There are RoutingGroups that activate the data path for unicast or multicast events of an event group. And there are RoutingGroups that activate the data path for initial events that are triggered, namely events that are sent out on the server side after a client got subscribed. Please note that this attribute is only valid for event communication (Sender Receiver communication) and shall be omitted in MethodActivationRoutingGroups.
iPduIdentifier Tcp	SoConIPduIdentifier	*	ref	PduIdentifiers assigned for transmission over Tcp in case that the referencing PduActivationRoutingGroup is activated.
iPduIdentifier Udp	SoConIPduIdentifier	*	ref	PduIdentifiers assigned for transmission over Udp in case that the referencing PduActivationRoutingGroup is activated.

Table A.796: PduActivationRoutingGroup

Class	PduMappingDefaultValue			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Multiplatform			
Note	Default Value which will be distributed if no I-Pdu has been received since last sending.			
Base	<i>ARObject</i>			
Aggregated by	TargetIPduRef.defaultValue			
Attribute	Type	Mult.	Kind	Note
defaultValue Element	DefaultValueElement	*	aggr	The default value consists of a number of elements. Each default value element is represented by the element and the position in an array.

Table A.797: PduMappingDefaultValue

Class	«atpPrototype» PduToFrameMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	A PduToFrameMapping defines the composition of Pdus in each frame.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			





Class	«atpPrototype» PduToFrameMapping			
Aggregated by	Frame.pduToFrameMapping			
Attribute	Type	Mult.	Kind	Note
packingByte Order	ByteOrderEnum	0..1	attr	This attribute defines the order of the bytes of the Pdu and the packing into the Frame. Please consider that [constr_3246] and [constr_3222] are restricting the usage of this attribute.
pdu	Pdu	0..1	ref	Reference to a I-Pdu, N-Pdu or NmPdu that is transmitted in the Frame.
startPosition	Integer	0..1	attr	<p>This attribute describes the bitposition of a Pdu within a Frame.</p> <p>Please note that the absolute position of the Pdu in the Frame is determined by the definition of the packingByte Order attribute. If Big Endian is specified, the start position indicates the bit position of the most significant bit in the Frame. If Little Endian is specified, the start position indicates the bit position of the least significant bit in the Frame. The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7.</p> <p>The Pdus are byte aligned in a Frame and only the values 0, 8, 16, 24,... (for little endian) and 7, 15, 23, ... (for big endian) are allowed.</p>
update IndicationBit Position	Integer	0..1	attr	<p>Indication to the receivers that the corresponding Pdu was updated by the sender. This attribute describes the position of the update bit in the frame that aggregates this PDUToFrameMapping. Length is always one bit.</p> <p>Note that the exact bit position of the updateIndicationBit Position is linked to the value of the attribute packingByte Order because the method of finding the bit position is different for the values mostSignificantByteFirst and most SignificantByteLast. This means that if the value of packingByteOrder is changed while the value of update IndicationBitPosition remains unchanged the exact bit position of updateIndicationBitPosition within the enclosing Frame still undergoes a change.</p> <p>This attribute denotes the least significant bit for "Little Endian" and the most significant bit for "Big Endian" packed signals within the IPdu (see the description of the packingByteOrder attribute). In AUTOSAR the bit counting is always set to "sawtooth" and the bit order is set to "Decreasing". The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7.</p>

Table A.798: PduToFrameMapping

Class	PduTriggering
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication
Note	<p>The PduTriggering describes on which channel the IPdu is transmitted. The Pdu routing by the PduR is only allowed for subclasses of IPdu.</p> <p>Depending on its relation to entities such channels and clusters it can be unambiguously deduced whether a fan-out is handled by the Pdu router or the Bus Interface.</p> <p>If the fan-out is specified between different clusters it shall be handled by the Pdu Router. If the fan-out is specified between different channels of the same cluster it shall be handled by the Bus Interface.</p>
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable
Aggregated by	PhysicalChannel.pduTriggering





Class		PduTriggering		
Attribute	Type	Mult.	Kind	Note
iPdu	Pdu	0..1	ref	Reference to the Pdu for which the PduTriggering is defined. One I-Pdu can be triggered on different channels (PduR fan-out). The Pdu routing by the PduR is only allowed for subclasses of IPdu. Nevertheless is the reference to the Pdu element necessary since the PduTriggering element is also used to specify the sending and receiving connections to Ecu Ports.
iPduPort	IPduPort	*	ref	References to the IPduPort on every ECU of the system which sends and/or receives the I-PDU. References for both the sender and the receiver side shall be included when the system is completely defined.
iSignalTriggering	ISignalTriggering	*	ref	This reference provides the relationship to the ISignalTriggerings that are implemented by the PduTriggering. The reference is optional since no ISignalTriggering can be defined for DCM and Multiplexed Pdus. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=iSignalTriggering.iSignalTriggering, iSignalTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild
secOcCryptoMapping	SecOcCryptoServiceMapping	0..1	ref	This reference identifies the crypto profile applicable to the usage (send, receive) of the also referenced Secured IPdu. Obviously, this reference is only applicable if the PduTriggering also references a SecuredIPdu in the role i Pdu.
triggerIPduSendCondition	TriggerIPduSendCondition	*	aggr	Defines the trigger for the Com_TriggerIPDUSend API call. Only if all defined TriggerIPduSendConditions evaluate to true (AND associated) the Com_TriggerIPDUSend API shall be called.

Table A.799: PduTriggering

Class		PerInstanceMemory		
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::PerInstanceMemory			
Note	Defines a 'C' typed memory-block that needs to be available for each instance of the SW-component. This is typically only useful if supportsMultipleInstantiation is set to "true" or if the software-component defines NVRAM access via permanent blocks.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.perInstanceMemory			
Attribute	Type	Mult.	Kind	Note
initValue	String	0..1	attr	Specifies initial value(s) of the PerInstanceMemory
swDataDefProps	SwDataDefProps	0..1	aggr	This represents the ability to allocate RAM at specific memory sections, for example, to support the RAM Block recovery strategy by mapping to uninitialized RAM. Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps
type	CIdentifier	0..1	attr	The name of the "C"-type
typeDefinition	String	0..1	attr	A definition of the type with the syntax of a 'C' typedef.

Table A.800: PerInstanceMemory

Class	PerInstanceMemorySize			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcImplementation			
Note	Resources needed by the allocation of PerInstanceMemory for each SWC instance. Note that these resources are not covered by an ObjectFileSection, because they are supposed to be allocated by the RTE.			
Base	ARObject			
Aggregated by	SwcImplementation.perInstanceMemorySize			
Attribute	Type	Mult.	Kind	Note
alignment	PositiveInteger	0..1	attr	Required alignment (1,2,4,...) of the referenced Per InstanceMemory. Unit: byte.
perInstanceMemory	PerInstanceMemory	0..1	ref	This represents the referenced PerInstanceMemory.
size	PositiveInteger	0..1	attr	Size (in bytes) of the reference perInstanceMemory. The aggregation of PerInstanceMemorySize is subject to variability with the purpose to support variability in the software components implementations. Different algorithms in the implementation might require a different PerInstanceMemorySize. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.801: PerInstanceMemorySize

Class	PeriodicEventTriggering			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::EventTriggeringConstraint			
Note	Describes the behavior of an event with a strict periodic occurrence pattern, given by period . Additionally, it is possible to soften the strictness of the periodic occurrence behavior by specifying a jitter , so that there can be a deviation from the period up to the size of the jitter .			
Base	ARObject, EventTriggeringConstraint , Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee, TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
jitter	MultidimensionalTime	0..1	aggr	The maximum deviation of the periodic event occurrence. Tags: xml.sequenceOffset=20
minimumInterArrivalTime	MultidimensionalTime	0..1	aggr	The minimum time distance between subsequent consecutive occurrences of the associated event. If the minimumInterArrivalTime is less than the period minus the jitter , then the minimumInterArrivalTime has no effect on the properties of the constraint. Tags: xml.sequenceOffset=10
period	MultidimensionalTime	0..1	aggr	The periodic distance between subsequent occurrences of the event. Tags: xml.sequenceOffset=30

Table A.802: PeriodicEventTriggering

Class	PermissibleSignalPath			
Package	M2::AUTOSARTemplates::SystemTemplate::SignalPaths			
Note	<p>The PermissibleSignalPath describes the way a data element shall take in the topology. The path is described by ordered references to PhysicalChannels.</p> <p>If more than one PermissibleSignalPath is defined for the same signal/operation attributes, any of them can be chosen. Such a signal path can be a constraint for the communication matrix. This path describes that one data element should take path A (e.g. 1. CAN channel, 2. LIN channel) and not path B (1. CAN channel, FlexRay channel A).</p> <p>This has an effect on the frame generation and the frame path.</p>			
Base	ARObject, SignalPathConstraint			
Aggregated by	SystemMapping.signalPathConstraint			
Attribute	Type	Mult.	Kind	Note
operation	SwcToSwcOperation Arguments	*	aggr	The arguments of an operation that can take the predefined way in the topology.
physical Channel (ordered)	PhysicalChannel	*	ref	The SwcToSwcSignal can be transmitted on one of these physical channels.
signal	SwcToSwcSignal	*	aggr	The data element which can take the predefined way in the topology.

Table A.803: PermissibleSignalPath

Class	PhysConstrs			
Package	M2::MSR::AsamHdo::Constraints::GlobalConstraints			
Note	This meta-class represents the ability to express physical constraints. Therefore it has (in opposite to InternalConstrs) a reference to a Unit.			
Base	ARObject			
Aggregated by	DataConstrRule.physConstrs			
Attribute	Type	Mult.	Kind	Note
lowerLimit	Limit	0..1	attr	<p>This specifies the lower limit of the constraint.</p> <p>Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=20</p>
maxDiff	Numerical	0..1	attr	<p>Maximum difference that is permitted between two consecutive values if the constraint is applied to an axis.</p> <p>Tags: xml.sequenceOffset=60</p>
maxGradient	Numerical	0..1	attr	<p>This element specifies the maximum slope that may be used in curves and maps.</p> <p>Tags: xml.sequenceOffset=50</p>
monotony	MonotonyEnum	0..1	attr	<p>This specifies the monotony constraints on the data object. Note that this applies only to curves and maps.</p> <p>Tags: xml.sequenceOffset=70</p>
scaleConstr (ordered)	ScaleConstr	*	aggr	<p>This is one particular scale which contributes to the data constraints.</p> <p>Tags: atp.Status=obsolete xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=40 xml.typeElement=false xml.typeWrapperElement=false</p>





Class	PhysConstrs			
unit	Unit	0..1	ref	This is the unit to which the physical constraints relate to. In particular, it is the physical unit of the specified limits. Tags: xml.sequenceOffset=80
upperLimit	Limit	0..1	attr	This specifies the upper limit of the constraint. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=30

Table A.804: PhysConstrs

Class	<i>PhysicalChannel</i> (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology			
Note	A physical channel is the transmission medium that is used to send and receive information between communicating ECUs. Each CommunicationCluster has at least one physical channel. Bus systems like CAN and LIN only have exactly one PhysicalChannel. A FlexRay cluster may have more than one PhysicalChannels that may be used in parallel for redundant communication. An ECU is part of a cluster if it contains at least one controller that is connected to at least one channel of the cluster.#			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>AbstractCanPhysicalChannel</i> , <i>EthernetPhysicalChannel</i> , <i>FlexrayPhysicalChannel</i> , <i>LinPhysicalChannel</i> , <i>UserDefinedPhysicalChannel</i>			
Aggregated by	<i>CommunicationCluster.physicalChannel</i>			
Attribute	Type	Mult.	Kind	Note
comm Connector	Communication Connector	*	ref	Reference to the ECUInstance via a Communication Connector to which the channel is connected. atpVariation: Variable assignment of Physical Channels to different CommunicationConnectors is expressed with this variation. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=commConnector.communicationConnector, commConnector.variationPoint.shortLabel vh.latestBindingTime=postBuild
frameTriggering	FrameTriggering	*	aggr	One frame triggering is defined for exactly one channel. Channels may have assigned an arbitrary number of frame triggerings. atpVariation: If signals/PDUs/frames are variable, the corresponding triggerings shall be variable, too. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=frameTriggering.shortName, frameTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	PhysicalChannel (abstract)			
iSignalTriggering	ISignalTriggering	*	aggr	<p>One ISignalTriggering is defined for exactly one channel. Channels may have assigned an arbitrary number of ISignalTriggerings.</p> <p>atpVariation: If signals/PDUs/frames are variable, the corresponding triggerings shall be variable, too.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=iSignalTriggering.shortName, iSignalTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
managedPhysicalChannel	PhysicalChannel	*	ref	Reference between a channel with role managing channel and a channel with role managed channel.
pduTriggering	PduTriggering	*	aggr	<p>One PduTriggering is defined for exactly one channel. Channels may have assigned an arbitrary number of I-Pdu triggerings.</p> <p>atpVariation: If signals/PDUs/frames are variable, the corresponding triggerings shall be variable, too.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=pduTriggering.shortName, pduTriggering.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>

Table A.805: PhysicalChannel

Class	PhysicalDimension			
Package	M2::MSR::AsamHdo::Units			
Note	<p>This class represents a physical dimension. If the physical dimension of two units is identical, then a conversion between them is possible. The conversion between units is related to the definition of the physical dimension.</p> <p>Note that the equivalence of the exponents does not per se define the convertibility. For example Energy and Torque share the same exponents (Nm).</p> <p>Please note further the value of an exponent does not necessarily have to be an integer number. It is also possible that the value yields a rational number, e.g. to compute the square root of a given physical quantity. In this case the exponent value would be a rational number where the numerator value is 1 and the denominator value is 2.</p> <p>Tags: atp.recommendedPackage=PhysicalDimensions</p>			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
currentExp	Numerical	0..1	attr	<p>This attribute represents the exponent of the physical dimension "electric current".</p> <p>Tags: xml.sequenceOffset=50</p>
lengthExp	Numerical	0..1	attr	<p>The exponent of the physical dimension "length".</p> <p>Tags: xml.sequenceOffset=20</p>
luminousIntensityExp	Numerical	0..1	attr	<p>The exponent of the physical dimension "luminous intensity".</p> <p>Tags: xml.sequenceOffset=80</p>





Class	PhysicalDimension			
massExp	Numerical	0..1	attr	The exponent of the physical dimension "mass". Tags: xml.sequenceOffset=30
molarAmountExp	Numerical	0..1	attr	The exponent of the physical dimension "quantity of substance". Tags: xml.sequenceOffset=70
temperatureExp	Numerical	0..1	attr	The exponent of the physical dimension "temperature". Tags: xml.sequenceOffset=60
timeExp	Numerical	0..1	attr	The exponent of the physical dimension "time". Tags: xml.sequenceOffset=40

Table A.806: PhysicalDimension

Class	PhysicalDimensionMapping			
Package	M2::MSR::AsamHdo::Units			
Note	This class represents a specific mapping between two PhysicalDimensions.			
Base	ARObject			
Aggregated by	PhysicalDimensionMappingSet.physicalDimensionMapping			
Attribute	Type	Mult.	Kind	Note
firstPhysicalDimension	PhysicalDimension	0..1	ref	This represents the first PhysicalDimension of the enclosing PhysicalDimensionMapping.
secondPhysicalDimension	PhysicalDimension	0..1	ref	This represents the first PhysicalDimension of the enclosing PhysicalDimensionMapping.

Table A.807: PhysicalDimensionMapping

Class	PlcaProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This meta-class allows to configure the PLCA (Physical Layer Collision Avoidance) in case 10-BASE-T1S Ethernet is used and PLCA is enabled on the CouplingPort (PHY).			
Base	ARObject			
Aggregated by	CouplingPort.plcaProps			
Attribute	Type	Mult.	Kind	Note
plcaLocalNodeId	PositiveInteger	0..1	attr	This attribute defines the node ID when the PLCA mode for 10BASE-T1S is used.
plcaMaxBurstCount	PositiveInteger	0..1	attr	Defines maximum packets allowed to be transmitted within a TO. This configuration can be different from one ECU to another within the PLCA mixed segment.
plcaMaxBurstTimer	PositiveInteger	0..1	attr	Limits the burst frames in bit time. This configuration can be different from one ECU to another within the PLCA mixed segment. For PLCA burst mode to work properly this timer should be set greater than one IPG.

Table A.808: PlcaProps

Enumeration	PncGatewayTypeEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreTopology
Note	Defines the PncGateway roles.
Aggregated by	CommunicationConnector.pncGatewayType
Literal	Description
active	The active PncGateway functionality shall be performed Tags: atp.EnumerationLiteralIndex=0
none	No PncGateway functionality shall be performed Tags: atp.EnumerationLiteralIndex=1
passive	The passive PncGateway functionality shall be performed Tags: atp.EnumerationLiteralIndex=2

Table A.809: PncGatewayTypeEnum

Class	PncMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::PncMapping			
Note	Describes a mapping between one or several Virtual Function Clusters onto Partial Network Clusters. A Virtual Function Cluster is realized by a PortGroup. A Partial Network Cluster is realized by one or more IPduGroups.			
Base	<i>ARObject, Describable</i>			
Aggregated by	SystemMapping.pncMapping			
Attribute	Type	Mult.	Kind	Note
dynamicPncMappingPduGroup	ISignalIPduGroup	*	ref	Reference to an ISignalIPduGroup that allows mapping of this PNC without statically mapping this PNC directly to a channel. This is needed to describe dynamic PNCs that can be learned only at run-time and which have also a relation to an ISignalIPduGroup. Stereotypes: atpSplitable Tags: atp.Splitkey=dynamicPncMappingPduGroup atp.Status=draft
ident	PncMappingIdent	0..1	aggr	This adds the ability to become referable to PncMapping.
physicalChannel	PhysicalChannel	*	ref	This reference maps the partial network to a communication channel. Stereotypes: atpSplitable Tags: atp.Splitkey=physicalChannel
pncConsumedProvidedServiceInstanceGroup	ConsumedProvidedServiceInstanceGroup	*	ref	ConsumedProvidedServiceInstanceGroup used in a Partial Network Cluster. This reference is optional, since this could be used for starting and stopping ConsumedProvidedServiceInstanceGroup according the requested partial network, but is not necessarily needed. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=pncConsumedProvidedServiceInstanceGroup.consumedProvidedServiceInstanceGroup, pncConsumedProvidedServiceInstanceGroup.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	PncMapping			
pncGroup	ISignalPduGroup	*	ref	IPduGroup participating in a Partial Network Cluster. This reference is optional in case an ecu extract has only indirect pnc access, i.e. ecu is not directly connected to a network which supports partial network. Stereotypes: atpSplitable Tags: atp.Splitkey=pncGroup
pncIdentifier	PositiveInteger	0..1	attr	Identifier of the Partial Network Cluster. This number represents the absolute bit position of this Partial Network Cluster in the NM Pdu.
pncPdurGroup	PdurIPduGroup	*	ref	This reference maps the Partial Network Cluster to a set of PdurIpduGroups. Stereotypes: atpSplitable Tags: atp.Splitkey=pncPdurGroup
pncWakeup Enable	Boolean	0..1	attr	If this parameter is available and set to true then this PNC will be woken up as soon as a channel wakeup occurs on a channel where this PNC is assigned to. This is ensured by adding this PNC to the corresponding channel wakeup sources during upstream mapping.
relevantFor DynamicPnc Mapping	EcuInstance	*	ref	Reference to a PNC Gateway ECU for PNCs which do not have a static channel mapping. This is needed to describe dynamic PNCs that can be learned only at run-time and which have no relation to an ISignalPdu Group. Stereotypes: atpSplitable Tags: atp.Splitkey=relevantForDynamicPncMapping atp.Status=draft
shortLabel	Identifier	0..1	attr	This attribute specifies an identifying shortName for the PncMapping. It shall be unique in the System scope.
vfc	PortGroup	*	iref	Virtual Function Cluster to be mapped onto a Partial Network Cluster. This reference is optional in case that the System Description doesn't use a complete Software Component Description (VFB View). This supports the inclusion of legacy systems. InstanceRef implemented by: PortGroupInSystem InstanceRef
wakeupFrame	FrameTriggering	*	ref	Reference to collection of FrameTriggerings that are used for the wakeup of this PNC (Application Frames or Nm Frames can be used). This reference is only valid if this EcuExtract represents an ECU which has direct PNC access, i.e. ECU is directly connected to a network which supports partial network. Stereotypes: atpSplitable Tags: atp.Splitkey=wakeupFrame

Table A.810: PncMapping

Class	PncMappingIdent			
Package	M2::AUTOSARTemplates::SystemTemplate::PncMapping			
Note	This meta-class is created to add the ability to become the target of a reference to the non-Referrable PncMapping.			
Base	ARObject , Referrable			
Aggregated by	PncMapping.ident			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.811: PncMappingIdent

Class	PortAPIOption			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::PortAPIOptions			
Note	Options how to generate the signatures of calls for an AtomicSwComponentType in order to communicate over a PortPrototype (for calls into a RunnableEntity as well as for calls from a RunnableEntity to the PortPrototype).			
Base	ARObject			
Aggregated by	SwcInternalBehavior.portAPIOption			
Attribute	Type	Mult.	Kind	Note
enableTakeAddress	Boolean	0..1	attr	If set to true, the software-component is able to use the API reference for deriving a pointer to an object.
errorHandling	DataTransformationErrorHandlingEnum	0..1	attr	This specifies whether a RunnableEntity accessing a PortPrototype that is referenced by this PortAPIOption shall specifically handle transformer errors or not.
indirectAPI	Boolean	0..1	attr	If set to true this attribute specifies an "indirect API" to be generated for the associated port which means that the software-component is able to access the actions on a port via a pointer to an object representing a port. This allows e.g. iterating over ports in a loop. This option has no effect for PPortPrototypes of client/server interfaces.
port	PortPrototype	0..1	ref	The option is valid for generated functions related to communication over this port
portArgValue (ordered)	PortDefinedArgumentValue	*	aggr	An argument value defined by this port.
supportedFeature	SwcSupportedFeature	*	aggr	This collection specifies which features are supported by the RunnableEntities which access a PortPrototype that it referenced by this PortAPIOption.
transformerStatusForwarding	DataTransformationStatusForwardingEnum	0..1	attr	This attribute specifies whether a RunnableEntity accessing a PortPrototype that is referenced by this PortAPIOption shall be able to forward a status code to the transformer chain.

Table A.812: PortAPIOption

Class	PortDefinedArgumentValue			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::PortAPIOptions			
Note	A PortDefinedArgumentValue is passed to a RunnableEntity dealing with the ClientServerOperations provided by a given PortPrototype. Note that this is restricted to PPortPrototypes of a ClientServerInterface.			
Base	ARObject			
Aggregated by	PortAPIOption.portArgValue			
Attribute	Type	Mult.	Kind	Note
value	ValueSpecification	0..1	aggr	Specifies the actual value.
valueType	ImplementationDataType	0..1	trf	The implementation type of this argument value. It should not be composite type or a pointer. Stereotypes: isOfType

Table A.813: PortDefinedArgumentValue

Class	PortElementToCommunicationResourceMapping			
Package	M2::AUTOSARTemplates::SystemTemplate			
Note	This meta class maps a communication resource to CP Software Clusters. In this case the kind of PortPrototype specified whether the Software Cluster has to provide or to require the resource.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			





Class		PortElementToCommunicationResourceMapping		
Aggregated by	CpSoftwareClusterMappingSet.portElementToComResourceMapping, SystemMapping.portElementToComResourceMapping			
Attribute	Type	Mult.	Kind	Note
clientServer Operation	ClientServerOperation	0..1	iref	ClientServerOperation instance qualifying the communication resource InstanceRef implemented by: OperationInSystemInstanceRef
communication Resource	CpSoftwareClusterCommunicationResource	0..1	ref	Communication resource for which the mapping applies.
mode Declaration GroupPrototype	ModeDeclarationGroupPrototype	0..1	iref	ModeDeclarationGroupPrototype instance qualifying the communication resource InstanceRef implemented by: ModeDeclarationGroupPrototypeInSystemInstanceRef
parameterData Prototype	ParameterDataPrototype	0..1	iref	ParameterDataPrototype instance qualifying the communication resource. InstanceRef implemented by: ParameterDataPrototypeInSystemInstanceRef
trigger	Trigger	0..1	iref	Trigger instance qualifying the communication resource. InstanceRef implemented by: TriggerInSystemInstanceRef
variableData Prototype	VariableDataPrototype	0..1	iref	VariableDataPrototype instance qualifying the communication resource InstanceRef implemented by: VariableDataPrototypeInSystemInstanceRef

Table A.814: PortElementToCommunicationResourceMapping

Class		PortGroup		
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	<p>Group of ports which share a common functionality.</p> <p>Example: need specific network resources. This information shall be available on the VFB level in order to delegate it properly via compositions. When propagated into the ECU extract, this information is used as input for the configuration of Services like the Communication Manager.</p> <p>A PortGroup is defined locally in a component (which can be a composition) and refers to the "outer" ports belonging to the group as well as to the "inner" groups which propagate this group into the components which are part of a composition. A PortGroup within an atomic SWC cannot be linked to inner groups.</p>			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwComponentType.portGroup			
Attribute	Type	Mult.	Kind	Note
innerGroup	PortGroup	*	iref	Links a PortGroup in a composition to another PortGroup, that is defined in a component which is part of this CompositionSwComponentType. InstanceRef implemented by: InnerPortGroupInCompositionInstanceRef





Class	PortGroup			
outerPort	PortPrototype	*	ref	Outer PortPrototype of this AtomicSwComponentType which belongs to the group. A port can belong to several groups or to no group at all. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=outerPort.portPrototype, outerPort.variation Point.shortLabel vh.latestBindingTime=preCompileTime

Table A.815: PortGroup

Class	PortInterface (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Abstract base class for an interface that is either provided or required by a port of a software component.			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Subclasses	ClientServerInterface , DataInterface , ModeSwitchInterface , TriggerInterface			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
isService	Boolean	0..1	attr	This flag is set if the PortInterface is to be used for communication between an <ul style="list-style-type: none"> • ApplicationSwComponentType or • ServiceProxySwComponentType or • SensorActuatorSwComponentType or • ComplexDeviceDriverSwComponentType • ServiceSwComponentType • EcuAbstractionSwComponentType and a ServiceSwComponentType (namely an AUTOSAR Service) located on the same ECU. Otherwise the flag is not set. Stereotypes: atpVariation Tags: vh.latestBindingTime=blueprintDerivationTime
serviceKind	ServiceProviderEnum	0..1	attr	This attribute provides further details about the nature of the applied service.

Table A.816: PortInterface

Class	PortInterfaceMapping (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Specifies one PortInterfaceMapping to support the connection of Ports typed by two different Port Interfaces with PortInterface elements having unequal names and/or unequal semantic (resolution or range).			
Base	ARObject , AtpBlueprint , AtpBlueprintable , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	ClientServerInterfaceMapping , ModelInterfaceMapping , TriggerInterfaceMapping , VariableAndParameterInterfaceMapping			
Aggregated by	PortInterfaceMappingSet.portInterfaceMapping			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.817: PortInterfaceMapping

Class	PortPrototype (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	Base class for the ports of an AUTOSAR software component. The aggregation of PortPrototypes is subject to variability with the purpose to support the conditional existence of ports.			
Base	<i>ARObject</i> , <i>AtpBlueprintable</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>AbstractProvidedPortPrototype</i> , <i>AbstractRequiredPortPrototype</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>SwComponentType.port</i>			
Attribute	Type	Mult.	Kind	Note
clientServer Annotation	ClientServerAnnotation	*	aggr	Annotation of this PortPrototype with respect to client/server communication.
delegatedPort Annotation	DelegatedPortAnnotation	0..1	aggr	Annotations on this delegated port.
ioHwAbstractionServer Annotation	IoHwAbstractionServerAnnotation	*	aggr	Annotations on this IO Hardware Abstraction port.
modePort Annotation	ModePortAnnotation	*	aggr	Annotations on this mode port.
nvDataPort Annotation	NvDataPortAnnotation	*	aggr	Annotations on this non volatile data port.
parameterPort Annotation	ParameterPortAnnotation	*	aggr	Annotations on this parameter port.
senderReceiver Annotation	SenderReceiverAnnotation	*	aggr	Collection of annotations of this ports sender/receiver communication.
triggerPort Annotation	TriggerPortAnnotation	*	aggr	Annotations on this trigger port.

Table A.818: PortPrototype

Class	PortPrototypeBlueprint			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::BlueprintDedicated::PortPrototypeBlueprint			
Note	This meta-class represents the ability to express a blueprint of a PortPrototype by referring to a particular PortInterface. This blueprint can then be used as a guidance to create particular PortPrototypes which are defined according to this blueprint. By this it is possible to standardize application interfaces without the need to also standardize software-components with PortPrototypes typed by the standardized Port Interfaces. Tags: atp.recommendedPackage=PortPrototypeBlueprints			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>AtpStructureElement</i> , <i>CollectableElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Aggregated by	<i>ARPackage.element</i> , <i>AtpClassifier.atpFeature</i>			
Attribute	Type	Mult.	Kind	Note
initValue	PortPrototypeBlueprint InitValue	*	aggr	This specifies the init values for the dataElements in the particular PortPrototypeBlueprint.
interface	PortInterface	1	ref	This is the interface for which the blueprint is defined. It may be a blueprint itself or a standardized PortInterface
providedCom Spec	PPortComSpec	*	aggr	Provided communication attributes per interface element (data element or operation).
requiredCom Spec	RPortComSpec	*	aggr	Required communication attributes, one for each interface element.

Table A.819: PortPrototypeBlueprint

Primitive	PositiveUnlimitedInteger
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes
Note	This is a positive unlimited integer which can be denoted in decimal, binary, octal and hexadecimal. Tags: xml.xsd.customType=POSITIVE-UNLIMITED-INTEGER xml.xsd.pattern=0 [+]?[1-9][0-9]* 0[xX][0-9a-fA-F]+ 0[bB][0-1]+ 0[0-7]+ xml.xsd.type=string

Table A.820: PositiveUnlimitedInteger

Class	PostBuildVariantCondition			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling			
Note	This class specifies the value which shall be assigned to a particular variant criterion in order to bind the variation point. If multiple criterion/value pairs are specified, they shall all match to bind the variation point. In other words binding can be represented by (criterion1 == value1) && (condition2 == value2) ...			
Base	<i>ARObject</i>			
Aggregated by	VariationPoint.postBuildVariantCondition , VariationPointProxy.postBuildVariantCondition			
Attribute	Type	Mult.	Kind	Note
matching Criterion	PostBuildVariant Criterion	1	ref	This is the criterion which needs to match the value in order to make the PostbuildVariantCondition to be true.
value	Integer	1	attr	This is the particular value of the post-build variant criterion. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.821: PostBuildVariantCondition

Class	PredefinedVariant			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling			
Note	This specifies one predefined variant. It is characterized by the union of all system constant values and post-build variant criterion values aggregated within all referenced system constant value sets and post build variant criterion value sets plus the value sets of the included variants. Tags: atp.recommendedPackage=PredefinedVariants			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , MultilanguageReferrable , <i>PackageableElement</i> , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
includedVariant	PredefinedVariant	*	ref	The associated variants are considered part of this PredefinedVariant. This means the settings of the included variants are included in the settings of the referencing PredefinedVariant. Nevertheless the included variants might be included in several predefined variants.
postBuildVariant CriterionValue Set	PostBuildVariant CriterionValueSet	*	ref	This is the postBuildVariantCriterionValueSet contributing to the predefined variant.
sw Systemconstant ValueSet	SwSystemconstant ValueSet	*	ref	This is the set of Systemconstant Values contributing to the predefined variant.

Table A.822: PredefinedVariant

Class	PrimitiveAttributeCondition			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	The PrimitiveAttributeCondition evaluates to true, if the referenced primitive attribute is accepted by all rules of this condition.			
Base	ARObject, AbstractCondition, AbstractMultiplicityRestriction, AbstractValueRestriction, AttributeCondition			
Aggregated by	ClassContentConditional.condition, InvertCondition.condition			
Attribute	Type	Mult.	Kind	Note
attribute	PrimitiveAttributeTailoring	1	ref	The primitive attribute that has to be accepted by the restrictions of this PrimitiveAttributeCondition

Table A.823: PrimitiveAttributeCondition

Class	PrimitiveAttributeTailoring			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	Tailoring of primitive attributes. Primitive attributes are attributes that have a type which is marked by the stereotype <<primitive>> or <<enumeration>>			
Base	ARObject, AttributeTailoring, DataFormatElementReference, DataFormatElementScope, Identifiable, MultilanguageReferrable, Referrable, SpecElementReference, SpecElementScope			
Aggregated by	ClassContentConditional.attributeTailoring, PrimitiveAttributeTailoring.subAttributeTailoring			
Attribute	Type	Mult.	Kind	Note
defaultValueHandling	DefaultValueApplicationStrategyEnum	0..1	attr	Specification of how to handle AUTOSAR defined default values.
subAttributeTailoring	PrimitiveAttributeTailoring	*	aggr	Tailors the attribute of a <<primitive>> data type.
valueRestriction	ValueRestrictionWithSeverity	0..1	aggr	The restriction of the attribute value.

Table A.824: PrimitiveAttributeTailoring

Class	ProvidedServiceInstance			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Service instances that are provided by the ECU that is connected via the ApplicationEndpoint to a CommunicationConnector.			
Base	ARObject, AbstractServiceInstance, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	ApplicationEndpoint.providedServiceInstance, ServiceInstanceCollectionSet.serviceInstance			
Attribute	Type	Mult.	Kind	Note
allowedServiceConsumer	NetworkEndpoint	*	ref	NetworkEndpoints on which the ConsumedServiceInstances that are communicating with this ProvidedServiceInstance are allowed to be located so that the ACL check in the ServiceDiscovery is successful and the connection is allowed to be established. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=allowedServiceConsumer.networkEndpoint, allowedServiceConsumer.variationPoint.shortLabel atp.Status=draft vh.latestBindingTime=postBuild
autoAvailable	Boolean	0..1	attr	Defines that this ProvidedServiceInstance shall be offered by the service discovery at ECU start.





Class	ProvidedServiceInstance			
eventHandler	EventHandler	*	aggr	Collection of event groups provided by the Provided ServiceInstance Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=eventHandler.shortName, eventHandler.variationPoint.shortLabel vh.latestBindingTime=postBuild
instance Identifier	PositiveInteger	0..1	attr	Instance identifier. Can be used for e.g. service discovery to identify the instance of the service.
loadBalancing Priority	PositiveInteger	0..1	attr	Defines the value to be used for load balancing priority in the service offer. Lower value means higher priority.
loadBalancing Weight	PositiveInteger	0..1	attr	Defines the value to be used for load balancing weight in the service offer. Higher value means higher probability to be chosen.
localUnicast Address	ApplicationEndpoint	0..2	ref	The local address over which the PSI is provided (udp, tcp or both). Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=localUnicastAddress.applicationEndpoint, localUnicastAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
minorVersion	PositiveInteger	0..1	attr	Minor Version of the Service that is provided by this ProvidedServiceInstance.
priority	PositiveInteger	0..1	attr	Defines the frame priority where values from 0 (best effort) to 7 (highest) are allowed.
remoteMulticast Subscription Address	ApplicationEndpoint	*	ref	This reference defines the remote multicast subscribed addresses of service consumers. This reference shall ONLY be used if the remote address of the clients is determined from the configuration and not at runtime. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=remoteMulticastSubscriptionAddress.applicationEndpoint, remoteMulticastSubscriptionAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
remoteUnicast Address	ApplicationEndpoint	*	ref	This reference defines the remote addresses of service consumers. This reference shall ONLY be used if the remote address of the clients is determined from the configuration and not at runtime. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=remoteUnicastAddress.applicationEndpoint, remoteUnicastAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
sdServerConfig	SdServerConfig	0..1	aggr	Service Discovery Server configuration. Tags: atp.Status=obsolete
sdServerTimer Config	SomeipSdServerServiceInstanceConfig	0..1	ref	Server specific configuration settings relevant for the SOME/IP service discovery. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=sdServerTimerConfig.someipSdServerServiceInstanceConfig, sdServerTimerConfig.variationPoint.shortLabel vh.latestBindingTime=postBuild
servicelIdentifier	PositiveInteger	0..1	attr	This attribute represents the ability to describe the SOME/IP service ID that is offered.

Table A.825: ProvidedServiceInstance

Class	QueuedReceiverComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes specific to queued receiving.			
Base	ARObject , RPortComSpec , ReceiverComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec , PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
queueLength	PositiveInteger	0..1	attr	Length of queue for received events.

Table A.826: QueuedReceiverComSpec

Class	QueuedSenderComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes specific to distribution of events (PPortPrototype, SenderReceiverInterface and dataElement carries an "event").			
Base	ARObject , PPortComSpec , SenderComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec , PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.827: QueuedSenderComSpec

Class	RPortComSpec (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes of a required PortPrototype. This class will contain attributes that are valid for all kinds of require-ports, independent of client-server or sender-receiver communication patterns.			
Base	ARObject			
Subclasses	ClientComSpec , ModeSwitchReceiverComSpec , NvRequireComSpec , ParameterRequireComSpec , ReceiverComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec , PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.828: RPortComSpec

Class	RPortPrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	Component port requiring a certain port interface.			
Base	ARObject , AbstractRequiredPortPrototype , AtpBlueprintable , AtpFeature , AtpPrototype , Identifiable , MultilanguageReferrable , PortPrototype , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwComponentType.port			
Attribute	Type	Mult.	Kind	Note
maybeUnconnected	Boolean	0..1	attr	If set to true, this attribute indicates that the enclosing RPortPrototype may be left unconnected and that this aspect has explicitly been considered in the software-component's design.
requiredInterface	PortInterface	0..1	tref	The interface that this port requires. Stereotypes: isOfType

Table A.829: RPortPrototype

Class	RTEEvent (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	Abstract base class for all RTE-related events			
Base	ARObject , AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	AsynchronousServerCallReturnsEvent , BackgroundEvent , DataReceiveErrorEvent , DataReceivedEvent , DataSendCompletedEvent , DataWriteCompletedEvent , ExternalTriggerOccurredEvent , InitEvent , InternalTriggerOccurredEvent , ModeSwitchedAckEvent , OperationInvokedEvent , OsTaskExecutionEvent , SwcModeManagerErrorEvent , SwcModeSwitchEvent , TimingEvent , TransformerHardErrorEvent			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
disabledMode	ModeDeclaration	*	iref	Reference to the Modes that disable the Event. Stereotypes: atpSplitable Tags: atp.Splitkey=disabledMode.contextPort, disabledMode.contextModeDeclarationGroupPrototype, disabledMode.targetModeDeclaration InstanceRef implemented by: RModeInAtomicSwc InstanceRef
startOnEvent	RunnableEntity	0..1	ref	The referenced RunnableEntity starts when the corresponding RTEEvent is raised.

Table A.830: RTEEvent

Class	RapidPrototypingScenario			
Package	M2::AUTOSARTemplates::SWComponentTemplate::RPTScenario			
Note	This meta-class provides the ability to describe a Rapid Prototyping Scenario. Such a Rapid Prototyping Scenario consist out of two main aspects, the description of the byPassPoints and the relation to an rpt Hook. Tags: atp.recommendedPackage=RapidPrototypingScenarios			
Base	ARElement , ARObject , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
hostSystem	System	0..1	ref	System which describes the software components of the host ECU.
rptContainer	RptContainer	*	aggr	Top-level rptContainer definitions of this specific rapid prototyping scenario. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptContainer.shortName, rptContainer.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
rptProfile	RptProfile	*	aggr	Defiens the applicable Rapid Prototyping profls which are especially defining the smbol of the service functions and the valid id range. The order of the RptProfiles determines the order of the service function invocation by RTE. Stereotypes: atpSplitable Tags: atp.Splitkey=rptProfile.shortName
rptSystem	System	0..1	ref	System which describes the rapid prototyping algorithm in the format of AUTOSAR Software Components. Stereotypes: atpSplitable Tags: atp.Splitkey=rptSystem

Table A.831: RapidPrototypingScenario

Class	ReceiverComSpec (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Receiver-specific communication attributes (RPortPrototype typed by SenderReceiverInterface).			
Base	ARObject, RPortComSpec			
Subclasses	NonqueuedReceiverComSpec, QueuedReceiverComSpec			
Aggregated by	AbstractRequiredPortPrototype.requiredComSpec, PortPrototypeBlueprint.requiredComSpec			
Attribute	Type	Mult.	Kind	Note
composite Network Representation	CompositeNetworkRepresentation	*	aggr	This represents a CompositeNetworkRepresentation defined in the context of a ReceiverComSpec. The purpose of this aggregation is to be able to specify the network representation of leaf elements of Application CompositeDataTypes. Stereotypes: atpSplittable Tags: atp.Splitkey=compositeNetworkRepresentation
dataElement	AutosarDataPrototype	0..1	ref	Data element these attributes belong to.
handleOutOfRange	HandleOutOfRangeEnum	0..1	attr	This attribute controls how values that are out of the specified range are handled according to the values of HandleOutOfRangeEnum.
handleOutOfRangeStatus	HandleOutOfRangeStatusEnum	0..1	attr	Control the way how return values are created in case of an out-of-range situation.
maxDeltaCounterInit	PositiveInteger	0..1	attr	Initial maximum allowed gap between two counter values of two consecutively received valid Data, i.e. how many subsequent lost data is accepted. For example, if the receiver gets Data with counter 1 and MaxDeltaCounter Init is 1, then at the next reception the receiver can accept Counters with values 2 and 3, but not 4. Note that if the receiver does not receive new Data at a consecutive read, then the receiver increments the tolerance by 1. Caveat: The E2E wrapper approach involves technologies that are not subjected to the AUTOSAR standard and is superseded by the superior E2E transformer approach (which is fully standardized by AUTOSAR). Hence, new projects (without legacy constraints due to carry-over parts) shall use the fully standardized E2E transformer approach. Stereotypes: atpVariation Tags: atp.Status=obsolete vh.latestBindingTime=preCompileTime
maxNoNewOrRepeatedData	PositiveInteger	0..1	attr	The maximum amount of missing or repeated Data which the receiver does not expect to exceed under normal communication conditions. Caveat: The E2E wrapper approach involves technologies that are not subjected to the AUTOSAR standard and is superseded by the superior E2E transformer approach (which is fully standardized by AUTOSAR). Hence, new projects (without legacy constraints due to carry-over parts) shall use the fully standardized E2E transformer approach. Tags: atp.Status=obsolete
networkRepresentation	SwDataDefProps	0..1	aggr	A NetworkRepresentation is used to define how the data Element is mapped to a communication bus. Stereotypes: atpSplittable Tags: atp.Splitkey=networkRepresentation
receptionProps	ReceptionComSpecProps	0..1	aggr	"This aggregation represents the definition transmission props in the context of the enclosing ReceiverComSpec.





Class	ReceiverComSpec (abstract)			
replaceWith	VariableAccess	0..1	aggr	This aggregation is used to identify the AutosarData Prototype to be taken for sourcing an external replacement in the out-of-range and invalidValue handling.
syncCounterInit	PositiveInteger	0..1	attr	Number of Data required for validating the consistency of the counter that shall be received with a valid counter (i.e. counter within the allowed lock-in range) after the detection of an unexpected behavior of a received counter. Caveat: The E2E wrapper approach involves technologies that are not subjected to the AUTOSAR standard and is superseded by the superior E2E transformer approach (which is fully standardized by AUTOSAR). Hence, new projects (without legacy constraints due to carry-over parts) shall use the fully standardized E2E transformer approach. Tags: atp.Status=obsolete
transformationComSpecProps	TransformationComSpecProps	*	aggr	This references the TransformationComSpecProps which define port-specific configuration for data transformation.
usesEndToEndProtection	Boolean	0..1	attr	This indicates whether the corresponding dataElement shall be transmitted using end-to-end protection. Caveat: The E2E wrapper approach involves technologies that are not subjected to the AUTOSAR standard and is superseded by the superior E2E transformer approach (which is fully standardized by AUTOSAR). Hence, new projects (without legacy constraints due to carry-over parts) shall use the fully standardized E2E transformer approach. Stereotypes: atpVariation Tags: atp.Status=obsolete vh.latestBindingTime=preCompileTime

Table A.832: ReceiverComSpec

Class	ReceptionComSpecProps			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	This meta-class defines a set of reception attributes which the application software is assumed to implement.			
Base	ARObject			
Aggregated by	ReceiverComSpec.receptionProps			
Attribute	Type	Mult.	Kind	Note
dataUpdatePeriod	TimeValue	0..1	attr	This attribute defines the period in which the application shall check for updated data. This attribute is used for the configuration of the E2E protection, but may also indicate a general data reception period.
timeout	TimeValue	0..1	attr	This attribute defines the time interval after which the application shall assume that the to be received data reception has timed out, i.e. the respective data has not been received for that amount of time.

Table A.833: ReceptionComSpecProps

Class	RecordValueSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	Specifies the values for a record.			
Base	<i>ARObject</i> , <i>CompositeValueSpecification</i> , <i>ValueSpecification</i>			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, CompositeRuleBasedValueSpecification.argument, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeipEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
field (ordered)	ValueSpecification	*	aggr	The value for a single record field. This could also be mapped explicitly to a record element of the data type using the shortName of the ValueSpecification. But this would introduce a relationship to the data type that is too strong. As of now, it is only important that the structure of the data type matches the structure of the ValueSpecification independently of the shortNames. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=field, field.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.834: RecordValueSpecification

Enumeration	ReentrancyLevelEnum
Package	M2::AUTOSARTemplates::CommonStructure::InternalBehavior
Note	Specifies if and in which kinds of environments an entity is reentrant.
Aggregated by	<i>ExecutableEntity.reentrancyLevel</i>
Literal	Description
multicoreReentrant	Unlimited concurrent execution of this entity is possible, including preemption and parallel execution on multi core systems. Tags: atp.EnumerationLiteralIndex=0
nonReentrant	Concurrent execution of this entity is not possible. Tags: atp.EnumerationLiteralIndex=1
singleCoreReentrant	Pseudo-concurrent execution (i.e. preemption) of this entity is possible on single core systems. Tags: atp.EnumerationLiteralIndex=2

Table A.835: ReentrancyLevelEnum

Primitive	Ref			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes			
Note	<p>This primitive denotes a name based reference. For detailed syntax see the <code>xsd.pattern</code>.</p> <ul style="list-style-type: none"> • first slash (relative or absolute reference) [optional] • Identifier [required] • a sequence of slashes and Identifiers [optional] <p>This primitive is used by the meta-model tools to create the references.</p> <p>Tags: <code>xml.xsd.customType=REF</code> <code>xml.xsd.pattern=/?[a-zA-Z][a-zA-Z0-9_]{0,127}/([a-zA-Z][a-zA-Z0-9_]{0,127})*</code> <code>xml.xsd.type=string</code></p>			
Attribute	Type	Mult.	Kind	Note
base	Identifier	0..1	attr	<p>This attribute reflects the base to be used for this reference.</p> <p>Tags: <code>xml.attribute=true</code></p>
blueprintValue	String	0..1	attr	<p>This represents a description that documents how the value shall be defined when deriving objects from the blueprint.</p> <p>Tags: <code>atp.Status=draft</code> <code>xml.attribute=true</code></p>
index	PositiveInteger	0..1	attr	<p>This attribute supports the use case to point on specific elements in an array. This is in particular required if arrays are used to implement particular data objects.</p> <p>The counting of array indices starts with the value 0, i.e. the index of the first array element is 0.</p> <p>Tags: <code>xml.attribute=true</code></p>

Table A.836: Ref

Class	ReferenceBase			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::ARPackage			
Note	This meta-class establishes a basis for relative references. Reference bases are identified by the short Label which shall be unique in the current package.			
Base	ARObject			
Aggregated by	ARPackage.referenceBase			
Attribute	Type	Mult.	Kind	Note
globalElement	ReferrableSubtypes Enum	*	attr	<p>This attribute represents a meta-class for which the global referencing is supported via this reference base.</p> <p>Tags: <code>xml.sequenceOffset=29</code></p>
globalInPackage	ARPackage	*	ref	<p>This represents the ability to express that global elements live in various packages which do not have a common ancestor package. Packages mentioned by ReferenceBase.globalInPackage are used in addition to the one in ReferenceBase.package.</p> <p>Tags: <code>xml.sequenceOffset=28</code></p>
isDefault	Boolean	1	attr	<p>This attribute denotes if the current ReferenceBase is the default. Note that there can only be one default reference base within a package.</p> <p>Tags: <code>atp.Status=obsolete</code> <code>xml.sequenceOffset=20</code></p>





Class	ReferenceBase			
package	ARPackage	0..1	ref	This association specifies the basis of all relative references with the base equals shortLabel. Tags: xml.sequenceOffset=30
shortLabel	Identifier	1	attr	This is the name of the reference base. By this name, particular references can denote the applicable base. Stereotypes: atpIdentityContributor Tags: xml.sequenceOffset=10

Table A.837: ReferenceBase

Class	ReferenceCondition			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	The ReferenceCondition evaluates to true, if the referenced reference is accepted by all rules of this condition.			
Base	ARObject , AbstractCondition , AbstractMultiplicityRestriction , AttributeCondition			
Aggregated by	ClassContentConditional.condition , InvertCondition.condition			
Attribute	Type	Mult.	Kind	Note
reference	ReferenceTailoring	1	ref	The reference that has to be accepted by the restrictions of this ReferenceCondition

Table A.838: ReferenceCondition

Class	ReferenceTailoring			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::DataFormatTailoring			
Note	Tailoring of Non-Containment References.			
Base	ARObject , AttributeTailoring , DataFormatElementReference , DataFormatElementScope , Identifiable , MultilanguageReferrable , Referrable , SpecElementReference , SpecElementScope			
Aggregated by	ClassContentConditional.attributeTailoring			
Attribute	Type	Mult.	Kind	Note
typeTailoring	ClassTailoring	*	aggr	Local class tailoring for content that is referenced by this reference.
unresolvedReferenceRestriction	UnresolvedReferenceRestrictionWithSeverity	0..1	aggr	Specifies the severity of unresolved references.

Table A.839: ReferenceTailoring

Class	ReferenceValueSpecification			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	Specifies a reference to a data prototype to be used as an initial value for a pointer in the software.			
Base	ARObject , ValueSpecification			





Class	ReferenceValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeipEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
referenceValue	DataPrototype	0..1	ref	The referenced data prototype.

Table A.840: ReferenceValueSpecification

Class	Referrable (abstract)			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::Identifiable			
Note	Instances of this class can be referred to by their identifier (while adhering to namespace borders).			
Base	ARObject			
Subclasses	AtpDefinition, BswDistinguishedPartition, BswModuleCallPoint, BswModuleClientServerEntry, BswVariableAccess, CouplingPortTrafficClassAssignment, DiagnosticEnvModeElement, EthernetPriorityRegeneration, ExclusiveAreaNestingOrder, HwDescriptionEntity, ImplementationProps, LinSlaveConfigIdent, ModeTransition, MultilanguageReferrable, PncMappingIdent, SingleLanguageReferrable, SoConlPduIdentifier, SocketConnectionBundle, TimeSyncServerConfiguration, TpConnectionIdent			
Attribute	Type	Mult.	Kind	Note
shortName	Identifier	1	attr	This specifies an identifying shortName for the object. It needs to be unique within its context and is intended for humans but even more for technical reference. Stereotypes: atpIdentityContributor Tags: xml.enforceMinMultiplicity=true xml.sequenceOffset=-100
shortName Fragment	ShortNameFragment	*	aggr	This specifies how the Referrable.shortName is composed of several shortNameFragments. Tags: xml.sequenceOffset=-90

Table A.841: Referrable

Class	RelativeTolerance			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	Maximum allowable deviation			
Base	ARObject, TimeRangeTypeTolerance			
Aggregated by	TimeRangeType.tolerance			
Attribute	Type	Mult.	Kind	Note
relative	Integer	0..1	attr	Maximum allowable deviation in percent (percent of the corresponding TimeValue).

Table A.842: RelativeTolerance

Class	RequestResponseDelay			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Time to wait before answering the query.			
Base	ARObject			
Aggregated by	SdClientConfig.requestResponseDelay, SdServerConfig.requestResponseDelay, SomeipSdClientEventGroupTimingConfig.requestResponseDelay , SomeipSdServerEventGroupTimingConfig.requestResponseDelay , SomeipSdServerServiceInstanceConfig.requestResponseDelay			
Attribute	Type	Mult.	Kind	Note
maxValue	TimeValue	0..1	attr	Maximum allowable response delay to entries received by multicast in seconds.
minValue	TimeValue	0..1	attr	Minimum allowable response delay to entries received by multicast in seconds.

Table A.843: RequestResponseDelay

Class	RoleBasedBswModuleEntryAssignment			
Package	M2::AUTOSARTemplates::BswModuleTemplate::BswBehavior			
Note	<p>This class specifies an assignment of a role to a particular BswModuleEntry (usually a configurable callback).</p> <p>With this assignment, the role of the callback is mapped to a specific ServiceNeeds element, so that a tool is able to create appropriate configuration values for the module that implements the AUTOSAR Service.</p>			
Base	ARObject			
Aggregated by	BswServiceDependency.assignedEntryRole			
Attribute	Type	Mult.	Kind	Note
assignedEntry	BswModuleEntry	0..1	ref	The assigned entry. It should be an implementedEntry or expectedEntry of the module or cluster that requires the ServiceNeeds.
role	Identifier	0..1	attr	<p>This is the role of the assigned BswModuleEntry in the given context. The attribute is required (for example) because different kind of callbacks may be associated with the same ServiceNeeds (e.g. end-notification vs. error-notification).</p> <p>The value shall be the role name of a configurable function call (usually a callback) as standardized in the Software Specification of the related AUTOSAR Service.</p>

Table A.844: RoleBasedBswModuleEntryAssignment

Class	RoleBasedDataAssignment			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	<p>This class specifies an assignment of a role to a particular data object in either</p> <ul style="list-style-type: none"> the SwcInternalBehavior of a software component (or in the BswInternalBehavior of a BSW module or BSW cluster) in the context of an AUTOSAR Service or an NvBlockDescriptor to sort out the assignment of event-based writing strategies to data elements in a PortPrototype. <p>With this assignment, the role of the data can be mapped to a DataPrototype that is used in the context of the definition of a specific ServiceNeeds or NvBlockDescriptor, so that a tool is able to create the correct access or writing strategy.</p>			
Base	ARObject			
Aggregated by	BswServiceDependency.assignedData , NvBlockDescriptor.writingStrategy , SwcServiceDependency.assignedData			
Attribute	Type	Mult.	Kind	Note





Class		RoleBasedDataAssignment		
role	Identifier	0..1	attr	This is the role of the assigned data in the given context. Possible values need to be specified on M1 level. Additionally the TPS Software Component Template provides a list of applicable roles for various service dependencies and service use cases in chapter 13 "Service Dependencies and Service Use Cases" (e.g., ramBlock in case of the needs for a permanent RAM block).
usedData Element	AutosarVariableRef	0..1	aggr	The VariableDataPrototype used in this role, e.g. <ul style="list-style-type: none"> Permanent RAM Block of an NVRAM Block which shall belong to the same SwcInternalBehavior or Bsw InternalBehavior. In the role signalBasedDiagnostics it has to refer to a VariableDataPrototype in a SenderReceiverInterface or a NvDataInterface.
usedParameter Element	AutosarParameterRef	0..1	aggr	The ParameterDataPrototype used in this role, e.g. <ul style="list-style-type: none"> ROM Block of an NVRAM Block. It shall belong to the same SwcInternalBehavior or BswInternalbehavior. In the role signalBasedDiagnostics it has to refer to a ParameterDataPrototype in a ParameterInterface.
usedPim	PerInstanceMemory	0..1	ref	The (untyped) PerInstanceMemory used in this role (e.g. as a Permanent RAM Block for an NVRAM Block).

Table A.845: RoleBasedDataAssignment

Class		RoleBasedDataTypeAssignment		
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ServiceMapping			
Note	This class specifies an assignment of a role to a particular data type of a software component (or in the BswModuleBehavior of a module or cluster) in the context of an AUTOSAR Service. With this assignment, the role of the data type can be mapped to a specific ServiceNeeds element, so that a tool is able to create the correct access.			
Base	<i>ARObject</i>			
Aggregated by	ServiceDependency.assignedDataType			
Attribute	Type	Mult.	Kind	Note
role	Identifier	0..1	attr	This is the role of the associated data type in the given context.
used Implementation DataType	ImplementationDataType	0..1	ref	This represents the associated ImplementationDataType.

Table A.846: RoleBasedDataTypeAssignment

Class		RoleBasedPortAssignment		
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ServiceMapping			
Note	This class specifies an assignment of a role to a particular service port (RPortPrototype or PPort Prototype) of an AtomicSwComponentType. With this assignment, the role of the service port can be mapped to a specific ServiceNeeds element, so that a tool is able to create the correct connector.			
Base	<i>ARObject</i>			
Aggregated by	NvBlockDescriptor.clientServerPort , SwcServiceDependency.assignedPort			
Attribute	Type	Mult.	Kind	Note





Class		RoleBasedPortAssignment		
portPrototype	PortPrototype	0..1	ref	Service PortPrototype used in the assigned role. This PortPrototype shall either belong to the same AtomicSw ComponentType as the SwcInternalBehavior which owns the ServiceDependency or to the same NvBlockSw ComponentType as the NvBlockDescriptor.
role	Identifier	0..1	attr	This is the role of the assigned Port in the given context. The value shall be a shortName of the Blueprint of a Port Interface as standardized in the Software Specification of the related AUTOSAR Service.

Table A.847: RoleBasedPortAssignment

Class		RootSwCompositionPrototype		
Package	M2::AUTOSARTemplates::SystemTemplate			
Note	<p>The RootSwCompositionPrototype represents the top-level-composition of software components within a given System.</p> <p>According to the use case of the System, this may for example be a more or less complete VFB description, the software of a System Extract or the software of a flat ECU Extract with only atomic SWCs.</p> <p>Therefore the RootSwComposition will only occasionally contain all atomic software components that are used in a complete VFB System. The OEM is primarily interested in the required functionality and the interfaces defining the integration of the Software Component into the System. The internal structure of such a component contains often substantial intellectual property of a supplier. Therefore a top-level software composition will often contain empty compositions which represent subsystems.</p> <p>The contained SwComponentPrototypes are fully specified by their SwComponentTypes (including Port Prototypes, PortInterfaces, VariableDataPrototypes, SwcInternalBehavior etc.), and their ports are interconnected using SwConnectorPrototypes.</p>			
Base	<i>ARObject, AtpFeature, AtpPrototype, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature, System.rootSoftwareComposition</i>			
Attribute	Type	Mult.	Kind	Note
calibrationParameterValueSet	CalibrationParameterValueSet	*	ref	Used CalibrationParameterValueSet for instance specific initialization of calibration parameters. Stereotypes: atpSplitable Tags: atp.Splitkey=calibrationParameterValueSet
flatMap	FlatMap	0..1	ref	The FlatMap used in the scope of this RootSwCompositionPrototype. Stereotypes: atpSplitable Tags: atp.Splitkey=flatMap
softwareComposition	CompositionSwComponentType	0..1	tref	We assume that there is exactly one top-level composition that includes all Component instances of the system. Stereotypes: isOfType

Table A.848: RootSwCompositionPrototype

Class		RoughEstimateHeapUsage		
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::HeapUsage			
Note	Rough estimation of the heap usage.			
Base	<i>ARObject, HeapUsage, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	ResourceConsumption.heapUsage			
Attribute	Type	Mult.	Kind	Note
memoryConsumption	PositiveInteger	0..1	attr	Rough estimate of the heap usage. Unit: byte.

Table A.849: RoughEstimateHeapUsage

Class	RoughEstimateOfExecutionTime			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::ExecutionTime			
Note	Provides a description of a rough estimate on the ExecutionTime.			
Base	ARObject, ExecutionTime, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	ResourceConsumption.executionTime			
Attribute	Type	Mult.	Kind	Note
additional Information	String	0..1	attr	Provides description on the rough estimate of the ExecutionTime.
estimated ExecutionTime	MultidimensionalTime	0..1	aggr	The estimated execution time.

Table A.850: RoughEstimateOfExecutionTime

Class	RoughEstimateStackUsage			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::StackUsage			
Note	Rough estimation of the stack usage.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, StackUsage			
Aggregated by	ResourceConsumption.stackUsage			
Attribute	Type	Mult.	Kind	Note
memory Consumption	PositiveInteger	0..1	attr	Rough estimate of the stack usage. Unit: byte.

Table A.851: RoughEstimateStackUsage

Class	RptComponent			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport::RptSupport			
Note	Description of component instance for which rapid prototyping support is implemented.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	RptSupportData.rptComponent			
Attribute	Type	Mult.	Kind	Note
mcData Assignment	RoleBasedMcData Assignment	*	aggr	Reference to related McDataElement describing the implementation of "RP global buffer", "RP global measurement buffer", "RP enabler flag" and the "RP runnable disabler flag".
rplmplPolicy	RptImplPolicy	0..1	aggr	Describes the implemented code preparation for rapid prototyping at data accesses.
rptExecutable Entity	RptExecutableEntity	*	aggr	ExecutableEntity instance which can be bypassed. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptExecutableEntity.shortName, rpt ExecutableEntity.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.852: RptComponent

Class	RptContainer			
Package	M2::AUTOSARTemplates::SWComponentTemplate::RPTScenario			
Note	<p>This meta-class defines a byPassPoint and the relation to a rptHook.</p> <p>Additionally it may contain further rptContainers if the byPassPoint is not atomic. For example a byPass Point referencing to a RunnableEntity may contain rptContainers referring to the data access points of the RunnableEntity.</p> <p>The RptContainer structure on M1 shall follow the M1 structure of the Software Component Descriptions. The category attribute denotes which level of the Software Component Description is annotated.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	RapidPrototypingScenario.rptContainer , RptContainer.rptContainer			
Attribute	Type	Mult.	Kind	Note
byPassPoint	AtpFeature	*	iref	<p>byPassPoint describes the required preparation of the host ECU. At a byPassPoint the host ECU shall be capable to communicate with a RPT System in order to support the execution of the rapid prototyping algorithms with the original data calculated by the host system and to replace dedicated results of the host system by the results of the rapid prototyping algorithm.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=byPassPoint.contextElement, byPass Point.target, byPassPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime InstanceRef implemented by: AnyInstanceRef</p>
explicitRpt ProfileSelection	RptProfile	*	ref	<p>This attribute defines the applicable RptProfiles for the specific RptContainer. If not any references to a specific RptProfile is defined, all RptProfiles defined in the Rapid PrototypingScenario are applicable.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=explicitRptProfileSelection</p>
rptContainer	RptContainer	*	aggr	<p>Sub-level rptContainer definitions of this specific rapid prototyping scenario.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptContainer.shortName, rpt Container.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
rptExecutable EntityProperties	RptExecutableEntity Properties	0..1	aggr	<p>Describes the required code preparation for rapid prototyping at ExecutableEntity invocation.</p>
rptHook	RptHook	0..1	aggr	<p>The rptHook describes the link between a byPassPoint and the rapid prototyping algorithm.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptHook, rptHook.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
rptImplPolicy	RptImplPolicy	0..1	aggr	<p>Describes the required code preparation for rapid prototyping at data accesses.</p>
rptSw Prototyping Access	RptSwPrototyping Access	0..1	aggr	<p>Describes the required accessibility of data and modes by the rapid prototyping tooling.</p>

Table A.853: RptContainer

Class	RptExecutableEntity			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport::RptSupport			
Note	This describes a ExecutableEntity instance which can be bypassed.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	RptComponent.rptExecutableEntity			
Attribute	Type	Mult.	Kind	Note
rptExecutableEntityEvent	RptExecutableEntityEvent	*	aggr	ExecutableEntity event instance activation the owning RptExecutableEntity. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptExecutableEntityEvent.shortName, rptExecutableEntityEvent.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
rptRead	RoleBasedMcDataAssignment	*	aggr	read access to a variable Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptRead, rptRead.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
rptWrite	RoleBasedMcDataAssignment	*	aggr	write access to a variable Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptWrite, rptWrite.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
symbol	CIdentifier	0..1	attr	The symbol describing this ExecutableEntity's entry point.

Table A.854: RptExecutableEntity

Class	RptExecutableEntityEvent			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport::RptSupport			
Note	This describes an ExecutableEntity event instance which can be bypassed.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	RptExecutableEntity.rptExecutableEntityEvent			
Attribute	Type	Mult.	Kind	Note
executionContext	RptExecutionContext	*	ref	This describes the context in which the event of the executable entity is executed.
mcDataAssignment	RoleBasedMcDataAssignment	*	aggr	Reference to related McDataElements describing the implementation of "RP runnable disabler flag" and "stimulation enabler flag" The possible roles of the RoleBasedMcDataAssignment.role attribute are: <ul style="list-style-type: none"> • RpRunnableDisablerFlag
rptEventId	PositiveInteger	0..1	attr	RPT event id used for service points call.
rptExecutableEntityProperties	RptExecutableEntityProperties	0..1	aggr	Describes the implemented code preparation for rapid prototyping at ExecutableEntity invocation.
rptImplPolicy	RptImplPolicy	0..1	aggr	Describes the RptImplPolicy of a RptExecutableEvent for service based bypassing.
rptServicePointPost	RptServicePoint	*	ref	This describes the applicable Post Service Points for a RTEEvent / BswEvent of a bypassed ExecutableEntity.
rptServicePointPre	RptServicePoint	*	ref	This describes the applicable Pre Service Points for a RTEEvent / BswEvent of a bypassed ExecutableEntity.

Table A.855: RptExecutableEntityEvent

Class	RptExecutableEntityProperties			
Package	M2::AUTOSARTemplates::SWComponentTemplate::RPTScenario			
Note	Describes the code preparation for rapid prototyping at ExecutableEntity invocation.			
Base	ARObject			
Aggregated by	RptContainer.rptExecutableEntityProperties , RptExecutableEntityEvent.rptExecutableEntityProperties			
Attribute	Type	Mult.	Kind	Note
maxRptEventId	PositiveInteger	0..1	attr	Highest RPT event id usable for RTE generated service points. This attribute is relevant, if dedicated id range shall be applied to the ExecutableEntitys of a software component or specific ExecutableEntitys.
minRptEventId	PositiveInteger	0..1	attr	Lowest RPT event id usable for RTE generated service points. This attribute is relevant, if dedicated id range shall be applied to the ExecutableEntitys of a software component or specific ExecutableEntitys.
rptExecutionControl	RptExecutionControlEnum	0..1	attr	This attribute specifies the rapid prototyping control of the executable
rptServicePoint	RptServicePointEnum	0..1	attr	Enables generation of service points by the RTE generator.

Table A.856: RptExecutableEntityProperties

Class	RptHook			
Package	M2::AUTOSARTemplates::SWComponentTemplate::RPTScenario			
Note	This meta-class provide the ability to describe a rapid prototyping hook. This can either be described by an other AUTOSAR system with the category RPT_SYSTEM or as a non AUTOSAR software.			
Base	ARObject			
Aggregated by	RptContainer.rptHook			
Attribute	Type	Mult.	Kind	Note
codeLabel	CIdentifier	0..1	attr	This attribute provides a code label which is used in the implementation of the hook. For example this can be an C function name or the name of data definition.
mcdIdentifier	NameToken	0..1	attr	This attribute provides an identifier which shall be used in a MCD System to display the Rpt Hook.
rptArHook	AtpFeature	0..1	iref	This describes the hook with the means of another AUTOSAR system. InstanceRef implemented by: AnyInstanceRef
sdg	Sdg	*	aggr	This property allows to keep special data which is not represented by the standard model. It can be utilized to keep e.g. tool specific data.

Table A.857: RptHook

Class	RptImplPolicy			
Package	M2::AUTOSARTemplates::SWComponentTemplate::RPTScenario			
Note	Describes the code preparation for rapid prototyping at data accesses.			
Base	ARObject			
Aggregated by	McDataInstance.rptImplPolicy , RptComponent.rptImplPolicy , RptContainer.rptImplPolicy , RptExecutableEntityEvent.rptImplPolicy			
Attribute	Type	Mult.	Kind	Note
rptEnablerImplType	RptEnablerImplTypeEnum	0..1	attr	For Level 2 or Level3 this property determines how the RTE implements the additional "RP enabler" flag.
rptPreparationLevel	RptPreparationEnum	0..1	attr	Mandates RP preparation level for access to VariableData Prototype within generated RTE implementation.

Table A.858: RptImplPolicy

Class	RptProfile			
Package	M2::AUTOSARTemplates::SWComponentTemplate::RPTScenario			
Note	The RptProfile describes the common properties of a Rapid Prototyping method.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	RapidPrototypingScenario.rptProfile			
Attribute	Type	Mult.	Kind	Note
maxServicePointId	PositiveInteger	0..1	attr	Highest service point id useable for RTE generated service points.
minServicePointId	PositiveInteger	0..1	attr	Lowest service point id useable for RTE generated service points.
servicePointSymbolPost	CIdentifier	0..1	attr	Complete symbol of the function implementing the post service point. This symbol is used for post-build hooking purposes.
servicePointSymbolPre	CIdentifier	0..1	attr	Complete symbol of the function implementing the pre service point. This symbol is used for post-build hooking purposes.
stimEnabler	RptEnablerImplType Enum	0..1	attr	Defines if the service points support the stimulation enabler. If RptProfile.stimEnabler is "none" then no stimulation enabler is passed to the service function. Otherwise the stimulation enabler will be passed as a parameter.

Table A.859: RptProfile

Class	RptServicePoint			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport::RptSupport			
Note	Description of a Service Point implemented for rapid prototyping.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	RptSupportData.rptServicePoint			
Attribute	Type	Mult.	Kind	Note
serviceId	PositiveInteger	0..1	attr	Unique ID (Range: 0 ... 65535) representing the service point.
symbol	CIdentifier	0..1	attr	Complete symbol of the function implementing the service point. This symbol is used for post-build hooking purposes.

Table A.860: RptServicePoint

Class	RptSupportData			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport::RptSupport			
Note	Root element for rapid prototyping support data related to one Implementation artifact on an ECU, in particular the RTE. The rapid prototyping support data may reference to elements provided for McSupportData.			
Base	ARObject			
Aggregated by	McSupportData.rptSupportData			
Attribute	Type	Mult.	Kind	Note
executionContext	RptExecutionContext	*	aggr	Defines an environment for the execution of Executable Entites.





Class	RptSupportData			
rptComponent	RptComponent	*	aggr	Description of components for which rapid prototyping support is implemented. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptComponent.shortName, rptComponent.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
rptServicePoint	RptServicePoint	*	aggr	This aggregation represents the collection of service points associated with the enclosing RptSupportData Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=rptServicePoint.shortName, rptServicePoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.861: RptSupportData

Class	RptSwPrototypingAccess			
Package	M2::AUTOSARTemplates::CommonStructure::MeasurementCalibrationSupport::RptSupport			
Note	Describes the accessibility of data and modes by the rapid prototyping tooling.			
Base	ARObject			
Aggregated by	McDataInstance.resultingRptSwPrototypingAccess , RptContainer.rptSwPrototypingAccess			
Attribute	Type	Mult.	Kind	Note
rptHookAccess	RptAccessEnum	0..1	attr	The related data element can be modified using a post-build hooking tool. An ENABLED VariableData Prototype is implicitly READABLE/WRITABLE.
rptReadAccess	RptAccessEnum	0..1	attr	The related data element can be used as input for bypass functionality by RP tool. If rptImpIPolicy is not specified then RTE generation shall ensure at least suitable MC read points are created.
rptWriteAccess	RptAccessEnum	0..1	attr	The related data element can be used as output for bypass functionality by RP tool. The data element shall be prepared to rptLevel2 and related write service points are present.

Table A.862: RptSwPrototypingAccess

Enumeration	RteApiReturnValueProvisionEnum	
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::AccessCount	
Note	This meta-class provides values to control how return values from RTE APIs are provided.	
Aggregated by	AbstractAccessPoint.returnValueProvision	
Literal	Description	
noReturnValue Provided	The RTE API shall not provide a return value. Tags: atp.EnumerationLiteralIndex=1	
returnValue Provided	The RTE API shall provide a return value. Tags: atp.EnumerationLiteralIndex=0	

Table A.863: RteApiReturnValueProvisionEnum

Class	RtePluginProps			
Package	M2::AUTOSARTemplates::CommonStructure::FlatMap			
Note	The properties of a communication graph with respect to the utilization of RTE Implementation Plug-in.			
Base	ARObject			
Aggregated by	FlatInstanceDescriptor.rtePluginProps			
Attribute	Type	Mult.	Kind	Note
associated CrossSwCluster ComRtePlugin	EcucContainerValue	0..1	ref	This associates a communication graph to a specific RTE Implementation Plug-in handling cross Software Cluster communication.
associatedRte Plugin	EcucContainerValue	0..1	ref	This associates a communication graph to a specific RTE Implementation Plug-in handling local Software Cluster communication or communication in a non-cluster ECU.

Table A.864: RtePluginProps

Class	RtpTp			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	RTP over UDP or over TCP as transport protocol. Tags: atp.Status=obsolete			
Base	ARObject, TransportProtocolConfiguration			
Aggregated by	ApplicationEndpoint.tpConfiguration			
Attribute	Type	Mult.	Kind	Note
ssrc	PositiveInteger	0..1	attr	Synchronization source identifier uniquely identifies the source of a stream. The synchronization sources within the same RTP session will be unique. Tags: atp.Status=obsolete
tcpUdpConfig	TcpUdpConfig	0..1	aggr	Tcp or Udp Configuration. Tags: atp.Status=obsolete

Table A.865: RtpTp

Class	«atpMixed» RuleArguments			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This represents the arguments for a rule-based value specification.			
Base	ARObject			
Aggregated by	RuleBasedValueSpecification.arguments			
Attribute	Type	Mult.	Kind	Note
v	Numerical	0..1	attr	This represents a numerical value for the RuleBased ValueSpecification.
vf	Numerical	0..1	attr	This represents a numerical value for the RuleBased ValueSpecification which may subject to variability. The latest binding time of the VariationPoint shall be pre CompileTime. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
vt	VerbatimString	0..1	attr	This represents a textual value for the RuleBasedValue Specification.





Class	«atpMixed» RuleArguments			
vtf	NumericalOrText	0..1	aggr	<p>This aggregation represents the ability to provide a value that is either numerical or text which existence is subject to variability.</p> <p>Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime</p>

Table A.866: RuleArguments

Class	RuleBasedAxisCont			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	<p>This represents the values for the axis of a compound primitive (curve, map). For standard and fix axes, SwAxisCont contains the values of the axis directly. The axis values of SwAxisCont with the category COM_AXIS, RES_AXIS are for display only. For editing and processing, only the values in the related GroupAxis are binding.</p>			
Base	ARObject			
Aggregated by	ApplicationRuleBasedValueSpecification.swAxisCont			
Attribute	Type	Mult.	Kind	Note
category	CalprmAxisCategory Enum	0..1	attr	<p>This category specifies the particular axis types:</p> <ul style="list-style-type: none"> • STD_AXIS • COM_AXIS • RES_AXIS (swArraysize necessary) <p>Tags: xml.sequenceOffset=20</p>
ruleBased Values	RuleBasedValue Specification	0..1	aggr	<p>This represents the rule based value specification for the axis of a compound primitive (curve, map).</p> <p>Tags: xml.roleElement=true xml.roleWrapperElement=false xml.sequenceOffset=80 xml.typeWrapperElement=false</p>
swArraysize	ValueList	0..1	aggr	<p>For multidimensional compound primitives (curve, map ...) it is necessary to know the dimensions. They are specified using swArraySize.</p> <p>Tags: xml.sequenceOffset=40</p>
swAxisIndex	AxisIndexType	0..1	attr	<p>This property allows to explicitly assign the axis contents to a particular axis. It is specified by numbers where 1 corresponds to the x-axis. It is also possible to derive the axis association from the sequence of the parent.</p> <p>Tags: xml.sequenceOffset=50</p>
unit	Unit	0..1	ref	<p>This represents the physical unit of the provided values.</p> <p>Tags: xml.sequenceOffset=30</p>

Table A.867: RuleBasedAxisCont

Class	RuleBasedValueCont			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	This represents the values of a compound primitive (CURVE, MAP, CUBOID, CUBE_4, CUBE_5, VAL_BLK) or an array.			
Base	ARObject			





Class				
RuleBasedValueCont				
Aggregated by ApplicationRuleBasedValueSpecification.swValueCont				
Attribute	Type	Mult.	Kind	Note
ruleBasedValues	RuleBasedValueSpecification	0..1	aggr	This represents the rule based value specification for the array or compound primitive (CURVE, MAP, CUBOID, CUBE_4, CUBE_5, VAL_BLK). Stereotypes: atpSplitable Tags: atp.Splitkey=ruleBasedValues xml.roleElement=true xml.roleWrapperElement=false xml.sequenceOffset=80 xml.typeWrapperElement=false
swArraysSize	ValueList	0..1	aggr	This attribute defines the size of each dimension for compound primitives CURVE, MAP, CUBOID, CUBE_4, CUBE_5, COM_AXIS, RES_AXIS, VAL_BLK. For each dimension one value has to be defined, e.g. one in case of COM_AXIS and two or more in case of MAP. Tags: xml.sequenceOffset=40
unit	Unit	0..1	ref	This represents the physical unit of the provided values. Tags: xml.sequenceOffset=30

Table A.868: RuleBasedValueCont

Class				
RuleBasedValueSpecification				
Package M2::AUTOSARTemplates::CommonStructure::Constants				
Note This meta-class is used to support a rule-based initialization approach for data types with an array-nature (ApplicationArrayDataType and ImplementationDataType of category ARRAY) or a compound ApplicationPrimitiveDataType (which also boils down to an array-nature).				
Base <i>ARObject</i>				
Aggregated by NumericalRuleBasedValueSpecification.ruleBasedValues , RuleBasedAxisCont.ruleBasedValues , RuleBasedValueCont.ruleBasedValues				
Attribute	Type	Mult.	Kind	Note
arguments	RuleArguments	0..1	aggr	This represents the arguments for the RuleBasedValueSpecification. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=30
maxSizeToFill	Integer	0..1	attr	If a rule is chosen which does not fill until the end, this determines until which size the rule shall fill the values. Tags: xml.sequenceOffset=40
rule	Identifier	0..1	attr	This denotes the name of the rule of the RuleBasedValueSpecification. The rule determines the calculation specification according which the arguments are used to calculate the values. Tags: xml.sequenceOffset=20

Table A.869: RuleBasedValueSpecification

Class	RunnableEntity			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior			
Note	A RunnableEntity represents the smallest code-fragment that is provided by an AtomicSwComponent Type and are executed under control of the RTE. RunnableEntities are for instance set up to respond to data reception or operation invocation on a server.			
Base	<i>ARObject, AtpClassifier, AtpFeature, AtpStructureElement, ExecutableEntity, Identifiable, Multilanguage Referrable, Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature, SwcInternalBehavior.runnable</i>			
Attribute	Type	Mult.	Kind	Note
argument (ordered)	RunnableEntity Argument	*	aggr	This represents the formal definition of a an argument to a RunnableEntity.
asynchronous ServerCall ResultPoint	AsynchronousServerCallResultPoint	*	aggr	The server call result point admits a runnable to fetch the result of an asynchronous server call. The aggregation of AsynchronousServerCallResultPoint is subject to variability with the purpose to support the conditional existence of client server PortPrototypes and the variant existence of server call result points in the implementation. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=asynchronousServerCallResultPoint.shortName, asynchronousServerCallResultPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
canBelInvoked Concurrently	Boolean	0..1	attr	If the value of this attribute is set to "true" the enclosing RunnableEntity can be invoked concurrently (even for one instance of the corresponding AtomicSwComponent Type). This implies that it is the responsibility of the implementation of the RunnableEntity to take care of this form of concurrency.
dataRead Access	VariableAccess	*	aggr	RunnableEntity has implicit read access to dataElement of a sender-receiver PortPrototype or nv data of a nv data PortPrototype. The aggregation of dataReadAccess is subject to variability with the purpose to support the conditional existence of sender receiver ports or the variant existence of dataReadAccess in the implementation. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataReadAccess.shortName, dataReadAccess.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
dataReceive PointBy Argument	VariableAccess	*	aggr	RunnableEntity has explicit read access to dataElement of a sender-receiver PortPrototype or nv data of a nv data PortPrototype. The result is passed back to the application by means of an argument in the function signature. The aggregation of dataReceivePointByArgument is subject to variability with the purpose to support the conditional existence of sender receiver PortPrototype or the variant existence of data receive points in the implementation. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataReceivePointByArgument.shortName, dataReceivePointByArgument.variationPoint.shortLabel vh.latestBindingTime=preCompileTime





Class	RunnableEntity			
dataReceivePointByValue	VariableAccess	*	aggr	<p>RunnableEntity has explicit read access to dataElement of a sender-receiver PortPrototype or nv data of a nv data PortPrototype.</p> <p>The result is passed back to the application by means of the return value. The aggregation of dataReceivePointByValue is subject to variability with the purpose to support the conditional existence of sender receiver ports or the variant existence of data receive points in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataReceivePointByValue.shortName, dataReceivePointByValue.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
dataSendPoint	VariableAccess	*	aggr	<p>RunnableEntity has explicit write access to dataElement of a sender-receiver PortPrototype or nv data of a nv data PortPrototype.</p> <p>The aggregation of dataSendPoint is subject to variability with the purpose to support the conditional existence of sender receiver PortPrototype or the variant existence of data send points in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataSendPoint.shortName, dataSendPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
dataWriteAccess	VariableAccess	*	aggr	<p>RunnableEntity has implicit write access to dataElement of a sender-receiver PortPrototype or nv data of a nv data PortPrototype.</p> <p>The aggregation of dataWriteAccess is subject to variability with the purpose to support the conditional existence of sender receiver ports or the variant existence of dataWriteAccess in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataWriteAccess.shortName, dataWriteAccess.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
externalTriggeringPoint	ExternalTriggeringPoint	*	aggr	<p>The aggregation of ExternalTriggeringPoint is subject to variability with the purpose to support the conditional existence of trigger ports or the variant existence of external triggering points in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=externalTriggeringPoint.ident.shortName, externalTriggeringPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
internalTriggeringPoint	InternalTriggeringPoint	*	aggr	<p>The aggregation of InternalTriggeringPoint is subject to variability with the purpose to support the variant existence of internal triggering points in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=internalTriggeringPoint.shortName, internalTriggeringPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	RunnableEntity			
modeAccess Point	ModeAccessPoint	*	aggr	<p>The runnable has a mode access point. The aggregation of ModeAccessPoint is subject to variability with the purpose to support the conditional existence of mode ports or the variant existence of mode access points in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=modeAccessPoint.ident.shortName, modeAccessPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
modeSwitch Point	ModeSwitchPoint	*	aggr	<p>The runnable has a mode switch point. The aggregation of ModeSwitchPoint is subject to variability with the purpose to support the conditional existence of mode ports or the variant existence of mode switch points in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=modeSwitchPoint.shortName, modeSwitchPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
parameter Access	ParameterAccess	*	aggr	<p>The presence of a ParameterAccess implies that a RunnableEntity needs read only access to a ParameterDataPrototype which may either be local or within a PortPrototype.</p> <p>The aggregation of ParameterAccess is subject to variability with the purpose to support the conditional existence of parameter ports and component local parameters as well as the variant existence of ParameterAccess (points) in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=parameterAccess.shortName, parameterAccess.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
readLocal Variable	VariableAccess	*	aggr	<p>The presence of a readLocalVariable implies that a RunnableEntity needs read access to a VariableDataPrototype in the role of implicitInterRunnableVariable or explicitInterRunnableVariable.</p> <p>The aggregation of readLocalVariable is subject to variability with the purpose to support the conditional existence of implicitInterRunnableVariable and explicitInterRunnableVariable or the variant existence of readLocalVariable (points) in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=readLocalVariable.shortName, readLocalVariable.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
serverCallPoint	ServerCallPoint	*	aggr	<p>The RunnableEntity has a ServerCallPoint. The aggregation of ServerCallPoint is subject to variability with the purpose to support the conditional existence of client server PortPrototypes or the variant existence of server call points in the implementation.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=serverCallPoint.shortName, serverCallPoint.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	RunnableEntity			
symbol	CIdentifier	0..1	attr	The symbol describing this RunnableEntity's entry point. This is considered the API of the RunnableEntity and is required during the RTE contract phase.
waitPoint	WaitPoint	*	aggr	The WaitPoint associated with the RunnableEntity.
writtenLocalVariable	VariableAccess	*	aggr	<p>The presence of a writtenLocalVariable implies that a RunnableEntity needs write access to a VariableData Prototype in the role of implicitInterRunnableVariable or explicitInterRunnableVariable.</p> <p>The aggregation of writtenLocalVariable is subject to variability with the purpose to support the conditional existence of implicitInterRunnableVariable and explicitInterRunnableVariable or the variant existence of writtenLocalVariable (points) in the implementation.</p> <p>Stereotypes: atpSplittable; atpVariation</p> <p>Tags: atp.Splitkey=writtenLocalVariable.shortName, writtenLocalVariable.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>

Table A.870: RunnableEntity

Class	RunnableEntityArgument			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RunnableEntity			
Note	This meta-class represents the ability to provide specific information regarding the arguments to a RunnableEntity.			
Base	ARObject			
Aggregated by	RunnableEntity.argument			
Attribute	Type	Mult.	Kind	Note
symbol	CIdentifier	0..1	attr	This represents the symbol to be generated into the actual signature on the level of the C programming language.

Table A.871: RunnableEntityArgument

Enumeration	RxAcceptContainedIPduEnum	
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication	
Note	Defines whether this ContainerIPdu has a fixed set of containedIPdus assigned for reception.	
Aggregated by	ContainerIPdu.rxAcceptContainedIPdu	
Literal	Description	
acceptAll	No fixed set of containedIPdus is defined for reception, any known containedIPdu (based on headerId) shall be expected within this ContainerIPdu. Tags: atp.EnumerationLiteralIndex=0	
acceptConfigured	A fixed set of containedIPdus is defined for reception. Only these assigned containedIPdus (based on headerId) are expected in this ContainerIPdu. If a not assigned containedIPdu is received within this ContainerIPdu this containedIPdu is discarded. Tags: atp.EnumerationLiteralIndex=1	

Table A.872: RxAcceptContainedIPduEnum

Class	RxIdentifierRange			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Can::CanCommunication			
Note	Optional definition of a CanId range to reduce the effort of specifying every possible FrameTriggering within the defined Id range during reception. All frames received within a range are mapped to the same Pdu that is passed to a upper layer module (e.g. Nm, CDD, PduR).			
Base	ARObject			
Aggregated by	CanFrameTriggering.rxIdentifierRange, CanXINmNodeProps.rxIdentifierRange, IEEE1722TpAcfCanPart.canIdentifierRange			
Attribute	Type	Mult.	Kind	Note
lowerCanId	PositiveInteger	0..1	attr	This attribute can be used together with the upperCanId attribute to define a range of CanIds.
upperCanId	PositiveInteger	0..1	attr	This attribute can be used together with the lowerCanId attribute to define a range of CanIds.

Table A.873: RxIdentifierRange

Class	SOMEIPTransformationDescription			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	The SOMEIPTransformationDescription is used to specify SOME/IP transformer specific attributes.			
Base	ARObject, Describable, TransformationDescription			
Aggregated by	TransformationTechnology.transformationDescription			
Attribute	Type	Mult.	Kind	Note
alignment	PositiveInteger	0..1	attr	Defines the padding for alignment purposes that will be added by the SOME/IP transformer after the serialized data of the variable data length data element. The alignment shall be specified in Bits.
byteOrder	ByteOrderEnum	0..1	attr	Defines which byte order shall be serialized by the SOME/IP transformer
interfaceVersion	PositiveInteger	0..1	attr	The interface version the SOME/IP transformer shall use.

Table A.874: SOMEIPTransformationDescription

Class	«atpVariation» SOMEIPTransformationISignalProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	The class SOMEIPTransformationISignalProps specifies ISignal specific configuration properties for SOME/IP transformer attributes.			
Base	ARObject, Describable, TransformationISignalProps			
Aggregated by	ISignal.transformationISignalProps, ISignalGroup.transformationISignalProps			
Attribute	Type	Mult.	Kind	Note
implements LegacyString Serialization	Boolean	0..1	attr	<p>This attribute indicates that Strings in the SOME/IP message shall NOT be serialized according to the SOME/IP specification for Strings.</p> <p>If this attribute is set to true, BOM and null-termination shall NOT be added in the serialization for Strings in the payload. If this attribute is set to false (or not set) BOM and null-termination shall be added in the serialization for Strings in the payload according to the SOME/IP specification for Strings.</p> <p>NOTE! This attribute is not future safe, and will be removed in an upcoming AUTOSAR release!"</p> <p>Tags: atp.Status=obsolete</p>
interfaceVersion	PositiveInteger	0..1	attr	The interface version the SOME/IP transformer shall use.





Class	«atpVariation» SOMEIPTransformationISignalProps			
isDynamicLengthFieldSize	Boolean	0..1	attr	This attribute shall be used to determine the wire type in the context of using the TLV encoding.
messageType	SOMEIPMessageType Enum	0..1	attr	The Message Type which shall be placed into the SOME/IP header.
sizeOfArrayLengthFields	PositiveInteger	0..1	attr	The size of all length fields (in Bytes) of fixed-size arrays or dynamic size arrays in the SOME/IP message. This attribute is valid for all available occurrences of fixed-size arrays or dynamic size arrays in the SOME/IP message.
sizeOfStringLengthFields	PositiveInteger	0..1	attr	The size of all length fields (in Bytes) of dynamic length strings in the SOME/IP message. This attribute is valid for all available occurrences of strings in the SOME/IP message.
sizeOfStructLengthFields	PositiveInteger	0..1	attr	The size of all length fields (in Bytes) of structs in the SOME/IP message. This attribute is valid for all available occurrences of structures in the SOME/IP message. For a more fine granular modeling on the level of Data Prototypes the DataPrototypeTransformationProps shall be used.
sizeOfUnionLengthFields	PositiveInteger	0..1	attr	The size of all length fields (in Bytes) of unions in the SOME/IP message. This attribute is valid for all available occurrences of Unions in the SOME/IP message. For a more fine granular modeling on the level of Data Prototypes the DataPrototypeTransformationProps shall be used.
tlvDataIdDefinition	TlvDataIdDefinitionSet	*	ref	This reference identifies the TlvDataIdDefinitions relevant for the enclosing SOMEIPTransformationISignalProps

Table A.875: SOMEIPTransformationISignalProps

Class	SOMEIPTransformationProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	The class SOMEIPTransformationProps specifies SOME/IP specific configuration properties.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>TransformationProps</i>			
Aggregated by	TransformationPropsSet.transformationProps			
Attribute	Type	Mult.	Kind	Note
alignment	PositiveInteger	0..1	attr	Defines the padding for alignment purposes that will be added by the SOME/IP transformer after the serialized data of the variable data length data element. The alignment shall be specified in Bits.
sizeOfArrayLengthField	PositiveInteger	0..1	attr	This attribute describes the size of the length field (in Bytes) that will be put in front of the referenced Array in the SOME/IP message.
sizeOfStringLengthField	PositiveInteger	0..1	attr	This attribute describes the size of the length field (in Bytes) that will be put in front of the referenced String in the SOME/IP message.
sizeOfStructLengthField	PositiveInteger	0..1	attr	This attribute describes the size of the length field (in Bytes) that will be put in front of a Structure in the SOME/IP message.
sizeOfUnionLengthField	PositiveInteger	0..1	attr	This attribute describes the size of the length field (in Bytes) that will be put in front of a Union in the SOME/IP message.

Table A.876: SOMEIPTransformationProps

Class	<i>ScheduleTableEntry</i> (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Table entry in a LinScheduleTable. Specifies what will be done in the frame slot.			
Base	<i>ARObject</i>			
Subclasses	ApplicationEntry , FreeFormatEntry , LinConfigurationEntry			
Aggregated by	LinScheduleTable.tableEntry			
Attribute	Type	Mult.	Kind	Note
delay	TimeValue	0..1	attr	Relative delay between this tableEntry and the start of the successor in the schedule table in seconds.
introduction	DocumentationBlock	0..1	aggr	This represents introductory documentation about the schedule table entry. Tags: xml.sequenceOffset=-10
positionInTable	Integer	0..1	attr	Relative position in the schedule table. The first entry index in the schedule table is 0.

Table A.877: ScheduleTableEntry

Class	SdgClass			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::SpecialDataDef			
Note	An SdgClass specifies the name and structure of the SDG that may be used to store proprietary data in an AUTOSAR model. The SdgClass is similar to an UML stereotype.			
Base	<i>ARObject</i> , Identifiable , MultilanguageReferrable , Referrable , SdgElementWithGid			
Aggregated by	SdgDef.sdgClass			
Attribute	Type	Mult.	Kind	Note
attribute (ordered)	SdgAttribute	*	aggr	Defintion of the structure of the Sdg Tags: xml.sequenceOffset=30
caption	Boolean	0..1	attr	Specifies if a caption is required. Note: only Sdgs that have a caption can be referenced Tags: xml.sequenceOffset=20
extendsMeta Class	MetaClassName	0..1	attr	The AUTOSAR Meta-Class that may be extended by this SdgClass. Tags: xml.sequenceOffset=10
sdgConstraint	TraceableText	*	ref	Semantic constraints that restrict the structure of the special data group. Tags: xml.sequenceOffset=40

Table A.878: SdgClass

Class	SdgDef			
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::SpecialDataDef			
Note	A SdgDef groups several SdgClasses which belong to the same extension. The concept of an SdgDef is similiar to an UML Profile. Tags: atp.recommendedPackage=SdgDefs			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>CollectableElement</i> , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	SdgDef			
sdgClass	SdgClass	*	aggr	The owned sdgClasses which define the structure of the Sdgs Tags: xml.namePlural=SDG-CLASSES

Table A.879: SdgDef

Primitive	SectionInitializationPolicyType
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes
Note	<p>SectionInitializationPolicyType describes the intended initialization of MemorySections. The following values are standardized in AUTOSAR Methodology:</p> <ul style="list-style-type: none"> • INIT: To be used for (explicitly or not explicitly) initialized variables. • CLEARED: To be used for not explicitly initialized variables. • POWER-ON-CLEARED: To be used for variables that are not explicitly initialized (cleared) during normal start-up. Instead these are cleared only after power on reset. <p>Please note that the values are defined similar to the representation of enumeration types in the XML schema to ensure backward compatibility.</p> <p>Tags: xml.xsd.customType=SECTION-INITIALIZATION-POLICY-TYPE xml.xsd.type=NMTOKEN</p>

Table A.880: SectionInitializationPolicyType

Class	SectionNamePrefix			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::MemorySectionUsage			
Note	A prefix to be used for generated code artifacts defining a memory section name in the source code of the using module or SWC.			
Base	<i>ARObject</i> , <i>ImplementationProps</i> , <i>Referrable</i>			
Aggregated by	ResourceConsumption.sectionNamePrefix			
Attribute	Type	Mult.	Kind	Note
implementedIn	DependencyOnArtifact	0..1	ref	Optional reference that allows to Indicate the code artifact (header file) containing the preprocessor implementation of memory sections with this prefix. The usage of this link supersedes the usage of a memory mapping header with the default name (derived from the BswModuleDescription's shortName).

Table A.881: SectionNamePrefix

Class	SecureCommunicationAuthenticationProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Authentication properties used to configure SecuredIPdus.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	SecureCommunicationPropsSet.authenticationProps			
Attribute	Type	Mult.	Kind	Note
authInfoTx Length	PositiveInteger	0..1	attr	This attribute defines the length in bits of the authentication code to be included in the payload of the authenticated Pdu.

Table A.882: SecureCommunicationAuthenticationProps

Class	SecureCommunicationFreshnessProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Freshness properties used to configure SecuredIPdus.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	SecureCommunicationPropsSet.freshnessProps			
Attribute	Type	Mult.	Kind	Note
freshnessCounterSyncAttempts	PositiveInteger	0..1	attr	This attribute defines the number of Freshness Counter re-synchronization attempts when a verification failed for a Secured I-PDU. If the value is zero, there will be no additional verification attempt to synchronize with a potentially better fitting Freshness Counter value. This attribute is only applicable if useFreshnessTimestamp is FALSE.
freshnessTimestampTimePeriodFactor	PositiveInteger	0..1	attr	This attribute defines a factor that specifies the time period for the Freshness Timestamp. It holds a multiplication factor that specifies the concrete meaning of a Freshness Timestamp increment by one on basis of microseconds.
freshnessValueLength	PositiveInteger	0..1	attr	This attribute defines the complete length in bits of the Freshness Value. As long as the key doesn't change the counter shall not overflow. The length of the counter shall be determined based on the expected life time of the corresponding key and frequency of usage of the counter.
freshnessValueTxLength	PositiveInteger	0..1	attr	This attribute defines the length in bits of the Freshness Value to be included in the payload of the Secured I-PDU. This length is specific to the least significant bits of the complete Freshness Counter. If the attribute is 0 no Freshness Value is included in the Secured I-PDU.
useFreshnessTimestamp	Boolean	0..1	attr	This attribute specifies whether the Freshness Value is generated through individual Freshness Counters or by a Timestamps. The value is set to TRUE when Timestamps are used.

Table A.883: SecureCommunicationFreshnessProps

Class	SecureCommunicationProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	This meta-class contains configuration settings that are specific for an individual SecuredIPdu.			
Base	<i>ARObject</i>			
Aggregated by	SecuredIPdu.secureCommunicationProps			
Attribute	Type	Mult.	Kind	Note
authDataFreshnessLength	PositiveInteger	0..1	attr	This attribute defines the length in bits of the authentic PDU data that is passed to the SWC that verifies and generates the Freshness.
authDataFreshnessStartPosition	PositiveInteger	0..1	attr	This value determines the start position in bits of the Authentic PDU that shall be passed on to the SWC that verifies and generates the Freshness. The bit counting is done according to TPS_SYST_01068.
authenticationBuildAttempts	PositiveInteger	0..1	attr	This attribute specifies the number of authentication build attempts.
authenticationRetries	PositiveInteger	0..1	attr	This attribute defines the additional number of authentication attempts that are to be carried out when the generation of the authentication information failed for a given SecuredIPdu. If zero is set than only one authentication attempt is done.
dataId	PositiveInteger	0..1	attr	This attribute defines a numerical identifier for the Secured I-PDU.





Class	SecureCommunicationProps			
freshnessValue Id	PositiveInteger	0..1	attr	This attribute defines the Id of the Freshness Value. The Freshness Value might be a normal counter or a time value.
messageLink Length	PositiveInteger	0..1	attr	SecOC links an AuthenticIPdu and CryptographicIPdu together by repeating a specific part (Message Linker) of the AuthenticIPdu in the CryptographicIPdu. This attribute defines the length in bits of the messageLinker.
messageLink Position	PositiveInteger	0..1	attr	SecOC links an AuthenticIPdu and CryptographicIPdu together by repeating a specific part (Message Linker) of the AuthenticIPdu in the CryptographicIPdu. This attribute defines the startPosition in bits of the messageLinker.
secondary FreshnessValue Id	PositiveInteger	0..1	attr	This attribute defines the Id of the Secondary Freshness Value. The Secondary Freshness Value might be a normal counter or a time value. Please note that this attribute is for documentation only to allow the configuration of required freshness value manager and no upstream mapping is defined for it.
securedArea Length	PositiveInteger	0..1	attr	This attribute defines the length in bytes of the area within the payload Pdu which will be secured.
securedArea Offset	PositiveInteger	0..1	attr	This attribute defines the start position (offset in byte) of the area within the payload Pdu which will be secured.

Table A.884: SecureCommunicationProps

Class	SecuredIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>If useAsCryptographicPdu is not set or set to false this IPdu contains the payload of an Authentic IPdu supplemented by additional Authentication Information (Freshness Counter and an Authenticator).</p> <p>If useAsCryptographicPdu is set to true this IPdu contains the Authenticator for a payload that is transported in a separate message. The separate Authentic IPdu is described by the Pdu that is referenced with the payload reference from this SecuredIPdu.</p> <p>Tags: atp.recommendedPackage=Pdus</p>			
Base	ARElement , ARObject , CollectableElement , FibexElement , IPdu , Identifiable , MultilanguageReferrable , PackageableElement , Pdu , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
authentication Props	SecureCommunication AuthenticationProps	0..1	ref	Reference to authentication properties that are valid for this SecuredIPdu.
dynamic RuntimeLength Handling	Boolean	0..1	attr	<p>Defines whether the length information for handling this SecuredIPdu with SecuredIPdu.useSecuredPdu Header=noHeader is taken from the configuration or from the actually provided length information during runtime.</p> <p>true: SecuredIPdu length information is taken from the actually provided length information during runtime.</p> <p>false: SecuredIPdu length information is taken from the configuration.</p>
freshnessProps	SecureCommunication FreshnessProps	0..1	ref	Reference to freshness properties that are valid for this SecuredIPdu.
payload	PduTriggering	0..1	ref	Reference to a Pdu that will be protected against unauthorized manipulation and replay attacks.
secure Communication Props	SecureCommunication Props	0..1	aggr	Specific configuration properties for this SecuredIPdu.





Class	SecuredIPdu			
useAsCryptographicIPdu	Boolean	0..1	attr	<p>If this attribute is set to true the SecuredIPdu contains the Authentication Information for an AuthenticIPdu that is transmitted in a separate message. The AuthenticIPdu contains the original payload, i.e. the secured data.</p> <p>If this attribute is set to false this SecuredIPdu contains the payload of an Authentic IPdu supplemented by additional Authentication Information.</p>
useSecuredPduHeader	SecuredPduHeaderEnum	0..1	attr	<p>This attribute defines the size of the header which is inserted into the SecuredIPdu. If this attribute is set to anything but noHeader, the SecuredIPdu contains the Secured I-PDU Header to indicate the length of the AuthenticIPdu. The AuthenticIPdu contains the original payload, i.e. the secured data.</p>

Table A.885: SecuredIPdu

Class	SecurityEventContextProps			
Package	M2::AUTOSARTemplates::SecurityExtractTemplate			
Note	<p>This meta-class specifies the SecurityEventDefinition to be mapped to an IdsmInstance and adds mapping-dependent properties of this security event valid only for this specific mapping.</p> <p>Tags: atp.Status=candidate</p>			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	SecurityEventContextMapping.mappedSecurityEvent			
Attribute	Type	Mult.	Kind	Note
defaultReportingMode	SecurityEventReportingModeEnum	0..1	attr	<p>This attribute defines the default reporting mode for the referenced security event.</p> <p>Tags: atp.Status=candidate</p>
persistentStorage	Boolean	0..1	attr	<p>This attribute controls whether qualified reportings of the referenced security event shall be stored persistently by the mapped IdsmInstance or not.</p> <p>Tags: atp.Status=candidate</p>
securityEvent	SecurityEventDefinition	0..1	ref	<p>This reference defines the security event that is mapped and enriched by SecurityEventMappingProps with mapping dependent properties.</p> <p>Stereotypes: atpSplitable; atpVariation</p> <p>Tags: atp.Splitkey=securityEvent.securityEventDefinition, securityEvent.variationPoint.shortLabel atp.Status=candidate vh.latestBindingTime=systemDesignTime</p>
sensorInstanceId	PositiveInteger	0..1	attr	<p>This attribute defines the ID of the security sensor that detects the referenced security event.</p> <p>Tags: atp.Status=candidate</p>
severity	PositiveInteger	0..1	attr	<p>This attribute defines how critical/severe the referenced security event is. Please note that currently, the severity level meanings of specific integer values is not specified by AUTOSAR but left to the party responsible for the IDS system design (e.g. the OEM).</p> <p>Tags: atp.Status=candidate</p>

Table A.886: SecurityEventContextProps

Class	SegmentPosition			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	The StaticPart and the DynamicPart can be separated in multiple segments within the multiplexed PDU. The ISignalPdus are copied bit by bit into the MultiplexedIPdu. If the space of the first segment is 5 bits large than the first 5 bits of the ISignalPdu are copied into this first segment and so on.			
Base	ARObject			
Aggregated by	MultiplexedPart.segmentPosition			
Attribute	Type	Mult.	Kind	Note
segmentByte Order	ByteOrderEnum	0..1	attr	This attribute defines the order of the bytes of the segment and the packing into the MultiplexedIPdu. Please consider that [constr_3247] and [constr_3224] are restricting the usage of this attribute.
segmentLength	Integer	0..1	attr	Data Length of the segment in bits.
segment Position	Integer	0..1	attr	Segments bit position relatively to the beginning of a multiplexed IPdu. Note that the absolute position of the segment in the MultiplexedIPdu is determined by the definition of the segmentByteOrder attribute of the SegmentPosition. If Big Endian is specified, the start position indicates the bit position of the most significant bit in the IPdu. If Little Endian is specified, the start position indicates the bit position of the least significant bit in the IPdu. In AUTOSAR the bit counting is always set to "sawtooth" and the bit order is set to "Decreasing". The bit counting in byte 0 starts with bit 0 (least significant bit). The most significant bit in byte 0 is bit 7.

Table A.887: SegmentPosition

Class	SenderComSpec (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes for a sender port (PPortPrototype typed by SenderReceiverInterface).			
Base	ARObject, PPortComSpec			
Subclasses	NonqueuedSenderComSpec , QueuedSenderComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec , PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
composite Network Representation	CompositeNetworkRepresentation	*	aggr	This represents a CompositeNetworkRepresentation defined in the context of a SenderComSpec. Stereotypes: atpSplitable Tags: atp.Splitkey=compositeNetworkRepresentation
dataElement	AutosarDataPrototype	0..1	ref	Data element these quality of service attributes apply to.
handleOutOf Range	HandleOutOfRangeEnum	0..1	attr	This attribute controls how out-of-range values shall be dealt with.
network Representation	SwDataDefProps	0..1	aggr	A networkRepresentation is used to define how the data Element is mapped to a communication bus. Stereotypes: atpSplitable Tags: atp.Splitkey=networkRepresentation
transmission Acknowledge	TransmissionAcknowledgementRequest	0..1	aggr	Requested transmission acknowledgement for data element.
transmission Props	TransmissionComSpecProps	0..1	aggr	This aggregation represents the definition transmission props in the context of the enclosing SenderComSpec.





Class	SenderComSpec (abstract)			
usesEndToEndProtection	Boolean	0..1	attr	This indicates whether the corresponding dataElement shall be transmitted using end-to-end protection. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.888: SenderComSpec

Class	SenderRecArrayElementMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	The SenderRecArrayElement may be a primitive one or a composite one. If the element is primitive, it will be mapped to the SystemSignal (multiplicity 1). If the VariableDataPrototype that is referenced by SenderReceiverToSignalGroupMapping is typed by an ApplicationDataType the reference to the ApplicationArrayElement shall be used. If the VariableDataPrototype is typed by the ImplementationDataType the reference to the ImplementationArrayElement shall be used. If the element is composite, there will be no mapping to the SystemSignal (multiplicity 0). In this case the ArrayElementMapping element will aggregate the TypeMapping element. In that way also the composite datatypes can be mapped to SystemSignals. Regardless whether composite or primitive array element is mapped the indexed element always needs to be specified.			
Base	ARObject			
Aggregated by	SenderRecArrayTypeMapping.arrayElementMapping			
Attribute	Type	Mult.	Kind	Note
complexTypeMapping	SenderRecCompositeTypeMapping	0..1	aggr	This aggregation will be used if the element is composite.
indexedArrayElement	IndexedArrayElement	0..1	aggr	Reference to an indexed array element in the context of the dataElement or in the context of a composite element.
systemSignal	SystemSignal	0..1	ref	Reference to the system signal used to carry the primitive ApplicationArrayElement.

Table A.889: SenderRecArrayElementMapping

Class	SenderRecCompositeTypeMapping (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	Two mappings exist for the composite data types: "ArrayTypeMapping" and "RecordTypeMapping". In both, a primitive datatype will be mapped to a system signal. But it is also possible to combine the arrays and the records, so that an "array" could be an element of a "record" and in the same manner a "record" could be an element of an "array". Nesting these data types is also possible. If an element of a composite data type is again a composite one, the "CompositeTypeMapping" element will be used one more time (aggregation between the ArrayElementMapping and CompositeTypeMapping or aggregation between the RecordElementMapping and CompositeTypeMapping).			
Base	ARObject			
Subclasses	SenderRecArrayTypeMapping, SenderRecRecordTypeMapping			
Aggregated by	SenderRecArrayElementMapping.complexTypeMapping , SenderReceiverCompositeElementToSignalMapping.typeMapping , SenderReceiverToSignalGroupMapping.typeMapping , SenderRecRecordElementMapping.complexTypeMapping			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.890: SenderRecCompositeTypeMapping

Class	SenderRecRecordElementMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	<p>Mapping of a primitive record element to a SystemSignal. If the VariableDataPrototype that is referenced by SenderReceiverToSignalGroupMapping is typed by an ApplicationDataType the reference applicationRecordElement shall be used. If the VariableDataPrototype is typed by the ImplementationDataType the reference implementationRecordElement shall be used. Either the implementationRecordElement or applicationRecordElement reference shall be used.</p> <p>If the element is composite, there will be no mapping to the SystemSignal (multiplicity 0). In this case the RecordElementMapping element will aggregate the complexTypeMapping element. In that way also the composite datatypes can be mapped to SystemSignals.</p>			
Base	AObject			
Aggregated by	SenderRecRecordTypeMapping.recordElementMapping			
Attribute	Type	Mult.	Kind	Note
applicationRecordElement	ApplicationRecordElement	0..1	ref	Reference to an ApplicationRecordElement in the context of the dataElement or in the context of a composite element.
complexTypeMapping	SenderRecCompositeTypeMapping	0..1	aggr	This aggregation will be used if the element is composite.
implementationRecordElement	ImplementationDataTypeElement	0..1	ref	Reference to an ImplementationRecordElement in the context of the dataElement or in the context of a composite element.
senderToSignalTextTableMapping	TextTableMapping	0..1	aggr	This mapping allows for the text-table translation between the sending DataPrototype that is defined in the Port Prototype and the physicalProps defined for the System Signal.
signalToReceiverTextTableMapping	TextTableMapping	0..1	aggr	This mapping allows for the text-table translation between the physicalProps defined for the SystemSignal and a receiving DataPrototype that is defined in the Port Prototype.
systemSignal	SystemSignal	0..1	ref	Reference to the system signal used to carry the primitive ApplicationRecordElement.

Table A.891: SenderRecRecordElementMapping

Class	SenderReceiverAnnotation (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::ApplicationAttributes			
Note	Annotation of the data elements in a port that realizes a sender/receiver interface.			
Base	AObject, GeneralAnnotation			
Subclasses	ReceiverAnnotation, SenderAnnotation			
Aggregated by	PortPrototype.senderReceiverAnnotation			
Attribute	Type	Mult.	Kind	Note
computed	Boolean	0..1	attr	Flag whether this data element was not measured directly but instead was calculated from possibly several other measured or calculated values.
dataElement	VariableDataPrototype	0..1	ref	The instance of VariableDataPrototype annotated.
limitKind	DataLimitKindEnum	0..1	attr	This min or max has not to be mismatched with the min-and max for data-value in a compu-method. For example, this annotation shows when the result of the calculation performed in a RunnableEntity owned by one AtomicSw ComponentType is transmitted to another AtomicSw ComponentType whose RunnableEntity will use this value as a limit, e.g. the max.power which can be used by that software-component, or the current min. slip.
processingKind	ProcessingKindEnum	0..1	attr	This attribute controls how data is processed according to the possible values of ProcessingKindEnum.

Table A.892: SenderReceiverAnnotation

Class	SenderReceiverCompositeElementToSignalMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	Mapping of an Variable Data Prototype which is aggregated within a composite datatype to a System Signal (only one element of the composite data type is mapped).			
Base	<i>ARObject</i> , <i>DataMapping</i>			
Aggregated by	<i>SystemMapping.dataMapping</i>			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	0..1	iref	Reference to a data element with a composite datatype from which one element is mapped to a SystemSignal. InstanceRef implemented by: VariableDataPrototypeInSystemInstanceRef
systemSignal	SystemSignal	0..1	ref	Reference to the SystemSignal to which one primitive of the composite type is mapped.
typeMapping	SenderRecCompositeTypeMapping	0..1	aggr	The CompositeTypeMapping maps one VariableData Prototype of the composite data type to a SystemSignal.

Table A.893: SenderReceiverCompositeElementToSignalMapping

Class	SenderReceiverInterface			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	A sender/receiver interface declares a number of data elements to be sent and received. Tags: atp.recommendedPackage=PortInterfaces			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>AtpClassifier</i> , <i>AtpType</i> , <i>CollectableElement</i> , <i>DataInterface</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>PortInterface</i> , <i>Referrable</i>			
Aggregated by	<i>ARPackage.element</i>			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	*	aggr	The data elements of this SenderReceiverInterface.
invalidation Policy	InvalidationPolicy	*	aggr	InvalidationPolicy for a particular dataElement
metaDataItem Set	MetaDataItemSet	*	aggr	This aggregation defines fixed sets of meta-data items associated with dataElements of the enclosing Sender ReceiverInterface

Table A.894: SenderReceiverInterface

Class	SenderReceiverToSignalGroupMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	Mapping of a sender receiver communication data element with a composite datatype to a signal group.			
Base	<i>ARObject</i> , <i>DataMapping</i>			
Aggregated by	<i>SystemMapping.dataMapping</i>			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	0..1	iref	Reference to a data element with a composite datatype which is mapped to a signal group. InstanceRef implemented by: VariableDataPrototypeInSystemInstanceRef
signalGroup	SystemSignalGroup	0..1	ref	Reference to the signal group, which contain all primitive datatypes of the composite type
typeMapping	SenderRecCompositeTypeMapping	0..1	aggr	The CompositeTypeMapping maps the ApplicationArray Elements and ApplicationRecordElements to Signals of the SignalGroup.

Table A.895: SenderReceiverToSignalGroupMapping

Class	SenderReceiverToSignalMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	Mapping of a sender receiver communication data element to a signal.			
Base	<i>ARObject</i> , <i>DataMapping</i>			
Aggregated by	<i>SystemMapping.dataMapping</i>			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	0..1	iref	Reference to the data element. InstanceRef implemented by: VariableDataPrototypelnSystemInstanceRef
senderToSignal TextTable Mapping	TextTableMapping	0..1	aggr	This mapping allows for the text-table translation between the sending DataPrototype that is defined in the Port Prototype and the physicalProps defined for the System Signal.
signalTo ReceiverText TableMapping	TextTableMapping	0..1	aggr	This mapping allows for the text-table translation between the physicalProps defined for the SystemSignal and a receiving DataPrototype that is defined in the Port Prototype.
systemSignal	SystemSignal	0..1	ref	Reference to the system signal used to carry the data element.

Table A.896: SenderReceiverToSignalMapping

Class	SensorActuatorSwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	The SensorActuatorSwComponentType introduces the possibility to link from the software representation of a sensor/actuator to its hardware description provided by the ECU Resource Template. Tags: atp.recommendedPackage=SwComponentTypes			
Base	<i>ARElement</i> , <i>ARObject</i> , <i>AtomicSwComponentType</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>AtpClassifier</i> , <i>AtpType</i> , <i>CollectableElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i> , <i>SwComponentType</i>			
Aggregated by	<i>ARPackage.element</i>			
Attribute	Type	Mult.	Kind	Note
sensorActuator	HwDescriptionEntity	0..1	ref	Reference from the Sensor Actuator Software Component Type to the description of the actual hardware.

Table A.897: SensorActuatorSwComponentType

Enumeration	ServerArgumentImplPolicyEnum			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This defines how the argument type of the servers RunnableEntity is implemented.			
Aggregated by	ArgumentDataPrototype.serverArgumentImplPolicy			
Literal	Description			
useArgumentType	The argument type of the RunnableEntity is derived from the AutosarDataType of the Argument Prototype. Tags: atp.EnumerationLiteralIndex=0			
useVoid	The argument type of the RunnableEntity is void. Tags: atp.EnumerationLiteralIndex=2			

Table A.898: ServerArgumentImplPolicyEnum

Class	ServerCallPoint (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ServerCall			
Note	If a RunnableEntity owns a ServerCallPoint it is entitled to invoke a particular ClientServerOperation of a specific RPortPrototype of the corresponding AtomicSwComponentType			
Base	ARObject, AbstractAccessPoint, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, Referrable			
Subclasses	AsynchronousServerCallPoint, SynchronousServerCallPoint			
Aggregated by	AtpClassifier.atpFeature, RunnableEntity.serverCallPoint			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	0..1	iref	The operation that is called by this runnable. InstanceRef implemented by: ROperationInAtomicSwc InstanceRef
timeout	TimeValue	0..1	attr	Time in seconds before the server call times out and returns with an error message. It depends on the call type (synchronous or asynchronous) how this is reported.

Table A.899: ServerCallPoint

Class	ServerComSpec			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Communication attributes for a server port (PPortPrototype and ClientServerInterface).			
Base	ARObject, PPortComSpec			
Aggregated by	AbstractProvidedPortPrototype.providedComSpec, PortPrototypeBlueprint.providedComSpec			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	0..1	ref	Operation these communication attributes apply to.
queueLength	PositiveInteger	0..1	attr	Length of call queue on the server side. The queue is implemented by the RTE. The value shall be greater or equal to 1. Setting the value of queueLength to 1 implies that incoming requests are rejected while another request that arrived earlier is being processed.
transformation ComSpecProps	TransformationCom SpecProps	*	aggr	This references the TransformationComSpecProps which define port-specific configuration for data transformation.

Table A.900: ServerComSpec

Class	ServiceDependency (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Collects all dependencies of a software module or component on an AUTOSAR Service related to a specific item (e.g. an NVRAM Block, a diagnostic event etc.). It defines the quality of service (Service Needs) of this item as well as (optionally) references to additional elements. This information is required for tools in order to generate the related basic software configuration and ServiceSwComponentTypes.			
Base	ARObject			
Subclasses	BswServiceDependency, SwcServiceDependency			
Attribute	Type	Mult.	Kind	Note





Class	ServiceDependency (abstract)			
assignedData Type	RoleBasedDataTypeAssignment	0..1	aggr	This is the role of the assignment data type in the given context. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=assignedDataType, assignedDataType.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
diagnostic Relevance	ServiceDiagnostic RelevanceEnum	0..1	attr	If this attribute indicates a relevance for diagnostics then the integrator has a much easier time identifying the candidates for the configuration of the diagnostic stack. Example: identification of mode conditions (e.g. communication between application and BswM) relevant for the Dcm.
symbolicName Props	SymbolicNameProps	0..1	aggr	This attribute can be taken to contribute to the creation of symbolic name values.

Table A.901: ServiceDependency

Class	ServiceNeeds (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	This expresses the abstract needs that a Software Component or Basic Software Module has on the configuration of an AUTOSAR Service to which it will be connected. "Abstract needs" means that the model abstracts from the Configuration Parameters of the underlying Basic Software.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	BswMgrNeeds , ChargeManagerNeeds , ComMgrUserNeeds , CryptoKeyManagementNeeds , CryptoServiceJobNeeds , CryptoServiceNeeds , DiagnosticCapabilityElement , DltUserNeeds , DolpServiceNeeds , EcuStateMgrUserNeeds , ErrorTracerNeeds , FunctionInhibitionAvailabilityNeeds , FunctionInhibitionNeeds , GeneralPurposeTimerServiceNeeds , GlobalSupervisionNeeds , HardwareTestNeeds , IdsMgrCustomTimestampNeeds , IdsMgrNeeds , IndicatorStatusNeeds , J1939DcmDm19Support , J1939RmIncomingRequestServiceNeeds , J1939RmOutgoingRequestServiceNeeds , NvBlockNeeds , SecureOnBoardCommunicationNeeds , SupervisedEntityCheckpointNeeds , SupervisedEntityNeeds , SyncTimeBaseMgrUserNeeds , V2xDataManagerNeeds , V2xFacUserNeeds , V2xMUserNeeds , VendorSpecificServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.902: ServiceNeeds

Class	ServiceProxySwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	<p>This class provides the ability to express a software-component which provides access to an internal service for remote ECUs. It acts as a proxy for the service providing access to the service.</p> <p>An important use case is the request of vehicle mode switches: Such requests can be communicated via sender-receiver interfaces across ECU boundaries, but the mode manager being responsible to perform the mode switches is an AUTOSAR Service which is located in the Basic Software and is not visible in the VFB view. To handle this situation, a ServiceProxySwComponentType will act as proxy for the mode manager. It will have R-Ports to be connected with the mode requestors on VFB level and Service-Ports to be connected with the local mode manager at ECU integration time.</p> <p>Apart from the semantics, a ServiceProxySwComponentType has these specific properties:</p> <ul style="list-style-type: none"> • A prototype of it can be mapped to more than one ECUs in the system description. • Exactly one additional instance of it will be created in the ECU-Extract per ECU to which the prototype has been mapped. • For remote communication, it can have only R-Ports with sender-receiver interfaces and 1:n semantics. • There shall be no connectors between two prototypes of any ServiceProxySwComponentType. <p>Tags: atp.recommendedPackage=SwComponentTypes</p>			
Base	ARElement , ARObject , AtomicSwComponentType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.903: ServiceProxySwComponentType

Class	ServiceSwComponentType			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	<p>ServiceSwComponentType is used for configuring services for a given ECU. Instances of this class are only to be created in ECU Configuration phase for the specific purpose of the service configuration.</p> <p>Tags: atp.recommendedPackage=SwComponentTypes</p>			
Base	ARElement , ARObject , AtomicSwComponentType , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , SwComponentType			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.904: ServiceSwComponentType

Enumeration	ServiceVersionAcceptanceKindEnum			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Defined the possible acceptance kinds for required service instances.			
Aggregated by	ConsumedServiceInstance.versionDrivenFindBehavior , RequiredSomeipServiceInstance.versionDrivenFindBehavior			
Literal	Description			
exactOrAnyMinorVersion	<p>Search for ANY or specific minor version service instance and select either ALL returned service instances (in case of ANY) or exactly the specific minor version service instances defined in required MinorVersion.</p> <p>Tags: atp.EnumerationLiteralIndex=0</p>			





Enumeration	ServiceVersionAcceptanceKindEnum
minimumMinorVersion	Search for ANY minor version service instance and select only those service instances which have an equal or greater minor version than given in requiredMinorVersion. Tags: atp.EnumerationLiteralIndex=1

Table A.905: ServiceVersionAcceptanceKindEnum

Enumeration	SignalServiceTranslationControlEnum
Package	M2::AUTOSARTemplates::CommonStructure::SignalServiceTranslation
Note	This enumeration allows to define how the service instance offer/subscribe control shall behave.
Aggregated by	SignalServiceTranslationProps.serviceControl
Literal	Description
allPartialNetworksActive	Defines the start of service control when all specified partial networks are active. Tags: atp.EnumerationLiteralIndex=3
anyPartialNetworkActive	Defines the start of service control when any specified partial network is active. Tags: atp.EnumerationLiteralIndex=4
partialNetwork	Defines the start of service control when specific partial networks are active. Tags: atp.EnumerationLiteralIndex=1 atp.Status=obsolete
serviceDiscovery	Defines the start of service control when other service is available. Tags: atp.EnumerationLiteralIndex=2
translationStart	Defines the start of service control at translation start. Tags: atp.EnumerationLiteralIndex=0

Table A.906: SignalServiceTranslationControlEnum

Class	SignalServiceTranslationElementProps			
Package	M2::AUTOSARTemplates::CommonStructure::SignalServiceTranslation			
Note	Defined translation properties for individual mapped elements.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	SignalServiceTranslationEventProps.elementProps			
Attribute	Type	Mult.	Kind	Note
element	DataPrototypeReference	0..1	aggr	Reference to the leaf element the SignalServiceTranslationElementProps apply to.
filter	DataFilter	0..1	aggr	Defines an optional filter to be applied during translation.
transmissionTrigger	Boolean	0..1	attr	Defines whether the source element (which is mapped to the referenced element) triggers the sending of the respective payload.

Table A.907: SignalServiceTranslationElementProps

Class	SignalServiceTranslationEventProps
Package	M2::AUTOSARTemplates::CommonStructure::SignalServiceTranslation
Note	This element allows to define the properties which are applicable for the signal/service translation event.
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>





Class	SignalServiceTranslationEventProps			
Aggregated by	SignalServiceTranslationProps . signalServiceTranslationEventProps			
Attribute	Type	Mult.	Kind	Note
elementProps	SignalServiceTranslationElementProps	*	aggr	Defines properties for a single translated element.
safeTranslation	Boolean	0..1	attr	Defined whether the translation shall happen in a safe way.
secureTranslation	Boolean	0..1	attr	Defined whether the translation shall happen in a secure way.
translationTarget	VariableDataPrototype	0..1	iref	Reference to a VariableDataPrototype representing the target of signal/service translation. InstanceRef implemented by: VariableDataPrototypeInSystemInstanceRef

Table A.908: SignalServiceTranslationEventProps

Class	SignalServiceTranslationProps			
Package	M2::AUTOSARTemplates::CommonStructure::SignalServiceTranslation			
Note	This element allows to define the properties which are applicable for the signal/service translation service.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SignalServiceTranslationPropsSet . signalServiceTranslationProps			
Attribute	Type	Mult.	Kind	Note
controlConsumedEventGroup	ConsumedEventGroup	*	ref	Reference to the EventGroup which encapsulates the signal-based payload.
controlPnc	PncMappingIdent	*	ref	Reference to the PNCs which control the offer/subscribe behavior of the translated service instance. Stereotypes: atpSplittable Tags: atp.Splitkey=controlPnc
controlProvidedEventGroup	EventHandler	*	ref	Reference to the provided event group (aka Event Handler) which is automatically available when service Control equals translationStart.
serviceControl	SignalServiceTranslationControlEnum	0..1	attr	Defines how the service instance control shall behave.
signalServiceTranslationEventProps	SignalServiceTranslationEventProps	*	aggr	Defines properties for a single translated event.

Table A.909: SignalServiceTranslationProps

Class	SimulatedExecutionTime			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::ExecutionTime			
Note	Specifies the ExecutionTime which has been gathered using simulation means.			
Base	ARObject , ExecutionTime , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	ResourceConsumption . executionTime			
Attribute	Type	Mult.	Kind	Note
maximumExecutionTime	MultidimensionalTime	0..1	aggr	The maximum simulated execution time.





Class	SimulatedExecutionTime			
minimum ExecutionTime	MultidimensionalTime	0..1	aggr	The minimum simulated execution time.
nominal ExecutionTime	MultidimensionalTime	0..1	aggr	The nominal simulated execution time.

Table A.910: SimulatedExecutionTime

Class	SoAdConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	SoAd Configuration for one specific Physical Channel.			
Base	ARObject			
Aggregated by	EthernetPhysicalChannel.soAdConfig			
Attribute	Type	Mult.	Kind	Note
connection	SocketConnection	*	aggr	This aggregation is obsolete and will be removed in the future. The connectionGroup aggregation with bundled Connections shall be used instead. Old description: Collection of socket connections. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=connection, connection.variationPoint.shortLabel atp.Status=obsolete vh.latestBindingTime=postBuild
connection Bundle	SocketConnection Bundle	*	aggr	Collection of SocketConnectionBundles. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=connectionBundle.shortName, connectionBundle.variationPoint.shortLabel atp.Status=obsolete vh.latestBindingTime=postBuild
socketAddress	SocketAddress	*	aggr	Collection of SoAdAddresses. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=socketAddress.shortName, socketAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild

Table A.911: SoAdConfig

Class	SoConIPduIdentifier			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Identification of Pdu content on a socket connection. This Identifier is required in case that multiple Pdus are transmitted over the same socket connection.			
Base	ARObject , Referrable			
Aggregated by	SocketConnectionIpduIdentifierSet.IpduIdentifier			
Attribute	Type	Mult.	Kind	Note
headerId	PositiveInteger	0..1	attr	If multiple Pdus are transmitted over the same connection this headerId can be used to distinguish between the different Pdus. For the constraints on constructing the headerId for SOME/IP also see PRS_SOMEIP_00245.





Class	SoConIPdulIdentifier			
pduCollection PduTimeout	TimeValue	0..1	attr	Defines the timeout in seconds the PDU collection shall be transmitted at the latest after this PDU has been put into the buffer.
pduCollection Semantics	PduCollection SemanticsEnum	0..1	attr	Specifies if the referenced PduTriggering shall be collected using a queued (i.e. all PDU instances) or last-is-best (i.e. only the last PDU instance) semantics. If this attribute is not present the behavior of "queued" is assumed.
pduCollection Trigger	PduCollectionTrigger Enum	0..1	attr	Defines whether the referenced Pdu contributes to the triggering of the socket transmission if Pdu collection is enabled for this socket.
pduTriggering	PduTriggering	0..1	ref	Reference to a Pdu that is transmitted over a socket connection.

Table A.912: SoConIPdulIdentifier

Class	SocketAddress			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	This meta-class represents a socket address towards the rest of the meta-model. The actual semantics of the represented socket address, however, is contributed by aggregation of an ApplicationEndpoint.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SoAdConfig.socketAddress			
Attribute	Type	Mult.	Kind	Note
allowedIPv6Ext Headers	IPv6ExtHeaderFilterList	0..1	ref	Reference to a list of IPv6 Extension Headers allowed for this SocketConnection. If no list is referenced all IPv6 Extension Headers are allowed and processed.
allowedTcp Options	TcpOptionFilterList	0..1	ref	Reference to a list of TCP options allowed for this Socket Connection.
application Endpoint	ApplicationEndpoint	0..1	aggr	Application addressing
connector	EthernetCommunication Connector	0..1	ref	Association to a CommunicationConnector in the topology description. This reference shall be used if the SocketAddress describes an IP unicast address for an ECU that is part of the model.
differentiated ServiceField	PositiveInteger	0..1	attr	The 6-bit Differentiated Service Field in the IP headers may be used for classifying network traffic. If not set a value of zero is used to indicate packets that have not been classified.
flowLabel	PositiveInteger	0..1	attr	The 20-bit Flow Label field in the IPv6 header may be used by a source to label sequences of packets for which it requests special handling by the IPv6 routers, such as non-default quality of service. If not set a Flow Label of zero is used to indicate packets that have not been labeled.





Class	SocketAddress			
multicast Connector	EthernetCommunicationConnector	*	ref	Association to a CommunicationConnector in the topology description. This reference shall be used if the SocketAddress describes an IP multicast address, i.e. if the aggregated ApplicationEndpoint references a NetworkEndpoint that describes an IP Address in the IP multicast range. Such a SocketAddress contains references to those Ecus (via the multicastConnector reference) in the model that will receive multicast messages via the SocketAddress that is defined by the aggregated ApplicationEndpoint and NetworkEndpoint, i.e. IP Address and UDP Port combination. Stereotypes: atpSplittable Tags: atp.Splitkey=multicastConnector
pathMtu Discovery Enabled	Boolean	0..1	attr	Defines whether the Path MTU Discovery shall be performed for the related socket.
pduCollection MaxBufferSize	PositiveInteger	0..1	attr	Defines the maximum buffer size in Byte which shall be filled before a socket with Pdu collection enabled shall be transmitted to the lower layer.
pduCollection Timeout	TimeValue	0..1	attr	Defines the time in seconds which shall pass before a socket with Pdu collection enabled shall be transmitted to the lower layer after the first Pdu has been put into the socket buffer.
staticSocket Connection	StaticSocketConnection	*	aggr	Definition of a static SocketConnection. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=staticSocketConnection.shortName, static SocketConnection.variationPoint.shortLabel vh.latestBindingTime=postBuild
ttl	PositiveInteger	0..1	attr	This attribute defines a value set in the header of an Internet Protocol (IP) packet that tells network devices the maximum number of router hops the packet can make before it is discarded. The TTL value is a counter that is decremented by 1 every time the packet passes through a router.
udpChecksum Handling	UdpChecksum CalculationEnum	0..1	attr	Specifies if UDP checksum handling shall be enabled (udpChecksumEnabled) or skipped (udpChecksumDisabled) on the related socket connection.

Table A.913: SocketAddress

Class	SocketConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ObsoleteModel			
Note	The SoAd serves as a (De)Multiplexer between different PDU sources and the TCP/IP stack. Tags: atp.Status=obsolete			
Base	<i>ARObject, Describable</i>			
Aggregated by	SoAdConfig.connection , SocketConnectionBundle.bundledConnection			
Attribute	Type	Mult.	Kind	Note
clientIpAddr From Connection Request	Boolean	0..1	attr	If set to true the Server "learns" the client IP address on connection request. This means that the statically configured IP Address of the related client shall be ignored. If set to false the Server only accepts statically configured IP address, e.g. 192.168.1.2. This means that the statically configured IP Address of the Client shall be used.





Class	SocketConnection			
clientPort	SocketAddress	0..1	ref	Client Port for TCP/UDP connection in an abstract communication sense. The client is the major requester of the communication. Please note that the client may also produce data. Tags: atp.Status=obsolete
clientPortFrom Connection Request	Boolean	0..1	attr	If set to true the Server "learns" the client Port on connection request. This means that the statically configured Port of the related client shall be ignored. If set to false the Server only accepts statically configured Port. This means that the statically configured Port of the Client shall be used.
pdu	SocketConnectionIpdu Identifier	*	aggr	PDUs handed over by the PDU Router (Transmission over the Ethernet) or PDUs handed over by SoAd (Reception over Ethernet). Multiple IPdus can be transmitted over one socket connection. Tags: atp.Status=obsolete
pduCollection MaxBufferSize	PositiveInteger	0..1	attr	Defines the maximum buffer size in Byte which shall be filled before a socket with Pdu collection enabled shall be transmitted to the lower layer.
pduCollection Timeout	TimeValue	0..1	attr	Defines the time in seconds which shall pass before a socket with Pdu collection enabled shall be transmitted to the lower layer after the first Pdu has been put into the socket buffer.
runtimeIp Address Configuration	RuntimeAddress ConfigurationEnum	0..1	attr	This attribute determines which protocol is used by the client to obtain the IP Address information. If this attribute is not set to none the value determines the service used by the client to obtain the IP Address information for the SocketConnection. If this attribute is set to none the client used the statically configured IP Address information.
runtimePort Configuration	RuntimeAddress ConfigurationEnum	0..1	attr	This attribute determines which protocol is used by the client to obtain the Port information. If this attribute is not set to none the value determines the service used by the client to obtain the Port information for the Socket Connection. If this attribute is set to none the client uses the statically configured Port information.
shortLabel	Identifier	0..1	attr	This attribute specifies an identifying shortName for the SocketConnection. It shall be unique within its context.

Table A.914: SocketConnection

Class	SoftwareContext			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption			
Note	Specifies the context of the software for this resource consumption.			
Base	<i>ARObject</i>			
Aggregated by	ExecutionTime.softwareContext , HeapUsage.softwareContext , StackUsage.softwareContext			
Attribute	Type	Mult.	Kind	Note
input	String	0..1	attr	Specifies the input vector which is used to provide the ExecutionTime.
state	String	0..1	attr	Specifies the state the software is in when the Execution Time is provided.

Table A.915: SoftwareContext

Class	SomeipSdClientEventGroupTimingConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	This meta-class is used to specify configuration related to service discovery in the context of an event group on SOME/IP. Tags: atp.recommendedPackage=SomeipSdTimingConfigs			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
requestResponseDelay	RequestResponseDelay	0..1	aggr	The Service Discovery shall delay answers to unicast messages triggered by multicast messages (e.g. Subscribe Eventgroup after Offer Service).
subscribeEventgroupRetryDelay	TimeValue	0..1	attr	This attribute defines the interval in seconds to re-trigger a subscription to a Eventgroup, if a retry to subscribe to a Eventgroup is configured (subscribeEventgroupRetryMax > 0).
subscribeEventgroupRetryMax	PositiveInteger	0..1	attr	This attribute define the maximum counts of retries to subscribe to an Eventgroup. If the value is set to 0 no retry shall be done. If the value is set to 255 the retry shall be done as long as the Eventgroup is requested and no SubscribeEventGroupAck was received.
timeToLive	PositiveInteger	0..1	attr	Defines the time in seconds the subscription of this event is expected by the client. this value is sent from the client to the server in the SD-subscribeEvent message.

Table A.916: SomeipSdClientEventGroupTimingConfig

Class	SomeipSdClientServiceInstanceConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Client specific settings that are relevant for the configuration of SOME/IP Service-Discovery. Tags: atp.recommendedPackage=SomeipSdTimingConfigs			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
initialFindBehavior	InitialSdDelayConfig	0..1	aggr	Controls initial find behavior of clients.
priority	PositiveInteger	0..1	attr	This attribute defines the VLAN frame priority for Service Discovery messages that result from RequiredSomeipServiceInstances that are referncing this SomeipSdClientServiceInstanceConfig (Find, SubscribeEventGroup, StopSubscribeEventgroup). Values from 0 (best effort) to 7 (highest) are allowed.
serviceFindTimeToLive	PositiveInteger	0..1	attr	This attribute represents the ability to define the time in seconds the service find is valid. Note! The TTL value for FindService entries is not used and shall be ignored by the server service. This configuration is only kept for backward compatibility. Default value if not specified shall be 0xFFFFFFFF.

Table A.917: SomeipSdClientServiceInstanceConfig

Class	SomeipSdServerEventGroupTimingConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	EventGroup specific timing configuration settings. Tags: atp.recommendedPackage=SomeipSdTimingConfigs			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
requestResponseDelay	RequestResponseDelay	0..1	aggr	The Service Discovery shall delay answers to unicast messages triggered by multicast messages (e.g. Subscribe Eventgroup after Offer Service).

Table A.918: SomeipSdServerEventGroupTimingConfig

Class	SomeipSdServerServiceInstanceConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Server specific settings that are relevant for the configuration of SOME/IP Service-Discovery. Tags: atp.recommendedPackage=SomeipSdTimingConfigs			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
initialOfferBehavior	InitialSdDelayConfig	0..1	aggr	Controls offer behavior of the server.
offerCyclicDelay	TimeValue	0..1	attr	Optional attribute to define cyclic offers. Cyclic offer is active, if the delay is set (in seconds) and greater then 0.
priority	PositiveInteger	0..1	attr	This attribute defines the VLAN frame priority for Service Discovery messages that result from ProvidedSomeipServiceInstances that are referencing the SomeipSdServerServiceInstanceConfig (OfferService, StopOfferService, SubscribeEventGroupAck). Values from 0 (best effort) to 7 (highest) are allowed.
requestResponseDelay	RequestResponseDelay	0..1	aggr	Maximum/Minimum allowable response delay to entries received by multicast in seconds. The Service Discovery shall delay answers to entries that were transported in a multicast SOME/IP-SD message (e.g. FindService).
serviceOfferTimeToLive	PositiveInteger	0..1	attr	Defines the time in seconds the service offer is valid.

Table A.919: SomeipSdServerServiceInstanceConfig

Class	SomeipServiceVersion			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	This meta-class represents the ability to describe a version of a SOME/IP Service.			
Base	ARObject			
Aggregated by	ConsumedServiceInstance.blocklistedVersion, RequiredSomeipServiceInstance.blocklistedVersion, SomeipServiceInterfaceDeployment.serviceInterfaceVersion			
Attribute	Type	Mult.	Kind	Note
majorVersion	PositiveInteger	0..1	attr	Major Version of the ServiceInterface. Tags: xml.sequenceOffset=10
minorVersion	PositiveInteger	0..1	attr	Minor Version of the ServiceInterface. Tags: xml.sequenceOffset=20

Table A.920: SomeipServiceVersion

Class	SomeipTpConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	A connection identifies the sender and the receiver of this particular communication. The SOME/IP TP module routes a Pdu through this connection.			
Base	ARObject			
Aggregated by	SomeipTpConfig.tpConnection			
Attribute	Type	Mult.	Kind	Note
tpChannel	SomeipTpChannel	0..1	ref	Assignment of configuration properties valid for this SomeipTpConnection.
tpSdu	PduTriggering	0..1	ref	Reference to an IPdu that is segmented by the Transport Protocol.
transportPdu	PduTriggering	0..1	ref	Reference to the segmented IPdu.

Table A.921: SomeipTpConnection

Class	SpecElementReference (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::StandardizationTemplate::DataExchangePoint::Common Patterns			
Note	This is a reference to a specification element in the Autosar standard.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Subclasses	DataFormatElementReference , SpecElementScope			
Attribute	Type	Mult.	Kind	Note
alternative Name	String	0..1	attr	Alternative name of a specification element if its name doesn't fit into the shortName. E.g. because the name contains spaces.

Table A.922: SpecElementReference

Class	SporadicEventTriggering			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::EventTriggeringConstraint			
Note	Describes the behavior of an event which occurs occasionally or singularly.			
Base	ARObject, EventTriggeringConstraint , Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
jitter	MultidimensionalTime	0..1	aggr	The maximum deviation of the sporadic event occurrence. Jitter=max nthPeriod - standardPeriod Tags: xml.sequenceOffset=30
maximumInter ArrivalTime	MultidimensionalTime	0..1	aggr	The maximum time distance between two consecutive (subsequent) occurrences of the associated event. Tags: xml.sequenceOffset=20
minimumInter ArrivalTime	MultidimensionalTime	0..1	aggr	The minimum time distance between two consecutive (subsequent) occurrences of the associated event. Tags: xml.sequenceOffset=10
period	MultidimensionalTime	0..1	aggr	The periodic distance between subsequent occurrences of the event. Tags: xml.sequenceOffset=40

Table A.923: SporadicEventTriggering

Class	StateDependentFirewall			
Package	M2::AUTOSARTemplates::AdaptivePlatform::PlatformModuleDeployment::Firewall			
Note	Firewall rules that are defined in a firewall state Tags: atp.Status=candidate atp.recommendedPackage=StateDependentFirewallRules			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
defaultAction	FirewallActionEnum	0..1	attr	This attribute defines a defaultAction in case that the VehicleMode is not yet set. Tags: atp.Status=candidate
firewallRule Props (ordered)	FirewallRuleProps	*	aggr	Collection of firewall rules that apply in the vehicle mode Tags: atp.Status=candidate
firewallState Mode Declaration	ModeDeclaration	*	ref	Reference to firewall states in which the Firewall is active. If one of the referenced ModeDeclarations is the current firewall state then the firewall rule shall be considered as active. Tags: atp.Status=candidate

Table A.924: StateDependentFirewall

Class	StaticPart			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	Some parts/signals of the I-PDU may be the same regardless of the selector field. Such a part is called static part. The static part is optional.			
Base	ARObject, MultiplexedPart			
Aggregated by	MultiplexedIPdu.staticPart			
Attribute	Type	Mult.	Kind	Note
iPdu	ISignalIPdu	0..1	ref	Reference to a Com IPdu which is routed to the IPduM module and is combined to a multiplexedPdu.

Table A.925: StaticPart

Class	StaticSocketConnection			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::ServiceInstances			
Note	Definition of static SocketConnection between the Socket that is defined by the aggregating Socket Address and the remoteAddress.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	SocketAddress.staticSocketConnection			
Attribute	Type	Mult.	Kind	Note
iPduIdentifier	SoConIPduIdentifier	*	ref	Assignment of IPduIdentifiers that are transmitted over the static SocketConnection. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=iPduIdentifier.soConIPduIdentifier, iPduIdentifier.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	StaticSocketConnection			
remoteAddress	SocketAddress	0..1	ref	RemoteAddress of the static SocketConnection. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=remoteAddress.socketAddress, remoteAddress.variationPoint.shortLabel vh.latestBindingTime=postBuild
tcpConnectTimeout	TimeValue	0..1	attr	Specifies the time in seconds how long TCP connect attempts are repeated to reach SOAD_SOCON_ONLINE. This attribute is restricted to socket connection groups which are initiating a TCP connection and are under control of SoAd.
tcpRole	TcpRoleEnum	0..1	attr	Defines whether the local Address (that is aggregating the StaticSocketConnection) does a listen or a connect.

Table A.926: StaticSocketConnection

Class	Std			
Package	M2::MSR::Documentation::TextModel::InlineTextElements			
Note	This represents a reference to external standards.			
Base	<i>ARObject</i> , Referrable , <i>SingleLanguageReferrable</i>			
Aggregated by	MixedContentForParagraph.std			
Attribute	Type	Mult.	Kind	Note
date	DateTime	0..1	attr	This element specifies the release date of the external standard if applicable. Tags: xml.sequenceOffset=50
position	String	0..1	attr	This represents the reference to the relevant positions of a standard. Kept as a string. Tags: xml.sequenceOffset=70
state	String	0..1	attr	This represents version and state of a standard. Kept as a string. Tags: xml.sequenceOffset=40
subtitle	String	0..1	attr	This represents the subtitle of the standard. Tags: xml.sequenceOffset=30
url	Url	0..1	aggr	This represents the URL of the standard. Tags: xml.sequenceOffset=60

Table A.927: Std

Class	StructuredReq			
Package	M2::MSR::Documentation::BlockElements::RequirementsTracing			
Note	This represents a structured requirement. This is intended for a case where specific requirements for features are collected. Note that this can be rendered as a labeled list.			
Base	<i>ARObject</i> , <i>DocumentViewSelectable</i> , Identifiable , MultilanguageReferrable , <i>Paginateable</i> , Referrable , Traceable			
Aggregated by	DocumentationBlock.structuredReq			
Attribute	Type	Mult.	Kind	Note





Class	StructuredReq			
appliesTo	StandardNameEnum	*	attr	This attribute represents the platform the requirement is assigned to. Tags: xml.namePlural=APPLIES-TO-DEPENDENCIES xml.sequenceOffset=25
conflicts	DocumentationBlock	0..1	aggr	This represents an informal specification of conflicts. Tags: xml.sequenceOffset=40
date	DateTime	1	attr	This represents the date when the requirement was initiated. Tags: xml.sequenceOffset=5
dependencies	DocumentationBlock	0..1	aggr	This represents an informal specification of dependencies. Note that upstream tracing should be formalized in the property trace provided by the superclass Traceable. Tags: xml.sequenceOffset=30
description	DocumentationBlock	0..1	aggr	This represents the general description of the requirement. Tags: xml.sequenceOffset=10
importance	String	1	attr	This allows to represent the importance of the requirement. Tags: xml.sequenceOffset=8
issuedBy	String	1	attr	This represents the person, organization or authority which issued the requirement. Tags: xml.sequenceOffset=6
rationale	DocumentationBlock	0..1	aggr	This represents the rationale of the requirement. Tags: xml.sequenceOffset=20
remark	DocumentationBlock	0..1	aggr	This represents an informal remark. Note that this is not modeled as annotation, since these remark is still essential part of the requirement. Tags: xml.sequenceOffset=60
supportingMaterial	DocumentationBlock	0..1	aggr	This represents an informal specification of the supporting material. Tags: xml.sequenceOffset=50
testedItem	Traceable	*	ref	This association represents the ability to trace on the same specification level. This supports for example the of acceptance tests. Tags: xml.sequenceOffset=70
type	String	1	attr	This attribute allows to denote the type of requirement to denote for example is it an "enhancement", "new feature" etc. Tags: xml.sequenceOffset=7
useCase	DocumentationBlock	0..1	aggr	This describes the relevant use cases. Note that formal references to use cases should be done in the trace relation. Tags: xml.sequenceOffset=35

Table A.928: StructuredReq

Class	SubElementMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	This meta-class allows for the definition of mappings of elements of a composite data type.			
Base	ARObject			
Aggregated by	DataPrototypeMapping.subElementMapping			
Attribute	Type	Mult.	Kind	Note
firstElement	SubElementRef	0..1	aggr	This represents the first element referenced in the scope of the mapping. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=firstElement, firstElement.variation Point.shortLabel vh.latestBindingTime=preCompileTime
secondElement	SubElementRef	0..1	aggr	This represents the second element referenced in the scope of the mapping. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=secondElement, secondElement.variation Point.shortLabel vh.latestBindingTime=preCompileTime
textTable Mapping	TextTableMapping	0..2	aggr	This allows for the text-table translation of individual elements of a composite data type.

Table A.929: SubElementMapping

Class	SupervisedEntityNeeds			
Package	M2::AUTOSARTemplates::CommonStructure::ServiceNeeds			
Note	Specifies the abstract needs on the configuration of the Watchdog Manager for one specific Supervised Entity.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , ServiceNeeds			
Aggregated by	BswServiceDependency.serviceNeeds , SwcServiceDependency.serviceNeeds			
Attribute	Type	Mult.	Kind	Note
activateAtStart	Boolean	0..1	attr	true/false: supervision activation status of Supervised Entity shall be enabled/disabled at start.
checkpoints	SupervisedEntity CheckpointNeeds	*	ref	This reference indicates the checkpoints belonging to the Supervised Entity. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=checkpoints.supervisedEntityCheckpoint Needs, checkpoints.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
enable Deactivation	Boolean	0..1	attr	true: software-component shall be allowed to deactivate supervision of this SupervisedEntity false: software-component shall be not allowed to deactivate supervision of this SupervisedEntity
expectedAlive Cycle	TimeValue	0..1	attr	Expected cycle time of alive trigger of this Supervised Entity (in seconds).
maxAliveCycle	TimeValue	0..1	attr	Maximum cycle time of alive trigger of this Supervised Entity (in seconds).
minAliveCycle	TimeValue	0..1	attr	Minimum cycle time of alive trigger of this Supervised Entity (in seconds).





Class	SupervisedEntityNeeds			
toleratedFailedCycles	PositiveInteger	0..1	attr	<p>Number of consecutive failed alive cycles for this SupervisedEntity which shall be tolerated until the supervision status of the SupervisedEntity is set to WdGM_ALIVE_EXPIRED (see SWS WdgM for more details).</p> <p>Note that this value has to be recalculated with respect to the WdgM's own cycle time for ECU configuration.</p>

Table A.930: SupervisedEntityNeeds

Enumeration	SupportBufferLockingEnum
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::PortAPIOptions
Note	This enumeration represents the ability to define the buffer locking behavior.
Aggregated by	CommunicationBufferLocking.supportBufferLocking
Literal	Description
doesNotSupportBufferLocking	<p>Buffer locking is not supported.</p> <p>Tags: atp.EnumerationLiteralIndex=0</p>
supportsBufferLocking	<p>Buffer locking is supported.</p> <p>Tags: atp.EnumerationLiteralIndex=1</p>

Table A.931: SupportBufferLockingEnum

Class	SwAddrMethod			
Package	M2::MSR::DataDictionary::AuxillaryObjects			
Note	<p>Used to assign a common addressing method, e.g. common memory section, to data or code objects. These objects could actually live in different modules or components.</p> <p>Tags: atp.recommendedPackage=SwAddrMethods</p>			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
memoryAllocationKeywordPolicy	MemoryAllocationKeywordPolicyType	0..1	attr	Enumeration to specify the name pattern of the Memory Allocation Keyword.
option	Identifier	*	attr	<p>This attribute introduces the ability to specify further intended properties of the MemorySection in with the related objects shall be placed.</p> <p>These properties are handled as to be selected. The intended options are mentioned in the list.</p> <p>In the Memory Mapping configuration, this option list is used to determine an appropriate MemMapAddressing ModeSet.</p>





Class	SwAddrMethod			
section Initialization Policy	SectionInitializationPolicyType	0..1	attr	Specifies the expected initialization of the variables (inclusive those which are implementing VariableData Prototypes). Therefore this is an implementation constraint for initialization code of BSW modules (especially RTE) as well as the start-up code which initializes the memory segment to which the AutosarData Prototypes referring to the SwAddrMethod's are later on mapped. If the attribute is not defined it has the identical semantic as the attribute value "INIT"
sectionType	MemorySectionType	0..1	attr	Defines the type of memory sections which can be associated with this addressing method.

Table A.932: SwAddrMethod

Class	SwAxisCont			
Package	M2::MSR::CalibrationData::CalibrationValue			
Note	This represents the values for the axis of a compound primitive (curve, map). For standard and fix axes, SwAxisCont contains the values of the axis directly. The axis values of SwAxisCont with the category COM_AXIS, RES_AXIS are for display only. For editing and processing, only the values in the related GroupAxis are binding.			
Base	ARObject			
Aggregated by	ApplicationValueSpecification.swAxisCont			
Attribute	Type	Mult.	Kind	Note
category	CalprmAxisCategoryEnum	0..1	attr	This category specifies the particular axis types: <ul style="list-style-type: none"> • STD_AXIS • COM_AXIS • RES_AXIS (swArraysize necessary) Tags: xml.sequenceOffset=20
swArraysize	ValueList	0..1	aggr	For multidimensional compound primitives (curve, map ...) it is necessary to know the dimensions. They are specified using swArraySize. <ul style="list-style-type: none"> • RES_AXIS Tags: xml.sequenceOffset=70
swAxisIndex	AxisIndexType	0..1	attr	This property allows to explicitly assign the axis contents to a particular axis. It is specified by numbers where 1 corresponds to the x-axis. It is also possible to derive the axis association from the sequence of the parent. Tags: xml.sequenceOffset=50
swValuesPhys	SwValues	0..1	aggr	swValuesPhys represents the values in the physical domain. Tags: xml.sequenceOffset=80
unit	Unit	0..1	ref	This represents the physical unit of the provided values. Tags: xml.sequenceOffset=30
unitDisplay Name	SingleLanguageUnit Names	0..1	aggr	This represents the display name which is used for the physical unit of the axis. Tags: xml.sequenceOffset=40

Table A.933: SwAxisCont

Class	SwAxisGeneric			
Package	M2::MSR::DataDictionary::Axis			
Note	This meta-class defines a generic axis. In a generic axis the axispoints points are calculated in the ECU. The ECU is equipped with a fixed calculation algorithm. Parameters for the algorithm can be stored in the data component of the ECU. Therefore these parameters are specified in the data declaration, not in the calibration data.			
Base	ARObject			
Aggregated by	SwAxisIndividual.swAxisGeneric			
Attribute	Type	Mult.	Kind	Note
swAxisType	SwAxisType	0..1	ref	Associated axis calculation strategy. Tags: xml.sequenceOffset=20
swGenericAxisParam	SwGenericAxisParam	*	aggr	Specific parameter of a generic axis. Tags: xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=40 xml.typeElement=false xml.typeWrapperElement=false

Table A.934: SwAxisGeneric

Class	SwAxisGrouped			
Package	M2::MSR::DataDictionary::Axis			
Note	An SwAxisGrouped is an axis which is shared between multiple calibration parameters.			
Base	ARObject, SwCalprmAxisTypeProps			
Aggregated by	SwCalprmAxis.swCalprmAxisTypeProps			
Attribute	Type	Mult.	Kind	Note
sharedAxisType	ApplicationPrimitive DataType	0..1	ref	This is the datatype of the calibration parameter providing the shared axis.
swAxisIndex	AxisIndexType	0..1	attr	Describes which axis of the referenced calibration parameter provides the values for the group axis. The index satisfies the following convention: <ul style="list-style-type: none"> • 0 = value axis. in this case, the interpolation result of the referenced parameter is used as a base point index. • The index should only be specified if the parameter under swCalprm contains more than one axis. It is standard practice for the axis index of parameters with more than one axis, to be set to 1, if data has not been assigned to swAxisIndex. Tags: xml.sequenceOffset=20





Class	SwAxisGrouped			
swCalprmRef	SwCalprmRefProxy	1	aggr	<p>This property specifies the calibration parameter which serves as the input axis. In AUTOSAR, the type of the referenced Calibration parameter shall be compatible to the type specified by sharedAxisType.</p> <p>Please note that the multiplicity of this aggregation cannot be set to 0..1 based on the non-mainstream schema generation instructions defined at the aggregation.</p> <p>However, the multiplicity has to be factually considered 0..1 (i.e. a SwAxisGrouped that does not aggregate the role swCalprmRef is still valid according to the XML schema, depending on the use case documented in [constr_1015]).</p> <p>Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=30 xml.typeElement=false xml.typeWrapperElement=false</p>

Table A.935: SwAxisGrouped

Class	SwAxisIndividual			
Package	M2::MSR::DataDictionary::Axis			
Note	This meta-class describes an axis integrated into a parameter (field etc.). The integration makes this individual to each parameter. The so-called grouped axis represents the counterpart to this. It is conceived as an independent parameter (see class SwAxisGrouped).			
Base	<i>ARObject</i> , <i>SwCalprmAxisTypeProps</i>			
Aggregated by	SwCalprmAxis.swCalprmAxisTypeProps			
Attribute	Type	Mult.	Kind	Note
compuMethod	CompuMethod	0..1	ref	<p>This is the compuMethod which is expected for the axis. It is used in early stages if the particular input-value is not yet available.</p> <p>Tags: xml.sequenceOffset=30</p>
dataConstr	DataConstr	0..1	ref	<p>Refers to constraints, e.g. for plausibility checks.</p> <p>Tags: xml.sequenceOffset=80</p>
inputVariable Type	ApplicationPrimitive DataType	0..1	ref	<p>This is the datatype of the input value for the axis. This allows to define e.g. a type of curve, where the input value is finalized at the access point.</p>
swAxisGeneric	SwAxisGeneric	0..1	aggr	<p>this specifies the properties of a generic axis if applicable.</p> <p>Tags: xml.sequenceOffset=90</p>
swMaxAxis Points	Integer	0..1	attr	<p>Maximum number of base points contained in the axis of a map or curve.</p> <p>Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=60</p>
swMinAxis Points	Integer	0..1	attr	<p>Minimum number of base points contained in the axis of a map or curve.</p> <p>Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=70</p>





Class	SwAxisIndividual			
swVariableRef (ordered)	SwVariableRefProxy	*	aggr	<p>Refers to input variables of the axis. It is possible to specify more than one variable. Here the following is valid:</p> <ul style="list-style-type: none"> The variable with the highest priority shall be given first. It is used in the generation of the code and is also displayed first in the application system. All variables referenced shall be of the same physical nature. This is usually detected in that the conversion formulae affected refer back to the same SI-units. <p>In AUTOSAR this ensured by the constraint, that the referenced input variables shall use a type compatible to "inputVariableType".</p> <ul style="list-style-type: none"> This multiple referencing allows a base point distribution for more than one input variable to be used. One example of this are the temperature curves which can depend both on the induction air temperature and the engine temperature. <p>These variables can be displayed simultaneously by MCD systems (adjustment systems), enabling operating points to be shown in the curves.</p> <p>Tags: xml.roleElement=false xml.roleWrapperElement=true xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false</p>
unit	Unit	0..1	ref	<p>This represents the physical unit of the input value of the axis. It is provided to support the case that the particular input variable is not yet known.</p> <p>Tags: xml.sequenceOffset=40</p>

Table A.936: SwAxisIndividual

Class	SwBaseType			
Package	M2::MSR::AsamHdo::BaseTypes			
Note	<p>This meta-class represents a base type used within ECU software.</p> <p>Tags: atp.recommendedPackage=BaseTypes</p>			
Base	<p>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, BaseType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</p>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
-	-	-	-	-

Table A.937: SwBaseType

Enumeration	SwCalibrationAccessEnum			
Package	M2::MSR::DataDictionary::DataDefProperties			
Note	<p>Determines the access rights to a data object w.r.t. measurement and calibration.</p>			
Aggregated by	<p>ModeDeclarationGroupPrototype.swCalibrationAccess, SwCalprmAxis.swCalibrationAccess, SwDataDefProps.swCalibrationAccess</p>			
Literal	<i>Description</i>			





Enumeration	SwCalibrationAccessEnum
notAccessible	The element will not be accessible via MCD tools, i.e. will not appear in the ASAP file. Tags: atp.EnumerationLiteralIndex=0
readOnly	The element will only appear as read-only in an ASAP file. Tags: atp.EnumerationLiteralIndex=1
readWrite	The element will appear in the ASAP file with both read and write access. Tags: atp.EnumerationLiteralIndex=2

Table A.938: SwCalibrationAccessEnum

Class	SwCalprmAxis			
Package	M2::MSR::DataDictionary::CalibrationParameter			
Note	This element specifies an individual input parameter axis (abscissa).			
Base	ARObject			
Aggregated by	SwCalprmAxisSet.swCalprmAxis			
Attribute	Type	Mult.	Kind	Note
category	CalprmAxisCategory Enum	0..1	attr	This property specifies the category of a particular axis. Tags: xml.sequenceOffset=30
displayFormat	DisplayFormatString	0..1	attr	This property specifies how the axis values shall be displayed e.g. in documents or in measurement and calibration tools. Tags: xml.sequenceOffset=100
swAxisIndex	AxisIndexType	0..1	attr	This attribute specifies which axis is specified by the containing SwCalprmAxis. For example in a curve this is usually "1". In a map this is "1" or "2". Tags: xml.sequenceOffset=20
swCalibration Access	SwCalibrationAccess Enum	0..1	attr	Describes the applicability of parameters and variables. Tags: xml.sequenceOffset=90
swCalprmAxis TypeProps	SwCalprmAxisType Props	0..1	aggr	specific properties depending on the type of the axis. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=40 xml.typeElement=true xml.typeWrapperElement=false

Table A.939: SwCalprmAxis

Class	SwCalprmAxisSet			
Package	M2::MSR::DataDictionary::CalibrationParameter			
Note	This element specifies the input parameter axes (abscissas) of parameters (and variables, if these are used adaptively).			
Base	ARObject			
Aggregated by	SwDataDefProps.swCalprmAxisSet			
Attribute	Type	Mult.	Kind	Note





Class	SwCalprmAxisSet			
swCalprmAxis	SwCalprmAxis	*	aggr	One axis belonging to this SwCalprmAxisSet Tags: xml.roleElement=true xml.roleWrapperElement=false xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false

Table A.940: SwCalprmAxisSet

Class	SwCalprmRefProxy			
Package	M2::MSR::DataDictionary::DatadictionaryProxies			
Note	Wrapper class for different kinds of references to a calibration parameter.			
Base	<i>ARObject</i>			
Aggregated by	SwAxisGrouped.swCalprmRef , SwDataDependencyArgs.swCalprmRef			
Attribute	Type	Mult.	Kind	Note
arParameter	AutosarParameterRef	0..1	aggr	This represents a Parameter within AUTOSAR. Note that the Datatype of the referenced ParameterDataPrototype shall be an ApplicationDataType of category VALUE.
mcDataInstance	McDataInstance	0..1	ref	This reference is used in the McSupport file to express the final instance of group axis etc. It is not allowed to use this outside of an McDataInstance. The referenced mcDataInstance shall be originated from a ParameterDataPrototype.

Table A.941: SwCalprmRefProxy

Class	SwComponentPrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	Role of a software component within a composition.			
Base	<i>ARObject</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	AtpClassifier.atpFeature , CompositionSwComponentType.component			
Attribute	Type	Mult.	Kind	Note
type	SwComponentType	0..1	tref	Type of the instance. Stereotypes: isOfType

Table A.942: SwComponentPrototype

Class	SwComponentPrototypeAssignment			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	This meta-class is only required to allow for the variant modeling of an instanceRef.			
Base	<i>ARObject</i>			
Aggregated by	CpSoftwareCluster.swComponentAssignment			
Attribute	Type	Mult.	Kind	Note





Class	SwComponentPrototypeAssignment			
swComponent	SwComponentPrototype	0..1	iref	<p>hierarchical tree(s) of Software Components belonging to this CP Software Cluster. This reference is used to describe the belonging SWCs if the CP Software Cluster is described in the context of a System,</p> <p>InstanceRef implemented by: ComponentInSystem InstanceRef</p>

Table A.943: SwComponentPrototypeAssignment

Class	SwComponentType (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	Base class for AUTOSAR software components.			
Base	<i>ARElement, ARObject, AtpBlueprint, AtpBlueprintable, AtpClassifier, AtpType, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Subclasses	<i>AtomicSwComponentType, CompositionSwComponentType, ParameterSwComponentType</i>			
Aggregated by	<i>ARPackage.element</i>			
Attribute	Type	Mult.	Kind	Note
consistency Needs	ConsistencyNeeds	*	aggr	<p>This represents the collection of ConsistencyNeeds owned by the enclosing SwComponentType.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=consistencyNeeds.shortName, consistencyNeeds.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
port	PortPrototype	*	aggr	<p>The PortPrototypes through which this SwComponentType can communicate.</p> <p>The aggregation of PortPrototype is subject to variability with the purpose to support the conditional existence of PortPrototypes.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=port.shortName, port.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
portGroup	PortGroup	*	aggr	<p>A port group being part of this component.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=portGroup.shortName, portGroup.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
swcMapping Constraint	SwComponentMapping Constraints	*	ref	Reference to constraints that are valid for this SwComponentType.
swComponent Documentation	SwComponent Documentation	0..1	aggr	<p>This adds a documentation to the SwComponentType.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swComponentDocumentation, swComponentDocumentation.variationPoint.shortLabel vh.latestBindingTime=preCompileTime xml.sequenceOffset=-10</p>
unitGroup	UnitGroup	*	ref	This allows for the specification of which UnitGroups are relevant in the context of referencing SwComponentType.

Table A.944: SwComponentType

Class	SwConnector (abstract)			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Composition			
Note	The base class for connectors between ports. Connectors have to be identifiable to allow references from the system constraint template.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Subclasses	AssemblySwConnector , DelegationSwConnector , PassThroughSwConnector			
Aggregated by	AtpClassifier.atpFeature , CompositionSwComponentType.connector			
Attribute	Type	Mult.	Kind	Note
mapping	PortInterfaceMapping	0..1	ref	Reference to a PortInterfaceMapping specifying the mapping of unequal named PortInterface elements of the two different PortInterfaces typing the two PortPrototypes which are referenced by the ConnectorPrototype.

Table A.945: SwConnector

Class	«atpVariation» SwDataDefProps			
Package	M2::MSR::DataDictionary::DataDefProperties			
Note	<p>This class is a collection of properties relevant for data objects under various aspects. One could consider this class as a "pattern of inheritance by aggregation". The properties can be applied to all objects of all classes in which SwDataDefProps is aggregated.</p> <p>Note that not all of the attributes or associated elements are useful all of the time. Hence, the process definition (e.g. expressed with an OCL or a Document Control Instance MSR-DCI) has the task of implementing limitations.</p> <p>SwDataDefProps covers various aspects:</p> <ul style="list-style-type: none"> • Structure of the data element for calibration use cases: is it a single value, a curve, or a map, but also the recordLayouts which specify how such elements are mapped/converted to the DataTypes in the programming language (or in AUTOSAR). This is mainly expressed by properties like swRecordLayout and swCalprmAxisSet • Implementation aspects, mainly expressed by swImplPolicy, swVariableAccessImplPolicy, swAddr Method, swPointerTargetProps, baseType, implementationDataType and additionalNativeTypeQualifier • Access policy for the MCD system, mainly expressed by swCalibrationAccess • Semantics of the data element, mainly expressed by compuMethod and/or unit, dataConstr, invalid Value • Code generation policy provided by swRecordLayout <p>Tags: vh.latestBindingTime=codeGenerationTime</p>			
Base	ARObject			
Aggregated by	AutosarDataType.swDataDefProps , CompositeNetworkRepresentation.networkRepresentation , CppImplementationDataTypeElement.swDataDefProps , DataPrototype.swDataDefProps , DataPrototypeTransformationProps.networkRepresentationProps , DiagnosticDataElement.swDataDefProps , DiagnosticEnvDataElementCondition.swDataDefProps , DitArgument.networkRepresentation , FlatInstanceDescriptor.swDataDefProps , ImplementationDataTypeElement.swDataDefProps , InstantiationDataDefProps.swDataDefProps , ISignal.networkRepresentationProps , McDataInstance.resultingProperties , ParameterAccess.swDataDefProps , PerInstanceMemory.swDataDefProps , ReceiverComSpec.networkRepresentation , SecurityEventContextDataElement.networkRepresentation , SenderComSpec.networkRepresentation , SomeipDataPrototypeTransformationProps.networkRepresentation , SwPointerTargetProps.swDataDefProps , SwServiceArg.swDataDefProps , SwSystemconst.swDataDefProps , SystemSignal.physicalProps			
Attribute	Type	Mult.	Kind	Note





Class	«atpVariation» SwDataDefProps			
additionalNativeTypeQualifier	NativeDeclarationString	0..1	attr	This attribute is used to declare native qualifiers of the programming language which can neither be deduced from the baseType (e.g. because the data object describes a pointer) nor from other more abstract attributes. Examples are qualifiers like "volatile", "strict" or "enum" of the C-language. All such declarations have to be put into one string. Tags: xml.sequenceOffset=235
annotation	Annotation	*	aggr	This aggregation allows to add annotations (yellow pads ...) related to the current data object. Tags: xml.roleElement=true xml.roleWrapperElement=true xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false
baseType	SwBaseType	0..1	ref	Base type associated with the containing data object. Tags: xml.sequenceOffset=50
compuMethod	CompuMethod	0..1	ref	Computation method associated with the semantics of this data object. Tags: xml.sequenceOffset=180
dataConstr	DataConstr	0..1	ref	Data constraint for this data object. Tags: xml.sequenceOffset=190
displayFormat	DisplayFormatString	0..1	attr	This property describes how a number is to be rendered e.g. in documents or in a measurement and calibration system. Tags: xml.sequenceOffset=210
displayPresentation	DisplayPresentationEnum	0..1	attr	This attribute controls the presentation of the related data for measurement and calibration tools.
implementationDataType	AbstractImplementationDataType	0..1	ref	This association denotes the ImplementationDataType of a data declaration via its aggregated SwDataDefProps. It is used whenever a data declaration is not directly referring to a base type. Especially <ul style="list-style-type: none"> • redefinition of an ImplementationDataType via a "typedef" to another ImplementationDatatype • the target type of a pointer (see SwPointerTarget Props), if it does not refer to a base type directly • the data type of an array or record element within an ImplementationDataType, if it does not refer to a base type directly • the data type of an SwServiceArg, if it does not refer to a base type directly Tags: xml.sequenceOffset=215
invalidValue	ValueSpecification	0..1	aggr	Optional value to express invalidity of the actual data element. Tags: xml.sequenceOffset=255
stepSize	Float	0..1	attr	This attribute can be used to define a value which is added to or subtracted from the value of a DataPrototype when using up/down keys while calibrating.





Class	«atpVariation» SwDataDefProps			
swAddrMethod	SwAddrMethod	0..1	ref	Addressing method related to this data object. Via an association to the same SwAddrMethod it can be specified that several DataPrototypes shall be located in the same memory without already specifying the memory section itself. Tags: xml.sequenceOffset=30
swAlignment	AlignmentType	0..1	attr	The attribute describes the intended typical alignment of the DataPrototype. If the attribute is not defined the alignment is determined by the swBaseType size and the memoryAllocationKeywordPolicy of the referenced Sw AddrMethod. Tags: xml.sequenceOffset=33
swBit Representation	SwBitRepresentation	0..1	aggr	Description of the binary representation in case of a bit variable. Tags: xml.sequenceOffset=60
swCalibration Access	SwCalibrationAccess Enum	0..1	attr	Specifies the read or write access by MCD tools for this data object. Tags: xml.sequenceOffset=70
swCalprmAxis Set	SwCalprmAxisSet	0..1	aggr	This specifies the properties of the axes in case of a curve or map etc. This is mainly applicable to calibration parameters. Tags: xml.sequenceOffset=90
swComparison Variable	SwVariableRefProxy	*	aggr	Variables used for comparison in an MCD process. Tags: xml.sequenceOffset=170 xml.typeElement=false
swData Dependency	SwDataDependency	0..1	aggr	Describes how the value of the data object has to be calculated from the value of another data object (by the MCD system). Tags: xml.sequenceOffset=200
swHostVariable	SwVariableRefProxy	0..1	aggr	Contains a reference to a variable which serves as a host-variable for a bit variable. Only applicable to bit objects. Tags: xml.sequenceOffset=220 xml.typeElement=false
swImplPolicy	SwImplPolicyEnum	0..1	attr	Implementation policy for this data object. Tags: xml.sequenceOffset=230
swIntended Resolution	Numerical	0..1	attr	The purpose of this element is to describe the requested quantization of data objects early on in the design process. The resolution ultimately occurs via the conversion formula present (compuMethod), which specifies the transition from the physical world to the standardized world (and vice-versa) (here, "the slope per bit" is present implicitly in the conversion formula). In the case of a development phase without a fixed conversion formula, a pre-specification can occur through swIntendedResolution. The resolution is specified in the physical domain according to the property "unit". Tags: xml.sequenceOffset=240





Class	«atpVariation» SwDataDefProps			
swInterpolationMethod	Identifier	0..1	attr	This is a keyword identifying the mathematical method to be applied for interpolation. The keyword needs to be related to the interpolation routine which needs to be invoked. Tags: xml.sequenceOffset=250
swIsVirtual	Boolean	0..1	attr	This element distinguishes virtual objects. Virtual objects do not appear in the memory, their derivation is much more dependent on other objects and hence they shall have a swDataDependency . Tags: xml.sequenceOffset=260
swPointerTargetProps	SwPointerTargetProps	0..1	aggr	Specifies that the containing data object is a pointer to another data object. Tags: xml.sequenceOffset=280
swRecordLayout	SwRecordLayout	0..1	ref	Record layout for this data object. Tags: xml.sequenceOffset=290
swRefreshTiming	MultidimensionalTime	0..1	aggr	This element specifies the frequency in which the object involved shall be or is called or calculated. This timing can be collected from the task in which write access processes to the variable run. But this cannot be done by the MCD system. So this attribute can be used in an early phase to express the desired refresh timing and later on to specify the real refresh timing. Tags: xml.sequenceOffset=300
swTextProps	SwTextProps	0..1	aggr	the specific properties if the data object is a text object. Tags: xml.sequenceOffset=120
swValueBlockSize	Numerical	0..1	attr	This represents the size of a Value Block Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=80
swValueBlockSizeMult (ordered)	Numerical	*	attr	This attribute is used to specify the dimensions of a value block (VAL_BLK) for the case that that value block has more than one dimension. The dimensions given in this attribute are ordered such that the first entry represents the first dimension, the second entry represents the second dimension, and so on. For one-dimensional value blocks the attribute swValueBlockSize shall be used and this attribute shall not exist. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
unit	Unit	0..1	ref	Physical unit associated with the semantics of this data object. This attribute applies if no compuMethod is specified. If both units (this as well as via compuMethod) are specified the units shall be compatible. Tags: xml.sequenceOffset=350
valueAxisDataType	ApplicationPrimitiveDataType	0..1	ref	The referenced ApplicationPrimitiveDataType represents the primitive data type of the value axis within a compound primitive (e.g. curve, map). It supersedes CompuMethod, Unit, and BaseType. Tags: xml.sequenceOffset=355

Table A.946: SwDataDefProps

Class	SwGenericAxisParam			
Package	M2::MSR::DataDictionary::Axis			
Note	This meta-class describes a specific parameter of a generic axis. The name of the parameter is defined through a reference to a parameter type defined on a corresponding axis type. The value of the parameter is given here in case that it is not changeable during calibration. Example is shift / offset in a fixed axis.			
Base	ARObject			
Aggregated by	SwAxisGeneric.swGenericAxisParam			
Attribute	Type	Mult.	Kind	Note
swGenericAxisParamType	SwGenericAxisParamType	0..1	ref	Parameter type defined on a corresponding axis type. References can only be made to axis parameters types which are defined within the referenced axis type. Tags: xml.sequenceOffset=20
vf (ordered)	Numerical	*	attr	This attribute represents the value of the generic axis parameter. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.roleElement=true xml.roleWrapperElement=false xml.sequenceOffset=30 xml.typeElement=false

Table A.947: SwGenericAxisParam

Class	SwGenericAxisParamType			
Package	M2::MSR::DataDictionary::Axis			
Note	This meta-class describes a generic axis parameter type, namely: <ul style="list-style-type: none"> • Plausibility checks can be specified via dataConstr. • Textual description (desc), as a formal description is not of any use, due to the large variety of possibilities. • If this parameter contains structures, these can be simulated through the recursive use of SwGenericAxisParamTypes. 			
Base	ARObject, <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	SwAxisType.swGenericAxisParamType			
Attribute	Type	Mult.	Kind	Note
dataConstr	DataConstr	0..1	ref	This reference denoted data constraints applicable to the generic axis parameter. Tags: xml.sequenceOffset=20

Table A.948: SwGenericAxisParamType

Enumeration	SwImplPolicyEnum
Package	M2::MSR::DataDictionary::DataDefProperties
Note	Specifies the implementation strategy with respect to consistency mechanisms of variables.
Aggregated by	BswInternalTriggeringPoint.swImplPolicy, InternalTriggeringPoint.swImplPolicy, SwDataDefProps.swImplPolicy, Trigger.swImplPolicy
Literal	Description





Enumeration	SwImplPolicyEnum
const	forced implementation such that the running software within the ECU shall not modify it. For example implemented with the "const" modifier in C. This can be applied for parameters (not for those in NVRAM) as well as argument data prototypes. Tags: atp.EnumerationLiteralIndex=0
fixed	This data element is fixed. In particular this indicates, that it might also be implemented e.g. as in place data, (#DEFINE). Tags: atp.EnumerationLiteralIndex=1
measurementPoint	The data element is created for measurement purposes only. The data element is never read directly within the ECU software. In contrast to a "standard" data element in an unconnected provide port is, this unconnection is guaranteed for measurementPoint data elements. Tags: atp.EnumerationLiteralIndex=2
queued	The content of the data element is queued and the data element has 'event' semantics, i.e. data elements are stored in a queue and all data elements are processed in 'first in first out' order. The queuing is intended to be implemented by RTE Generator. This value is not applicable for parameters. Tags: atp.EnumerationLiteralIndex=3
standard	This is applicable for all kinds of data elements. For variable data prototypes the 'last is best' semantics applies. For parameter there is no specific implementation directive. Tags: atp.EnumerationLiteralIndex=4

Table A.949: SwImplPolicyEnum

Class	SwPointerTargetProps			
Package	M2::MSR::DataDictionary::DataDefProperties			
Note	<p>This element defines, that the data object (which is specified by the aggregating element) contains a reference to another data object or to a function in the CPU code. This corresponds to a pointer in the C-language.</p> <p>The attributes of this element describe the category and the detailed properties of the target which is either a data description or a function signature.</p>			
Base	ARObject			
Aggregated by	SwDataDefProps.swPointerTargetProps			
Attribute	Type	Mult.	Kind	Note
functionPointerSignature	BswModuleEntry	0..1	ref	<p>The referenced BswModuleEntry serves as the signature of a function pointer definition. Primary use case: function pointer passed as argument to other function.</p> <p>Tags: xml.sequenceOffset=40</p>
swDataDefProps	SwDataDefProps	0..1	aggr	<p>The properties of the target data type.</p> <p>Tags: xml.sequenceOffset=30</p>
targetCategory	Identifier	0..1	attr	<p>This specifies the category of the target:</p> <ul style="list-style-type: none"> • In case of a data pointer, it shall specify the category of the referenced data. • In case of a function pointer, it could be used to denote the category of the referenced BswModuleEntry. <p>Tags: xml.sequenceOffset=5</p>

Table A.950: SwPointerTargetProps

Class	SwRecordLayout			
Package	M2::MSR::DataDictionary::RecordLayout			
Note	<p>Defines how the data objects (variables, calibration parameters etc.) are to be stored in the ECU memory. As an example, this definition specifies the sequence of axis points in the ECU memory. Iterations through axis values are stored within the sub-elements swRecordLayoutGroup.</p> <p>Tags: atp.recommendedPackage=SwRecordLayouts</p>			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
swRecordLayoutGroup	SwRecordLayoutGroup	0..1	aggr	<p>This is the top level record layout group.</p> <p>Tags: xml.roleElement=true xml.roleWrapperElement=false xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false</p>

Table A.951: SwRecordLayout

Class	SwServiceArg			
Package	M2::MSR::DataDictionary::ServiceProcessTask			
Note	<p>Specifies the properties of a data object exchanged during the call of an SwService, e.g. an argument or a return value.</p> <p>The SwServiceArg can also be used in the argument list of a C-macro. For this purpose the category shall be set to "MACRO". A reference to implementationDataType can optional be added if the actual argument has an implementationDataType.</p>			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, Referrable</i>			
Aggregated by	BswModuleEntry.argument, BswModuleEntry.returnType			
Attribute	Type	Mult.	Kind	Note
direction	ArgumentDirectionEnum	0..1	attr	<p>Specifies the direction of the data transfer. The direction shall indicate the direction of the actual information that is being consumed by the caller and/or the callee, not the direction of formal arguments in C.</p> <p>The attribute is optional for backwards compatibility reasons. For example, if a pointer is used to pass a memory address for the expected result, the direction shall be "out". If a pointer is used to pass a memory address with content to be read by the callee, its direction shall be "in".</p> <p>Tags: xml.sequenceOffset=10</p>
swArraysSize	ValueList	0..1	aggr	<p>This turns the argument of the service to an array.</p> <p>Tags: xml.sequenceOffset=20</p>
swDataDefProps	SwDataDefProps	0..1	aggr	<p>Data properties of this SwServiceArg.</p> <p>Tags: xml.sequenceOffset=30</p>

Table A.952: SwServiceArg

Class	SwSystemconst			
Package	M2::MSR::DataDictionary::SystemConstant			
Note	<p>This element defines a system constant which serves an input to select a particular variation point. In particular a system constant serves as an operand of the binding function (swSyscond) in a Variation point.</p> <p>Note that the binding process can only happen if a value was assigned to to the referenced system constants.</p> <p>Tags: atp.recommendedPackage=SwSystemconst</p>			
Base	<i>ARElement, ARObject, AtpDefinition, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
swDataDef Props	SwDataDefProps	0..1	aggr	<p>This denotes the data definition properties of the system constant. This supports to express the limits and optionally a conversion within the internal to physical values by a compu method.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=swDataDefProps xml.sequenceOffset=40</p>

Table A.953: SwSystemconst

Class	SwSystemconstValue			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling			
Note	This meta-class assigns a particular value to a system constant.			
Base	ARObject			
Aggregated by	SwSystemconstantValueSet.swSystemconstantValue			
Attribute	Type	Mult.	Kind	Note
annotation	Annotation	*	aggr	<p>This provides the ability to add information why the value is set like it is.</p> <p>Tags: xml.sequenceOffset=30</p>
swSystemconst	SwSystemconst	1	ref	<p>This is the system constant to which the value applies.</p> <p>Tags: xml.sequenceOffset=10</p>
value	Numerical	1	attr	<p>This is the particular value of a system constant. It is specified as Numerical. Further restrictions may apply by the definition of the system constant.</p> <p>The value attribute defines the internal value of the Sw Systemconst as it is processed in the Formula Language.</p> <p>Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=20</p>

Table A.954: SwSystemconstValue

Class	SwSystemconstantValueSet			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling			
Note	<p>This meta-class represents the ability to specify a set of system constant values.</p> <p>Tags: atp.recommendedPackage=SwSystemconstantValueSets</p>			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			





Class	SwSystemconstantValueSet			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
sw Systemconstant Value	SwSystemconstValue	*	aggr	This is one particular value of a system constant.

Table A.955: SwSystemconstantValueSet

Class	SwTextProps			
Package	M2::MSR::DataDictionary::DataDefProperties			
Note	This meta-class expresses particular properties applicable to strings in variables or calibration parameters.			
Base	ARObject			
Aggregated by	SwDataDefProps.swTextProps			
Attribute	Type	Mult.	Kind	Note
arraySize Semantics	ArraySizeSemantics Enum	0..1	attr	This attribute controls the semantics of the arraysize for the array representing the string in an Implementation DataType. It is there to support a safe conversion between ApplicationDatatype and ImplementationDatatype, even for variable length strings as required e.g. for Support of SAE J1939.
baseType	SwBaseType	0..1	ref	This is the base type of one character in the string. In particular this baseType denotes the intended encoding of the characters in the string on level of ApplicationData Type. Tags: xml.sequenceOffset=30
swFillCharacter	Integer	0..1	attr	Filler character for text parameter to pad up to the maximum length swMaxTextSize. The value will be interpreted according to the encoding specified in the associated base type of the data object, e.g. 0x30 (hex) represents the ASCII character zero as filler character and 0 (dec) represents an end of string as filler character. The usage of the fill character depends on the arraySize Semantics. Tags: xml.sequenceOffset=40
swMaxTextSize	Integer	0..1	attr	Specifies the maximum text size in characters. Note the size in bytes depends on the encoding in the corresponding baseType. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=20

Table A.956: SwTextProps

Class	SwValueCont			
Package	M2::MSR::CalibrationData::CalibrationValue			
Note	This metaclass represents the content of one particular SwInstance.			
Base	ARObject			





Class				
SwValueCont				
Aggregated by				
ApplicationValueSpecification.swValueCont				
Attribute	Type	Mult.	Kind	Note
swArraysizes	ValueList	0..1	aggr	This attribute defines the size of each dimension for compound primitives CURVE, MAP, CUBOID, CUBE_4, CUBE_5, COM_AXIS, RES_AXIS, VAL_BLK. For each dimension one value has to be defined, e.g. one in case of COM_AXIS and two or more in case of MAP. Tags: xml.sequenceOffset=40
swValuesPhys	SwValues	0..1	aggr	swValuesPhys represents the values in the physical domain. Tags: xml.sequenceOffset=50
unit	Unit	0..1	ref	This represents the physical unit of the provided values. Tags: xml.sequenceOffset=20
unitDisplay Name	SingleLanguageUnit Names	0..1	aggr	This specifies how the physical units of the current value set shall be displayed in documents or in user interfaces of tools. Tags: xml.sequenceOffset=30

Table A.957: SwValueCont

Class				
«atpMixed» SwValues				
Package				
M2::MSR::CalibrationData::CalibrationValue				
Note				
This meta-class represents a list of values. These values can either be the input values of a curve (abscissa values) or the associated values (ordinate values). For multidimensional structures, the values are ordered such that they follow the memory layout, see [TPS_SWCT_01882] In particular for maps and cuboids etc. the resulting long value list can be subsectioned using Value Group. But the processing needs to be done as if vg is not there. Note that numerical values and textual values should not be mixed.				
Base				
ARObject				
Aggregated by				
SwAxisCont.swValuesPhys, SwValueCont.swValuesPhys, ValueGroup.vgContents				
Attribute	Type	Mult.	Kind	Note
v	Numerical	0..1	attr	This is a non variant Value. It is provided for sake of Compatibility to ASAM CDF. Tags: xml.sequenceOffset=40
vf	Numerical	0..1	attr	This allows to specify the value as VariationPoint. It is distinguished to non variant for sake of compatibility to ASAM CDF 2.0. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.sequenceOffset=20
vg	ValueGroup	0..1	aggr	This allows to have intersections in the values in order to support specific rendering (eg. using stylesheets). For tools it is important that the v values are always processed in the same (flattened) order and the tool is able to interpret it without respecting vg. Tags: xml.sequenceOffset=50





Class	«atpMixed» SwValues			
vt	VerbatimString	0..1	attr	This represents the values of textual data elements (Strings). Note that vt uses the to separate the values for the different bitfield masks in case that the semantics of the related DataPrototype is described by means of a BITFIELD_TEXTTABLE in the associated CompuMethod. Tags: xml.sequenceOffset=30
vtf	NumericalOrText	0..1	aggr	This aggregation represents the ability to provide a value that is either numerical or text which existence is subject to variability. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.958: SwValues

Class	SwVariableRefProxy			
Package	M2::MSR::DataDictionary::DatadictionaryProxies			
Note	Proxy class for several kinds of references to a variable.			
Base	ARObject			
Aggregated by	SwAxisIndividual.swVariableRef, SwDataDefProps.swComparisonVariable, SwDataDefProps.swHostVariable, SwDataDependencyArgs.swVariable			
Attribute	Type	Mult.	Kind	Note
autosarVariable	AutosarVariableRef	0..1	aggr	This represents the reference to a Variable in an Autosar system. Note that the target of the reference within AutosarVariableRef shall be typed by a primitive data type
mcDataInstanceVar	McDataInstance	0..1	ref	This reference is used in the McSupport file to express the final instance of input values etc. It is not allowed to use this outside of an McDataInstance. The referenced mcDataInstance shall be originated from a VariableDataPrototype.

Table A.959: SwVariableRefProxy

Class	SwcBswMapping			
Package	M2::AUTOSARTemplates::CommonStructure::SwcBswMapping			
Note	Maps an SwcInternalBehavior to an BswInternalBehavior. This is required to coordinate the API generation and the scheduling for AUTOSAR Service Components, ECU Abstraction Components and Complex Driver Components by the RTE and the BSW scheduling mechanisms. Tags: atp.recommendedPackage=SwcBswMappings			
Base	ARElement, ARObject, AtpClassifier, AtpFeature, AtpStructureElement, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element, AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
bswBehavior	BswInternalBehavior	0..1	ref	The mapped BswInternalBehavior
runnableMapping	SwcBswRunnableMapping	*	aggr	A mapping between a pair of SWC and BSW runnables. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=runnableMapping, runnableMapping.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
swcBehavior	SwcInternalBehavior	0..1	ref	The mapped SwcInternalBehavior.





Class	SwcBswMapping			
synchronized ModeGroup	SwcBswSynchronized ModeGroupPrototype	*	aggr	A pair of SWC and BSW mode group prototypes to be synchronized by the scheduler. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=synchronizedModeGroup, synchronized ModeGroup.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
synchronized Trigger	SwcBswSynchronized Trigger	*	aggr	A pair of SWC and BSW Triggers to be synchronized by the scheduler. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=synchronizedTrigger, synchronized Trigger.variationPoint.shortLabel vh.latestBindingTime=preCompileTime

Table A.960: SwcBswMapping

Class	SwcBswRunnableMapping			
Package	M2::AUTOSARTemplates::CommonStructure::SwcBswMapping			
Note	Maps a BswModuleEntity to a RunnableEntity if it is implemented as part of a BSW module (in the case of an AUTOSAR Service, a Complex Driver or an ECU Abstraction). The mapping can be used by a tool to find relevant information on the behavior, e.g. whether the bswEntity shall be running in interrupt context.			
Base	ARObject			
Aggregated by	SwcBswMapping.runnableMapping			
Attribute	Type	Mult.	Kind	Note
bswEntity	BswModuleEntity	0..1	ref	The mapped BswModuleEntity
swcRunnable	RunnableEntity	0..1	ref	The mapped SWC runnable.

Table A.961: SwcBswRunnableMapping

Class	SwcBswSynchronizedModeGroupPrototype			
Package	M2::AUTOSARTemplates::CommonStructure::SwcBswMapping			
Note	Synchronizes a mode group provided by a component via a port with a mode group provided by a BSW module or cluster.			
Base	ARObject			
Aggregated by	SwcBswMapping.synchronizedModeGroup			
Attribute	Type	Mult.	Kind	Note
bswModeGroup	ModeDeclarationGroup Prototype	0..1	ref	The BSW mode group prototype.
swcModeGroup	ModeDeclarationGroup Prototype	0..1	iref	The SWC mode group prototype provided by a particular port. InstanceRef implemented by: PModeGroupInAtomic SwcInstanceRef

Table A.962: SwcBswSynchronizedModeGroupPrototype

Class	SwcBswSynchronizedTrigger			
Package	M2::AUTOSARTemplates::CommonStructure::SwcBswMapping			
Note	Synchronizes a Trigger provided by a component via a port with a Trigger provided by a BSW module or cluster.			
Base	ARObject			
Aggregated by	SwcBswMapping.synchronizedTrigger			
Attribute	Type	Mult.	Kind	Note
bswTrigger	Trigger	0..1	ref	The BSW Trigger.
swcTrigger	Trigger	0..1	iref	The SWC Trigger provided by a particular port. InstanceRef implemented by: PTriggerInAtomicSwcTypeInstanceRef

Table A.963: SwcBswSynchronizedTrigger

Class	SwcExclusiveAreaPolicy			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior			
Note	Options how to generate the ExclusiveArea related APIs. If no SwcExclusiveAreaPolicy is specified for an ExclusiveArea the default values apply.			
Base	ARObject			
Aggregated by	SwcInternalBehavior.exclusiveAreaPolicy			
Attribute	Type	Mult.	Kind	Note
apiPrinciple	ApiPrincipleEnum	0..1	attr	Specifies for this ExclusiveArea if either one common set of Enter and Exit APIs for the whole software component is requested from the Rte or if the set of Enter and Exit APIs is expected per RunnableEntity. The default value is "common".
exclusiveArea	ExclusiveArea	0..1	ref	This reference represents the ExclusiveArea for which the policy applies.

Table A.964: SwcExclusiveAreaPolicy

Class	SwcImplementation			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcImplementation			
Note	This meta-class represents a specialization of the general Implementation meta-class with respect to the usage in application software. Tags: atp.recommendedPackage=SwcImplementations			
Base	ARElement, ARObject, CollectableElement, Identifiable , Implementation , MultilanguageReferrable , PackageableElement , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
behavior	SwcInternalBehavior	0..1	ref	The internal behavior implemented by this Implementation.





Class	SwcImplementation			
perInstanceMemorySize	PerInstanceMemorySize	*	aggr	<p>Allows a definition of the size of the per-instance memory for this implementation. The aggregation of PerInstanceMemorySize is subject to variability with the purpose to support variability in the software components implementations. Typically different algorithms in the implementation are requiring different number of memory objects, in this case PerInstanceMemory.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=perInstanceMemorySize, perInstanceMemorySize.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
requiredRTEVendor	String	0..1	attr	<p>Identify a specific RTE vendor. This information is potentially important at the time of integrating (in particular: linking) the application code with the RTE. The semantics is that (if the association exists) the corresponding code has been created to fit to the vendor-mode RTE provided by this specific vendor. Attempting to integrate the code with another RTE generated in vendor mode is in general not possible.</p>

Table A.965: SwcImplementation

Class	SwcInternalBehavior			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior			
Note	The SwcInternalBehavior of an AtomicSwComponentType describes the relevant aspects of the software-component with respect to the RTE, i.e. the RunnableEntities and the RTEEvents they respond to.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , InternalBehavior , MultilanguageReferrable , Referrable			
Aggregated by	AtomicSwComponentType.internalBehavior , AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
arTypedPerInstanceMemory	VariableDataPrototype	*	aggr	<p>Defines an AUTOSAR typed memory-block that needs to be available for each instance of the SW-component.</p> <p>This is typically only useful if supportsMultipleInstantiation is set to "true" or if the component defines NVRAM access via permanent blocks.</p> <p>The aggregation of arTypedPerInstanceMemory is subject to variability with the purpose to support variability in the software component's implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=arTypedPerInstanceMemory.shortName, arTypedPerInstanceMemory.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	SwcInternalBehavior			
event	RTEEvent	*	aggr	<p>This is a RTEEvent specified for the particular Swc InternalBehavior.</p> <p>The aggregation of RTEEvent is subject to variability with the purpose to support the conditional existence of RTE events. Note: the number of RTE events might vary due to the conditional existence of PortPrototypes using Data ReceivedEvents or due to different scheduling needs of algorithms.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=event.shortName, event.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
exclusiveArea Policy	SwcExclusiveArea Policy	*	aggr	<p>Options how to generate the ExclusiveArea related APIs. When no SwcExclusiveAreaPolicy is specified for an ExclusiveArea the default values apply.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=exclusiveAreaPolicy, exclusiveArea Policy.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
explicitInter Runnable Variable	VariableDataPrototype	*	aggr	<p>Implement state message semantics for establishing communication among runnables of the same component. The aggregation of explicitInterRunnable Variable is subject to variability with the purpose to support variability in the software components implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=explicitInterRunnableVariable.shortName, explicitInterRunnableVariable.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
implicitInter Runnable Variable	VariableDataPrototype	*	aggr	<p>Implement state message semantics for establishing communication among runnables of the same component. The aggregation of implicitInterRunnable Variable is subject to variability with the purpose to support variability in the software components implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=implicitInterRunnableVariable.shortName, implicitInterRunnableVariable.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
includedData TypeSet	IncludedDataTypeSet	*	aggr	<p>The includedDataTypeSet is used by a software component for its implementation.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=includedDataTypeSet</p>
includedMode Declaration GroupSet	IncludedMode DeclarationGroupSet	*	aggr	<p>This aggregation represents the included Mode DeclarationGroups</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=includedModeDeclarationGroupSet</p>





Class	SwcInternalBehavior			
instantiationDataDefProps	InstantiationDataDefProps	*	aggr	<p>The purpose of this is that within the context of a given SwComponentType some data def properties of individual instantiations can be modified. The aggregation of InstantiationDataDefProps is subject to variability with the purpose to support the conditional existence of Port Prototypes and component local memories like "per InstanceParameter" or "arTypedPerInstanceMemory".</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=instantiationDataDefProps, instantiationDataDefProps.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
perInstanceMemory	PerInstanceMemory	*	aggr	<p>Defines a per-instance memory object needed by this software component. The aggregation of PerInstanceMemory is subject to variability with the purpose to support variability in the software components implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=perInstanceMemory.shortName, perInstanceMemory.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
perInstanceParameter	ParameterDataPrototype	*	aggr	<p>Defines parameter(s) or characteristic value(s) that needs to be available for each instance of the software-component. This is typically only useful if supportsMultipleInstantiation is set to "true". The aggregation of perInstanceParameter is subject to variability with the purpose to support variability in the software components implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=perInstanceParameter.shortName, perInstanceParameter.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
portAPIOption	PortAPIOption	*	aggr	<p>Options for generating the signature of port-related calls from a runnable to the RTE and vice versa. The aggregation of PortPrototypes is subject to variability with the purpose to support the conditional existence of ports.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=portAPIOption, portAPIOption.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>





Class	SwcInternalBehavior			
runnable	RunnableEntity	*	aggr	<p>This is a RunnableEntity specified for the particular Swc InternalBehavior.</p> <p>The aggregation of RunnableEntity is subject to variability with the purpose to support the conditional existence of RunnableEntities. Note: the number of RunnableEntities might vary due to the conditional existence of Port Prototypes using DataReceivedEvents or due to different scheduling needs of algorithms.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=runnable.shortName, runnable.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
service Dependency	SwcService Dependency	*	aggr	<p>Defines the requirements on AUTOSAR Services for a particular item.</p> <p>The aggregation of SwcServiceDependency is subject to variability with the purpose to support the conditional existence of ports as well as the conditional existence of ServiceNeeds.</p> <p>The SwcServiceDependency owned by an SwcInternal Behavior can be located in a different physical file in order to support that SwcServiceDependency might be provided in later development steps or even by different expert domain (e.g OBD expert for Obd related Service Needs) tools. Therefore the aggregation is <<atp Splitable>>.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=serviceDependency.shortName, serviceDependency.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
shared Parameter	ParameterData Prototype	*	aggr	<p>Defines parameter(s) or characteristic value(s) shared between SwComponentPrototypes of the same Sw ComponentType The aggregation of sharedParameter is subject to variability with the purpose to support variability in the software components implementations. Typically different algorithms in the implementation are requiring different number of memory objects.</p> <p>Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=sharedParameter.shortName, sharedParameter.variationPoint.shortLabel vh.latestBindingTime=preCompileTime</p>
supports Multiple Instantiation	Boolean	0..1	attr	<p>Indicate whether the corresponding software-component can be multiply instantiated on one ECU. In this case the attribute will result in an appropriate component API on programming language level (with or without instance handle).</p>
variationPoint Proxy	VariationPointProxy	*	aggr	<p>Proxy of a variation points in the C/C++ implementation.</p> <p>Stereotypes: atpSplitable Tags: atp.Splitkey=variationPointProxy.shortName</p>

Table A.966: SwcInternalBehavior

Class	SwcModeManagerErrorEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when an error occurred during the handling of the referenced ModeDeclarationGroup Prototype.			
Base	<i>ARObject, AbstractEvent, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, Multilanguage Referrable, RTEEvent, Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature, SwcInternalBehavior.event</i>			
Attribute	Type	Mult.	Kind	Note
modeGroup	ModeDeclarationGroup Prototype	0..1	iref	This represents the ModeDeclarationGroupPrototype for which this SwcModeManagerErrorEvent is raised in case of an error. InstanceRef implemented by: PModeGroupInAtomic SwcInstanceRef

Table A.967: SwcModeManagerErrorEvent

Class	SwcModeSwitchEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when the specified mode change occurs.			
Base	<i>ARObject, AbstractEvent, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, Multilanguage Referrable, RTEEvent, Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature, SwcInternalBehavior.event</i>			
Attribute	Type	Mult.	Kind	Note
activation	ModeActivationKind	0..1	attr	Specifies if the event is raised on entering or exiting a specific mode or is raised on the transition between two modes.
mode (ordered)	ModeDeclaration	0..2	iref	The referenced mode or the transition between two modes raises this SwcModeSwitchEvent. InstanceRef implemented by: RModeInAtomicSwc InstanceRef

Table A.968: SwcModeSwitchEvent

Class	SwcServiceDependency			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ServiceMapping			
Note	Specialization of ServiceDependency in the context of an SwcInternalBehavior. It allows to associate ports, port groups and (in special cases) data defined for an atomic software component to a given ServiceNeeds element.			
Base	<i>ARObject, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, Referrable, ServiceDependency</i>			
Aggregated by	<i>AdaptiveSwcInternalBehavior.serviceDependency, AtpClassifier.atpFeature, SwcInternalBehavior.serviceDependency</i>			
Attribute	Type	Mult.	Kind	Note
assignedData	RoleBasedData Assignment	*	aggr	Defines the role of an associated data object of the same component. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=assignedData, assignedData.variation Point.shortLabel vh.latestBindingTime=preCompileTime





Class	SwcServiceDependency			
assignedPort	RoleBasedPortAssignment	*	aggr	Defines the role of an associated port of the same component. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=assignedPort, assignedPort.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
representedPortGroup	PortGroup	0..1	ref	This reference specifies an association between the ServiceNeeds and a PortGroup, for example to request a communication mode which applies for communication via these ports. The referred PortGroup shall be local to this atomic SWC, but via the links between the Port Groups, a tool can evaluate this information such that all the ports linked via this port group on the same ECU can be found.
serviceNeeds	ServiceNeeds	0..1	aggr	The associated ServiceNeeds.

Table A.969: SwcServiceDependency

Class	SwcToApplicationPartitionMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping			
Note	Allows to map a given SwComponentPrototype to a formally defined partition at a point in time when the corresponding EcuInstance is not yet known or defined.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	CpSoftwareClusterMappingSet.swcToApplicationPartitionMapping, SwComponentMappingConstraints.swcToApplicationPartitionMapping, SystemMapping.swcToApplicationPartitionMapping			
Attribute	Type	Mult.	Kind	Note
applicationPartition	ApplicationPartition	0..1	ref	Reference to an ApplicationPartition to which a SwComponentPrototype is mapped.
swComponentPrototype	SwComponentPrototype	0..1	iref	References to the software component instances that are mapped to the referenced ApplicationPartition. If the component prototype referenced is a composition, this indicates that all atomic software components within the composition are mapped to the ApplicationPartition. If there is additionally a mapping of some SwComponentPrototype INSIDE the Composition to another ApplicationPartition the inner mapping overrides the outer mapping. InstanceRef implemented by: ComponentInSystemInstanceRef

Table A.970: SwcToApplicationPartitionMapping

Class	SwcToEcuMapping
Package	M2::AUTOSARTemplates::SystemTemplate::SWmapping
Note	This meta-class is used: <ul style="list-style-type: none"> to map SwComponentPrototypes to a specific ECU Instance unit, optionally to map SwComponentPrototypes to a HwElement with category ProcessingUnit, optionally to map SwComponentPrototypes typed by SensorActuatorSwComponentType to a HwElement with category SensorActuator. For each combination of ECUInstance and the optional ProcessingUnit and the optional SensorActuator only one SwcToEcuMapping shall be used.





Class		SwcToEcuMapping		
Base		<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>		
Aggregated by		SystemMapping.swMapping		
Attribute	Type	Mult.	Kind	Note
component	SwComponent Prototype	*	iref	References to the software component instances that are mapped to the referenced ECUInstance. If the component prototype referenced is a composition, this indicates that all atomic software components within the composition are mapped to the ECU. If there is additionally a mapping of some SwComponent Prototype INSIDE the Composition to another ECU Instance the inner mapping overrides the outer mapping. InstanceRef implemented by: ComponentInSystem InstanceRef
controlledHw Element	HwElement	0..1	ref	Optional mapping of SwComponentPrototypes that are typed by SensorActuatorSwComponentType to a Hw Element with category SensorActuator.
ecuInstance	EcuInstance	0..1	ref	Reference to a specific ECU Instance description.
processingUnit	HwElement	0..1	ref	Optional mapping of software components to individual microcontroller cores residing in one ECU. A microcontroller core is described in the ECU Resource Template by the HwElement of HwCategory Processing Unit.

Table A.971: SwcToEcuMapping

Class		SwcToImplMapping		
Package		M2::AUTOSARTemplates::SystemTemplate::SWmapping		
Note		Map instances of an AtomicSwComponentType to a specific Implementation.		
Base		<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>		
Aggregated by		SystemMapping.swImplMapping		
Attribute	Type	Mult.	Kind	Note
component	SwComponent Prototype	*	iref	Reference to the software component instances that are being mapped to the specified Implementation. The targeted SwComponentPrototype needs be of the Atomic SwComponentType being implemented by the referenced Implementation. InstanceRef implemented by: ComponentInSystem InstanceRef
component Implementation	SwImplementation	0..1	ref	Reference to a specific Implementation description. Implementation to be used by the specified SW component instance. This allows to achieve more precise estimates for the resource consumption that results from mapping the instance of an atomic SW component onto an ECU.

Table A.972: SwcToImplMapping

Class	SwcToSwcOperationArguments			
Package	M2::AUTOSARTemplates::SystemTemplate::SignalPaths			
Note	The SwcToSwcOperationArguments describes the information (client server operation arguments, plus the operation identification, if required) that are exchanged between two SW Components from exactly one client to one server, or from one server back to one client. The direction attribute defines which direction is described. If direction == IN, all arguments sent from the client to the server are described by the SwcToSwcOperationArguments, in direction == OUT, it's the arguments sent back from server to client.			
Base	ARObject			
Aggregated by	CommonSignalPath.operation, ForbiddenSignalPath.operation , PermissibleSignalPath.operation , SeparateSignalPath.operation			
Attribute	Type	Mult.	Kind	Note
direction	SwcToSwcOperationArgumentsDirectionEnum	0..1	attr	Direction addressed by this SwcToSwcClientServer Operation element.
operation	ClientServerOperation	*	iref	Reference to the operation at the client and at the server side whose arguments are described by SwcToSwcOperationArguments. The two ports referenced shall be connected by a connector in the software component description. InstanceRef implemented by: OperationInSystemInstanceRef

Table A.973: SwcToSwcOperationArguments

Class	SwcToSwcSignal			
Package	M2::AUTOSARTemplates::SystemTemplate::SignalPaths			
Note	The SwcToSwcSignal describes the information (data element) that is exchanged between two SW Components. On the SWC Level it is possible that a SW Component sends one data element from one P-Port to two different SW Components (1:n Communication). The SwcToSwcSignal describes exactly the information which is exchanged between one P-Port of a SW Component and one R-Port of another SW Component.			
Base	ARObject			
Aggregated by	CommonSignalPath.signal, ForbiddenSignalPath.signal , PermissibleSignalPath.signal , SeparateSignalPath.signal			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	*	iref	Reference to a data element on the PPortPrototype and to the same data element on the RPortPrototype. InstanceRef implemented by: VariableDataPrototypeInSystemInstanceRef

Table A.974: SwcToSwcSignal

Enumeration	SwitchMacAddressLearningEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology
Note	Defines the MAC address learning mode.
Aggregated by	CouplingElement.switchMacAddressLearningMode
Literal	Description
independentVlanLearning	Defines the Independent Vlan Learning (IVL) mode. Tags: atp.EnumerationLiteralIndex=1
sharedVlanLearning	Defines the Shared Vlan Learning (SVL) mode. Tags: atp.EnumerationLiteralIndex=0

Table A.975: SwitchMacAddressLearningEnum

Class	SymbolProps			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Components			
Note	This meta-class represents the ability to attach with the symbol attribute a symbolic name that is conform to C language requirements to another meta-class, e.g. AtomicSwComponentType, that is a potential subject to a name clash on the level of RTE source code.			
Base	ARObject, ImplementationProps , Referrable			
Aggregated by	Allocator.namespace, ApApplicationErrorDomain.namespace, AtomicSwComponentType.symbolProps , CplusplusImplementationDataType.namespace , ImplementationDataType.symbolProps , PortInterface.namespace , SecurityEventDefinition.eventSymbolName			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.976: SymbolProps

Class	SynchronizationTimingConstraint			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingConstraint::SynchronizationTimingConstraint			
Note	<p>This constraint is used to restrict the timing behavior of different, but correlated events or event chains, with regard to synchronization. Two scenarios are supported:</p> <ul style="list-style-type: none"> • If (synchronizationConstraintType==responseSynchronization) <ul style="list-style-type: none"> – TimingDescriptionEvents: An arbitrary number of correlated events which play the role of responses shall occur synchronously with respect to a predefined tolerance. – TimingDescriptionEventChains: An arbitrary number of correlated event chains with a common stimulus, but different responses, where the responses shall occur synchronously with respect to a predefined tolerance. • If (synchronizationConstraintType==stimulusSynchronization) <ul style="list-style-type: none"> – TimingDescriptionEvents: An arbitrary number of correlated events which play the role of stimuli shall occur synchronously with respect to a predefined tolerance. – TimingDescriptionEventChains: An arbitrary number of correlated event chains with a common response, but different stimuli, where the stimuli shall occur synchronously with respect to a predefined tolerance. <p>In case the constraint is imposed on events the following two scenarios are supported:</p> <ul style="list-style-type: none"> • If (eventOccurrenceKind==singleOccurrence): any of the events shall occur only once in the given time interval. • If (eventOccurrenceKind==multipleOccurrences): any of the events may occur more than once in the given time interval. In other words multiple occurrences of an event within the given time interval are permitted. 			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingConstraint , Traceable			
Aggregated by	TimingExtension.timingGuarantee , TimingExtension.timingRequirement			
Attribute	Type	Mult.	Kind	Note
eventOccurrenceKind	EventOccurrenceKind Enum	0..1	attr	Indicates whether the referenced events shall occur only once (single occurrence) or multiple times (multiple occurrences) in the given time interval.
scope	TimingDescriptionEventChain	*	ref	The event chains that are in the scope of the constraint. Mutually exclusive to scopeEvent , see ([constr_4522]).
scopeEvent	TimingDescriptionEvent	*	ref	The events that are in the scope of the constraint. Mutually exclusive to scope , see ([constr_4522])
synchronizationConstraintType	SynchronizationType Enum	0..1	attr	Indicates whether the associated events of the SynchronizationTimingConstraint have a common stimulus or response.





Class	SynchronizationTimingConstraint			
tolerance	MultidimensionalTime	0..1	aggr	The maximum time interval, within which the synchronized events shall occur. The events may occur in any order within this time interval. The time interval starts at the point-in-time when one of the referenced events occurs.

Table A.977: SynchronizationTimingConstraint

Class	SynchronousServerCallPoint			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::ServerCall			
Note	This means that the RunnableEntity is supposed to perform a blocking wait for a response from the server.			
Base	ARObject , AbstractAccessPoint , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable , ServerCallPoint			
Aggregated by	AtpClassifier.atpFeature , RunnableEntity.serverCallPoint			
Attribute	Type	Mult.	Kind	Note
calledFrom WithinExclusive Area	ExclusiveAreaNesting Order	0..1	ref	This indicates that the call point is located at the deepest level inside one or more ExclusiveAreas that are nested in the given order.

Table A.978: SynchronousServerCallPoint

Class	System			
Package	M2::AUTOSARTemplates::SystemTemplate			
Note	<p>The top level element of the System Description. The System description defines five major elements: Topology, Software, Communication, Mapping and Mapping Constraints.</p> <p>The System element directly aggregates the elements describing the Software, Mapping and Mapping Constraints; it contains a reference to an ASAM FIBEX description specifying Communication and Topology.</p> <p>Tags: atp.recommendedPackage=Systems</p>			
Base	ARElement , ARObject , AtpClassifier , AtpFeature , AtpStructureElement , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element , AtpClassifier.atpFeature			
Attribute	Type	Mult.	Kind	Note
clientId DefinitionSet	ClientIdDefinitionSet	*	ref	Set of Client Identifiers that are used for inter-ECU client-server communication in the System.
containerIPdu HeaderByte Order	ByteOrderEnum	0..1	attr	Defines the byteOrder of the header in ContainerIPdus.
ecuExtract Version	RevisionLabelString	0..1	attr	Version number of the Ecu Extract.





Class	System			
fibexElement	FibexElement	*	ref	<p>Reference to ASAM FIBEX elements specifying Communication and Topology.</p> <p>All Fibex Elements used within a System Description shall be referenced from the System Element.</p> <p>atpVariation: In order to describe a product-line, all Fibex Elements can be optional.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=fibexElement.fibexElement, fibexElement.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
interpolationRoutineMappingSet	InterpolationRoutineMappingSet	*	ref	<p>This reference identifies the InterpolationRoutineMapping Sets that are relevant in the context of the enclosing System.</p>
j1939SharedAddressCluster	J1939SharedAddressCluster	*	aggr	<p>Collection of J1939Clusters that share a common address space for the routing of messages.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=j1939SharedAddressCluster.shortName, j1939SharedAddressCluster.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
mapping	SystemMapping	*	aggr	<p>Aggregation of all mapping aspects (mapping of SW components to ECUs, mapping of data elements to signals, and mapping constraints).</p> <p>In order to support OEM / Tier 1 interaction and shared development for one common System this aggregation is atpSplittable and atpVariation. The content of System Mapping can be provided by several parties using different names for the SystemMapping.</p> <p>This element is not required when the System description is used for a network-only use-case.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=mapping.shortName, mapping.variationPoint.shortLabel vh.latestBindingTime=postBuild</p>
pncVectorLength	PositiveInteger	0..1	attr	<p>Length of the partial networking request release information vector (in bytes).</p>
pncVectorOffset	PositiveInteger	0..1	attr	<p>Absolute offset (with respect to the NM-PDU) of the partial networking request release information vector that is defined in bytes as an index starting with 0.</p>
rootSoftwareComposition	RootSwCompositionPrototype	0..1	aggr	<p>Aggregation of the root software composition, containing all software components in the System in a hierarchical structure. This element is not required when the System description is used for a network-only use-case.</p> <p>atpVariation: The RootSwCompositionPrototype can vary.</p> <p>Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=rootSoftwareComposition.shortName, rootSoftwareComposition.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime</p>





Class	System			
swCluster	CpSoftwareCluster	*	ref	CP Software Clusters of this System Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swCluster.cpSoftwareCluster, swCluster.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
system Documentation	Chapter	*	aggr	Possibility to provide additional documentation while defining the System. The System documentation can be composed of several chapters. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=systemDocumentation.shortName, systemDocumentation.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime xml.sequenceOffset=-10
systemVersion	RevisionLabelString	0..1	attr	Version number of the System Description.

Table A.979: System

Class	SystemMapping			
Package	M2::AUTOSARTemplates::SystemTemplate			
Note	The system mapping aggregates all mapping aspects (mapping of SW components to ECUs, mapping of data elements to signals, and mapping constraints).			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	System.mapping			
Attribute	Type	Mult.	Kind	Note
application PartitionToEcu Partition Mapping	ApplicationPartitionToEcuPartitionMapping	*	aggr	Mapping of ApplicationPartitions to EcuPartitions Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=applicationPartitionToEcuPartitionMapping.shortName, applicationPartitionToEcuPartitionMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild
appOsTask ProxyToEcu TaskProxy Mapping	AppOsTaskProxyToEcuTaskProxyMapping	*	aggr	Mapping of an OsTaskProxy that was created in the context of a SwComponent to an OsTaskProxy that was created in the context of an Ecu.
com Management Mapping	ComManagementMapping	*	aggr	Mappings between Mode Management PortGroups and communication channels. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=comManagementMapping.shortName, comManagementMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
cryptoService Mapping	CryptoServiceMapping	*	aggr	This aggregation represents the collection of crypto service mappings in the context of the enclosing System Mapping. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=cryptoServiceMapping.shortName, cryptoServiceMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	SystemMapping			
dataMapping	DataMapping	*	aggr	The data mappings defined. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=dataMapping, dataMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild
ddsISignalToTopicMapping	DdsCplSignalToDdsTopicMapping	*	aggr	Collection of DdsISignalToDdsTopicMappings. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=ddsISignalToTopicMapping, ddsISignalToTopicMapping.variationPoint.shortLabel atp.Status=candidate vh.latestBindingTime=postBuild
ecuResourceMapping	ECUMapping	*	aggr	Mapping of hardware related topology elements onto their counterpart definitions in the ECU Resource Template. atpVariation: The ECU Resource type might be variable. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=ecuResourceMapping.shortName, ecuResourceMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
j1939ControllerApplicationToJ1939NmNodeMapping	J1939ControllerApplicationToJ1939NmNodeMapping	*	aggr	Mapping of a J1939ControllerApplication to a J1939NmNode.
mappingConstraint	MappingConstraint	*	aggr	Constraints that limit the mapping freedom for the mapping of SW components to ECUs. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=mappingConstraint, mappingConstraint.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
pncMapping	PncMapping	*	aggr	Mappings between Virtual Function Clusters and Partial Network Clusters. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=pncMapping, pncMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
portElementToComResourceMapping	PortElementToCommunicationResourceMapping	*	aggr	maps a communication resource to CP Software Clusters Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=portElementToComResourceMapping.shortName, portElementToComResourceMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild
resourceEstimation	EcuResourceEstimation	*	aggr	Resource estimations for this set of mappings, zero or one per ECU instance. atpVariation: Used ECUs are variable. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=resourceEstimation, resourceEstimation.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime





Class	SystemMapping			
resourceToApplicationPartitionMapping	CpSoftwareClusterResourceToApplicationPartitionMapping	*	aggr	Maps a Software Cluster resource to an Application Partition to restrict the usage. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=resourceToApplicationPartitionMapping.shortName, resourceToApplicationPartitionMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
rteEventSeparation	RteEventInSystemSeparation	*	aggr	Separation constraint that limits the mapping freedom for the mapping of RteEvents to OsTasks in the System context.
rteEventToOsTaskProxyMapping	RteEventInSystemToOsTaskProxyMapping	*	aggr	Constraint that enforces a mapping of RteEvent to a particular OsTask in the System context.
signalPathConstraint	SignalPathConstraint	*	aggr	Constraints that limit the mapping freedom for the mapping of data elements to signals. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=signalPathConstraint, signalPathConstraint.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
softwareClusterToApplicationPartitionMapping	CpSoftwareClusterToApplicationPartitionMapping	*	aggr	The mapping of ApplicationPartitions to a CpSoftware Cluster. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=softwareClusterToApplicationPartitionMapping.shortName, softwareClusterToApplicationPartitionMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
softwareClusterToResourceMapping	CpSoftwareClusterToResourceMapping	*	aggr	maps a service resource to CP Software Clusters Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=softwareClusterToResourceMapping.shortName, softwareClusterToResourceMapping.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
swClusterMapping	CpSoftwareClusterToEcuInstanceMapping	*	aggr	The mappings of SW cluster to ECUs. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swClusterMapping.shortName, swClusterMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
swcToApplicationPartitionMapping	SwcToApplicationPartitionMapping	*	aggr	Allows to map a given SwComponentPrototype to a formally defined partition at a point in time when the corresponding EcuInstance is not yet known or defined. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swcToApplicationPartitionMapping.shortName, swcToApplicationPartitionMapping.variationPoint.shortLabel vh.latestBindingTime=postBuild





Class	SystemMapping			
swImplMapping	SwcToImplMapping	*	aggr	The mappings of AtomicSoftwareComponent Instances to Implementations. atpVariation: Derived, because SwcToEcuMapping is variable. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swImplMapping.shortName, swImplMapping.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
swMapping	SwcToEcuMapping	*	aggr	The mappings of SW components to ECUs. atpVariation: SWC shall be mapped to other ECUs. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=swMapping.shortName, swMapping.variationPoint.shortLabel vh.latestBindingTime=preCompileTime
systemSignalGroupToComResourceMapping	SystemSignalGroupToCommunicationResourceMapping	*	aggr	Mapping of a communication resource to a SystemSignal Group. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=systemSignalGroupToComResourceMapping.shortName, systemSignalGroupToComResourceMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime
systemSignalToComResourceMapping	SystemSignalToCommunicationResourceMapping	*	aggr	Mapping of a communication resource to a SystemSignal. Stereotypes: atpSplitable; atpVariation Tags: atp.Splitkey=systemSignalToComResourceMapping.shortName, systemSignalToComResourceMapping.variationPoint.shortLabel vh.latestBindingTime=systemDesignTime

Table A.980: SystemMapping

Class	SystemSignal			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	The system signal represents the communication system's view of data exchanged between SW components which reside on different ECUs. The system signals allow to represent this communication in a flattened structure, with exactly one system signal defined for each data element prototype sent and received by connected SW component instances. Tags: atp.recommendedPackage=SystemSignals			
Base	<i>ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable</i>			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
dynamicLength	Boolean	0..1	attr	The length of dynamic length signals is variable in run-time. Only a maximum length of such a signal is specified in the configuration (attribute length in ISignal element).
physicalProps	SwDataDefProps	0..1	aggr	Specification of the physical representation. Stereotypes: atpSplitable Tags: atp.Splitkey=physicalProps

Table A.981: SystemSignal

Class	SystemSignalGroup			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	<p>A signal group refers to a set of signals that shall always be kept together. A signal group is used to guarantee the atomic transfer of AUTOSAR composite data types.</p> <p>The SystemSignalGroup defines a signal grouping on VFB level. On cluster level the Signal grouping is described by the ISignalGroup element.</p> <p>Tags: atp.recommendedPackage=SystemSignalGroups</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
systemSignal	SystemSignal	*	ref	Reference to a set of SystemSignals that shall always be kept together.
transforming SystemSignal	SystemSignal	0..1	ref	Optional reference to the SystemSignal which shall contain the transformed (linear) data.

Table A.982: SystemSignalGroup

Class	SystemSignalGroupToCommunicationResourceMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	This meta class maps a communication resource to a SystemSignalGroup. This mapping can be used in an early process stage in which the DataMapping linking the Ports and mapped CpSoftwareCluster CommunicationResource(s) to SystemSignals of a SystemSignalGroup is not yet available.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	SystemMapping.systemSignalGroupToComResourceMapping			
Attribute	Type	Mult.	Kind	Note
softwareCluster ComResource	CpSoftwareCluster Communication Resource	0..1	ref	Communication resource for which the mapping applies.
systemSignal Group	SystemSignalGroup	0..1	ref	SystemSignalGroup to which the communication resource is assigned

Table A.983: SystemSignalGroupToCommunicationResourceMapping

Class	SystemSignalToCommunicationResourceMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SoftwareCluster			
Note	This meta class maps a communication resource to a SystemSignal. This mapping can be used in an early process stage in which the DataMapping linking the Ports and mapped CpSoftwareCluster CommunicationResource(s) to the SystemSignal is not yet available.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	SystemMapping.systemSignalToComResourceMapping			
Attribute	Type	Mult.	Kind	Note
softwareCluster ComResource	CpSoftwareCluster Communication Resource	0..1	ref	Communication resource for which the mapping applies.
systemSignal	SystemSignal	0..1	ref	SystemSignal to which the communication resource is assigned

Table A.984: SystemSignalToCommunicationResourceMapping

Class	SystemTiming			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingExtensions			
Note	<p>A model element used to refine timing descriptions and constraints (from a VfbTiming) at System level, utilizing information about topology, software deployment, and signal mapping described in the System Template.</p> <p>TimingDescriptions aggregated by SystemTiming are restricted to events which are derived from the class TDEventVfb, TDEventSwcInternalBehavior and TDEventCom.</p> <p>Tags: atp.recommendedPackage=TimingExtensions</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable , MultilanguageReferrable , PackageableElement , Referrable , TimingExtension			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
system	System	0..1	ref	This defines the scope of a SystemTiming. All corresponding timing descriptions and constraints shall be defined within this scope.

Table A.985: SystemTiming

Class	TDCpSoftwareClusterMapping			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingCpSoftwareCluster			
Note	This is used to specify a mapping between a software cluster that provides temporal and dynamic resources and the software clusters that need these resources.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TDCpSoftwareClusterMappingSet.tdCpSoftwareClusterToTdMapping			
Attribute	Type	Mult.	Kind	Note
provider	CpSoftwareCluster	0..1	ref	This is the software cluster that provides the temporal and dynamic resource.
requestor	CpSoftwareCluster	*	ref	This is the software cluster that requests the temporal and dynamic resource.
timing Description	TimingDescription	0..1	ref	The timing description representing the temporal and dynamic resource.

Table A.986: TDCpSoftwareClusterMapping

Class	TDCpSoftwareClusterResourceMapping			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingCpSoftwareCluster			
Note	This is used to assign an unequivocal global resource identification to a temporal and dynamic resource.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TDCpSoftwareClusterMappingSet.tdCpSoftwareClusterResourceToTdMapping			
Attribute	Type	Mult.	Kind	Note
resource	CpSoftwareClusterResource	0..1	ref	The specific resource identification assigned to the temporal and dynamic resource.
timing Description	TimingDescription	0..1	ref	The timing description representing the temporal and dynamic resource.

Table A.987: TDCpSoftwareClusterResourceMapping

Class	TDEventBsw (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventBsw			
Note	This is used to describe timing events related to BSW modules.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingDescription , TimingDescriptionEvent			
Subclasses	TDEventBswModeDeclaration , TDEventBswModule			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
bswModule Description	BswModuleDescription	0..1	ref	The scope of this timing event.

Table A.988: TDEventBsw

Class	TDEventBswInternalBehavior			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventBswInternalBehavior			
Note	This is used to describe timing events related to the BswInternalBehavior of a BSW module.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
bswModule Entity	BswModuleEntity	0..1	ref	The scope of this timing event.
tdEventBsw Internal BehaviorType	TDEventBswInternal BehaviorTypeEnum	0..1	attr	The specific type of this timing event.

Table A.989: TDEventBswInternalBehavior

Class	TDEventBswModeDeclaration			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventBsw			
Note	This is used to describe timing events related to the mode communication on BSW level.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TDEventBsw , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
entryMode Declaration	ModeDeclaration	0..1	ref	Optional parameter which refines the scope of the TDEventBswModeDeclaration. If the parameter is set, the event occurs only if the mode declaration group prototype instance shall enter into the referenced ModeDeclaration.
exitMode Declaration	ModeDeclaration	0..1	ref	Optional parameter which refines the scope of the TDEventBswModeDeclaration. If the parameter is set, the event occurs only if the mode declaration group prototype instance shall exit from the referenced ModeDeclaration.
mode Declaration	ModeDeclarationGroup Prototype	0..1	ref	The scope of this timing event.
tdEventBsw Mode DeclarationType	TDEventBswMode DeclarationTypeEnum	0..1	attr	The specific type of this timing event.

Table A.990: TDEventBswModeDeclaration

Class	TDEventBswModule			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventBsw			
Note	This is used to describe timing events related to the interaction between BSW modules.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>TDEventBsw</i> , <i>TimingDescription</i> , <i>TimingDescriptionEvent</i>			
Aggregated by	<i>TimingExtension</i> .timingDescription			
Attribute	Type	Mult.	Kind	Note
bswModuleEntry	BswModuleEntry	0..1	ref	The scope of this timing event.
tdEventBswModuleType	TDEventBswModuleTypeEnum	0..1	attr	The specific type of this timing event.

Table A.991: TDEventBswModule

Class	TDEventComplex			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventComplex			
Note	This is used to describe complex timing events. The context of a complex timing event either is described informally, e.g. using the documentation block, or is described formally by the associated TDEventOccurrenceExpression.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>TimingDescription</i> , <i>TimingDescriptionEvent</i>			
Aggregated by	<i>TimingExtension</i> .timingDescription			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.992: TDEventComplex

Class	TDEventCycleStart (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventCom			
Note	This is the abstract parent class to describe timing events related to a point in time where a communication cycle starts. Via the attribute "cycleRepetition", a filtered view to the cycle start can be defined.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i> , <i>TDEventCom</i> , <i>TimingDescription</i> , <i>TimingDescriptionEvent</i>			
Subclasses	TDEventFrClusterCycleStart , TDEventTTCanCycleStart			
Aggregated by	<i>TimingExtension</i> .timingDescription			
Attribute	Type	Mult.	Kind	Note
cycleRepetition	Integer	0..1	attr	The start of every <cycleRepetition> cycle is targeted by this event.

Table A.993: TDEventCycleStart

Class	TDEventFrClusterCycleStart			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventCom			
Note	This is used to describe the timing event related to a point in time where a communication cycle starts on a FlexRay cluster.			





Class	TDEventFrClusterCycleStart			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, Referrable, TDEventCom, TDEventCycleStart, TimingDescription, TimingDescriptionEvent</i>			
Aggregated by	<i>TimingExtension.timingDescription</i>			
Attribute	Type	Mult.	Kind	Note
frCluster	FlexrayCluster	0..1	ref	The scope of this timing event.

Table A.994: TDEventFrClusterCycleStart

Class	TDEventFrame			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventCom			
Note	This is used to describe timing events related to the exchange of frames between the communication controller and the bus specific (FlexRay / CAN / LIN) Interface BSW module.			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, Referrable, TDEventCom, TimingDescription, TimingDescriptionEvent</i>			
Aggregated by	<i>TimingExtension.timingDescription</i>			
Attribute	Type	Mult.	Kind	Note
frame	Frame	0..1	ref	The scope of this timing event.
physicalChannel	PhysicalChannel	0..1	ref	The PhysicalChannel on which the Frame is transmitted.
tdEventType	TDEventFrameTypeEnum	0..1	attr	The specific type of this timing event.

Table A.995: TDEventFrame

Class	TDEventFrameEthernet			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventCom			
Note	This is used to describe timing description events related to the exchange of Ethernet frames between an Ethernet communication controller and the BSW Ethernet interface and driver module.			
Base	<i>ARObject, Identifiable, MultilanguageReferrable, Referrable, TDEventCom, TimingDescription, TimingDescriptionEvent</i>			
Aggregated by	<i>TimingExtension.timingDescription</i>			
Attribute	Type	Mult.	Kind	Note
staticSocketConnection	StaticSocketConnection	0..1	ref	Specifies the SocketConnection by the means of which Physical Data Units (PDU) are transmitted or received within an Ethernet Frame.
tdEventType	TDEventFrameEthernetTypeEnum	0..1	attr	This is used to describe the specific event type of a TDEventFrameEthernet.
tdHeaderIdFilter	TDHeaderIdRange	*	aggr	Specifies the header identifier or a range of header identifiers that if contained in the Ethernet frame let the TDEventFrameEthernet occur.
tdPduTriggeringFilter	PduTriggering	*	ref	Specifies the PDU that if contained in the Ethernet frame let the TDEventFrameEthernet occur.

Table A.996: TDEventFrameEthernet

Class	TDEventIPdu			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventCom			
Note	Describe timing events related to the exchange of IPdus between the bus specific (FlexRay / CAN / LIN) Interface BSW module and COM.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, TDEventCom, TimingDescription, TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
iPdu	IPdu	0..1	ref	The scope of this timing event.
physical Channel	PhysicalChannel	0..1	ref	The PhysicalChannel on which the IPdu is transmitted.
tdEventType	TDEventIPduTypeEnum	0..1	attr	The specific type of this timing event.

Table A.997: TDEventIPdu

Class	TDEventISignal			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventCom			
Note	Describe timing events related to the exchange of TDEventISignals between COM and RTE.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, TDEventCom, TimingDescription, TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
iSignal	ISignal	0..1	ref	The scope of this timing event.
physical Channel	PhysicalChannel	0..1	ref	The PhysicalChannel on which the ISignal is transmitted.
tdEventType	TDEventISignalTypeEnum	0..1	attr	The specific type of this timing event.

Table A.998: TDEventISignal

Class	TDEventModeDeclaration			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventVfb			
Note	A TimingDescriptionEvent triggered by a mode switch in a ModeSwitchInterface on VFB level.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable, TDEventVfb, TDEventVfbPort, TimingDescription, TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
entryMode Declaration	ModeDeclaration	0..1	ref	Optional parameter which refines the scope of the TDEventModeDeclaration. If the parameter is set, the event occurs only if the mode declaration group prototype instance shall enter into the referenced ModeDeclaration.
exitMode Declaration	ModeDeclaration	0..1	ref	Optional parameter which refines the scope of the TDEventModeDeclaration. If the parameter is set, the event occurs only if the mode declaration group prototype instance shall exit from the referenced ModeDeclaration.
mode Declaration	ModeDeclarationGroup Prototype	0..1	ref	The referenced ModeDeclarationGroupPrototype from a{ModeSwitchInterface}.
tdEventMode DeclarationType	TDEventModeDeclarationTypeEnum	0..1	attr	The specific type of this timing event.

Table A.999: TDEventModeDeclaration

Class	TDEventOccurrenceExpression			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventOccurrenceExpression			
Note	This is used to specify a filter on the occurrences of TimingDescriptionEvents by means of a TDEventOccurrenceExpressionFormula. Filter criteria can be variable and argument values, i.e. the timing event only occurs for specific values, as well as the temporal characteristics of the occurrences of arbitrary timing events.			
Base	<i>ARObject</i>			
Aggregated by	TimingDescriptionEvent.occurrenceExpression			
Attribute	Type	Mult.	Kind	Note
argument	AutosarOperationArgumentInstance	*	aggr	An occurrence expression can reference an arbitrary number of OperationArgumentPrototypes in its expression. This association aggregates instance references to OperationArgumentPrototypes which can be referenced in the expression.
formula	TDEventOccurrenceExpressionFormula	0..1	aggr	This is the expression formula which is used to describe the occurrence expression.
mode	TimingModelInstance	*	aggr	An occurrence expression can reference an arbitrary number of TimingModelInstances in its expression. This association aggregates instance references to Mode Declaration which can be referenced in the expression.
variable	AutosarVariableInstance	*	aggr	An occurrence expression can reference an arbitrary number of VariableDataPrototypes in its expression. This association aggregates instance references to VariableDataPrototypes which can be referenced in the expression.

Table A.1000: TDEventOccurrenceExpression

Class	«atpMixedString» TDEventOccurrenceExpressionFormula			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventOccurrenceExpression			
Note	This is an extension of the FormulaExpression for the AUTOSAR Timing Extensions. A TDEventOccurrenceExpressionFormula provides the means to express the temporal characteristics of timing event occurrences in correlation with specific variable and argument values. The formal definition of the extended functions (ExtUnaryFunctions) is described in detail in the AUTOSAR Timing Extensions.			
Base	<i>ARObject, FormulaExpression</i>			
Aggregated by	TDEventOccurrenceExpression.formula			
Attribute	Type	Mult.	Kind	Note
argument	AutosarOperationArgumentInstance	0..1	ref	This is one particular argument value used in the expression formula.
event	TimingDescriptionEvent	0..1	ref	This is one particular timing description event used in the expression formula.
mode	TimingModelInstance	0..1	ref	This is one particular mode used in the expression formula.
variable	AutosarVariableInstance	0..1	ref	This is one particular variable value used in the expression formula.

Table A.1001: TDEventOccurrenceExpressionFormula

Class	TDEventOperation			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventVfb			
Note	A TimingDescriptionEvent triggered by the sending/receiving of a ClientServerOperation in a ClientServerInterface on VFB level.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TDEventVfb , TDEventVfbPort , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	0..1	ref	The referenced ClientServerOperation from a ClientServerInterface .
tdEventOperationType	TDEventOperationTypeEnum	0..1	attr	The specific type of this timing event.

Table A.1002: TDEventOperation

Class	TDEventSwc (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventSwcInternalBehavior			
Note	This is the abstract parent class to describe timing events at Software Component (SW-C) level.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TimingDescription , TimingDescriptionEvent			
Subclasses	TDEventSwcInternalBehavior , TDEventSwcInternalBehaviorReference			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
component	SwComponentPrototype	0..1	iref	The context for the scope of this timing event. InstanceRef implemented by: ComponentInCompositionInstanceRef

Table A.1003: TDEventSwc

Class	TDEventSwcInternalBehavior			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventSwcInternalBehavior			
Note	This is used to describe timing events related to the SwcInternalBehavior of an AtomicSwComponent Type.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TDEventSwc , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
runnable	RunnableEntity	0..1	ref	The scope of this timing event.
tdEventSwcInternalBehaviorType	TDEventSwcInternalBehaviorTypeEnum	0..1	attr	The specific type of this timing event.
variableAccess	VariableAccess	0..1	ref	The scope of this timing event.

Table A.1004: TDEventSwcInternalBehavior

Class	TDEventSwcInternalBehaviorReference			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventSwcInternalBehavior			
Note	This is used to reference timing description events related to the Software Component (SW-C) view which are specified in other timing views.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TDEventSwc , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
referenced TDEventSwc	TDEventSwc	0..1	ref	The referenced timing description event.

Table A.1005: TDEventSwcInternalBehaviorReference

Enumeration	TDEventSwcInternalBehaviorTypeEnum			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventSwcInternalBehavior			
Note	This is used to describe the specific event type of a TDEventSwcInternalBehavior.			
Aggregated by	TDEventSwcInternalBehavior . tdEventSwcInternalBehaviorType			
Literal	Description			
runnableEntity Activated	A point in time where the associated RunnableEntity has been activated, which means that it has entered the state "to be started". Tags: atp.EnumerationLiteralIndex=0			
runnableEntity Started	A point in time where the associated RunnableEntity has entered the state "started" after its activation. Tags: atp.EnumerationLiteralIndex=1			
runnableEntity Terminated	A point in time where the associated RunnableEntity has terminated and entered the state "suspended". Tags: atp.EnumerationLiteralIndex=2			
runnableEntity VariableAccess	A point in time where the associated variable is accessed. Tags: atp.EnumerationLiteralIndex=3			

Table A.1006: TDEventSwcInternalBehaviorTypeEnum

Class	TDEventTTCanCycleStart			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventCom			
Note	This is used to describe the timing event related to a point in time where a communication cycle starts on a TTCAN cluster.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TDEventCom , TDEventCycleStart , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
ttCanCluster	TtcanCluster	0..1	ref	The scope of this timing event.

Table A.1007: TDEventTTCanCycleStart

Class	TDEventTrigger			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventVfb			
Note	A TimingDescriptionEvent triggered by a Trigger in a TriggerInterface on VFB level.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TDEventVfb , TDEventVfbPort , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
tdEventTrigger Type	TDEventTriggerType Enum	0..1	attr	The specific type of this timing event.
trigger	Trigger	0..1	ref	The referenced Trigger from a TriggerInterface .

Table A.1008: TDEventTrigger

Enumeration	TDEventTriggerTypeEnum			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventVfb			
Note	This is used to describe the specific event type of a TDEventTrigger.			
Aggregated by	TDEventTrigger.tdEventTriggerType			
Literal	Description			
triggerActivated	A point in time where the referenced trigger has been successfully released and is activating runnable entities of the receiving SW-C. Tags: atp.EnumerationLiteralIndex=0			
triggerReleased	A point in time where the referenced trigger has been successfully released by the emitting SW-C. Tags: atp.EnumerationLiteralIndex=1			

Table A.1009: TDEventTriggerTypeEnum

Class	TDEventVariableDataPrototype			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventVfb			
Note	A TimingDescriptionEvent triggered by the sending/receiving of a VariableDataPrototype in a SenderReceiverInterface on VFB level.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TDEventVfb , TDEventVfbPort , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
dataElement	VariableDataPrototype	0..1	ref	The referenced VariableDataPrototype from a SenderReceiverInterface .
tdEventVariable DataPrototype Type	TDEventVariableData PrototypeTypeEnum	0..1	attr	The specific type of this timing event.

Table A.1010: TDEventVariableDataPrototype

Enumeration	TDEventVariableDataPrototypeTypeEnum			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventVfb			
Note	This is used to describe the specific event type of a TDEventVariableDataPrototype			
Aggregated by	TDEventVariableDataPrototype.tdEventVariableDataPrototypeType			





Enumeration	TDEventVariableDataPrototypeTypeEnum
Literal	Description
variableDataPrototypeReceived	A point in time where the referenced variable data prototype has been successfully transmitted and is available in the related communication buffer (of the RTE) for the receiving SWC. Tags: atp.EnumerationLiteralIndex=0
variableDataPrototypeSent	A point in time where the referenced variable data prototype has been successfully sent out by the sending SWC, so that it is available in the related communication buffer (of the RTE) for transmission. Tags: atp.EnumerationLiteralIndex=1

Table A.1011: TDEventVariableDataPrototypeTypeEnum

Class	TDEventVfb (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventVfb			
Note	A TimingDescriptionEvent occurring on a Virtual Functional Bus (VFB) PortPrototype .			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TimingDescription , TimingDescriptionEvent			
Subclasses	TDEventVfbPort , TDEventVfbPortGroup , TDEventVfbReference			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
component	SwComponentPrototype	0..1	iref	The context for the scope of this timing event. InstanceRef implemented by: ComponentInCompositionInstanceRef

Table A.1012: TDEventVfb

Class	TDEventVfbPort (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescriptionEvents::TDEventVfb			
Note	A TimingDescriptionEvent occurring on a PortPrototype .			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TDEventVfb , TimingDescription , TimingDescriptionEvent			
Subclasses	TDEventModeDeclaration , TDEventOperation , TDEventTrigger , TDEventVariableDataPrototype			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
isExternal	Boolean	0..1	attr	This attribute is used to refer to external events that are related to hardware I/O, like physical sensors and actuators, at Virtual Functional Bus (VFB) level.
port	PortPrototype	0..1	ref	port on which the TimingEvent shall apply Tags: atp.Status=obsolete
portPrototype	PortPrototype	0..1	iref	PortPrototype on which the TimingEvent occurs Tags: atp.Status=draft xml.typeElement=true InstanceRef implemented by: PortInCompositionTypeInstanceRef
portPrototypeBlueprint	PortPrototypeBlueprint	0..1	ref	port on which the TimingEvent shall apply (in the context of an AUTOSAR blueprint)

Table A.1013: TDEventVfbPort

Class	TDEventVfbReference			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventVfb			
Note	Reference to "other" TimingDescriptionEvents . These other TimingDescriptionEvents may be specified in other views and re-used in this view.			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable , TDEventVfb , TimingDescription , TimingDescriptionEvent			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
referenced TDEventVfb	TDEventVfb	0..1	ref	The referenced timing description event.

Table A.1014: TDEventVfbReference

Class	TDHeaderIdRange			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription::TimingDescription Events::TDEventCom			
Note	Specifies a range of PDU header identifiers. This range is specified by a minimum and maximum header identifier; and the maximum header identifier shall be greater than or equal the minimum header identifier.			
Base	ARObject			
Aggregated by	TDEventFrameEthernet.tdHeaderIdFilter			
Attribute	Type	Mult.	Kind	Note
maxHeaderId	Integer	0..1	attr	Specifies the maximum PDU header identifier, in other words the upper bound of a range of PDU header identifiers.
minHeaderId	Integer	0..1	attr	Specifies the minimum PDU header identifier, in other words the lower bound of a range of PDU header identifiers.

Table A.1015: TDHeaderIdRange

Class	TargetIPduRef			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Multiplatform			
Note	Target destination of the referencing mapping.			
Base	ARObject			
Aggregated by	IPduMapping.targetIPdu			
Attribute	Type	Mult.	Kind	Note
defaultValue	PduMappingDefaultValue	0..1	aggr	If no I-Pdu has been received a default value will be distributed.
targetIPdu	PduTriggering	0..1	ref	IPdu Reference

Table A.1016: TargetIPduRef

Class	Tcplplcmpv4Props			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This meta-class specifies the configuration options for ICMPv4 (Internet Control Message Protocol).			
Base	ARObject			
Aggregated by	EthTcplplcmpProps.icmpV4Props			
Attribute	Type	Mult.	Kind	Note





Class	Tcplplcmpv4Props			
tcplplcmpV4EchoReplyEnabled	Boolean	0..1	attr	This attribute enables or disables transmission of ICMP echo reply message in case of a ICMP echo reception.
tcplplcmpV4Ttl	PositiveInteger	0..1	attr	This attribute is only relevant in case that ICMP (Internet Control Message Protocol) is used. It specifies the default Time-to-live value of outgoing ICMP packets.

Table A.1017: Tcplplcmpv4Props

Class	Tcplplcmpv6Props			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This meta-class specifies the configuration options for ICMPv6 (Internet Control Message Protocol).			
Base	ARObject			
Aggregated by	EthTcplplcmpProps.icmpV6Props			
Attribute	Type	Mult.	Kind	Note
tcplplcmpV6EchoReplyAvoidFragmentation	Boolean	0..1	attr	This attribute defines whether the echo reply is only transmitted in case that the incoming ICMPv6 Echo Request (Pings) fits the MTU of the respective interface, i.e. can be transmitted without IPv6 fragmentation.
tcplplcmpV6EchoReplyEnabled	Boolean	0..1	attr	This attribute enables or disables transmission of ICMP echo reply message in case of a ICMP echo reception.
tcplplcmpV6HopLimit	PositiveInteger	0..1	attr	Default Hop-Limit value of outgoing ICMPv6 packets.
tcplplcmpV6MsgDestinationUnreachableEnabled	Boolean	0..1	attr	This attribute Enables/Disables the transmission of Destination Unreachable Messages.
tcplplcmpV6MsgParameterProblemEnabled	Boolean	0..1	attr	If enabled an ICMPv6 parameter problem message will be sent if a received packet has been dropped due to unknown options or headers that are found in the packet.

Table A.1018: Tcplplcmpv6Props

Class	TcpOptionFilterList			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::TcpOptionFilterSet			
Note	Permitted list for the filtering of TCP options.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TcpOptionFilterSet.tcpOptionFilterList			
Attribute	Type	Mult.	Kind	Note
allowedTcpOption	PositiveInteger	*	attr	TCP option kind allowed by this filter.

Table A.1019: TcpOptionFilterList

Class		TcpProps		
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This meta-class specifies the configuration options for TCP (Transmission Control Protocol).			
Base	ARObject			
Aggregated by	EthTcplpProps.tcpProps			
Attribute	Type	Mult.	Kind	Note
tcpCongestion Avoidance Enabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) support of TCP congestion avoidance algorithm according to IETF RFC 5681.
tcpDelayedAck Timeout	TimeValue	0..1	attr	The maximal time an acknowledgement is delayed for transmission in seconds.
tcpFast Recovery Enabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) support of TCP Fast Recovery according to IETF RFC 5681.
tcpFast Retransmit Enabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) support of TCP Fast Retransmission according to IETF RFC 5681.
tcpFin Wait2Timeout	TimeValue	0..1	attr	Timeout in [s] to receive a FIN from the remote node (after this node has initiated connection termination), i.e. maximum time waiting in FINWAIT-2 for a connection termination request from the remote TCP.
tcpKeepAlive Enabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) TCP Keep Alive Probes according to IETF RFC 1122 chapter 4.2.3.6.
tcpKeepAlive Interval	TimeValue	0..1	attr	Specifies the interval in seconds between subsequent keepalive probes.
tcpKeepAlive ProbesMax	PositiveInteger	0..1	attr	Maximum number of times that a TCP Keep Alive is retransmitted before the connection is closed.
tcpKeepAlive Time	TimeValue	0..1	attr	Specifies the time in [s] between the last data packet sent (simple ACKs are not considered data) and the first keepalive probe.
tcpMaxRtx	PositiveInteger	0..1	attr	Maximum number of times that a TCP segment is retransmitted before the TCP connection is closed. This parameter is only valid if tcpRetransmissionTimeout is configured. Note: This parameter also applies for FIN retransmissions.
tcpMsl	TimeValue	0..1	attr	Maximum segment lifetime in [s].
tcpNagle Enabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) support of Nagle's algorithm according to IETF RFC 1122 (chapter 4.2.3.4 When to Send Data). If enabled the Nagle's algorithm is activated per default for all TCP sockets, but can be deactivated per Socket (with the attribute TcpTp.nagle Algorithm).
tcpReceive WindowMax	PositiveInteger	0..1	attr	Default value of maximum receive window in bytes.
tcp Retransmission Timeout	TimeValue	0..1	attr	Timeout in [s] before an unacknowledged TCP segment is sent again. If the timeout is disabled, no TCP segments shall be retransmitted.
tcpSlowStart Enabled	Boolean	0..1	attr	Enables (TRUE) or disables (FALSE) support of TCP slow start algorithm according to IETF RFC 5681.
tcpSynMaxRtx	PositiveInteger	0..1	attr	Maximum number of times that a TCP SYN is retransmitted.
tcpSynReceived Timeout	TimeValue	0..1	attr	Timeout in [s] to complete a remotely initiated TCP connection establishment, i.e. maximum time waiting in SYN-RECEIVED for a confirming connection request acknowledgement after having both received and sent a connection request.
tcpTtl	PositiveInteger	0..1	attr	Default Time-to-live value of outgoing TCP packets.

Table A.1020: TcpProps

Class	TcpTp			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Content Model for TCP configuration.			
Base	<i>ARObject</i> , TcpUdpConfig , <i>TransportProtocolConfiguration</i>			
Aggregated by	ApApplicationEndpoint.tpConfiguration, ApplicationEndpoint.tpConfiguration , HttpTp.tcpTpConfig , RtpTp.tcpUdpConfig			
Attribute	Type	Mult.	Kind	Note
keepAliveInterval	TimeValue	0..1	attr	Specifies the interval in seconds between subsequent keepalive probes.
keepAliveProbesMax	PositiveInteger	0..1	attr	Maximum number of times that TCP retransmits an individual data segment before aborting the connection.
keepAlives	Boolean	0..1	attr	Indicates if Keep-Alive messages are sent.
keepAliveTime	TimeValue	0..1	attr	Specifies the time in seconds between the last data packet sent and the first keepalive probe.
naglesAlgorithm	Boolean	0..1	attr	Indicates if Nagle's Algorithm is used.
receiveWindowMin	PositiveInteger	0..1	attr	Minimum size of the TCP receive window in bytes.
tcpRetransmissionTimeout	TimeValue	0..1	attr	Defines the timeout in seconds before an unacknowledged TCP segment is sent again. If the tcpRetransmissionTimeout is not defined or set to "INF", no TCP segments shall be re-transmitted.
tcpTpPort	TpPort	0..1	aggr	TCP Port configuration.

Table A.1021: TcpTp

Class	TcpUdpConfig (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Tcp or Udp Transport Protocol Configuration.			
Base	<i>ARObject</i> , <i>TransportProtocolConfiguration</i>			
Subclasses	TcpTp , UdpTp			
Aggregated by	ApApplicationEndpoint.tpConfiguration, ApplicationEndpoint.tpConfiguration , RtpTp.tcpUdpConfig			
Attribute	Type	Mult.	Kind	Note
-	-	-	-	-

Table A.1022: TcpUdpConfig

Class	TextTableMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Defines the mapping of two DataPrototypes typed by AutosarDataTypes that refer to CompuMethods of category TEXTTABLE, SCALE_LINEAR_AND_TEXTTABLE or BITFIELD_TEXTTABLE.			
Base	<i>ARObject</i>			
Aggregated by	DataPrototypeMapping.textTableMapping , SenderRecArrayTypeMapping.senderToSignalTextTableMapping , SenderRecArrayTypeMapping.signalToReceiverTextTableMapping , SenderReceiverToSignalMapping.senderToSignalTextTableMapping , SenderReceiverToSignalMapping.signalToReceiverTextTableMapping , SenderRecRecordElementMapping.senderToSignalTextTableMapping , SenderRecRecordElementMapping.signalToReceiverTextTableMapping , SubElementMapping.textTableMapping			
Attribute	Type	Mult.	Kind	Note





Class	TextTableMapping			
bitfieldTextTableMaskFirst	PositiveInteger	0..1	attr	This attribute can be used to support the mapping of bit field to bit field, boolean values to bit fields, and vice versa. The attribute defines the bit mask for the first element of the TextTableMapping. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
bitfieldTextTableMaskSecond	PositiveInteger	0..1	attr	This attribute can be used to support the mapping of bit field to bit field, boolean values to bit fields, and vice versa. The attribute defines the bit mask for the second element of the TextTableMapping. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
identicalMapping	Boolean	0..1	attr	If identicalMapping is set == true the values of the two referenced DataPrototypes do not need any conversion of the values.
mappingDirection	MappingDirectionEnum	0..1	attr	Specifies the conversion direction for which the TextTableMapping is applicable.
valuePair	TextTableValuePair	*	aggr	Defines a pair of values which are translated into each other.

Table A.1023: TextTableMapping

Class	TextTableValuePair			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Defines a pair of text values which are translated into each other.			
Base	ARObject			
Aggregated by	TextTableMapping.valuePair			
Attribute	Type	Mult.	Kind	Note
firstValue	Numerical	0..1	attr	Value of first DataPrototype provided similar to a numerical ValueSpecification which is intended to be assigned to a Primitive data element. Note that the numerical value is a variant, it can be computed by a formula. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime
secondValue	Numerical	0..1	attr	Value of second DataPrototype provided similar to a numerical ValueSpecification which is intended to be assigned to a Primitive data element. Note that the numerical value is a variant, it can be computed by a formula. Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime

Table A.1024: TextTableValuePair

Class	TextValueSpecification
Package	M2::AUTOSARTemplates::CommonStructure::Constants
Note	The purpose of TextValueSpecification is to define the labels that correspond to enumeration values.
Base	ARObject, ValueSpecification





Class	TextValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, MetaDataItem.metaDataItemtype, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeipEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalIdValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
value	VerbatimString	0..1	attr	This is the value itself. Note that vt uses the operator to separate the values for the different bitfield masks in case that the semantics of the related DataPrototype is described by means of a BITFIELD_TEXTTABLE in the associated CompuMethod.

Table A.1025: TextValueSpecification

Class	TimeRangeType			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	The timeRange can be specified with the value attribute. Optionally a tolerance can be defined.			
Base	ARObject			
Aggregated by	CyclicTiming.timeOffset, CyclicTiming.timePeriod, EventControlledTiming.repetitionPeriod			
Attribute	Type	Mult.	Kind	Note
tolerance	TimeRangeType Tolerance	0..1	aggr	Optional specification of a tolerance.
value	TimeValue	0..1	attr	Average value of a date (in seconds)

Table A.1026: TimeRangeType

Class	TimeSyncClientConfiguration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines the configuration of the time synchronisation client. Tags: atp.Status=obsolete			
Base	ARObject			
Aggregated by	TimeSynchronization.timeSyncClient			
Attribute	Type	Mult.	Kind	Note
orderedMaster (ordered)	OrderedMaster	*	aggr	Defines a list of ordered NetworkEndpoints. Tags: atp.Status=obsolete xml.namePlural=ORDERED-MASTER-LIST
timeSync Technology	TimeSyncTechnology Enum	0..1	attr	Defines the time synchronisation technology used. Tags: atp.Status=obsolete

Table A.1027: TimeSyncClientConfiguration

Class	TimeSyncServerConfiguration			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Defines the configuration of the time synchronisation server. Tags: atp.Status=obsolete			
Base	<i>ARObject</i> , <i>Referrable</i>			
Aggregated by	TimeSynchronization.timeSyncServer			
Attribute	Type	Mult.	Kind	Note
priority	PositiveInteger	0..1	attr	Server Priority. Tags: atp.Status=obsolete
syncInterval	TimeValue	0..1	attr	Synchronisation interval used by the time synchronisation server (in seconds). Tags: atp.Status=obsolete
timeSyncServer Identifier	String	0..1	attr	Identifier of the TimeSyncServer. Tags: atp.Status=obsolete
timeSync Technology	TimeSyncTechnology Enum	0..1	attr	Defines the time synchronisation technology used. Possible values are: NTP_RFC958, PTP_IEEE1588_2002, PTP_IEEE1588_2008, AVB_IEEE802_1AS and others. Tags: atp.Status=obsolete

Table A.1028: TimeSyncServerConfiguration

Class	TimingDescription (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription			
Note	The abstract parent class of the model elements that are used to define the scope of a timing constraint.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Subclasses	<i>TimingDescriptionEvent</i> , <i>TimingDescriptionEventChain</i>			
Aggregated by	<i>TimingExtension</i> .timingDescription			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.1029: TimingDescription

Class	TimingDescriptionEvent (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription			
Note	<p>A timing event is the abstract representation of a specific system behavior -- that can be observed at runtime -- in the AUTOSAR specification. Timing events are used to define the scope for timing constraints. Depending on the specific scope, the view on the system, and the level of abstraction different types of events are defined.</p> <p>In order to avoid confusion with existing event descriptions in the AUTOSAR templates the timing specific event types use the prefix TD.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingDescription			
Subclasses	TDEventBsw , TDEventBswInternalBehavior , TDEventCom , TDEventComplex , TDEventSwc , TDEventVfb			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
clockReference	TimingClock	0..1	ref	Optional reference to a clock that holds the time base for an TD event. Tags: atp.Status=draft
occurrence Expression	TDEventOccurrence Expression	0..1	aggr	The occurrence expression for this event.

Table A.1030: TimingDescriptionEvent

Class	TimingDescriptionEventChain			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingDescription			
Note	<p>An event chain describes the causal order for a set of functionally dependent timing events. Each event chain has a well defined stimulus and response, which describe its start and end point. Furthermore, it can be hierarchically decomposed into an arbitrary number of sub-chains, so called <i>event chain segments</i>.</p>			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , TimingDescription			
Aggregated by	TimingExtension.timingDescription			
Attribute	Type	Mult.	Kind	Note
isPipelining Permitted	Boolean	0..1	attr	States whether the scheduled entities in an LET interval shall use pipelined execution or not i.e. "permitted pipelining property" If TRUE, then the scheduled entities must implement pipelining. If FALSE or undefined, no pipelining applies. Tags: atp.Status=draft
response	TimingDescriptionEvent	0..1	ref	The response event representing the point in time where the event chain is terminated. Tags: xml.sequenceOffset=20
segment	TimingDescriptionEvent Chain	*	ref	A composed event chain consists of an arbitrary number of sub-chains. Tags: xml.sequenceOffset=30
stimulus	TimingDescriptionEvent	0..1	ref	The stimulus event representing the point in time where the event chain is activated. Tags: xml.sequenceOffset=10

Table A.1031: TimingDescriptionEventChain

Class	TimingEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is used to start RunnableEntities that shall be executed periodically.			
Base	ARObject, AbstractEvent , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , RTEEvent , Referrable			
Aggregated by	AtpClassifier.atpFeature , SwcInternalBehavior.event			
Attribute	Type	Mult.	Kind	Note
offset	TimeValue	0..1	attr	The value makes an assumption about the time offset of the first activation of the RunnableEntity triggered by the mapped TimingEvent relative to the periodic activation of the time base of this TimingEvent. Unit: second.
period	TimeValue	0..1	attr	Period of timing event in seconds. The value of this attribute shall be greater than zero.

Table A.1032: TimingEvent

Class	TlsCryptoCipherSuite			
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This meta-class represents a cipher suite for describing cryptographic operations in the context of establishing a connection of ApplicationEndpoints that is protected by TLS.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	TlsCryptoServiceMapping.tlsCipherSuite , TlsSecureComProps.tlsCipherSuite			
Attribute	Type	Mult.	Kind	Note
authentication	CryptoServicePrimitive	0..1	ref	This reference identifies the crypto service primitive for the generation and verification of MACs.
certificate	CryptoServiceCertificate	0..1	ref	This reference identifies the applicable local certificate.
cipherSuiteId	PositiveInteger	0..1	attr	Identification of the CipherSuite according to the IANA assignments list.
cipherSuiteShortLabel	String	0..1	attr	Name of the CipherSuite according to the IANA assignments list.
ellipticCurve	CryptoEllipticCurveProps	*	ref	This references point to the properties of elliptic curves.
encryption	CryptoServicePrimitive	0..1	ref	This reference identifies the crypto service primitive for the execution of encryption.
keyExchange	CryptoServicePrimitive	*	ref	This reference identifies the individual (i.e. per cipher suite) crypto service primitive for the execution of key exchange during the handshake phase.
keyExchangeAuthentication	CryptoServicePrimitive	*	ref	This reference identifies the crypto service primitives for the generation and verification of signatures during the key exchange algorithm.
priority	PositiveInteger	0..1	attr	This attribute identifies the priority of the cipher suite. Range: 1..65535. Lower values represent higher priorities.
props	TlsCryptoCipherSuiteProps	0..1	aggr	The aggregated TlsCryptoCipherSuiteProps provide details for the TLS Cipher Suite.
pskIdentity	TlsPskIdentity	0..1	aggr	Pre-shared key identity shared during the handshake among the communication parties, to establish a TLS connection if the handshake is based on the existence of a pre-shared key.
remoteCertificate	CryptoServiceCertificate	0..1	ref	This reference identifies the applicable remote certificate.
signatureScheme	CryptoSignatureScheme	*	ref	This reference points to the properties of a TLS Signature Scheme.
version	TlsVersionEnum	0..1	attr	This attribute supports the definition of the applicable version of TLS.

Table A.1033: TlsCryptoCipherSuite

Class	TlsCryptoServiceMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This meta-class has the ability to represent a crypto service mapping for the socket-based configuration of Transport Layer Security (TLS).			
Base	ARObject, CryptoServiceMapping , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	SystemMapping.cryptoServiceMapping			
Attribute	Type	Mult.	Kind	Note





Class	TlsCryptoServiceMapping			
keyExchange	CryptoServicePrimitive	*	ref	This reference identifies the shared(i.e. applicable for each of the aggregated cipher suites) crypto service primitive for the execution of key exchange during the handshake phase.
tlsCipherSuite	TlsCryptoCipherSuite	*	aggr	This aggregation represents the collection of supported cipher suites.
useClient Authentication Request	Boolean	0..1	attr	Defines if client authentication shall be applied for this TLS connection.
useSecurity Extension RecordSize Limit	Boolean	0..1	attr	Defines if the security extension for max_fragment_length shall be supported as defined in IETF RFC 8449, chapter 4.1.

Table A.1034: TlsCryptoServiceMapping

Class	TlsPskIdentity			
Package	M2::AUTOSARTemplates::SystemTemplate::SecureCommunication			
Note	This element is used to describe the pre-shared key shared during the handshake among the communication parties, to establish a TLS connection if the handshake is based on the existence of a pre-shared key.			
Base	<i>ARObject</i>			
Aggregated by	TlsCryptoCipherSuite.pskIdentity			
Attribute	Type	Mult.	Kind	Note
preSharedKey	CryptoServiceKey	0..1	ref	This reference identifies the applicable cryptographic key.
pskIdentity	String	0..1	attr	This attribute provides the key identification.
pskIdentityHint	String	0..1	attr	This attribute provides the identity hint for a pre-shared key.

Table A.1035: TlsPskIdentity

Class	TlvDataIdDefinition			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	This meta-class represents the ability to define the tlvDataId.			
Base	<i>ARObject</i>			
Aggregated by	TlvDataIdDefinitionSet.tlvDataIdDefinition			
Attribute	Type	Mult.	Kind	Note
id	PositiveInteger	0..1	attr	This attribute represents the definition of the value of the TlvDataId Stereotypes: atpIdentityContributor
tlvArgument	ArgumentDataPrototype	0..1	ref	This reference assigns a tlvDataId to a given argument of a ClientServerOperation.
tlv Implementation Data Type Element	AbstractImplementationDataElement	0..1	ref	This reference associates the definition of a TLV data id with a given AbstractImplementationDataElement.
tlvRecord Element	ApplicationRecordElement	0..1	ref	This reference associates the definition of a TLV data id with a given ApplicationRecordElement.

Table A.1036: TlvDataIdDefinition

Class	TlvDataIdDefinitionSet			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	This meta-class acts as a container of TlvDataIdDefinitions to be used in a given context Tags: atp.recommendedPackage=TlvDataDefinitionSets			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
tlvDataIdDefinition	TlvDataIdDefinition	*	aggr	This aggregation represents the collection of TlvDataIdDefinitions aggregated by the TlvDataIdDefinitionSet Stereotypes: atp.Splittable Tags: atp.Splitkey=tlvDataIdDefinition.id

Table A.1037: TlvDataIdDefinitionSet

Class	Topic1			
Package	M2::MSR::Documentation::Chapters			
Note	This meta-class represents a topic of a documentation. Topics are similar to chapters but they cannot be nested. They also do not appear in the table of content. Topics can be used to produce intermediate headlines thus structuring a chapter internally.			
Base	ARObject, DocumentViewSelectable, Identifiable, MultilanguageReferrable, Paginateable, Referrable			
Aggregated by	MsrQueryResultTopic1.topic1, TopicOrMsrQuery.topic1			
Attribute	Type	Mult.	Kind	Note
helpEntry	String	0..1	attr	This specifies an entry point in an online help system to be linked with the parent class. The syntax shall be defined by the applied help system respectively help system generator. Tags: xml.attribute=true
topicContent	TopicContentOrMsrQuery	0..1	aggr	This is the content of the topic. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=20 xml.typeElement=false xml.typeWrapperElement=false

Table A.1038: Topic1

Class	TpAddress			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	An ECUs TP address on the referenced channel. This represents the diagnostic Address.			
Base	ARObject, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	FlexrayArTpConfig.tpAddress, FlexrayTpConfig.tpAddress, J1939TpConfig.tpAddress, LinTpConfig.tpAddress			
Attribute	Type	Mult.	Kind	Note
tpAddress	Integer	0..1	attr	An ECUs TP address on the referenced channel. This represents the diagnostic Address.

Table A.1039: TpAddress

Class	TpConfig (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::TransportProtocols			
Note	Contains all configuration elements for AUTOSAR TP.			
Base	<i>ARObject</i> , <i>CollectableElement</i> , <i>FibexElement</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PackageableElement</i> , <i>Referrable</i>			
Subclasses	CanTpConfig , DolpTpConfig , EthTpConfig , FlexrayArTpConfig , FlexrayTpConfig , IEEE1722TpConfig , J1939TpConfig , LinTpConfig , SomeipTpConfig			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
communication Cluster	CommunicationCluster	0..1	ref	A TpConfig is existing always in the context of exactly one CommunicationCluster.

Table A.1040: TpConfig

Class	TpConnection (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::DiagnosticConnection			
Note	TpConnection Base Class.			
Base	<i>ARObject</i>			
Subclasses	CanTpConnection , DolpTpConnection , EthTpConnection , FlexrayArTpConnection , FlexrayTpConnection , J1939TpConnection , LinTpConnection			
Attribute	Type	Mult.	Kind	Note
ident	TpConnectionIdent	0..1	aggr	This adds the ability to become referrable to Tp Connection.

Table A.1041: TpConnection

Class	TpConnectionIdent			
Package	M2::AUTOSARTemplates::SystemTemplate::DiagnosticConnection			
Note	This meta-class is created to add the ability to become the target of a reference to the non-Referrable Tp Connection.			
Base	<i>ARObject</i> , <i>Referrable</i>			
Aggregated by	TpConnection.ident			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.1042: TpConnectionIdent

Class	TpPort			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Dynamic or direct assignment of a PortNumber.			
Base	<i>ARObject</i>			
Aggregated by	TcpTp.tcpTpPort , UdpTp.udpTpPort			
Attribute	Type	Mult.	Kind	Note
dynamically Assigned	Boolean	0..1	attr	Indicates whether the source port is dynamically assigned. Tags: atp.Status=obsolete
portNumber	PositiveInteger	0..1	attr	Port Number.

Table A.1043: TpPort

Class	Traceable (abstract)			
Package	M2::MSR::Documentation::BlockElements::RequirementsTracing			
Note	This meta class represents the ability to be subject to tracing within an AUTOSAR model. Note that it is expected that its subclasses inherit either from MultilanguageReferrable or from Identifiable. Nevertheless it also inherits from MultilanguageReferrable in order to provide a common reference target for all Traceables.			
Base	ARObject, MultilanguageReferrable , Referrable			
Subclasses	StructuredReq , TimingConstraint , TraceableTable , TraceableText			
Attribute	Type	Mult.	Kind	Note
trace	Traceable	*	ref	This association represents the ability to trace to upstream requirements / constraints. This supports for example the bottom up tracing ProjectObjectives <- MainRequirements <- Features <- RequirementSpecs <- BSW/AI Tags: xml.sequenceOffset=20

Table A.1044: Traceable

Class	TraceableText			
Package	M2::MSR::Documentation::BlockElements::RequirementsTracing			
Note	Represents a paragraph level text which can be referenced in order to establish tracing. It supports specific tracing of document items as specified in [TPS_STDT_00098]. The following approach applies: <ul style="list-style-type: none"> • shortName: represents the tag for tracing • longName: represents the headline • category: represents the kind of the tagged text 			
Base	ARObject, DocumentViewSelectable , Identifiable , MultilanguageReferrable , Paginateable , Referrable , Traceable			
Aggregated by	DocumentationBlock.trace			
Attribute	Type	Mult.	Kind	Note
text	DocumentationBlock	1	aggr	This represents the text to which the tag applies. Tags: xml.roleElement=false xml.roleWrapperElement=false xml.sequenceOffset=30 xml.typeElement=false xml.typeWrapperElement=false

Table A.1045: TraceableText

Enumeration	TransferPropertyEnum		
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication		
Note	Transfer Properties of a Signal.		
Aggregated by	ISignalToIPduMapping.transferProperty		
Literal	Description		
pending	If the signal has the TransferProperty pending, then the function Com_SendSignal shall not perform a transmission of the IPdu associated with the signal. Tags: atp.EnumerationLiteralIndex=0		
triggered	The signal in the assigned IPdu is updated and a request for the IPdu's transmission is made. Tags: atp.EnumerationLiteralIndex=1		





Enumeration	TransferPropertyEnum
triggeredOnChange	The signal in the assigned IPdu is updated and a request for the IPdus transmission is made only if the signal value is different from the already stored signal value. Tags: atp.EnumerationLiteralIndex=2
triggeredOnChange WithoutRepetition	The signal in the assigned IPdu is updated and a request for the IPdus transmission is made only if the signal value is different from the already stored signal value. In the DIRECT/N-TIMES or MIXED transmission mode (EventControlledTiming) the IPdu will be transmitted just once without a repetition, independent of the defined NumberOfRepeats. Tags: atp.EnumerationLiteralIndex=3
triggeredWithout Repetition	The signal in the assigned IPdu is updated and a request for the IPdu's transmission is made. In the DIRECT/N-TIMES or MIXED transmission mode (EventControlledTiming) the IPdu will be transmitted just once without a repetition, independent of the defined NumberOfRepeats. Tags: atp.EnumerationLiteralIndex=4

Table A.1046: TransferPropertyEnum

Class	TransformationDescription (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	The TransformationDescription is the abstract class that can be used by specific transformers to add transformer specific properties.			
Base	ARObject, Describable			
Subclasses	EndToEndTransformationDescription, SOMEIPTransformationDescription, UserDefinedTransformationDescription			
Aggregated by	TransformationTechnology.transformationDescription			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.1047: TransformationDescription

Class	«atpVariation» TransformationISignalProps (abstract)			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	TransformationISignalProps holds all the attributes for the different TransformationTechnologies that are ISignal specific. Tags: vh.latestBindingTime=postBuild			
Base	ARObject, Describable			
Subclasses	EndToEndTransformationISignalProps, SOMEIPTransformationISignalProps, UserDefinedTransformationISignalProps			
Aggregated by	ISignal.transformationISignalProps, ISignalGroup.transformationISignalProps			
Attribute	Type	Mult.	Kind	Note
csErrorReaction	CSTransformerErrorReactionEnum	0..1	attr	Defines whether the transformer chain of client/server communication coordinates an autonomous error reaction together with the RTE or whether any error reaction is the responsibility of the application.
dataPrototype Transformation Props	DataPrototype TransformationProps	*	aggr	Fine granular modeling of TransformationProps on the level of DataPrototypes. Note: This atpSplitable property has no atp.Splitkey due to atpVariation (PropertySetPattern). Stereotypes: atpSplitable





Class	«atpVariation» TransformationSignalProps (abstract)			
ident	TransformationSignalPropsIdent	0..1	aggr	This adds the ability to add a shortName to TransformationSignalProps. Please note that the short-name needs to be provided if the splittable mechanism is used.
transformer	TransformationTechnology	0..1	ref	Reference to the TransformationTechnology description that contains transformer specific and ISignal independent configuration properties.

Table A.1048: TransformationSignalProps

Class	TransformationTechnology			
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer			
Note	A TransformationTechnology is a transformer inside a transformer chain. Tags: xml.namePlural=TRANSFORMATION-TECHNOLOGIES			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	DataTransformationSet.transformationTechnology			
Attribute	Type	Mult.	Kind	Note
bufferProperties	BufferProperties	0..1	aggr	Aggregation of the mandatory BufferProperties.
hasInternalState	Boolean	0..1	attr	This attribute defines whether the Transformer has an internal state or not.
needsOriginalData	Boolean	0..1	attr	Specifies whether this transformer gets access to the SWC's original data.
protocol	String	0..1	attr	Specifies the protocol that is implemented by this transformer.
transformationDescription	TransformationDescription	0..1	aggr	A transformer can be configured with transformer specific parameters which are represented by the Transformer Description. Stereotypes: atpSplittable; atpVariation Tags: atp.Splitkey=transformationDescription, transformationDescription.variationPoint.shortLabel vh.latestBindingTime=postBuild
transformerClass	TransformerClassEnum	0..1	attr	Specifies to which transformer class this transformer belongs.
version	String	0..1	attr	Version of the implemented protocol.

Table A.1049: TransformationTechnology

Enumeration	TransformerClassEnum
Package	M2::AUTOSARTemplates::SystemTemplate::Transformer
Note	Specifies the transformer class of a transformer.
Aggregated by	TransformationTechnology.transformerClass
Literal	Description
custom	The transformer is a custom transformer. Tags: atp.EnumerationLiteralIndex=0
safety	The transformer is a safety transformer. Tags: atp.EnumerationLiteralIndex=1





Enumeration	TransformerClassEnum
security	The transformer is a security transformer. Tags: atp.EnumerationLiteralIndex=2
serializer	The transformer is a serializing transformer. Tags: atp.EnumerationLiteralIndex=3

Table A.1050: TransformerClassEnum

Class	TransformerHardErrorEvent			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents			
Note	This event is raised when data are received which should trigger a Client/Server operation or an external Trigger but during transformation of the data a hard transformer error occurred.			
Base	<i>ARObject</i> , <i>AbstractEvent</i> , <i>AtpClassifier</i> , <i>AtpFeature</i> , <i>AtpStructureElement</i> , <i>Identifiable</i> , <i>Multilanguage Referrable</i> , <i>RTEEvent</i> , <i>Referrable</i>			
Aggregated by	<i>AtpClassifier.atpFeature</i> , <i>SwcInternalBehavior.event</i>			
Attribute	Type	Mult.	Kind	Note
operation	ClientServerOperation	0..1	iref	This represents the ClientServerOperation for which the transformer can raise this TransformerHardErrorEvent. InstanceRef implemented by: POperationInAtomicSwc InstanceRef
requiredTrigger	Trigger	0..1	iref	This represents the Trigger for which the transformer can raise this TransformerHardErrorEvent. InstanceRef implemented by: RTriggerInAtomicSwc InstanceRef

Table A.1051: TransformerHardErrorEvent

Class	TransmissionAcknowledgementRequest			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	Requests transmission acknowledgement that data has been sent successfully. Success/failure is reported via a SendPoint of a RunnableEntity.			
Base	<i>ARObject</i>			
Aggregated by	<i>SenderComSpec.transmissionAcknowledge</i>			
Attribute	Type	Mult.	Kind	Note
timeout	TimeValue	0..1	attr	Number of seconds before an error is reported or in case of allowed redundancy, the value is sent again.

Table A.1052: TransmissionAcknowledgementRequest

Class	TransmissionComSpecProps			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Communication			
Note	This meta-class defines a set of transmission attributes which the application software is assumed to implement.			
Base	<i>ARObject</i>			
Aggregated by	<i>SenderComSpec.transmissionProps</i>			
Attribute	Type	Mult.	Kind	Note
dataUpdate Period	TimeValue	0..1	attr	This attribute defines the period in which the application is assumed to transmit the respective data.





Class	TransmissionComSpecProps			
minimumSendInterval	TimeValue	0..1	attr	This attribute defines the minimum interval between two consecutive transmissions of the respective data the application is assumed to ensure.
onChangeDataPrototype	DataPrototypeReference	*	aggr	This reference defines which DataPrototypes trigger the onChange transmission of the data.
transmissionMode	TransmissionModeDefinitionEnum	0..1	attr	The attribute defines the mode in which the application is assumed to transmit the respective data.

Table A.1053: TransmissionComSpecProps

Class	TransmissionModeCondition			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	Possibility to attach a condition to each signal within an I-PDU. If at least one condition evaluates to true, TRANSMISSION MODE True shall be used for this I-Pdu. In all other cases, the TRANSMISSION MODE FALSE shall be used.			
Base	ARObject			
Aggregated by	TransmissionModeDeclaration.transmissionModeCondition			
Attribute	Type	Mult.	Kind	Note
dataFilter	DataFilter	0..1	aggr	Possibilities to define conditions
iSignalInIPdu	ISignalToIPduMapping	0..1	ref	Reference to a signal to which a condition is attached.

Table A.1054: TransmissionModeCondition

Class	TransmissionModeTiming			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	If the COM Transmission Mode is false the timing is aggregated by the TransmissionModeTiming element in the role of transmissionModeFalseTiming. If the COM Transmission Mode is true the timing is aggregated by the TransmissionModeTiming element in the role of transmissionModeTrueTiming. COM supports the following Transmission Modes: <ul style="list-style-type: none"> • Periodic (Cyclic Timing) • Direct /n-times (EventControlledTiming) • Mixed (Cyclic and EventControlledTiming are assigned) • None (no timing is assigned) 			
Base	ARObject			
Aggregated by	TransmissionModeDeclaration.transmissionModeFalseTiming, TransmissionModeDeclaration.transmissionModeTrueTiming			
Attribute	Type	Mult.	Kind	Note
cyclicTiming	CyclicTiming	0..1	aggr	Periodic Transmission Mode.
eventControlledTiming	EventControlledTiming	0..1	aggr	Direct Transmission Mode.

Table A.1055: TransmissionModeTiming

Class	Trigger			
Package	M2::AUTOSARTemplates::CommonStructure::TriggerDeclaration			
Note	A trigger which is provided (i.e. released) or required (i.e. used to activate something) in the given context.			
Base	ARObject , AtpClassifier , AtpFeature , AtpStructureElement , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	AtpClassifier.atpFeature , BswModuleDescription.releasedTrigger , BswModuleDescription.requiredTrigger , ServiceInterface.trigger , TriggerInterface.trigger			
Attribute	Type	Mult.	Kind	Note
swImplPolicy	SwImplPolicyEnum	0..1	attr	This attribute, when set to value queued, allows for a queued processing of Triggers.
triggerPeriod	MultidimensionalTime	0..1	aggr	Optional definition of a period in case of a periodically (time or angle) driven external trigger.

Table A.1056: Trigger

Class	TriggerIPduSendCondition			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication::Timing			
Note	The condition defined by this class evaluates to true if one of the referenced modeDeclarations (OR associated) is active. The condition is used to define when the Pdu is triggered with the Com_Trigger IPDU Send API call.			
Base	ARObject			
Aggregated by	PduTriggering.triggerIPduSendCondition			
Attribute	Type	Mult.	Kind	Note
mode Declaration	ModeDeclaration	*	ref	Reference to one modeDeclaration which is OR associated in the context of the TriggerIPduSend Condition.

Table A.1057: TriggerIPduSendCondition

Class	TriggerInterface			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	A trigger interface declares a number of triggers that can be sent by an trigger source. Tags: atp.recommendedPackage=PortInterfaces			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , AtpClassifier , AtpType , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , PortInterface , Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
trigger	Trigger	*	aggr	The Trigger of this trigger interface.

Table A.1058: TriggerInterface

Class	TriggerInterfaceMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Defines the mapping of unequal named Triggers in context of two different TriggerInterfaces.			
Base	ARObject , AtpBlueprint , AtpBlueprintable , Identifiable , MultilanguageReferrable , PortInterfaceMapping , Referrable			
Aggregated by	PortInterfaceMappingSet.portInterfaceMapping			
Attribute	Type	Mult.	Kind	Note
triggerMapping	TriggerMapping	*	aggr	Mapping of two Trigger in two different TriggerInterface

Table A.1059: TriggerInterfaceMapping

Class	TriggerMapping			
Package	M2::AUTOSARTemplates::CommonStructure::TriggerDeclaration			
Note	Defines the mapping of two particular unequally named Triggers in the given context.			
Base	ARObject			
Aggregated by	TriggerInterfaceMapping.triggerMapping			
Attribute	Type	Mult.	Kind	Note
firstTrigger	Trigger	0..1	ref	A Trigger to be mapped.
secondTrigger	Trigger	0..1	ref	A Trigger to be mapped.

Table A.1060: TriggerMapping

Class	TriggerPortAnnotation			
Package	M2::AUTOSARTemplates::SWComponentTemplate::ApplicationAttributes			
Note	Annotation to a port used for calibration regarding a certain Trigger.			
Base	ARObject, GeneralAnnotation			
Aggregated by	PortPrototype.triggerPortAnnotation			
Attribute	Type	Mult.	Kind	Note
trigger	Trigger	0..1	ref	The instance of annotated trigger.

Table A.1061: TriggerPortAnnotation

Class	TriggerToSignalMapping			
Package	M2::AUTOSARTemplates::SystemTemplate::DataMapping			
Note	This meta-class represents the ability to map a trigger to a SystemSignal of size 0. The Trigger does not transport any other information than its existence, therefore the limitation in terms of signal length.			
Base	ARObject, DataMapping			
Aggregated by	SystemMapping.dataMapping			
Attribute	Type	Mult.	Kind	Note
systemSignal	SystemSignal	0..1	ref	This is the SystemSignal taken to transport the Trigger over the network. Tags: xml.sequenceOffset=20
trigger	Trigger	0..1	iref	This represents the Trigger that shall be used to trigger RunnableEntities deployed to a remote ECU. Tags: xml.sequenceOffset=10 InstanceRef implemented by: TriggerInSystemInstance Ref

Table A.1062: TriggerToSignalMapping

Class	«atpVariation» TtcanCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ttcan::TtcanTopology			
Note	TTCAN bus specific cluster attributes. Tags: atp.recommendedPackage=CommunicationClusters			
Base	ARElement, ARObject, AbstractCanCluster, CollectableElement, CommunicationCluster , FibexElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , UploadableDesignElement , UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note





Class	«atpVariation» TtcanCluster			
basicCycleLength	Integer	0..1	attr	Length of a basic-cycle. Unit: NTUs
ntu	TimeValue	0..1	attr	Unit measuring all times and providing a constant of the whole network. For level 1, this is always the CAN bit time. Unit: seconds.
operationMode	Boolean	0..1	attr	Possible operation modes True: Time-Triggered False: Event-Synchronised-Time-Triggered

Table A.1063: TtcanCluster

Class	UdpNmCluster			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	Udp specific NmCluster attributes			
Base	ARObject , Identifiable , MultilanguageReferrable , NmCluster , Referrable			
Aggregated by	NmConfig.nmCluster			
Attribute	Type	Mult.	Kind	Note
nmCbvPosition	Integer	0..1	attr	Defines the position of the control bit vector within the Nm Pdu (Byte position). If this attribute is not configured, the Control Bit Vector is not used.
nmImmediateNmCycleTime	TimeValue	0..1	attr	Defines the immediate NmPdu cycle time in seconds which is used for nmImmediateNmTransmissions NmPdu transmissions. This attribute is only valid if nmImmediateNmTransmissions is greater one.
nmImmediateNmTransmissions	PositiveInteger	0..1	attr	Defines the number of immediate NmPdus which shall be transmitted. If the value is zero no immediate NmPdus are transmitted. The cycle time of immediate NmPdus is defined by nmImmediateNmCycleTime.
nmMessageTimeoutTime	TimeValue	0..1	attr	Timeout of a NmPdu in seconds. It determines how long the NM shall wait with notification of transmission failure while communication errors occur on the bus.
nmMsgCycleTime	TimeValue	0..1	attr	Period of a NmPdu in seconds. It determines the periodic rate in the periodic transmission mode with bus load reduction and is the basis for transmit scheduling in the periodic transmission mode without bus load reduction.
nmNetworkTimeout	TimeValue	0..1	attr	Network Timeout for NmPdus in seconds. It denotes the time how long the UdpNm shall stay in the Network Mode before transition into Prepare Bus-Sleep Mode shall take place.
nmNidPosition	Integer	0..1	attr	Defines the byte position of the source node identifier within the NmPdu. If this attribute is not configured, the Node Identification is not used.
nmRemoteSleepIndicationTime	TimeValue	0..1	attr	Timeout for Remote Sleep Indication in seconds. It defines the time how long it shall take to recognize that all other nodes are ready to sleep.
nmRepeatMessageTime	TimeValue	0..1	attr	Timeout for Repeat Message State in seconds. Defines the time how long the NM shall stay in the Repeat Message State.
nmWaitBusSleepTime	TimeValue	0..1	attr	Timeout for bus calm down phase in seconds. It denotes the time how long the CanNm shall stay in the Prepare Bus-Sleep Mode before transition into Bus-Sleep Mode shall take place.
vlan	EthernetPhysicalChannel	0..1	ref	Reference to the vlan (represented by the Ethernet PhysicalChannel) this UdpNmCluster shall apply to.

Table A.1064: UdpNmCluster

Class	UdpNmNode			
Package	M2::AUTOSARTemplates::SystemTemplate::NetworkManagement			
Note	Udp specific NM Node attributes.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>NmNode</i> , <i>Referrable</i>			
Aggregated by	<i>NmCluster.nmNode</i>			
Attribute	Type	Mult.	Kind	Note
allNmMessages KeepAwake	Boolean	0..1	attr	Specifies if Nm drops irrelevant NM PDUs. false: Only NM PDUs with a Partial Network Information Bit (PNI) = true and containing a Partial Network request for this ECU trigger the standard RX indication handling and thus keep the ECU awake true: Every NM PDU triggers the standard RX indication handling and keeps the ECU awake
nmMsgCycle Offset	TimeValue	0..1	attr	Node specific time offset in the periodic transmission node. It determines the start delay of the transmission. Specified in seconds.

Table A.1065: UdpNmNode

Class	UdpProps			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	This meta-class specifies the configuration options for UDP (User Datagram Protocol).			
Base	<i>ARObject</i>			
Aggregated by	<i>EthTcplpProps.udpProps</i>			
Attribute	Type	Mult.	Kind	Note
udpTtl	PositiveInteger	0..1	attr	Default Time-to-live value of outgoing UDP packets.

Table A.1066: UdpProps

Class	UdpTp			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Content Model for UDP configuration.			
Base	<i>ARObject</i> , <i>TcpUdpConfig</i> , <i>TransportProtocolConfiguration</i>			
Aggregated by	<i>ApApplicationEndpoint.tpConfiguration</i> , <i>ApplicationEndpoint.tpConfiguration</i> , <i>RtpTp.tcpUdpConfig</i>			
Attribute	Type	Mult.	Kind	Note
udpTpPort	<i>TpPort</i>	0..1	aggr	Udp Port configuration.

Table A.1067: UdpTp

Class	UnassignFrameId			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Lin::LinCommunication			
Note	Schedule entry for an Unassign Frame Id master request where the protected identifier is assigned the value 0x40. This will disable reception/transmission of a previously dynamically assigned frame identifier.			
Base	<i>ARObject</i> , <i>LinConfigurationEntry</i> , <i>ScheduleTableEntry</i>			
Aggregated by	<i>LinScheduleTable.tableEntry</i>			
Attribute	Type	Mult.	Kind	Note
unassigned FrameTriggering	<i>LinFrameTriggering</i>	0..1	ref	The frame whose identifier is reset by this assignment.

Table A.1068: UnassignFrameId

Class	Unit			
Package	M2::MSR::AsamHdo::Units			
Note	<p>This is a physical measurement unit. All units that might be defined should stem from SI units. In order to convert one unit into another factor and offset are defined.</p> <p>For the calculation from SI-unit to the defined unit the factor (factorSiToUnit) and the offset (offsetSiToUnit) are applied as follows:</p> $x \{unit\} := y * \{siUnit\} * factorSiToUnit \{unit\} / \{siUnit\} + offsetSiToUnit \{unit\}$ <p>For the calculation from a unit to SI-unit the reciprocal of the factor (factorSiToUnit) and the negation of the offset (offsetSiToUnit) are applied.</p> $y \{siUnit\} := (x * \{unit\} - offsetSiToUnit \{unit\}) / (factorSiToUnit \{unit\} / \{siUnit\})$ <p>Tags: atp.recommendedPackage=Units</p>			
Base	ARElement, ARObject, CollectableElement, Identifiable, MultilanguageReferrable, PackageableElement, Referrable			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
displayName	SingleLanguageUnitNames	0..1	aggr	<p>This specifies how the unit shall be displayed in documents or in user interfaces of tools. The displayName corresponds to the Unit.Display in an ASAM MCD-2MC file.</p> <p>Tags: xml.sequenceOffset=20</p>
factorSiToUnit	Float	0..1	attr	<p>This is the factor for the conversion from SI Units to units. The inverse is used for conversion from units to SI Units.</p> <p>Tags: xml.sequenceOffset=30</p>
offsetSiToUnit	Float	0..1	attr	<p>This is the offset for the conversion from and to siUnits.</p> <p>Tags: xml.sequenceOffset=40</p>
physicalDimension	PhysicalDimension	0..1	ref	<p>This association represents the physical dimension to which the unit belongs to. Note that only values with units of the same physical dimensions might be converted.</p> <p>Tags: xml.sequenceOffset=50</p>

Table A.1069: Unit

Primitive	UnlimitedInteger
Package	M2::AUTOSARTemplates::GenericStructure::GeneralTemplateClasses::PrimitiveTypes
Note	<p>An instance of UnlimitedInteger is an element in the set of integer numbers (..., -2, -1, 0, 1, 2, ...).</p> <p>The range is limited by constraint 2534.</p> <p>The value can be expressed in decimal, octal, hexadecimal and binary representation. Negative numbers can only be expressed in decimal notation.</p> <p>Tags: xml.xsd.customType=UNLIMITED-INTEGER xml.xsd.pattern=0[\+ -]?[1-9][0-9]* 0[xX][0-9a-fA-F]+ 0[bB][0-1]+ 0[0-7]+ xml.xsd.type=string</p>

Table A.1070: UnlimitedInteger

Class	UserDefinedIPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	UserDefinedIPdu allows to describe PDU-based communication over Complex Drivers. If a new BSW module is added above the PduR (e.g. a Diagnostic Service) then this IPdu element shall be used to describe the communication. Tags: atp.recommendedPackage=Pdus			
Base	ARElement, ARObject, CollectableElement, FibexElement, IPdu, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
cddType	String	0..1	attr	This attribute defines the CDD that transmits or receives the UserDefinedPdu. If several CDDs are defined this attribute is used to distinguish between them.

Table A.1071: UserDefinedIPdu

Class	UserDefinedPdu			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::FibexCore::CoreCommunication			
Note	UserDefinedPdu allows to describe PDU-based communication over Complex Drivers. If a new BSW module is added above the BusIf (e.g. a new Nm module) then this Pdu element shall be used to describe the communication. Tags: atp.recommendedPackage=Pdus			
Base	ARElement, ARObject, CollectableElement, FibexElement, Identifiable, MultilanguageReferrable, PackageableElement, Pdu, Referrable, UploadableDesignElement, UploadablePackageElement			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
cddType	String	0..1	attr	This attribute defines the CDD that transmits or receives the UserDefinedIPdu. If several CDDs are defined this attribute is used to distinguish between them.

Table A.1072: UserDefinedPdu

Class	UserDefinedPhysicalChannel			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::CddSupport			
Note	This element allows the modeling of arbitrary Physical Channels.			
Base	ARObject, Identifiable, MultilanguageReferrable, PhysicalChannel, Referrable			
Aggregated by	CommunicationCluster.physicalChannel			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.1073: UserDefinedPhysicalChannel

Class	«atpMixed» ValueList			
Package	M2::MSR::DataDictionary::DataDefProperties			
Note	This is a generic list of numerical values.			
Base	ARObject			
Aggregated by	RuleBasedAxisCont.swArraysize, RuleBasedValueCont.swArraysize, SwAxisCont.swArraysize, SwServiceArg.swArraysize, SwValueCont.swArraysize			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–





Class	«atpMixed» ValueList			
v	Numerical	0..1	attr	This is a particular numerical value without variation. Tags: xml.sequenceOffset=30
vf (ordered)	Numerical	*	attr	This is one entry in the list of numerical values Stereotypes: atpVariation Tags: vh.latestBindingTime=preCompileTime xml.roleElement=true xml.roleWrapperElement=false xml.typeElement=false xml.typeWrapperElement=false

Table A.1074: ValueList

Class	ValueSpecification (abstract)			
Package	M2::AUTOSARTemplates::CommonStructure::Constants			
Note	Base class for expressions leading to a value which can be used to initialize a data object.			
Base	ARObject			
Subclasses	AbstractRuleBasedValueSpecification, ApplicationValueSpecification, CompositeValueSpecification, ConstantReference, NotAvailableValueSpecification, NumericalValueSpecification, ReferenceValueSpecification, TextValueSpecification			
Aggregated by	ApplicationAssocMapElementValueSpecification.key, ApplicationAssocMapElementValueSpecification.value, ArrayValueSpecification.element, CalibrationParameterValue.applInitValue, CalibrationParameterValue.implInitValue, ConstantSpecification.valueSpec, CryptoServiceKey.developmentValue, DiagnosticEnvDataCondition.compareValue, DiagnosticEnvDataElementCondition.compareValue, FieldSenderComSpec.initValue, ISignal.initValue, ISignal.receptionDefaultValue, ISignal.timeoutSubstitutionValue, NonqueuedReceiverComSpec.initValue, NonqueuedReceiverComSpec.timeoutSubstitutionValue, NonqueuedSenderComSpec.initValue, NvProvideComSpec.ramBlockInitValue, NvProvideComSpec.romBlockInitValue, NvRequireComSpec.initValue, ParameterDataPrototype.initValue, ParameterProvideComSpec.initValue, ParameterRequireComSpec.initValue, PersistencyDataRequiredComSpec.initValue, PersistencyKeyValuePair.initValue, PortDefinedArgumentValue.value, PortPrototypeBlueprintInitValue.value, RecordValueSpecification.field, SomeipEventDeployment.eventReceptionDefaultValue, StateManagementCompareCondition.compareValue, SwDataDefProps.invalidValue, UserDefinedEventDeployment.eventReceptionDefaultValue, VariableDataPrototype.initValue			
Attribute	Type	Mult.	Kind	Note
shortLabel	Identifier	0..1	attr	This can be used to identify particular value specifications for human readers, for example elements of a record type.

Table A.1075: ValueSpecification

Class	VariableAccess			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements			
Note	The presence of a VariableAccess implies that a RunnableEntity needs access to a VariableData Prototype. The kind of access is specified by the role in which the class is used.			
Base	ARObject, AbstractAccessPoint, AtpClassifier, AtpFeature, AtpStructureElement, Identifiable, MultilanguageReferrable, Referrable			
Aggregated by	AtpClassifier.atpFeature, ReceiverComSpec.replaceWith, RunnableEntity.dataReadAccess, RunnableEntity.dataReceivePointByArgument, RunnableEntity.dataReceivePointByValue, RunnableEntity.dataSendPoint, RunnableEntity.dataWriteAccess, RunnableEntity.readLocalVariable, RunnableEntity.writtenLocalVariable			
Attribute	Type	Mult.	Kind	Note
accessed Variable	AutosarVariableRef	0..1	aggr	This denotes the accessed variable.





Class	VariableAccess			
scope	VariableAccessScope Enum	0..1	attr	This attribute allows for constraining the scope of the corresponding communication. For example, it possible to express whether the communication is intended to cross the boundary of an ECU or whether it is intended not to cross the boundary of a single partition.

Table A.1076: VariableAccess

Class	VariableAndParameterInterfaceMapping			
Package	M2::AUTOSARTemplates::SWComponentTemplate::PortInterface			
Note	Defines the mapping of VariableDataPrototypes or ParameterDataPrototypes in context of two different SenderReceiverInterfaces, NvDataInterfaces or ParameterInterfaces.			
Base	<i>ARObject</i> , <i>AtpBlueprint</i> , <i>AtpBlueprintable</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>PortInterfaceMapping</i> , <i>Referrable</i>			
Aggregated by	PortInterfaceMappingSet.portInterfaceMapping			
Attribute	Type	Mult.	Kind	Note
dataMapping	DataPrototypeMapping	*	aggr	Defines the mapping of two particular VariableData Prototypes or ParameterDataPrototypes with unequal names and/or unequal semantic (resolution or range) in context of two different SenderReceiverInterfaces, Nv DataInterfaces or ParameterInterfaces Stereotypes: atpSplitable Tags: atp.Splitkey=dataMapping

Table A.1077: VariableAndParameterInterfaceMapping

Class	VariableDataPrototype			
Package	M2::AUTOSARTemplates::SWComponentTemplate::Datatype::DataPrototypes			
Note	A VariableDataPrototype represents a formalized generic piece of information that is typically mutable by the application software layer. VariableDataPrototype is used in various contexts and the specific context gives the otherwise generic VariableDataPrototype a dedicated semantics.			
Base	<i>ARObject</i> , <i>AtpFeature</i> , <i>AtpPrototype</i> , <i>AutosarDataPrototype</i> , <i>DataPrototype</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	ApplicationInterface.indication, <i>AtpClassifier.atpFeature</i> , <i>BswInternalBehavior.arTypedPerInstanceMemory</i> , <i>BswModuleDescription.providedData</i> , <i>BswModuleDescription.requiredData</i> , <i>BulkNvDataDescriptor.bulkNvBlock</i> , <i>InternalBehavior.staticMemory</i> , <i>NvBlockDescriptor.ramBlock</i> , <i>NvDataInterface.nvData</i> , <i>SenderReceiverInterface.dataElement</i> , <i>ServiceInterface.event</i> , <i>SwcInternalBehavior.arTypedPerInstanceMemory</i> , <i>SwcInternalBehavior.explicitInterRunnableVariable</i> , <i>SwcInternalBehavior.implicitInterRunnableVariable</i>			
Attribute	Type	Mult.	Kind	Note
initValue	ValueSpecification	0..1	aggr	Specifies initial value(s) of the VariableDataPrototype

Table A.1078: VariableDataPrototype

Class	VariableDataPrototypeInSystemInstanceRef			
Package	M2::AUTOSARTemplates::SystemTemplate::InstanceRefs			
Note				
Base	<i>ARObject</i> , <i>AtpInstanceRef</i>			





Class	VariableDataPrototypeInSystemInstanceRef			
Aggregated by	EndToEndProtectionVariablePrototype.receiver, EndToEndProtectionVariablePrototype.sender, PortElementToCommunicationResourceMapping.variableDataPrototype, SenderReceiverCompositeElementToSignalMapping.dataElement, SenderReceiverToSignalGroupMapping.dataElement, SenderReceiverToSignalMapping.dataElement, SignalServiceTranslationEventProps.translationTarget, SwcToSwcSignal.dataElement			
Attribute	Type	Mult.	Kind	Note
base	System	0..1	ref	Stereotypes: atpDerived
context Component (ordered)	SwComponent Prototype	*	ref	
context Composition	RootSwComposition Prototype	0..1	ref	
contextPort	PortPrototype	1	ref	
targetData Prototype	VariableDataPrototype	0..1	ref	

Table A.1079: VariableDataPrototypeInSystemInstanceRef

Class	VariableInAtomicSWCTypeInstanceRef			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::DataElements::InstanceRefs Usage			
Note				
Base	ARObject, AtpInstanceRef			
Aggregated by	AutosarVariableRef.autosarVariable			
Attribute	Type	Mult.	Kind	Note
base	AtomicSwComponent Type	0..1	ref	Stereotypes: atpDerived Tags: xml.sequenceOffset=10
contextData Prototype (ordered)	ApplicationComposite ElementDataPrototype	*	ref	This is the context in a compositeDataType. Tags: xml.sequenceOffset=40
portPrototype	PortPrototype	0..1	ref	This is the port providing the parameter or the entry point to the parameter structure. Tags: xml.sequenceOffset=20
rootVariable DataPrototype	VariableDataPrototype	0..1	ref	Tags: xml.sequenceOffset=30
targetData Prototype	DataPrototype	0..1	ref	This is the target of the instance ref. Note that it shall be one of ApplicationCompositeElementDataPrototype of VariableDataPrototype. Tags: xml.sequenceOffset=50

Table A.1080: VariableInAtomicSWCTypeInstanceRef

Class	VariationPoint			
Package	M2::AUTOSARTemplates::GenericStructure::VariantHandling			
Note	This meta-class represents the ability to express a "structural variation point". The container of the variation point is part of the selected variant if swSyscond evaluates to true and each postBuildVariant Criterion is fulfilled.			
Base	ARObject			
Attribute	Type	Mult.	Kind	Note





Class	VariationPoint			
blueprintCondition	DocumentationBlock	0..1	aggr	This represents a description that documents how the variation point shall be resolved when deriving objects from the blueprint. Note that variationPoints are not allowed within a blueprintCondition. Tags: xml.sequenceOffset=28
desc	MultiLanguageOverviewParagraph	0..1	aggr	This allows to describe shortly the purpose of the variation point. Tags: xml.sequenceOffset=20
formalBlueprintGenerator	BlueprintGenerator	0..1	aggr	This represents a description that documents how the variation point shall be resolved when deriving objects from the blueprint by using ARMQL. Note that variationPoints are not allowed within a formalBlueprintGenerator. Tags: atp.Status=draft xml.sequenceOffset=30
postBuildVariantCondition	PostBuildVariantCondition	*	aggr	This is the set of post build variant conditions which all shall be fulfilled in order to (postbuild) bind the variation point. Tags: xml.sequenceOffset=40
sdg	Sdg	0..1	aggr	An optional special data group is attached to every variation point. These data can be used by external software systems to attach application specific data. For example, a variant management system might add an identifier, an URL or a specific classifier. Tags: xml.sequenceOffset=50
shortLabel	Identifier	0..1	attr	This provides a name to the particular variation point to support the RTE generator. It is necessary for supporting splittable aggregations and if binding time is later than codeGenerationTime, as well as some RTE conditions. It needs to be unique with in the enclosing Identifiables with the same ShortName. Stereotypes: atpIdentityContributor Tags: xml.sequenceOffset=10
swSyscond	ConditionByFormula	0..1	aggr	This condition acts as Binding Function for the Variation Point. Note that the multiplicity is 0..1 in order to support pure postBuild variants. Tags: xml.sequenceOffset=30

Table A.1081: VariationPoint

Class	VariationPointProxy			
Package	M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::VariantHandling			
Note	The VariationPointProxy represents variation points of the C/C++ implementation. In case of bindingTime = compileTime the RTE provides defines which can be used for Pre Processor directives to implement compileTime variability.			
Base	<i>ARObject</i> , <i>Identifiable</i> , <i>MultilanguageReferrable</i> , <i>Referrable</i>			
Aggregated by	BswInternalBehavior.variationPointProxy , SwcInternalBehavior.variationPointProxy			
Attribute	Type	Mult.	Kind	Note
conditionAccess	ConditionByFormula	0..1	aggr	This condition acts as Binding Function for the Variation Point.





Class	VariationPointProxy			
implementationDataType	AbstractImplementationDataType	0..1	ref	This association to ImplementationDataType shall be taken as an implementation hint by the RTE generator.
postBuildValueAccess	PostBuildVariantCriterion	0..1	ref	This represents the applicable PostBuildVariantCriterion in the context of a VariationPointProxy. Note that the technical details how to access the particular postBuildValueAccess are still considered internal to the RTE and are consequently not standardized.
postBuildVariantCondition	PostBuildVariantCondition	*	aggr	This represents that applicable PostBuildVariantCondition in the context of aVariationPointProxy.
valueAccess	AttributeValueVariationPoint	0..1	aggr	This value acts as Binding Function for the VariationPoint.

Table A.1082: VariationPointProxy

Class	VfbTiming			
Package	M2::AUTOSARTemplates::CommonStructure::Timing::TimingExtensions			
Note	A model element used to define timing descriptions and constraints at VFB level. TimingDescriptions aggregated by VfbTiming are restricted to event chains referring to events which are derived from the class TDEventVfb. Tags: atp.recommendedPackage=TimingExtensions			
Base	ARElement , ARObject , AtpBlueprint , AtpBlueprintable , CollectableElement , Identifiable , MultilanguageReferrable , PackageableElement , Referrable , TimingExtension			
Aggregated by	ARPackage.element			
Attribute	Type	Mult.	Kind	Note
component	SwComponentType	0..1	ref	This defines the scope of a VfbTiming. All corresponding timing descriptions and constraints shall be defined within this scope.

Table A.1083: VfbTiming

Class	VlanConfig			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	VLAN Configuration attributes			
Base	ARObject , Identifiable , MultilanguageReferrable , Referrable			
Aggregated by	EthernetPhysicalChannel.vlan			
Attribute	Type	Mult.	Kind	Note
vlanIdentifier	PositiveInteger	0..1	attr	A VLAN is identified by this attribute according to IEEE 802.1Q. The allowed values range is from 0..4095.

Table A.1084: VlanConfig

Class	VlanMembership			
Package	M2::AUTOSARTemplates::SystemTemplate::Fibex::Fibex4Ethernet::EthernetTopology			
Note	Static logical channel or VLAN binding to a switch-port. The reference to an EthernetPhysicalChannel without a VLAN defined represents the handling of untagged frames.			
Base	ARObject			





Class		VlanMembership		
Aggregated by		CouplingPort.vlanMembership		
Attribute	Type	Mult.	Kind	Note
defaultPriority	PositiveInteger	0..1	attr	Standard output-priority outgoing Frames will be tagged with. Defines the priority that received frames are assigned together with the VLAN Id (defaultVlan). The values from 0 (best effort) to 7 (highest) are allowed. In case modifyVlan and an already tagged received frame, the actual priority of the received frame is not modified.
dhcpAddress Assignment	DhcpServer Configuration	0..1	aggr	Specifies the IP Address which will be assigned to a DHCP Client at this SwitchPort. If no dhcpAddress Assignment is provided all DHCP-Discover messages received at this Port will be discarded by the DHCP Server.
sendActivity	EthernetSwitchVlan EgressTaggingEnum	0..1	attr	Attribute denotes whether a VLAN tagged ethernet frame will be 1. sent with its VLAN tag (sentTagged) 2. sent without a VLAN tag (sentUntagged) 3. will be dropped at this port (notSent or VLAN not member of this list)
vlan	EthernetPhysical Channel	0..1	ref	References a channel that represents a VLAN or an untagged channel.

Table A.1085: VlanMembership

Class		WaitPoint		
Package		M2::AUTOSARTemplates::SWComponentTemplate::SwcInternalBehavior::RTEEvents		
Note		This defines a wait-point for which the RunnableEntity can wait.		
Base		ARObject, Identifiable, MultilanguageReferrable, Referrable		
Aggregated by		RunnableEntity.waitPoint		
Attribute	Type	Mult.	Kind	Note
timeout	TimeValue	0..1	attr	Time in seconds before the WaitPoint times out and the blocking wait call returns with an error indicating the timeout.
trigger	RTEEvent	0..1	ref	This is the RTEEvent this WaitPoint is waiting for.

Table A.1086: WaitPoint

Class		WorstCaseHeapUsage		
Package		M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::HeapUsage		
Note		Provides a formal worst case heap usage.		
Base		ARObject, HeapUsage, Identifiable, MultilanguageReferrable, Referrable		
Aggregated by		ResourceConsumption.heapUsage		
Attribute	Type	Mult.	Kind	Note
memory Consumption	PositiveInteger	0..1	attr	Worst case heap consumption. Unit: byte.

Table A.1087: WorstCaseHeapUsage

Class	WorstCaseStackUsage			
Package	M2::AUTOSARTemplates::CommonStructure::ResourceConsumption::StackUsage			
Note	Provides a formal worst case stack usage.			
Base	ARObject, Identifiable , MultilanguageReferrable , Referrable , StackUsage			
Aggregated by	ResourceConsumption.stackUsage			
Attribute	Type	Mult.	Kind	Note
memory Consumption	PositiveInteger	0..1	attr	Worst case stack consumption. Unit: byte.

Table A.1088: WorstCaseStackUsage

Class	Xdoc			
Package	M2::MSR::Documentation::TextModel::InlineTextElements			
Note	This meta-class represents the ability to refer to an external document which can be rendered as printed matter.			
Base	ARObject, Referrable , SingleLanguageReferrable			
Aggregated by	MixedContentForParagraph.xdoc			
Attribute	Type	Mult.	Kind	Note
date	DateTime	0..1	attr	This element specifies the release date of the external document if applicable. Tags: xml.sequenceOffset=50
number	String	0..1	attr	This represents document number of an external document that is referenced. Kept as a string. Tags: xml.sequenceOffset=30
position	String	0..1	attr	This represents the reference to the relevant positions of a standard. Kept as a string. Tags: xml.sequenceOffset=80
publisher	String	0..1	attr	This represents the publisher of an external document that is being referenced. Kept as a string. Tags: xml.sequenceOffset=60
state	String	0..1	attr	This represents version and state of the external document. Kept as a string. Tags: xml.sequenceOffset=40
url	Url	0..1	aggr	This specifies the URL of the external document. Tags: xml.sequenceOffset=70

Table A.1089: Xdoc

Class	Xfile			
Package	M2::MSR::Documentation::TextModel::InlineTextElements			
Note	This represents to reference an external file within a documentation.			
Base	ARObject, Referrable , SingleLanguageReferrable			
Aggregated by	MixedContentForParagraph.xfile			
Attribute	Type	Mult.	Kind	Note
tool	String	0..1	attr	This element describes the tool which was used to generate the corresponding Xfile . Kept as a string since no specific syntax can be provided to denote a tool. Tags: xml.sequenceOffset=50





Class	Xfile			
toolVersion	String	0..1	attr	This element describes the tool version which was used to generate the corresponding xfile. Kept as a string, since no specific syntax can be specified. Tags: xml.sequenceOffset=60
url	Url	0..1	aggr	This represents the URL of the external file. Tags: xml.sequenceOffset=30

Table A.1090: Xfile

Class	XrefTarget			
Package	M2::MSR::Documentation::TextModel::InlineTextElements			
Note	This element specifies a reference target which can be scattered throughout the text.			
Base	<i>ARObject</i> , Referrable , <i>SingleLanguageReferrable</i>			
Aggregated by	<i>MixedContentForOverviewParagraph.xrefTarget</i> , MixedContentForParagraph.xrefTarget			
Attribute	Type	Mult.	Kind	Note
–	–	–	–	–

Table A.1091: XrefTarget

B Change history of AUTOSAR traceable items

Please note that the lists in this chapter also include traceable items that have been removed from the specification in a later version. These items do not appear as hyperlinks in the document.

B.1 Traceable item history of this document according to AUTOSAR Release R24-11

B.1.1 Added Constraints in R24-11

Number	Heading
[constr_10520]	Multiplicity of AssemblySwConnector.provider
[constr_10521]	Multiplicity of AssemblySwConnector.requester
[constr_10522]	OBD trouble code shall only be placed in primary fault memory
[constr_10523]	Existence of role DiagnosticTroubleCodeUdsToTroubleCodeObdMapping.troubleCodeUds
[constr_10524]	Existence of role DiagnosticTroubleCodeUdsToTroubleCodeObdMapping.troubleCodeObd
[constr_10525]	Existence of attribute ApplicationValueSpecification.category
[constr_10527]	Existence of RoleBasedDataAssignment.usedDataElement . autosarVariable for RoleBasedDataAssignment.role = ramBlock
[constr_10529]	Existence of AsynchronousServerCallResultPoint for AsynchronousServerCallPoint where attribute timeout is defined
[constr_10532]	Restriction for SenderComSpec.transmissionProps . onChangeDataPrototype
[constr_10533]	Existence of TransmissionComSpecProps.onChangeDataPrototype . dataPrototypeInSenderReceiverInterface.rootDataPrototypeInSr
[constr_10534]	Existence of TransmissionComSpecProps.onChangeDataPrototype . rootDataPrototype
[constr_10538]	Existence of attribute ReceiverComSpec.dataElement
[constr_10539]	Existence of attribute SenderComSpec.dataElement
[constr_10542]	RunnableEntity is referenced by an OperationInvokedEvent
[constr_10543]	Uniqueness of reference PortAPIOption.port
[constr_10544]	Ownership of reference PortAPIOption.port
[constr_10545]	Existence of DiagnosticParameterIdentifier.dataElement .
[constr_10548]	Uniqueness of ReceiverComSpec.dataElement
[constr_10549]	Uniqueness of SenderComSpec.dataElement
[constr_10550]	Uniqueness of ClientComSpec.operation
[constr_10551]	Uniqueness of ServerComSpec.operation
[constr_10552]	Uniqueness of ModeSwitchSenderComSpec.modeGroup





Number	Heading
[constr_10553]	Uniqueness of <code>ModeSwitchReceiverComSpec.modeGroup</code>
[constr_10554]	Uniqueness of <code>ParameterProvideComSpec.parameter</code>
[constr_10555]	Uniqueness of <code>ParameterRequireComSpec.parameter</code>
[constr_10556]	Uniqueness of <code>NvRequireComSpec.variable</code>
[constr_10557]	Uniqueness of <code>NvProvideComSpec.variable</code>
[constr_10558]	<code>SwBaseType</code> associated with corresponding <code>ApplicationRecordElement</code> and <code>ImplementationDataTypeElement</code>
[constr_10559]	Uniqueness of <code>DataPrototypeMapping.firstDataPrototype</code> and <code>secondDataPrototype</code>
[constr_10560]	Uniqueness of <code>ClientServerOperationMapping.firstOperation</code> and <code>secondOperation</code>
[constr_10561]	Uniqueness of <code>ClientServerApplicationErrorMapping.firstApplicationError</code> and <code>secondApplicationError</code>
[constr_10562]	Uniqueness of <code>ModeDeclarationGroupPrototypeMapping.firstModeGroup</code> and <code>secondModeGroup</code>
[constr_10563]	Uniqueness of <code>ModeDeclarationMapping.firstMode</code> and <code>secondMode</code>
[constr_10564]	Uniqueness of <code>TriggerMapping.firstTrigger</code> and <code>secondTrigger</code>
[constr_10565]	Uniqueness of <code>SubElementMapping.firstElement</code> and <code>secondElement</code>
[constr_10573]	Existence of attribute <code>DiagnosticServiceTable.diagnosticServiceInstance</code>
[constr_10575]	No multiple instantiation of <code>NvBlockSwComponentType</code>
[constr_10577]	Existence of <code>DiagnosticResponseOnEventClass.storeEventEnabled</code>
[constr_10606]	Existence of <code>ConstantSpecificationMapping</code> or <code>CalibrationParameterValue</code> for <code>ApplicationValueSpecification</code> or <code>ApplicationRuleBasedValueSpecification</code> of category <code>CURVE</code> , <code>MAP</code> , <code>CUBOID</code> , <code>CUBE_4</code> , and <code>CUBE_5</code>
[constr_10607]	Number of <code>ConstantSpecificationMappings</code> that are allowed to reference a <code>ApplicationValueSpecification</code> or <code>ApplicationRuleBasedValueSpecification</code> in the context of an <code>InternalBehavior</code>
[constr_10608]	Number of <code>ConstantSpecificationMappings</code> that are allowed to reference a <code>ApplicationValueSpecification</code> or <code>ApplicationRuleBasedValueSpecification</code> in the context of a <code>ParameterSwComponentType</code>
[constr_10610]	Compatibility of <code>PhysicalDimensions</code> in the context is the creation of an <code>ApplicationValueSpecification</code>
[constr_3763]	Allowed value for <code>maxDeltaCounter</code> in the context of a <code>profileName</code>
[constr_3764]	Applicability of <code>CouplingPort.macAddressVlanAssignment</code>
[constr_3765]	Applicability of <code>MacAddressVlanMembership.vlan</code>
[constr_3766]	Valid <code>MacAddressVlanMembership.vlan</code> target <code>EthernetPhysicalChannel</code>
[constr_3767]	<code>NmNode.nmVariant</code> setting to <code>slavePassive</code>
[constr_3768]	<code>NmNode.nmVariant</code> setting to <code>slaveActive</code>
[constr_3769]	<code>NmNode.nmVariant</code> setting to <code>full</code>





Number	Heading
[constr_3770]	NmNode.nmVariant setting to passive
[constr_3771]	Range of NmCluster.nmLightTimeout
[constr_3779]	Number of ISignal.receptionDefaultValue elements
[constr_3780]	ISignal.receptionDefaultValue definition in case that the SOME/IP Serializer receives less data than expected
[constr_3781]	Each PNC assigned to multiple PhysicalChannels shall have a top level PNC-Coordinator
[constr_3782]	Consistent framePreemptionSupport setting in the scope of one CouplingPortConnection
[constr_3783]	Definition of CouplingPortFifo.trafficClassPreemptionSupport only in context of an Ethernet switch
[constr_3784]	Applicable CouplingPortFifo as predecessor for portScheduler = enhancedTrafficShaper
[constr_3785]	Exclusive definition of etsAvailableBandwidthInPercent or etsAvailableBandwidthInWeightValue
[constr_3786]	Consistent usage of either etsAvailableBandwidthInPercent or etsAvailableBandwidthInWeightValue for portScheduler = enhancedTrafficShaper
[constr_3787]	Existence of CouplingPortTrafficClassAssignment.trafficClass
[constr_3788]	Existence of CouplingPortFifo.assignedTrafficClass
[constr_3789]	Allowed values for CouplingPortFifo.assignedTrafficClass
[constr_3790]	Existence of CouplingPortDetails.defaultTrafficClass
[constr_3791]	Allowed values for CouplingPortDetails.defaultTrafficClass
[constr_3792]	FrameMapping between identical bus systems
[constr_3793]	Usage of KeepLocalPduBuffer
[constr_3794]	Usage of PduBufferAlignment
[constr_6918]	Referenced TimingDescriptions in TDCpSoftwareClusterMapping and TDCpSoftwareClusterResourceMapping
[constr_6919]	Referenced CpSoftwareCluster of TDCpSoftwareClusterMapping
[constr_6920]	Existence of LatencyTimingConstraint.minimum used in an LET interval
[constr_6921]	Disallow TimingDescriptionEventChain segmental circular-referencing
[constr_9316]	Multi instantiated BSW Modules not mappable
[constr_9317]	StateDependentFirewall.firewallStateModeDeclaration reference restriction
[constr_9318]	Reception of CanFrameTriggerings with the same identifier by an EcuInstance
[constr_9319]	Value of BusMirrorChannelMappingCan.mirroringProtocol
[constr_9320]	Value of BusMirrorChannelMappingFlexray.mirroringProtocol
[constr_9321]	Same time base for all BusMirrorChannelMappings of one EcuInstance
[constr_9326]	Exclusive existence of ISignalTriggering.iSignal and ISignalTriggering.iSignalGroup





Number	Heading
[constr_9330]	Derivation of network representation in case that several DataMappings are defined that map the same SystemSignal to different VariableDataPrototypes
[constr_9331]	E2E protection of a ClientServerOperation
[constr_9332]	Existence of J1939TpConnection.tpProtocolType
[constr_9333]	FibexElements in ECU_EXTRACT
[constr_9343]	Allowed J1939ProtectedIPdu.payload reference target
[constr_9346]	Existence of EthernetVlanTranslationTable.translatedVlanId
[constr_9347]	Range of EthernetVlanTranslationTable.ingressVlanId and EthernetVlanTranslationTable.translatedVlanId
[constr_9348]	EthernetVlanTranslationTable.translatedVlanId and vlanMembership

Table B.1: Added Constraints in R24-11

B.1.2 Changed Constraints in R24-11

Number	Heading
[constr_1000]	End-to-end protection is limited to sender/receiver communication
[constr_1001]	Value of dataId shall be unique
[constr_1002]	End-to-end protection does not support n:1 communication
[constr_10024]	Existence of reference in the role DiagnosticSecurityEventReportingModeMapping.dataElement
[constr_1007]	Allowed attributes of SwDataDefProps for ApplicationDataTypes
[constr_10088]	Relation between event and DTC without event combination
[constr_10099]	Allowed values of the attribute SwDataDefProps.swImplPolicy vs. DataPrototypes and their roles
[constr_1012]	Value of category is FIXED_LENGTH
[constr_1053]	Compatibility of PhysicalDimensions in the context of the creation of a SwConnector
[constr_1070]	Compatibility of PortPrototypes of different DataInterfaces in the context of DelegationSwConnectors
[constr_1087]	AssemblySwConnector inside CompositionSwComponentType
[constr_1088]	DelegationSwConnector inside CompositionSwComponentType
[constr_1111]	Constraints of dataId in PROFILE_01
[constr_1112]	Constraints of dataIdMode in PROFILE_01
[constr_1113]	Existence of attributes of meta-class EndToEndDescription in PROFILE_01
[constr_1114]	Constraints of crcOffset in PROFILE_01
[constr_1115]	Constraints of counterOffset in PROFILE_01
[constr_1116]	Constraints of dataLength in PROFILE_01





Number	Heading
[constr_1117]	Constraints of maxDeltaCounterInit in PROFILE_01
[constr_1118]	Existence of attributes of meta-class EndToEndDescription in PROFILE_02
[constr_1119]	Constraints of dataLength in PROFILE_02
[constr_1120]	Constraints of dataId in PROFILE_02
[constr_1121]	Constraints of maxDeltaCounterInit in PROFILE_02
[constr_1170]	Existence of attribute EndToEndDescription.maxDeltaCounterInit for PROFILE_01
[constr_1171]	Existence of attribute EndToEndDescription.maxDeltaCounterInit for PROFILE_02
[constr_1183]	EndToEndProtectionVariablePrototypes aggregated by EndToEndProtection
[constr_1211]	Constraints of maxNoNewOrRepeatedData in PROFILE_01
[constr_1212]	Constraints of syncCounterInit in PROFILE_01
[constr_1213]	Constraints of maxNoNewOrRepeatedData in PROFILE_02
[constr_1214]	Constraints of syncCounterInit in PROFILE_02
[constr_1215]	Existence of attribute EndToEndDescription.maxNoNewOrRepeatedData for PROFILE_01
[constr_1216]	Existence of attribute EndToEndDescription.syncCounterInit for PROFILE_01
[constr_1217]	Existence of attribute EndToEndDescription.maxNoNewOrRepeatedData for PROFILE_02
[constr_1218]	Existence of attribute EndToEndDescription.syncCounterInit for PROFILE_02
[constr_1261]	Applicability for EndToEndDescription.dataIdNibbleOffset
[constr_1295]	PortInterfaces and category DATA_REFERENCE
[constr_1349]	Value of udsDtcValue shall be unique
[constr_1363]	Existence of attributes of DiagnosticValueNeeds
[constr_1519]	Existence of attributes vs. category of ApplicationValueSpecification
[constr_1768]	Existence of attribute DiagnosticEvent.associatedEventIdentification
[constr_1829]	Existence of reference DiagnosticConnectedIndicator.indicator
[constr_1901]	Existence of attribute EndToEndDescription.category
[constr_1902]	Existence of attribute EndToEndProtection.endToEndProfile
[constr_1986]	Existence of the reference DiagnosticRoutineNeeds.diagRoutineType
[constr_3153]	E2E header field reservation required by COM Based transformer
[constr_3163]	EndToEndTransformationISignalProps.minDataLength and EndToEndTransformationISignalProps.maxDataLength in PROFILE_04, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, and PROFILE_76
[constr_3164]	EndToEndTransformationISignalProps.dataLength in PROFILE_04, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, and PROFILE_76





Number	Heading
[constr_3167]	Effect of EndToEndTransformationDescription.upperHeaderBitsToShift value in PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m and PROFILE_76
[constr_3169]	EndToEndTransformationDescription.offset value in PROFILE_02, PROFILE_22 and PROFILE_76
[constr_3174]	EndToEndTransformationDescription settings not allowed in PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_11, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m and PROFILE_76
[constr_3186]	Multiplicity of EndToEndTransformationDescription.dataIdMode in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76
[constr_3188]	Multiplicity of EndToEndTransformationDescription.counterOffset in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76
[constr_3190]	Multiplicity of EndToEndTransformationDescription.crcOffset in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76
[constr_3192]	Multiplicity of EndToEndTransformationDescription.dataIdNibbleOffset in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m and PROFILE_76 or dataIdMode different from lower12Bit
[constr_3194]	Multiplicity of EndToEndTransformationDescription.offset in PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_08, PROFILE_22, PROFILE_04m, PROFILE_07m, PROFILE_08m, PROFILE_44, PROFILE_44m, PROFILE_76
[constr_3257]	TimeSyncTechnology of servers and clients in a time synchronized network.
[constr_3267]	PduTriggerings in Service Discovery StaticSocketConnections
[constr_3268]	Service Discovery StaticSocketConnection aggregation by a SocketAddress
[constr_3269]	Service Discovery StaticSocketConnection remoteAddress reference to a TpPort
[constr_3270]	Service Discovery SocketConnection remoteAddress reference to an IP Address
[constr_3272]	SoConIPduIdentifier.headerId setting for SD StaticSocketConnections
[constr_3273]	Service Discovery multicast StaticSocketConnection 's aggregation by an ApplicationEndpoint
[constr_3274]	Service Discovery unicast StaticSocketConnection 's aggregation by an ApplicationEndpoint
[constr_3519]	Value of category of GlobalTimeDomain





Number	Heading
[constr_3600]	Setting of EthernetCommunicationController.slaveActAsPassiveCommunicationSlave
[constr_3697]	Latest existence time of CanControllerXlConfiguration and CanControllerXlConfigurationRequirements
[constr_3714]	Multiple top level PNC-coordinators shall be allowed
[constr_3716]	SecuredIPdu.dynamicRuntimeLengthHandling for dynamic length Pdus
[constr_4014]	Call type and execution context
[constr_4016]	BswCalledEntity constraints
[constr_4018]	BswInterruptEntity constraints
[constr_4071]	Synchronized runnables and schedulable entities shall be consistent
[constr_4089]	Association callbackHeader is only applicable for BSW modules
[constr_4090]	The callbackHeader reference has to be consistent with behavior reference
[constr_4102]	Semantics of McGroupDataRefSet.mcDataInstance
[constr_4500]	Restricted usage of Occurrence Expression functions
[constr_4502]	Use references only as function operands
[constr_4503]	Restricted usage of AutosarOperationArgumentInstance for Content Filter
[constr_4504]	Restriction of the scope of an AgeConstraint
[constr_4505]	Specifying minimum and maximum number of occurrences
[constr_4506]	Specifying minimum inter-arrival time and pattern length
[constr_4507]	Specifying pattern length, pattern jitter and patten period
[constr_4508]	Existence of TDEventVfbPort.portPrototypeBlueprint
[constr_4510]	Specifying references to RunnableEntity and VariableAccess
[constr_4511]	Validity of referencing RunnableEntity
[constr_4512]	Validity of referencing VariableAccess
[constr_4513]	SynchronizationTimingConstraint shall reference at least two events
[constr_4514]	SynchronizationTimingConstraint shall reference at least two event chains
[constr_4515]	Orthogonality of stimulus and response in a TimingDescriptionEventChain
[constr_4516]	Completeness of a composed TimingDescriptionEventChain
[constr_4518]	Specifying end-points of a composed TimingDescriptionEventChain
[constr_4519]	Specifying patternLength
[constr_4520]	Specifying attribute synchronizationConstraintType
[constr_4521]	Specifying attribute synchronizationConstraintType
[constr_4522]	SynchronizationTimingConstraint shall either reference events or event chains
[constr_4523]	Restriction of maxCycleRepetitions and maxSlotsPerCycle to Repetitive Execution Order Constraint
[constr_4525]	Precedence of successor relationships successor and directSuccessor
[constr_4526]	Specifying maxCycles and maxSlots in a Repetitive Execution Order Constraint
[constr_4527]	Referencing TimingDescriptionEvent in a Repetitive Execution Order Constraint





Number	Heading
[constr_4528]	The <i>root</i> EOCExecutableEntityRefGroup shall reference only EOCExecutableEntityRefGroups
[constr_4529]	Number of nested elements referenced by the <i>root</i> EOCExecutableEntityRefGroup
[constr_4530]	An EOCExecutableEntityRefGroup representing a cycle shall reference only EOCExecutableEntityRefs respectively EOCEventRefs
[constr_4531]	Number of nested elements referenced by EOCExecutableEntityRefGroup representing a cycle
[constr_4532]	Successor relationship is not self-referencing
[constr_4533]	Maximum number of successor relationships
[constr_4534]	Maximum number of directSuccessor relationships
[constr_4536]	Compatible recurrence of any ExecutableEntity
[constr_4537]	References among elements in an ExecutionOrderConstraint
[constr_4538]	Hierarchical Execution Order Constraint: EOCExecutableEntityRef , EOCEventRef , and EOCExecutableEntityRefGroup shall be target or source of a successor relationship
[constr_4539]	The successor relationships successor and directSuccessor shall not be used
[constr_4540]	maxCycles and maxSlots shall not be zero
[constr_4541]	Existence of EOCExecutableEntityRef.executable in an Ordinary Execution Order Constraint
[constr_4542]	Existence of EOCExecutableEntityRef.executable in a Hierarchical Execution Order Constraint
[constr_4543]	Maximum value of minimumInterArrivalTime
[constr_4544]	Specifying patternLength , patternJitter and patternPeriod
[constr_4545]	Referring either ExecutableEntities or AbstractEvents
[constr_4546]	Setting the attribute isEvent
[constr_4547]	Restriction of ExecutionOrderConstraint . permitMultipleReferencesToEE
[constr_4548]	Existence of EOCEventRef.event in an Ordinary Execution Order Constraint
[constr_4549]	Existence of EOCEventRef.event in a Hierarchical Execution Order Constraint
[constr_4551]	Use only Numericals in TDEventOccurrenceExpression
[constr_4552]	Restricted usage of AutosarVariableInstance for Content Filter
[constr_4554]	Restriction of the referenced TimingDescriptionEventChain for a letInterval
[constr_4559]	Restriction of TimingDescriptionEvent.category
[constr_4561]	Usage of the category value <code>DISPATCH_ENTRY_POINT</code> in TimingDescriptionEvent
[constr_4562]	Usage of the category value <code>DISPATCH_EXIT_POINT</code> in TimingDescriptionEvent
[constr_4565]	Consistency of TDCpSoftwareClusterMapping.timingDescription and TDCpSoftwareClusterResourceMapping.timingDescription
[constr_5049]	Ethernet switch packet to traffic class assignment restriction





Number	Heading
[constr_5091]	Relevance of <code>tcpRole</code> attribute
[constr_5105]	Mapping of <code>Pdu</code> with dynamic length in a <code>FlexrayFrame</code>
[constr_5168]	<code>pncGatewayType</code> <code>passive</code> and connected ECUs
[constr_5221]	Multiplicity of <code>EndToEndTransformationISignalProps.sourceId</code> in PROFILE_01, PROFILE_02, PROFILE_04, PROFILE_05, PROFILE_06, PROFILE_07, PROFILE_11, PROFILE_22, and PROFILE_76
[constr_5273]	One <code>ISignalTriggering</code> pair allowed per <code>EthernetPhysicalChannel</code> for a <code>ClientServerOperation</code>
[constr_5380]	Assignment of the same event <code>Pdu</code> to several <code>EventHandlers</code> is forbidden in case one of the <code>EventHandlers</code> has the <code>multicastThreshold</code> set to a value greater than 0 in the context of an <code>EcuInstance</code>
[constr_6816]	Restricted usage of <code>TimingDescriptionEventChain.isPipeliningPermitted</code> in <code>TimingDescriptionEventChain</code>
[constr_6817]	Restricted usage of <code>TimingDescriptionEvent.clockReference</code>
[constr_6818]	Existence of <code>EventTriggeringConstraint.event</code>
[constr_6819]	Existence of <code>PeriodicEventTriggering.jitter</code>
[constr_6820]	Existence of <code>PeriodicEventTriggering.minimumInterArrivalTime</code>
[constr_6821]	Existence of <code>PeriodicEventTriggering.period</code>
[constr_6822]	Existence of <code>SporadicEventTriggering.maximumInterArrivalTime</code>
[constr_6823]	Existence of <code>SporadicEventTriggering.minimumInterArrivalTime</code>
[constr_6824]	Existence of <code>ConcretePatternEventTriggering.patternLength</code>
[constr_6825]	Existence of <code>BurstPatternEventTriggering.maxNumberOfOccurrences</code>
[constr_6826]	Existence of <code>BurstPatternEventTriggering.minimumInterArrivalTime</code>
[constr_6827]	Existence of <code>BurstPatternEventTriggering.patternLength</code>
[constr_6828]	Existence of <code>ArbitraryEventTriggering.minimumDistance</code>
[constr_6829]	Existence of <code>ArbitraryEventTriggering.maximumDistance</code>
[constr_6830]	Existence of <code>ConfidenceInterval.lowerBound</code>
[constr_6831]	Existence of <code>ConfidenceInterval.propability</code>
[constr_6832]	Existence of <code>ConfidenceInterval.upperBound</code>
[constr_6833]	Existence of <code>ExecutionOrderConstraint.orderedElement</code>
[constr_6834]	Existence of <code>EOCExecutableEntityRefGroup.nestedElement</code>
[constr_6835]	Existence of <code>ExecutionTimeConstraint.executionTimeType</code>
[constr_6836]	Existence of <code>ExecutionTimeConstraint.executable</code>
[constr_6837]	Existence of <code>LatencyTimingConstraint.latencyConstraintType</code>
[constr_6838]	Existence of <code>LatencyTimingConstraint.maximum</code>
[constr_6839]	Existence of <code>LatencyTimingConstraint.minimum</code>
[constr_6841]	Existence of <code>LatencyTimingConstraint.scope</code>
[constr_6842]	Existence of <code>OffsetTimingConstraint.maximum</code>
[constr_6843]	Existence of <code>OffsetTimingConstraint.minimum</code>
[constr_6844]	Existence of <code>OffsetTimingConstraint.source</code>
[constr_6845]	Existence of <code>OffsetTimingConstraint.target</code>





Number	Heading
[constr_6846]	Existence of SynchronizationTimingConstraint.synchronizationConstraintType
[constr_6847]	Existence of SynchronizationTimingConstraint.tolerance
[constr_6848]	Existence of VfbTiming.component
[constr_6849]	Existence of SystemTiming.system
[constr_6850]	Existence of BswModuleTiming.behavior
[constr_6851]	Existence of BswCompositionTiming.implementation
[constr_6852]	Existence of EcuTiming.ecuConfiguration
[constr_6853]	Existence of ModeInBswInstanceRef.contextModeDeclarationGroupPrototype
[constr_6854]	Existence of ModeInBswInstanceRef.targetModeDeclaration
[constr_6855]	Existence of ModeInSwcInstanceRef.contextModeDeclarationGroupPrototype
[constr_6856]	Existence of ModeInSwcInstanceRef.contextPort
[constr_6857]	Existence of ModeInSwcInstanceRef.targetModeDeclaration
[constr_6858]	Existence of TDEventBswInternalBehavior.tdEventBswInternalBehaviorType
[constr_6859]	Existence of TDEventBswInternalBehavior.bswModuleEntity
[constr_6860]	Existence of TDEventBswModule.tdEventBswModuleType
[constr_6861]	Existence of TDEventBswModule.bswModuleEntry
[constr_6862]	Existence of TDEventBswModeDeclaration.tdEventBswModeDeclarationType
[constr_6863]	Existence of TDEventBswModeDeclaration.modeDeclaration
[constr_6864]	Existence of TDEventISignal.tdEventType
[constr_6865]	Existence of TDEventISignal.iSignal
[constr_6866]	Existence of TDEventISignal.physicalChannel
[constr_6867]	Existence of TDEventIPdu.tdEventType
[constr_6868]	Existence of TDEventIPdu.iPdu
[constr_6869]	Existence of TDEventIPdu.physicalChannel
[constr_6870]	Existence of TDEventFrame.tdEventType
[constr_6871]	Existence of TDEventFrame.frame
[constr_6872]	Existence of TDEventFrame.physicalChannel
[constr_6873]	Existence of TDEventFrameEthernet.tdEventType
[constr_6874]	Existence of TDHeaderIdRange.maxHeaderId
[constr_6875]	Existence of TDHeaderIdRange.minHeaderId
[constr_6876]	Existence of TDEventCycleStart.cycleRepetition
[constr_6877]	Existence of TDEventFrClusterCycleStart.frCluster
[constr_6878]	Existence of TDEventTTCanCycleStart.ttCanCluster
[constr_6879]	Existence of TDEventOccurrenceExpression.formula
[constr_6880]	Existence of AutosarVariableInstance.variableInstance





Number	Heading
[constr_6881]	Existence of AutosarOperationArgumentInstance. operationArgumentInstance
[constr_6882]	Existence of TDEventSwcInternalBehavior. tdEventSwcInternalBehaviorType
[constr_6883]	Existence of TDEventSwcInternalBehavior.runnable
[constr_6884]	Existence of TDEventSwcInternalBehaviorReference. referencedTDEventSwc
[constr_6885]	Existence of TDEventVfbPort.isExternal
[constr_6886]	Existence of TDEventVfbReference.referencedTDEventVfb
[constr_6887]	Existence of TDEventVariableDataPrototype. tdEventVariableDataPrototypeType
[constr_6888]	Existence of TDEventVariableDataPrototype.dataElement
[constr_6889]	Existence of TDEventOperation.tdEventOperationType
[constr_6890]	Existence of TDEventOperation.operation
[constr_6891]	Existence of TDEventModeDeclaration.tdEventModeDeclarationType
[constr_6892]	Existence of TDEventModeDeclaration.modeDeclaration
[constr_6893]	Existence of TDEventTrigger.tdEventTriggerType
[constr_6894]	Existence of TDEventTrigger.trigger
[constr_6895]	Existence of TimingDescriptionEventChain.response
[constr_6896]	Existence of TimingDescriptionEventChain.stimulus
[constr_6897]	Existence of TimingDescriptionEventChain.segment
[constr_6898]	Existence of ConcretePatternEventTriggering.offset
[constr_6899]	Existence of ModeInSwcInstanceRef.base
[constr_6900]	Dual existence of TDEventVfb.port and TDEventVfb. portPrototypeBlueprint
[constr_6901]	Existence of TDEventBsw.bswModuleDescription
[constr_6906]	Conformity of stimulus and response in a TimingDescriptionEventChain
[constr_6907]	Restriction of EOCExecutableEntityRefGroup.triggeringEvent
[constr_6908]	Restriction of EOCExecutableEntityRefGroup.letDataExchangeParadigm
[constr_6909]	Singleton ROOT_GROUP in a Hierarchical Execution Order Constraint
[constr_6910]	Referencing from a ROOT_GROUP in a Hierarchical Execution Order Constraint
[constr_6911]	Referencing to a ROOT_GROUP in a Hierarchical Execution Order Constraint
[constr_6912]	Mandatory specification of LET interval recurrence
[constr_6913]	Restriction on RTEEvents used in an LET interval
[constr_6914]	Restriction of the port context of an AgeConstraint
[constr_6915]	Affinity of ISignal in TDEventISignal
[constr_6916]	Affinity of Frame in TDEventFrame
[constr_6917]	Affinity of IPdu in TDEventIPdu
[constr_9112]	Existence of GenericTp.tpTechnology
[constr_9115]	Existence of RtpTp.ssrc



△

Number	Heading
[constr_9116]	Existence of <code>RtpTp.tcpUdpConfig</code>
[constr_9119]	Existence of <code>Ieee1722Tp.streamIdentifier</code>
[constr_9120]	Existence of <code>HttpTp.protocolVersion</code>
[constr_9121]	Existence of <code>HttpTp.tcpTpConfig</code>
[constr_9207]	Existence of <code>EndToEndProtectionISignalIPdu.iSignalIPdu</code>
[constr_9208]	Existence of <code>EndToEndProtectionISignalIPdu.iSignalGroup</code>
[constr_9209]	Existence of <code>EndToEndProtectionISignalIPdu.dataOffset</code>
[constr_9267]	Existence of <code>J1939TpConnection.broadcast</code>

Table B.2: Changed Constraints in R24-11

B.1.3 Deleted Constraints in R24-11

Number	Heading
[constr_10017]	
[constr_1364]	
[constr_1433]	
[constr_1796]	
[constr_1891]	
[constr_2051]	
[constr_2525]	
[constr_2540]	
[constr_3522]	
[constr_4086]	
[constr_4517]	
[constr_4550]	
[constr_4560]	
[constr_4563]	
[constr_4564]	
[constr_4567]	
[constr_4568]	
[constr_5169]	
[constr_5391]	

Table B.3: Deleted Constraints in R24-11