

Document Title	Requirements on RAM Test
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	114
Document Classification	Auxiliary

Document Version	1.1.5
Document Status	Final
Part of Release	3.2
Revision	3

Document Change History			
Date	Version	Changed by	Change Description
28.02.2014	1.1.5	AUTOSAR Release Management	<ul style="list-style-type: none"> • Editorial changes • Removed chapter(s) on change documentation
23.03.2011	1.1.4	AUTOSAR Administration	Legal disclaimer revised
23.06.2008	1.1.3	AUTOSAR Administration	Legal disclaimer revised
31.10.2007	1.1.2	AUTOSAR Administration	<ul style="list-style-type: none"> • Document meta information extended • Small layout adaptations made
24.01.2007	1.1.1	AUTOSAR Administration	<ul style="list-style-type: none"> • “Advice for users” revised • “Revision Information” added
01.12.2006	1.1.0	AUTOSAR Administration	<ul style="list-style-type: none"> • [BSW13814] rejected “modified Hamming code” test removed • Legal disclaimer revised
14.03.2006	1.0.0	AUTOSAR Administration	Initial release

Disclaimer

This specification and the material contained in it, as released by AUTOSAR is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only.

For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Advice for users

AUTOSAR Specification Documents may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the Specification Documents for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such Specification Documents, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.

Table of Contents

1	Scope of this document	4
2	How to read this document.....	5
2.1	Conventions used.....	5
2.2	Requirement structure.....	5
3	Acronyms and abbreviations	7
4	Requirement Specification.....	8
4.1	RAM Test	8
4.1.1	Functional Overview.....	8
4.1.2	Functional Requirements	8
4.1.2.1	Configuration	8
4.1.2.1.1	[BSW13800] Number of tested cells shall be changeable at runtime	8
4.1.2.1.2	[BSW13801] Test cell size shall be configurable at pre-compile time	8
4.1.2.1.3	[BSW13802] Multiple RAM areas shall be configurable at post build/ link time	9
4.1.2.1.4	[BSW13803] A subset of available RAM Test algorithms shall be selectable at pre-compile time.....	9
4.1.2.1.5	[BSW13804] A subset of the pre-compile time selected RAM Check test algorithms shall be selectable at runtime.....	10
4.1.2.2	Normal Operation	10
4.1.2.2.1	[BSW13822]Test algorithm with low coverage shall be available	10
4.1.2.2.2	[SRS_RamTst_13823] Test algorithm with medium coverage shall be available.....	11
4.1.2.2.3	[SRS_RamTst_13824] Test algorithm with high coverage shall be available	11
4.1.2.2.4	[BSW13809] RAM Test Execution Management.....	11
4.1.2.2.5	[BSW13810] Current status of RAM test execution per block shall be available through a get status interface.....	12
4.1.2.2.6	[BSW13820] RAM test execution status shall be provided by a notification mechanism.....	12
4.1.2.2.7	[BSW13811] Non Destructive RAM Test.....	12
4.1.2.2.8	[BSW13812] Destructive RAM Test	13
4.1.3	Non-Functional Requirements (Qualities)	13
4.1.3.1	[BSW13816] Effects of Instruction / Data queue shall be taken into account	13
4.1.3.2	[SRS_RamTst_13825] The RAM Test Module shall be usable to comply with requirements of the different ASIL levels of ISO 26262.	14
5	References	15
5.1	Deliverables of AUTOSAR	15
5.2	Related standards and norms	15

1 Scope of this document

This document specifies requirements on the module RAM Test.

This document covers requirements only for software algorithms to check the RAM. A hardware RAM check (like ECC check) is not in the scope of this document.

2 How to read this document

Each requirement has its unique identifier starting with the prefix “BSW” (for “Basic Software”). For any review annotations, remarks or questions please refer to this unique ID rather than chapter or page numbers!

2.1 Conventions used

In requirements, the following specific semantics are used (taken from Request for Comment RFC 2119 from the Internet Engineering Task Force IETF)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119. Note that the requirement level of the document in which they are used modifies the force of these words.

- **MUST:** This word, or the terms "REQUIRED" or "SHALL", mean that the definition is an absolute requirement of the specification.
- **MUST NOT:** This phrase, or the phrase „SHALL NOT“, means that the definition is an absolute prohibition of the specification.
- **SHOULD:** This word, or the adjective "RECOMMENDED", mean that there may exist valid reasons in particular circumstances to ignore a particular item, but the full implications must be understood and carefully weighed before choosing a different course.
- **SHOULD NOT:** This phrase, or the phrase "NOT RECOMMENDED" mean that there may exist valid reasons in particular circumstances when the particular behaviour is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behaviour described with this label.
- **MAY:** This word, or the adjective „OPTIONAL“, means that an item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because the vendor feels that it enhances the product while another vendor may omit the same item. An implementation, which does not include a particular option, **MUST** be prepared to interoperate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, **MUST** be prepared to interoperate with another implementation, which does not include the option (except, of course, for the feature the option provides.)

2.2 Requirement structure

Each module specific chapter contains a short functional description of the Basic Software Module. Requirements of the same kind within each chapter are grouped under the following headlines (where applicable):

Functional Requirements:

- Configuration (which elements of the module need to be configurable)

- Initialization
- Normal Operation
- Shutdown Operation
- Fault Operation
- ...

Non-Functional Requirements:

- Timing Requirements
- Resource Usage
- Usability
- Output for other WPs (e.g. Description Templates, Tooling,...)
- ...

3 Acronyms and abbreviations

Acronyms and abbreviations that have a local scope are not contained in the AUTOSAR glossary. These must appear in a local glossary.

Acronym:	Description:
ECU	Electric Control Unit
EOL	End Of Line Often used in the term 'EOL Programming' or 'EOL Configuration'
HIS	Herstellerinitiative Software
MAL	Old name of Microcontroller Abstraction Layer (replaced by MCAL because 'MAL' is a french term meaning 'bad')
MCAL	Microcontroller Abstraction Layer
MCU	Microcontroller Unit
NMI	Non maskable interrupt
OS	Operating System
SPAL	The name of this working group
SFR	Special Function Register
RTE	Runtime environment
WP	Work Package

Abbreviation:	Description:
STD	Standard
REQ	Requirement
UNINIT	Uninitialized (= not initialized)

As this is a document from professionals for professionals, all other terms are expected to be known.

4 Requirement Specification

4.1 RAM Test

4.1.1 Functional Overview

This module has the task to test the RAM memory area by software.

4.1.2 Functional Requirements

4.1.2.1 Configuration

4.1.2.1.1 [BSW13800] Number of tested cells shall be changeable at runtime

Initiator:	Delphi
Date:	22.07.2005
Short Description:	The number of tested cells shall be changeable at runtime.
Type:	New
Importance:	Medium
Description:	To react on different requirements (sleep, driving cycle) the user shall have the possibility to change the number of tested cells per cycle "online".
Rationale:	Influences the interrupt disable times.
Use Case:	When car is driven the system interrupt locking time must be much shorter than in case of sleep mode.
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.1.2 [BSW13801] Test cell size shall be configurable at pre-compile time

Initiator:	Delphi
Date:	23.11.2005
Short Description:	Test cell size shall be configurable at pre-compile time.
Type:	Changed
Importance:	High
Description:	The user shall have the possibility to change test cell size (bit, byte, word, long word) dependent on the controller properties.
Rationale:	--
Use Case:	Runtime optimization due to controller properties.
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.1.3 [BSW13802] Multiple RAM areas shall be configurable at post build/ link time

Initiator:	Delphi
Date:	23.11.2005
Short Description:	Multiple RAM areas shall be configurable at post build/ link time.
Type:	Changed
Importance:	High
Description:	It shall be possible to configure multiple RAM areas (by configuring their start and end address). If two RAM areas overlap and an error is detected in the overlapping region while testing one of the blocks, the driver does not guarantee to update the status of the other block.
Rationale:	--
Use Case:	User shall have the possibility to configure the memory mapping.
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.1.4 [BSW13803] A subset of available RAM Test algorithms shall be selectable at pre-compile time

Initiator:	Delphi
Date:	23.11.2005
Short Description:	A subset of available RAM Test algorithms shall be selectable at pre-compile time.
Type:	Changed
Importance:	High
Description:	The user shall select at pre-compile time the available algorithms which matches to the project safety requirements.
Rationale:	Avoid unused code.
Use Case:	Depending on ECU safety analysis different RAM test algorithms should be selectable. To save ROM space the algorithms should be selectable at compile time
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.1.5 [BSW13804] A subset of the pre-compile time selected RAM Check test algorithms shall be selectable at runtime

Initiator:	WP4.2.2.1.12
Date:	23.11.2005
Short Description:	A subset of the pre-compile time selected RAM Check test algorithms shall be selectable at runtime.
Type:	Changed
Importance:	High
Description:	The user shall select the test algorithms from those available at runtime to conform to the project safety requirements.
Rationale:	Different levels of testing are available.
Use Case:	During normal operation a simple test is executed and before going to sleep mode a more complex RAM test algorithm will be executed. The complex RAM test can not be executed during normal operation because of stronger interrupt latency requirements.
Dependencies:	[BSW13803]
Conflicts:	--
Supporting Material:	--

4.1.2.2 Normal Operation

4.1.2.2.1 [BSW13822] Test algorithm with low coverage shall be available

Initiator:	WP-1.3
Date:	11.07.2012
Short Description:	A test algorithm with low coverage (60%) shall be available
Type:	New
Importance:	High
Description:	A test algorithm, which fulfils a diagnostic coverage of 60 % shall be available.
Rationale:	Detect permanent faults in RAM.
Use Case:	Support of EOL, quick start-up tests and where low diagnostic coverage tests are required, e.g. if system has safety goals with low ISO 26262 ASIL rating only.
Dependencies:	--
Conflicts:	--
Supporting Material:	ISO 26262-5:2011, Tables 4, 5, D.1 and D.6, sections D.2.5.1, D.2.5.2 and D.2.5.3
Contributes to:	--

4.1.2.2.2 [SRS_RamTst_13823] Test algorithm with medium coverage shall be available

Initiator:	WP-1.3
Date:	11.07.2012
Short Description:	A test algorithm with medium coverage (90%) shall be available
Type:	New
Importance:	High
Description:	A test algorithm, which fulfils a diagnostic coverage of 90 % shall be available.
Rationale:	Detect permanent faults in RAM.
Use Case:	Support of EOL, start-up tests and where medium diagnostic coverage tests are required, e.g. if the latent fault metric of ISO 26262 for the ASIL level of the safety goals of a system can be achieved with medium coverage.
Dependencies:	--
Conflicts:	--
Supporting Material:	ISO 26262-5:2011, Tables 4, 5, D.1 and D.6, sections D.2.5.1, D.2.5.2 and D.2.5.3
Contributes to:	--

4.1.2.2.3 [SRS_RamTst_13824] Test algorithm with high coverage shall be available

Initiator:	WP-1.3
Date:	11.07.2012
Short Description:	A test algorithm with high coverage (99%) shall be available
Type:	New
Importance:	High
Description:	A test algorithm, which fulfils a diagnostic coverage of 99 % shall be available.
Rationale:	Detect permanent faults in RAM.
Use Case:	Support of EOL, diligent start-up, shut-down or runtime tests and where high diagnostic coverage tests are required, e.g. if system has a safety goal with high ISO 26262 ASIL rating.
Dependencies:	--
Conflicts:	--
Supporting Material:	ISO 26262-5:2011, Tables 4, 5, D.1 and D.6, sections D.2.5.1, D.2.5.2 and D.2.5.3
Contributes to:	--

4.1.2.2.4 [BSW13809] RAM Test Execution Management

Initiator:	Delphi
Date:	16.08.2005
Short Description:	RAM Test Execution Management
Type:	New
Importance:	High
Description:	It shall be possible to divide the RAM test execution into smaller pieces. With one call of the RAM test it shall be possible to execute only a part of the whole RAM test.
Rationale:	Avoid long interrupt disable times

Use Case:	Drivers who need short interrupt latency times
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.2.5 [BSW13810] Current status of RAM test execution per block shall be available through a get status interface

Initiator:	WP4.2.2.1.12
Date:	23.11.2005
Short Description:	Current status of RAM test execution per block shall be available through a get status interface.
Type:	Changed
Importance:	Medium
Description:	RAM test execution status per block (RESULT_NOT_TESTED, RESULT_OK, RESULT_NOT_OK, and RESULT_UNDEFINED) shall be provided to the user. User shall have the possibility to get the status of the RAM test at any time. This shall be implemented as a get status interface and shall be configurable during compile time. This function shall be optional.
Rationale:	--
Use Case:	Diagnostics may need to know if there has been errors occurred or not.
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.2.6 [BSW13820] RAM test execution status shall be provided by a notification mechanism

Initiator:	Delphi
Date:	22.07.2005
Short Description:	RAM test execution status shall be provided by a notification mechanism.
Type:	New
Importance:	Medium
Description:	Information when error has been detected or test has been finished shall be provided to the user by a notification mechanism. This function shall be optional.
Rationale:	--
Use Case:	Diagnostics may need to know immediately if an error has been detected or not.
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.2.7 [BSW13811] Non Destructive RAM Test

Initiator:	WP4.2.2.1.12
Date:	01.06.2005
Short Description:	Non destructive RAM test
Type:	New

Importance:	High
Description:	The RAM test module shall be able to perform its tests in a non-destructive manner.
Rationale:	Original data shall be preserved
Use Case:	Destroying of all RAM data may lead to longer reaction times (e.g. wake up), higher resource consumption (e.g.: EEPROM)
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.2.2.8 [BSW13812] Destructive RAM Test

Initiator:	WP4.2.2.1.12
Date:	01.06.2005
Short Description:	Destructive RAM Test
Type:	New
Importance:	High
Description:	The RAM test module shall be able to perform its tests in a destructive manner. The state of the RAM after testing shall be defined.
Rationale:	Original data does not need to be preserved
Use Case:	--
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.3 Non-Functional Requirements (Qualities)

4.1.3.1 [BSW13816] Effects of Instruction / Data queue shall be taken into account

Initiator:	Delphi
Date:	01.07.2005
Short Description:	Effects of Instruction / Data queue / cache shall be taken into account
Type:	New
Importance:	High
Description:	When writing to a cell and after reading back this may lead to the problem that the read-back value comes from the data queue and not from the RAM cell to be tested. In that case instruction(s) have to be injected to eliminate such an effect.
Rationale:	Read back the value from a tested cell
Use Case:	Controller with instruction or data queue may have such effects
Dependencies:	--
Conflicts:	--
Supporting Material:	--

4.1.3.2 [SRS_RamTst_13825] The RAM Test Module shall be usable to comply with requirements of the different ASIL levels of ISO 26262.

ID:	SRS_RamTst_13825
Initiator:	WP-1.3
Date:	11.07.2012
Short Description:	The RAM Test Module shall be usable to comply with requirements of the different ASIL levels of ISO 26262.
Type:	New
Importance:	High
Description:	The RAM Test Module shall provide and document (fault models and fault coverage) diagnostic capability for permanent faults in RAMs to enable fulfillment of the latent fault metric targets of ISO 26262 for the different ASIL levels.
Rationale:	Usability of AUTOSAR for systems which need to comply with ISO 26262.
Use Case:	--
Dependencies:	--
Conflicts:	--
Supporting Material:	ISO 26262-5:2011, Tables 4, 5, D.1 and D.6, sections D.2.5.1, D.2.5.2 and D.2.5.3
Contributes to:	--

5 References

5.1 Deliverables of AUTOSAR

- [1] Glossary
AUTOSAR_Glossary.pdf
- [2] Layered Software Architecture
AUTOSAR_LayeredSoftwareArchitecture.pdf
- [3] General Requirements on Basic
AUTOSAR_SRS_General.pdf
- [4] General Requirements on SPAL
AUTOSAR_SRS_SPAL_General.pdf

5.2 Related standards and norms

- [5] ISO 26262-5:2011: Road vehicles – Functional safety – Part 5: Product development at the hardware level.