

<b>Document Title</b>	Requirements on Ethernet Support in AUTOSAR
<b>Document Owner</b>	AUTOSAR
<b>Document Responsibility</b>	AUTOSAR
<b>Document Identification No</b>	419
<b>Document Classification</b>	Auxiliary
<b>Document Version</b>	2.1.0
<b>Document Status</b>	Final
<b>Part of Release</b>	4.1
<b>Revision</b>	2

<b>Document Change History</b>			
<b>Date</b>	<b>Version</b>	<b>Changed by</b>	<b>Change Description</b>
31.10.2013	2.1.0	AUTOSAR Release Management	<ul style="list-style-type: none"> <li>• Added support for ISO 13400-2</li> <li>• Updated Document Traceability</li> <li>• Editorial changes</li> </ul>
30.01.2013	2.0.0	AUTOSAR Administration	<ul style="list-style-type: none"> <li>• Introduced IPv6 Protocol, VLAN</li> <li>• Added support for SWS_Service Discovery</li> <li>• Added support for SWS_TCPIP</li> <li>• Added support for SWS_DoIP</li> <li>• Editorial changes</li> </ul>
14.10.2011	1.1.0	AUTOSAR Administration	New traceability mechanism
07.12.2009	1.0.0	AUTOSAR Administration	Initial Release

## Disclaimer

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only.

For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

## Advice for users

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.

## Table of Contents

1	Scope of Document .....	5
2	Conventions to be used .....	6
2.1	Acronyms and abbreviations .....	7
3	Functional Overview .....	8
3.1	TCP/IP Protocol Stack (TCPIP) .....	8
3.2	SWS Socket Adaptor (SoAd) .....	8
3.3	SWS Diagnostics over IP (DoIP) .....	8
3.4	SWS Ethernet Interface (EthIf) .....	8
3.5	SWS Ethernet Driver (Eth) .....	8
3.6	SWS Ethernet Transceiver Driver (EthTrcv) .....	8
3.7	SWS Ethernet State Manager (EthSM) .....	8
3.8	SWS UDP Network Management (UdpNm) .....	9
3.9	SWS Service Discovery (Sd) .....	9
4	Requirements traceability .....	10
5	Requirements Specification .....	11
5.1	General Requirements .....	11
5.1.1	Configuration .....	11
5.1.2	AUTOSAR Interfaces .....	11
5.2	Functional Requirement .....	12
5.2.1	SWS TCP/IP Protocol Stack .....	12
5.2.2	TCP/IP Internet Protocol .....	12
5.2.3	TCP/IP Sub Module: IPv4 .....	13
5.2.4	TCP/IP Sub Module: IPv6 .....	14
5.2.5	TCP/IP ICMP .....	14
5.2.6	TCP/IP UDP .....	15
5.2.7	TCP/IP DHCP .....	16
5.2.8	TCP/IP Sub-Module: DHCPv6 .....	17
5.3	SWS Socket Adaptor (SoAd) .....	18
5.4	SWS Diagnostics over IP (DoIP) .....	22
5.5	SWS Ethernet Interface (EthIf) .....	25
5.6	SWS Ethernet Driver (Eth) .....	27
5.7	SWS Ethernet Transceiver Driver (EthTrcv) .....	28
5.8	SWS Ethernet State Manager (EthSM) .....	28
5.9	SWS UDP Network Management (UdpNm) .....	28
5.10	SWS Service Discovery (Sd) .....	29
5.11	Non-Functional Requirements .....	29
5.11.1	SWS TCP/IP Protocol Stack .....	29
5.11.2	SWS Socket Adaptor (SoAd) .....	30
5.11.3	SWS Ethernet Interface (EthIf) .....	30
5.11.4	SWS Ethernet Driver (Eth) .....	31
5.11.5	SWS Ethernet Transceiver Driver (EthTrcv) .....	31
5.11.6	SWS Ethernet State Manager (EthSM) .....	31
5.11.7	SWS UDP Network Management (UdpNm) .....	32
6	References .....	33

6.1	Deliverables of AUTOSAR .....	33
6.2	Related standards and norms .....	33
6.2.1	IETF Requests For Comments (RFCs).....	33

## 1 Scope of Document

This document is intended to list the general requirements resulting from concept UID 387 TCP/IP CommStack Extensions (TCP/IP).

These will need to be implemented by the following software specifications:

- 414 UDP Network Management (UdpNm)
- 415 Ethernet State Manager (EthSM)
- 416 Socket Adaptor (SoAd)
- 417 Ethernet Interface (EthIf)
- 418 Diagnostics over IP (DoIP)
- 430 Ethernet Driver (Eth)
- 431 Ethernet Transceiver Driver (Eth Trcv)
- 616 Service Discovery (Sd)
- 617 Tcp/Ip Stack (Tcplp)

## 2 Conventions to be used

- The representation of requirements in AUTOSAR documents follows the table specified in [7].
- In requirements, the following specific semantics shall be used (based on the Internet Engineering Task Force IETF).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as:

- **SHALL**: This word means that the definition is an absolute requirement of the specification.
- **SHALL NOT**: This phrase means that the definition is an absolute prohibition of the specification.
- **MUST**: This word means that the definition is an absolute requirement of the specification due to legal issues.
- **MUST NOT**: This phrase means that the definition is an absolute prohibition of the specification due to legal constraints.
- **SHOULD**: This word, or the adjective "RECOMMENDED", mean that there may exist valid reasons in particular circumstances to ignore a particular item, but the full implications must be understood and carefully weighed before choosing a different course.
- **SHOULD NOT**: This phrase, or the phrase "NOT RECOMMENDED" mean that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
- **MAY**: This word, or the adjective „OPTIONAL“, means that an item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because the vendor feels that it enhances the product while another vendor may omit the same item. An implementation, which does not include a particular option, **MUST** be prepared to interoperate with another implementation, which does include the option, though perhaps with reduced functionality. In the same vein an implementation, which does include a particular option, **MUST** be prepared to interoperate with another implementation, which does not include the option (except, of course, for the feature the option provides.)

## 2.1 Acronyms and abbreviations

<b>Abbreviation / Acronym:</b>	<b>Description:</b>
ARP	Address Resolution Protocol
COTS	Commercial Of The Shelf
DEM	Diagnostic Event Manager
DET	Development Error Tracer
DHCP	Dynamic Host Configuration Protocol
DoIP	Diagnostics over IP
HTTP	HyperText Transfer Protocol
IANA	Internet Assigned Numbers Authority
ICMP	Internet Control Message Protocol
IP	Internet Protocol
SoAd	AUTOSAR Socket Adaptor Module
TCP	Transmission Control Protocol
TCP/IP	A family of communication protocols used in computer networks
UDP	User Datagram Protocol
UdpNm	AUTOSAR UDP Network Management Module
XCP	eXtended Calibration Protocol

## 3 Functional Overview

### 3.1 TCP/IP Protocol Stack (TCPIP)

The TCP/IP protocol stack (TCP/IP stack) is intended to handle layers 2 through 4 of the ISO/OSI layer model. This includes, but is not limited to protocols like IP, DHCP, ARP, TCP, UDP, ICMP and others.

In Terms of this model the SoAd and therefore the whole AUTOSAR COM stack above represent the application at layer 7.

### 3.2 SWS Socket Adaptor (SoAd)

The SoAd is an adaptor layer, not only matching the AUTOSAR APIs to standard socket APIs [9], but also mapping PDU IDs to socket connections.

### 3.3 SWS Diagnostics over IP (DoIP)

The DoIP part of the SoAd implements the functionality required by [10].

### 3.4 SWS Ethernet Interface (EthIf)

The Ethernet Interface provides standardized interfaces to provide the communication with the Ethernet bus system of an ECU. The APIs are independent from the specific Ethernet Controllers and Transceivers and their access through the responsible Driver layer. The Ethernet Interface is conceptually able to access one or more Ethernet Drivers and Ethernet Transceiver Drivers via one uniform interface.

### 3.5 SWS Ethernet Driver (Eth)

The Ethernet Driver offers uniform interfaces for the Ethernet Interface. The Ethernet Driver hides hardware specific details of the used Ethernet controller.

### 3.6 SWS Ethernet Transceiver Driver (EthTrcv)

The Ethernet Transceiver Driver offers uniform interfaces for the Ethernet Interface. The Ethernet Transceiver Driver hides hardware specific details of the used Ethernet transceiver.

### 3.7 SWS Ethernet State Manager (EthSM)

The Ethernet State Manager offers uniform interfaces for the Communication Manager (ComM). The Ethernet State Manager hides network specific details.



### **3.8 SWS UDP Network Management (UdpNm)**

The UDP Network Management offers uniform interfaces for the Network Management Interface (NmIf). The UDP Network Management hides network specific details.

### **3.9 SWS Service Discovery (Sd)**

Service Discovery serves primarily to determine the operational status of a service. A service may be comprised of any combination of SW-Cs and/or BSWs in an ECU. The BswM is used to aggregate the SW-Cs and BSWs status and trigger Sd when the required combination is available. Secondly Sd can also be used as a registration protocol for publish/subscribe communication patterns. In both cases Sd can transport addressing information in addition to the registration and availability information.

## 4 Requirements traceability

Document: Requirements on AUTOSAR Features[1].

<b>Requirement</b>	<b>Satisfied by</b>
[RS_BRF_00286]	OK, see Chapter 5
[RS_BRF_00283]	OK, see Chapter 5

## 5 Requirements Specification

### 5.1 General Requirements

#### 5.1.1 Configuration

##### 5.1.1.1 [SRS\_Eth\_00053] SWS shall specify configuration

<b>Type:</b>	New
<b>Description:</b>	The SWS documents shall include a configuration section to allow adaption of the functionality.
<b>Rationale:</b>	The functionality needs to be adapted to different use-cases and environments.
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

](RS\_BRF\_01056)

#### 5.1.2 AUTOSAR Interfaces

##### 5.1.2.1 [SRS\_Eth\_00055] SoAd shall support UDP NM

<b>Type:</b>	New
<b>Description:</b>	The SoAd shall offer an interface API for UDP NM to send network management messages. This interface shall mimic the API of interfaces in Autosar.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

](RS\_BRF\_01784)

##### 5.1.2.2 [SRS\_Eth\_00056] SoAd shall support XCP

<b>Type:</b>	Valid
<b>Description:</b>	The SoAd module shall offer a data path to the AUTOSAR XCP module.
<b>Rationale:</b>	Exchange XCP frames between master and client
<b>Use Case:</b>	Calibration and Measurement
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	ASAM XCP

](RS\_BRF\_01656)

##### 5.1.2.3 [SRS\_Eth\_00058] SoAd shall support generic upper layer

[

<b>Type:</b>	Valid
<b>Description:</b>	The SoAd shall offer an interface API for a generic upper layer to send and receive PDUs via socket connections, to control socket connections and to provide notification of socket connection and IP address assignment state changes.
<b>Rationale:</b>	Simplifies adding of additional upper layers
<b>Use Case:</b>	DoIP, V2G, DNS-SD
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

] (RS\_BRF\_1056)

## 5.2 Functional Requirement

### 5.2.1 SWS TCP/IP Protocol Stack

#### 5.2.1.1 TCP/IP General Requirements

##### 5.2.1.1.1 [SRS\_Eth\_00054] TCPIP minimum functionality

<b>Type:</b>	Valid
<b>Description:</b>	If DoIP is not implemented, the minimum requirements on the functionality of the TCP/IP stack shall be determined by the configuration of the Socket Adaptor.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

] (RS\_BRF\_1784)

##### 5.2.1.1.2 [SRS\_Eth\_00019] TCP and UDP related requirement specified in IETF RFC 1122 shall be implemented

<b>Type:</b>	Valid
<b>Description:</b>	TCP and UDP related requirements specified in IETF RFC 1122 shall be implement in the TCP/IP stack
<b>Rationale:</b>	--
<b>Use Case:</b>	IETF RFC 768, IETF RFC 793
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]; IETF RFC 1122

] (RS\_BRF\_1784)

### 5.2.2 TCP/IP Internet Protocol

#### 5.2.2.1 [SRS\_Eth\_00045] TCPIP automatic IP address assignment

[

<b>Type:</b>	Valid
<b>Description:</b>	The TCP/IP stack shall implement a mechanism to automatically configure an IP addresses..
<b>Rationale:</b>	This is necessary when no static IP-addresses are assigned to still allow for plug and play configuration of the TCP/IP stack.
<b>Use Case:</b>	--
<b>Dependencies:</b>	[SRS_Eth_00002]
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_1784)

### 5.2.3 TCP/IP Sub Module: IPv4

#### 5.2.3.1 [SRS\_Eth\_00014] IPv4 shall be implemented according to IETF RFC 791

<b>Type:</b>	Valid
<b>Description:</b>	The Internet Protocol (IPv4) shall at least be implemented in the TCP/IP stack as stated in IETF RFC 791
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]; IETF RFC 791;

]( RS\_BRF\_1784)

#### 5.2.3.2 [SRS\_Eth\_00015] ARP shall be implemented according to IETF RFC 826

<b>Type:</b>	Valid
<b>Description:</b>	For DoIP the Address Resolution Protocol (ARP) shall at least be implemented in the TCP/IP stack as stated in IETF RFC 826
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	[SRS_Eth_00014]
<b>Supporting Material:</b>	[10]; IETF RFC 826

]( RS\_BRF\_1784)

#### 5.2.3.3 [SRS\_Eth\_00022] The dynamic configuration of IPv4 link-local addresses as specified in IETF RFC 3927 shall be implemented

<b>Type:</b>	Valid
<b>Description:</b>	For DoIP the dynamic configuration of IPv4 link-local addresses as specified in IETF RFC 3927 shall be implemented in the TCP/IP stack
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]; IETF RFC 3927

]( RS\_BRF\_1784)

## 5.2.4 TCP/IP Sub Module: IPv6

### 5.2.4.1 [SRS\_Eth\_00059] IPv6 shall be implemented according to IETF RFC 2460

<b>Type:</b>	Valid
<b>Description:</b>	Internet Protocol Version 6 (IPv6) shall at least be implemented in the TCP/IP stack as stated in IETF RFC 2460. Limitation: the Authentication and Encapsulating Security Payload extension headers and other IPsec functionalities may not be supported. The handling of IPsec headers shall be tolerated
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_1784)

### 5.2.4.2 [SRS\_Eth\_00060] IPv6 shall be implemented according to IETF RFC 2461

<b>Type:</b>	Valid
<b>Description:</b>	Neighbour Discovery Protocol shall at least be implemented in the TCP/IP stack as stated in IETF RFC 2461
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_1784)

## 5.2.5 TCP/IP ICMP

### 5.2.5.1 [SRS\_Eth\_00016] ICMP shall be implemented according to IETF RFC 792

<b>Type:</b>	Valid
<b>Description:</b>	For DoIP the Internet Control Message Protocol (ICMP) shall at least be implemented in the TCP/IP stack as stated in IETF RFC 792
<b>Rationale:</b>	
<b>Use Case:</b>	--
<b>Dependencies:</b>	[SRS_Eth_00014]
<b>Supporting Material:</b>	[10]; IETF RFC 792

]( RS\_BRF\_1784)

### 5.2.5.2 [SRS\_Eth\_00061]An API shall be available to generate any ICMP message

[

<b>Type:</b>	Valid
<b>Description:</b>	An API Shall be available to generate any ICMP message
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

|( RS\_BRF\_01784)

### 5.2.5.3 [SRS\_Eth\_00062]A call-back function shall be configurable for any received ICMP message type

<b>Type:</b>	Valid
<b>Description:</b>	A call-back function shall be configurable for any received ICMP message type
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

|( RS\_BRF\_01784)

### 5.2.5.4 [SRS\_Eth\_00017] TCP shall be implemented according to IETF RFC 793

<b>Type:</b>	Valid
<b>Description:</b>	The Transmission Control Protocol (TCP) shall at least be implemented in the TCP/IP stack as stated in IETF RFC 793
<b>Rationale:</b>	
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]; IETF RFC 793

|( RS\_BRF\_01784)

### 5.2.5.5 [SRS\_Eth\_00063]TCP shall be independent of IP-Version

<b>Type:</b>	Valid
<b>Description:</b>	TCP shall be independent of any IP-Version
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

|( RS\_BRF\_01784)

## 5.2.6 TCP/IP UDP

### 5.2.6.1 [SRS\_Eth\_00018] UDP shall be implemented according to IETF RFC 768

|

<b>Type:</b>	Valid
<b>Description:</b>	The User Datagram Protocol (UDP) shall at least be implemented in the TCP/IP stack as stated in IETF RFC 768
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10], IETF RFC 768

]( RS\_BRF\_01784)

### 5.2.6.2 [SRS\_Eth\_00064]TCP shall be independent of IP-Version

[

<b>Type:</b>	Valid
<b>Description:</b>	TCP shall be independent of any IP-Version
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01784)

## 5.2.7 TCP/IP DHCP

### 5.2.7.1 [SRS\_Eth\_00065]An API shall be available to fill DHCP field

[

<b>Type:</b>	Valid
<b>Description:</b>	An API shall be available to fill any DHCP options field
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01784)

### 5.2.7.2 [SRS\_Eth\_00066]An API shall be available to read any received DHCP field

[

<b>Type:</b>	Valid
<b>Description:</b>	An API shall be available to read any received DHCP options field
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01784)

### 5.2.7.3 [SRS\_Eth\_00020] DHCP shall be implemented according to IETF RFC 2131

[



<b>Type:</b>	Valid
<b>Description:</b>	The Dynamic Host Configuration Protocol (DHCP) shall at least be implemented in the TCP/IP stack as stated in IETF RFC 2131
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	
<b>Supporting Material:</b>	[10]; IETF RFC 2131

]( RS\_BRF\_01784)

#### 5.2.7.4 [SRS\_Eth\_00021] The DHCP host name option shall be implemented according to IETF RFC 2132

<b>Type:</b>	Valid
<b>Description:</b>	For DoIP DHCP host name option shall at least be implemented in the TCP/IP stack as stated in IETF RFC 2132
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	[SRS_Eth_00047]; SRS_Eth_00020
<b>Supporting Material:</b>	[10]; IETF RFC 2132

]( RS\_BRF\_01784)

### 5.2.8 TCP/IP Sub-Module: DHCPv6

#### 5.2.8.1 [SRS\_Eth\_00067]The IPv6 stack shall implement DHCP as a DHCP client according to IETF RFC 3315

<b>Type:</b>	Valid
<b>Description:</b>	The IPv6 stack shall implement the Dynamic Host Configuration Protocol for IPv6 as a DHCP client.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	IETF RFC 3315

]( RS\_BRF\_01784)

#### 5.2.8.2 [SRS\_Eth\_00068]The DNS configuration options for DHCP for IPv6 shall be supported by IETF RFC 3646

<b>Type:</b>	Valid
<b>Description:</b>	The DNS Configuration Options for Dynamic Host Configuration Protocol for IPv6 shall be supported by IETF RFC 3646.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	IETF RFC 3646

]( RS\_BRF\_01784)

## 5.3 SWS Socket Adaptor (SoAd)

### 5.3.1.1 [SRS\_Eth\_00004] The SoAd shall support a local multi-homed host

<b>Type:</b>	Valid
<b>Description:</b>	The SoAd shall support a local multi-homed host.
<b>Rationale:</b>	An ECU might be connected to multiple IP networks for different use-cases
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.2 [SRS\_Eth\_00002] The IP addresses as well as the method of acquisition shall be a configurable item.

<b>Type:</b>	Valid
<b>Description:</b>	The IP addresses as well as the method of acquisition shall be a configurable item.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.3 [SRS\_Eth\_00001] The initialisation the SoAd shall be able to establish all TCP connections

<b>Type:</b>	Valid
<b>Description:</b>	The initialisation the SoAd shall be able to establish all TCP connections as described in the configuration.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.4 [SRS\_Eth\_00005] Both UDP or TCP shall be usable

<b>Type:</b>	Valid
<b>Description:</b>	Both UDP or TCP shall be usable.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.5 [SRS\_Eth\_00009] Upon Shutdown the Socket Adaptor shall close all open TCP connections

<b>Type:</b>	Valid
<b>Description:</b>	Upon Shutdown the Socket Adaptor shall close all open TCP connections.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.6 [SRS\_Eth\_00008] The Socket Adaptor shall immediately try to re-establish any TCP connection if it is lost

<b>Type:</b>	Valid
<b>Description:</b>	The Socket Adaptor shall immediately try to re-establish any TCP connection if it is lost. 'never give up' strategy
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.7 [SRS\_Eth\_00010] The SoAd shall implement a mechanism by which resources can be shared among multiple socket connections

<b>Type:</b>	Valid
<b>Description:</b>	The SoAd shall implement a mechanism by which resources can be shared among multiple socket connections.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.8 [SRS\_Eth\_00011] The resources required for the socket connections shall be predictable by analyzing the configuration information

<b>Type:</b>	Valid
<b>Description:</b>	The resources required for the socket connections shall be predictable by analyzing the configuration information.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.9 [SRS\_Eth\_00012] An API shall be offered where buffer memory is required

|

<b>Type:</b>	Valid
<b>Description:</b>	The Socket Adaptor, Tcplp, Ethlf and Eth shall offer an API where buffer memory for transmission and reception of AUTOSAR PDUs via Ethernet is required
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	AUTOSAR API will be able to satisfy this requirement!

]( RS\_BRF\_01776)

#### 5.3.1.10 [SRS\_Eth\_00013] An API shall be offered for reduced copy operation

<b>Type:</b>	Valid
<b>Description:</b>	The Socket Adaptor, Tcplp, Ethlf and Eth shall offer an API where the number of copy operations for transmission and reception of AUTOSAR PDUs via Ethernet is optimized (i.e. reduced to a minimum)
<b>Rationale:</b>	--
<b>Use Case:</b>	AUTOSAR API
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.3.1.11 [SRS\_Eth\_00006] The Socket Adaptor shall be able to transfer data using TCP/IP without the introduction of additional protocol overhead

<b>Type:</b>	Valid
<b>Description:</b>	The Socket Adaptor shall be able to transfer data using TCP/IP without the introduction of additional protocol overhead.
<b>Rationale:</b>	The protocol overhead introduced by Ethernet and TCP/IP is so large, that additional overhead is considered harmful.
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.3.1.12 [SRS\_Eth\_00048] SoAd shall implement a mechanism to bi-directionally route PDUs between an AUTOSAR connector and the TCP/IP stack

<b>Type:</b>	Valid
<b>Description:</b>	SoAd shall implement a mechanism to bi-directionally route PDUs between an AUTOSAR connector and the TCP/IP stack.
<b>Rationale:</b>	This is necessary to allow communication
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

**5.3.1.13 [SRS\_Eth\_00049] SoAd shall implement an API towards higher layers, which is equivalent to the API provided by interface modules**

<b>Type:</b>	Valid
<b>Description:</b>	SoAd shall implement an API towards higher layers, which is equivalent to the API provided by interface modules like FrIf, CanIf and LinIf.
<b>Rationale:</b>	Higher layers shall not be aware of the underlining communication stack.
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

**5.3.1.14 [SRS\_Eth\_00050] SoAd shall implement an API towards higher layers, which is equivalent to the API provided by transport layer**

<b>Type:</b>	Valid
<b>Description:</b>	SoAd shall implement an API towards higher layers, which is equivalent to the API provided by transport layer modules like FrTP and CanTP.
<b>Rationale:</b>	Higher layers shall not be aware of the underlining communication stack.
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

**5.3.1.15 [SRS\_Eth\_00051] The Socket Adapter shall specify and be able to use a call-back interface towards the TCP/IP stack**

<b>Type:</b>	Valid
<b>Description</b>	The Socket Adapter shall specify and be able to use a call-back interface towards the TCP/IP stack.
<b>Rationale</b>	the SoAd shall specify and be able to make use of a call-back interface, that reduces the number of required copy actions to and from the TCP/IP stack (optimized parameter) and reduces the latency (call-back functions).
<b>Use Case</b>	Instead of a commercial of the shelf TCP/IP stack an optimized automotive TCP/IP stack shall be usable.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	

]( RS\_BRF\_01776)

**5.3.1.16 [SRS\_Eth\_00069]The Socket Adapter shall implement a mechanism to share multiple PDUs from/to the same or different upper modules**

[

<b>Type:</b>	Valid
<b>Description:</b>	The SoAd shall implement a mechanism by which a socket connection can be shared among multiple PDUs from/to the same or different upper layer modules.
<b>Rationale:</b>	Minimize resource consumption
<b>Use Case:</b>	Transmission of multiple COM-PDUs to the same remote node.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.17 [SRS\_Eth\_00070]The Socket Adapter shall implement a mechanism to transmit PDUs to more than one receiver

[

<b>Type:</b>	Valid
<b>Description:</b>	The SoAd shall implement a mechanism by which a PDU shall be transmitted to more than one receiver using the same or a different socket connection and by which a received PDU shall be forwarded to more than one upper layer PDU using the same or a different socket connection to the same or a different upper layer module. (i.e. fan out to lower and upper layer, fan in from multiple connections)
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.3.1.18 [SRS\_Eth\_00071]The Socket Adapter shall implement a mechanism to activate or deactivate an upper layer using a routing group

[

<b>Type:</b>	Valid
<b>Description:</b>	The SoAd shall implement a mechanism by which a routing group can be activated or deactivated by an upper layer during runtime. A routing group consist of a number of PDUs from the same or different socket connections which shall be blocked (i.e. not routed to or from the upper layer). A PDU may only be part of a single routing group.
<b>Rationale:</b>	Blocking of undesired messages
<b>Use Case:</b>	Blocking of undesired notifications from a Publish/Subscribe Server
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

## 5.4 SWS Diagnostics over IP (DoIP)

### 5.4.1.1 [SRS\_Eth\_00047] DoIP shall be able to access the DHCP host name option.

[

<b>Type:</b>	Valid
<b>Description:</b>	The value used in the DHCP host name option shall be accessible and changeable by DoIP.
<b>Rationale:</b>	--
<b>Use Case:</b>	--
<b>Dependencies:</b>	[SRS_Eth_00021]
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.2 [SRS\_Eth\_00024] DoIP messages shall be bi-directionally routed

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall implement a mechanism to bi-directionally route DoIP messages between the vehicle networks and TCP sockets.
<b>Rationale:</b>	This is necessary to allow DoIP communication
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.3 [SRS\_Eth\_00025] Valid DoIP messages shall be recognized

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall provide a mechanism to recognize valid DoIP Messages
<b>Rationale:</b>	This is necessary to ensure correct DoIP communication
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.4 [SRS\_Eth\_00026] DoIP Vehicle Identification shall be provided

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall provide a mechanism to identify a vehicle respective its DoIP entity in a network
<b>Rationale:</b>	This is necessary to determine the IP addresses of the DoIP entity
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.5 [SRS\_Eth\_00027] DoIP diagnostic message shall have a format

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall implement a message format to allow the routing of diagnostic messages
<b>Rationale:</b>	This is necessary to allow DoIP
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.6 [SRS\_Eth\_00028] Multiple DoIP sockets shall be allowed on a single port

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall implement a mechanism to allow the use and assignment of multiple sockets on a single port, while ensuring that no active communication is disturbed
<b>Rationale:</b>	This is necessary for the efficient use of socket communication
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.7 [SRS\_Eth\_00080] DoIP shall implement a mechanism to retrieve diagnostic power mode

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall implement a mechanism to retrieve the diagnostic power mode of a DoIP Entity via a diagnostic power mode request as described in ISO 134000-2:2012. The service is needed to provide the tester with the diagnostic capability information.
<b>Rationale:</b>	This is necessary to allow DoIP
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.8 [SRS\_Eth\_00081]DoIP shall be able to dynamically maintain connection to different testers

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall be able to dynamically maintain the connection to different testers as described in ISO 134000-2:2012
<b>Rationale:</b>	This is necessary to allow DoIP
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.9 [SRS\_Eth\_00082]DoIP shall implement a mechanism to retrieve Entity Status



<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall implement a mechanism to retrieve the entity status information of a DoIP Entity via an Entity status request as described in ISO 134000-2:2012. The service is needed to provide the tester with the diagnostic capability information
<b>Rationale:</b>	This is necessary to allow DoIP
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.10 [SRS\_Eth\_00083]DoIP shall implement a mechanism to check if diagnostic testers are alive

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall implement a mechanism to check if the connected testers are still available to allow an efficient management of connections for diagnostics from the DoIP entity point of view. The alive check mechanism shall be according to 13400-2:2012.
<b>Rationale:</b>	This is necessary to allow DoIP
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

#### 5.4.1.11 [SRS\_Eth\_00084]DoIP shall implement routing activation mechanism

<b>Type:</b>	Valid
<b>Description:</b>	DoIP shall implement a mechanism to allow the selective activation of diagnostics on all supported socket connections with the Routing activation mechanisms described in ISO 13400-2:2012
<b>Rationale:</b>	This is necessary to allow DoIP
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	[10]

]( RS\_BRF\_01440)

## 5.5 SWS Ethernet Interface (EthIf)

### 5.5.1.1 [SRS\_Eth\_00031] The Ethernet Interface shall be pre-compile time configurable for interrupt or polling.

[

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Interface shall provide configuration for interrupt and polling mode. In interrupt mode received frames shall be reported from the driver. In polling mode the main function shall check for received frames.
<b>Rationale</b>	Interface and interaction
<b>Use Case</b>	For low latency interrupt mode is crucial. On systems with high system load the polling mode reduces the system load
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.5.1.2 [SRS\_Eth\_00032] The Ethernet Interface shall provide hardware configuration and initialization.

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Interface shall provide hardware independent configuration and initialization interface.
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used Ethernet controller and transceiver shall be transparent and only be reflected by replacing the used driver.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.5.1.3 [SRS\_Eth\_00033] The Ethernet Interface shall provide indication for link state change.

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Interface shall provide indication for link state change of connected transceivers.
<b>Rationale</b>	Interface and interaction
<b>Use Case</b>	Disconnection of the cable results in invalid IP address. Thus a valid IP assignment cycle has to be started.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.5.1.4 [SRS\_Eth\_00072]The Ethernet Interface shall provide VLAN support

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Interface shall support VLAN tagging of Ethernet frames according to IEEE 802.1Q, i.e. add/remove VLAN tag at transmission/reception of Ethernet frames. A VLAN shall appear as a separate Ethlf controller to the upper layer. The VLAN identifier shall be specified via Ethlf configuration; the VLAN priority shall be specified by the upper layer as part of the transmission request and ignored at reception.
<b>Rationale</b>	Separation of logical networks
<b>Use Case</b>	Separation of internal and external vehicle communication
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

## 5.6 SWS Ethernet Driver (Eth)

### 5.6.1.1 [SRS\_Eth\_00035] The Ethernet Driver shall be pre-compile time configurable for interrupt or polling.

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Driver shall provide configuration for interrupt and polling mode. In interrupt mode received frames shall be reported from the driver.
<b>Use Case</b>	For low latency interrupt mode is crucial. On systems with high system load the polling mode reduces the system load
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.6.1.2 [SRS\_Eth\_00036] The Ethernet Driver shall provide hardware configuration and initialization.

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Driver shall provide hardware independent configuration and initialization interface.
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used Ethernet controller shall be transparent and only be reflected by replacing the used driver.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.6.1.3 [SRS\_Eth\_00073]The Ethernet Driver shall support to receive MAC broadcast frames

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet driver shall support the configuration of the Ethernet controller to receive MAC broadcast frames.
<b>Rationale</b>	Reception of frames by all nodes
<b>Use Case</b>	ARP Request
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.6.1.4 [SRS\_Eth\_00074]The Ethernet Driver shall support to receive MAC groupcast frames

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet driver shall support the configuration of the Ethernet controller to receive MAC multicast frames.
<b>Rationale</b>	Reception of frames by multiple nodes
<b>Use Case</b>	Notification messages
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

## 5.7 SWS Ethernet Transceiver Driver (EthTrcv)

**5.7.1.1 [SRS\_Eth\_00039] The Ethernet Transceiver Driver shall provide hardware configuration and initialization.**

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Transceiver Driver shall provide hardware independent configuration and initialization interface.
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used Ethernet transceiver shall be transparent and only be reflected by replacing the used driver.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

|( RS\_BRF\_01776)

**5.7.1.2 [SRS\_Eth\_00040] The Ethernet Transceiver Driver shall provide access to the link state.**

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Transceiver Driver shall provide access to the link state of connected transceivers.
<b>Rationale</b>	Interface and interaction
<b>Use Case</b>	Disconnection of the cable results in invalid IP address. Thus a valid IP assignment cycle has to be started.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

|( RS\_BRF\_01776)

## 5.8 SWS Ethernet State Manager (EthSM)

**5.8.1.1 [SRS\_Eth\_00043] The Ethernet State Manager shall provide network configuration and initialization.**

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet State Manager shall provide network independent configuration and initialization interface.
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used network shall be transparent and only be reflected by replacing the used State Manager.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

|( RS\_BRF\_01776,RS\_BRF\_01664)

## 5.9 SWS UDP Network Management (UdpNm)

**5.9.1.1 [SRS\_Eth\_00037] The UDP Network Management shall provide an interface for transmission of network management information.**

<b>Type:</b>	Valid
<b>Description:</b>	The UDP Network Management shall provide an interface to send and receive network management information over UDP.
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used network shall be transparent and only be reflected by replacing the used Network Management.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776,RS\_BRF\_01680)

### 5.9.1.2 [SRS\_Eth\_00075]The UDP Network Management shall atleast provide the functionality of CAN NM.

<b>Type:</b>	Valid
<b>Description:</b>	The UDP Network Management shall match the functionality of CAN NM. (i.e Including optional services such as Partial Networking)
<b>Rationale</b>	Bus independence
<b>Use Case</b>	Replacement of CAN by Ethernet and IP
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776,RS\_BRF\_01680)

## 5.10 SWS Service Discovery (Sd)

### 5.10.1.1 [SRS\_Eth\_00076]The APIs of the Service Discovery module shall support any protocol

<b>Type:</b>	Valid
<b>Description:</b>	The APIs of the Sd module shall encapsulate the use of any protocol on the wire.
<b>Rationale</b>	The Sd functionality may be achieved with any number of different wire protocols.
<b>Use Case</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

## 5.11 Non-Functional Requirements

### 5.11.1 SWS TCP/IP Protocol Stack

#### 5.11.1.1 [SRS\_Eth\_00077]The TCP/IP stack shall be implemented as independent sub-modules.

[

<b>Type:</b>	Valid
<b>Description:</b>	The TCP/IP stack shall be implemented as independent sub-modules.
<b>Rationale:</b>	The TCP/IP protocol suite is too large to be implemented in a monolithic block.
<b>Use Case:</b>	--
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01784)

[]

## 5.11.2 SWS Socket Adaptor (SoAd)

### 5.11.2.1 [SRS\_Eth\_00078]The SoAd module shall be the sole interface to the TCP/IP stack

[

<b>Type:</b>	Valid
<b>Description:</b>	SoAd module shall be the single interface to the TCP/IP stack for AUTOSAR modules.
<b>Rationale:</b>	Modular design Single implementations of PDU to socket transformation
<b>Use Case:</b>	PDU communication via Ethernet used by multiple AUTOSAR modules.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

[]

## 5.11.3 SWS Ethernet Interface (EthIf)

### 5.11.3.1 [SRS\_Eth\_00029] Ethernet Interface shall be the single interface of all Ethernet modules to the Ethernet hardware drivers.

[

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Interface shall be the single interface for all upper modules (i.e. TCP/IP module and Ethernet State Manager) to the lower layer Ethernet hardware drivers for each Ethernet controller (Ethernet Driver) and Ethernet transceiver (Ethernet Transceiver Driver).
<b>Rationale:</b>	Interface and interaction
<b>Use Case:</b>	Multiple software modules shall transmit and receive data through multiple Ethernet connections in a uniform way.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

### 5.11.3.2 [SRS\_Eth\_00030] The Ethernet Interface shall be independent of the actual hardware.

[

<b>Type:</b>	Valid
<b>Description:</b>	The Ethernet Interface shall provide a hardware independent interface to its upper layer modules (i.e. TCP/IP module and Ethernet State Manager).
<b>Rationale</b>	Portability and reusability
<b>Use Case</b>	Exchanging the used Ethernet controller and transceiver shall be transparent and only be reflected by replacing the used driver.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.11.4 SWS Ethernet Driver (Eth)

##### 5.11.4.1 [SRS\_Eth\_00034] An Ethernet Driver shall offer a hardware independent interface.

<b>Type:</b>	Valid
<b>Description:</b>	An Ethernet Driver shall offer a hardware independent interface for all Ethernet controllers of the same type
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used Ethernet controller shall be transparent and only be reflected by replacing the used driver.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.11.5 SWS Ethernet Transceiver Driver (EthTrcv)

##### 5.11.5.1 [SRS\_Eth\_00038] An Ethernet Transceiver Driver shall offer a hardware independent interface.

<b>Type:</b>	Valid
<b>Description:</b>	An Ethernet Transceiver Driver shall offer a hardware independent interface for all Ethernet transceivers of the same type
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used Ethernet transceiver shall be transparent and only be reflected by replacing the used driver.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776)

#### 5.11.6 SWS Ethernet State Manager (EthSM)

##### 5.11.6.1 [SRS\_Eth\_00041] An Ethernet State Manager shall offer network independent state handling

[

<b>Type:</b>	Valid
<b>Description:</b>	An Ethernet State Manager shall offer network independent state handling. - Uninitialized - No Communication - Full Communication
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used network shall be transparent and only be reflected by replacing the used State Manager.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776,RS\_BRF\_01664)

### 5.11.7 SWS UDP Network Management (UdpNm)

#### 5.11.7.1 [SRS\_Eth\_00042] A UDP Network Management shall offer network independent interface.

<b>Type:</b>	Valid
<b>Description:</b>	A UDP Network Management shall offer network independent interface
<b>Rationale</b>	Hardware abstraction
<b>Use Case</b>	Exchanging the used network shall be transparent and only be reflected by replacing the used Network Management.
<b>Dependencies:</b>	--
<b>Supporting Material:</b>	--

]( RS\_BRF\_01776,RS\_BRF\_01680)



## 6 References

- [1] Requirements on AUTOSAR Features  
AUTOSAR\_RS\_Features.pdf

### 6.1 Deliverables of AUTOSAR

- [2] AUTOSAR Layered Architecture  
AUTOSAR\_EXP\_LayeredSoftwareArchitecture.pdf
- [3] AUTOSAR UDP Network Management  
AUTOSAR\_SWS\_UDPNetworkManagement.pdf
- [4] AUTOSAR Ethernet State Manager  
AUTOSAR\_SWS\_EthernetStateManager.pdf
- [5] AUTOSAR Socket Adaptor  
AUTOSAR\_SWS\_SocketAdaptor.pdf
- [6] AUTOSAR Ethernet Interface  
AUTOSAR\_SWS\_EthernetInterface.pdf
- [7] SoftwareComponentTemplate  
AUTOSAR\_TPS\_SoftwareComponentTemplate.pdf

### 6.2 Related standards and norms

- [8] IEC 7498-1, "The Basic Model", IEC Norm, 1994
- [9] IEEE Std. 1003.1™, 2004 Edition, "POSIX"  
<http://www.opengroup.org/onlinepubs/000095399/>
- [10] ISO 13400-2 Diagnostic communication over Internet Protocol (DoIP)  
June 2012
- [11] XCP, The Universal Measurement and Calibration Protocol Family, ASAM  
e.V., 2003

#### 6.2.1 IETF Requests For Comments (RFCs)

- [12] IETF RFC 791 Internet Protocol - DARPA Internet Program – Protocol  
Specification (September 1981)
- [13] IETF RFC 793 Transmission Control Protocol - DARPA Internet Program  
- Protocol Specification (September 1981)
- [14] IETF RFC 768 User Datagram Protocol (August 1980)
- [15] IETF RFC 1122 Requirements for Internet Hosts - Communication Layers  
(October 1989)
- [16] RFC 896, "Congestion Control in IP/TCP Internetworks", (Nagle algorithm)
- [17] IETF RFC 2131 Dynamic Host Configuration Protocol (March 1997)

- [18] IETF RFC 826      An Ethernet Address Resolution Protocol (November 1982)
- [19] IETF RFC 792      Internet Control Message Protocol DARPA Internet Program - Protocol Specification (September 1981)
- [20] IETF RFC 2132     DHCP Options and BOOTP Vendor Extensions (March 1997)
- [21] IETF RFC 3927     Dynamic Configuration of IPv4 Link-Local Addresses (May 2005)
- [22] IETF RFC 2460     Internet Protocol, Version 6 (IPv6) (December 1998)