

Document Title	SWS_FlexRayTransceiverDriver: Complete Change Documentation 4.3.0 - 4.3.1
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	695

Document Status	Final
Part of AUTOSAR Standard	Classic Platform
Part of Standard Release	4.3.1

Table of Contents

1	SWS_FlexRayTransceiverDriver	4
1.1	Specification Item SWS_FrTrcv_00085	4
1.2	Specification Item SWS_FrTrcv_00275	5
1.3	Specification Item SWS_FrTrcv_00276	9
1.4	Specification Item SWS_FrTrcv_00277	13
1.5	Specification Item SWS_FrTrcv_00278	17
1.6	Specification Item SWS_FrTrcv_00279	21
1.7	Specification Item SWS_FrTrcv_00280	24
1.8	Specification Item SWS_FrTrcv_00281	28
1.9	Specification Item SWS_FrTrcv_00282	32
1.10	Specification Item SWS_FrTrcv_00283	36
1.11	Specification Item SWS_FrTrcv_00284	39
1.12	Specification Item SWS_FrTrcv_00295	43
1.13	Specification Item SWS_FrTrcv_00304	45
1.14	Specification Item SWS_FrTrcv_00305	48
1.15	Specification Item SWS_FrTrcv_00306	51
1.16	Specification Item SWS_FrTrcv_00308	56
1.17	Specification Item SWS_FrTrcv_00312	59
1.18	Specification Item SWS_FrTrcv_00313	63
1.19	Specification Item SWS_FrTrcv_00354	66
1.20	Specification Item SWS_FrTrcv_00384	70
1.21	Specification Item SWS_FrTrcv_00390	72
1.22	Specification Item SWS_FrTrcv_00395	73
1.23	Specification Item SWS_FrTrcv_00396	74
1.24	Specification Item SWS_FrTrcv_00397	78
1.25	Specification Item SWS_FrTrcv_00398	81
1.26	Specification Item SWS_FrTrcv_00424	85
1.27	Specification Item SWS_FrTrcv_00437	89
1.28	Specification Item SWS_FrTrcv_00439	93
1.29	Specification Item SWS_FrTrcv_00459	97
1.30	Specification Item SWS_FrTrcv_00460	100
1.31	Specification Item SWS_FrTrcv_00461	103
1.32	Specification Item SWS_FrTrcv_00462	107
1.33	Specification Item SWS_FrTrcv_00463	110
1.34	Specification Item SWS_FrTrcv_00464	114
1.35	Specification Item SWS_FrTrcv_00465	117
1.36	Specification Item SWS_FrTrcv_00466	120
1.37	Specification Item SWS_FrTrcv_00467	124
1.38	Specification Item SWS_FrTrcv_00472	127
1.39	Specification Item SWS_FrTrcv_00488	128

1.40 Specification Item SWS_FrTrcv_00493 130

1 SWS_FlexRayTransceiverDriver

1.1 Specification Item SWS_FrTrcv_00085

Trace References:

none

Content:

Development Error Types

Type or error	Related error code	Value [hex]
API service called with wrong parameter	FRTRCV_E_FR_INVALID_TRCVIDX FlexRay transceiver index out of range	0x01
API service called with wrong parameter	FRTRCV_E_FR_INVALID_BRANCHIDX FlexRay transceiver branch index out of range	0x02
API Service used without initialization	FRTRCV_E_FR_UNINIT	0x10
API service called in wrong transceiver operation mode	FRTRCV_E_FR_TRCV_NOT_STANDBY FRTRCV_E_FR_TRCV_NOT_NORMAL FRTRCV_E_FR_TRCV_NOT_SLEEP FRTRCV_E_FR_TRCV_NOT_RECEIVEONLY	0x11 0x12 0x13 0x14
API service called passing a NULL pointer as a parameter	FRTRCV_E_PARAM_POINTER	0x15
No/incorrect communication to transceiver	FRTRCV_E_FR_NO_CONTROL_TRCV	0x16
Invalid configuration set selection	FRTRCV_E_INIT_FAILED	0x17

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another.
 Please also check the related requirements (and background information) which is

referring to that error and adapt them if needed.

- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

1.2 Specification Item SWS_FrTrcv_00275

Trace References:

none

Content:

If **default development** error detection for the module FrTrcv is enabled: If the parameter FrTrcv_TrvcIdx is not within the allowed range, the function FrTrcv_SetTransceiverMode shall raise development error FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

— SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to

"Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

-Last change on issue 73570 comment 47-

BW-C-Level:

Application	Specification	Bus
1	1	1

1.3 Specification Item SWS_FrTrcv_00276

Trace References:

none

Content:

If **default error detection for the module FrTrcv is enabled**: If the **the** mode transition fails (SWS_FrTrcv_00452), the function FrTrcv_SetTransceiverMode shall raise the following **development runtime** error:

- FRTRCV_E_FR_TRCV_NOT_STANDBY:

Transition to FRTRCV_TRCVMODE_STANDBY failed

- FRTRCV_E_FR_TRCV_NOT_NORMAL:

Transition to FRTRCV_TRCVMODE_NORMAL failed

- FRTRCV_E_FR_TRCV_NOT_SLEEP:

Transition to FRTRCV_TRCVMODE_SLEEP failed

- FRTRCV_E_FR_TRCV_NOT_RECEIVEONLY:

Transition to FRTRCV_TRCVMODE_RECEIVEONLY failed

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is

referring to that error and adapt them if needed.

- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the

correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.4 Specification Item SWS_FrTrcv_00277

Trace References:

none

Content:

If **default development** error detection for the module FrTrcv is enabled: if the transceiver has not been initialized, the function FrTrcv_SetTransceiverMode shall raise development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
- Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.5 Specification Item SWS_FrTrcv_00278

Trace References:

none

Content:

In case of a fault during transceiver access, the function FrTrcv_SetTransceiverMode shall raise **development runtime** error FRTRCV_E_FR_NO_CONTROL_TRCV **if default error detection for the module FrTrcv is enabled** (see also SWS_FrTrcv_00237).

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

- [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance

Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.6 Specification Item SWS_FrTrcv_00279

Trace References:

none

Content:

If **default development** error detection for the module FrTrcv is enabled: if the parameter FrTrcv_TrcvIdx is out of range, the function FrTrcv_GetTransceiverMode shall raise the development error FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.7 Specification Item SWS_FrTrcv_00280

Trace References:

none

Content:

If **default development** error detection for the module FrTrcv is enabled: if the transceiver has not been initialized, the function FrTrcv_GetTransceiverMode shall raise the development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.8 Specification Item SWS_FrTrcv_00281

Trace References:

SRS_Fr_05151

Content:

In case of a fault during transceiver access, the function FrTrcv_GetTransceiverMode shall raise the **development runtime error FRTRCV_E_FR_NO_CONTROL_TRCV if default error detection for the module FrTrcv is enabled** (see also SWS_FrTrcv_00237).

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:
 Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

***** ECUC XML *****

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.9 Specification Item SWS_FrTrcv_00282

Trace References:

none

Content:

If **default development** error detection of the module FrTrcv is enabled: if the parameter FrTrcv_TrcvIdx is out of range, the function FrTrcv_GetTransceiverWUReason shall raise the development error FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.10 Specification Item SWS_FrTrcv_00283

Trace References:

none

Content:

If **default development** error detection of the module FrTrcv is enabled: if the transceiver has not been initialized, the function FrTrcv_GetTransceiverWUReason shall raise the development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]
- If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case default errors are enabled,..."
- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]
- In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"
- "[SWS_xxx_yyyyy]
- If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
- [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.11 Specification Item SWS_FrTrcv_00284

Trace References:

none

Content:

In case of a fault during transceiver access, the function FrTrcv_GetTransceiverWURReason shall raise **development runtime error FRTRCV_E_FR_NO_CONTROL_TRCV if default error detection for the module FrTrcv is enabled** (see also SWS_FrTrcv_00237).

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.

- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:
 - In chapter "3.3 Related AUTOSAR documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:
 - In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:
 - In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:
 - In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.12 Specification Item SWS_FrTrcv_00295

Trace References:

none

Content:

The FrTrcv module shall check for bus errors and report them to DEM executing Dem_SetEventStatus(FRTRCV_E_FR_BUSERROR_TRCV<TrcvIdx>_<TrcvIdx>, DEM_EVENT_STATUS_PREFAILED).

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

***** BSW UML Model *****

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API
 UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

***** ECUC XML *****

Not affected. No configuration of runtime error reporting required (see SWS BSW
 General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

1.13 Specification Item SWS_FrTrcv_00304

Trace References:

none

Content:

If **default development** error detection is enabled for the module FrTrcv: if the parameter FrTrcv_Trvcldx is out of range, the function FrTrcv_ClearTransceiverWakeup shall raise the development error code FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"
- "[SWS_xxx_yyyyy]"
- In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"
- "[SWS_xxx_yyyyy]"
- If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case default errors are enabled,..."
- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]"
- In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"
- "[SWS_xxx_yyyyy]"
- If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
- [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows

the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.14 Specification Item SWS_FrTrcv_00305

Trace References:

none

Content:

If **default development** error detection is enabled for the module FrTrcv: if the transceiver has not been initialized, the function FrTrcv_ClearTransceiverWakeup shall raise the development error code FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.15 Specification Item SWS_FrTrcv_00306

Trace References:

SRS_Fr_05151

Content:

In case of a fault during transceiver access, the function FrTrcv_ClearTransceiverWakeup shall raise the **development runtime** error FRTRCV_E_FR_NO_CONTROL_TRCV if **default error detection for the module FrTrcv is enabled** (see also SWS_FrTrcv_00237).

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
–Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API
UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW

General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer"

to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
- Last change on issue 73570 comment 47-

BW-C-Level:

Application	Specification	Bus
1	1	1

1.16 Specification Item SWS_FrTrcv_00308

Trace References:

none

Content:

If **default development** error detection of the module FrTrcv is enabled: if any of the configured transceivers is not initialized, the function FrTrcv_MainFunction shall raise development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.17 Specification Item SWS_FrTrcv_00312

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the parameter FrTrcv_TrcvIdx is out of range, the function FrTrcv_CheckWakeupByTransceiver shall raise development error FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.18 Specification Item SWS_FrTrcv_00313

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the FrTrcv module is not initialized, the function FrTrcv_CheckWakeupByTransceiver shall raise development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]
- If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case default errors are enabled,..."
- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]
- In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"
- "[SWS_xxx_yyyyy]
- If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
- [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.19 Specification Item SWS_FrTrcv_00354

Trace References:

none

Content:

In case of faults of the transceiver hardware, the FlexRay Transceiver Driver shall raise a **development runtime** error FRTRCV_E_FR_NO_CONTROL_TRCV **if default error detection for the module FrTrcv is enabled.**

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.

- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.20 Specification Item SWS_FrTrcv_00384

Trace References:

none

Content:

If an error (e.g. the state of the ERRN pin is active low) is detected the module shall execute Dem_SetEventStatus(FRTRCV_E_FR_ERRN_TRCV<TrcvIdx>_<TrcvIdx>, DEM_EVENT_STATUS_PREFAILED).

In the above description, <TrcvIdx> represents the transceiver index.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
–Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API
UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW
General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

1.21 Specification Item SWS_FrTrcv_00390

Trace References:

none

Content:

If the configuration parameter FrTrcvErrorCheckInInit is set true, the function FrTrcv_Init shall check state of ERRN to detect hardware failure. If an error is detected, FrTrcv_Init shall raise a production error FRTRCV_E_FR_ERRN_TRCV<TrcvIdx>_<TrcvIdx>.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

1.22 Specification Item SWS_FrTrcv_00395

Trace References:

none

Content:

If an error is not detected (e.g. the state of the ERRN pin is passive high) the module shall execute Dem_SetEventStatus(FRTRCV_E_FR_ERRN_TRCV<TrcvIdx>_<TrcvIdx>, DEM_EVENT_STATUS_PREPASSED).

In the above descriptions, <TrcvIdx> represents the transceiver index.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRuntimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

1.23 Specification Item SWS_FrTrcv_00396

Trace References:

none

Content:

When a NULL pointer is passed as a parameter value of FrTrcv_GetVersionInfo, the development error FRTRCV_E_PARAM_POINTER shall be reported to DET shall be reported to DET if **default development** error detection is enabled.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.24 Specification Item SWS_FrTrcv_00397

Trace References:

none

Content:

When the caller provides a NULL pointer as a parameter value to the API

FrTrcv_GetTransceiverMode, the return value shall be E_NOT_OK and the development error FRTRCV_E_PARAM_POINTER shall be reported to DET if **default development** error detection is enabled.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET

does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

errors"

- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.25 Specification Item SWS_FrTrcv_00398

Trace References:

none

Content:

When the caller provides a NULL pointer as a parameter value to the API FrTrcv_GetTransceiverWUReason, the development error FRTRCV_E_PARAM_POINTER shall be reported to DET if **default development** error detection is enabled.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx

module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

-Last change on issue 73570 comment 47-

BW-C-Level:

Application	Specification	Bus
1	1	1

1.26 Specification Item SWS_FrTrcv_00424

Trace References:

none

Content:

Det.h – FrTrcv.c shall include Det.h **only if default error detection is turned on.**

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
–Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API
UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init

was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."
- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
- Last change on issue 73570 comment 47-

BW-C-Level:

Application	Specification	Bus
1	1	1

1.27 Specification Item SWS_FrTrcv_00437

Trace References:

none

Content:

In case of a fault during transceiver access, the initialization process shall be restarted from the beginning. It shall be retried until the retry counter exceeds the number specified by FrTrcvRetryCountInInit. If the process doesn't succeed, the function FrTrcv_Init shall raise a **development runtime error FRTRCV_E_FR_NO_CONTROL_TRCV if default error detection for the module FrTrcv is enabled** (see also SWS_FrTrcv_00237).

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 -Last change on issue 59085 comment 26-

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.

- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"
- "[SWS_xxx_yyyyy]
- In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"
- "[SWS_xxx_yyyyy]
- If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case default errors are enabled,..."
- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]
- In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"
- "[SWS_xxx_yyyyy]
- If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents":
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.28 Specification Item SWS_FrTrcv_00439

Trace References:

none

Content:

When the caller provides a NULL pointer as a parameter value to the API FrTrcv_Get TransceiverError the return value shall be E_NOT_OK and the development error FRTRCV_E_PARAM_POINTER shall be reported to DET if default development error detection is enabled.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
- Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.29 Specification Item SWS_FrTrcv_00459

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the FrTrcv module is not initialized, the function FrTrcv_GetTransceiverError shall raise development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"
- "[SWS_xxx_yyyyy]
- In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"
- "[SWS_xxx_yyyyy]
- If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case default errors are enabled,..."
- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]
- In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"
- "[SWS_xxx_yyyyy]
- If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
- [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance

Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.30 Specification Item SWS_FrTrcv_00460

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the parameter FrTrcv_TrcvIdx is out of range, the function FrTrcv_GetTransceiverError shall raise development error FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

-Last change on issue 73570 comment 47-

BW-C-Level:

Application	Specification	Bus
1	1	1

1.31 Specification Item SWS_FrTrcv_00461

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the parameter FrTrcv_BranchIdx is out of range (ECUC_FrTrcv_00357), the function FrTrcv_GetTransceiverError shall raise development error FRTRCV_E_FR_INVALID_BRANCHIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"
- "The DET provides services to store default errors"
- ...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
- [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
Rename "Development Error Tracer" to "Default Error Tracer"
Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.32 Specification Item SWS_FrTrcv_00462

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the FrTrcv module is not initialized, the function FrTrcv_DisableTransceiverBranch shall raise development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_XXX_YYYYY]

In case default error detection is enabled for the XXXX module: The XXXX module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_XXX_YYYYY]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_XXX_YYYYY]

In case development error detection is enabled for the XXXX module: The XXXX module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_XXX_YYYYY]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AU-

TOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AU-

TOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AU-

TOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.33 Specification Item SWS_FrTrcv_00463

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the parameter FrTrcv_TrcvIdx is out of range, the function FrTrcv_DisableTransceiverBranch shall raise development error FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.34 Specification Item SWS_FrTrcv_00464

Trace References:

none

Content:

If **default** **development** error detection of module FrTrcv is enabled: if the parameter FrTrcv_BranchIdx is out of range (ECUC_FrTrcv_00357), the function FrTrcv_DisableTransceiverBranch shall raise development error FRTRCV_E_FR_INVALID_BRANCHIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_XXX_yyyyy]

In case default error detection is enabled for the XXXX module: The XXXX module

shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.35 Specification Item SWS_FrTrcv_00465

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the FrTrcv module is not initialized, the function FrTrcv_EnableTransceiverBranch shall raise development error FRTRCV_E_FR_UNINIT.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately renamed "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the

correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

– SWS_RTE –

- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "7 References":
 Rename "Development Error Tracer" to "Default Error Tracer"
 Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

–Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.36 Specification Item SWS_FrTrcv_00466

Trace References:

none

Content:

If **default development** error detection of module FrTrcv is enabled: if the parameter FrTrcv_TrcvIdx is out of range, the function FrTrcv_EnableTransceiverBranch shall raise development error FRTRCV_E_FR_INVALID_TRCVIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"
- "[SWS_xxx_yyyyy]"
 In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"
- "[SWS_xxx_yyyyy]"
 If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"
- "In case development errors are enabled,..."
- "module raises the development error XXX_E_TRANSITION"
- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —
- Change 4.8 Default errors to 4.8 Development errors
- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"
- Remove [SWS_Rte_07676]
- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."
- Change [SWS_Rte_06631]
 [SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"
- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

-Last change on issue 73570 comment 47-

BW-C-Level:

Application	Specification	Bus
1	1	1

1.37 Specification Item SWS_FrTrcv_00467

Trace References:

none

Content:

If **default** **development** error detection of module FrTrcv is enabled: if the parameter FrTrcv_BranchIdx is out of range (ECUC_FrTrcv_00357), the function FrTrcv_EnableTransceiverBranch shall raise development error FRTRCV_E_FR_INVALID_BRANCHIDX.

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #73570: No "default error" in AUTOSAR

Problem description:

The DET was renamed from development error tracer to default error tracer.

This change was most of the time done automatically and unfortunately re-named "development error" to "default error".

"default error" should always be followed by "tracer", otherwise, "development error" is probably the right term.

This could increase the impact (compared to my selection of impacted document, but formally, the configuration parameters *DevErrorDetect are not using the correct description:

"Switches the Default Error Tracer (Det) detection and notification..."

The parameter switches on/off the development error detection. The DET does not need to be detected and can be present even when the parameter is set to false.

Agreed solution:

Rename "default error" to "development error" in all impacted documents, but not in an automated way (Do not change "default error tracer" to "development error

tracer"!)

Blueprint/Example:

- sub chapter is now called "7.x Default errors"

- "[SWS_xxx_yyyyy]

In case default error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If default error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the default error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case default errors are enabled,..."

- "module raises the Default error XXX_E_TRANSITION"

- "The DET provides services to store default errors"

...

The correct text would be:

- sub chapter is called "7.x Development errors"

- "[SWS_xxx_yyyyy]

In case development error detection is enabled for the xxxx module: The xxxx module shall check API parameters for validity and report detected development errors to the DET. ()"

- "[SWS_xxx_yyyyy]

If development error detection is enabled: the function shall check that the service xxx_Init was previously called. If the check fails, the function shall raise the development error XXX_E_NOT_INITIALIZED otherwise (if DET is disabled) return E_NOT_OK. ()"

- "In case development errors are enabled,..."

- "module raises the development error XXX_E_TRANSITION"

- "The DET provides services to store development errors"

Solution for SWS_RTE:

- SWS_RTE —

- Change 4.8 Default errors to 4.8 Development errors

- Change "Errors which can occur at runtime in the RTE are classified as default errors" to "Errors which can occur at runtime in the RTE are classified as development errors"

- Remove [SWS_Rte_07676]

- Change [SWS_RTE_06611]"If a violation is detected the RTE shall report a default error to the DET." to "If a violation is detected the RTE shall report a development error to the DET."

- Change [SWS_Rte_06631]

[SWS_Rte_06631] d The RTE shall use the OS Application Identifier as the Instance Id to enable the developer to identify in which runtime section of the RTE the error occurs. This Instance ID is even unique across multi cores and so implicitly allows the development error to be traced to a specific core. c(SRS_BSW_00337)

SRS_Libraries:

- In chapter "3 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_SPALGeneral:

- In chapter "6.1.1.3.1 [SRS_SPAL_00157] ...": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "6.1.1.4.2 [SRS_SPAL_12448] ...": Rename "Development Error Tracer" to "Default Error Tracer"

SRS_FlashTest:

- In chapter "6.1 Functional Requirements": Rename "Development Error Tracer" to "Default Error Tracer"

- In chapter "7 References":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_MFXLibrary:

- In chapter "2 Acronyms and abbreviations": Rename "Development Error Tracer" to "Default Error Tracer"

SWS_MemoryAbstractionInterface:

- In chapter "3.1 Input documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_FlexRayNetworkManagement:

- In chapter "3.3 Related AUTOSAR documents":

Rename "Development Error Tracer" to "Default Error Tracer"

Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AU-

TOSAR_SWS_DefaultErrorTracer"

SWS_CANStateManager:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_PDURouter:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"

SWS_EEPROMDriver:

- In chapter "3.1 Input documents": Rename "AUTOSAR_SWS_DevelopmentErrorTracer" to "AUTOSAR_SWS_DefaultErrorTracer"
 –Last change on issue 73570 comment 47–

BW-C-Level:

Application	Specification	Bus
1	1	1

1.38 Specification Item SWS_FrTrcv_00472

Trace References:

none

Content:

If a no bus error is detected, the module shall execute Dem_SetEventStatus(FRTRCV_E_FR_BUSERROR_TRCV<TrcvIdx>_<TrcvIdx>, DEM_EVENT_STATUS_PREPASSED).

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRuntimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

1.39 Specification Item SWS_FrTrcv_00488

Trace References:

none

Content:

Error Name:	FRTRCV_E_FR_BUSERRORRORBUSERROR_TRCV_<TrcvIdx>	
Short Description:	Error Status of Class B serial peripheral interface controlled transceiver where TrcvIdx is the transceiver index.	
Long Description:	Error Status of Class B serial peripheral interface controlled transceiver where TrcvIdx is the transceiver index.	
Detection Criteria:	Fail	Bus error, i.e. if any of bit 1...9 is set for transceivers according to class B of [5], see also SWS_FrTrcv_00458
	Pass	No Bus error, i.e. all of bit 1...9 are cleared for transceivers according to class B of [5], see also SWS_FrTrcv_00458
Secondary Parameters:	Fail: Unexpected HALT of the FlexRay communication controller. Pass: NORMAL_ACTIVE of the FlexRay communication controller (e.g. FRIF_ONLINE). In case of bus short circuit, non-cold start FlexRay nodes will not transmit, so in this case the pass information from the transceiver driver alone is not sufficient to ensure there is no short circuit.	
Time Required:	Consider the pipeline delay and schedule of the serial peripheral interface. Fault detection depends on hardware design and on frame transmission, refer to [REF] for details.	
Monitor Frequency	On unexpected HALT of the FlexRay communication controller On achieving NORMAL_ACTIVE of the FlexRay communication controller	

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors
 –Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment
<https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***
 SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRuntimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1

1.40 Specification Item SWS_FrTrcv_00493

Trace References:

none

Content:

RfCs affecting this spec item between releases 4.3.0 and 4.3.1:

- RfC #59085: Rollout of 'Runtime errors'

Problem description:

Inconsistencies in SWS with semantics of Default errors

–Last change on issue 59085 comment 26–

Agreed solution:

solution in Column "G" of the new attachment <https://www.autosar.org/bugzilla/attachment.cgi?id=4604>

Notes:

- It is not enough just to migrate the error from one classification table to another. Please also check the related requirements (and background information) which is referring to that error and adapt them if needed.
- The review task of the ITs shall be done by the WP to which the specification "belongs".

*** BSW UML Model ***

SWS_CanNm:

Chapter 8.6.1 Optional Interfaces:

Add within SWS_CanNm_00325 the API function Det_ReportRunTimeError

SWS_LinIf:

SWS_LinIf_00359: add Det_ReportRuntimeError

SWS_UdpNm:

Replace UDPNM_E_NO_INIT with UDPNM_E_UNINIT in description of API UdpNm_MainFunction_<Instance Id> (SWS_UdpNm_00234)

*** ECUC XML ***

Not affected. No configuration of runtime error reporting required (see SWS BSW General).

–Last change on issue 59085 comment 88–

BW-C-Level:

Application	Specification	Bus
1	4	1